

Topic 10

return values, Math methods

"Thinking like a computer scientist means more than being able to program a computer. It requires thinking at multiple levels of abstraction."

Jeannette M. Wing, Ph.D.

Director, Data Science Institute, Columbia University
Corporate Vice President, Microsoft Research (past)

Based on slides by Mike Scott.

Used with permission.


https://www.cs.utexas.edu/~scottm/cs312/handouts/slides/topic10_return_values.pdf

Based on slides by Marty Stepp and Stuart Reges
from <http://www.buildingjavaprograms.com/>



Return

- ▶ **return:** To send out a value as the result of a method.
 - The opposite of a parameter:
 - Parameters send information *in* from the caller to the method.
 - Return values send information *out* from a method to its caller.
 - A call to the method can be used as part of an expression.



Returning a value from a method

```
public static type name(parameters) {  
    statements;  
    ...  
    return expression;  
}
```

► Example:

```
// Returns the slope of the line between the given points.  
public static double slope(int x1, int y1, int x2, int y2) {  
    double dy = y2 - y1;  
    double dx = x2 - x1;  
    return dy / dx;  
}
```

slope(5, 11, 1, 3) returns 2.0

Return examples

// Converts degrees Fahrenheit to Celsius.

```
public static double fToC(double degreesF) {  
    double degreesC = 5.0 / 9.0 * (degreesF - 32);  
    return degreesC;  
}
```

// Computes triangle hypotenuse length given its side lengths.

```
public static double hypotenuse(int a, int b) {  
    double c = Math.sqrt(a * a + b * b);  
    return c;  
}
```

- You can shorten the examples by returning an expression:

```
public static double fToC(double degreesF) {  
    return 5.0 / 9.0 * (degreesF - 32);  
}
```

Common error: Not storing

- ▶ a `return` statement DOES NOT send a variable's name back to the calling method.

```
public static void main(String[] args) {  
    slope(0, 0, 6, 3);  
    System.out.println("The slope is " + result);  
    // ERROR: result not defined  
  
}  
  
public static double slope(int x1, int x2, int y1, int y2) {  
    double dy = y2 - y1;  
    double dx = x2 - x1;  
    double result = dy / dx;  
    return result;  
}
```

Fixing the common error

- ▶ Instead, returning sends the variable's *value* back.
 - The returned value must be stored into a variable or used in an expression to be useful to the caller.

```
public static void main(String[] args) {  
    double s = slope(0, 0, 6, 3);  
    System.out.println("The slope is " + s);  
}
```

```
public static double slope(int x1, int x2, int y1, int y2) {  
    double dy = y2 - y1;  
    double dx = x2 - x1;  
    double result = dy / dx;  
    return result;  
}
```

Clicker 3

► What is the output of the following code?

```
int x = 5;
int y = 7;
System.out.print(m(x, y) + " " + x + " " + m(y, x));

public static int m(int x, int y) {
    x += 2;
    System.out.print(x + " ");
    y -= 2;
    return x * y;
}
```

A. 7 9 35 5 27

B. 7 7 35 7 27

C. 7 5 9 27 35

D. 35 7 5 9 27

E. None of A - D are correct

Exercise

- ▶ In physics, the *displacement* of a moving body represents its change in position over time while accelerating.
 - Given initial velocity v_0 in m/s, acceleration a in m/s^2 , and elapsed time t in s, the displacement of the body is:
 - Displacement = $v_0 t + \frac{1}{2} a t^2$
- ▶ Write a method `displacement` that accepts v_0 , a , and t and computes and returns the change in position.
 - example: `displacement(3.0, 4.0, 5.0)`
returns `65.0`

Exercise solution

```
public static double displacement(  
    double v0, double a,  
    double t) {  
  
    double d = v0 * t + 0.5  
                * a * Math.pow(t, 2);  
    return d;  
}
```

Exercises

- ▶ write a method to
 - return the int average of 3 ints
 - return the double average of 3 ints
 - return the average of a given number of rolls of 2 six sided dice
 - calculate and return N factorial (N!).
 - return the number of seconds in a given number of years.
 - return the Nth digit of a given integer.
 - return the distance between two points.



Exercise

- ▶ If you drop two balls, which will hit the ground first?
 - Ball 1: height of 600m, initial velocity = 25 m/sec downward
 - Ball 2: height of 500m, initial velocity = 15 m/sec downward
- ▶ Write a program that determines how long each ball takes to hit the ground (and draws each ball falling).
- ▶ Total time is based on the force of gravity on each ball.
 - Acceleration due to gravity $\cong 9.81 \text{ m/s}^2$, downward
 - Displacement = $v_0 t + \frac{1}{2} a t^2$

Ball solution

```
// Simulates the dropping of two balls from various heights.
import java.awt.*;

public class Balls {
    public static void main(String[] args) {
        DrawingPanel panel = new DrawingPanel(600, 600);
        Graphics g = panel.getGraphics();

        int ball1x = 100, ball1y = 0, v01 = 25;
        int ball2x = 200, ball2y = 100, v02 = 15;

        // draw the balls at each time increment
        for (double t = 0; t <= 10.0; t = t + 0.1) {
            g.setColor(Color.GRAY);
            panel.fillRect(0, 0, 600, 600);
            g.setColor(Color.RED);
            double disp1 = displacement(v01, t, 9.81);
            g.fillOval(ball1x, ball1y + (int) disp1, 10, 10);
            double disp2 = displacement(v02, t, 9.81);
            g.fillOval(ball2x, ball2y + (int) disp2, 10, 10);

            panel.sleep(50);    // pause for 50 ms
        }
    }
    ...
}
```