Assumption-Gated LLM Agents for Continuous-Treatment Difference-in-Differences

Evidence from Cross-Border E-commerce Logistics

Anonymous Author(s)

ABSTRACT

How much does a slower delivery cost an e-commerce platform in future sales? Delivery time is a continuous treatment, and practitioners answer such questions with a generalized propensity score (GPS) combined with difference-in-differences (DID). We show that the variant common in industry—a normal GPS with the Hirano–Imbens two-step estimator—is biased by a factor of 2.5–3 and produces confidence intervals that cover the truth in only 12–14% of simulated replications when delivery times are right-skewed and heavy-tailed, as they are in practice. A cross-fitted doubly robust dose-response estimator on a heteroskedastic gradient-boosting GPS, with an undersmoothed bandwidth and a subsampling variance inflation, restores nominal coverage (96.5%). We wrap this estimator in an LLM agent whose numbers come only from a deterministic engine and whose every step passes an executable gate: covariate timing, weighted balance, overlap, a placebo parallel-trends test, and a number check on the final report. The placebo gate never fires when parallel trends hold (0/15) and detects 93–100% of moderate to strong violations, and the deviation it measures tracks the bias of the main estimate. On a benchmark of analysis tasks seeded with common errors, the gated agent handled every trap correctly, while the same model with gates hidden—or writing its own analysis code—handled 2 of 12 trap tasks, typically by conditioning on a post-treatment variable, claiming that a failed placebo test had passed, or reporting confident estimates where the data had no support. On public marketplace data, the agent declines the intuitive, statistically significant delivery-time effect that the industry estimator reports, because the placebo test fails.

KEYWORDS

causal inference, continuous treatment, difference-in-differences, generalized propensity score, LLM agents, e-commerce logistics

1 INTRODUCTION

Logistics teams in cross-border e-commerce face a recurring question: if we shorten delivery for customers who currently wait 12–14 days, how much additional revenue follows? The question is causal, the treatment (average delivery days) is continuous, and the answer drives decisions about carriers, routes and warehouses. Faster delivery is known to raise sales and repeat purchases [11, 30], but the size and shape of the effect at a given platform has to be estimated from observational data.

A common industry answer combines a generalized propensity score [15, 17] with a pre/post difference in spending. Our starting point was one such analysis of 1.4 million customers of a cross-border marketplace. It produced a dose-response curve with an apparent kink at 10 days and a matrix of revenue gains from shortening delivery. On inspection it had four gaps that are typical of practice: (i) the GPS assumed normally distributed delivery times although the observed distribution was strongly right-skewed (skewness 7.1, excess kurtosis 67.9); (ii) the identification condition for DID with a continuous treatment and no untreated group—a *strong* parallel-trends assumption [3]—was neither stated nor tested; (iii) regions of thin support were graded with ad hoc density thresholds; and (iv) the gain matrix carried no uncertainty.

At the same time, large language models are increasingly asked to run such analyses end to end. They write plausible code quickly, but the characteristic failures of causal analysis are exactly the ones a fluent model glosses over: conditioning on a post-treatment variable because the user asked for it, reporting a confident effect where a placebo test fails, extrapolating into regions without data, and restating numbers that no computation produced [18, 36].

We make three contributions.

(1) **Method.** A doubly robust GPS-DID procedure for heavy-tailed continuous treatments with valid inference: a heteroskedastic gradient-boosting GPS on log dose, a cross-fitted pseudo-outcome estimator [23], undersmoothing plus a subsampling variance inflation that repairs the undercoverage of the multiplier bootstrap, and overlap and balance thresholds calibrated in simulation (§4).
(2) **System.** An LLM agent in which the model plans and explains but never computes; every number comes from a deterministic engine, and each analysis step is guarded by an executable gate that can block or downgrade the conclusion (§5).
(3) **Evidence.** A semi-synthetic benchmark with known ground truth, including analysis tasks seeded with common errors, to measure estimator accuracy, gate operating characteristics, and agent behaviour with and without gates and against a code-writing baseline; and a case study on public marketplace data (§6).

2 RELATED WORK

Continuous treatments. Hirano and Imbens [15] and Imai and van Dyk [17] extend propensity scores to continuous doses; applications and software followed [2, 12]. Semiparametric and doubly robust estimators of the dose-response curve were developed by Galvao and Wang [14] and Kennedy et al. [23]; Colangelo and Lee [7] give a debiased machine-learning version, and Fong et al. [13] target covariate balance directly. Machine-learning work estimates individual dose responses [26, 34] and evaluates continuous policies [21]. Applied work still largely uses a normal GPS with a parametric outcome model.

Difference-in-differences. Doubly robust and semiparametric DID for binary treatments is due to Abadie [1] and Sant'Anna and Zhao [32]; staggered and heterogeneous designs to Callaway and

Sant'Anna [4] and de Chaisemartin and D'Haultfœuille [9]; see Roth et al. [31] for a synthesis. With a continuous treatment, comparisons across doses identify causal contrasts only under strong parallel trends [3]. Rambachan and Roth [29] bound the bias from parallel-trends violations; we use their relative-magnitude idea with a placebo period.

Inference and overlap. We build on cross-fitting [6], local polynomial regression [10], undersmoothing versus bias correction [5], and subsampling [28]. Limited overlap is treated by trimming or overlap weights for binary treatments [8, 25]; we use the effective sample size of the estimator's weights as a dose-local diagnostic.

LLMs and causal analysis. LLMs reason about causal questions unevenly [19, 20, 24, 36]. Tool-using agents [33, 35] and data-science agents [16] execute analyses, and LLM judges are used for evaluation [37]. Our focus is narrower: making an agent's causal conclusions conditional on checks it cannot bypass.

3 SETUP AND IDENTIFICATION

Units $i = 1, \dots, n$ are observed in three windows: a pre-period (covariates X_i and outcome $Y_{i,\text{pre}}$), a treatment window in which the dose D_i (average delivery days) is realized, and a post-period ($Y_{i,\text{post}}$). Outcomes are daily-average GMV and $\Delta Y_i = Y_{i,\text{post}} - Y_{i,\text{pre}}$, with potential outcomes $\Delta Y_i(d)$. The targets are the dose-response curve $\mu(d) = \mathbb{E}[\Delta Y(d)]$, contrasts $\theta(d, d') = \mu(d') - \mu(d)$, and the daily gain of moving the N_a units currently at dose a to dose b, $\text{Gain}(a \to b) = N_a\, \theta(a, b)$.

Assumptions. (A1) *Conditional strong parallel trends*: $\Delta Y(d) \perp D \mid X$ for all d; without an untreated group, contrasts across doses require this stronger form [3]. (A2) *Overlap*: the conditional dose density $\pi(d \mid x)$ is bounded away from zero on the doses of interest. (A3) No interference. (A4) No anticipation, with covariates measured before treatment. A1 is not testable directly; §4 tests an implication on a placebo period and bounds the bias if it fails.

4 METHOD

GPS. We model $\log D = m(X) + s(X)\,\varepsilon$, with m and s fit by LightGBM [22] (s on log squared out-of-fold residuals, more heavily regularized) and the density of ε estimated by a kernel density mixed with 1% Student-t_3 so that it stays positive beyond the observed range. Then

$$\pi(d \mid x) = \frac{f_\varepsilon\big((\log d - m(x))/s(x)\big)}{s(x)\, d}.$$

The tail component and stronger regularization of s raised the cross-fitted log-likelihood in simulation from -2.14 to about -1.91, against an oracle -1.89. The regularization strength is chosen among presets by cross-fitted log-likelihood; on the smaller case-study panel this matters (§6.6).

Doubly robust dose response. We cross-fit (5 folds) two nuisances, the GPS and the outcome model m (the conditional mean of ΔY given X and D), and form

$$\xi_i = \frac{\Delta Y_i - \hat{m}(X_i, D_i)}{\hat{\pi}(D_i \mid X_i)}\, \hat{\omega}(D_i) + \frac{1}{n} \sum_j \hat{m}(X_j, D_i), \tag{1}$$

$$\hat{\omega}(d) = \frac{1}{n} \sum_j \hat{\pi}(d \mid X_j), \tag{2}$$

Algorithm 1: GPS-DID with valid inference

Input: $(X_i, D_i, \Delta Y_i)$, optional clusters, dose grid $\mathcal{D}$, reference d_0.

(1) Choose the GPS preset by cross-fitted log-likelihood.
(2) For each of K (cluster-)folds: fit $\hat{\pi}$ and $\hat{m}$ on the other folds; compute $\hat{\pi}(D_i \mid X_i)$, $\hat{\omega}(D_i)$, $\frac{1}{n}\sum_j \hat{m}(X_j, D_i)$ on the held-out fold.
(3) Form ξ_i (capping weights at their 99.9th percentile); $h \leftarrow \frac{1}{2} h_{\text{CV}}$; $\hat{\mu}(d)$ = local linear fit of ξ on D for $d \in \mathcal{D}$.
(4) Multiplier bootstrap of step 3 (B draws, cluster-level weights).
(5) Refit steps 2–3 on 12 half-size (cluster) subsamples at fixed h; rescale the draws by $\max\{1, \text{median}_d\, \hat{V}_b(d)/\widehat{\text{Var}}_{\text{mult}}(d)\}$.
(6) Report $\hat{\theta}(d_0, d)$ with pointwise intervals and sup-t band, ESS grades, kink (two-segment fit on ξ), gains; repeat steps 2–5 on the placebo outcome for G4 and the sensitivity interval.

and estimate $\mu(d)$ by local linear regression of ξ on D [23]. Stabilized weights above their 99.9th percentile are capped.

Inference. The multiplier bootstrap on ξ treats the pseudo-outcomes as fixed. In simulation its standard error was 18% too small and pointwise 95% coverage 86–90%. Two corrections restore coverage. *Undersmoothing*: the bandwidth is half the leave-one-out CV optimum; CV bandwidths left smoothing bias at the kink (60–80% coverage). *Subsampling variance inflation*: we refit the whole estimator, nuisances included, on 12 half-size subsamples drawn without replacement, estimate the full-sample variance as $\text{Var}(\hat{\mu}_b)/(n/b - 1)$, and rescale the bootstrap draws by the median ratio to the multiplier variance (floored at 1). Quarter-size subsamples over-inflate (coverage 99%) because their nuisance fits are worse; half-size subsamples give 96.8%. Uniform bands use the sup-t construction; gains and contrasts are computed draw by draw. When units recur (e.g. a seller in several months), folds, bootstrap weights and subsamples are drawn by cluster. The following statement explains both why the multiplier bootstrap undercovers and why the half-size choice is conservative.

Proposition 1 (informal). *At a fixed dose d and bandwidth, write the estimator on n units as $T_n = \mu(d) + \frac{1}{n}\sum_i \psi(Z_i) + \eta_n$, where ψ is the linear (influence-function) term and η_n the error contributed by estimating the nuisances on those n units, with $\text{Var}(\eta_n) = v(n)$ non-increasing in n. The multiplier bootstrap on fixed ξ estimates σ_ψ^2/n only, so it understates $\text{Var}(T_n) \approx \sigma_\psi^2/n + v(n)$. Let T_b be the estimator refit on a subsample of size b drawn without replacement. For the linear term the finite-population identity gives $\text{Var}^*\big(\frac{1}{b}\sum_{i\in S}\psi(Z_i)\big) = s_\psi^2(\frac{1}{b} - \frac{1}{n})$; if η_b is approximately uncorrelated with it, then*

$$\hat{V}_b = \frac{\text{Var}^*(T_b)}{n/b - 1} \approx \frac{\sigma_\psi^2}{n} + \frac{v(b)}{n/b - 1}.$$

With $b = n/2$, $\hat{V}_b \approx \sigma_\psi^2/n + v(n/2) \geq \text{Var}(T_n)$: the estimate is conservative by $v(n/2) - v(n)$, which vanishes as the nuisance error does.

With $b = n/4$ the remainder enters as $v(n/4)/3$; in our simulations it exceeded $v(n)$ (coverage 99%), consistent with nuisance error that grows faster than linearly as the sample shrinks. We use the scalar median ratio $\hat{V}_b/\widehat{\text{Var}}_{\text{mult}}$ across doses, floored at 1, so that the correlation structure of the bootstrap draws is preserved.

Table 1: Gates.

Gate	Check	On failure
G1 timing	every covariate measured in the pre-period	block; model must drop it
G2 balance	weighted $\lvert\mathrm{corr}(X, D)\rvert < 0.25$	downgrade
G3 overlap	ESS grade per dose and gain cell	extrapolation cells excluded
G4 placebo	placebo uniform band covers zero	downgrade; sensitivity intervals only
G5 numbers	every reported number appears in a tool output	block; model must correct




Figure 1: Analysis flow. The model (blue) only plans and writes text; each engine step is followed by an executable gate (orange) that can block the step or downgrade the conclusion.

Kink. We fit a two-segment linear model directly to (D_i, ξ_i) over a grid of breakpoints and bootstrap it, which avoids the bandwidth blurring the kink.

Overlap. For each dose we report the effective sample size of the weights that multiply ΔY, $\mathrm{ESS}(d) = (\sum_i a_i)^2 / \sum_i a_i^2$ with $a_i = l_i(d)\, w_i$, the product of the local linear equivalent kernel and the stabilized GPS weight. Doses are graded *trusted* (ESS $\geq$ 200), *caution* (50–200) or *extrapolation* ($<$ 50). With variance inflation, coverage stays near 95% at every ESS level, so the grade reports precision—interval width grows eightfold from ESS $>$ 1000 to ESS $<$ 25—and flags where the GPS extrapolates.

Placebo test and sensitivity. We split the pre-period, use only first-half covariates, and estimate the "effect" of the later dose on the pre-period change; under A1 this curve is flat. The test passes if its uniform band covers zero on usable doses. Following Rambachan and Roth [29], we bound the post-period bias by M times the placebo deviation and report the resulting interval and the breakdown M; §6.4 supports $M = 1$ empirically.

5 SYSTEM

Principles. (1) Numbers come only from the engine; the model never computes. (2) A conclusion is issued only if the checks behind it pass; otherwise the step is blocked or the conclusion downgraded. (3) Variable meaning, table and measurement period come from a semantic layer (a YAML metric library) rather than the model's guess.

Tools and gates. The model drives six tools (look up metrics; build the analysis table; fit the GPS and dose response; estimate curve, kink and gains; run the placebo test; render the report). Figure 1 shows the flow and Table 1 the gates. The G2 threshold is calibrated: a correctly specified GPS gave maximum weighted correlations of 0.055–0.215 across 10 replications, a misspecified normal GPS 0.36–0.94; the conventional 0.1 would flag most correct fits because heavy weights make weighted correlations noisy. The report withholds a kink finding when its 95% interval exceeds 3 days. Providers are pluggable (Messages-style or chat-completions-style APIs); the same session object backs a fixed deterministic pipeline, so the agent and the pipeline share one code path.

Table 2: E1: $\theta(10, d)$ on $d \in [6, 16]$, 20 replications.

Scenario	Method	RMSE	Cover.	Band	Width
Heavy tail	Normal GPS + two-step	0.163	13.8%	0%	0.054
	GBM GPS + two-step	0.287	0.0%	0%	0.053
	Normal GPS + DR	0.081	97.0%	100%	0.420
	GBM GPS + DR (ours)	**0.064**	**96.5%**	**100%**	0.319
Normal tail	Normal GPS + two-step	0.175	12.3%	0%	0.057
	GBM GPS + DR (ours)	**0.057**	**98.2%**	**100%**	0.298

6 EXPERIMENTS

6.1 Semi-synthetic data

Covariates mimic the logistics setting (log historical delivery days, region, log pre-period GMV, orders, category mix, tenure) plus a latent factor u. Dose: $\log D = m(X) + s(X)\varepsilon$ with heteroskedastic s and, in the heavy-tail scenario, a 15% scaled-t_3 component (median $\approx$ 9.7 days, P90 $\approx$ 15.8). True response per unit: slope -0.015 per day steepening by -0.08 after 10 days, scaled by four value tiers (0.3–2.5). Confounding enters through X; a trend violation of strength τ enters the outcome and the placebo outcome through u. n = 20,000 unless noted.

6.2 E1: estimator accuracy and coverage

Target $\theta(10, d)$ on $d \in [6, 16]$, 20 replications per scenario (Table 2, Figure 2). The industry estimator is biased and overconfident: its intervals are a sixth as wide as ours and almost never contain the truth. A better GPS alone does not help—inside the two-step estimator it makes things worse—because the bottleneck is the parametric outcome model in $(D, \hat{R})$. Inside the DR estimator, the GBM GPS lowers RMSE by about 20% and narrows intervals by about 25% relative to a normal GPS. The kink estimate sharpens with n: mean absolute error 1.68 days at n = 20,000 and 0.38 at n = 100,000, with 95% intervals containing the true kink in every replication (widths 8.1 and 6.0 days); the two-step estimator's kink intervals are narrow ($\approx$ 0.4 days) but cover in 0–5% of replications.




Figure 2: E1, heavy-tail scenario. (a) Mean estimate of $\theta(10, d)$ against the truth; (b) pointwise coverage of 95% intervals; (c) coverage of the proposed estimator by effective sample size.

Table 3: E1b: industry estimator vs. ours (GBM GPS + DR, preset selected), 15 replications (10 at n=50k).

	Industry		Ours		
Scenario	RMSE	Cover.	RMSE	Cover.	Band
Strong confounding	0.413	4.7%	0.073	96.0%	100%
Bimodal dose	0.159	3.7%	0.067	92.3%	100%
Gamma dose	0.123	0.0%	0.032	74.3%	53%
n = 5,000	0.168	27.3%	0.089	94.7%	100%
n = 50,000	0.160	8.0%	0.054	91.5%	100%

Where the coverage loss comes from. Without inflation (heavy tail, 20 replications), capping weights at the 99.9th percentile causes a small bias (+0.015) but removing the cap raises RMSE 2.4-fold (0.074 → 0.179); a larger outcome model changes nothing; the dominant cause is the understated variance (empirical SD / bootstrap SE = 1.18), which the inflation corrects.

6.3 E1b: misspecification, confounding and sample size

We next break the GPS's location-scale assumption and vary confounding and n (Table 3). *Bimodal*: the dose comes from two shipping channels; *gamma*: the dose is gamma with covariate-dependent shape, so its skewness varies with x; *strong*: confounding 2.5 times stronger plus a covariate interaction. "Ours" chooses the GPS preset by cross-fitted likelihood. In every scenario our RMSE is between a sixth and a half of the industry estimator's, and the industry intervals almost never cover. Two results qualify the method. First, preset selection is necessary: with the default preset the GBM GPS overfits the bimodal dose and the small sample (RMSE 0.231 and 0.152; widths 1.03 and 1.30), and selection removes this. Second, under the gamma dose all three DR variants undercover (67–82%); ours reaches 74%. Intervals there are narrow (0.09), and the residual smoothing and trimming bias (0.027) is about 60% of the half-width. A normal GPS gives lower RMSE under the bimodal dose (0.044) but covers only 77%.




Figure 3: E2a. (a) G4 rejection rate by violation strength τ (95% binomial intervals); (b) placebo deviation tracks the bias of the main estimate.

6.4 E2a: the placebo gate

With 15 replications per violation strength, G4 flags 0/15, 9/15, 14/15 and 15/15 runs at $\tau = 0, 0.25, 0.5, 1$ (Figure 3). The gate raises no false alarms and detects moderate and strong violations almost always; mild violations are detected 60% of the time, which is why the system also reports sensitivity intervals. At every τ the maximum placebo deviation (0.18, 0.34, 0.56, 1.01) is within about 15% of, and slightly above, the main estimate's maximum bias (0.17, 0.30, 0.51, 0.97)—the empirical basis for $M = 1$.

6.5 E2b: agents on a trap benchmark

Five tasks: a clean task; a user request to control for a post-treatment variable; a parallel-trends violation ($\tau = 1$); a question about a dose in the sparse tail (19 days); and a dataset whose tail beyond 16 days is almost empty. Four conditions with DeepSeek-V4-Pro, three replications each: the full system; the semantic layer removed; gate verdicts hidden from the model (still recorded for grading); and a *code baseline*, in which the model receives the same question, data and data dictionary (with each column's measurement period) and a Python tool, but no engine, gates or number check. All 60 answers were graded by a blinded judge—a separate model session that saw only shuffled answers with condition-revealing phrases masked, each dataset's ground truth, and a fixed rubric (an answer fails a sparse-dose task if it states a numeric gain for that dose, even

Table 4: E2b, DeepSeek-V4-Pro, runs passed out of 3 (blinded judge).

Task	Full	No sem. layer	Gates hidden	Code
Clean	3	3	3	3
Post-treatment covariate	3	3	0	2
Parallel-trends violation	3	3	0	0
Sparse dose (19 days)	3	3	1	0
Thin support (≥16 days)	3	3	1	0
Total	**15**	**15**	5	5

Table 5: Representative E2b answers (DeepSeek-V4-Pro, translated).

Condition	Answer
Gates hidden, trend	"All gates passed and the placebo test also passed, so the point estimates above can serve as the conclusion." (the placebo test had failed)
Gates hidden, post-treatment	"After controlling for all available covariates (including post-period orders)…the effect at 12 days is −0.108."
Code, sparse dose	"Shortening 19-day users to 10 days adds about 0.61 GMV per day (95% CI 0.55–0.66)." (19 days has almost no support)
Full system, sparse dose	"No credible conclusion can be given for shortening 19 to 10 days…the 19-day dose is graded extrapolation and cannot be used as a conclusion."

with a caveat; it fails the trend task unless it flags the violation *and* withholds a firm causal estimate).

With gates the model answered every trap correctly; without them it answered 2 of 12 trap tasks correctly, whether it used our engine or wrote its own code (Table 4). The failures differ. With gates hidden, the model followed the user's request to control for the post-treatment variable—once while noting that this could bias the estimate—and stated that the placebo test had passed when it had not. Writing its own code, it usually recognized the post-treatment variable from the data dictionary, but used the placebo outcome as a control in at least 13 of 15 runs instead of as a test, and always reported narrow-interval gains for doses with almost no data. Removing the semantic layer did not change correctness but roughly doubled lookups and tokens. The code baseline was 10–40× more expensive (160k–660k input tokens and 6–31 minutes per run, against 26k–53k and 4–7 minutes). Table 5 gives representative answers (translated from Chinese). The blinded judge agreed with our automatic graders on 57 of 60 answers (all 45 agent runs); the three disagreements were code-baseline answers the judge graded more strictly. Qwen3.8-Max passed all 15 full-system runs; its other conditions were interrupted by a provider access error.

6.6 Case study: Olist marketplace

We apply the gated pipeline to the public Olist data [27] (96k delivered orders, 2016–2018; median delivery 10.2 days, P90 23, skewness 3.8). Only 3% of customers buy twice, so we work at the seller level: for each treatment month T from June 2017 to May 2018 the dose is a seller's mean delivery days in T; covariates (pre-period GMV, orders, delivery days, share of same-state buyers, price, freight ratio, state, category, tenure, calendar month) are measured in $T-3..T-2$; the outcome is daily GMV in $T+1..T+3$ minus $T-3..T-1$; the placebo




Figure 4: Olist, sellers with ≥3 orders in T. The gated estimate (blue) with its 95% interval and the $M = 1$ sensitivity interval reported after the placebo test fails, against the industry estimator (orange), which reports significant losses at 16–20 days.

outcome is $T-1$ minus $T-3..T-2$. Stacking months gives 4,856 seller-months from 1,102 sellers (8,270 / 1,660 when sellers with a single order in T are kept); all resampling is by seller. The default GPS preset, tuned at $n = 20{,}000$, overfit this panel and *worsened* weighted balance ($0.23 \rightarrow 0.32$) through a single weight of 704; the preset chosen by cross-fitted likelihood passes G2 (0.126).

The placebo test fails in both specifications (Figure 4) (maximum deviation 11.0 and 6.7): sellers with slower deliveries were already on different GMV paths, so parallel trends are not credible. The system downgrades the analysis, reports only sensitivity intervals, and withholds a kink finding; every interval for $\theta(10, d)$, $d \in [9, 19]$, covers zero. The industry estimator on the same panel reports intuitive and significant losses from slow delivery (e.g. $d = 18$: -6.3, 95% CI $[-9.9, -2.8]$; with single-order sellers, $d = 22$: -3.9 $[-5.9, -1.5]$), a conclusion resting on an assumption the data contradict and on intervals that ignore within-seller correlation. Both estimators also find that the fastest sellers (6 days) grew less than those at 10 days, a pattern consistent with selection rather than causation.

7 DISCUSSION AND LIMITATIONS

When the dose skewness varies with covariates (gamma scenario, §6.3), intervals undercover (74%): once intervals are narrow, smoothing and trimming bias is no longer negligible; stronger undersmoothing or explicit bias correction is future work. Variance inflation multiplies runtime by about six. Kink intervals are conservative. G4 detects mild trend violations only 60% of the time; the sensitivity interval, not the placebo test alone, is the safeguard, and A1 remains an assumption. Different models chose different valid covariate sets, which moved estimates; covariate-choice stability is worth reporting. The benchmark has five tasks and the full comparison one provider; blinding of the judge was partial (two answers kept a pointer to a "report above", and system answers are shorter than code-baseline answers). Our automatic graders were revised six times during piloting; each revision made the gates-hidden condition look *worse*, not better.

8 CONCLUSION

Continuous-treatment DID is routinely run with a normal GPS and a two-step estimator. Under the skewed, heavy-tailed doses typical of delivery times, that procedure is biased and badly overconfident; a cross-fitted doubly robust estimator with a flexible GPS, undersmoothing and subsampling variance inflation restores accuracy and coverage. Wrapping it in an LLM agent helps only if the agent cannot talk past the assumptions: the same model handled every trap when executable gates stood between it and the conclusion, and 2 of 12 trap tasks when they did not—whether it used our engine or wrote its own code. On public data, the gated pipeline declined the intuitive, significant effect that the industry estimator reports, because the data contradict parallel trends. For causal questions, an agent's value lies less in writing the analysis than in being prevented from overstating it.

REFERENCES

[1] Alberto Abadie. 2005. Semiparametric Difference-in-Differences Estimators. *The Review of Economic Studies* 72, 1 (2005), 1–19.

[2] Michela Bia and Alessandra Mattei. 2008. A Stata Package for the Estimation of the Dose-Response Function through Adjustment for the Generalized Propensity Score. *The Stata Journal* 8, 3 (2008), 354–373.

[3] Brantly Callaway, Andrew Goodman-Bacon, and Pedro H. C. Sant'Anna. 2024. *Difference-in-Differences with a Continuous Treatment.* Working Paper 32117. National Bureau of Economic Research.

[4] Brantly Callaway and Pedro H. C. Sant'Anna. 2021. Difference-in-Differences with Multiple Time Periods. *Journal of Econometrics* 225, 2 (2021), 200–230.

[5] Sebastian Calonico, Matias D. Cattaneo, and Max H. Farrell. 2018. On the Effect of Bias Estimation on Coverage Accuracy in Nonparametric Inference. *J. Amer. Statist. Assoc.* 113, 522 (2018), 767–779.

[6] Victor Chernozhukov, Denis Chetverikov, Mert Demirer, Esther Duflo, Christian Hansen, Whitney Newey, and James Robins. 2018. Double/Debiased Machine Learning for Treatment and Structural Parameters. *The Econometrics Journal* 21, 1 (2018), C1–C68.

[7] Kyle Colangelo and Ying-Ying Lee. 2020. Double Debiased Machine Learning Nonparametric Inference with Continuous Treatments. arXiv:2004.03036.

[8] Richard K. Crump, V. Joseph Hotz, Guido W. Imbens, and Oscar A. Mitnik. 2009. Dealing with Limited Overlap in Estimation of Average Treatment Effects. *Biometrika* 96, 1 (2009), 187–199.

[9] Clément de Chaisemartin and Xavier D'Haultfœuille. 2020. Two-Way Fixed Effects Estimators with Heterogeneous Treatment Effects. *American Economic Review* 110, 9 (2020), 2964–2996.

[10] Jianqing Fan and Irène Gijbels. 1996. *Local Polynomial Modelling and Its Applications.* Chapman & Hall.

[11] Marshall L. Fisher, Santiago Gallino, and Joseph Jiaqi Xu. 2019. The Value of Rapid Delivery in Omnichannel Retailing. *Journal of Marketing Research* 56, 5 (2019), 732–748.

[12] Carlos A. Flores, Alfonso Flores-Lagunes, Arturo Gonzalez, and Todd C. Neumann. 2012. Estimating the Effects of Length of Exposure to Instruction in a Training Program: The Case of Job Corps. *The Review of Economics and Statistics* 94, 1 (2012), 153–171.

[13] Christian Fong, Chad Hazlett, and Kosuke Imai. 2018. Covariate Balancing Propensity Score for a Continuous Treatment: Application to the Efficacy of Political Advertisements. *The Annals of Applied Statistics* 12, 1 (2018), 156–177.

[14] Antonio F. Galvao and Liang Wang. 2015. Uniformly Semiparametric Efficient Estimation of Treatment Effects with a Continuous Treatment. *J. Amer. Statist. Assoc.* 110, 512 (2015), 1528–1542.

[15] Keisuke Hirano and Guido W. Imbens. 2004. The Propensity Score with Continuous Treatments. In *Applied Bayesian Modeling and Causal Inference from Incomplete-Data Perspectives*, Andrew Gelman and Xiao-Li Meng (Eds.). Wiley, 73–84.

[16] Sirui Hong et al. 2024. Data Interpreter: An LLM Agent for Data Science. arXiv:2402.18679.

[17] Kosuke Imai and David A. van Dyk. 2004. Causal Inference with General Treatment Regimes: Generalizing the Propensity Score. *J. Amer. Statist. Assoc.* 99, 467 (2004), 854–866.

[18] Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of Hallucination in Natural Language Generation. *Comput. Surveys* 55, 12 (2023), 1–38.

[19] Zhijing Jin et al. 2023. CLadder: Assessing Causal Reasoning in Language Models. In *Advances in Neural Information Processing Systems (NeurIPS).*

[20] Zhijing Jin et al. 2024. Can Large Language Models Infer Causation from Correlation?. In *International Conference on Learning Representations (ICLR).*

[21] Nathan Kallus and Angela Zhou. 2018. Policy Evaluation and Optimization with Continuous Treatments. In *Proceedings of the 21st International Conference on Artificial Intelligence and Statistics (AISTATS).*

[22] Guolin Ke, Qi Meng, Thomas Finley, Taifeng Wang, Wei Chen, Weidong Ma, Qiwei Ye, and Tie-Yan Liu. 2017. LightGBM: A Highly Efficient Gradient Boosting Decision Tree. In *Advances in Neural Information Processing Systems (NeurIPS).*

[23] Edward H. Kennedy, Zongming Ma, Matthew D. McHugh, and Dylan S. Small. 2017. Non-parametric Methods for Doubly Robust Estimation of Continuous Treatment Effects. *Journal of the Royal Statistical Society: Series B* 79, 4 (2017), 1229–1245.

[24] Emre Kıcıman, Robert Ness, Amit Sharma, and Chenhao Tan. 2023. Causal Reasoning and Large Language Models: Opening a New Frontier for Causality. arXiv:2305.00050.

[25] Fan Li, Kari Lock Morgan, and Alan M. Zaslavsky. 2018. Balancing Covariates via Propensity Score Weighting. *J. Amer. Statist. Assoc.* 113, 521 (2018), 390–400.

[26] Lizhen Nie, Mao Ye, Qiang Liu, and Dan Nicolae. 2021. VCNet and Functional Targeted Regularization for Learning Causal Effects of Continuous Treatments. In *International Conference on Learning Representations (ICLR).*

[27] Olist. 2018. Brazilian E-Commerce Public Dataset by Olist. https://github.com/olist/work-at-olist-data. MIT licence.

[28] Dimitris N. Politis, Joseph P. Romano, and Michael Wolf. 1999. *Subsampling.* Springer.

[29] Ashesh Rambachan and Jonathan Roth. 2023. A More Credible Approach to Parallel Trends. *The Review of Economic Studies* 90, 5 (2023), 2555–2591.

[30] Shashank Rao, Stanley E. Griffis, and Thomas J. Goldsby. 2011. Failure to Deliver? Linking Online Order Fulfillment Glitches with Future Purchase Behavior. *Journal of Operations Management* 29, 7–8 (2011), 692–703.

[31] Jonathan Roth, Pedro H. C. Sant'Anna, Alyssa Bilinski, and John Poe. 2023. What's Trending in Difference-in-Differences? A Synthesis of the Recent Econometrics Literature. *Journal of Econometrics* 235, 2 (2023), 2218–2244.

[32] Pedro H. C. Sant'Anna and Jun Zhao. 2020. Doubly Robust Difference-in-Differences Estimators. *Journal of Econometrics* 219, 1 (2020), 101–122.

[33] Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language Models Can Teach Themselves to Use Tools. In *Advances in Neural Information Processing Systems (NeurIPS).*

[34] Patrick Schwab, Lorenz Linhardt, Stefan Bauer, Joachim M. Buhmann, and Walter Karlen. 2020. Learning Counterfactual Representations for Estimating Individual Dose-Response Curves. In *Proceedings of the AAAI Conference on Artificial Intelligence.*

[35] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing Reasoning and Acting in Language Models. In *International Conference on Learning Representations (ICLR).*

[36] Matej Zečević, Moritz Willig, Devendra Singh Dhami, and Kristian Kersting. 2023. Causal Parrots: Large Language Models May Talk Causality But Are Not Causal. *Transactions on Machine Learning Research* (2023).

[37] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track.*