Supplementary material for: When should a neural text-entry decoder commit? Risk-controlled commits from a stream-level trust layer

[TODO: authors, affiliations, e-mail]

References to Sections 1–9, Tables 1–5, Figures 1–3, Algorithm 1 and Appendix A point to the main paper. All numbers come from committed result files; the round-4 analyses are in `experiments/2026-11-12-paper1-r4-analyses/` of the repository.

Contents

S1 Notation 2

S2 Fitting and calibration 2

S3 Decision flow 3

S4 User-model variants and baselines 3

S5 Decoder quality 4

S6 Per-device settings 4

S7 All policies on the fixed test sets 5

S8 Time-ordered tests: all designs and rules 6

S9 Per-day risk under the primary rule 6

S10 Random re-splits: sEMG rows and population risk 7

S11 Published-gate bonus 8

S12 Calibration and the commit trade-off 9

S13 Ablation 9

S14 Data reuse and the fixed-split drift tests 10

S15 Online re-calibration 11

S16 LM leakage check 11

S17 MEG decoder and sentence-level limits 12

S18 Stream format, standards and audit log 12

S19 What each calibration set was and was not used for 13

S20 Controls **14**

S21 How to state the guarantees **15**

S22 Data sets and licences **15**

S1 Notation

Table S1: Notation. Prose uses "error among commits"; tables use EAC.

Symbol	Meaning	Symbol	Meaning
F_i, V	frames in the stream of item i; vocabulary size	λ	commit threshold on s_i
K	candidate list size ($K = 10$; 11 for the published gate)	s_i	commit score: $\hat{p}_{\text{top1}}$ if eligible, else $-\infty$
$\hat{p}_{\text{top1}}$	calibrated probability of the top candidate	c_i	1 if the top candidate is wrong
τ_f, τ_s	frame and sentence temperatures	$L_i(\lambda)$	loss $c_i\,\mathbf{1}[s_i \geq \lambda]$
g_i	guard risk of the top candidate, in $[0, 1]$	$R(\lambda)$, $\hat{R}_n(\lambda)$	population and calibration risk
r_{abst}, $r_{\max}$	guard limits for abstain and commit	n	number of calibration items
k, $k_{\max}$	offered candidates; offer limit	α	target wrong-commit rate (0.05)
q	conformal quantile of the sentence set	β	target error among commits (0.10, 0.20)
n_λ, k_λ	calibration commits and wrong commits at λ	δ	failure probability of LTT (0.1)
η, γ	step sizes of the online controllers	T, d	items in an online sequence; feedback delay

S2 Fitting and calibration

Algorithm S1 Fitting and calibration of the commit threshold

Require: fit items $\mathcal{F}$ (parts $\mathcal{F}_1$, $\mathcal{F}_2$, $\mathcal{F}_3$; see below), disjoint calibration items $\mathcal{C}$ (n items with truth), α, β, δ

1: $\tau_f \leftarrow \arg\min_\tau$ cross-entropy of the aligned true tokens at the greedy CTC peaks of $\mathcal{F}_1$ ▷ golden section, $\tau \in [0.05, 20]$

2: $\tau_s \leftarrow \arg\min_\tau$ binary NLL of $[y_1 = \text{truth}]$ under $\text{softmax}(\text{score}/\tau)_1$ on $\mathcal{F}_1$

3: $q \leftarrow$ the $\lceil (m+1)(1-0.1) \rceil$-th smallest $1 - \hat{p}_{\text{truth}}$ over the m items of $\mathcal{F}_2$ whose truth is in the K-best list

4: $(\lambda_{\text{tuned}}, r_{\max}, r_{\text{abst}}, k_{\max}, \text{fallback}) \leftarrow$ grid point with the highest eWPM on $\mathcal{F}_3$ among those with wrong-commit rate $\leq \alpha$ (first in grid order on ties; if none, the lowest wrong-commit rate)

5: compute s_i and c_i for every $i \in \mathcal{C}$ (Algorithm 1 up to the commit score)

6: **CRC:** $\hat{\lambda}_{\text{CRC}} \leftarrow \min\{\lambda \in \{s_i\} \cup \{+\infty\} : (\sum_i c_i \mathbf{1}[s_i \geq \lambda] + 1)/(n+1) \leq \alpha\}$

7: **LTT:** for $\lambda = 1.00, 0.99, \ldots, 0.00$: $k \leftarrow \sum_i c_i \mathbf{1}[s_i \geq \lambda]$; if $\Pr(\text{Bin}(n, \alpha) \leq k) \leq \delta$ then $\hat{\lambda}_{\text{LTT}} \leftarrow \lambda$ else stop ▷ $+\infty$ if the first test fails

8: **Max rule (primary):** $\lambda \leftarrow \max(\lambda_{\text{tuned}}, \hat{\lambda}_{\text{LTT}})$ ▷ CRC max rule: $\max(\lambda_{\text{tuned}}, \hat{\lambda}_{\text{CRC}})$

9: **Joint LTT** (targets α, β): for $\lambda \in \{0.05, 0.10, \ldots, 1.00\}$: $p_{\text{marg}} \leftarrow \Pr(\text{Bin}(n, \alpha) \leq n\hat{R}_n(\lambda))$, $p_{\text{sel}} \leftarrow \Pr(\text{Bin}(n_\lambda, \beta) \leq k_\lambda)$ (1 if $n_\lambda = 0$); reject if $\max(p_{\text{marg}}, p_{\text{sel}}) \leq \delta/20$; $\hat{\lambda}_{\text{joint}} \leftarrow$ the smallest rejected λ ($+\infty$ if none). *LTT-sel*: the same with p_{sel} only.

10: **SGR** (comparison): bisection over the sorted finite s_i (m eligible items, $\lceil \log_2 m \rceil$ steps); accept λ if the exact binomial upper $(1 - \delta/\lceil \log_2 m \rceil)$ bound on $\Pr(c = 1 \mid s \geq \lambda)$ is $< \beta$ (strict, as in the code); $\hat{\lambda}_{\text{SGR}} \leftarrow$ the lowest accepted λ

Fit sets. Brain-to-Text '25: $\mathcal{F}_1$ = first half of the fit items in file order, $\mathcal{F}_2$ = second half, $\mathcal{F}_3$ = all fit items. sEMG: $\mathcal{F}_1$, $\mathcal{F}_2$ = the two halves of fit half A; $\mathcal{F}_3$ = fit half B (or its policy part). MEG: $\mathcal{F}_1$, $\mathcal{F}_2$ = halves of the validation instances, $\mathcal{F}_3$ = all validation instances. Each item has one attempt. The policy also has an optional maximum set size for a commit (not used). No max rule is applied to joint LTT, because raising λ keeps the marginal bound but not the selective one. A worked example of why selective bounds need many commits: with 40 calibration commits, the one-sided exact 90% upper bound on the error among commits is 0.056 for 0 wrong and 0.159 for 3 wrong (0.124 and 0.248 at the LTT-sel level $\delta/20$).

S3 Decision flow




Figure S1: Trust decision for one item (primary rule). A candidate is committed only if the guard (input-validity check) accepts it and its calibrated confidence reaches $\hat{\lambda} = \max(\lambda_{\text{tuned}}, \hat{\lambda}_{\text{LTT}})$. LTT bounds the risk over the mix of sessions that the calibration data come from. Otherwise the layer offers alternatives or abstains, and the user types with the fallback keyboard.

S4 User-model variants and baselines

Each variant changes one group of parameters of Table 5 and refits every policy: fallback speed 10 or 40 characters per minute (main 20); all selection, scanning, word-selection and navigation times scaled by 0.5 or 2; miss probability of a wrong committed word 0 or 0.2 (main 0.05). In the *symmetric-offer* variants, an offer without the intended sentence makes the user fix the closest candidate word by word, missing each wrong word with the same probability as after a commit; full retyping is disabled. In the *misspecified* evaluation, policies fitted under the main user are scored under each variant without refitting; they lost at most 0.2 eWPM against refitting, except with symmetric offers and miss probability 0.2 on the weak decoders (MEG 1.18 vs 2.75).

Gaze typing with word completion. The user types letter by letter at the fallback speed. Before each letter, the keyboard shows the three most frequent vocabulary words (counts ≥ 2) that start with the typed prefix; there is no sentence context. If the intended word is shown and selecting it is faster, the user selects it at the scan-and-select cost for three slots plus the word-selection time. The main baseline charges no time for looking at the list, which favours it [1]. Clinical AAC uses stronger, context-dependent prediction, so a realistic AAC baseline would probably be faster. Gaze typing with completion reached 5.84 (B2T '25), 6.19 (sEMG) and 4.10 (MEG) eWPM (point values).

Always commit against the layer. Table S2 gives the paired difference per variant (plug-in layer, refitted).

Table S2: Trust layer minus always commit (eWPM, 95% cluster-bootstrap CI), all policies refitted under each user-model variant. Values below 0: always commit is faster.

Variant	B2T ours	B2T publ.	sEMG s.-cal.	sEMG x-sess.	sEMG x-subj.	MEG
main	+0.10 [−0.14, 0.33]	−0.85 [−1.01, −0.66]	+0.22 [0.02, 0.39]	+0.57 [0.46, 0.69]	+0.55 [0.43, 0.66]	+0.62 [0.45, 0.83]
fallback 10 cpm	+0.50 [0.35, 0.64]	−0.76 [−1.02, −0.52]	+0.49 [0.32, 0.68]	+0.46 [0.38, 0.54]	+0.39 [0.33, 0.46]	+0.38 [0.28, 0.50]
fallback 40 cpm	−0.32 [−0.43, −0.18]	−0.88 [−1.00, −0.74]	+0.06 [−0.16, 0.29]	+0.56 [0.38, 0.72]	+0.57 [0.45, 0.68]	+0.84 [0.59, 1.12]
selection ×0.5	+0.28 [0.03, 0.53]	−0.46 [−0.59, −0.32]	+0.32 [0.13, 0.50]	+0.66 [0.54, 0.78]	+0.62 [0.50, 0.74]	+0.71 [0.52, 0.93]
selection ×2	−0.18 [−0.40, 0.04]	−1.47 [−1.72, −1.20]	+0.06 [−0.14, 0.25]	+0.30 [0.18, 0.42]	+0.28 [0.21, 0.34]	+0.42 [0.28, 0.58]
miss prob. 0	−0.11 [−0.30, 0.06]	−0.77 [−0.87, −0.67]	−0.02 [−0.14, 0.12]	−0.05 [−0.10, 0.02]	−0.06 [−0.07, −0.06]	−0.04 [−0.05, −0.04]
miss prob. 0.2	+0.74 [0.47, 1.05]	−0.96 [−1.21, −0.63]	+1.13 [0.83, 1.42]	+1.98 [1.78, 2.17]	+2.10 [1.95, 2.26]	+1.97 [1.75, 2.20]
symmetric, miss 0.05	−0.09 [−0.29, 0.09]	−0.79 [−0.90, −0.68]	+0.02 [−0.14, 0.19]	−0.01 [−0.06, 0.05]	−0.04 [−0.07, −0.01]	+0.21 [−0.09, 0.49]
symmetric, miss 0.2	−0.00 [−0.24, 0.25]	−0.83 [−0.94, −0.72]	+0.26 [0.08, 0.45]	+0.72 [0.04, 1.27]	+1.37 [0.98, 1.73]	+1.55 [1.25, 1.82]
always commit faster	5 of 9	9 of 9	1 of 9	2 of 9	2 of 9	1 of 9

S5 Decoder quality

Excluding the 6 MEG test sentences with a close training variant (CER ≤ 0.25 to a training sentence) gave 0.519 (greedy) and 0.492 (beam), so memorisation of near variants explains at most 0.02 of the CER. On sEMG, plain key accuracies (0.299, 0.168, 0.209) are below the majority-class rate (space, 0.338) because the CNNs rarely predict space; balanced accuracy is the fair metric. Over three MEG seeds, the greedy CER was 0.254, 0.243 and 0.140 below the shuffled control of the same seed (Table S4). For context, the published asynchronous MEG encoder reports a CER of 0.59 ± 0.02 with another split and without key-time training labels [2].

Table S3: Decoder quality and input controls (test sets). Exact: share of items whose top-1 sentence is right; in K-best: share whose intended sentence is in the 10-best list. MEG: the trust harness keeps an insertion bonus of 1.0 tuned on raw streams; the validation-tuned bonus of 0 gives the 0.475 row. "—": not applicable or not computed.

Device / decoder	CER	WER	Exact / in K-best	Controls and floors
MEG, asynchronous, greedy	0.506	0.842	—	shuffled 0.760, zeros 0.925
MEG, beam + LM tuned on validation	0.475	0.809	0.005 / —	text-only floor 0.688
MEG, beam in the trust harness	0.522	—	0.003 / 0.016	—
B2T '25, our phoneme-to-word decoder	0.095	0.149	0.390 / 0.623	—
B2T '25, published decoder	0.031	0.043	0.806 / —	—
sEMG keys: accuracy (balanced)	0.299 (0.367) / 0.168 (0.240) / 0.209 (0.226)		—	permuted labels 0.022 (0.032)
sEMG sentences after LM	0.123 / 0.398 / 0.479	0.214 / 0.579 / 0.681	0.459 / 0.118 / 0.038	in K-best 0.64 / 0.21 / 0.08

Table S4: MEG decoder over three training seeds (637 test instances; trust harness fitted on validation). Seed 0 is the paper's decoder.

	Seed 0	Seed 1	Seed 2	Mean ± SD
Test CER, greedy	0.506	0.502	0.592	0.533 ± 0.051
Test CER, beam + LM (validation-tuned)	0.475	0.467	0.567	0.503 ± 0.056
Shuffled MEG, greedy	0.760	0.745	0.732	0.746 ± 0.014
Zero input, greedy	0.925	0.948	0.819	0.897 ± 0.069
Always commit: eWPM / wrong-commit	2.58 / 0.997	2.55 / 0.994	2.35 / 1.000	
Trust: eWPM / commits	3.20 / 0	3.16 / 0	2.96 / 0	
Trust − gaze (gaze 3.15)	[−0.11, +0.26]	[−0.15, +0.23]	[−0.30, −0.05]	
Eligible to commit / truth in 10-best	0.024 / 0.016	0.036 / 0.019	0.002 / 0.000	

S6 Per-device settings

The policy grid has 1,980 points: commit threshold $\lambda \in \{0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.85, 0.9, 0.95, 0.98, 1.01\}$; maximum guard risk for a commit $r_{\max} \in \{0.1, 0.2, 0.3, 0.5, 1.0\}$; offer limit $k_{\max} \in \{0, 1, 2, 3, 5, 8\}$; abstain risk $r_{\text{abst}} \in \{0.6, 0.8, 1.01\}$; and fallback $\in$ {offer, abstain}. τ_s

reached the upper end of its search interval (20, which flattens the confidence) on MEG and sEMG cross-subject. Decoder settings are in the experiment configurations in the repository.

Table S5: Per-device settings of the shared trust-layer implementation (full-fit pipeline; fitted on each device's fit data, MEG: validation set). Max. guard risk: largest guard risk that still allows a commit.

	MEG	B2T '25, ours	B2T '25, published gate	sEMG (cal. / x-sess. / x-subj.)
Frame temperature τ_f	3.30	3.78	3.78	1.25 / 1.78 / 2.17
Sentence temperature τ_s	20.0	4.56	1.72	2.42 / 5.42 / 20.0
LM weight (beam)	0.5 (insertion bonus 1.0)	1.0 (word LM; edit penalty 12, word bonus 3)	as ours	1.0 / 1.0 / 1.5
Candidate list K	10	10	published sentence + our 10 (bonus +2.0)	10
Plug-in commit threshold	0.5	0.5	0.7	0.7 / 0.3 / 0.3
Max. guard risk for commit	0.3	0.5	0.5	1.0 / 1.0 / 0.1
Offer size k	1	2	1	2 / 2 / 1
Guard	low-evidence threshold 0.5; consistency over the top 5; risk = max(low evidence, 1 − consistency)			

S7 All policies on the fixed test sets

Why the fit-A rows differ from the full-fit plug-in row. In the two fixed splits, the fall from 0.059 (full fit) to 0.025 (split A) came entirely from the policy grid chosen on fit-A (commit threshold 0.3 and maximum guard risk 0.1, against 0.5 and 0.5 on the full fit data): the full-fit temperatures with the fit-A policy also gave 0.0245. In split A, CRC and LTT were not binding (CRC's calibration bound at the chosen threshold was 0.0075); in split B, the fit-A policy (threshold 0.4, guard 0.3) gave 0.060, and the risk control removed correct commits. Over random re-splits, the CRC max rule changed the plug-in decisions in 54% (ours) and 34% (published) of re-splits. Pure CRC on split A stops at the lowest eligible calibration score (0.3075); test items below it are never committed, which is why pure CRC (20 wrong) is stricter than LTT at $\lambda = 0$ (22 wrong).

Per day, plug-in layer. The plug-in layer beat always offering on 12 of 13 days with a difference (ours; sign test $p = 0.003$) and 14 of 14 (published; $p = 0.0001$); against always committing it tied (7 of 14 days; $p = 1.0$) and lost on 13 of 14 days (published).

Table S6: More policies on the fixed test sets. Columns as in Table 3. Plain threshold: full fit, no guard. Pure CRC / LTT: fit-A pipeline, clean calibration (B2T split A, $n = 401$; sEMG 143; MEG 199 instances of 5 sentences, no guarantee for new sentences), without the max rule. 256 non-templated: sEMG test sentences without a near variant in the LM text (Section S16). Unified bootstrap ($B = 2000$, seed 20261112).

Device	Policy	eWPM [CI]	Wrong-commit [CI]	Commit	EAC	Silent
B2T '25, ours	plain threshold (full fit)	11.51 [10.79, 12.35]	0.036 [0.025, 0.046]	0.17	0.22	0
	CRC, pure (split A)	11.48 [10.79, 12.29]	0.025 [0.015, 0.035]	0.10	0.24	0.001
	LTT, pure (split A)	11.48 [10.79, 12.29]	0.027 [0.016, 0.038]	0.10	0.26	0.001
B2T '25, published	plain threshold (full fit)	18.62 [17.01, 20.17]	0.025 [0.014, 0.038]	0.38	0.06	0.001
	CRC, pure (split A)	18.79 [17.13, 20.37]	0.048 [0.029, 0.071]	0.49	0.10	0.005
	LTT, pure (split A)	18.65 [17.04, 20.20]	0.029 [0.013, 0.050]	0.40	0.07	0.001
sEMG session-cal.	always offer	8.01 [6.92, 9.17]	0	0	—	0
	trust, plug-in	8.02 [6.93, 9.19]	0.004 [0, 0.009]	0.04	2/21	0
	CRC, pure	8.07 [6.98, 9.26]	0.040 [0.025, 0.056]	0.24	0.17	0.005
	LTT, pure	8.04 [6.97, 9.21]	0.022 [0.009, 0.036]	0.18	0.12	0.002
	trust, 256 non-templated	6.97 [5.94, 8.09]	0.004 (1/256)	0.01	1/2	0
sEMG cross-session	always offer	4.67 [4.19, 5.25]	0	0	—	0
	CRC, pure	4.66 [4.18, 5.24]	0.056 [0.039, 0.074]	0.09	0.61	0.007
	LTT, pure	4.67 [4.18, 5.25]	0.031 [0.021, 0.042]	0.05	0.57	0.005
	trust, 256 non-templated	4.08 [3.77, 4.42]	0	0	—	0
sEMG cross-subject	LM weight re-tuned	4.84 [4.28, 5.51]	0.002 [0, 0.006]	0.01	1/6	0
	trust, 256 non-templated	3.69 [3.50, 3.92]	0	0	—	0
MEG	CRC, pure (instance level)	3.20 [3.01, 3.43]	0.028 [0.006, 0.061]	0.03	18/19	0.005
	LTT, pure (instance level)	3.20 [3.01, 3.44]	0	0.002	0/1	0

S8 Time-ordered tests: all designs and rules

Order inside a day is file order (the only time order in the data file). For each prefix of days, the pipeline is fitted on all trials of the fit days (the fit-A recipe) and item tables are built for every later day. Table S7 gives every design and rule, with and without the guard. Applying the V1 threshold 2–12 days later kept the LTT max rate near 0.02–0.03 on average (repository table). The plug-in rule had one day with a CP lower bound above α in V1 (day 46), V4 (day 48) and V3 (day 34) on our decoder.

Table S7: Time-ordered tests, all designs (Brain-to-Text '25). Each cell: test days above α / test days, pooled wrong-commit rate (pooled commit rate). V1: calibrate on the previous day; V4: on the two previous days; V2: fit on days 1–3, calibrate on all earlier days; V3: calibrate on the first half of the test day.

Condition	Design	Plug-in	CRC pure	CRC max	LTT max	Joint β=0.10	Joint β=0.20
ours, guard	V1	5/12, 0.052 (0.21)	5/12, 0.041 (0.18)	4/12, 0.036 (0.16)	2/12, 0.022 (0.11)	0/12, 0.000 (0.00)	0/12, 0.000 (0.00)
ours, guard	V4	5/11, 0.060 (0.22)	5/11, 0.045 (0.20)	4/11, 0.042 (0.19)	0/11, 0.027 (0.14)	0/11, 0.000 (0.00)	0/11, 0.000 (0.00)
ours, guard	V2	6/10, 0.057 (0.25)	4/10, 0.046 (0.20)	4/10, 0.046 (0.20)	1/10, 0.027 (0.15)	0/10, 0.000 (0.00)	0/10, 0.000 (0.00)
ours, guard	V3	5/13, 0.058 (0.22)	5/13, 0.039 (0.17)	3/13, 0.029 (0.14)	2/13, 0.015 (0.09)	0/13, 0.000 (0.00)	0/13, 0.000 (0.00)
ours, no guard	V1	1/12, 0.038 (0.16)	5/12, 0.043 (0.17)	0/12, 0.029 (0.13)	0/12, 0.018 (0.10)	0/12, 0.000 (0.00)	0/12, 0.000 (0.00)
ours, no guard	V4	3/11, 0.041 (0.17)	6/11, 0.048 (0.19)	3/11, 0.031 (0.15)	1/11, 0.027 (0.14)	0/11, 0.000 (0.00)	0/11, 0.000 (0.00)
ours, no guard	V2	1/10, 0.032 (0.15)	3/10, 0.043 (0.18)	1/10, 0.032 (0.15)	0/10, 0.028 (0.14)	0/10, 0.000 (0.00)	0/10, 0.000 (0.00)
ours, no guard	V3	3/13, 0.043 (0.17)	4/13, 0.038 (0.15)	2/13, 0.025 (0.12)	2/13, 0.018 (0.09)	0/13, 0.000 (0.00)	0/13, 0.000 (0.00)
published, guard	V1	1/12, 0.023 (0.38)	4/12, 0.041 (0.45)	1/12, 0.021 (0.37)	0/12, 0.016 (0.32)	0/12, 0.000 (0.00)	0/12, 0.003 (0.08)
published, guard	V4	0/11, 0.020 (0.37)	3/11, 0.043 (0.46)	0/11, 0.020 (0.37)	0/11, 0.020 (0.35)	0/11, 0.001 (0.04)	0/11, 0.009 (0.24)
published, guard	V2	0/10, 0.024 (0.29)	0/10, 0.023 (0.29)	0/10, 0.023 (0.29)	0/10, 0.023 (0.29)	0/10, 0.002 (0.06)	0/10, 0.020 (0.26)
published, guard	V3	1/13, 0.028 (0.40)	2/13, 0.026 (0.40)	1/13, 0.020 (0.37)	1/13, 0.010 (0.19)	0/13, 0.000 (0.00)	0/13, 0.004 (0.03)
published, no guard	V1	1/12, 0.016 (0.34)	3/12, 0.043 (0.50)	0/12, 0.015 (0.34)	0/12, 0.010 (0.27)	0/12, 0.000 (0.00)	0/12, 0.003 (0.08)
published, no guard	V4	0/11, 0.014 (0.34)	2/11, 0.039 (0.49)	0/11, 0.014 (0.34)	0/11, 0.014 (0.33)	0/11, 0.001 (0.05)	0/11, 0.011 (0.28)
published, no guard	V2	0/10, 0.008 (0.26)	4/10, 0.046 (0.55)	0/10, 0.008 (0.26)	0/10, 0.008 (0.26)	0/10, 0.010 (0.22)	0/10, 0.018 (0.35)
published, no guard	V3	1/13, 0.021 (0.36)	3/13, 0.049 (0.49)	1/13, 0.020 (0.35)	1/13, 0.014 (0.21)	0/13, 0.000 (0.00)	0/13, 0.005 (0.04)

S9 Per-day risk under the primary rule

Table S8 gives the LTT max wrong-commit rate per day. On the published gate, day 34 was above α in 94% of re-splits; CRC max gave 0.108 and the plug-in rule 0.110 on that day. Joint LTT with $\beta = 0.10$ gave 0.016 on day 34 at a commit rate of 0.060. On sEMG, per test participant, LTT max stayed at or below 0.038 (session-calibrated), 0.023 (cross-session) and 0 (cross-subject). Per-day (Mondrian) LTT with a quarter of a day as calibration (8–52 items) was feasible only for day 76 (52 items $\geq$ 45) and committed nothing on the other 13 days.

Table S8: Per-day wrong-commit rate, LTT max rule (Brain-to-Text '25, guard on). Random re-splits: pooled over re-splits (5th–95th percentile), and share of re-splits with a day rate above α. Fixed splits: wrong commits / test trials of the day. Bold: pooled rate above α.

		Ours, 50 re-splits		Published, re-splits			Ours	Published	
Day	n_{test}	Pooled	$> \alpha$	Pooled, 50 (p05–p95)	$> \alpha$	Pooled, 200	Split A	Split A	Split B
27	14	0.000	0.00	0.047 (0.000–0.143)	0.58	0.048	0/15	1/15	1/15
34	50	0.036	0.28	**0.102** (0.049–0.160)	0.94	0.098	3/50	8/50	8/50
46	49	0.032	0.14	0.039 (0.000–0.082)	0.28	0.040	0/50	0/50	0/50
48	57	0.039	0.42	0.016 (0.000–0.035)	0.02	0.016	2/58	2/58	2/58
69	57	0.020	0.10	0.012 (0.000–0.035)	0.00	0.015	0/58	0/58	0/58
74	38	0.042	0.48	0.025 (0.000–0.053)	0.20	0.027	0/37	0/37	0/37
76	104	0.030	0.10	0.033 (0.010–0.053)	0.06	0.031	1/104	4/104	4/104
81	70	0.022	0.04	0.030 (0.006–0.065)	0.08	0.030	3/69	1/69	1/69
83	85	0.034	0.14	0.048 (0.024–0.077)	0.36	0.047	3/85	4/85	4/85
88	46	0.030	0.14	0.021 (0.000–0.043)	0.04	0.020	0/45	1/45	2/45
90	74	0.026	0.08	0.018 (0.000–0.041)	0.04	0.019	3/74	0/74	0/74
95	26	0.049	0.42	0.007 (0.000–0.038)	0.00	0.006	1/25	0/25	0/25
223	74	0.021	0.06	0.020 (0.000–0.041)	0.04	0.020	1/73	1/73	1/73
244	74	0.038	0.26	0.018 (0.000–0.041)	0.04	0.017	3/73	2/73	2/73

S10 Random re-splits: sEMG rows and population risk

Table S9: Random re-splits, sEMG and reuse rows (50; guard on). Columns as in Table 2. sEMG repeats keep the 551 test sentences fixed, so their spread is fit and calibration variation only. Cross-session: 34% of re-splits never committed under the max rules, so the means mix zero-commit and committing re-splits. Cross-subject never committed under the max rules. Reused: pure CRC calibrated on the data that also fitted the pipeline.

Condition	Rule	Wrong-commit	$> \alpha$ [CP95]	Commit	EAC
sEMG session-cal.	plug-in	0.015 (0.004–0.033)	0 [0, 0.07]	0.12	0.13
	CRC, pure	0.029 (0.011–0.061)	0.06 [0.01, 0.17]	0.19	0.15
	CRC, max rule	0.013 (0.004–0.024)	0 [0, 0.07]	0.11	0.12
	LTT, pure	0.017 (0.009–0.034)	0 [0, 0.07]	0.14	0.13
	LTT, max rule	0.011 (0.004–0.019)	0 [0, 0.07]	0.09	0.12
sEMG cross-session	plug-in	0.008 (0–0.033)	0.04 [0, 0.14]	0.02	0.44
	CRC, pure	0.025 (0–0.063)	0.14 [0.06, 0.27]	0.04	0.58
	CRC, max rule	0.007 (0–0.027)	0 [0, 0.07]	0.02	0.41
	LTT, pure	0.017 (0–0.044)	0.02 [0, 0.11]	0.03	0.53
	LTT, max rule	0.006 (0–0.023)	0 [0, 0.07]	0.02	0.38
B2T '25 ours	CRC, pure, reused	0.055 (0.037–0.085)	0.58	0.21	0.26
B2T '25 published	CRC, pure, reused	0.050 (0.032–0.073)	0.48	0.48	0.10

Population risk. LTT bounds the population risk at the chosen threshold, not the test rate of a finite split. A random split of a finite pool does not give that risk: the pool rate includes the calibration items on which the threshold was chosen (biased low), and the held-out rate adds test-sampling noise. If calibration sets are drawn *with replacement* from the pool, the pool is the exact population of an i.i.d. draw, and its risk at the chosen threshold is known. On the test pools of 816 trials (2,000 draws, $n_{\text{cal}} = 408$), the population risk of pure LTT exceeded α in 4.7% [3.8, 5.7] (ours) and 4.1% [3.3, 5.1] (published) of draws, within $\delta = 0.1$; pure CRC exceeded it in 37% and 38%, which CRC does not promise to avoid, while its mean population risk stayed at or below α (0.047–0.048). The pool-including-calibration design of an earlier version of this analysis (0.5% and 1.5%) is biased low; it gives 1.1% and 0.9% with 2,000 draws, and the held-out design gives 15% and 12%. For the random re-splits, with 200 with-replacement draws per re-split from that re-split's calibration and test pool, the population exceedance of LTT max was 0.026 (ours) and 0.014 (published); with 200 re-splits, 0.020 and 0.016, and the test-set exceedance $15/200 = 0.075$ [0.043, 0.121] and $11/200 = 0.055$ [0.028, 0.096]. LTT max was never above α in a re-split where CRC max was not (exact McNemar, 50 re-splits: 0 vs 3 discordant, $p = 0.25$, and 0 vs 6, $p = 0.031$; 200 re-splits: $p = 4.8 \times 10^{-7}$ and 1.2×10^{-7}).

CRC and LTT on random splits of the test pool. Random calibration/test splits of the test pool are exchangeable by construction, so they check the implementation, not the assumption. Table S10 and Figure S2 give CRC and LTT at several calibration sizes. With 20 calibration trials, CRC kept the mean valid but never committed in 17% of splits; LTT cannot commit below 45 items. A session-start block of the first 20 trials of each day gave CRC rates of 0.009 (ours) and 0.025 (published) at commit rates of 0.04 and 0.32, and 6 of 14 days never committed.

Table S10: CRC and LTT on random calibration/test splits of the test pool ($\alpha = 0.05$, $\delta = 0.1$; 500 splits). Wrong-commit: mean test rate; p90: its 90th percentile; $P_{>\alpha}$: share of splits with a test rate above α; Err. | commit: pooled over splits; Never: share of splits without a commit. MEG: pool of 637 instances (no guarantee for new sentences).

Data	Method, n_{cal}	Wrong-commit	p90	$P_{>\alpha}$	Commit	Err. | commit	Never
B2T '25, our decoder	CRC, 20	0.0308	0.089	0.22	0.123	0.25	0.17
	CRC, 100	0.0456	0.075	0.38	0.186	0.25	0
	CRC, 408	0.0479	0.069	0.43	0.192	0.25	0
	LTT, 50	0.0201	0.046	0.09	0.097	0.21	0
	LTT, 408	0.0356	0.052	0.15	0.156	0.23	0
B2T '25, published gate	CRC, 408	0.0495	0.071	0.46	0.484	0.10	0
	LTT, 408	0.0355	0.054	0.15	0.429	0.08	0
MEG, asynchronous	CRC, 408	0.0197	0.031	0	0.021	0.93	0
	LTT, 408	0.0220	0.031	0	0.024	0.93	0




Figure S2: CRC bounds the mean over splits; LTT bounds the population risk with probability $1 - \delta$ (full-fit pipeline). Test wrong-commit rate over 200 random calibration/test splits of the test pool with (a) 100 and (b) 408 calibration items. Dots: mean; bars: 5th to 90th percentile. Dotted line: $\alpha = 0.05$. A test rate above α in a single split is not a violation of either guarantee.

S11 Published-gate bonus

The gate puts the published sentence on top of our K-best list with score = our best score + bonus (`published_margin` in `experiments/2026-11-10-b2t25-trust/config.json`). The value 2.0 came with the first commit of that experiment (`3fb8154`, 2026-11-10) and never changed; no grid, tuning stage or selection record exists. The data file holds the published sentence but no scores or logits of the published decoder. With the published sentence as the only candidate (score 0, no character confidences), the layer has no signal to rank trials: the fitted policy never commits (threshold 1.01) and every rule equals always offering (18.11 eWPM). Bonus 0 makes the published sentence tie with our top candidate; the layer then commits less and is 1.3 eWPM slower.


Table S11: Sensitivity to the published-gate bonus (guard on). Full fit: plug-in wrong-commit [day-cluster CI], commit, eWPM. Splits A, B: LTT max wrong-commit (commit). Re-splits (50): LTT max mean wrong-commit, share above α (commit).

Bonus	Full fit: wrong-commit	Commit	eWPM	Split A	Split B	Re-splits
0	0.0233 [0.013, 0.037]	0.35	17.46	0.0245 (0.37)	0.0233 (0.35)	0.0224, 0.00 (0.34)
0.5	0.0453 [0.028, 0.069]	0.47	18.77	0.0233 (0.33)	0.0221 (0.33)	0.0277, 0.02 (0.38)
1	0.0319 [0.019, 0.046]	0.41	18.66	0.0221 (0.33)	0.0319 (0.41)	0.0292, 0.02 (0.39)
2 (paper)	0.0441 [0.027, 0.068]	0.47	18.77	0.0294 (0.40)	0.0306 (0.42)	0.0307, 0.02 (0.39)
4	0.0466 [0.028, 0.070]	0.48	18.78	0.0392 (0.47)	0.0306 (0.40)	0.0328, 0.02 (0.40)
published sentence alone	0 commits	0	18.11	0 commits	0 commits	—

S12 Calibration and the commit trade-off

Table S12: Sentence calibration and error detection (full-fit pipelines, fixed test sets; 95% percentile bootstrap at the primary unit). ECE: 15 equal-width bins; the binned ECE is biased upwards, so a percentile interval can lie beside its point value. AUROC: positive class = wrong top-1 sentence. [a]MEG: 2 of 637 top-1 sentences are right, so its AUROC is not informative.

Condition	n	Top-1 acc.	ECE raw	ECE calibrated	AUROC $1-\hat{p}$	AUROC guard
B2T '25 ours	816	0.390	0.448 [0.419, 0.475]	0.067 [0.065, 0.104]	0.797 [0.773, 0.819]	0.702 [0.677, 0.733]
B2T '25 published	816	0.806	0.102 [0.058, 0.161]	0.058 [0.044, 0.090]	0.710 [0.678, 0.744]	0.667 [0.620, 0.713]
sEMG session-cal.	551	0.459	0.154 [0.113, 0.199]	0.148 [0.117, 0.187]	0.828 [0.793, 0.860]	0.647 [0.559, 0.719]
sEMG cross-session	551	0.118	0.328 [0.293, 0.365]	0.072 [0.044, 0.102]	0.755 [0.686, 0.824]	0.555 [0.500, 0.616]
sEMG cross-subject	551	0.038	0.500 [0.481, 0.519]	0.083 [0.069, 0.099]	0.674 [0.506, 0.812]	0.497 [0.388, 0.639]
MEG[a]	637	0.003	0.205 [0.192, 0.220]	0.101 [0.091, 0.104]	0.952 [0.883, 0.998]	0.958 [0.917, 0.989]



(a) Sentence-level ECE. **(b)** Marginal risk. **(c)** Error among commits.

Figure S3: Calibration and the commit trade-off (full-fit plug-in pipeline, test sets; not the guaranteed rule). (a) Sentence ECE before and after temperature scaling. (b) For each commit threshold: share of test items committed (x) and committed wrongly (y); dotted line: $\alpha = 0.05$. (c) Error among commits at the same thresholds; dashed line: $\beta = 0.10$. Items blocked by the guard are never committed. Curves start at 10 commits. The error among commits of our decoder falls to 0.1–0.2 only below about 10% commits; that of the published decoder stays near or below 0.15.

S13 Ablation

Table S13 refits each variant on the condition's fit data and scores it on the same test items. *No calibration*: no temperature. *Confidence only*: both temperatures fitted, but the beam decodes the raw stream. *No sentence temperature*: the frame temperature is applied before the beam and the sentence calibrator is the identity. *No conformal sets*: OFFER shows the fitted top k. *LM weight re-tuned*: on sEMG, the LM weight is chosen on fit-A CER with the frame-calibrated streams; on MEG, the validation-tuned beam (3.14 instead of 3.20 eWPM, also no commits).

Without the sentence temperature, the wrong-commit rate on our intracortical decoder rose to 0.076 (paired [+0.001, +0.036]). Without the guard, it fell to 0.036 on our decoder (paired [−0.035, −0.011]; lower on 9 of 10 days with a difference, sign test $p = 0.021$) and to 0.025 on the published gate ([−0.034, −0.007]); its AUROC for a wrong top sentence (0.702) was below that of $\hat{p}_{\text{top1}}$. On sEMG cross-subject, re-tuning the LM weight gave 4.84 [4.28, 5.51] eWPM at top-1 CER 0.360 (instead of 0.479).

Table S13: Unified ablation (full fit; eWPM / wrong-commit rate; point values; "=": equal to trust).

Variant	B2T '25 ours	B2T '25 published	sEMG s.-cal.	sEMG x-sess.	sEMG x-subj.	MEG
trust (as reported)	11.55 / 0.059	18.77 / 0.044	8.02 / 0.004	4.68 / 0.004	4.08 / 0	3.20 / 0
no calibration	11.57 / 0.071	18.73 / 0.043	8.15 / 0.045	4.75 / 0.013	4.76 / 0.005	3.04 / 0.005
confidence only (raw decoding)	11.54 / 0.074	18.74 / 0.047	8.07 / 0.018	4.76 / 0.007	4.75 / 0	3.04 / 0
no sentence temperature	11.50 / 0.076	18.66 / 0.032	8.11 / 0.040	4.67 / 0.018	4.07 / 0.044	3.20 / 0
no guard	11.51 / 0.036	18.62 / 0.025	=	=	=	=
no conformal sets	11.53 / 0.059	=	8.07 / 0.020	=	=	=
OFFER_WORDS off (small grid)	11.25 / 0.032	18.62 / 0.025	7.98 / 0.004	4.64 / 0	4.08 / 0	3.20 / 0
OFFER_WORDS on (small grid)	11.32 / 0.054	18.59 / 0.026	7.99 / 0.015	4.64 / 0.005	4.08 / 0	3.20 / 0
LM weight re-tuned	—	—	8.02 / 0.004	4.73 / 0.013	4.84 / 0.002	3.14 / 0
gaze typing only	4.08	4.08	4.27	4.27	4.27	3.15

S14 Data reuse and the fixed-split drift tests

Table S14 gives all 12 reuse comparisons (reused minus clean calibration, test wrong-commit, paired by re-split). The Wilcoxon test over re-splits is valid only conditional on this pool of trials, because the re-splits overlap. The delete-a-day (or delete-a-participant) jackknife recomputes both thresholds without each cluster over all re-splits, so its standard error includes the overlap; it does not refit the pipeline. Holm corrects over the 12 comparisons. Only our decoder shows an effect after Holm (pure CRC and CRC max). With 200 re-splits, our decoder's pure-CRC effect is +0.0032 (jackknife Holm-adjusted $p = 0.17$). A single deployment detects a shift of 0.035 (our decoder), 0.038 (published) or 0.040–0.057 (sEMG) with 80% power.

Table S14: Calibration on reused data: all 12 comparisons (50 re-splits). Diff: mean of reused minus clean test wrong-commit. Wilcoxon over re-splits (conditional on the pool; Holm-adjusted in brackets); sign: re-splits with reused higher / lower; jackknife 95% CI and p (Holm).

Condition	Rule	Diff	Wilcoxon p (Holm)	Sign	Jackknife CI	Jackknife p (Holm)
B2T '25 ours	CRC pure	+0.0091	0.0027 (0.027)	35/14	[+0.0050, +0.0131]	3.2×10^{-4} (0.0038)
B2T '25 ours	CRC max	+0.0066	1.1×10^{-5} (1.3×10^{-4})	26/1	[+0.0025, +0.0107]	0.0042 (0.046)
B2T '25 ours	LTT pure	+0.0052	0.034 (0.24)	31/13	[−0.0018, +0.0122]	0.13 (1)
B2T '25 published	CRC pure	+0.0009	0.72 (1)	26/23	[−0.0051, +0.0068]	0.76 (1)
B2T '25 published	CRC max	+0.0035	0.0014 (0.015)	15/3	[−0.0015, +0.0085]	0.16 (1)
B2T '25 published	LTT pure	+0.0013	0.49 (1)	23/16	[−0.0027, +0.0053]	0.5 (1)
sEMG session-cal.	CRC pure	−0.0016	0.71 (1)	23/23	[−0.0106, +0.0074]	0.71 (1)
sEMG session-cal.	CRC max	+0.0019	0.011 (0.095)	9/1	[−0.0004, +0.0042]	0.1 (0.92)
sEMG session-cal.	LTT pure	−0.0038	0.02 (0.16)	15/33	[−0.0110, +0.0034]	0.28 (1)
sEMG cross-session	CRC pure	+0.0073	0.036 (0.24)	18/13	[+0.0012, +0.0134]	0.021 (0.21)
sEMG cross-session	CRC max	+0.0012	0.11 (0.54)	3/0	[−0.0006, +0.0029]	0.19 (1)
sEMG cross-session	LTT pure	+0.0008	0.81 (1)	13/15	[−0.0077, +0.0094]	0.84 (1)

Fixed-split drift tests. On the fixed splits (Table S15), clean CRC gave 0.0245 and 0.0600 on our decoder, against 0.0625 when the full-fit pipeline was calibrated on its own fit data. The two clean values above α were within the range of exchangeable splits ($p = 0.21$ and 0.30). In split A the test rate was above the exchangeable reference ($p = 0.012$; day-stratified $p = 0.014$) but below α, where CRC was not binding; after Holm correction over the six tests, none was significant (split A: 0.072). These tests have low power: the 5th–95th percentile range of the reference is 0.029–0.071 on split B and the published gate, and 0.014–0.022 on split A. We claim neither within-day drift nor that reuse caused the old value of 0.0625.

Table S15: Fixed splits: clean vs reused calibration (pure CRC; test sets). Bound: CRC calibration bound $(n\hat{R}_n(\hat{\lambda})+1)/(n+1)$. Exch. ref.: mean (5th–95th percentile) over 1,000 random splits of the pooled calibration and test items; $p=(k+1)/(B+1)$, one-sided; Holm over the six tests.

Data (n_{test})	Reused	Clean CRC [CI]	Bound	Exch. ref.	p	Holm	LTT, pure
B2T '25 ours, split A (816)	0.0625	0.0245 [0.015, 0.035]	0.0075	0.018 (0.014–0.022)	0.012	0.072	0.0270
B2T '25 ours, split B (816)	0.0625	0.0600 [0.049, 0.071]	0.0498	0.049 (0.029–0.071)	0.21	1.0	0.0515
B2T '25 published, split A (816)	0.0490	0.0478 [0.029, 0.071]	0.0498	0.049 (0.029–0.074)	0.54	1.0	0.0294
B2T '25 published, split B (816)	0.0490	0.0490 [0.030, 0.073]	0.0498	0.050 (0.031–0.074)	0.50	1.0	0.0306
sEMG cross-session (551)	0.0635	0.0563 [0.039, 0.074]	0.0486	0.045 (0.018–0.080)	0.30	1.0	0.0309
sEMG session-cal. (551)	0.0417	0.0399 [0.025, 0.056]	0.0486	0.047 (0.018–0.082)	0.60	1.0	0.0218

S15 Online re-calibration

An online controller re-tunes the commit threshold from user feedback, with a long-run guarantee for any sequence of items (Table S16). On the fixed splits (warm start on the clean calibration data, then the test data in file order), the online controllers kept the long-run rate at 0.0245–0.0527 (Brain-to-Text '25) and 0.0381–0.0526 (sEMG), at eWPM within 0.06 of offline CRC (Table S17). The bounds say nothing about short windows: the largest rate in a rolling window of 50 items was 0.06–0.18. When only noticed errors were fed back (delay 10), `aci` reached 0.027–0.058 while its certificate on the observed losses was at most 0.0509: silent errors look correct to the controller. The sEMG online order is participant by participant, not a time sequence.

Table S16: Online re-calibration methods. L_t: realised loss of item t; T: items in the sequence; d: feedback delay. The `aci` variants bound the long-run average of the *observed* losses for any sequence; `window` and `decay` have no guarantee under shift.

Method	Update	Guarantee	Feedback
`window`	CRC on the last $N=200$ items with known truth	none under shift	full
`decay`	weighted CRC on all past items, weights 0.99^{age}	none under shift	full
`aci`	$\lambda_{t+1}=\max(0,\lambda_t+\eta(L_t-\alpha))$, $\eta=0.05$ [3–5]	$\frac{1}{T}\sum_t L_t \le \alpha+\frac{\lambda_{T+1}-\lambda_1}{\eta T}$; a priori $\alpha+\frac{1-\lambda_1+\eta(1+d)}{\eta T}$	realised only
`aci_window`	window CRC at level α_t; $\alpha_{t+1}=\min(2\alpha,\alpha_t+\gamma(\alpha-L_t))$, $\gamma=0.005$	$\frac{1}{T}\sum_t L_t \le \alpha+\frac{\alpha_1-\alpha_{T+1}}{\gamma T}$	full + realised

Table S17: Online re-calibration on the fixed splits (long-run test wrong-commit rate). Cert. / a priori: `aci` bound after the fact and in advance.

Data	`window`	`decay`	`aci`	`aci_window`	Cert. / a priori
B2T '25 ours, split A	0.0245	0.0257	0.0270	0.0245	0.043 / 0.068
B2T '25 ours, split B	0.0478	0.0453	0.0527	0.0490	0.053 / 0.066
B2T '25 published, split A	0.0429	0.0392	0.0478	0.0453	0.048 / 0.059
B2T '25 published, split B	0.0441	0.0392	0.0478	0.0453	0.048 / 0.059
sEMG cross-session	0.0472	0.0381	0.0526	0.0490	0.053 / 0.081
sEMG session-cal.	0.0490	0.0454	0.0490	0.0490	0.049 / 0.072

S16 LM leakage check

A near variant is a sentence within a character edit distance of 0.25 times its length, after normalisation, in the 600,000-sentence training slice of the English character LM. Of the 1,717 unique Brain-to-Text '25 cue sentences, 22 have an exact copy and 310 an exact or near variant; of the 551 sEMG test sentences, none has an exact copy and 295 have a near variant (Tatoeba is heavily templated). Rebuilding the LMs without these sentences changed 2 of 1,628 top-1 sentences on Brain-to-Text '25 and sEMG trust eWPM by at most -0.04, and no wrong-commit rate by more than 0.002. Rebuilding does not remove the advantage of templated test sentences, which are easier to decode, so we also scored the 256 sEMG test sentences without a near variant:

trust eWPM fell from 8.02, 4.68 and 4.08 to 6.97, 4.08 and 3.69; trust minus gaze typing became [+1.82, +3.92], [−0.37, +0.27] and [−0.66, −0.23]; always-commit wrong-commit rates rose to 0.664, 0.961 and 0.992; and the layer stayed safe (1 wrong commit in 256 sentences; one-sided upper bound 0.018). On Brain-to-Text '25, excluding the 147 test trials with a near variant gave a trust wrong-commit rate of 0.055 (all: 0.059) on our decoder and 0.042 (0.044) on the published gate.

S17 MEG decoder and sentence-level limits

We split 19 participants' data by a hash of the sentence text into 101 training, 11 validation and 17 test sentences (637 test instances); the same people appear in all splits, and no test sentence is in training or LM text. All trust parameters are fitted on the 437 validation instances (6 sentences fit, 5 calibrate in the deployment protocol). The decoder is a convolutional front end (320 channels) followed by 4 Conformer layers of width 256 [6], trained with CTC and a keystroke auxiliary loss that uses key times as training labels. At inference it takes the MEG segment (first key − 0.4 s to last key press + 0.5 s), its length and the participant index; it has no key input (the published asynchronous decoder takes the same inputs but uses no key-time labels [2]). The trust harness keeps the beam settings of the earlier harness; with the validation-tuned beam the layer also committed nothing.

Sentence-grouped calibration. Instances of one sentence are dependent, so a guarantee for new sentences needs the sentence as the unit: sentence-level CRC needs at least 19 calibration sentences and LTT 45, while the data set has 5 clean calibration, 11 validation and 17 test sentences. Sentence-level CRC was therefore infeasible and never committed. With calibration and test sentences disjoint, instance-level CRC gave mean test rates of 0.016–0.019 (never above α in 1,000 splits each with 5, 8 or 11 calibration sentences), but only 2.4% of instances were eligible and 0.91–0.94 of the commits were wrong; the max rule committed nothing. Two-way MEG intervals: trust minus gaze typing [−0.10, +0.25] (sentences [−0.04, +0.15], participants [−0.08, +0.22]); gaze typing with word completion was faster [−1.13, −0.64]. A synchronous control decoder with oracle key times gave the same trust result; over trials (instead of sentences) its difference to gaze typing excluded 0, which shows how trial-level intervals overstate MEG gains.

S18 Stream format, standards and audit log

Fields and rules. Besides the log-probability array, frame times, vocabulary, vocabulary type (`char`, `key`, `phoneme`, ...) and blank index, optional fields give the frame period, latency, producer and a `meta` object with named key prefixes (`device.*`, `decoder.*`, `lm.*`, `calibration.*`, `adapter.*`). A field is interpreted as a probability only if the stream declares it as one in `calibration.*`. Raw signals and direct identifiers stay out of the stream. NWB [7], BCI2000 and OpenViBE [8, 9], IEEE P2731 and P2794 [10–12] and decoder benchmarks [13, 14] each cover part of the stack; none defines a per-frame decoded-output format with confidence semantics.

Serialisations, conformance and adapters. The reference serialisations are an NPZ file and a JSON Lines streaming form. A conformance suite runs 60 checks, each tied to a specification clause, at three cumulative levels (*core*, *trust-ready*, *provenance*); it ships 52 golden test vectors, and the reference consumer passes all 52. The adapters have 412 (intracortical), 568 (sEMG) and 156 (MEG) physical lines of Python. Mapping the decoders into the stream needed no change to the frame core of v0.1, a Development release written by the same authors.

Table S18: Devices, data and streams. All data sets are public.

	Intracortical (speech)	Forearm sEMG (keys)	MEG (typing)
Data set (licence)	B2T '25 copy task (CC0)	Toronto sEMG (CC BY 4.0)	SpanishBCBL (CC BY-NC 4.0)
Participants	1 (T15, ALS)	19 (healthy typists)	19 (healthy typists)
Test unit	816 trials, 14 days	551 composed sentences	637 instances of 17 sentences
Decoder	published online RNN; own phoneme-to-word decoder	own CNN	own asynchronous ConvCTC
Stream vocabulary	`phoneme` (CTC, 41 tokens)	`key` (W3C codes)	`char` (CTC)
Frame	80 ms	one per key press	40 ms
Commit decision tested?	yes	weakly (0–9% committed)	no (no right top-1)




Figure S4: Architecture. Each device's decoder emits a stream through a small adapter. The trust layer reads the stream: it calibrates confidence, builds candidate sentences, and chooses an action under a risk-control rule. The user's corrections and picks (dashed) can feed online re-calibration. Decisions can be written to a hash-chained audit log that stores no raw signals.

Audit log. Each decision can be appended to a JSON Lines log. Context entries are content-addressed and hold the adapter, decoder, LM, calibration and policy versions; decision entries hold the action, scores, a hash of the stream and its frame range; correction entries link to the decision they correct. Each entry stores the hash of the previous entry, so any edit, deletion or reordering breaks the chain; a separately stored head anchor detects truncation. The log stores no raw signals and is tamper-evident, not tamper-proof (no signature in v0). A replay of the 816 Brain-to-Text '25 test trials (1,723 entries) passed verification, recorded the same wrong commits as the harness, and detected every tampering case we tried, at about 0.1 ms and 1.1 kB per decision (Figure S5).

Wrong commit `dec-000041-ed60b4bd` (entry 44, hash `8cf2c6c67053b185...`)
Committed: "who you never expect to when"
Correction (known cue sentence, hash-linked): "who you never expect to win"; 2 character edits, 1 word edit
Scores: $\hat{p}_{\text{top1}}$ 0.5814, set size 3, guard risk 0.2857; reason: $\hat{p}_{\text{top1}} \geq 0.50$
Input: stream `1b4b60e8e4950710...`, frames [0, 335], item `b2t25-test-trial-196`
Decoder: published online RNN + our phoneme-to-word decoder; LM: Tatoeba character 6-gram + word unigram + CMUdict
Calibration `cal-692fb52a73417552`: τ_f 3.7809, τ_s 4.5551; policy `pol-2eaa4ff51919527a`: commit threshold 0.5

Figure S5: One entry of the audit report (B2T '25 replay, full-fit plug-in layer, our decoder; public CC0 copy-task cue, not the participant's own words). Hashes are shortened.

S19 What each calibration set was and was not used for

Both guarantees need the parts that define s_i (temperatures, conformal sets, guard and policy thresholds) to be fitted on data disjoint from the calibration items. Four exceptions remain. (1) Brain-to-Text '25, fixed splits: the word-decoder grid (LM weight, edit penalty, word bonus; 12

points) was tuned on a random 400 of the 812 fit trials, so 187 and 189 of the 401 calibration trials of splits A and B were in that tuning set; re-tuning on fit-A only selected the same setting in both splits. (2) Brain-to-Text '25, random re-splits and time-ordered tests: the same 400 trials are permuted into fit-A, calibration and test parts (about 100 into calibration and 200 into test per re-split); the re-tune check covers only the two fixed splits, so this overlap is not checked. The grid is small, so the bias is likely small. (3) MEG: the decoder checkpoint was selected by validation CER, and the validation sentences include the 5 calibration sentences. (4) sEMG session-calibrated: calibration and test logits come from two cross-fitted decoder runs, so their score functions differ by design. LTT also needs i.i.d. sampling; our random splits sample without replacement from a finite pool, which makes its binomial test conservative.

S20 Controls

Table S19 gives the commits on the Brain-to-Text '25 control streams for the frozen configurations of drafts v3 and v4. With the guard, the split-A pipeline committed no frame-shuffled or uniform stream on either decoder, and its real-trial test rate was unchanged (0.0245 ours, 0.0294 published; a refit that reproduces the committed values). On Brain-to-Text '25, the guard risk separated frame-shuffled and uniform streams from real ones with AUROC 0.981 and 0.998. On MEG the layer committed nothing on real input either, so its zero commits on controls carry no information; the guard risk separated shuffled MEG, zero input and uniform streams (AUROC 0.92, 1.00, 1.00), but not frame-shuffled streams (0.47) (Figure S6c).

Table S19: Commits on the Brain-to-Text '25 control streams (300 test trials; split-A pipeline unless marked). Other trial: the real stream of a different sentence (intent mismatch). Frame-shuffled and uniform streams carry no neural information, so every commit on them is wrong. Uniform WC: wrong-commit rate on uniform streams.

Decoder	Configuration	Real	Other trial	Frame-shuffled	Uniform	Uniform WC
ours	guard on (frozen v4), LTT max	29/300	29/300	0/300	0/300	0.00
ours	guard on, joint LTT $\beta = 0.10$	0/300	0/300	0/300	0/300	0.00
ours	guard off (frozen v3), LTT max	43/300	43/300	3/300	198/300	0.66
ours	guard off, plug-in, full fit	38/300	38/300	2/300	203/300	0.68
published	guard on (frozen v4), LTT max	115/300	0/300	0/300	0/300	0.00
published	guard on, joint LTT $\beta = 0.10$	0/300	0/300	0/300	0/300	0.00
published	guard off (frozen v3), LTT max	110/300	0/300	0/300	0/300	0.00
published	guard off, plug-in, full fit	106/300	0/300	0/300	0/300	0.00




Figure S6: Controls (full-fit plug-in layer with the guard). (a, b) Commit rate of always commit (orange) and the trust layer (blue) on real input, the intent-mismatch control (other sentence) and signal-destroying controls: (a) B2T '25, our decoder, 300 test trials; (b) sEMG cross-session, 200 test sentences. (c) MEG, 637 instances: AUROC of the guard risk for separating each control from real input (dotted line: chance).

S21 How to state the guarantees

With LTT and the max rule (primary): "if the calibration sentences and later sentences are i.i.d. draws from the same mix of sessions, and the calibration sentences fitted no other part of the system, then, with probability at least 0.9 over the choice of the calibration sentences, the long-run share of sentences committed wrongly, averaged over that mix of sessions, is at most 0.05". It is not a statement about each session; in our data one day ran at about 0.10. With CRC: "under exchangeability and the same separation, averaged over the choice of the n calibration sentences and over a new sentence, the probability that the new sentence is committed wrongly is at most 0.05"; a single calibration set can exceed 0.05. With joint LTT: "with probability at least 0.9, both the long-run wrong-commit share is at most α and the long-run share of wrong sentences among committed sentences is at most β" (i.i.d. calibration sentences, separate from all fitted parts). With SGR: the bound of Geifman and El-Yaniv (2017, Theorem 3.2) on the error among accepted items, with probability at least 0.9, for i.i.d. calibration sentences separate from all fitted parts; its thresholds are chosen by bisection on the same data. With adaptive online re-calibration: "for any sequence of sentences, the average observed wrong-commit rate over the first T sentences is at most $0.05 + (1 - \lambda_1 + \eta(1 + d))/(\eta T)$". On MEG the unit is the sentence, and none of these statements applies to new sentences. All statements count only the errors that the system observes, so each should be reported with the measured silent-error rate.

S22 Data sets and licences

Table S20: Data sets, resources and licences.

Data set / resource	Licence	Use	Note
SpanishBCBL [15, 16]	CC BY-NC 4.0	MEG decoder training and evaluation	Research only; weights trained on it are not released for commercial use
Brain-to-Text '25 copy-task logits [17, 18]	CC0 1.0	intracortical trust evaluation	Companion code has no licence; we wrote our own loader
Toronto sEMG typing [19, 20]	CC BY 4.0	sEMG decoder and trust evaluation	Baseline code (CC BY-SA 4.0) not used
Tatoeba English / Spanish sentences	CC BY 2.0 FR (some CC0)	character LMs; composed sEMG sentences	Sentences from Tatoeba (`https://tatoeba.org`), by the Tatoeba contributors
CMUdict (commit 7479086)	BSD-2-Clause style	phoneme-to-word lexicon	Copyright notice kept
Brain2Qwerty code (Meta)	CC BY-NC 4.0	read only, not copied	Our decoders are our own implementations
Fidetype code and specification	Apache-2.0	all methods	—

References

[1] Heidi Horstmann Koester and Simon P. Levine. Modeling the speed of text entry with a word prediction interface. *IEEE Transactions on Rehabilitation Engineering*, 2(3):177–187, 1994. doi: 10.1109/86.331567.

[2] Mingfang Zhang, Jarod Lévy, Cedric Rommel, Jérémy Rapin, Corentin Bel, Julie Bonnaire, Daniel Nieto, Pierre Bourdillon, Svetlana Pinet, Stéphane d'Ascoli, Thomas Moreau, and

Jean-Rémi King. Accurate decoding of natural sentences from non-invasive brain recordings, 2026. arXiv:2608.18114.

[3] Isaac Gibbs and Emmanuel Candès. Adaptive conformal inference under distribution shift. In *Advances in Neural Information Processing Systems*, volume 34, pages 1660–1672, 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/hash/0d441de75945e5acbc865406fc9a2559-Abstract.html. arXiv:2106.00170.

[4] Anastasios N. Angelopoulos, Emmanuel J. Candès, and Ryan J. Tibshirani. Conformal PID control for time series prediction. In *Advances in Neural Information Processing Systems*, volume 36, pages 23047–23074, 2023. doi: 10.52202/075280-1000. arXiv:2307.16895.

[5] Shai Feldman, Liran Ringel, Stephen Bates, and Yaniv Romano. Achieving risk control in online learning settings. *Transactions on Machine Learning Research*, 2023. URL https://openreview.net/forum?id=5Y04GWvoJu. arXiv:2205.09095.

[6] Anmol Gulati, James Qin, Chung-Cheng Chiu, Niki Parmar, Yu Zhang, Jiahui Yu, Wei Han, Shibo Wang, Zhengdong Zhang, Yonghui Wu, and Ruoming Pang. Conformer: Convolution-augmented transformer for speech recognition, 2020. arXiv:2005.08100.

[7] Oliver Rübel, Andrew Tritt, Ryan Ly, Benjamin K. Dichter, Satrajit Ghosh, Lawrence Niu, Pamela Baker, Ivan Soltesz, Lydia Ng, Karel Svoboda, Loren Frank, and Kristofer E. Bouchard. The Neurodata Without Borders ecosystem for neurophysiological data science. *eLife*, 11:e78362, 2022. doi: 10.7554/eLife.78362.

[8] Gerwin Schalk, Dennis J. McFarland, T. Hinterberger, Niels Birbaumer, and Jonathan R. Wolpaw. BCI2000: A general-purpose brain-computer interface (BCI) system. *IEEE Transactions on Biomedical Engineering*, 51(6):1034–1043, 2004. doi: 10.1109/TBME.2004.827072.

[9] Yann Renard, Fabien Lotte, Guillaume Gibert, Marco Congedo, Emmanuel Maby, Vincent Delannoy, Olivier Bertrand, and Anatole Lécuyer. OpenViBE: An open-source software platform to design, test, and use brain–computer interfaces in real and virtual environments. *Presence: Teleoperators and Virtual Environments*, 19(1):35–53, 2010. doi: 10.1162/pres.19.1.35.

[10] IEEE. P2731: IEEE draft standard for a unified terminology for brain-computer interfaces. IEEE Standards Association project page, 2018. URL https://standards.ieee.org/ieee/2731/7383/. Active PAR, approved 27 September 2018.

[11] IEEE. P2794: IEEE draft trial-use standard for reporting standards for in vivo neural interface research (RSNIR). IEEE Standards Association project page, 2022. URL https://standards.ieee.org/ieee/2794/11108/. Active PAR, approved 3 December 2022.

[12] Calvin Eiber, Jean Delbeke, Jorge Cardoso, Martijn de Neeling, Sam John, Chang Won Lee, Jerry Skefos, Argus Sun, Dimiter Prodanov, and Zach McKinney. Preliminary minimum reporting requirements for in-vivo neural interface research: I. implantable neural interfaces. *IEEE Open Journal of Engineering in Medicine and Biology*, 2:74–83, 2021. doi: 10.1109/OJEMB.2021.3060919.

[13] Vinay Jayaram and Alexandre Barachant. MOABB: Trustworthy algorithm benchmarking for BCIs, 2018. arXiv:1805.06427.

[14] Hubert Banville, Stéphane d'Ascoli, Simon Dahan, Jérémy Rapin, et al. NeuralBench: A unifying framework to benchmark NeuroAI models, 2026. arXiv:2605.08495.

[15] Jarod Lévy, Mingfang Zhang, Svetlana Pinet, Jérémy Rapin, Hubert Banville, Stéphane d'Ascoli, and Jean-Rémi King. Noninvasive decoding of typed sentences from human brain activity. *Nature Neuroscience*, 29(10):2438–2444, 2026. doi: 10.1038/s41593-026-02303-2.

[16] BCBL. DECOMEG — brain activity during typing (MEG & EEG) (dataset). Hugging Face, https://huggingface.co/datasets/bcbl190626/SpanishBCBL, 2026. Basque Center on Cognition, Brain and Language. CC BY-NC 4.0.

[17] Nicholas S. Card, Maitreyee Wairagkar, Carrina Iacobacci, Xianda Hou, Tyler Singer-Clark, Francis R. Willett, Erin M. Kunz, Chaofei Fan, Maryam Vahdati Nia, Darrel R. Deo, Aparna Srinivasan, Eun Young Choi, Matthew F. Glasser, Leigh R. Hochberg, Jaimie M. Henderson, Kiarash Shahlaie, Sergey D. Stavisky, and David M. Brandman. An accurate and rapidly calibrating speech neuroprosthesis. *New England Journal of Medicine*, 391(7): 609–618, 2024. doi: 10.1056/NEJMoa2314132.

[18] Nicholas S. Card et al. Data for: An accurate and rapidly calibrating speech neuroprosthesis. Dryad, version 5, 2025. doi: 10.5061/dryad.dncjsxm85. CC0 1.0.

[19] Jonathan Eby, Moshe Beutel, David Koivisto, Idan Achituve, Ethan Fetaya, and José Zariffa. Electromyographic typing gesture classification dataset for neurotechnological human-machine interfaces. *Scientific Data*, 12:440, 2025. doi: 10.1038/s41597-025-04763-w.

[20] José Zariffa. Electromyographic typing gesture classification dataset for neurotechnological human-machine interfaces. Borealis (University of Toronto Dataverse), version 1.0, 2024. doi: 10.5683/SP3/KV65VI. CC BY 4.0.