

# Tree-like graphings of countable Borel equivalence relations

An exposition to

*Tree-like graphings, wallings, and median graphings of equivalence relations*

by Ruiyuan Chen, Antoine Poulin, Ran Tao, and Anush Tserunyan

Zhaoshen Zhai

October 1, 2024

# Countable Borel Equivalence Relations

## Definition

A *countable Borel equivalence relation (CBER)* on a standard Borel space  $X$  is a Borel equivalence relation  $E \subseteq X^2$  such that each  $E$ -class is countable.

# Countable Borel Equivalence Relations

## Definition

A *countable Borel equivalence relation (CBER)* on a standard Borel space  $X$  is a Borel equivalence relation  $E \subseteq X^2$  such that each  $E$ -class is countable.

## Example

Any Borel action  $\Gamma \curvearrowright X$  of a countable (discrete) group on a standard Borel space induces its *orbit equivalence relation*  $E_\Gamma^X$ , which is a CBER.



# Countable Borel Equivalence Relations

## Definition

A *countable Borel equivalence relation* (CBER) on a standard Borel space  $X$  is a Borel equivalence relation  $E \subseteq X^2$  such that each  $E$ -class is countable.

## Example

Any Borel action  $\Gamma \curvearrowright X$  of a countable (discrete) group on a standard Borel space induces its *orbit equivalence relation*  $E_\Gamma^X$ , which is a CBER.



# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation = on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .

# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation = on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .
- $\mathbb{Z}$ -coset equivalence on  $\mathbb{R}$ :  $x E_{\mathbb{Z}}^{\mathbb{R}} y$  iff  $x - y \in \mathbb{Z}$ .

# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation  $=$  on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .
- $\mathbb{Z}$ -coset equivalence on  $\mathbb{R}$ :  $x E_{\mathbb{Z}}^{\mathbb{R}} y$  iff  $x - y \in \mathbb{Z}$ .

## Example (Hyperfinite)

$E_0$  on  $2^{\mathbb{N}}$ , where  $x E_0 y$  iff  $\exists n \in \mathbb{N}, \forall m \geq n : x_m = y_m$ .

# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation  $=$  on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .
- $\mathbb{Z}$ -coset equivalence on  $\mathbb{R}$ :  $x E_{\mathbb{Z}}^{\mathbb{R}} y$  iff  $x - y \in \mathbb{Z}$ .

## Example (Hyperfinite)

$E_0$  on  $2^{\mathbb{N}}$ , where  $x E_0 y$  iff  $\exists n \in \mathbb{N}, \forall m \geq n : x_m = y_m$ .

This CBER is *hyperfinite*:  $E_0 = \bigcup_n F_n$  for an increasing sequence  $F_0 \subseteq F_1 \cdots$  of finite Borel equivalence relations:



# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation = on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .
- $\mathbb{Z}$ -coset equivalence on  $\mathbb{R}$ :  $x E_{\mathbb{Z}}^{\mathbb{R}} y$  iff  $x - y \in \mathbb{Z}$ .

## Example (Hyperfinite)

$E_0$  on  $2^{\mathbb{N}}$ , where  $x E_0 y$  iff  $\exists n \in \mathbb{N}, \forall m \geq n : x_m = y_m$ .

This CBER is *hyperfinite*:  $E_0 = \bigcup_n F_n$  for an increasing sequence  $F_0 \subseteq F_1 \cdots$  of finite Borel equivalence relations:

$$x F_n y \quad \leftrightarrow \quad \forall m \geq n : x_m = y_m.$$

# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation = on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .
- $\mathbb{Z}$ -coset equivalence on  $\mathbb{R}$ :  $x E_{\mathbb{Z}}^{\mathbb{R}} y$  iff  $x - y \in \mathbb{Z}$ .

## Example (Hyperfinite)

$E_0$  on  $2^{\mathbb{N}}$ , where  $x E_0 y$  iff  $\exists n \in \mathbb{N}, \forall m \geq n : x_m = y_m$ .

This CBER is *hyperfinite*:  $E_0 = \bigcup_n F_n$  for an increasing sequence  $F_0 \subseteq F_1 \cdots$  of finite Borel equivalence relations:

$$x F_n y \quad \leftrightarrow \quad \forall m \geq n : x_m = y_m.$$

## Theorem (Slaman-Steel, Weiss)

Let  $E$  be a CBER on a standard Borel space  $X$ . TFAE:

1.  $E$  is hyperfinite.  $E = \bigcup_n F_n$  where  $F_0 \subseteq F_1 \subseteq \cdots$  are FBERs.
2.  $E$  is induced by a Borel  $\mathbb{Z}$ -action.  $E = E_{\mathbb{Z}}^X$  for some  $\mathbb{Z} \curvearrowright X$ .



# Smooth and Hyperfinite CBERs

## Example (Smooth)

- Identity relation = on a standard Borel space, say  $\mathbb{R}$  or  $2^{\mathbb{N}}$ .
- $\mathbb{Z}$ -coset equivalence on  $\mathbb{R}$ :  $x E_{\mathbb{Z}}^{\mathbb{R}} y$  iff  $x - y \in \mathbb{Z}$ .

## Example (Hyperfinite)

$E_0$  on  $2^{\mathbb{N}}$ , where  $x E_0 y$  iff  $\exists n \in \mathbb{N}, \forall m \geq n : x_m = y_m$ .



# Graphing of a CBER





## Definition

A *graphing* of a CBER  $E$  on  $X$  is a Borel graph  $G \subseteq X^2$  whose connected relation is  $E$ , i.e.,  $xEy \leftrightarrow xG \cdots Gy$  for all  $x, y \in X$ .

# Graphing of a CBER

## Definition





A *graphing* of a CBER  $E$  on  $X$  is a Borel graph  $G \subseteq X^2$  whose connected relation is  $E$ , i.e.,  $xEy \leftrightarrow xG \cdots Gy$  for all  $x, y \in X$ .



# Treeings and Treeability

## Definition


A *treeing* of a CBER  $E$  is an acyclic graphing, and a CBER  $E$  is said to be *treeable* if it admits a treeing.



# Treeable CBERs

## Example (Free Actions)


Free actions of a free group  $F_r \curvearrowright X$ .



# Treeable CBERs

## Example (Free Actions)

Free actions of a free group  $F_r \curvearrowright X$ .



## Theorem (JKL02)


*Free actions of virtually-free groups are treeable.*



# Treeable CBERs

## Example (Free Actions)

Free actions of a free group  $F_r \curvearrowright X$ .



## Theorem (JKL02)

*Free actions of virtually-free groups are treeable.*


## Theorem (GdlH90)

*Every finitely-generated group whose Cayley graph is a quasi-tree is virtually-free, and hence treeable.*

# Treeable CBERs

## Example (Free Actions)

Free actions of a free group  $F_r \curvearrowright X$ .



## Theorem (JKL02)

*Free actions of virtually-free groups are treeable.*

## Theorem (GdlH90)

*Every finitely-generated group whose Cayley graph is a quasi-tree is virtually-free, and hence treeable.*

## Question (Robin Tucker-Drob; 2015)

Is the class of treeable CBERs robust under quasi-isometries?

# Main Result

Theorem (Chen, Poulin, Tao, Tserunyan; 2023+)


*If a CBER  $E$  admits a locally-finite graphing such that each component is a quasi-tree, then  $E$  is treeable.*

# Main Result

Theorem (Chen, Poulin, Tao, Tserunyan; 2023+)

*If a CBER  $E$  admits a locally-finite graphing such that each component is a quasi-tree, then  $E$  is treeable.*

Two metric spaces  $X, Y$  are *quasi-isometric* if they are isometric up to a bounded multiplicative and additive error;  $X$  is a *quasi-tree* if it is quasi-isometric to a tree.



# Game Plan

Quasi-treeing

Treeing


# Game Plan

Quasi-treeing



Quasi-tree

Treeing




# Game Plan

Quasi-treeing

Treeing

Quasi-tree

Finitely-sep.  
family of cuts



# Game Plan

Quasi-treeing

Treeing

Quasi-tree

Finitely-sep.  
family of cuts





# Game Plan


Quasi-treeing

Treeing

Quasi-tree

Finitely-sep.  
family of cuts

Median graph w/  
finite hyperplanes



# Game Plan

Quasi-treeing


Treeing

Quasi-tree



Finitely-sep.  
family of cuts

Median graph w/  
finite hyperplanes



'Canonical'  
spanning tree



# Game Plan



# Game Plan



# The End

Thank you!