Material Safety Data Sheet



Calcium Carbide, Lump

Revised: 11/18/2011 **Replaces:** 11/17/2011 **Printed:** 12/01/2011

Carolina Biological Supply Company

2700 York Rd | Burlington, NC 27215 • to order: 800.334.5551 • for support: 800.227.1150



Section 1 - Product Description

Product Name: Calcium Carbide Lump

Product Code(s): 85-1700

Size: 500 g

Chemical Name: Calcium Carbide

CAS Number: 75-20-7 **Formula:** CaC2/CaO

Synonyms: Acetylenogen, Carbide

Distributor: Carolina Biological Supply Company, 2700 York Road, Burlington, NC 27215

Chemical Information: 800-227-1150 (8am-5pm (ET) M-F) Chemtrec 800-424-9300 (Transportation Spill Response 24

hours)

Section 2 - Hazard Identification

Emergency Overview: Flammable. Reacts violently with water, liberating extremely flammable gases. Harmful if swallowed.

Irritating to eyes and skin. **Potential Health Effects:**

Eyes: May cause irritation. **Skin:** May cause irritation to skin.

Ingestion: May cause gastrointestinal discomfort. **Inhalation:** May cause irritation to respiratory tract.

Section 3 - Composition / Information on Ingredients

Principal Hazardous Components: Calcium Carbide, Lump (CAS# 75-20-7) 65-85%; Calci

TLV units: ACGIH-TLV 2 mg/m3 (TWA) **PEL units:** OSHA-PEL 5 mg/m3 (TWA)

Section 4 - First Aid Measures

Emergency and First Aid Procedures:

Eves - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin - After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Ingestion - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. If swallowed, rinse mouth with water (only if the person is conscious).

Inhalation - In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Section 5 - Firefighting Procedures

Product Name: Calcium Carbide, Lump Page 1 of 4

Flash Point (Method Used): Flash Point of generated acetylene gas is 0 °C

NFPA Rating: Health: 3 Fire: 3 Reactivity: 2

Extinguisher Media: Use dry chemical or cover with dry sand or lime.

Flammable Limits in Air % by Volume: Acetylene gas LEL: 2.5% UEL: 100% **Autoignition Temperature:** Temperature of generated Acetylene Gas is 305 °C

Special Firefighting Procedures: Firefighters should wear full protective equipment and NIOSH approved self-contained

breathing apparatus.

Unusual Fire and Explosion Hazards: Reacts violently with water, liberating extremely flammable gases.

Never add water to this product.

Above flashpoint, explosive vapor-air mixtures may be formed.

Section 6 - Spill or Leak Procedures

Steps to Take in Case Material Is Released or Spilled: Ventilate area of spill. Clean-up personnel should wear proper protective equipment. Avoid creating dust. Sweep or scoop up and containerize for disposal.

Section 7 - Special Precautions

Precautions to Take in Handling or Storing: Risk of explosion by shock, friction, fire or other sources of ignition.

Do not use copper ground strap or cable.

Keep away from combustible material.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Keep away from ... (incompatible materials to be indicated by the manufacturer).

Keep container dry.

Keep away from sources of ignition - No smoking.

Never add water to this product. Keep container tightly closed in a cool, well-ventilated place.

Section 8 - Protection Information

Respiratory Protection (Specify Type): None needed under normal conditions of use with adequate ventilation. A NIOSH/MSHA chemical cartridge respirator should be worn if PEL or TLV is exceeded.

Ventilation:

Local Exhaust: Yes

Mechanical(General): Yes (Explosion Proof)

Special: No **Other:** No

Protective Gloves: Natural rubber, Neoprene, PVC or equivalent. **Eye Protection:** Splash proof chemical safety goggles should be worn.

Other Protective Clothing or Equipment: Lab coat, apron, eye wash, safety shower.

Section 9 - Physical Data

Molecular Weight:64.1Melting Point:2300 °CBoiling Point:N/AVapor Pressure:N/A

Vapor Density(Air=1):N/ASpecific Gravity (H2O=1):2.22 at 20 °CPercent Volatile by Volume:N/AEvaporation Rate (BuAc=1):N/A

Solubility in Water: Soluble **Appearance and Odor:** Gray-bluish black, rock-like appearance;

odor of acetylene (garlic-like) always present.

Section 10 - Reactivity Data

Stability: Stable

Conditions to Avoid: Heat and sources of ignition.

Water; Product is water reactive.

Incompatibility (Materials to Avoid): Metals, Water,

Product Name: Calcium Carbide, Lump Page 2 of 4

Hazardous Decomposition Products: Hydrocarbons, CaOH2

Hazardous Polymerization: Will not occur

Section 11 - Toxicity Data

Toxicity Data: N/A
Effects of Overexposure:
Acute: See Section 2
Chronic: N/A

Conditions Aggravated by Overexposure: Respiratory disorders, Skin disorders, Eye disorders,

Target Organs: Respiratory system, Skin, Eyes,

Primary Route(s) of Entry: N/A

Section 12 - Ecological Data

EPA Waste Numbers: N/A

Section 13 - Disposal Information

Waste Disposal Methods: Dispose in accordance with all applicable Federal, State and Local regulations. Always contact a permitted waste disposer (TSD) to assure compliance.

Section 14 - Transport Information

DOT Proper Shipping Name: UN1402, Calcium Carbide, 4.3, II

Section 15 - Regulatory Information

EPA TSCA Status: On TSCA Inventory

Hazard Category for SARA Section 311/312 Reporting: Acute

Name List: Chemical Category:

No No

CERCLA Section 103 RQ(lb.): 10 **RCRA Section 261.33:** No

Section 16 - Additional Information

The information provided in this Material Safety Data Sheet represents a compilation of data drawn directly from various sources available to us. Carolina Biological Supply makes no representation or guarantee as to the suitability of this information to a particular application of the substance covered in the Material Safety Data Sheet. Any employer must carefully assess the applicability of any information contained herein in regards to the particular use to which the employer puts the material.

Glossary

ACGIH American Conference of Governmental Industrial Hygienists

CAS Number Chemical Services Abstract Number

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

DOT U.S. Department of Transportation

IARC International Agency of Research on Cancer

N/A Not Available

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

ppm Parts per million

RCRA Resource Conservation and Recovery Act

Product Name: Calcium Carbide, Lump Page 3 of 4

Superfund Amendments and Reauthorization Act Threshold Limit Value Toxic Substances Control Act SARA TLV TSCA

Product Name: Calcium Carbide, Lump