The Brain Imaging Data Structure (BIDS) Specification

Version 1.1.2

Available under the CC-BY 4.0 International license

Table of contents

- Introduction (01-introduction.pdf)
- Motivation (01-introduction.pdf)
- Extensions (01-introduction.pdf)
- · Citing BIDS (01-introduction.pdf)
- Common principles (02-common-principles.pdf)
- Definitions (02-common-principles.pdf)
- · Compulsory, optional, and additional data and metadata (02-common-principles.pdf)
- · Source vs. raw vs. derived data (02-common-principles.pdf)
- The Inheritance Principle (02-common-principles.pdf)
 - Good practice recommendations (02-common-principles.pdf)
- File Formation specification (02-common-principles.pdf)
 - Imaging files (02-common-principles.pdf)
 - Tabular files (02-common-principles.pdf)
- Key/value files (dictionaries) (02-common-principles.pdf)
- Participant names and other labels (02-common-principles.pdf)
- Units (02-common-principles.pdf)
- Directory structure (02-common-principles.pdf)
 - Single session example (02-common-principles.pdf)
- Modality-agnostic files (03-modality-agnostic-files.pdf)
- Dataset description (03-modality-agnostic-files.pdf)
 - dataset_description.json (03-modality-agnostic-files.pdf)
 - README (03-modality-agnostic-files.pdf)
 - CHANGES (03-modality-agnostic-files.pdf)
- Participants file (03-modality-agnostic-files.pdf)
- Scans file (03-modality-agnostic-files.pdf)
- Code (03-modality-agnostic-files.pdf)
- · Modality-specific-files
 - Magnetic Resonance Imaging data (04-modality-specific-files/01-magnetic-resonance-imagingdata.pdf)
 - · Common metadata fields (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - Scanner Hardware (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - Sequence Specifics (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - In-Plane Spatial Encoding (04-modality-specific-files/01-magnetic-resonance-imagingdata.pdf)
 - Timing Parameters (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - RF & Contrast (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - Slice Acceleration (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - Anatomical landmarks (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
 - Institution information (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)

- Anatomy imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Required fields (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Other RECOMMENDED metadata (04-modality-specific-files/01-magnetic-resonanceimaging-data.pdf)
 - Timing Parameters (04-modality-specific-files/01-magnetic-resonance-imagingdata.pdf)
 - fMRI task information (04-modality-specific-files/01-magnetic-resonance-imagingdata.pdf)
- Diffusion imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Fieldmap data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Phase difference image and at least one magnitude image (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Two phase images and two magnitude images (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- A real fieldmap image (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Case 4: Multiple phase encoded directions ("pepolar") (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)
- Magnetoencephalography (MEG) (04-modality-specific-files/02-magnetoencephalography.pdf)
- MEG recording data (04-modality-specific-files/02-magnetoencephalography.pdf)
 - Sidecar JSON document (*_meg.json) (04-modality-specific-files/02-magnetoencephalography.pdf)
- Channels description table (*_channels.tsv) (04-modality-specific-files/02-magnetoencephalography.pdf)
- Coordinate System JSON document (*_coordsystem.json) (04-modality-specific-files/02-magnetoencephalography.pdf)
 - Landmark photos (*_photo.jpg) (04-modality-specific-files/02-magnetoencephalography.pdf)
 - 3-D head point /electrode locations file (04-modality-specific-files/02-magnetoencephalography.pdf)
 - Empty-room files (sub-emptyroom) (04-modality-specific-files/02-magnetoencephalography.pdf)
- Task events (04-modality-specific-files/03-task-events.pdf)
- Physiological and other continuous recordings (04-modality-specific-files/04-physiological-andother-continuous-recordings.pdf)
- Behavioral experiments (with no MRI) (04-modality-specific-files/05-behavioural-experiments.pdf)
- Longitudinal studies with multiple sessions (visits) (05-longitudinal-and-multi-site-studies.pdf)
- Sessions file (05-longitudinal-and-multi-site-studies.pdf)
- Multi-site or multi-center studies (05-longitudinal-and-multi-site-studies.pdf)
 - Treat each site/center as a separate dataset (05-longitudinal-and-multi-site-studies.pdf)
 - Option 2: Combining sites/centers into one dataset (05-longitudinal-and-multi-site-studies.pdf)
- Contributing to and extending the BIDS specification (06-extensions.pdf)
- Contributing to BIDS (06-extensions.pdf)
 - The BIDS Starter Kit (06-extensions.pdf)
 - The BIDS Contributor guide (06-extensions.pdf)

- BIDS Extension Proposals (06-extensions.pdf)
- Appendices
 - Appendix I: Contributors (99-appendices/01-contributors.pdf)
 - Appendix II: Licenses (99-appendices/02-licenses.pdf)
 - Appendix III: Hierarchical Event Descriptor (HED) Tags (99-appendices/03-hed.pdf)
 - Appendix IV: Entity table (99-appendices/04-entity-table.pdf)
 - Appendix V: Units (99-appendices/05-units.pdf)
 - Prefixes (99-appendices/05-units.pdf)
 - Multiples (99-appendices/05-units.pdf)
 - Submultiples (99-appendices/05-units.pdf)
 - Appendix VI: MEG file formats (99-appendices/06-meg-file-formats.pdf)
 - CTF (99-appendices/06-meg-file-formats.pdf)
 - Neuromag/Elekta/MEGIN (99-appendices/06-meg-file-formats.pdf)
 - BTi/4D neuroimaging (99-appendices/06-meg-file-formats.pdf)
 - KIT/Yokogawa/Ricoh (99-appendices/06-meg-file-formats.pdf)
 - KRISS (99-appendices/06-meg-file-formats.pdf)
 - ITAB (99-appendices/06-meg-file-formats.pdf)
 - Aalto MEG-MRI (99-appendices/06-meg-file-formats.pdf)
 - Appendix VII: preferred names of MEG systems (99-appendices/07-meg-systems.pdf)
 - Appendix VIII: preferred names of Coordinate systems (99-appendices/08-coordinatesystems.pdf)
 - MEG specific Coordinate Systems (99-appendices/08-coordinate-systems.pdf)
 - EEG specific Coordinate Systems (99-appendices/08-coordinate-systems.pdf)
 - Template based Coordinate Systems (99-appendices/08-coordinate-systems.pdf)

Documentation built with MkDocs (https://www.mkdocs.org/).

Introduction

Motivation

Neuroimaging experiments result in complicated data that can be arranged in many different ways. So far there is no consensus how to organize and share data obtained in neuroimaging experiments. Even two researchers working in the same lab can opt to arrange their data in a different way. Lack of consensus (or a standard) leads to misunderstandings and time wasted on rearranging data or rewriting scripts expecting certain structure. Here we describe a simple and easy-to-adopt way of organising neuroimaging and behavioural data. By using this standard you will benefit in the following ways:

- It will be easy for another researcher to work on your data. To understand the organisation of the files
 and their format you will only need to refer them to this document. This is especially important if you are
 running your own lab and anticipate more than one person working on the same data over time. By using
 BIDS you will save time trying to understand and reuse data acquired by a graduate student or postdoc
 that has already left the lab.
- There are a growing number of data analysis software packages that can understand data organised according to BIDS (see http://bids.neuroimaging.io (http://bids.neuroimaging.io) for the most up to date list).
- Databases such as OpenNeuro.org accept datasets organised according to BIDS. If you ever plan to share your data publicly (nowadays some journals require this) you can minimize the additional time and energy spent on publication, and speed up the curation process by using BIDS to structure and describe your data right after acquisition.
- There are validation tools (https://github.com/Squishymedia/BIDS-Validator) that can check your dataset integrity and let you easily spot missing values.

BIDS is heavily inspired by the format used internally by OpenfMRI.org and has been supported by the International Neuroinformatics Coordinating Facility and the Neuroimaging Data Sharing Task Force. While working on BIDS we consulted many neuroscientists to make sure it covers most common experiments, but at the same time is intuitive and easy to adopt. The specification is intentionally based on simple file formats and folder structures to reflect current lab practices and make it accessible to a wide range of scientists coming from different backgrounds.

Extensions

The BIDS specification can be extended in a backwards compatible way and will evolve over time. This is accomplished through community-driven BIDS Extention Proposals (BEPs). For more information about the BEP process, and list of current BEP proposals, see Extending the BIDS specification (06-extensions.pdf).

Citing BIDS

When referring to BIDS in context of academic literature please cite:

Gorgolewski, K.J., Auer, T., Calhoun, V.D., Craddock, R.C., Das, S., Duff, E.P., Flandin, G., Ghosh, S.S., Glatard, T., Halchenko, Y.O., Handwerker, D.A., Hanke, M., Keator, D., Li, X., Michael, Z., Maumet, C., Nichols, B.N., Nichols, T.E., Pellman, J., Poline, J.-B., Rokem, A., Schaefer, G., Sochat, V., Triplett, W., Turner, J.A., Varoquaux, G., Poldrack, R.A., 2016. The brain imaging data structure, a format for organizing and describing outputs of neuroimaging experiments (https://www.nature.com/articles/sdata201644). Sci Data 3, 160044.

as well as other papers describing specific BIDS extensions (see below).

BIDS has also a Research Resource Identifier (RRID) (https://www.force11.org/group/resource-identification-initiative) - RRID: SCR_016124 - which you can also include in your manuscript in addition to citing the paper.

Documentation built with MkDocs (https://www.mkdocs.org/).

Common principles

Definitions

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119 (https://www.ietf.org/rfc/rfc2119.txt)].

Throughout this protocol we use a list of terms. To avoid misunderstanding we clarify them here.

- 1. Dataset a set of neuroimaging and behavioural data acquired for a purpose of a particular study. A dataset consists of data acquired from one or more subjects, possibly from multiple sessions.
- 2. Subject a person or animal participating in the study.
- 3. Session a logical grouping of neuroimaging and behavioural data consistent across subjects. Session can (but doesn't have to) be synonymous to a visit in a longitudinal study. In general, subjects will stay in the scanner during one session. However, for example, if a subject has to leave the scanner room and then be re-positioned on the scanner bed, the set of MRI acquisitions will still be considered as a session and match sessions acquired in other subjects. Similarly, in situations where different data types are obtained over several visits (for example fMRI on one day followed by DWI the day after) those can be grouped in one session. Defining multiple sessions is appropriate when several identical or similar data acquisitions are planned and performed on all -or most- subjects, often in the case of some intervention between sessions (e.g., training).
- 4. Data acquisition a continuous uninterrupted block of time during which a brain scanning instrument was acquiring data according to particular scanning sequence/protocol.
- 5. Data type a functional group of different types of data. In BIDS we define five data types: func (task based and resting state functional MRI), dwi (diffusion weighted imaging), fmap (field inhomogeneity mapping data such as field maps), anat (structural imaging such as T1, T2, etc.), meg (magnetoencephalography).
- 6. Task a set of structured activities performed by the participant. Tasks are usually accompanied by stimuli and responses, and can greatly vary in complexity. For the purpose of this protocol we consider the so-called "resting state" a task. In the context of brain scanning, a task is always tied to one data acquisition. Therefore, even if during one acquisition the subject performed multiple conceptually different behaviours (with different sets of instructions) they will be considered one (combined) task.
- 7. Event a stimulus or subject response recorded during a task. Each event has an onset time and duration. Note that not all tasks will have recorded events (e.g., resting state).
- 8. Run an uninterrupted repetition of data acquisition that has the same acquisition parameters and task (however events can change from run to run due to different subject response or randomized nature of the stimuli). Run is a synonym of a data acquisition.

Compulsory, optional, and additional data and metadata

The following standard describes a way of arranging data and writing down metadata for a subset of neuroimaging experiments. Some aspects of the standard are compulsory. For example a particular file name format is required when storing structural scans. Some aspects are regulated but optional. For example a T2 volume does not need to be included, but when it is available it should be saved under a particular file name specified in the standard. This standard aspires to describe a majority of datasets, but acknowledges that there will be cases that do not fit. In such cases one can include additional files and subfolders to the existing folder structure following common sense. For example one may want to include eye tracking data in a vendor specific format that is not covered by this standard. The most sensible place to put it is next to the continuous recording file with the same naming scheme but different extensions. The solutions will change from case to case and publicly available datasets will be reviewed to include common data types in the future releases of the BIDS spec.

Source vs. raw vs. derived data

BIDS in its current form is designed to harmonize and describe raw (unprocessed or minimally processed due to file format conversion) data. During analysis such data will be transformed and partial as well as final results will be saved. Derivatives of the raw data (other than products of DICOM to NIfTI conversion) MUST be kept separate from the raw data. This way one can protect the raw data from accidental changes by file permissions. In addition it is easy to distinguish partial results from the raw data and share the latter. Similar rules apply to source data which is defined as data before harmonization and/or file format conversion (for example E-Prime event logs or DICOM files).

This specification currently does not go into details of recommending a particular naming scheme for including different types of source data (raw event logs, parameter files, etc. before conversion to BIDS) and data derivatives (correlation maps, brain masks, contrasts maps, etc.). However, in the case that these data are to be included:

- 1. These data MUST be kept in separate sourcedata and derivatives folders each with a similar folder structure as presented below for the BIDS-managed data. For example:

 derivatives/fmriprep/sub-01/ses-pre/sub-01_ses-pre_mask.nii.gz or sourcedata/sub-01/ses-pre/func/sub-01_ses-pre_task-rest_bold.dicom.tgz or sourcedata/sub-01/ses-pre/func/MyEvent.sce.
- 2. A README file SHOULD be found at the root of the sourcedata or the derivatives folder (or both). This file should describe the nature of the raw data or the derived data. In the case of the existence of a derivatives folder, we RECOMMEND including details about the software stack and settings used to generate the results. Inclusion of non-imaging objects that improve reproducibility are encouraged (scripts, settings files, etc.).
- 3. We RECOMMEND including the PDF print-out with the actual sequence parameters generated by the scanner in the sourcedata folder.

The Inheritance Principle

Any metadata file (.json , .bvec , .tsv , etc.) may be defined at any directory level, but no more than one applicable file may be defined at a given level (Example 1). The values from the top level are inherited by all lower levels unless they are overridden by a file at the lower level. For example,

sub-*_task-rest_bold.json may be specified at the participant level, setting TR to a specific value. If one of the runs has a different TR than the one specified in that file, another sub-*_task-rest_bold.json file can be placed within that specific series directory specifying the TR for that specific run. There is no notion of "unsetting" a key/value pair. For example if there is a JSON file corresponding to particular participant/run defining a key/value and there is a JSON file on the root level of the dataset that does not define this key/value it will not be "unset" for all subjects/runs. Files for a particular participant can exist only at participant level directory, i.e /dataset/sub-*[/ses-*]/sub-*_T1w.json . Similarly, any file that is not specific to a participant is to be declared only at top level of dataset for eg: task-sist_bold.json must be placed under /dataset/task-sist_bold.json

Example 1: Two JSON files at same level that are applicable for NIfTI file.

```
sub-01/
ses-test/
sub-test_task-overtverbgeneration_bold.json
sub-test_task-overtverbgeneration_run-2_bold.json
anat/
sub-01_ses-test_T1w.nii.gz
func/
sub-01_ses-test_task-overtverbgeneration_run-1_bold.nii.gz
sub-01_ses-test_task-overtverbgeneration_run-2_bold.nii.gz
```

In the above example, two JSON files are listed under <code>sub-01/ses-test/</code>, which are each applicable to <code>sub-01_ses-test_task-overtverbgeneration_run-2_bold.nii.gz</code>, violating the constraint that no more than one file may be defined at a given level of the directory structure. Instead <code>task-overtverbgeneration_run-2_bold.json</code> should have been under <code>sub-01/ses-test/func/</code>.

Example 2: Multiple run and rec with same acquisition (acq) parameters acq-test1

```
sub-01/
anat/
func/
sub-01_task-xyz_acq-test1_run-1_bold.nii.gz
sub-01_task-xyz_acq-test1_run-2_bold.nii.gz
sub-01_task-xyz_acq-test1_rec-recon1_bold.nii.gz
sub-01_task-xyz_acq-test1_rec-recon2_bold.nii.gz
sub-01_task-xyz_acq-test1_bold.json
```

For the above example, all NIfTI files are acquired with same scanning parameters (acq-test1). Hence a JSON file describing the acq parameters will apply to different runs and rec files. Also if the JSON file (task-xyz_acq-test1_bold.json) is defined at dataset top level directory, it will be applicable to all task runs with test1 acquisition parameter.

Case 2: Multiple json files at different levels for same task and acquisition parameters

In the above example, the fields from <code>task-xyz_acq-test1_bold.json</code> file will apply to all bold runs. However, if there is a key with different value in <code>sub-01/func/sub-01_task-xyz_acq-test1_run-1_bold.json</code>, the new value will be applicable for that particular run/task NIfTI file/s.

Good practice recommendations

Try to avoid excessive amount of overrides. Do not specify a field value in the upper levels if lower levels have more or less even distribution of multiple possible values. E.g., if a field X has one value for all ses-01/ and another for all ses-02/ it better not to be defined at all in the join at the upper level.

File Formation specification

Imaging files

All imaging data MUST be stored using the NIfTI file format. We RECOMMEND using compressed NIfTI files (.nii.gz), either version 1.0 or 2.0. Imaging data SHOULD be converted to the NIfTI format using a tool that provides as much of the NIfTI header information (such as orientation and slice timing information) as possible. Since the NIfTI standard offers limited support for the various image acquisition parameters available in DICOM files, we RECOMMEND that users provide additional meta information extracted from DICOM files in a sidecar JSON file (with the same filename as the <code>.nii[.gz]</code> file, but with a <code>.json</code> extension). Extraction of BIDS compatible metadata can be performed using dcm2nii https://www.nitrc.org/projects/dcm2nii/ (https://www.nitrc.org/projects/dcm2nii/) and dicm2nii http://www.mathworks.com/matlabcentral/fileexchange/42997-dicom-to-nifti-converter/content/dicm2nii.m (http://www.mathworks.com/matlabcentral/fileexchange/42997-dicom-to-nifti-converter/content/dicm2nii.m) DICOM to NIfTI converters. A provided validatorhttps://github.com/INCF/bids-validator (https://github.com/INCF/bids-validator) will check for conflicts between the JSON file and the data recorded in the NIfTI header.

Tabular files

Tabular data MUST be saved as tab delimited values (.tsv) files, i.e. csv files where commas are replaced by tabs. Tabs MUST be true tab characters and MUST NOT be a series of space characters. Each TSV file MUST start with a header line listing the names of all columns (with the exception of physiological and other continuous acquisition data - see below for details). Names MUST be separated with tabs. String values containing tabs MUST be escaped using double quotes. Missing and non-applicable values MUST be coded as n/a.

Example:

```
onset duration response_time correct stop_trial go_trial 200 200 0 n/a n/a
```

Tabular files MAY be optionally accompanied by a simple data dictionary in a JSON format (see below). The data dictionaries MUST have the same name as their corresponding tabular files but with . j son extensions. If a JSON file is provided, it MAY contain one or more fields describing the columns found in the TSV file (in addition to any other metadata one wishes to include that describe the file as a whole). Note that if a field name included in the JSON sidecar matches a column name in the TSV file, then that field MUST contain a description of the corresponding column, using an object containing the following fields:

Field **Definition** name

LongName Long (unabbreviated) name of the column.

Description Description of the column.

Levels For categorical variables: a dictionary of possible values (keys) and their descriptions (values).

Measurement units. [| construction | construct

Units RECOMMENDED (see Appendix V).

TermURL URL pointing to a formal definition of this type of data in an ontology available on the web.

Example:

```
"test": {
    "LongName": "Education level",
    "Description": "Education level, self-rated by participant",
    "Levels": {
      "1": "Finished primary school",
      "2": "Finished secondary school",
      "3": "Student at university",
      "4": "Has degree from university"
    }
  },
  "bmi": {
    "LongName": "Body mass index",
    "Units": "kilograms per squared meters",
    "TermURL": "http://purl.bioontology.org/ontology/SNOMEDCT/60621009"
  }
}
```

Key/value files (dictionaries)

JavaScript Object Notation (JSON) files MUST be used for storing key/value pairs. Extensive documentation of the format can be found here: http://json.org/ (http://json.org/). Several editors have built-in support for JSON syntax highlighting that aids manual creation of such files. An online editor for JSON with built-in validation is available at: http://jsoneditoronline.org (http://jsoneditoronline.org). JSON files MUST be in UTF-8 encoding.

Example:

```
"RepetitionTime": 3,
  "Instruction": "Lie still and keep your eyes open"
}
```

Participant names and other labels

BIDS uses custom user-defined labels in several situations (naming of participants, sessions, acquisition schemes, etc.) Labels are strings and MUST only consist of letters (lower or upper case) and/or numbers. If numbers are used we RECOMMEND zero padding (e.g., 01 instead of 1 if you have more than nine subjects) to make alphabetical sorting more intuitive. Please note that the sub- prefix is not part of the subject label, but must be included in file names (similarly to other key names). In contrast to other labels, run and echo labels MUST be integers. Those labels MAY include zero padding, but this is NOT RECOMMENDED to maintain their uniqueness.

Units

All units SHOULD be specified as per International System of Units (abbreviated as SI, from the French Système international (d'unités)) and can be SI units or SI derived units. In case there are valid reasons to deviate from SI units or SI derived units, the units MUST be specified in the sidecar JSON file. In case data is expressed in SI units or SI derived units, the units MAY be specified in the sidecar JSON file. In case prefixes are added to SI or non-SI units (e.g. mm), the prefixed units MUST be specified in the JSON file (see Appendix V (99-appendices/05-units.pdf): Units). In particular:

- Elapsed time SHOULD be expressed in seconds. Please note that some DICOM parameters have been traditionally expressed in milliseconds. Those need to be converted to seconds.
- · Frequency SHOULD be expressed in Hertz.

Describing dates and timestamps:

- Date time information MUST be expressed in the following format YYYY-MM-DDThh:mm:ss (one of the ISO8601 (https://en.wikipedia.org/wiki/ISO_8601) date-time formats). For example: 2009-06-15T13:45:
- Time stamp information MUST be expressed in the following format: 13:45:30
- Dates can be shifted by a random number of days for privacy protection reasons. To distinguish real dates from shifted dates always use year 1900 or earlier when including shifted years. For longitudinal studies please remember to shift dates within one subject by the same number of days to maintain the interval information. Example: 1867–06–15T13:45:30
- Age SHOULD be given as the number of years since birth at the time of scanning (or first scan in case of
 multi session datasets). Using higher accuracy (weeks) should in general be avoided due to privacy
 protection, unless when appropriate given the study goals, e.g., when scanning babies.

Directory structure

Single session example

This is an example of the folder and file structure. Because there is only one session, the session level is not required by the format. For details on individual files see descriptions in the next section:

```
sub-control01/
   anat/
        sub-control01_T1w.nii.gz
        sub-control01_T1w.json
        sub-control01 T2w.nii.gz
        sub-control01_T2w.json
    func/
        sub-control01 task-nback bold.nii.gz
        sub-control01_task-nback_bold.json
        sub-control01_task-nback_events.tsv
        sub-control01_task-nback_physio.tsv.gz
        sub-control01_task-nback_physio.json
        sub-control01_task-nback_sbref.nii.gz
   dwi/
        sub-control01_dwi.nii.gz
        sub-control01_dwi.bval
        sub-control01_dwi.bvec
   fmap/
        sub-control01 phasediff.nii.gz
        sub-control01_phasediff.json
        sub-control01_magnitude1.nii.gz
        sub-control01 scans.tsv
   code/
        deface.py
   derivatives/
   README
   participants.tsv
   dataset description.json
   CHANGES
```

Additional files and folders containing raw data may be added as needed for special cases. They should be named using all lowercase with a name that reflects the nature of the scan (e.g., calibration). Naming of files within the directory should follow the same scheme as above (e.g., sub-control01_calibration_Xcalibration.nii.gz)

Documentation built with MkDocs (https://www.mkdocs.org/).

Modality-agnostic files

Dataset description

Template: dataset_description.json README CHANGES

dataset_description.json

The file dataset_description.json is a JSON file describing the dataset. Every dataset MUST include this file with the following fields:

Field name	Definition
Name	REQUIRED. Name of the dataset.
BIDSVersion	REQUIRED. The version of the BIDS standard that was used.
	RECOMMENDED. What license is this dataset distributed under? The use of license name
License	abbreviations is suggested for specifying a license. A list of common licenses with suggested abbreviations can be found in Appendix II.
Authors	OPTIONAL. List of individuals who contributed to the creation/curation of the dataset.
Acknowledgements	OPTIONAL. Text acknowledging contributions of individuals or institutions beyond those listed in Authors or Funding.
	OPTIONAL. Instructions how researchers using this dataset should acknowledge the
HowToAcknowledge	e original authors. This field can also be used to define a publication that should be cited in publications that use the dataset.
Funding	OPTIONAL. List of sources of funding (grant numbers)
ReferencesAndLinks	OPTIONAL. List of references to publication that contain information on the dataset, or links.
DatasetDOI Example:	OPTIONAL. The Document Object Identifier of the dataset (not the corresponding paper).

```
"Name": "The mother of all experiments",
  "BIDSVersion": "1.0.1",
  "License": "CCO",
  "Authors": [
    "Paul Broca",
    "Carl Wernicke"
  ],
  "Acknowledgements": "Special thanks to Korbinian Brodmann for help in formatting this dataset in BID
  "HowToAcknowledge": "Please cite this paper: https://www.ncbi.nlm.nih.gov/pubmed/001012092119281",
  "Funding": [
    "National Institute of Neuroscience Grant F378236MFH1",
    "National Institute of Neuroscience Grant 5RMZ0023106"
  ],
  "ReferencesAndLinks": [
    "https://www.ncbi.nlm.nih.gov/pubmed/001012092119281",
    "Alzheimer A., & Kraepelin, E. (2015). Neural correlates of presenile dementia in humans. Journal
 ],
  "DatasetDOI": "10.0.2.3/dfjj.10"
}
```

README

In addition a free form text file (README) describing the dataset in more details SHOULD be provided.

CHANGES

Version history of the dataset (describing changes, updates and corrections) MAY be provided in the form of a CHANGES text file. This file MUST follow the CPAN Changelog convention: http://search.cpan.org/~haarg/CPAN-Changes-0.400002/lib/CPAN/Changes/Spec.pod (https://metacpan.org/pod/release/HAARG/CPAN-Changes-0.400002/lib/CPAN/Changes/Spec.pod). README and CHANGES files MUST be either in ASCII or UTF-8 encoding.

Example:

```
1.0.1 2015-08-27
  - Fixed slice timing information.

1.0.0 2015-08-17
  - Initial release.
```

Participants file

Template:

```
participants.tsv
participants.json
phenotype/<measurement_tool_name>.tsv
phenotype/<measurement_tool_name>.json
```

Optional: Yes

The purpose of this file is to describe properties of participants such as age, handedness, sex, etc. In case of single session studies this file has one compulsory column participant_id that consists of sub-<label>, followed by a list of optional columns describing participants. Each participant needs to be described by one and only one row.

```
participants.tsv example:
```

```
participant_id age sex group
sub-control01 34 M control
sub-control02 12 F control
sub-patient01 33 F patient
```

If the dataset includes multiple sets of participant level measurements (for example responses from multiple questionnaires) they can be split into individual files separate from participants.tsv. Those measurements should be kept in phenotype/ folder and end with the tsv extension. They can include arbitrary set of columns, but one of them has to be participant_id with matching sub-<label>. As with all other tabular data, those additional phenotypic information files can be accompanied by a JSON file describing the columns in detail (see here (02-common-principles.pdf)). In addition to the column description, a section describing the measurement tool (as a whole) can be added under the name MeasurementToolMetadata. This section consists of two keys: Description - a free text description of the tool, and TermURL a link to an entity in an ontology corresponding to this tool. For example (content of phenotype/acds_adult.json):

```
{
  "MeasurementToolMetadata": {
    "Description": "Adult ADHD Clinical Diagnostic Scale V1.2",
    "TermURL": "http://www.cognitiveatlas.org/task/id/trm_5586ff878155d"
  },
  "adhd b": {
    "Description": "B. CHILDHOOD ONSET OF ADHD (PRIOR TO AGE 7)",
    "Levels": {
      "1": "YES",
      "2": "NO"
    }
  },
  "adhd_c_dx": {
    "Description": "As child met A, B, C, D, E and F diagnostic criteria",
    "Levels": {
      "1": "YES",
      "2": "NO"
    }
  }
}
```

Please note that in this example MeasurementToolMetadata includes information about the questionnaire and adhd_b and adhd_c_dx correspond to individual columns.

In addition to the keys available to describe columns in all tabular files (LongName, Description, Levels, Units, and TermURL) the participants.json file as well as phenotypic files can also include column descriptions with Derivative field that, when set to true, indicates that values in the corresponding column is a transformation of values from other columns (for example a summary score based on a subset of items in a questionnaire).

Scans file

Template:

```
sub-<label>/[ses-<label>/]
sub-<label>[_ses-<label>]_scans.tsv
```

Optional: Yes

The purpose of this file is to describe timing and other properties of each imaging acquisition sequence (each run _nii[.gz] file) within one session. Each _nii[.gz] file should be described by at most one row. Relative paths to files should be used under a compulsory filename header. If acquisition time is included it should be under acq_time header. Datetime should be expressed in the following format 2009-06-15T13:45:30 (year, month, day, hour (24h), minute, second; this is equivalent to the RFC3339 "date-time" format, time zone is always assumed as local time). For anonymization purposes all dates within one subject should be shifted by a randomly chosen (but common across all runs etc.) number of days. This way relative timing would be preserved, but chances of identifying a person based on the date and time of their scan would be decreased. Dates that are shifted for anonymization purposes should be set to a year 1900 or earlier to clearly distinguish them from unmodified data. Shifting dates is recommended, but not required.

Additional fields can include external behavioural measures relevant to the scan. For example vigilance questionnaire score administered after a resting state scan.

Example:


```
filename acq_time
func/sub-control01_task-nback_bold.nii.gz 1877-06-15T13:45:30
func/sub-control01_task-motor_bold.nii.gz 1877-06-15T13:55:33
```

Code

Template: code/*

Source code of scripts that were used to prepare the dataset (for example if it was anonymized or defaced) MAY be stored here.¹ Extra care should be taken to avoid including original IDs or any identifiable information with the source code. There are no limitations or recommendations on the language and/or code organization of these scripts at the moment.

¹Storing actual source files with the data is preferred over links to external source repositories to maximize long term preservation (which would suffer if an external repository would not be available anymore).



Documentation built with MkDocs (https://www.mkdocs.org/).

Magnetic Resonance Imaging data

Common metadata fields

MR Data described in sections 8.3.x share the following RECOMMENDED metadata fields (stored in sidecar JSON files). MRI acquisition parameters are divided into several categories based on "A checklist for fMRI acquisition methods reporting in the literature" (https://thewinnower.com/papers/977-a-checklist-for-fmri-acquisition-methods-reporting-in-the-literature) by Ben Inglis:

Scanner Hardware

Field name	Definition			
Manufacturer	RECOMMENDED. Manufacturer of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 0070 Manufacturer			
ManufacturersModelName	RECOMMENDED. Manufacturer's model name of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 1090 Manufacturers Model Name			
DeviceSerialNumber	RECOMMENDED. The serial number of the equipment that produced the composite instances. Corresponds to DICOM Tag 0018, 1000 DeviceSe Number. A pseudonym can also be used to prevent the equipment from being identifiable, so long as each pseudonym is unique within the datas			
StationName	RECOMMENDED. Institution defined name of the machine that produced the composite instances. Corresponds to DICOM Tag 0008, 1010 Station Name			
SoftwareVersions	RECOMMENDED. Manufacturer's designation of software version of the equipment that produced the composite instances. Corresponds to DICOM Tag 0018, 1020 Software Versions			
HardcopyDeviceSoftwareVersion	(Deprecated) Manufacturer's designation of the software of the device that created this Hardcopy Image (the printer). Corresponds to DICOM Tag 0018, 101A Hardcopy Device Software Version			
MagneticFieldStrength	RECOMMENDED. Nominal field strength of MR magnet in Tesla. Corresponds to DICOM Tag 0018,0087 Magnetic Field Strength			
ReceiveCoilName	RECOMMENDED. Information describing the receiver coil. Corresponds to DICOM Tag 0018, 1250 Receive Coil Name, although not all vendors populate that DICOM Tag, in which case this field can be derived from an appropriate private DICOM field			

Field name	Definition
	RECOMMENDED. Information describing the active/selected elements of the receiver coil. This doesn't correspond to a tag in the DICOM ontology. The vendor-defined terminology for active coil elements can go in this field. As an example, for Siemens, coil channels are typically not activated/selected
	individually, but rather in pre-defined selectable "groups" of individual
	channels, and the list of the "groups" of elements that are active/selected in
	any given scan populates the Coil String entry in Siemen's private
ReceiveCoilActiveElements	DICOM fields (e.g., HEA; HEP for the Siemens standard 32 ch coil when both the anterior and posterior groups are activated). This is a flexible field that can be used as most appropriate for a given vendor and coil to define the "active" coil elements. Since individual scans can sometimes not have the intended coil elements selected, it is preferable for this field to be populated directly from the DICOM for each individual scan, so that it can be used as a mechanism for checking that a given scan was collected with the intended coil elements selected
GradientSetType	RECOMMENDED. It should be possible to infer the gradient coil from the scanner model. If not, e.g. because of a custom upgrade or use of a gradient insert set, then the specifications of the actual gradient coil should be reported independently
MRTransmitCoilSequence	RECOMMENDED. This is a relevant field if a non-standard transmit coil is used. Corresponds to DICOM Tag 0018, 9049 MR Transmit Coil Sequence
MatrixCoilMode	RECOMMENDED. (If used) A method for reducing the number of independent channels by combining in analog the signals from multiple coil elements. There are typically different default modes when using un-accelerated or accelerated (e.g. GRAPPA, SENSE) imaging
CoilCombinationMethod	RECOMMENDED. Almost all fMRI studies using phased-array coils use root- sum-of-squares (rSOS) combination, but other methods exist. The image reconstruction is changed by the coil combination method (as for the matrix coil mode above), so anything non-standard should be reported

Sequence Specifics

Field name	Definition
PulseSequenceType	RECOMMENDED. A general description of the pulse sequence used for the scan
r discocquence type	(i.e. MPRAGE, Gradient Echo EPI, Spin Echo EPI, Multiband gradient echo EPI).
ScanningSequence	RECOMMENDED. Description of the type of data acquired. Corresponds to
ScariffingSequence	DICOM Tag 0018, 0020 Scanning Sequence.
SequenceVariant	RECOMMENDED. Variant of the ScanningSequence. Corresponds to DICOM Tag
Sequencevariant	0018,0021 Sequence Variant.
ScanOptions	RECOMMENDED. Parameters of ScanningSequence. Corresponds to DICOM
Scarioptions	Tag 0018, 0022 Scan Options.
SaguanaoNama	RECOMMENDED. Manufacturer's designation of the sequence name.
SequenceName	Corresponds to DICOM Tag 0018, 0024 Sequence Name.

Field name D	Definition
PulseSequenceDetails s	RECOMMENDED. Information beyond pulse sequence type that identifies the pecific pulse sequence used (i.e. "Standard Siemens Sequence distributed with the VB17 software," "Siemens WIP ### version #.##," or "Sequence written by X sing a version compiled on MM/DD/YYYY").
NonlinearGradientCorrection	RECOMMENDED. Boolean stating if the image saved has been corrected for radient nonlinearities by the scanner sequence.
In-Plane Spatial Encoding	g
Field name	Definition
NumberShots	RECOMMENDED. The number of RF excitations need to reconstruct a slice or volume. Please mind that this is not the same as Echo Train Length which denotes the number of lines of k-space collected after an excitation.
ParallelReductionFactorInPlan	RECOMMENDED. The parallel imaging (e.g, GRAPPA) factor. Use the denominator of the fraction of k-space encoded for each slice. For example, 2 means half of k-space is encoded. Corresponds to DICOM Tag 0018, 9069 [Parallel Reduction Factor In-plane].
ParallelAcquisitionTechnique	RECOMMENDED. The type of parallel imaging used (e.g. GRAPPA, SENSE). Corresponds to DICOM Tag 0018, 9078 Parallel Acquisition Technique.
PartialFourier	RECOMMENDED. The fraction of partial Fourier information collected. Corresponds to DICOM Tag 0018, 9081 Partial Fourier.
PartialFourierDirection	RECOMMENDED. The direction where only partial Fourier information was collected. Corresponds to DICOM Tag 0018, 9036 Partial Fourier Direction.
PhaseEncodingDirection	RECOMMENDED. Possible values: i, j, k, i-, j-, k The letters i, j, k correspond to the first, second and third axis of the data in the NIFTI file. The polarity of the phase encoding is assumed to go from zero index to maximum index unless – sign is present (then the order is reversed - starting from the highest index instead of zero). PhaseEncodingDirection is defined as the direction along which phase is was modulated which may result in visible distortions. Note that this is not the same as the DICOM term InPlan ePhaseEncodingDirection which can have ROW or COL values. This parameter is REQUIRED if corresponding fieldmap data is present or when using multiple runs with different phase encoding directions (which can be later used for field inhomogeneity correction).
EffectiveEchoSpacing	RECOMMENDED. The "effective" sampling interval, specified in seconds, between lines in the phase-encoding direction, defined based on the size of the reconstructed image in the phase direction. It is frequently, but incorrectly, referred to as "dwell time" (see <code>DwellTime</code> parameter below for actual dwell time). It is required for unwarping distortions using field maps. Note that beyond just in-plane acceleration, a variety of other manipulations to the phase encoding need to be accounted for properly, including partial fourier, phase oversampling, phase resolution, phase field-of-view and interpolation. This parameter is REQUIRED if corresponding fieldmap data is present.

Field name Definition RECOMMENDED. This is actually the "effective" total readout time, defined as the readout duration, specified in seconds, that would have generated data with the given level of distortion. It is NOT the actual, physical duration of the readout train. If EffectiveEchoSpacing has been properly computed, it is **TotalReadoutTime** just EffectiveEchoSpacing * (ReconMatrixPE - 1).3. This parameter is REQUIRED if corresponding "field/distortion" maps acquired with opposing phase encoding directions are present (see 8.9.4). ²Conveniently, for Siemens' data, this value is easily obtained as 1/[BWPPPE * ReconMatrixPE], where BWPPPE is the "BandwidthPerPixelPhaseEncode in DICOM tag (0019,1028) and ReconMatrixPE is the size of the actual reconstructed data in the phase direction (which is NOT reflected in a single DICOM tag for all possible aforementioned scan manipulations). See here (https://lcni.uoregon.edu/kb-articles/kb-0003) and here (https://github.com/neurolabusc/dcm_ga/tree/master/ln/TotalReadoutTime) ³We use the "FSL definition", i.e, the time between the center of the first "effective" echo and the center of the last "effective" echo. Timing Parameters Field name **Definition** RECOMMENDED. The echo time (TE) for the acquisition, specified in seconds. This parameter is REQUIRED if corresponding fieldmap data is present or the data comes **EchoTime** from a multi echo sequence. Corresponds to DICOM Tag 0018, 0081 Echo Time (please note that the DICOM term is in milliseconds not seconds). RECOMMENDED. The inversion time (TI) for the acquisition, specified in seconds. Inversion time is the time after the middle of inverting RF pulse to middle of excitation InversionTime pulse to detect the amount of longitudinal magnetization. Corresponds to DICOM Tag 0018, 0082 Inversion Time (please note that the DICOM term is in milliseconds not seconds). RECOMMENDED. The time at which each slice was acquired within each volume (frame) of the acquisition. Slice timing is not slice order -- rather, it is a list of times (in JSON format) containing the time (in seconds) of each slice acquisition in relation to the beginning of volume acquisition. The list goes through the slices along the slice axis in the slice encoding dimension (see below). Note that to ensure the proper interpretation of the SliceTiming field, it is important to check if the OPTIONAL SliceTiming SliceEncodingDirection exists. In particular, if SliceEncodingDirection is negative, the entries in SliceTiming are defined in reverse order with respect to the slice axis (i.e., the final entry in the SliceTiming list is the time of acquisition of slice 0). This parameter is REQUIRED for sparse sequences that do not have the DelayTim e | field set. In addition without this parameter slice time correction will not be possible. RECOMMENDED. Possible values: (i), (j), (k), (i-), (j-), (k-) (the axis of the NIfTI data along which slices were acquired, and the direction in which SliceTiming is defined with respect to). i, j, k identifiers correspond to the first, second and third axis of the data in the NIfTI file. A [-] sign indicates that the contents of SliceEncodingDirection SliceTiming are defined in reverse order - that is, the first entry corresponds to the slice with the largest index, and the final entry corresponds to slice index zero. When present, the axis defined by SliceEncodingDirection needs to be consistent with the 'slice_dim' field in the NIfTI header. When absent, the entries in SliceTiming must be in the order of increasing slice index as defined by the NIfTI header.

Field name	Definition
DwellTime	RECOMMENDED. Actual dwell time (in seconds) of the receiver per point in the
	readout direction, including any oversampling. For Siemens, this corresponds to
	DICOM field (0019,1018) (in ns). This value is necessary for the optional readout
	distortion correction of anatomicals in the HCP Pipelines. It also usefully provides a
	handle on the readout bandwidth, which isn't captured in the other metadata tags. Not
	to be confused with EffectiveEchoSpacing, and the frequent mislabeling of echo
	spacing (which is spacing in the phase encoding direction) as "dwell time" (which is
	spacing in the readout direction).

RF & Contrast

Field name	Definition
FlipAngle	RECOMMENDED. Flip angle for the acquisition, specified in degrees.
TilpAtigle	Corresponds to: DICOM Tag 0018, 1314 Flip Angle.

MultibandAccelerationFactor RECOMMENDED. The multiband factor, for multiband acquisitions.

OPTIONAL. Boolean (true or false) value specifying whether increasing voxel intensity (within sample voxels) denotes a decreased value with respect to the contrast suffix. This is commonly the case when Cerebral Blood Volume is estimated via usage of a contrast agent in conjunction with a T2* weighted acquisition protocol.

Slice Acceleration

NegativeContrast

Field name Definition

MultibandAccelerationFactor RECOMMENDED. The multiband factor, for multiband acquisitions.

Anatomical landmarks

Useful for multimodal co-registration with MEG, (S)EEG, TMS, etc.

Field name	Definition				
	RECOMMENDED. Key:value pairs of any number of additional anatomical				
	landmarks and their coordinates in voxel units (where first voxel has index				
AnatomicalLandmarkCoordinates	0,0,0) relative to the associated anatomical MRI, (e.g. {"AC":				
AnatomicalcandinarkCoordinates	[127,119,149], "PC": [128,93,141], "IH": [131,114,206]}, or				
	{"NAS": [127,213,139], "LPA": [52,113,96], "RPA":				
	[202,113,91]}).				

Institution information

Field name	Definition
InstitutionName	RECOMMENDED. The name of the institution in charge of the equipment that produced the composite instances. Corresponds to DICOM Tag 0008, 0080
	InstitutionName .
	RECOMMENDED. The address of the institution in charge of the equipment that
InstitutionAddress	produced the composite instances. Corresponds to DICOM Tag 0008, 0081
	InstitutionAddress.
	RECOMMENDED. The department in the institution in charge of the equipment
InstitutionalDepartmentName	e that produced the composite instances. Corresponds to DICOM Tag 0008, 1040
	Institutional Department Name .

When adding additional metadata please use the camelcase version of DICOM ontology terms (https://scicrunch.org/scicrunch/interlex/dashboard) whenever possible.

Anatomy imaging data

Template:

```
sub-<label>/[ses-<label>/]
anat/
sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>][_rec-<label>][_run-<index>]_<modality_lab
sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>][_rec-<label>][_run-<index>][_mod-<label>]
```

Anatomical (structural) data acquired for that participant. Currently supported modalities include:

Name	modality_label Description					
T1 weighted	T1w					
T2 weighted	T2w					
T1 Rho map	T1rho	Quantitative T1rho brain imaging http://www.ncbi.nlm.nih.gov/pubmed/24474423 (http:// rho www.ncbi.nlm.nih.gov/pubmed/24474423) http://www.ncbi.nlm.nih.gov/pmc/articles/PMC4346383/ (http:// www.ncbi.nlm.nih.gov/pubmed/24474423)				
T1 map	T1map	quantitative T1 map				
T2 map	T2map	quantitative T2 map				
T2*	T2star	High resolution T2* image				
FLAIR	FLAIR					
FLASH	FLASH					
Proton density	PD					
Proton density map	PDmap					
Combined PD/ T2	PDT2					
Inplane T1	inplaneT1	T1-weighted anatomical image matched to functional acquisition				
Inplane T2	inplaneT2	T2-weighted anatomical image matched to functional acquisition				
Angiography	angio					

If several scans of the same modality are acquired they MUST be indexed with a key-value pair: __run-1 , __run-2 , __run-3 etc. (only integers are allowed as run labels). When there is only one scan of a given type the run key MAY be omitted. Please note that diffusion imaging data is stored elsewhere (see below).

The OPTIONAL <code>acq-<label></code> key/value pair corresponds to a custom label the user MAY use to distinguish a different set of parameters used for acquiring the same modality. For example this should be used when a study includes two T1w images - one full brain low resolution and and one restricted field of view but high resolution. In such case two files could have the following names: <code>sub-01_acq-highres_T1w.nii.gz</code> and <code>sub-01_acq-lowres_T1w.nii.gz</code>, however the user is free to choose any other label than <code>highres</code> and <code>lowres</code> as long as they are consistent across subjects and sessions. In case different sequences are used to record the same modality (e.g. RARE and FLASH for T1w) this field can also be used to make that distinction. At what level of detail to make the distinction (e.g. just between RARE and FLASH, or between RARE, FLASH, and FLASHsubsampled) remains at the discretion of the researcher.

Similarly the OPTIONAL ce-<label> key/value can be used to distinguish sequences using different contrast enhanced images. The label is the name of the contrast agent. The key ContrastBolusIngredient MAY be also be added in the JSON file, with the same label.

Similarly the OPTIONAL rec-<label> key/value can be used to distinguish different reconstruction algorithms (for example ones using motion correction).

If the structural images included in the dataset were defaced (to protect identity of participants) one CAN provide the binary mask that was used to remove facial features in the form of __defacemask files. In such cases the OPTIONAL mod-<label> key/value pair corresponds to modality label for eg: T1w, inplaneT1, referenced by a defacemask image. E.g., sub-01_mod-T1w_defacemask.nii.gz.

Some meta information about the acquisition MAY be provided in an additional JSON file. See Common metadata fields for a list of terms and their definitions. There are also some OPTIONAL JSON fields specific to anatomical scans:

Field name Definition

OPTIONAL. Active ingredient of agent. Values MUST be one of: IODINE,

ContrastBolusIngredient GADOLINIUM, CARBON DIOXIDE, BARIUM, XENON Corresponds to DICOM Tag 0018,1048.

Task (including resting state) imaging data

Currently supported image contrasts include:

Name contrast_label Description

BOLD bold Blood-Oxygen-Level Dependent contrast (specialized T2* weighting)

CBV cbv Cerebral Blood Volume contrast (specialized T2* weighting or difference between T1

weighted images)

Template:

```
sub-<label>/[ses-<label>/]
func/
sub-<label>[_ses-<label>]_task-<label>[_acq-<label>] [_ce-<label>] [_dir-<label>] [_rec-<label>] [
sub-<label>[_ses-<label>] [_acq-<label>] [_ce-<label>] [_dir-<label>] [_rec-<label>] [
```

Imaging data acquired during functional imaging (i.e. imaging which supports rapid temporal repetition). This includes but is not limited to task based fMRI as well as resting state fMRI (i.e. rest is treated as another task). For task based fMRI a corresponding task events file (see below) MUST be provided (please note that this file is not necessary for resting state scans). For multiband acquisitions, one MAY also save the single-band reference image as type <code>sbref</code> (e.g. <code>sub-control01_task-nback_sbref.nii.gz</code>).

Each task has a unique label MUST only include of letters and/or numbers (other characters including spaces and underscores are not allowed). Those labels MUST be consistent across subjects and sessions.

If more than one run of the same task has been acquired a key/value pair: __run-1 , __run-2 , __run-3 etc. MUST be used. If only one run was acquired the _run-<index> can be omitted. In the context of functional imaging a run is defined as the same task, but in some cases it can mean different set of stimuli (for example randomized order) and participant responses.

The OPTIONAL <code>acq-<label></code> key/value pair corresponds to a custom label one may use to distinguish different set of parameters used for acquiring the same task. For example this should be used when a study includes two resting state images - one single band and one multiband. In such case two files could have the following names: <code>sub-01_task-rest_acq-singleband_bold.nii.gz</code> and <code>sub-01_task-rest_acq-multiband_bold.nii.gz</code>, however the user is MAY choose any other label than <code>singleband</code> and <code>multiband</code> as long as they are consistent across subjects and sessions and consist only of the legal label characters.

Similarly the OPTIONAL ce-<label> key/value can be used to distinguish sequences using different contrast enhanced images. The label is the name of the contrast agent. The key ContrastBolusIngredient MAY be also be added in the JSON file, with the same label.

Similarly the OPTIONAL rec-<label> key/value can be used to distinguish different reconstruction algorithms (for example ones using motion correction).

Similarly the OPTIONAL dir-<label> and rec-<label> key/values can be used to distinguish different phase-encoding directions and reconstruction algorithms (for example ones using motion correction). See fmap Case 4 (01-magnetic-resonance-imaging-data.pdf) for more information on dir field specification.

Multi echo data MUST be split into one file per echo. Each file shares the same name with the exception of the _echo-<index> key/value. For example:

```
sub-01/
func/
sub-01_task-cuedSGT_run-1_echo-1_bold.nii.gz
sub-01_task-cuedSGT_run-1_echo-1_bold.json
sub-01_task-cuedSGT_run-1_echo-2_bold.nii.gz
sub-01_task-cuedSGT_run-1_echo-2_bold.json
sub-01_task-cuedSGT_run-1_echo-3_bold.nii.gz
sub-01_task-cuedSGT_run-1_echo-3_bold.json
```

Please note that the <index> denotes the number/index (in a form of an integer) of the echo not the echo time value which needs to be stored in the field EchoTime of the separate JSON file.

Some meta information about the acquisition MUST be provided in an additional JSON file.

Required fields

Field name Definition

REQUIRED. The time in seconds between the beginning of an acquisition of one volume and the beginning of acquisition of the volume following it (TR). Please note that this definition includes time between scans (when no data has been acquired) in case of sparse acquisition schemes. This value needs to be consistent with the <code>pixdim[4]</code> field (after accounting for units stored in <code>xyzt_units</code> field) in the NIfTI header. This field is mutually exclusive with VolumeTiming and is derived from DICOM Tag 0018, 0080 and converted to seconds.

REQUIRED. The time at which each volume was acquired during the acquisition. It is described using a list of times (in JSON format) referring to the onset of each volume in the BOLD series. The list must have the same length as the BOLD series, and the values must be non-negative

VolumeTiming

and monotonically increasing. This field is mutually exclusive with RepetitionTime and DelayTime. If defined, this requires acquisition time (TA) be defined via either SliceTiming or AcquisitionDuration be defined.

Field name	Definition
TaskName	REQUIRED. Name of the task. No two tasks should have the same name. Task label (task-) included in the file name is derived from this field by removing all non alphanumeric ([a-zA-Z0-9]) characters. For example task name faces n-back will corresponds to task label
iaskivairie	facesnback . A RECOMMENDED convention is to name resting state task using labels
	beginning with rest.
For the fields	described above and in the following section, the term "Volume" refers to a reconstruction of the

For the fields described above and in the following section, the term "Volume" refers to a reconstruction of the object being imaged (e.g., brain or part of a brain). In case of multiple channels in a coil, the term "Volume" refers to a combined image rather than an image from each coil.

Other RECOMMENDED metadata

Timing Parameters

Field name **Definition** RECOMMENDED. Number of volumes ("dummy scans") discarded by the scanner (as opposed to those discarded by the user post hoc) before saving the imaging file. For example, a sequence that automatically discards the first 4 volumes before saving would have NumberOfVolumesDiscardedByScanner this field as 4. A sequence that doesn't discard dummy scans would have this set to 0. Please note that the onsets recorded in the _event.tsv file should always refer to the beginning of the acquisition of the first volume in the corresponding imaging file - independent of the value of NumberOfVolumesDiscardedByScanner | field. RECOMMENDED. Number of volumes ("dummy scans") discarded by the user before including the file in the dataset. If possible, including all of the volumes is strongly recommended. Please note that the NumberOfVolumesDiscardedByUser onsets recorded in the _event.tsv file should always refer to the beginning of the acquisition of the first volume in the corresponding imaging file - independent of the value of NumberOfVolumesDiscardedByUser field. RECOMMENDED. User specified time (in seconds) to delay the acquisition of data for the following volume. If the field is not present it is assumed to be set to zero. Corresponds to Siemens CSA header DelayTime field | LDelayTimeInTR |. This field is REQUIRED for sparse sequences using the RepetitionTime | field that do not have the | SliceTiming field set to allowed for accurate calculation of "acquisition time". This field is mutually exclusive with VolumeTiming. RECOMMENDED. Duration (in seconds) of volume acquisition. Corresponds to DICOM Tag 0018,9073 Acquisition Duration. This field is REQUIRED for sequences that are described with the Vol AcquisitionDuration umeTiming field and that not have the SliceTiming field set to allowed for accurate calculation of "acquisition time". This field is mutually exclusive with RepetitionTime. RECOMMENDED. Duration (in seconds) from trigger delivery to scan onset. This delay is commonly caused by adjustments and loading DelayAfterTrigger times. This specification is entirely independent of NumberOfVolumesDiscardedByScanner or NumberOfVolumesDisca rdedByUser, as the delay precedes the acquisition.

The following table recapitulates the different ways that specific fields have to be populated for functional sequences. Note that all those options can used for non sparse sequences but that only options B, D and E are valid for sparse sequences.

RepetitionTime SliceTiming AcquisitionDuration DelayTime VolumeTiming

option A [X]		[]		[]
option B[]	[X]		[]	[X]
option C[]		[X]	[]	[X]
option D[X]	[X]	[]		[]
option E [X]		[]	[X]	[]

Legend - [X] --> has to be filled - [] --> has to be left empty - empty cell --> can be specified but not required

fMRI task information

Field name Definition

RECOMMENDED. Text of the instructions given to participants before the scan. This is especially important in context of resting state fMRI and distinguishing between eyes open and eyes closed paradigms.

TaskDescription RECOMMENDED. Longer description of the task.

CogAtlasID RECOMMENDED. URL of the corresponding Cognitive Atlas (http://www.cognitiveatlas.org/)
Task term.

CogPOID RECOMMENDED. URL of the corresponding CogPO (http://www.cogpo.org/) term.

See Common metadata fields for a list of additional terms and their definitions.

Example:

```
sub-control01/
func/
sub-control01_task-nback_bold.json
```

```
{
  "TaskName": "N Back",
  "RepetitionTime": 0.8,
  "EchoTime": 0.03,
  "FlipAngle": 78,
  "SliceTiming": [0.0, 0.2, 0.4, 0.6, 0.0, 0.2, 0.4, 0.6, 0.0, 0.2, 0.4, 0.6, 0.0, 0.2, 0.4, 0.6],
  "MultibandAccelerationFactor": 4,
  "ParallelReductionFactorInPlane": 2,
  "PhaseEncodingDirection": "j",
  "InstitutionName": "Stanford University",
  "InstitutionAddress": "450 Serra Mall, Stanford, CA 94305-2004, USA",
  "DeviceSerialNumber": "11035"
}
```

If this information is the same for all participants, sessions and runs it can be provided in task—(label>_bold.json) (in the root directory of the dataset). However, if the information differs between subjects/runs it can be specified in the sub-<label>/func/sub-<label>_task-<label>[_acq-<label>] [_runindex>]_bold.json file. If both files are specified fields from the file corresponding to a particular participant, task and run takes precedence.

Diffusion imaging data

Template:

```
sub-<label>/[ses-<label>/]
dwi/
sub-<label>[_ses-<label>] [_acq-<label>] [_dir-<label>] [_run-<index>]_dwi.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_dir-<label>] [_run-<index>]_dwi.bval
sub-<label>[_ses-<label>] [_acq-<label>] [_dir-<label>] [_run-<index>]_dwi.bvec
sub-<label>[_ses-<label>] [_acq-<label>] [_dir-<label>] [_run-<index>]_dwi.json
sub-<label>[_ses-<label>] [_acq-<label>] [_dir-<label>] [_run-<index>]_sbref.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_dir-<label>] [_run-<index>]_sbref.json
```

Diffusion-weighted imaging data acquired for that participant. The OPTIONAL acq-<label> key/value pair corresponds to a custom label the user may use to distinguish different set of parameters. For example this should be used when a study includes two diffusion images - one single band and one multiband. In such case two files could have the following names: sub-01_acq-singleband_dwi.nii.gz and sub-01_acq-multiband_dwi.nii.gz, however the user is free to choose any other label than singleband and multiband as long as they are consistent across subjects and sessions. For multiband acquisitions, one can also save the single-band reference image as type sbref (e.g. dwi/sub-control01_sbref.nii[.gz]) The bvec and bval files are in the FSL format⁴: The bvec files contain 3 rows with n space-delimited floating-point numbers (corresponding to the n volumes in the relevant NIfTI file). The first row contains the x elements, the second row contains the y elements and third row contains the z elements of a unit vector in the direction of the applied diffusion gradient, where the i-th elements in each row correspond together to the i-th volume with [0,0,0] for non-diffusion-weighted volumes. Inherent to the FSL format for bvec specification is the fact that the coordinate system of the bvecs is with respect to the participant (i.e., defined by the axes of the corresponding dwi.nii file) and not the magnet's coordinate system, which means that any rotations applied to dwi.nii also need to be applied to the corresponding bvec file.

4http://fsl.fmrib.ox.ac.uk/fsl/fsl4.0/fdt/fdt_dtifit.html (http://fsl.fmrib.ox.ac.uk/fsl/fsl4.0/fdt/fdt_dtifit.html)

bvec example:

```
0 0 0.021828 -0.015425 -0.70918 -0.2465
0 0 0.80242 0.22098 -0.00063106 0.1043
0 0 -0.59636 0.97516 -0.70503 -0.96351
```

The bval file contains the b-values (in s/mm²) corresponding to the volumes in the relevant NIfTI file), with 0 designating non-diffusion-weighted volumes, space-delimited.

bval example:

```
0 0 2000 2000 1000 1000
```

• bval and • bvec files can be saved on any level of the directory structure and thus define those values for all sessions and/or subjects in one place (see Inheritance principle).

See Common metadata fields for a list of additional terms that can be included in the corresponding JSON file. JSON example:

```
{
   "PhaseEncodingDirection": "j-",
   "TotalReadoutTime": 0.095
}
```

Fieldmap data

Data acquired to correct for B0 inhomogeneities can come in different forms. The current version of this standard considers four different scenarios. Please note that in all cases fieldmap data can be linked to a specific scan(s) it was acquired for by filling the IntendedFor field in the corresponding JSON file. For example:

```
{
    "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
}
```

The IntendedFor field may contain one or more filenames with paths relative to the subject subfolder. The path needs to use forward slashes instead of backward slashes. Here's an example with multiple target scans:

The IntendedFor field is OPTIONAL and in case the fieldmaps do not correspond to any particular scans it does not have to be filled.

Multiple fieldmaps can be stored. In such case the _run-1, _run-2 should be used. The OPTIONAL acq-<label> key/value pair corresponds to a custom label the user may use to distinguish different set of parameters.

Phase difference image and at least one magnitude image

Template:

```
sub-<label>/[ses-<label>/]
fmap/
sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phasediff.nii[.gz]
sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_phasediff.json
sub-<label>[_ses-<label>][_acq-<label>][_run-<index>]_magnitude1.nii[.gz]
```

OPTIONAL

```
sub-<label>/[ses-<label>/]
fmap/
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_magnitude2.nii[.gz]
```

This is a common output for build in fieldmap sequence on Siemens scanners. In this particular case the sidecar JSON file has to define the Echo Times of the two phase images used to create the difference image. EchoTime1 corresponds to the shorter echo time and EchoTime2 to the longer echo time. Similarly _magnitude1 image corresponds to the shorter echo time and the OPTIONAL _magnitude2 image to the longer echo time. For example:

```
{
    "EchoTime1": 0.00600,
    "EchoTime2": 0.00746,
    "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
}
```

Two phase images and two magnitude images

Template:

```
sub-<label>/[ses-<label>/]
fmap/
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_phase1.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_phase1.json
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_phase2.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_phase2.json
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_magnitude1.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_magnitude2.nii[.gz]
```

Similar to the case above, but instead of a precomputed phase difference map two separate phase images are presented. The two sidecar JSON file need to specify corresponding EchoTime values. For example:

```
{
    "EchoTime": 0.00746,
    "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
}
```

A real fieldmap image

Template:

```
sub-<label>/[ses-<label>/]
fmap/
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_magnitude.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_fieldmap.nii[.gz]
sub-<label>[_ses-<label>] [_acq-<label>] [_run-<index>]_fieldmap.json
```

In some cases (for example GE) the scanner software will output a precomputed fieldmap denoting the B0 inhomogeneities along with a magnitude image used for coregistration. In this case the sidecar JSON file needs to include the units of the fieldmap. The possible options are: Hz, rad/s, or Tesla. For example:

```
"Units": "rad/s",
"IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
}
```

Case 4: Multiple phase encoded directions ("pepolar")

Template:

```
sub-<label>/[ses-<label>/]
fmap/
sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>]_dir-<label>[_run-<index>]_epi.nii[.gz]
sub-<label>[_ses-<label>][_acq-<label>][_ce-<label>]_dir-<label>[_run-<index>]_epi.json
```

The phase-encoding polarity (PEpolar) technique combines two or more Spin Echo EPI scans with different phase encoding directions to estimate the underlying inhomogeneity/deformation map. Examples of tools using this kind of images are FSL TOPUP, AFNI 3dqwarp and SPM. In such a case, the phase encoding direction is specified in the corresponding JSON file as one of: i, j, k, i-, j-, k-. For these differentially phase encoded sequences, one also needs to specify the Total Readout Time defined as the time (in seconds) from the center of the first echo to the center of the last echo (aka "FSL definition" - see here (https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/topup/Faq#How_do_l_know_what_phase-encode_vectors_to_put_into_my_--datain_text_file.3F) and here (https://lcni.uoregon.edu/kb-articles/kb-0003) how to calculate it). For example

```
{
   "PhaseEncodingDirection": "j-",
   "TotalReadoutTime": 0.095,
   "IntendedFor": "func/sub-01_task-motor_bold.nii.gz"
}
```

label value of _dir- can be set to arbitrary alphanumeric label ([a-zA-Z0-9]+ for example LR or AP) that can help users to distinguish between different files, but should not be used to infer any scanning parameters (such as phase encoding directions) of the corresponding sequence. Please rely only on the JSON file to obtain scanning parameters. _epi files can be a 3D or 4D - in the latter case all timepoints share the same scanning parameters. To indicate which run is intended to be used with which functional or diffusion scan the IntendedFor field in the JSON file should be used.

Documentation built with MkDocs (https://www.mkdocs.org/).

Magnetoencephalography (MEG)

Support for MEG was developed as a BIDS Extension Proposal. Please cite the following paper when referring to this part of the standard in context of the academic literature:

Niso Galan, J.G., Gorgolewski, K.J., Bock, E., Brooks, T.L., Flandin, G., Gramfort, A., Henson, R.N., Jas, M., Litvak, V., Moreau, J., Oostenveld, R., Schoffelen, J.-M., Tadel, F., Wexler, J., Baillet, S., 2018. MEG-BIDS, the brain imaging data structure extended to magnetoencephalography (https://www.nature.com/articles/sdata2018110). Scientific Data volume 5, Article number: 180110 (2018)

MEG recording data

Template:

```
sub-<label>/
    [ses-<label>]/
    meg/
    sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_proc-<label>]_meg.<manufact
    [sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_proc-<label>]_meg.json]
```

Unprocessed MEG data MUST be stored in the native file format of the MEG instrument with which the data was collected. With MEG-BIDS, we wish to promote the adoption of good practices in the management of scientific data. Hence, the emphasis of MEG-BIDS is not to impose a new, generic data format for the modality, but rather to standardize the way data is stored in repositories. Further, there is currently no widely accepted standard file format for MEG, but major software applications, including free and open-source solutions for MEG data analysis provide readers of such raw files.

Some software reader may skip important metadata that is specific to MEG system manufacturers. It is therefore RECOMMENDED that users provide additional meta information extracted from the manufacturer raw data files in a sidecar JSON file. This allows for easy searching and indexing of key metadata elements without the need to parse files in proprietary data format. Other relevant files MAY be included alongside the MEG data; examples are provided below.

This template is for MEG data of any kind, including but not limited to task-based, resting-state, and noise recordings. If multiple Tasks were performed within a single Run, the task description can be set to task-multitask. The _meg.json SHOULD contain details on the Tasks. Some manufacturers data storage conventions use folders which contain data files of various nature: e.g., CTF's .ds format, or 4D/BTi. Please refer to Appendix VI (../99-appendices/06-meg-file-formats.pdf) for examples from a selection of MEG manufacturers.

The proc label is analogous to rec for MR and denotes a variant of a file that was a result of particular processing performed on the device. This is useful for files produced in particular by Elekta's MaxFilter (e.g. sss, tsss, trans, quat, mc, etc.), which some installations impose to be run on raw data because of active shielding software corrections before the MEG data can actually be exploited.

Sidecar JSON document (*_meg.json)

Generic fields MUST be present:

Field name

Definition

REQUIRED. Name of the task (for resting state use the rest prefix). Different Tasks SHOULD NOT TaskName have the same name. The Task label is derived from this field by removing all non alphanumeric ([a -zA-Z0-9]) characters.

SHOULD be present: For consistency between studies and institutions, we encourage users to extract the values of these fields from the actual raw data. Whenever possible, please avoid using ad-hoc wording.

Field name	Definition	
InstitutionName	RECOMMENDED. The name of the institution in charge of the equipment that	
	produced the composite instances.	
InstitutionAddress	RECOMMENDED. The address of the institution in charge of the equipment that	
	produced the composite instances.	
	RECOMMENDED. Manufacturer of the MEG system (CTF), Elekta/Neuromag,	
Manufacturer	4D/BTi, KIT/Yokogawa, ITAB, KRISS, Other). See Appendix VII (/99-	
	appendices/07-meg-systems.pdf) with preferred names	
	RECOMMENDED. Manufacturer's designation of the MEG scanner model (e.g.	
ManufacturersModelName CTF-275). See Appendix VII (/99-appendices/07-meg-systems.pdf) with		
	preferred names	
SoftwareVersions	RECOMMENDED. Manufacturer's designation of the acquisition software.	
TaskDescription	RECOMMENDED. Description of the task.	
Instructions	RECOMMENDED. Text of the instructions given to participants before the scan.	
	This is not only important for behavioural or cognitive tasks but also in resting state	
	paradigms (e.g. to distinguish between eyes open and eyes closed).	
	RECOMMENDED. URL of the corresponding Cognitive Atlas (http://	
CogAtlasID	www.cognitiveatlas.org/) term that describes the task (e.g. Resting State with eyes	
oog, maoib	closed "http://www.cognitiveatlas.org/term/id/trm_54e69c642d89b (http://	
	www.cognitiveatlas.org/term/id/trm_54e69c642d89b)")	
CogPOID	RECOMMENDED. URL of the corresponding CogPO (http://www.cogpo.org/) term	
	that describes the task (e.g. Rest "http://wiki.cogpo.org/index.php?title=Rest	
	(http://wiki.cogpo.org/index.php?title=Rest)")	
DeviceSerialNumber	RECOMMENDED. The serial number of the equipment that produced the	
	composite instances. A pseudonym can also be used to prevent the equipment	
	from being identifiable, as long as each pseudonym is unique within the dataset.	

Specific MEG fields MUST be present:

Field name Definition

SamplingFrequency REQUIRED. Sampling frequency (in Hz) of all the data in the recording, regardless of their type (e.g., 2400)

Field name	Definition
PowerLineFrequency	REQUIRED. Frequency (in Hz) of the power grid at the geographical location of the MEG instrument (i.e. 50 or 60)
DewarPosition	REQUIRED. Position of the dewar during the MEG scan: upright, supine or degree s of angle from vertical: for example on CTF systems, upright=15°, supine = 90°.
SoftwareFilters	REQUIRED. List of temporal and/or spatial software filters applied, or ideally key:value pairs of pre-applied software filters and their parameter values: e.g., {"SSS": {"frame": "head", "badlimit": 7}}, {"SpatialCompensation": {"GradientOrder": Order of the gradient compensation}}. Write n/a if no software filters applied.
DigitizedLandmarks	REQUIRED. Boolean ("true" or "false") value indicating whether anatomical landmark points (i.e. fiducials) are contained within this recording.
DigitizedHeadPoints	REQUIRED. Boolean (true or false) value indicating whether head points outlining the scalp/face surface are contained within this recording.
SHOULD be present	

Field name	Definition	
MEGChannelCount	RECOMMENDED. Number of MEG channels (e.g. 275)	
MEGREFChannelCount	RECOMMENDED. Number of MEG reference channels (e.g. 23). For systems	
	without such channels (e.g. Neuromag Vectorview), MEGREFChannelCount =0	
EEGChannelCount	RECOMMENDED. Number of EEG channels recorded simultaneously (e.g. 21)	
ECOGChannelCount	RECOMMENDED. Number of ECoG channels	
SEEGChannelCount	RECOMMENDED. Number of SEEG channels	
EOGChannelCount	RECOMMENDED. Number of EOG channels	
ECGChannelCount	RECOMMENDED. Number of ECG channels	
EMGChannelCount	RECOMMENDED. Number of EMG channels	
MiscChannelCount	RECOMMENDED. Number of miscellaneous analog channels for auxiliary signals	
TriggerChannelCount	RECOMMENDED. Number of channels for digital (TTL bit level) triggers	
RecordingDuration	RECOMMENDED. Length of the recording in seconds (e.g. 3600)	
	RECOMMENDED. Defines whether the recording is continuous or epoched;	
RecordingType	this latter limited to time windows about events of interest (e.g., stimulus	
	presentations, subject responses etc.)	
EpochLength	RECOMMENDED. Duration of individual epochs in seconds (e.g. 1) in case of	
	epoched data	
RECOMMENDED. Boolean (true or false) value indicating whether continuous head localisation was performed.		
	RECOMMENDED. List of frequencies (in Hz) used by the head localisation coils	
HeadCoilFrequency	('HLC' in CTF systems, 'HPI' in Elekta, 'COH' in 4D/BTi) that track the subject's	
	head position in the MEG helmet (e.g. [293, 307, 314, 321])	
MaxMovement	RECOMMENDED. Maximum head movement (in mm) detected during the	
Maximo vollione	recording, as measured by the head localisation coils (e.g., 4.8)	
	RECOMMENDED. Freeform description of the observed subject artefact and its	
SubjectArtefactDescription	possible cause (e.g. "Vagus Nerve Stimulator", "non-removable implant"). If this	
	field is set to n/a, it will be interpreted as absence of major source of artifacts	
	except cardiac and blinks.	

Field name	Definition
AssociatedEmptyRoom	RECOMMENDED. Relative path in BIDS folder structure to empty-room file associated with the subject's MEG recording. The path needs to use forward
	slashes instead of backward slashes (e.g. sub-emptyroom/ses-/meg/sub-
	<pre>emptyroom_sestask-noise_runmeg.ds).</pre>
Specific FEG fields (if reco	rded with MEG) SHOULD be present:

Field name	Definition
	OPTIONAL. Placement scheme of EEG electrodes. Either the name of a
EEGPlacementScheme	standardised placement system (e.g., "10-20") or a list of standardised
	electrode names (e.g. ["Cz", "Pz"]).
	OPTIONAL. Manufacturer's designation of the EEG amplifier model (e.g., B
ManufacturersAmplifierModelNam	iosemi-ActiveTwo).
CapManufacturer	OPTIONAL. Manufacturer of the EEG cap (e.g. EasyCap)
CapManufacturersModelName	OPTIONAL. Manufacturer's designation of the EEG cap model (e.g., M10)
EECDeference	OPTIONAL. Description of the type of EEG reference used (e.g., M1 for
EEGReference	left mastoid, average, or longitudinal bipolar).

By construct, EEG when recorded simultaneously with the same MEG system, should have the same SamplingFrequency as MEG. Note that if EEG is recorded with a separate amplifier, it should be stored separately under a new /eeg data type (see BEP006 (https://docs.google.com/document/d/1ArMZ9Y_quTKXCjNXZksnedK2VHHoKP3HCeO5HPcgLE/edit#heading=h.4k1noo90gelw)).

Example:

```
"InstitutionName": "Stanford University",
"InstitutionAddress": "450 Serra Mall, Stanford, CA 94305-2004, USA",
"Manufacturer": "CTF",
"ManufacturersModelName": "CTF-275",
"DeviceSerialNumber": "11035",
"SoftwareVersions": "Acq 5.4.2-linux-20070507"
"PowerLineFrequency": 60,
"SamplingFrequency": 2400,
"MEGChannelCount": 270,
"MEGREFChannelCount": 26.
"EEGChannelCount": 0.
"EOGChannelCount": 2.
"ECGChannelCount": 1.
"EMGChannelCount": 0.
  "DewarPosition": "upright",
"SoftwareFilters": {
  "SpatialCompensation": {"GradientOrder": "3rd"}
},
"RecordingDuration": 600,
"RecordingType": "continuous",
"EpochLength": 0,
"TaskName": "rest",
"ContinuousHeadLocalization": true,
"HeadCoilFrequency": [1470,1530,1590],
"DigitizedLandmarks": true,
"DigitizedHeadPoints": true
```

Note that the date and time information SHOULD be stored in the Study key file (scans.tsv), see Scans.tsv (../03-modality-agnostic-files.pdf). As it is indicated there, date time information MUST be expressed in the following format YYYY-MM-DDThh:mm:ss (ISO8601 (https://en.wikipedia.org/wiki/ISO_8601) date-time format). For example: 2009-06-15T13:45:30. It does not need to be fully detailed, depending on local REB/IRB ethics board policy.

Channels description table (*_channels.tsv)

Template:

```
sub-<label>/
  [ses-<label>]/
  meg/
  [sub-<label>[_ses-<label>]_task-<label>[_acq-<label>][_run-<index>][_proc-<label>]_channels.ts
```

This file is RECOMMENDED as it provides easily searchable information across MEG-BIDS datasets for e.g., general curation, response to queries or batch analysis. To avoid confusion, the channels SHOULD be listed in the order they appear in the MEG data file. Missing values MUST be indicated with n/a.

The columns of the Channels description table stored in *_channels.tsv are:

MUST be present:

Field name	Definition
name	REQUIRED. Channel name (e.g., MRT012, MEG023)
type	REQUIRED. Type of channel; MUST use the channel types listed below.
units	REQUIRED. Physical unit of the data values recorded by this channel in SI (see Appendix V (/99-
uiiitS	appendices/05-units.pdf): Units for allowed symbols).
SHOUL	he present:

SHOULD be present

Field name	Definition
description	OPTIONAL. Brief free-text description of the channel, or other information of interest. See examples below.
sampling_frequenc	y OPTIONAL. Sampling rate of the channel in Hz.
low_cutoff	OPTIONAL. Frequencies used for the high-pass filter applied to the channel in Hz. If no high-pass filter applied, use n/a.
high_cutoff	OPTIONAL. Frequencies used for the low-pass filter applied to the channel in Hz. If no low-pass filter applied, use n/a. Note that hardware anti-aliasing in A/D conversion of all MEG/EEG electronics applies a low-pass filter; specify its frequency here if applicable.
notch	OPTIONAL. Frequencies used for the notch filter applied to the channel, in Hz. If no notch filter applied, use n/a .
software_filters	OPTIONAL. List of temporal and/or spatial software filters applied (e.g. "SSS", "SpatialC ompensation"). Note that parameters should be defined in the general MEG sidecar .json file. Indicate n/a in the absence of software filters applied.
status	OPTIONAL. Data quality observed on the channel (good/bad). A channel is considered bad if its data quality is compromised by excessive noise. Description of noise type SHOULD be provided in [status_description].
status_description	OPTIONAL. Freeform text description of noise or artifact affecting data quality on the channel. It is meant to explain why the channel was declared bad in [status].

Example:

name type units description sampling_frequency low_cutoff high_cutoff notch software_filters status UDIO001 TRIG V analogue trigger 1200 0.1 300 0 n/a good MLC11 MEGGRADAXIAL T sensor 1st-order grad 1200 0 n/a 50 SSS bad

Restricted keyword list for field type

Keyword	Definition
MEGMAG	MEG magnetometer
MEGGRADAXIAL	MEG axial gradiometer
MEGGRADPLANAR	MEG planargradiometer
MEGREFMAG	MEG reference magnetometer
MEGREFGRADAXIAL	MEG reference axial gradiometer
MEGREFGRADPLANAR	MEG reference planar gradiometer
MEGOTHER	Any other type of MEG sensor
EEG	Electrode channel
ECOG	Electrode channel
SEEG	Electrode channel
DBS	Electrode channel

Keyword	Definition
VEOG	Vertical EOG (electrooculogram)
HEOG	Horizontal EOG
EOG	Generic EOG channel
ECG	ElectroCardioGram (heart)
EMG	ElectroMyoGram (muscle)
TRIG	System Triggers
AUDIO	Audio signal
PD	Photodiode
EYEGAZE	Eye Tracker gaze
PUPIL	Eye Tracker pupil diameter
MISC	Miscellaneous
SYSCLOCK	System time showing elapsed time since trial started
ADC	Analog to Digital input

ADC Analog to Digital input
DAC Digital to Analog output

HLU Measured position of head and head coils
FITERR Fit error signal from each head localization coil

OTHER Any other type of channel

Example of free text for field description

• stimulus, response, vertical EOG, horizontal EOG, skin conductance, sats, intracranial, eyetracker

Example:

```
name type units description
VEOG VEOG V vertical EOG
FDI EMG V left first dorsal interosseous
UDI0001 TRIG V analog trigger signal
UADC001 AUDIO V envelope of audio signal presented to participant
```

Coordinate System JSON document (*_coordsystem.json)

Template:

```
sub-<label>/
    [ses-<label>]/
    meg/
    [sub-<label>[_ses-<label>] [_acq-<label>]_coordsystem.json]
```

OPTIONAL. A JSON document specifying the coordinate system(s) used for the MEG, EEG, head localization coils, and anatomical landmarks.

MEG and EEG sensors:

Field name	Description
MEGCoordinateSystem	REQUIRED. Defines the coordinate system for the MEG sensors. See Appendix VIII (/99-appendices/08-coordinate-systems.pdf): preferred names of Coordinate systems. If Other, provide definition of the coordinate system in [MEGCoordinateSystemDescription].
MEGCoordinateUnits	REQUIRED. Units of the coordinates of MEGCoordinateSystem. MUST be m, cm, or mm.
MEGCoordinateSystemDescriptio	OPTIONAL. Freeform text description or link to document describing the MEG coordinate system system in detail.
EEGCoordinateSystem	OPTIONAL. Describes how the coordinates of the EEG sensors are to be interpreted.
EEGCoordinateUnits	OPTIONAL. Units of the coordinates of EEGCoordinateSystem. MUST be m, cm, or mm.
	OPTIONAL. Freeform text description or link to document describing the

EEGCoordinateSystemDescription OPTIONAL. Freeform text description or link to document describing the EEG coordinate system system in detail.

Head localization coils:

Field name	Description
	OPTIONAL. Key:value pairs describing head localization coil labels and their
	coordinates, interpreted following the HeadCoilCoordinateSystem, e.g., { NA
LloadCoilCoordinates	[12.7,21.3,13.9], LPA: [5.2,11.3,9.6], RPA: [20.2,11.3,9.1]}. N
HeadCoilCoordinates	coils are not always placed at locations that have a known anatomical name (e.g
	Elekta, Yokogawa systems); in that case generic labels can be used (e.g. { coil
	2,21.3,12.3], coil2: [6.7,12.3,8.6], coil3: [21.9,11.0,8.1]}).
HeadCoilCoordinateSystem	OPTIONAL. Defines the coordinate system for the coils. See Appendix VIII (/99 appendices/08-coordinate-systems.pdf): preferred names of Coordinate system "Other", provide definition of the coordinate system in
•	HeadCoilCoordinateSystemDescription .
HeadCoilCoordinateUnits	OPTIONAL. Units of the coordinates of HeadCoilCoordinateSystem. MUST bm, or mm.
	ODTIONAL Francisco to describitor or links describe and describe a describe

HeadCoilCoordinateSystemDescription OPTIONAL. Freeform text description or link to document describing the Head coordinate system in detail.

Digitized head points:

Field name	Description
	OPTIONAL. Relative path to the file containing the locations
	of digitized head points collected during the session (e.g.,
DigitizedHeadPoints	sub-01_headshape.pos). RECOMMENDED for all MEG
	systems, especially for CTF and 4D/BTi. For Elekta/
	Neuromag the head points will be stored in the fif file.
	OPTIONAL. Defines the coordinate system for the digitized
	head points. See Appendix VIII (/99-appendices/08-
Digitized Head Boints Coordinate System	coordinate-systems.pdf): preferred names of Coordinate
	systems. If Other, provide definition of the coordinate
	system in
	$\begin{tabular}{ll} Digitized Head Points Coordinate System Description \end{tabular}. \label{table_points}$

Field name	Description
	OPTIONAL. Units of the coordinates of
DigitizedHeadPointsCoordinateUnits	$\label{eq:decomposition} \textbf{DigitizedHeadPointsCoordinateSystem} \;. \; \textbf{MUST be} \; \big(\; \textbf{m} \; \big),$
	cm, or mm.
	OPTIONAL. Freeform text description or link to document
DigitizedHeadPointsCoordinateSystemDesc	ription describing the Digitized head Points coordinate system
	system in detail.
Anatomical MDI	

Anatomical MRI:

Field name Description

OPTIONAL. Path or list of path relative to the subject subfolder pointing to the structural MRI, possibly of different types if a list is specified, to be used with the MEG recording. The path(s) need(s) to use forward slashes instead of backward slashes (e.g. ses-/anat/sub-01_T1w.nii.gz).

Anatomical landmarks:

Field name	Description
	OPTIONAL. Key:value pairs of the labels and 3-D digitized
	locations of anatomical landmarks, interpreted following
AnatomicalLandmarkCoordinates	the AnatomicalLandmarkCoordinateSystem, e.g.,
	{"NAS": [12.7,21.3,13.9], "LPA": [5.2,11.3,9.6],
	"RPA": [20.2,11.3,9.1] }.
	OPTIONAL. Defines the coordinate system for the
	anatomical landmarks. See Appendix VIII (/99-
AnatomicalLandmarkCoordinateSystem	appendices/08-coordinate-systems.pdf): preferred names
AnatomicalcandmarkCoordinateSystem	of Coordinate systems. If Other, provide definition of the
	coordinate system in
	$\label{lem:anatomicalLandmarkCoordinateSystemDescription} .$
	OPTIONAL. Units of the coordinates of
AnatomicalLandmarkCoordinateUnits	AnatomicalLandmarkCoordinateSystem . MUST be m ,
	cm, or mm.

OPTIONAL. Freeform text description or link to document AnatomicalLandmarkCoordinateSystemDescription describing the Head Coil coordinate system in detail.

It is also RECOMMENDED that the MRI voxel coordinates of the actual anatomical landmarks for coregistration of MEG with structural MRI are stored in the AnatomicalLandmarkCoordinates field in the JSON sidecar of the corresponding T1w MRI anatomical data of the subject seen in the MEG session (see here (01-magnetic-resonance-imaging-data.pdf)) - for example: sub-01/ses-mri/anat/sub-01_ses-mri_acq-mprage_T1w.json

In principle, these locations are those of absolute anatomical markers. However, the marking of NAS, LPA and RPA is more ambiguous than that of e.g., AC and PC. This may result in some variability in their 3-D digitization from session to session, even for the same participant. The solution would be to use only one T1w file and populate the AnatomicalLandmarkCoordinates field with session-specific labels e.g., "NAS-session1": [127,213,139], "NAS-session2": [123,220,142], etc.

Fiducials information:

Field name

Description

FiducialsDescription

OPTIONAL. A freeform text field documenting the anatomical landmarks that were used and how the head localization coils were placed relative to these. This field can describe, for instance, whether the true anatomical locations of the left and right pre-auricular points were used and digitized, or rather whether they were defined as the intersection between the tragus and the helix (the entry of the ear canal), or any other anatomical description of selected points in the vicinity of the ears.

For more information on the definition of anatomical landmarks, please visit: http://www.fieldtriptoolbox.org/faq/how_are_the_lpa_and_rpa_points_define (http://www.fieldtriptoolbox.org/faq/how_are_the_lpa_and_rpa_points_defined)

For more information on typical coordinate systems for MEG-MRI coregistration: http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined (http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined), or: http://neuroimage.usc.edu/brainstorm/CoordinateSystems (http://neuroimage.usc.edu/brainstorm/CoordinateSystems)

Landmark photos (*_photo.jpg)


Photos of the anatomical landmarks and/or head localization coils (*_photo.jpg)

Template:

```
sub-<label>/
  [ses-<label>]/
  meg/
  [sub-<label>[_ses-<label>] [_acq-<label>]_photo.jpg]
```

Photos of the anatomical landmarks and/or head localization coils on the subject's head are RECOMMENDED. If the coils are not placed at the location of actual anatomical landmarks, these latter may be marked with a piece of felt-tip taped to the skin. Please note that the photos may need to be cropped or blurred to conceal identifying features prior to sharing, depending on the terms of the consent form signed by the participant.

Example of the NAS fiducial placed between the eyebrows, rather than at the actual anatomical nasion: sub-0001_ses-001_acq-NAS_photo.jpg



3-D head point /electrode locations file

Template:

```
sub-<label>/
  [ses-<label>]/
  meg/
  [sub-<label>[_ses-<label>] [_acq-<label>]_headshape.manufacturer_specific_extension>]
```

This file is RECOMMENDED.

The 3-D locations of head points and/or EEG electrode locations can be digitized and stored in separate files. The *_acq-<label> can be used when more than one type of digitization in done for a session, for example when the head points are in a separate file from the EEG locations. These files are stored in the specific format of the 3-D digitizer's manufacturer (see Appendix VI (../99-appendices/06-meg-file-formats.pdf)).

Example:

```
sub-control01
ses-01
sub-control01_ses-01_acq-HEAD_headshape.pos
sub-control01_ses-01_acq-ECG_headshape.pos
```

Note that the *_headshape file(s) is shared by all the runs and tasks in a session. If the subject needs to be taken out of the scanner and the head-shape has to be updated, then for MEG it could be considered to be a new session.


Empty-room files (sub-emptyroom)

Empty-room MEG files capture the environment and system noise. Their collection is RECOMMENDED, before/during/after each session. This data is stored inside a subject folder named sub-emptyroom. The session. The

Example:

```
sub-control01/
sub-control02/
sub-emptyroom/
ses-20170801/
sub-emptyroom_ses-20170801_scans.tsv
    meg/
    sub-emptyroom_ses-20170801_task-noise_meg.ds
    sub-emptyroom_ses-20170801_task-noise_meg.json
```

TaskName in the *_meg.json file should be set to "noise".



Task events

Template:

Where <matches> corresponds to task file name. For example: sub-control01_task-nback. It is also possible to have a single _events.tsv file describing events for all participants and runs (see "Inheritance rule" (../02-common-principles.pdf)). As with all other tabular data, _events files may be accompanied by a JSON file describing the columns in detail (see here (../02-common-principles.pdf)).

The purpose of this file is to describe timing and other properties of events recorded during the scan. Events MAY be either stimuli presented to the participant or participant responses. A single event file MAY include any combination of stimuli and response events. Events MAY overlap in time. Please mind that this does not imply that only so called "event related" study designs are supported (in contract to "block" designs) - each "block of events" can be represented by an individual row in the _events.tsv file (with a long duration). Each task events file REQUIRES a corresponding task imaging data file (but a single events file MAY be shared by multiple imaging data files - see Inheritance rule). The tabular files consists of one row per event and a set of REQUIRED and OPTIONAL columns:

Column name	Description
onset	REQUIRED. Onset (in seconds) of the event measured from the beginning of the acquisition of the first volume in the corresponding task imaging data file. If any acquired scans have been discarded before forming the imaging data file, ensure that a time of 0 corresponds to the first image stored. In other words negative numbers in "onset" are allowed ⁵ .
duration	REQUIRED. Duration of the event (measured from onset) in seconds. Must always be either zero or positive. A "duration" value of zero implies that the delta function or event is so short as to be effectively modeled as an impulse.
trial_type	OPTIONAL. Primary categorisation of each trial to identify them as instances of the experimental conditions. For example: for a response inhibition task, it could take on values "go" and "no-go" to refer to response initiation and response inhibition experimental conditions.
response_time	OPTIONAL. Response time measured in seconds. A negative response time can be used to represent preemptive responses and "n/a" denotes a missed response.
stim_file	OPTIONAL. Represents the location of the stimulus file (image, video, sound etc.) presented at the given onset time. There are no restrictions on the file formats of the stimuli files, but they should be stored in the /stimuli folder (under the root folder of the dataset; with optional subfolders). The values under the stim_file column correspond to a path relative to "/stimuli". For example "images/cat03.jpg" will be translated to "/stimuli/images/cat03.jpg".

Column name	Description
HED	OPTIONAL. Hierarchical Event Descriptor (HED) Tag. See Appendix III (/99-appendices/03-hed.pdf) for details.

⁵ For example in case there is an in scanner training phase that begins before the scanning sequence has started events from this sequence should have negative onset time counting down to the beginning of the acquisition of the first volume.

An arbitrary number of additional columns can be added. Those allow describing other properties of events that could be later referred in modelling and hypothesis extensions of BIDS.

In case of multi-echo task run, a single _events.tsv file will suffice for all echoes.

Example:

```
sub-control01/
func/
sub-control01_task-stopsignal_events.tsv
```

```
onset duration trial_type response_time stim_file
1.2 0.6 go 1.435 images/red_square.jpg
5.6 0.6 stop 1.739 images/blue_square.jpg
```

References to existing databases can also be encoded using additional columns. Example 2 includes references to the Karolinska Directed Emotional Faces (KDEF) database⁶:

⁶http://www.emotionlab.se/resources/kdef (http://www.emotionlab.se/resources/kdef)


Example:


```
sub-control01/
func/
sub-control01_task-emoface_events.tsv
```

```
onset duration trial_type identifier database response_time
1.2 0.6 afraid AF01AFAF kdef 1.435
5.6 0.6 angry AM01AFAN kdef 1.739
5.6 0.6 sad AF01ANSA kdef 1.739
```

For multi-echo files events.tsv file is applicable to all echos of particular run:

```
sub-01_task-cuedSGT_run-1_events.tsv
sub-01_task-cuedSGT_run-1_echo-1_bold.nii.gz
sub-01_task-cuedSGT_run-1_echo-2_bold.nii.gz
sub-01_task-cuedSGT_run-1_echo-3_bold.nii.gz
```





Physiological and other continuous recordings

Template:

Optional: Yes

Where <matches> corresponds to task file name without the _bold.nii[.gz] suffix. For example: sub-control01_task-nback_run-1. If the same continuous recording has been used for all subjects (for example in the case where they all watched the same movie) one file can be used and placed in the root directory. For example: task-movie_stim.tsv.gz

Physiological recordings such as cardiac and respiratory signals and other continuous measures (such as parameters of a film or audio stimuli) can be specified using two files: a gzip compressed TSV file with data (without header line) and a JSON for storing start time, sampling frequency, and name of the columns from the TSV. Please note that in contrast to other TSV files this one does not include a header line. Instead the name of columns are specified in the JSON file. This is to improve compatibility with existing software (FSL PNM) as well as make support for other file formats possible in the future. Start time should be expressed in seconds in relation to the time of start of acquisition of the first volume in the corresponding imaging file (negative values are allowed). Sampling frequency should be expressed in Hz. Recordings with different sampling frequencies and/or starting times should be stored in separate files. The following naming conventions should be used for column names:

Column name Definition

cardiac continuous pulse measurement respiratory continuous breathing measurement

trigger continuous measurement of the scanner trigger signal

Any combination of those three can be included as well as any other stimuli related continuous variables (such as low level image properties in a video watching paradigm).

Physiological recordings (including eye tracking) should use the _physio suffix, and signals related to the stimulus should use _stim suffix. For motion parameters acquired from scanner side motion correction please use _physio suffix.

More than one continuous recording file can be included (with different sampling frequencies). In such case use different labels. For example: __recording-contrast , __recording-saturation . The full file name could then look like this: sub-control01_task-nback_run-2_recording-movie_stim.tsv.gz

For multi-echo data, physio.tsv file is applicable to all echos of particular run. For eg:

```
sub-01 task-cuedSGT run-1 physio.tsv.gz
 sub-01_task-cuedSGT_run-1_echo-1_bold.nii.gz
 sub-01_task-cuedSGT_run-1_echo-2_bold.nii.gz
 sub-01_task-cuedSGT_run-1_echo-3_bold.nii.gz
Example:
 sub-control01/
     func/
         sub-control01_task-nback_physio.tsv.gz
(after decompression)
 34 110 0
 44 112 0
 23 100 1
 sub-control01/
     func/
         sub-control01_task-nback_physio.json
    "SamplingFrequency": 100.0,
    "StartTime": -22.345,
    "Columns": ["cardiac", "respiratory", "trigger"]
 }
```

Behavioral experiments (with no MRI)

Template:

```
sub-<label>/[ses-<label>/]
beh/

sub-<label>[_ses-<label>]_task-<task_name>_events.tsv
sub-<label>[_ses-<label>]_task-<task_name>_events.json
sub-<label>[_ses-<label>]_task-<task_name>_beh.tsv
sub-<label>[_ses-<label>]_task-<task_name>_beh.json
sub-<label>[_ses-<label>]_task-<task_name>_physio.tsv.gz
sub-<label>[_ses-<label>]_task-<task_name>_physio.json
sub-<label>[_ses-<label>]_task-<task_name>_stim.tsv.gz
sub-<label>[_ses-<label>]_task-<task_name>_stim.json
```

In addition to logs from behavioral experiments performed along imaging data acquisitions one can also include data from experiments performed outside of the scanner. The results of those experiments can be stored in the beh folder using the same formats for event timing (_events.tsv), metadata (_events.json), physiological (_physio.tsv.gz), _physio.json) and other continuous recordings (_stim.tsv.gz), _stim.json) as for tasks performed during MRI acquisitions. Additionally, events files that do not include the mandatory onset and duration columns can still be included, but should be labelled _beh.tsv rather than _events.tsv.

Longitudinal studies with multiple sessions (visits)

Multiple sessions (visits) are encoded by adding an extra layer of directories and file names in the form of ses-<label>. Session label can consist only of alphanumeric characters [a-zA-Z0-9] and should be consistent across subjects. If numbers are used in session labels we recommend using zero padding (for example ses-0 1, ses-11 instead of ses-1, ses-11). This makes results of alphabetical sorting more intuitive. Acquisition time of session can be defined in the sessions file (see below for details).

The extra session layer (at least one /ses-<label> subfolder) should be added for all subjects if at least one subject in the dataset has more than one session. Skipping the session layer for only some subjects in the dataset is not allowed. If a /ses-<label> subfolder is included as part of the directory hierarchy, then the same ses-<label> tag must also be included as part of the file names themselves.

```
sub-control01/
    ses-predrug/
        anat/
            sub-control01_ses-predrug_T1w.nii.gz
            sub-control01 ses-predrug T1w.json
            sub-control01 ses-predrug T2w.nii.gz
            sub-control01_ses-predrug_T2w.json
        func/
            sub-control01_ses-predrug_task-nback_bold.nii.gz
            sub-control01_ses-predrug_task-nback_bold.json
            sub-control01 ses-predrug task-nback events.tsv
            sub-control01 ses-predrug task-nback cont-physio.tsv.gz
            sub-control01_ses-predrug_task-nback_cont-physio.json
            sub-control01_ses-predrug_task-nback_sbref.nii.gz
        dwi/
            sub-control01_ses-predrug_dwi.nii.gz
            sub-control01 ses-predrug dwi.bval
            sub-control01 ses-predrug dwi.bvec
        fmap/
            sub-control01 ses-predrug phasediff.nii.gz
            sub-control01_ses-predrug_phasediff.json
            sub-control01 ses-predrug magnitude1.nii.gz
        sub-control01_ses-predrug_scans.tsv
    ses-postdrug/
        func/
            sub-control01 ses-postdrug task-nback bold.nii.gz
            sub-control01 ses-postdrug task-nback bold.json
            sub-control01_ses-postdrug_task-nback_events.tsv
            sub-control01 ses-postdrug task-nback cont-physio.tsv.gz
            sub-control01_ses-postdrug_task-nback_cont-physio.json
            sub-control01_ses-postdrug_task-nback_sbref.nii.gz
        fmap/
            sub-control01_ses-postdrug_phasediff.nii.gz
            sub-control01_ses-postdrug_phasediff.json
            sub-control01 ses-postdrug magnitude1.nii.gz
        sub-control01 ses-postdrug scans.tsv
    sub-control01_sessions.tsv
participants.tsv
dataset_description.json
README
CHANGES
```

Sessions file

Template:

```
sub-<label>/
sub-<label>_sessions.tsv
```

Optional: Yes

In case of multiple sessions there is an option of adding an additional participant key files describing variables changing between sessions. In such case one file per participant should be added. These files need to include compulsory session_id column and describe each session by one and only one row. Column names in per participant key files have to be different from group level participant key column names.

```
_sessions.tsv example:
```

```
session_id acq_time systolic_blood_pressure ses-predrug 2009-06-15T13:45:30 120 ses-postdrug 2009-06-16T13:45:30 100 ses-followup 2009-06-17T13:45:30 110
```

Multi-site or multi-center studies

This version of the BIDS specification does not explicitly cover studies with data coming from multiple sites or multiple centers (such extension is planned in BIDS 2.0.0). There are however ways to model your data without any loss in terms of metadata.

Treat each site/center as a separate dataset

The simplest way of dealing with multiple sites is to treat data from each site as a separate and independent BIDS dataset with a separate participants.tsv and other metadata files. This way you can feed each dataset individually to BIDS Apps and everything should just work.

Option 2: Combining sites/centers into one dataset

Alternatively you can combine data from all sites into one dataset. To identify which site each subjects comes from you can add a site column in the participants.tsv file indicating the source site. This solution allows you to analyze all of the subjects together in one dataset. One caveat is that subjects from all sites will have to have unique labels. To enforce that and improve readability you can use a subject label prefix identifying the site. For example sub-NUY001, sub-MIT002, sub-MPG002 etc. Remember that hyphens and underscores are not allowed in subject labels.

Contributing to and extending the BIDS specification

This page lists some ways that you can get involved with the BIDS community.

Contributing to BIDS

There are many ways to get involved with the BIDS community!

The BIDS Starter Kit

If you're new to the BIDS community and you'd like to learn a bit more, we recommend checking out the BIDS Starter Kit (https://github.com/bids-standard/bids-starter-kit/blob/master/README.md). This has introductory information about the BIDS specification, tools in the BIDS ecosystem, and how you can get involved.

The BIDS Contributor guide

If you'd like to get involved more heavily in helping extend the BIDS specification or develop tools for it, see the BIDS Contributor Guide (https://docs.google.com/document/d/1pWmEEY-1-

WuwBPNy5tDAxVJYQ9Een4hZJM06tQZg8X4/edit?usp%3Dsharing&sa=D&ust=1537468908724000). It contains more in-depth information for getting involved with the BIDS community.

BIDS Extension Proposals

The BIDS specification can be extended in a backwards compatible way and will evolve over time. These are accomplished with BIDS Extension Proposals (BEPs), which are community-driven processes.

Below is a table of currently-active BEPs.

Title

BEP001 (https://docs.google.com/document/d/ 1QwfHyBzOyFWOLO4u_kkojLpUhW0-4_M7Ubafu9Gf4Gg)

BEP002 (https://docs.google.com/document/d/ 1bq5eNDHTb6Nkx3WUiOBgKvLNnaa5OMcGtD0AZ9yms2M)

BEP003 (https://docs.google.com/document/d/ 1Wwc4A6Mow4ZPPszDIWfCUCRNstn7d_zzaWPcfcHmgI4) Structural acquisitions that include multiple contrasts (meecho, flip angle, inversion time) sequences (https://docs.google.com/document/d/

1QwfHyBzOyFWOLO4u_kkojLpUhW0-4_M7Ubafu9Gf4G The BIDS Models Specification (https://docs.google.com/document/d/

1bq5eNDHTb6Nkx3WUiOBgKvLNnaa5OMcGtD0AZ9ym Common Derivatives (https://docs.google.com/documer 1Wwc4A6Mow4ZPPszDIWfCUCRNstn7d_zzaWPcfcHmg

Extension label	Title
BEP004 (https://docs.google.com/document/d/	Susceptibility Weighted Imaging (SWI) (https://docs.google.com/document/d/
1kyw9mGgacNqeMbp4xZet3RnDhcMmf4_BmRgKaOkO2Sc)	1kyw9mGgacNqeMbp4xZet3RnDhcMmf4_BmRgKaOkO
BEP005 (https://docs.google.com/document/d/	Arterial Spin Labeling (ASL) (https://docs.google.com/document/d/
15tnn5F10KpgHypaQJNNGiNKsni9035GtDqJzWqkkP6c)	15tnn5F10KpgHypaQJNNGiNKsni9035GtDqJzWqkkP6c
BEP006 (https://docs.google.com/document/d/ 1ArMZ9Y_quTKXC-jNXZksnedK2VHHoKP3HCeO5HPcgLE)	Electroencephalography (EEG) (https://docs.google.com/document/d/1ArMZ9Y_quTKXC-jNXZksnedK2VHHoKP3HCeO5HPcgLE)
BEP009 (https://docs.google.com/document/d/	Positron Emission Tomography (PET) (https://docs.google.com/document/d/
1mqMLnxVdLwZjDd4ZiWFqjEAmOmfcModA_R535v3eQs0)	1mqMLnxVdLwZjDd4ZiWFqjEAmOmfcModA_R535v3eQ
BEP010 (https://docs.google.com/document/d/1qMUkoaXzRMIJuOcfTYNr3fTsrl4SewWjffjMD5Ew6GY)	intracranial Electroencephalography (iEEG) (https://docs.google.com/document/d/1qMUkoaXzRMIJuOcfTYNr3fTsrl4SewWjffjMD5Ew6GY)
BEP011 (https://docs.google.com/document/d/	The structural preprocessing derivatives (https://docs.google.com/document/d/
1YG2g4UkEio4t_STIBOqYOwneLEs1emHIXbGKynx7V0Y)	1YG2g4UkEio4t_STIBOqYOwneLEs1emHIXbGKynx7V0Y
BEP012 (https://docs.google.com/document/d/ 16CvBwVMAs0IMhdoKmlmcm3W8254dQmNARo-7HhE-IJU)	The functional preprocessing derivatives (https://docs.google.com/document/d/16CvBwVMAs0IMhdoKmlmcm3W8254dQmNARo-7HhE
BEP013 (https://docs.google.com/document/d/ 1qBNQimDx6CuvHjbDvuFyBIrf2WRFUOJ-u50canWjjaw)	The resting state fMRI derivatives (https://docs.google.co document/d/1qBNQimDx6CuvHjbDvuFyBIrf2WRFUOJ- u50canWjjaw)
BEP014 (https://docs.google.com/document/d/ 11gCzXOPUbYyuQx8fErtMO9tnOKC3kTWiL9axWkkILNE)	The affine transformations and nonlinear field warps (http docs.google.com/document/d/ 11gCzXOPUbYyuQx8fErtMO9tnOKC3kTWiL9axWkkILNE
BEP015 (https://docs.google.com/document/d/	Mapping file (https://docs.google.com/document/d/
1WYOTXDB7GzlHoWqLjd45l3uGBgPxXddST-NTqBnroJE)	1WYOTXDB7GzlHoWqLjd45l3uGBgPxXddST-NTqBnroJl
BEP016 (https://docs.google.com/document/d/	The diffusion weighted imaging derivatives (https://docs.google.com/document/d/
1cQYBvToU7tUEtWMLMwXUCB_T8gebCotE1OczUpMYW60)	1cQYBvToU7tUEtWMLMwXUCB_T8gebCotE1OczUpMY
BEP017 (https://docs.google.com/document/d/	Generic BIDS connectivity data schema (https://docs.google.com/document/d/
1ugBdUF6dhElXdj3u9vw0iWjE6f_Bibsro3ah7sRV0GA)	1ugBdUF6dhEIXdj3u9vw0iWjE6f_Bibsro3ah7sRV0GA)

Extension label	Title
BEP018 (https://docs.google.com/document/d/ 1uRkgyzESLKuGjXi98Z97Wh6vt-iLN5nOAb9TG16CjUs)	Genetic information (https://docs.google.com/document 1uRkgyzESLKuGjXi98Z97Wh6vt-iLN5nOAb9TG16CjUs)
BEP019 (https://docs.google.com/document/d/ 1FqJI791ycXr0bfRg2qyLqAf0RpVttJ2cInOgMWrKsNU)	DICOM Metadata (https://docs.google.com/document/d 1FqJI791ycXr0bfRg2qyLqAf0RpVttJ2cInOgMWrKsNU)
BEP020 (https://docs.google.com/document/d/ 1eggzTCzSHG3AEKhtnEDbcdk-2avXN6l94X8aUPEBVsw)	Eye Tracking including Gaze Position and Pupil Size(ET) (https://docs.google.com/document/d/ 1eggzTCzSHG3AEKhtnEDbcdk-2avXN6I94X8aUPEBVsv
BEP021 (https://docs.google.com/document/d/ 1PmcVs7vg7Th-cGC-UrX8rAhKUHIzOI-uIOh69_mvdlw)	Common Electrophysiological Derivatives (https://docs.google.com/document/d/1PmcVs7vg7Th-cGC-UrX8rAhKUHlzOI-ulOh69_mvdlw)
BEP022 (https://docs.google.com/document/d/ 1pWCb02YNv5W-UZZja24fZrdXLm4X7knXMiZI7E2z7mY)	Magnetic Resonance Spectroscopy (MRS) (https://docs.google.com/document/d/1pWCb02YNv5W-UZZja24fZrdXLm4X7knXMiZl7E2z7mY)
BEP023 (https://docs.google.com/document/d/1yzsd1J9GT-aA0DWhdlgNr5LCu6_gvbjLyfvYq2FuxlY)	PET Preprocessing derivatives (https://docs.google.com/document/d/1yzsd1J9GT-aA0DWhdlgNr5LCu6_gvbjLyfvYq2FuxlY)
BEP024 (https://docs.google.com/document/d/ 1fqnJZ18x5LJC8jiJ8yvPHUGFzNBZ6gW2kywYrUKWtuo)	Computed Tomography scan (CT) (https://docs.google.cdocument/d/ 1fqnJZ18x5LJC8jiJ8yvPHUGFzNBZ6gW2kywYrUKWtuo
BEP025 (https://docs.google.com/document/d/1chZv7vAPE-ebPDxMktfl9i1OkLNR2FELIfpVYsaZPr4)	Medical Population Imaging Data structure (MIDS) (https://docs.google.com/document/d/1chZv7vAPE-ebPDxMktfl9i1OkLNR2FELlfpVYsaZPr4)
BEP026 (https://docs.google.com/document/d/14KC1d5- Lx-7ZSMtwS7pVAAvz-2WR_uoo5FvsNirzqJw)	Microelectrode Recordings (MER) (https://docs.google.c document/d/14KC1d5- Lx-7ZSMtwS7pVAAvz-2WR_uoo5FvsNirzqJw)
When an extension reaches maturity it is merged into the mair	. – . ,
All of the extension ideas that are not backwards compatible a	and thus will have to wait for BIDS 2.0 are listed

All of the extension ideas that are not backwards compatible and thus will have to wait for BIDS 2.0 are listed here (https://docs.google.com/document/d/1LEgsMiisGDe1Gv-hBp1EcLmoz7AlKj6VYULUgDD3Zdw)

Documentation built with MkDocs (https://www.mkdocs.org/).							

Appendix I: Contributors

Legend (source: https://github.com/kentcdodds/all-contributors (https://github.com/kentcdodds/all-contributors))

Emoji Represents

- Answering Questions (on the mailing list, NeuroStars, GitHub, or in person)
- Bug reports
- Blogposts
- Code
- Documentation and specification
- Design
- Examples
- Event Organizers
- Financial Support
- Funding/Grant Finders
- Ideas & Planning
- Infrastructure (Hosting, Build-Tools, etc)
- Plugin/utility libraries
- Reviewed Pull Requests
- Tools
- Translation
- Tests
- Tutorials
- Talks
- Videos

The following individuals have contributed to the Brain Imaging Data Structure ecosystem (in alphabetical order). If you contributed to the BIDS ecosystem and your name is not listed, please add it.

- Stefan Appelhoff W99% ?
- Sylvain Baillet
- Elizabeth Bock
- Eric Bridgeford

- Vince D. Calhoun
- Alexander L. Cohen
- R. Cameron Craddock
- Samir Das
- Alejandro de la Vega





Appendix II: Licenses

This section lists a number of common licenses for datasets and defines suggested abbreviations for use in the dataset metadata specifications

Identifie	er License name	Description
PD	Public Domain	No license required for any purpose; the work is not subject to copyright in any jurisdiction.
PDDL	Open Data Commons Public Domain Dedication and License	License to assign public domain like permissions without giving up the copyright: http://opendatacommons.org/licenses/pddl/ (http://opendatacommons.org/licenses/pddl/)
CC0	Creative Commons Zero	Use this if you are a holder of copyright or database rights, and you wish to waive all your interests in your work worldwide: http://opendatacommons.org/licenses/cc0/ (https://creativecommons.org/about/cc0)

Appendix III: Hierarchical Event Descriptor (HED) Tags

HED is a controlled vocabulary of terms describing events in a behavioral paradigm. HED was originally developed with EEG in mind, but is applicable to all behavioral experiments. Each level of a hierarchical tag is delimited with a forward slash (/). An HED string contains one or more HED tags separated by commas (,). Parentheses (brackets, ()) group tags and enable specification of multiple items and their attributes in a single HED string (see section 2.4 in HED Tagging Strategy Guide (http://www.hedtags.org/downloads/HED%20Tagging%20Strategy%20Guide.pdf)). For more information about HED and tools available to validate and match HED strings, please visit www.hedtags.org (http://www.hedtags.org). Since dedicated fields already exist for the overall task classification in the sidecar JSON files (CogAtlasID and CogPOID), HED tags from the Paradigm HED subcategory should not be used to annotate events.

There are several ways to associate HED annotations with events within the BIDS framework. The most direct way is to use the HED column of the _events.tsv file to annotate events:

Example:

```
onset duration HED

1.1 n/a Event/Category/Experimental stimulus, Event/Label/CrossFix, Sensory presentation/Visual, Item

1.3 n/a Event/Category/Participant response, Event/Label/ButtonPress, Action/Button press

...
```

The direct approach requires that each line in the events file must be annotated. Since there are typically thousands of events in each experiment, this method of annotation is usually not convenient unless the annotations are automatically generated. In many experiments, the event instances fall into a much smaller number of categories, and often these categories are labeled with numerical codes or short names. It is therefore more convenient to associate the HED annotations with these categories and allow the analysis tools to make the association with individual event instances during analysis. To use this approach, your _events.tsv file should associate a category (often called an event code) with each event instance. Since BIDS allows an arbitrary number of columns to be included in an _events.tsv file, you can make this association by including columns representing various types of event categories in your _events.tsv file.

Example:

```
onset duration mycodes

1.1 n/a Fixation

1.3 n/a Button

1.8 n/a Target
...
```

If you provide an _events.json file somewhere in your data hierarchy that has an HED mapping for _mycodes , the HED tags associated with a given _mycodes value can then be associated with the event instances in that category. You may provide a HED column and multiple category columns. The union of the relevant HED tags will then be associated with the event instance.

Example:

```
"mycodes": {
    "HED": {
        "Fixation": "Event/Category/Experimental stimulus, Event/Label/CrossFix, Event/Description
        "Target": "Event/Label/Target image, Event/Description/A white airplane as the RSVP target
        "Button": "..."
     }
}
```

The tags in the HED column are often specific to the event instances, while the common properties associated with categories such as mycodes are encapsulated in the _events.json dictionary. Downstream tools should not distinguish between tags specified using the different mechanisms. Further, the normal BIDS inheritance rules apply so these data dictionaries can appear higher in the BIDS hierarchy.

Appendix IV: Entity table

This section compiles the entities (key-value pairs) described throughout this specification, and establishes a common order within a filename. For example, if a file has an acquisition and reconstruction label, the acquisition entity must precede the reconstruction entity. REQUIRED and OPTIONAL entities for a given file type are denoted. Entity formats indicate whether the value is alphanumeric (<label>) or numeric (<index>).

(<index>).</index>								
Entity	Format	anat (T1w T2w T1rho T1map T2map T2star FLAIR FLASH PD PDmap PDT2 inplaneT1 inplaneT2 angio)	func (bold) sbref events)	func (physio stim)	dwi (dwi bvec bval)	fmap (phasediff phase1 phase2 magnitude magnitude magnitude fieldmap)	` . ,	beh (eve stim phys
Subject	sub- <label></label>	REQUIRED REQUIRED	REQUIRE	REQUIRE	D REQUIRED	REQUIRED	REQUIRED	REG
Session	ses- <label></label>	OPTIONAL OPTIONAL	OPTIONAL	_OPTIONAL	_ OPTIONAL	OPTIONAL	OPTIONAL	OPT
Task	task- <label></label>		REQUIRE	REQUIRE	D			REG
Acquisition	acq- <label></label>	OPTIONAL OPTIONAL	OPTIONAL	_OPTIONAL	_ OPTIONAL	OPTIONAL	OPTIONAL	-
Contrast Enhancing Agent	ce- <label< td=""><td>> OPTIONAL OPTIONAL</td><td>OPTIONAL</td><td>-</td><td></td><td></td><td>OPTIONAL</td><td>-</td></label<>	> OPTIONAL OPTIONAL	OPTIONAL	-			OPTIONAL	-
Reconstruction	rec- <label></label>	OPTIONAL OPTIONAL	OPTIONAL	OPTIONAL	_			
Phase- Encoding Direction	dir- <label></label>		OPTIONAL	-	OPTIONAL	-	REQUIRED)
Run	run- <index></index>		OPTIONAL	_OPTIONAL	_ OPTIONAL	OPTIONAL	OPTIONAL	_
Corresponding	mod-	OPTIONAL						

modality

<label>

Entity		anat (T1w T2w T1rho T1map T2map T2star FLAIR FLASH PI PDmap PDT2 inplaneT2 angio)	anat D ^{(defacemask}	func (bold) sbref events)	func (physio stim)	dwi (dwi bvec bval)	fmap (phasediff phase1 phase2 magnitude1 magnitude2 magnitude fieldmap)	 beh (eve stin phy
Echo	echo- <index></index>			OPTIONAL	-			
Recording	recording- <pre><label></label></pre>	}			OPTIONAL	-		
Processed (on device)	proc- <label></label>				OPTIONAL	-		

Appendix V: Units

Following the International System of Units (SI, abbreviated from the French Système international (d'unités))

Unit name	Unit symbo	ol Quantity name
metre	m	length
kilogram	kg	mass
second	S	time
ampere	Α	electric current
kelvin	K	thermodynamic temperature
mole	mol	amount of substance
candela	cd	luminous intensity
radian	rad	angle
steradian	sr	solid angle
hertz	Hz	frequency
newton	N	force, weight
pascal	Pa	pressure, stress
joule	J	energy, work, heat
watt	W	power, radiant flux
coulomb	С	electric charge or quantity of electricity
volt	V	voltage (electrical potential), emf
farad	F	capacitance
ohm	Ω	resistance, impedance, reactance
siemens	S	electrical conductance
weber	Wb	magnetic flux
tesla	T	magnetic flux density
henry	Н	inductance
degree Celsiu	s°C	temperature relative to 273.15 K
lumen	lm	luminous flux
lux	lx	illuminance
becquerel	Bq	radioactivity (decays per unit time)
gray	Gy	absorbed dose (of ionizing radiation)
sievert	Sv	equivalent dose (of ionizing radiation)
katal	kat	catalytic activity

Prefixes

Multiples

Prefix name	Prefix symbo	l Factor
deca (https://www.wikiwand.com/en/Deca-)	da	10 ¹
hecto (https://www.wikiwand.com/en/Hecto-	·) h	10 ²
kilo (https://www.wikiwand.com/en/Kilo-)	k	10 ³
mega (https://www.wikiwand.com/en/Mega-)) M	10 ⁶
giga (https://www.wikiwand.com/en/Giga-)	G	10 ⁹
tera (https://www.wikiwand.com/en/Tera-)	Т	10 ¹²
peta (https://www.wikiwand.com/en/Peta-)	Р	10 ¹⁵
exa (https://www.wikiwand.com/en/Exa-)	E	10 ¹⁸
zetta (https://www.wikiwand.com/en/Zetta-)	Z	10 ²¹
yotta (https://www.wikiwand.com/en/Yotta-)	Υ	10 ²⁴

Submultiples

Prefix name	Prefix symbo	l Factor
deci (https://www.wikiwand.com/en/Deci-)	d	10 ⁻¹
centi (https://www.wikiwand.com/en/Centi-)	С	10 ⁻²
milli (https://www.wikiwand.com/en/Milli-)	m	10 ⁻³
micro (https://www.wikiwand.com/en/Micro-)	μ	10 ⁻⁶
nano (https://www.wikiwand.com/en/Nano-)	n	10 ⁻⁹
pico (https://www.wikiwand.com/en/Pico-)	р	10 ⁻¹²
femto (https://www.wikiwand.com/en/Femto-) f	10 ⁻¹⁵
atto (https://www.wikiwand.com/en/Atto-)	а	10 ⁻¹⁸
zepto (https://www.wikiwand.com/en/Zepto-)	z	10 ⁻²¹
yocto (https://www.wikiwand.com/en/Yocto-)	У	10 ⁻²⁴

Appendix VI: MEG file formats

Each MEG system brand has specific file organization and data formats. RECOMMENDED values for manufacturer_specific_extensions:

Value Definition

- ctf CTF (folder with .ds extension)
- fif Neuromag / Elekta / MEGIN and BabyMEG (file with extension .fif)
- 4d BTi / 4D Neuroimaging (folder containing multiple files without extensions)
- kit KIT / Yokogawa / Ricoh (file with extension .sqd , .con , .raw , .ave or .mrk)
- kdf KRISS (file with extension .kdf)
- itab Chieti system (file with extension .raw and .mhd)

Below are specifications for each system brand.

CTF

Each experimental run with a CTF system yields a folder with a ds extension, containing several files. The OPTIONAL digitized positions of the head points are usually stored in a separate post file, not necessarily within the ds folder.

```
[sub-<label>[_ses-<label>]_headshape.pos]
sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.ds>
```

CTF's data storage is therefore via directories containing multiple files. The files contained within a .ds directory are named such that they match the parent directory, but conserve the original file extension (e.g.,

meg4, res4, etc.). The renaming of CTF datasets SHOULD be done using the CTF newDs command-line application.

Example:

```
sub-control01/
ses-001/
sub-control01_ses-001_scans.tsv
meg/
sub-control01_ses-001_coordsystem.json
sub-control01_ses-001_headshape.pos
sub-control01_ses-001_task-rest_run-01_meg.ds
sub-control01_ses-001_task-rest_run-01_meg.json
sub-control01_ses-001_task-rest_run-01_channels.tsv
```

To learn more about CTF's data organization: http://www.fieldtriptoolbox.org/getting_started/ctf (http://www.fieldtriptoolbox.org/getting_started/ctf)

Neuromag/Elekta/MEGIN

Neuromag/Elekta/MEGIN data and Tristan Technologies BabyMEG data is stored with file extension __fif_.

The digitized positions of the head points are saved inside the fif file along with the MEG data, with typically no _headshape | file.

```
sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.fif
```

Note that we do not provide specific specifications for cross-talk and fine-calibration matrix files in the present MEG-BIDS version.

Example:

```
sub-control01/
ses-001/
sub-control01_ses-001_scans.tsv
meg/
sub-control01_ses-001_coordsystem.json
sub-control01_ses-001_task-rest_run-01_meg.fif
sub-control01_ses-001_task-rest_run-01_meg.json
sub-control01_ses-001_task-rest_run-01_channels.tsv
```

After applying the MaxFilter pre-processing tool, files should be renamed with the corresponding label (e.g. proc-sss) and placed into a derivatives subfolder.

Example:

```
sub-control01_ses-001_task-rest_run-01_proc-sss_meg.fif
sub-control01_ses-001_task-rest_run-01_proc-sss_meg.json
```

In the case of data runs exceeding 2Gb, the data is stored in two separate files:

```
sub-control01_ses-001_task-rest_run-01_meg.fif
sub-control01_ses-001_task-rest_run-01_meg-1.fif
```

Each of these two files has a pointer to the next file. In some software applications, like MNE, one can simply specify the name of the first file, and data will be read in both files via this pointer. For this reason, it is RECOMMENDED to rename and write back the file once read, to avoid the persistence of a pointer associated with the old file name.

Naming convention:

```
sub-control01_ses-001_task-rest_run-01_part-01_meg.fif
sub-control01_ses-001_task-rest_run-01_part-02_meg.fif
```

More about the Neuromag/Elekta/MEGIN data organization at: http://www.fieldtriptoolbox.org/getting_started/neuromag (http://www.fieldtriptoolbox.org/getting_started/neuromag) And BabyMEG: http://www.fieldtriptoolbox.org/getting_started/babysquid (http://www.fieldtriptoolbox.org/getting_started/babysquid)

BTi/4D neuroimaging

Each experimental run on a 4D neuroimaging/BTi system results in a folder containing multiple files without extensions.

```
[sub-<label>[_ses-<label>]_headshape.pos]
sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg>
```

One SHOULD rename/create a father run specific directory and keep the original files for each run inside (e.g. "c,rfhp0.1Hz", "config" and "hs_file").

Example:

Where:

```
sub-control01_ses-001_task-rest_run-01_meg/
  config
  hs_file
  e,rfhp1.0Hz.COH
  c,rfDC
```

More about the 4D neuroimaging/BTi data organization at: http://www.fieldtriptoolbox.org/getting_started/bti (http://www.fieldtriptoolbox.org/getting_started/bti)

KIT/Yokogawa/Ricoh

Each experimental run on a KIT/Yokogawa/Ricoh system yields a raw (.sqd , .con) file with its associated marker coil file (.mrk), which contains coil positions in the acquisition system's native space. Head points and marker points in head space are acquired using third-party hardware. One SHOULD rename/create a father run specific directory and keep the original files for each run inside.

Example:

```
sub-control01/
ses-001/
sub-control01_ses-001_scans.tsv
meg/
sub-control01_ses-001_coordsystem.json
sub-control01_ses-001_headshape.txt
sub-control01_ses-001_task-rest_run-01_meg
sub-control01_ses-001_task-rest_run-01_meg.json
sub-control01_ses-001_task-rest_run-01_channels.tsv
Where:

sub-control01_ses-001_task-rest_run-01_meg/
sub-control01_ses-001_task-rest_run-01_meg.
```

More about the KIT/Yokogawa/Ricoh data organization at: http://www.fieldtriptoolbox.org/getting_started/yokogawa (http://www.fieldtriptoolbox.org/getting_started/yokogawa)

KRISS

Each experimental run on the KRISS system produces a file with extension .kdf. Additional files can be available in the same folder: the digitized positions of the head points (_digitizer.txt), the position of the center of the MEG coils (.chn) and the event markers (.trg).

```
[sub-<label>[_ses-<label>]_headshape.txt]
sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.kdf
sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.chn
sub-<label>[_ses-<label>]_task-<label>[_run-<index>]_meg.trg
```

Example:

```
sub-control01/
ses-001/
sub-control01_ses-001_scans.tsv
meg/
sub-control01_ses-001_coordsystem.json
sub-control01_ses-001_headshape.txt
sub-control01_ses-001_task-rest_run-01_meg
sub-control01_ses-001_task-rest_run-01_meg.json
sub-control01_ses-001_task-rest_run-01_channels.tsv
```

Where:

```
sub-control01_ses-001_task-rest_run-01_meg/
sub-control01_ses-001_task-rest_run-01_meg.chn
sub-control01_ses-001_task-rest_run-01_meg.kdf
sub-control01_ses-001_task-rest_run-01_meg.trg
```

ITAB

Each experimental run on a ITAB-ARGOS153 system yields a raw (. raw) data file plus an associated binary header file (.mhd). The raw data file has an ASCII header that contains detailed information about the data acquisition system, followed by binary data. The associated binary header file contains part of the information from the ASCII header, specifically the one needed to process data, plus other information on offline preprocessing performed after data acquisition (e.g., sensor position relative to subject's head, head markers, stimulus information). One should rename/create a father run specific directory and keep the original files for each run inside.

Example:


```
sub-control01/
ses-001/
sub-control01_ses-001_coordsystem.json
sub-control01_ses-001_headshape.txt
sub-control01_ses-001_task-rest_run-01_meg
sub-control01_ses-001_task-rest_run-01_meg.json
sub-control01_ses-001_task-rest_run-01_channels.tsv
```

Where:

```
sub-control01_ses-001_task-rest_run-01_meg/
sub-control01_ses-001_task-rest_run-01_meg.raw
sub-control01_ses-001_task-rest_run-01_meg.raw.mhd
```

Aalto MEG-MRI

For stand-alone MEG data, the Aalto hybrid device uses the standard <code>.fif</code> data format and follows the conventions of Elekta/Neuromag as described above in section 5.2. The <code>.fif</code> files may contain unreconstructed MRI data. The inclusion of MRI data and information for accurate reconstruction will be fully standardized at a later stage.



Appendix VII: preferred names of MEG systems

Restricted keywords for Manufacturer field in the *meg.json file:

- CTF
- Elekta/Neuromag (https://docs.google.com/document/d/ 1FWex_kSPWVh_f4rKgd5rxJmxlboAPtQlmBc1gyZIRZM/edit#heading=h.a7ggx48p7aaf)
- 4D/BTi (https://docs.google.com/document/d/ 1FWex_kSPWVh_f4rKgd5rxJmxlboAPtQlmBc1gyZlRZM/edit#heading=h.gy0kbzisg1f1)
- KIT/Yokogawa/Ricoh (https://docs.google.com/document/d/ 1FWex_kSPWVh_f4rKgd5rxJmxlboAPtQlmBc1gyZlRZM/edit#heading=h.2gmmxawyna7r)
- KRISS
- ITAB (https://docs.google.com/document/d/1FWex_kSPWVh_f4rKgd5rxJmxlboAPtQlmBc1gyZlRZM/edit#heading=h.58whib3oq56y)
- Aalto/MEG-MRI
- Other

Restricted keywords for ManufacturersModelName field in the *meg.json file:

System Model Name	Manufacturer	Details
CTF-64	CTF	
CTF-151	CTF	https://www.ctf.com/products (https://www.ctf.com/products)
CTF-275	CTF	CTF-275: OMEGA 2000
Neuromag-122	Elekta/	
	Neuromag	
ElektaVectorview	Elekta/	102 magnetometers + 204 planar gradiometers
	Neuromag	
ElektaTRIUX	Elekta/	https://www.elekta.com/diagnostic-solutions/ (https://
	Neuromag	www.elekta.com/diagnostic-solutions/)
4D-Magnes-WH2500	4D/BTi	
4D-Magnes-WH3600	4D/BTi	
KIT-157	KIT/Yokogawa	
KIT-160	KIT/Yokogawa	
KIT-208	KIT/Yokogawa	
ITAB-ARGOS153	ITAB	
Aalto-MEG-MRI-YYYY/ MM	Aalto/MEG-MR	I YYYY-MM (year, month; or major version)

Documentation built with MkDocs (https://www.mkdocs.org/).

Appendix VIII: preferred names of Coordinate systems

To interpret a coordinate (x, y, z), it is required that you know relative to which origin the coordinates are expressed, you have to know the interpretation of the three axes, and you have to know the units in which the numbers are expressed. This information is sometimes called the coordinate system.

These letters help describe the coordinate system definition:

A/P means anterior/posterior L/R means left/right S/I means superior/inferior

For example: RAS means that the first dimension (X) points towards the right hand side of the head, the second dimension (Y) points towards the Anterior aspect of the head, and the third dimension (Z) points towards the top of the head.

Besides coordinate systems, defined by their origin and direction of the axes, BIDS defines "spaces" as an artificial frame of reference, created to describe different anatomies in a unifying manner (see e.g. https://doi.org/10.1016/j.neuroimage.2012.01.024 (https://www.sciencedirect.com/science/article/pii/S1053811912000419?via%3Dihub)). The "space" and all coordinates expressed in this space are by design a transformation of the real world geometry, and nearly always different from the individual subject space that it stems from. An example is the Talairach-Tournoux space, which is constructed by piecewise linear scaling of an individual's brain to that of the Talairach-Tournoux 1988 atlas. In the Talairach-Tournoux space, the origin of the coordinate system is at the AC and units are expressed in mm.

The coordinate systems below all relate to neuroscience and therefore to the head or brain coordinates. Please be aware that all data acquisition starts with "device coordinates" (scanner), which does not have to be identical to the initial "file format coordinates" (DICOM), which are again different from the "head" coordinates (e.g. NIFTI). Not only do device coordinate vary between hardware manufacturers, but also the head coordinates differ, mostly due to different conventions used in specific software packages developed by different (commercial or academic) groups.

MEG specific Coordinate Systems

The first two pieces of information (origin, orientation) are specified in XXXCoordinateSystem, the units are specified in XXXCoordinateSystemUnits.

Restricted keywords for the XXXCoordinateSystem field in the coordinatesystem.json file for MEG datasets:

- CTF: ALS orientation and the origin between the ears
- · ElektaNeuromag: RAS orientation and the origin between the ears
- 4DBti: ALS orientation and the origin between the ears
- KitYokogawa: ALS orientation and the origin between the ears

- · Chietiltab: RAS orientation and the origin between the ears
- Other: Use this for other coordinate systems and specify further details in the XXXCoordinateSystemDescription field

Note that the short descriptions above do not capture all details, there are detailed descriptions of these coordinate systems on the FieldTrip toolbox web page: http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined (http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined)

EEG specific Coordinate Systems

The first two pieces of information (origin, orientation) are specified in XXXCoordinateSystem, the units are specified in XXXCoordinateSystemUnits.

Restricted keywords for the XXXCoordinateSystem field in the coordsystem.json file for EEG datasets:

- BESA: Although natively this is a spherical coordinate system, the electrode positions should be expressed in Cartesian coordinates, with a RAS orientation. The X axis is the T8-T7 line, positive at T8. The Y axis is the Oz-Fpz line, positive at Fpz. The origin of the sphere fitted to the electrodes is approximately 4 cm above the point between the ears.
- Captrak : RAS orientation and the origin between the ears

Note that the short descriptions above do not capture all details, There are detailed extensive descriptions of these EEG coordinate systems on the FieldTrip toolbox web page and on the BESA wiki: http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined (http://www.fieldtriptoolbox.org/faq/how_are_the_different_head_and_mri_coordinate_systems_defined) http://wiki.besa.de/index.php?title=Electrodes_and_Surface_Locations#Coordinate_systems (http://wiki.besa.de/index.php?title=Electrodes_and_Surface_Locations#Coordinate_systems)

Template based Coordinate Systems

The transformation of the real world geometry to an artificial frame of reference is described in XXXCoordinate System. Unless otherwise specified below, the origin is at the AC and the orientation of the axes is RAS. Unless specified explicitly in the sidecar file in the XXCoordinateSystemUnits field, the units are assumed to be mm.

Coordinate System	Description
MNI152Lin	Also known as ICBM (version with linear coregistration) http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152Lin (http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152Lin)
MNI152NLin6[Sym Asym]	Also known as ICBM 6th generation (non-linear coregistration). Used by SPM99 - SPM8 and FSL (MNI152NLin6Sym). http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin6 (http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin6)
MNI152NLin2009[a-c] [Sym Asym]	Also known as ICBM (non-linear coregistration with 40 iterations, released in 2009). It comes in either three different flavours each in symmetric or asymmetric version. http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin2009 (http://www.bic.mni.mcgill.ca/ServicesAtlases/ICBM152NLin2009)

Coordinate System	Description
	Average of 27 T1 scans of a single subject http://www.bic.mni.mcgill.ca/
MNIColin27	ServicesAtlases/Colin27Highres (http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27Highres)
MNI305	Also known as avg305.
	Pediatric templates generated from the NIHPD sample. Available for different age
NIHPD	groups (4.5–18.5 y.o., 4.5–8.5 y.o., 7–11 y.o., 7.5–13.5 y.o., 10–14 y.o., 13–18.5 y.o. This template also comes in either -symmetric or -asymmetric flavor. http://
	www.bic.mni.mcgill.ca/ServicesAtlases/NIHPD-obj1 (http://www.bic.mni.mcgill.ca/ServicesAtlases/NIHPD-obj1)
Talairach	Piecewise linear scaling of the brain is implemented as described in TT88. http://www.talairach.org/ (http://www.talairach.org/)
OASIS30AntsOASISAnts	https://figshare.com/articles/ANTs_ANTsR_Brain_Templates/915436 (https://figshare.com/articles/ANTs_ANTsR_Brain_Templates/915436)
OASIS30Atropos	http://www.mindboggle.info/data.html (http://www.mindboggle.info/data.html)
ICBM452AirSpace	Reference space defined by the "average of 452 T1-weighted MRIs of normal young adult brains" with "linear transforms of the subjects into the atlas space using a 12-parameter affine transformation" http://www.loni.usc.edu/ICBM/Downloads/Downloads_452T1.shtml (http://www.loni.usc.edu/ICBM/Downloads/Downloads_452T1.shtml)
ICBM452Warp5Space	Reference space defined by the "average of 452 T1-weighted MRIs of normal young adult brains" "based on a 5th order polynomial transformation into the atlas space" http://www.loni.usc.edu/ICBM/Downloads/Downloads_452T1.shtml (http://www.loni.usc.edu/ICBM/Downloads/Downloads_452T1.shtml)
IXI549Space	Reference space defined by the average of the "549 () subjects from the IXI dataset" linearly transformed to ICBM MNI 452.Used by SPM12. http://www.brain-development.org/ (http://www.brain-development.org/)
fsaverage[3 4 5 6 sym]	Images were sampled to the FreeSurfer surface reconstructed from the subject's T1w image, and registered to an fsaverage template
UNCInfant[0 1 2]V[21 22 23]	Infant Brain Atlases from Neonates to 1- and 2-year-olds. https://www.nitrc.org/projects/pediatricatlas (https://www.nitrc.org/projects/pediatricatlas)

Documentation built with MkDocs (https://www.mkdocs.org/).

Changelog

1.1.2 (https://github.com/bids-standard/bids-specification/tree/1.1.2) (2019-01-10)

- Update 01-contributors.md #120 (https://github.com/bids-standard/bids-specification/pull/120) (oesteban (https://github.com/oesteban))
- Global fields in data dictionaries #117 (https://github.com/bids-standard/bids-specification/pull/117) (chrisfilo (https://github.com/chrisfilo))
- Propose BEP026 MER #116 (https://github.com/bids-standard/bids-specification/pull/116) (greydongilmore (https://github.com/greydongilmore))
- Remove duplicate entries in MEG table #113 (https://github.com/bids-standard/bids-specification/pull/ 113) (franklin-feingold (https://github.com/franklin-feingold))
- Propose BEP025 MIDS #110 (https://github.com/bids-standard/bids-specification/pull/110) (josator2 (https://github.com/josator2))
- repair links #106 (https://github.com/bids-standard/bids-specification/pull/106) (sappelhoff (https://github.com/sappelhoff))
- Autogenerate CHANGES.md #103 (https://github.com/bids-standard/bids-specification/pull/103) (franklin-feingold (https://github.com/franklin-feingold))
- Added contributor information #100 (https://github.com/bids-standard/bids-specification/pull/100) (jgrethe (https://github.com/jgrethe))
- ENH: First(?) good practice recommendation. No excessive overrides in Inheritance principle #99 (https://github.com/bids-standard/bids-specification/pull/99) (yarikoptic (https://github.com/yarikoptic))
- adding extensions page #97 (https://github.com/bids-standard/bids-specification/pull/97) (choldgraf (https://github.com/choldgraf))
- Fix up some urls (as detected to be broken/inconsistent #95 (https://github.com/bids-standard/bids-specification/pull/95) (yarikoptic (https://github.com/yarikoptic))
- Change BEP numbers to include MRS #94 (https://github.com/bids-standard/bids-specification/pull/94)
 (Hboni (https://github.com/Hboni))
- RF harmonize and thus shorten templates etc #93 (https://github.com/bids-standard/bids-specification/pull/93) (yarikoptic (https://github.com/yarikoptic))
- put links and some text into README #91 (https://github.com/bids-standard/bids-specification/pull/91) (sappelhoff (https://github.com/sappelhoff))
- Add extension proposal in 01-introduction.md #88 (https://github.com/bids-standard/bids-specification/pull/88) (Hboni (https://github.com/Hboni))
- additional table to recap 'volume acquisition timing' #87 (https://github.com/bids-standard/bids-specification/pull/87) (Remi-Gau (https://github.com/Remi-Gau))
- Small typo in "scanning sequence" DICOM tag #84 (https://github.com/bids-standard/bids-specification/pull/84) (Remi-Gau (https://github.com/Remi-Gau))
- Update 01-contributors.md #83 (https://github.com/bids-standard/bids-specification/pull/83) (teonbrooks (https://github.com/teonbrooks))
- Added CBV contrast #82 (https://github.com/bids-standard/bids-specification/pull/82) (TheChymera (https://github.com/TheChymera))

- Add CC-BY 4.0 license #81 (https://github.com/bids-standard/bids-specification/pull/81) (KirstieJane (https://github.com/KirstieJane))
- Fix Travis break #80 (https://github.com/bids-standard/bids-specification/pull/80) (franklin-feingold (https://github.com/franklin-feingold))
- ENH: allow _dir for other EPI (func, dwi) sequences #78 (https://github.com/bids-standard/bids-specification/pull/78) (yarikoptic (https://github.com/yarikoptic))
- Added appendix to mkdocs and added some internal links #77 (https://github.com/bids-standard/bids-specification/pull/77) (franklin-feingold (https://github.com/franklin-feingold))
- DOC: added JC Houde as contributor. #76 (https://github.com/bids-standard/bids-specification/pull/76) (jchoude (https://github.com/jchoude))
- Updated my contributions #75 (https://github.com/bids-standard/bids-specification/pull/75) (nicholst (https://github.com/nicholst))
- update HED appendix #74 (https://github.com/bids-standard/bids-specification/pull/74) (sappelhoff (https://github.com/sappelhoff))
- [MRG] unicode: replace greek mu and omega by micro and ohm signs #73 (https://github.com/bids-standard/bids-specification/pull/73) (sappelhoff (https://github.com/sappelhoff))
- Update 01-contributors.md #72 (https://github.com/bids-standard/bids-specification/pull/72) (francopestilli (https://github.com/francopestilli))
- add ce-\<label> for fmri data #70 (https://github.com/bids-standard/bids-specification/pull/70) (dasturge (https://github.com/dasturge))
- pin pip version #68 (https://github.com/bids-standard/bids-specification/pull/68) (chrisfilo (https://github.com/chrisfilo))
- Fix link in index #46 (https://github.com/bids-standard/bids-specification/pull/46) (chrisfilo (https://github.com/chrisfilo))
- edit contributing md #44 (https://github.com/bids-standard/bids-specification/pull/44) (Park-Patrick (https://github.com/Park-Patrick))
- Mkdocs configuration and RTD setup #42 (https://github.com/bids-standard/bids-specification/pull/42) (choldgraf (https://github.com/choldgraf))
- Move definitions, compulsory, and raw/derivatives sections to principles #40 (https://github.com/bids-standard/bids-specification/pull/40) (chrisfilo (https://github.com/chrisfilo))
- Remove duplicate section #39 (https://github.com/bids-standard/bids-specification/pull/39) (chrisfilo (https://github.com/chrisfilo))
- mkdocs rendering #36 (https://github.com/bids-standard/bids-specification/pull/36) (chrisfilo (https://github.com/chrisfilo))
- Style consistency #35 (https://github.com/bids-standard/bids-specification/pull/35) (chrisfilo (https://github.com/chrisfilo))
- Renaming files to conform with style guide #34 (https://github.com/bids-standard/bids-specification/pull/34) (chrisfilo (https://github.com/chrisfilo))
- enable travis cache #32 (https://github.com/bids-standard/bids-specification/pull/32) (chrisfilo (https://github.com/chrisfilo))
- FIX corrected link that is shown for CC0 #31 (https://github.com/bids-standard/bids-specification/pull/31) (robertoostenveld (https://github.com/robertoostenveld))
- [WIP] added linter integration via travis #30 (https://github.com/bids-standard/bids-specification/pull/30) (chrisfilo (https://github.com/chrisfilo))
- Cleanup #29 (https://github.com/bids-standard/bids-specification/pull/29) (chrisfilo (https://github.com/chrisfilo))
- [MRG] split intro, commons, mr, and meg into folder from specification.md #28 (https://github.com/bids-standard/bids-specification/pull/28) (teonbrooks (https://github.com/teonbrooks))

- Add some bids starter kit contributors #27 (https://github.com/bids-standard/bids-specification/pull/27) (KirstieJane (https://github.com/KirstieJane))
- Embedded footnotes into text #25 (https://github.com/bids-standard/bids-specification/pull/25) (franklin-feingold (https://github.com/franklin-feingold))
- Making HED Strategy Guide link prettier #24 (https://github.com/bids-standard/bids-specification/pull/ 24) (fake-filo (https://github.com/fake-filo))
- Fix/more cleanup #21 (https://github.com/bids-standard/bids-specification/pull/21) (chrisfilo (https://github.com/chrisfilo))
- formatted MEG (8.4) #17 (https://github.com/bids-standard/bids-specification/pull/17) (franklin-feingold (https://github.com/franklin-feingold))
- small fixes #16 (https://github.com/bids-standard/bids-specification/pull/16) (chrisfilo (https://github.com/chrisfilo))
- Add meg img #14 (https://github.com/bids-standard/bids-specification/pull/14) (sappelhoff (https://github.com/sappelhoff))
- [WIP] Cleaning up the specification #13 (https://github.com/bids-standard/bids-specification/pull/13) (chrisfilo (https://github.com/chrisfilo))
- Adding code of conduct #6 (https://github.com/bids-standard/bids-specification/pull/6) (chrisfilo (https://github.com/chrisfilo))
- Renaming the main document #1 (https://github.com/bids-standard/bids-specification/pull/1) (chrisfilo (https://github.com/chrisfilo))

1.1.1

- Improved the MEG landmark coordinates description.
- Replaced ManufacturersCapModelName in meg.json with CapManufacturer and CapManufacturersModelName.
- Remove EEGSamplingFrequency and ManufacturersAmplifierModelName from the meg.json.
- · Improved the behavioural data description.

1.1.0

- Added support for MEG data (merged BEP008)
- Added SequenceName field.
- Added support for describing events with Hierarchical Event Descriptors [4.3 Task events (04-modality-specific-files/03-task-events.pdf)].
- Added VolumeTiming and AcquisitionDuration fields [4.1 Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].
- · Added DwellTime field.

1.0.2

- Added support for high resolution (anatomical) T2star images [4.1 Anatomy imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].
- Added support for multiple defacing masks [4.1 Anatomy imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].

- Added optional key and metadata field for contrast enhanced structural scans [4.1 Anatomy imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)]
- Added DelayTime field [4.1 Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].
- Added support for multi echo BOLD data [4.1 Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].

1.0.1

- Added InstitutionName field [4.1 Task (including resting state) imaging data (04-modality-specific-files/ 01-magnetic-resonance-imaging-data.pdf)].
- Added InstitutionAddress field [4.1 Task (including resting state) imaging data (04-modality-specific-files/ 01-magnetic-resonance-imaging-data.pdf)].
- Added DeviceSerialNumber field [4.1 Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].
- Added NumberOfVolumesDiscardedByUser and NumberOfVolumesDiscardedByScanner field [4.1 Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].
- Added TotalReadoutTime to functional images metadata list [4.1 Task (including resting state) imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].

1.0.1-rc1

- Added T1 Rho maps [4.1 Anatomy imaging data (04-modality-specific-files/01-magnetic-resonance-imaging-data.pdf)].
- Added support for phenotypic information split into multiple files [3.2 Participant key file (03-modality-agnostic-files.pdf)].
- · Added recommendations for multi site datasets
- · Added SoftwareVersions
- Added run-<run_index> to the phase encoding maps. Improved the description.
- · Added InversionTime metadata key.
- · Clarification on the source vs raw language.
- Added trial_type column to the event files.
- Added missing sub-<participant_label> in behavioural data file names
- · Added ability to store stimuli files.
- · Clarified the language describing allowed subject labels.
- Added quantitative proton density maps.

1.0.0

- · Added ability to specify fieldmaps acquired with multiple parameter sets.
- · Added ability to have multiple runs of the same fieldmap.
- · Added FLASH anatomical images.

1.0.0-rc4

- · Replaced links to neurolex with explicit DICOM Tags.
- · Added sourcedata.
- · Added data dictionaries.
- · Be more explicit about contents of JSON files for structural (anatomical) scans.

1.0.0-rc3

- Renamed PhaseEncodingDirection values from "x", "y", "z" to "i", "j", "k" to avoid confusion with FSL parameters
- Renamed SliceEncodingDirection values from "x", "y", "z" to "i", "j", "k"

1.0.0-rc2

- Removed the requirement that TSV files cannot include more than two consecutive spaces.
- · Refactor of the definitions sections (copied from the manuscript)
- · Make support for uncompressed .nii files more explicit.
- · Added BIDSVersion to dataset.json
- · Remove the statement that SliceEncodingDirection is necessary for slice time correction
- Change dicom converter recommendation from dcmstack to dcm2nii and dicm2nii following interactions
 with the community (see https://github.com/moloney/dcmstack/issues/39 (https://github.com/moloney/
 dcmstack/issues/39) and https://github.com/neurolabusc/dcm2niix/issues/4 (https://github.com/
 neurolabusc/dcm2niix/issues/4)).
- · Added section on behavioral experiments with no accompanying MRI acquisition
- Add _magnitude.nii[.gz] image for GE type fieldmaps.
- Replaced EchoTimeDifference with EchoTime1 and EchoTime2 (SPM toolbox requires this input).
- · Added support for single band reference image for DWI.
- Added DatasetDOI field in the dataset description.
- · Added description of more metadata fields relevant to DWI fieldmap correction.

- PhaseEncodingDirection is now expressed in "x", "y" etc. instead of "PA" "RL" for DWI scans (so it's the same as BOLD scans)
- Added rec-<label> flag to BOLD files to distinguish between different reconstruction algorithms (analogous to anatomical scans).
- Added recommendation to use _physio suffix for continuous recordings of motion parameters obtained by the scanner side reconstruction algorithms.

1.0.0-rc1

· Initial release

Documentation built with MkDocs (https://www.mkdocs.org/).

^{*} This Change Log was automatically generated by github_changelog_generator (https://github.com/skywinder/Github-Changelog-Generator)