

## **OUTDOOR HEATER**

- To make the outdoor life more fascinating
- Mainly utilized in hotel, bar, garden and other outdoor activities Low consumption, high efficiency and less pollution
- Up to 46,000 BTU's (12.5kw) of heat output with variable heat control
- Easily assembly, simple operation by easy ignition with piezo or electric ignitor

## SICTEC Group Inc.

D'Arcy Draper
Director, Sales & Marketing
905-943-7571
d.draper@sictec.com
7050 Woodbine Avenue, St. 201
Markham,Ontario L3R 4G8,Canada



Creates a warm comfort zone for dining group setting of 6-8 people for one table

Use on to Table Side or Table Center

Fitting all standard umbrella hole openings 1-1/2" or greater

Heating Output: 15,000~30,000 BTU' s(8kw)max

Easy moveable with optional castors assembly



(steel with powder coated)							
Pressure	Max Power	Consumption	on Gas Type	Weight	Packing Dimensions	track	<b></b>
mbar	Kw	kg/h kg/ł	า 13	kg	I xwxh	Type	Sets
		max mir	1				
28-30/37	12	0.87 0.43	5   13+,13 B/P	22	(I)cm 85x85x10.5	20	120
50	12	1.00 0.48	3 13+,13	Hmxd:20	(ÍI)cm 44x40x87	40	250
					, ,	40H	288