Induction Cooker



SICTEC Group Inc

D'Arcy Draper
Director, Sales & Marketing
905-943-7571
d.draper@sictec.com
SICTEC Group Inc.
7050 Woodbine Avenue, St. 201
Markham,Ontario L3R 4G8,Canada

Induction Cooker



Model:

IC-10

1 pcs inner gift box, 4 pcs per carton Unit size: 340 * 300 * 66 mm Carton dimension: 720 * 345 * 430 mm G.W.: 20kgs N.W.: 18kgs Qty per 20ft 960pcs

Qty per 40ft 1980pcs Qty per 40HQ 2376pcs

M.O.Q.: 960pcs

- 1500W, White, Induction Cooker With Digital Timer Control
- 7 Cooking Functions: Cook, Steam, Stew, Hot Pot, Fry, Stir Fry, Keep Warm;
- 5 Power Adjustments:70.120.150.180.220-degree:
- 4 Time Settings:15,30, 45,60 Minutes;
- Overheat and Overvoltage Protection;
- Ceramic With High Temperature Resistance;
- Accessory: A stainless steel cooking pot (0.5mm thickness, 260mm diameter)
- Material: Plastic:50%; Ceramic:40%; Metal:5%; Others:5%

Model:

IC-20

1 pcs inner gift box, 4 pcs per carton Unit size:343x296x60mm Gift box size:404x206x371mm Carton size:820x430x390mm G.W.: 4.25kg N.W.:3.5kg Qty per 20ft 700pcs Qty per 40ft 1500pcs Qty per 40HQ 1900pcs M.O.Q.: 1500pcs

- 120V 60Hz 1300W
- Ceramic Glass plate
- 8 Prosetting cooking program
- Digital timer display
- Six level power adjustable
- Soft touch control panel
- Auto pan detection
- Unique shell shape design
- stainless steel pot as accessories
- ETL certificate approval



Induction Cooker



Model:

IC-30

1 pcs inner gift box, 4 pcs per carton Gift box size: 415 * 115 * 420 mm Carton size: 485 * 430 * 440 mm G.W.: 16kgs N.W.: 12kgs Qty per 20ft 1200pcs Qty per 40ft 2400pcs Qty per 40HQ 2600pcs M.O.Q.: 1200pcs

- 120V 60Hz 1300W
- Vitroceramic Glass plate
- Brushed Stainless steel frame
- Digital timer display
- Six level power adjustable
- Soft touch control panel
- Auto pan detection
- ETL certificate approval

Model:

IC-40

6pcs/CTN

Carton size: 535 * 360 * 420 mm

Qty per 20ft 2160pcs Qty per 40ft 4374pcs M.O.Q.: 500pcs

- 1600W/120V/60Hz
- Silver color plastic housing
- Heat-resistant ceramic glass, full in black color
- base: ABS material
- LED display
- 10 power levels (400-2000W)
- 10-level temperature setting
- Temperature range: 60-240°C
- Timer: up to 3 hours(180minutes) use with 5 minutes intervals
- Electronic overheating protection

