



Texture Mapping

Pasting textures on surfaces



Coordinate Systems Involved


FIGURE 8.35 Drawing texture on several objects of different shape.




$$(s_x, s_y) = T_{ws}(T_{tw}(s, t))$$

Textures are Images

They are always assigned the shown
parametric coordinates (s,t)



Texture to Screen




$$(s_x, s_y) = T_{ws}(T_{tw}(s, t))$$

We would have to calculate pixel coverages

Screen to Texture

Better approach



$$(s,t) = T_{wt}(T_{sw}(s_x, s_y))$$

Requires inverting the projection matrix

From Texture to World (Object)

To apply a texture to an object, we must find a correspondance between (s,t) and some object coordinate system

- Mapping via a parametric representation of the object space
- Manually

Mapping the Texture to an Object Parametric Representation

Linear transformation

From texture space (s,t) to object space (u,v)

$$u = u(s,t) = a_u s + b_u t + c_u$$

$$v = v(s,t) = a_v s + b_v t + c_v$$

$$s \text{ in } [0,1]$$


$$t \text{ in } [0,1]$$

Example 1: Image to a Quadrilateral

Simply

$$u = u(s,t) = s$$

$$v = v(s,t) = t$$



```
glTexCoord2f(0,0) ; glVertex3dv(v1) ;
```

```
glTexCoord2f(1,0) ; glVertex3dv(v2) ;
```

```
glTexCoord2f(1,1) ; glVertex3dv(v3) ;
```


```
glTexCoord2f(0,1) ; glVertex3dv(v4) ;
```

Example 2: Piece of Image to a Quadrilateral

Use only left part

$$u = u(s, t) = 0.55s$$

$$v = v(s, t) = t$$



```
glTexCoord2f(0,0) ; glVertex3dv(v1) ;
```


```
glTexCoord2f(0.55,0) ; glVertex3dv(v2) ;
```

```
glTexCoord2f(0.55,1) ; glVertex3dv(v3) ;
```

```
glTexCoord2f(0,1) ; glVertex3dv(v4) ;
```

Packing textures for efficiency

Example 3: Square Texture to Cylinder



Parametric form of cylinder:


$$x = r \cos \theta, \quad y = r \sin \theta, \quad z$$

$$\text{Surface parameters: } u = \theta, \quad v = z$$

$$\text{with } 0 \leq u \leq \pi/2, \text{ and } 0 \leq v \leq 1$$

Example 3: Square Texture to Cylinder

Square texture to cylinder




We pick the following linear transformation that maps $(s, t) = (0, 0)$ to $(u, v) = (0, 0)$ and $(s, t) = (1, 1)$ to $(u, v) = (\frac{\pi}{2}, 1)$:

$$u = s\frac{\pi}{2}, \quad v = t$$

Example 3: Square Texture to Cylinder

From screen to texture



1. Inverse transform (s_x, s_y) to get world position (x, y, z) .
2. Then having (x, y, z) ,

$$u = \tan^{-1}(y/x), \quad v = z$$

$$s = 2u/\pi, \quad t = v$$


Wrapping Textures on Curved Surfaces

$$s = \frac{\theta - \theta_a}{\theta_b - \theta_a}, \quad t = \frac{z - z_a}{z_b - z_a}$$

Cylinder with N faces

Left edge at azimuth $\theta_i = 2\pi i / N$


Upper left vertex texture coordinates $s_i = \frac{\theta_i - \theta_a}{\theta_b - \theta_a}, \quad t_i = 1$




Guerrilla CG Tutorial 09: The Basics of UV Mapping



Example 4: Facial Capture





Capturing Facial Shape and Texture



Sampling Facial Shape


Fitted mesh nodes sample range data



Textured 3D Geometric Model


*Texture map
coordinates*

- Positions of fitted mesh nodes in RGB texture image



Example 5: Multiple Texture Maps Many Vertices and Texture Coordinates

Geometry + *Texture maps*



+ lighting =



How Does this Work With the Graphics Pipeline?

Only polygons

Only vertices go down the graphics pipeline


Interior points?

*Calculate texture coordinates by interpolation along
scanlines*


Rendering the Texture

Scanline in screen space

- Generating s, t coordinates for each pixel




Interpolation of Texture Coordinates




Problem

Perspective foreshortening

- Scan conversion takes equal steps along scanline in screen space
- Equal steps in screen space are **not** equal steps in world space



Reminder: In-Between Points



$$\left. \begin{aligned} R'_1(f) &= \frac{\text{lerp}(a_1, b_1, g)}{\text{lerp}(a_4, b_4, g)} \\ R'_1(f) &= \text{lerp}\left(\frac{a_1}{a_4}, \frac{b_1}{b_4}, f\right) \end{aligned} \right\} \Rightarrow g = \frac{f}{\text{lerp}\left(\frac{b_4}{a_4}, 1, f\right)}$$

substituting this in $R(g) = (1-g)A + gB$ yields

$$R_1 = \frac{\text{lerp}\left(\frac{A_1}{a_4}, \frac{B_1}{b_4}, f\right)}{\text{lerp}\left(\frac{1}{a_4}, \frac{1}{b_4}, f\right)} \quad \text{and similarly for } R_2 \text{ and } R_3$$

Rendering Images Incrementally


A maps to a (homogeneous)

B maps to b

C maps to c

D maps to d

For scanline y and two edges:



$$s_{left}(y) = \frac{\text{lerp}(\frac{s_A}{a_4}, \frac{s_B}{b_4}, f_l)}{\text{lerp}(\frac{1}{a_4}, \frac{1}{b_4}, f_l)}, \quad s_{right}(y) = \frac{\text{lerp}(\frac{s_C}{c_4}, \frac{s_D}{d_4}, f_r)}{\text{lerp}(\frac{1}{c_4}, \frac{1}{d_4}, f_r)}$$



Once we have s_{left} and s_{right} another hyperbolic interpolation fills in the scanline

Interpolation Along the Scanline

$$s_{left}(y) = \frac{\text{lerp}(\frac{s_A}{a_4}, \frac{s_B}{b_4}, f_l)}{\text{lerp}(\frac{1}{a_4}, \frac{1}{b_4}, f_l)},$$

$$s_{right}(y) = \frac{\text{lerp}(\frac{s_C}{c_4}, \frac{s_D}{d_4}, f_r)}{\text{lerp}(\frac{1}{c_4}, \frac{1}{d_4}, f_r)}$$

$$s(x, y) = \frac{\text{lerp}(\frac{s_{left}}{h_{left}}, \frac{s_{right}}{h_{right}}, f)}{\text{lerp}(\frac{1}{h_{left}}, \frac{1}{h_{right}}, f)}$$



What are f and the h 's?

Interpolation Along the Scanline


$$s_{left}(y) = \frac{\text{lerp}(\frac{s_A}{a_4}, \frac{s_B}{b_4}, f_l)}{\text{lerp}(\frac{1}{a_4}, \frac{1}{b_4}, f_l)}, \quad s_{right}(y) = \frac{\text{lerp}(\frac{s_C}{c_4}, \frac{s_D}{d_4}, f_r)}{\text{lerp}(\frac{1}{c_4}, \frac{1}{d_4}, f_r)}$$

$$s(x, y) = \frac{\text{lerp}(\frac{s_{left}}{h_{left}}, \frac{s_{right}}{h_{right}}, f)}{\text{lerp}(\frac{1}{h_{left}}, \frac{1}{h_{right}}, f)}$$

$$h_{left} = \text{lerp}(a_4, b_4, f_l)$$

$$h_{right} = \text{lerp}(c_4, d_4, f_r)$$

$$f = (x - x_{left}) / (x_{right} - x_{left})$$



Interpolating Information (Incrementally)

**Texture coordinates,
Color, Normal, etc.**

Right edge (1,2):


$$\frac{I_{r,(y+1)} - I_{r,y}}{(y+1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \Rightarrow I_{r,(y+1)} = I_{r,y} + \frac{I_1 - I_2}{y_1 - y_2}$$

Left Edge (1,3):

$$\frac{I_{l,(y+1)} - I_{l,y}}{(y+1) - y} = \frac{I_1 - I_3}{y_1 - y_3} \Rightarrow I_{l,(y+1)} = I_{l,y} + \frac{I_1 - I_3}{y_1 - y_3}$$

Along scanline:

$$\frac{I_{(x+1)} - I_x}{(x+1) - x} = \frac{I_r - I_l}{x_r - x_l} \Rightarrow I_{r,(y+1)} = I_{r,y} + \frac{I_r - I_l}{x_r - x_l}$$



Interpolating Information (Incrementally)

**Color, Normal,
Texture coordinates**

Right edge (1,2):


$$\frac{I_{r,(y+1)} - I_{r,y}}{(y+1) - y} = \frac{I_1 - I_2}{y_1 - y_2} \Rightarrow I_{r,(y+1)} = I_{r,y} + \frac{I_1 - I_2}{y_1 - y_2}$$

Left Edge (1,3):

$$\frac{I_{l,(y+1)} - I_{l,y}}{(y+1) - y} = \frac{I_1 - I_3}{y_1 - y_3} \Rightarrow I_{l,(y+1)} = I_{l,y} + \frac{I_1 - I_3}{y_1 - y_3}$$


Along scanline:

$$\frac{I_{(x+1)} - I_x}{(x+1) - x} = \frac{I_r - I_l}{x_r - x_l} \Rightarrow I_{r,(y+1)} = I_{r,y} + \frac{I_r - I_l}{x_r - x_l}$$



Constant along the line

Pipeline with Hyperbolic Interpolation



Light Maps

For static objects



Bump Mapping



Guerrilla CG Tutorial 10: Displacement and Bump Mapping



Procedural Texture

Volumetric textures

$$C = B(x,y,z)$$



