



Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

# Saliency Detection

## 显著性检测

Zhu Yafei

CVBIOUC

<http://vision.ouc.edu.cn/~zhenghaiyong>

March 24, 2015



# Contents

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

## 1 Background

## 2 Development

## 3 Features

## 4 Priors

## 5 Aggregation



# What?

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

A rich stream of visual data ( $10^8 - 10^9$  bits) enters our eyes every second.<sup>1</sup>

---

<sup>1</sup>K. Koch and J. McLean, “How much the eye tells the brain”, Current Biology, 2006.



# What?

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation



分辨率:  
500\*375



# What?

Saliency  
Detection

Background

Development

Features

Priors

Aggregation


$$500 \times 375 \times 3 \times 8 = 4500000 \text{ bit}$$



# What?

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# What?

Saliency  
Detection

Background

Development

Features

Priors


Aggregation





# What?

Saliency  
Detection



Background

Development

Features

Priors

Aggregation



# What?

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation






# Visual Attention

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Theory

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

- “*Feature Integration Theory*”, Treisman & Gelade, 1980.
- “*Guided Search Theory*”, Wolfe & Cave, 1989.
- “*Integrated Competition Theory*”, Desimone & Duncan, 1995.



# Framework

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

- Koch and Ullman<sup>1</sup> proposed a feed-forward model to combine features and introduced the concept of a *saliency map* which is a topographic map that represents conspicuousness of scene locations.
- Zoom Lens Model<sup>2</sup>

---

<sup>1</sup>C. Koch and S. Ullman, “Shifts in selective visual attention: towards the underlying neural circuitry”, Human Neurobiology, 1985.

<sup>2</sup>Eriksen, C.W., J.D. St. James. “Visual attention within and around the field of focal attention: a zoom lens model”, Perception and Psychophysics, 1986.




# Basic Structure of Computational Models

Saliency  
Detection

Background  
Development  
Features  
Priors

Aggregation






# Two Waves<sup>3</sup>

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation



<sup>3</sup>Ali Borji, Ming-Ming Cheng, "Salient object detection: a survey", 2014.



# Fixation Prediction

Saliency  
Detection

Background  
Development

Features

Priors

Aggregation

Fixation prediction models are constructed originally to understand human visual attention and eye movement prediction.





# Fixation Prediction: example

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Fixation Prediction: example

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Fixation Prediction: example

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Fixation Prediction: example

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Fixation Prediction: example

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Fixation Prediction: example

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Representative Work


Saliency  
Detection

Background  
Development  
Features

Priors

Aggregation

- A model of saliency-based visual attention for rapid scene analysis. PAMI 1998, Itti et al.






# Architecture

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation






# General Procedure of fixation prediction models

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation






# Salient Object Detection

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation




- Learning to detect a salient object. CVPR 2007, Tie Liu et al.
- Frequency-tuned salient region detection. CVPR 2009, Achanta et al.



# Latest research achievements

Saliency  
Detection  
  
Background  
Development  
  
Features  
  
Priors  
  
Aggregation



From left to right: PBS<sup>4</sup>、DRFI<sup>5</sup>、RBD<sup>6</sup>、HDCT<sup>7</sup>

<sup>4</sup>Chuan Yang et al., “Graph-regularized saliency detection with convex-hull-based center prior, IEEE Signal Processing Letters, 2013.

<sup>5</sup>Huaizu Jiang et al., “Salient object detection: a discriminative regional feature integration approach”, in CVPR, 2013.

<sup>6</sup>Wangjiang Zhu et al., “Saliency optimization from robust background detection”, in CVPR, 2014.

<sup>7</sup>Jiwhan Kim et al., “Salient region detection via high-dimensional color transform”, in CVPR, 2014.



# Why?


Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

The emergence of salient object detection models is driven by the requirement of saliency-based applications.



Content aware resizing



Object manipulation



Image montage

Image collage



# What can saliency not do?

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation






# General Procedure

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation





# Features

Saliency  
Detection

Background  
Development

Features

Priors

Aggregation

Salient object detection: A discriminative regional feature integration approach, CVPR 2013

## ■ 26 维颜色纹理等对比度特征

Color and texture features		dim	Differences of features		Contrast	Backgroundness
	features		definition	dim		
$a_1$	the average RGB values	3	$d(a_1^R, a_1^S)$	3	$c_1 \sim c_3$	$b_1 \sim b_3$
$a_2$	the average L*a*b* values	3	$d(a_2^R, a_2^S)$	3	$c_4 \sim c_6$	$b_4 \sim b_6$
$r$	the absolute response of LM filters	15	$d(r^R, r^S)$	15	$c_7 \sim c_{21}$	$b_7 \sim b_{21}$
$r$	the max response among the LM filters	1	$d(r^R, r^S)$	1	$c_{22}$	$b_{22}$
$h_1$	the L*a*b* histogram	$8 \times 16 \times 16$	$\chi^2(h_1^R, h_1^S)$	1	$c_{23}$	$b_{23}$
$h_2$	the hue histogram	8	$\chi^2(h_2^R, h_2^S)$	1	$c_{24}$	$b_{24}$
$h_3$	the saturation histogram	8	$\chi^2(h_3^R, h_3^S)$	1	$c_{25}$	$b_{25}$
$h_4$	the texton histogram	65	$\chi^2(h_4^R, h_4^S)$	1	$c_{26}$	$b_{26}$

## ■ 34 维的区域特征

description		notation	dim	description		notation	dim
the average normalized x coordinates	$p_1$	1		the average normalized y coordinates	$p_2$	1	
the normalized perimeter	$p_7$	1		the 10th percentile of the normalized x coordinates	$p_3$	1	
the aspect ratio of the bounding box	$p_8$	1		the 10th percentile of the normalized y coordinates	$p_4$	1	
the variances of the RGB values	$p_9 \sim p_{11}$	3		the 90th percentile of the normalized x coordinates	$p_5$	1	
the variances of the L*a*b* values	$p_{12} \sim p_{14}$	3		the 90th percentile of the normalized y coordinates	$p_6$	1	
the variances of the HSV values	$p_{15} \sim p_{17}$	3		the variance of the response of the LM filters	$p_{18} \sim p_{32}$	15	
the normalized area	$p_{33}$	1		the normalized area of the neighbor regions	$p_{34}$	1	



# Features

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

- Pixel-based
  - Contrast:  $U_p(x) = \sum_{x' \in I \setminus \{x\}} D(x', x)$
  - Property: Geometric features
- Patch/Region/Superpixel-based
  - Contrast:  $U_r(A_i) = \sum_{1 \leq k \leq N, k \neq i} |\Lambda| D(\Lambda_k, \Lambda_i)$
  - Property: Geometric features, Appearance features
- Multi-scale based



# Contrast

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

- Color
- Texture



# Color

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

- *Color* is the visual perceptual property corresponding in humans to the categories called red, blue, yellow and others.
- *Color Space* is defined to identify colors numerically by their coordinates.



# Three Elements of Color

Saliency  
Detection


Background  
Development

Features

Priors

Aggregation

- Hue: What we think as “color”—yellow, orange, cyan and magenta are examples of different hues
- Saturation: Saturation refers to the relative purity or the amount of white light mixed with a hue
- Intensity





# Coding methods for humans

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

- **RGB** is an additive system (add colors to black) used for displays.
- **CMY** is a subtractive system for printing.
- **HSI** is a good perceptual space for art, psychology, and recognition.
- **YIQ** is used for TV and is good for compression.




# Device-dependent spaces

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

## ■ RGB、CMYK






# Transformation

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

Almost all the color spaces can be transformed from RGB color space.





# Color Histogram

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

- 对图像的颜色空间进行量化
- 计算矩阵  $Q$
- 超像素分割
- 对每个超像素区域，依据其中像素点的坐标值，求出对应的矩阵  $Q$  中的值
- 求区域之间的直方图的对比度



# What is texture?

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

Texture is actually a very nebulous concept, often attributed to human perception, as either the feel or the appearance of (woven) fabric.<sup>8</sup>

---

<sup>8</sup>Mark S.Nixon and Alberto S.Aguado, “Feature Extraction & Image Processing for Computer Vision”, Publishing House of Electronics Industry, 2013.



# LBP(Local Binary Pattern, 局部二值模式)


Saliency  
Detection

Background  
Development

Features

Priors

Aggregation





# LBP


Saliency  
Detection

Background  
Development

Features

Priors

Aggregation





# Regional property descriptor

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

- Geometric feature descriptor
  - size
  - perimeter
  - position
  - area of the neighbor regions
- Appearance feature descriptor
  - the variances of the RGB values
  - the variances of the response of the LM filters



# Priors

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

- Center Prior/Location Prior
- Backgroundness Prior
- Boundary Connectivity Prior
- Color Prior
- Objectness Prior
- Smoothness Prior



# Center Prior/Location Prior

Saliency  
Detection

Background  
Development  
Features

Priors  
Aggregation

Objects near the image center are more attractive to people.<sup>9</sup>

This prior can be simply and effectively modeled as a Gaussian map.



$$S_D(\mathbf{x}) = \exp\left(-\frac{||\mathbf{x} - \mathbf{c}||_2^2}{\sigma_D^2}\right) \quad (1)$$

---

<sup>9</sup>Zhang, Lin and Gu, Zhongyi and Li, Hongyu, “SDSP: A novel saliency detection method by combining simple priors”, in ICIP, 2013.



# Center Prior/Location Prior

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

The salient object in an image is most probably placed near the center of the image.<sup>10</sup>

Gaussian falloff weight:

$$w_i^{(n)} = \exp(-9(dx_i^{(n)})^2/w^2 - 9(dy_i^{(n)})^2/h^2) \quad (2)$$



---

<sup>10</sup>Jiang, Huaizu and Wang, Jingdong, "Automatic salient object segmentation based on context and shape prior", in BMVC, 2011



# Center Prior/Location Prior

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

Assigning higher saliency to the image elements near the image center becomes invalid when the objects are placed far off the image center<sup>11</sup>.

- Compute a convex hull enclosing interesting points to estimate the location of salient region.
- Use the centroid of the convex hull as the center to get the convex-hull-based center prior map.



---

<sup>11</sup>Yang, Chuan and Zhang, Lihe and Lu, Huchuan, "Graph-regularized saliency detection with convex-hull-based center prior", in Signal Processing Letters, IEEE, 2013



# Backgroundness Prior

Saliency  
Detection

Background  
Development  
Features  
Priors

Aggregation

*Backgroundness prior* is more general than center prior because salient objects can be placed off the center, but they seldom touch the image boundary.<sup>12</sup>

- Assuming that a narrow border of the image is background region, regional saliency can be computer as the contrast versus “background”.

---

<sup>12</sup>Wei, Yichen and Wen, Fang and Zhu, Wangjiang, “Geodesic saliency using background priors”, in ECCV, 2012.




# Boundary Connectivity Prior

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

Object regions are much less connected to image boundaries than background ones.<sup>13</sup>



*Boundary connectivity* is defined to quantify how heavily a region R is connected to the image boundaries.

$$BndCon(R) = \frac{|\{p | p \in R, p \in Bnd\}|}{\sqrt{|\{p | p \in R\}|}} \quad (3)$$

---

<sup>13</sup>Zhu, Wangjiang and Liang, Shuang, “Saliency optimization from robust background detection”, in CVPR, 2014.



# Color Prior

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

Warm colors, such as red and yellow, are more pronounced to the human visual system than cold colors, such as green and blue.<sup>14</sup>

$$f_{an}(\mathbf{x}) = \frac{f_a(x) - mina}{maxa - mina}, f_{bn}(\mathbf{x}) = \frac{f_b(x) - minb}{maxb - minb} \quad (4)$$

$$S_c(\mathbf{x}) = 1 - exp\left(-\frac{f_{an}^2(\mathbf{x}) + f_{bn}^2(\mathbf{x})}{\sigma_c^2}\right) \quad (5)$$

- $a^*$ -channel represents green-red information
- $b^*$ -channel represents blue-yellow information

---

<sup>14</sup>Zhang, Lin and Gu, Zhongyi and Li, Hongyu, "SDSP: A novel saliency detection method by combining simple priors", in ICIP, 2013.



# Objectness Prior

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

*Objectness* is defined as the probability of there being a complete object in a local window centered on each pixel.<sup>15</sup>

- Randomly sample  $N$  windows over the image
- Assign each window  $w$  a probability score  $P(w)$  to indicate its objectness
- Sum all the probability scores in windows that contains pixel  $x$

$$O_p(x) = \sum_{w \in W \text{ and } x \in w} P(W_x) \quad (6)$$

---

<sup>15</sup>Jiang, Peng and Ling, Haibin, “Salient region detection by ufo: uniqueness, focusness and objectness”, in ICCV, 2013



# Smoothness Prior

Saliency  
Detection

Background  
Development  
Features  
Priors

Aggregation

*Smoothness* constraint is often encoded by adding a pair-wise potential to the energy function which encourages neighboring pixels in the image to take the same label.<sup>16</sup>

$$w_{ij} = \exp\left(-\frac{\|c_i - c_j\|}{2\sigma_w^2}\right) \quad (7)$$

$$E(S) = \sum_i (S(i) - S_i n(i))^2 + \lambda \sum_{i,j} w_{ij} (S(i) - S(j))^2 \quad (8)$$

---


<sup>16</sup>Yang, Chuan and Zhang, Lihe and Lu, Huchuan, "Graph-regularized saliency detection with convex-hull-based center prior", in Signal Processing Letters, IEEE, 2013.



# Example: SDSP<sup>17</sup>

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation



<sup>17</sup>Zhang, Lin and Gu, Zhongyi and Li, Hongyu, "SDSP: A novel saliency detection method by combining simple priors", in ICIP, 2013.



# Non-linear<sup>18</sup>

Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

Combining the focusness, the objectness and the uniqueness maps:

$$S = \exp(F + U) \times O \quad (9)$$

---

<sup>18</sup>Peng Jiang et al., “Salient region detection by ufo: Uniqueness, focusness and objectness”, in ICCV, 2013.



# Energy minimization<sup>19</sup>

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

The ideal output of salient object detection is a clean binary object/background segmentation.

$$\underbrace{\sum_{i=1}^N w_i^{bg} s_i^2}_{\text{background}} + \underbrace{\sum_{i=1}^N w_i^{fg} (s_i - 1)^2}_{\text{foreground}} + \underbrace{\sum_{i,j} w_{ij} (s_i - s_j)^2}_{\text{smoothness}}$$

---

<sup>19</sup>Wangjiang Zhu and Shuang Liang, "Saliency Optimization from Robust Background Detection", in CVPR, 2014.



# Machine Learning<sup>20</sup>

Saliency  
Detection

Background

Development

Features

Priors

Aggregation

Training examples:

- a set of confident regions  $R = \{R_1, R_2, \dots, R_Q\}$
- the responding saliency scores  $A = \{a_1, a_2, \dots, a_Q\}$

---

<sup>20</sup>Huaizu Jiang et al., “Salient object detection: a discriminative regional feature integration approach”, in CVPR, 2013.



Saliency  
Detection

Background  
Development  
Features  
Priors  
Aggregation

Thanks

*Yafei Zhu*  
Ocean University of China  
*2015.03*