

# MLP&CNN

Jinna

School of information science and engineering

2016.9.26





计算机视觉实验室

# CONTENT

Training and testing code of MLP

What I learned from coding MLP

Introduction of CNN

Application of CNN

Conclusion



Training and testing code of MLP

计算机视觉实验室


Header File Here!

Code Here!



计算机视觉实验室


## Training and testing code of MLP






# 计算机视觉实验室

## Training and testing code of MLP





## Training and testing code of MLP





计算机视觉实验室

## What I learned from this process

C

1. Remember initializing variables
2. Organize your logic
3. Recommend using class, header File

MLP


4. Reset values
5. BP & gradient descent
6. Choose right activation function
7. Batch\_size
8. Coding is difficult but interesting



## Introduction of CNN

# CNN: Convolutional Neural Network

计算机视觉实验室







# CNN Net:

**LeNet**

**AlexNet**

**VGG Net**


**GoogLeNet**



## Introduction of CNN

### LeNet:

# 计算机视觉实验室






计算机视觉实验室

## Introduction of CNN

LeNet:







# Application of CNN

## 计算机视觉实验室

**Towards Convolutional Neural Networks Compression via Global Error Reconstruction**

Shaohui Lin<sup>1</sup>, Rongrong Ji<sup>1\*</sup>, Xiaowei Guo<sup>2</sup>, Xuelong Li<sup>3</sup>

<sup>1</sup>Xiamen University <sup>2</sup>Tencent BestImage <sup>3</sup>Chinese Academy of Sciences  
Contact: rrji@xmu.edu.cn

腾讯优图

### Introduction

- Convolutional neural networks have demonstrated impressive performance in various computer vision applications. However, the storage cost of CNNs is so essentially huge that cannot be directly deployed on mobile phones or embedding devices.
- A big limitation of state-of-the-art methods, i.e., a layer-wise parameter compression which only considered "implicit" compression and might magnify and propagate quantization error.
- A novel framework towards an "explicit" and "global" compression of CNNs: a Global Error Reconstruction which explicitly models the global reconstruction error between the outputs of both original and compressed CNNs and jointly compresses both weight parameters of inter-layer and intra-layer relationships.

### Three contributions:

- introduce an explicit objective function to directly minimize the reconstruction error of outputs.
- globally model the inter-layer correlation during the network compression.
- introduce an effective optimization method to solve the corresponding non-convex optimization.

### The Proposed Model

Framework of our compression for CNN via global error reconstruction

### Quantitative Evaluations

Datasets: ImageNet 2012

Quantitative Comparisons of Rate-Distortion curves between the proposed algorithm and alternatives

**Baselines:**

- GER-IC;
- LRD;
- BIN;
- PQ;
- AS.

### Model Components

**(1) Layer-by-layer Initialization by Alternating Optimization:**

- Consider non-linear function (e.g. ReLU), we want to minimize
 
$$\min_{\mathbf{W}} \sum_{i=1}^N \|f(\mathbf{W}^T \mathbf{a}_i^l) - f(\mathbf{W}^{l-1} \mathbf{a}_i^{l-1})\|^2 \quad (1)$$

$$s.t. \text{rank}(\mathbf{W}^l) \leq k_l$$
- Rewriting Eq. 1 and relax it to
 
$$\min_{\mathbf{W}} \sum_{i=1}^N \|f(\mathbf{W}^l \mathbf{a}_i^l) - f(\mathbf{W}^{l-1} \mathbf{a}_i^{l-1})\|^2 + \lambda \sum_{i=1}^N \|\mathbf{y}_i^{l-1} - \mathbf{W}^{l-1} \mathbf{c}_i^{l-1}\|^2 \quad (2)$$

$$s.t. \text{rank}(\mathbf{W}^l) \leq k_l$$
- Alternating step I: Fix  $\mathbf{y}_i^{l-1}$  and update  $\mathbf{W}^l$ 

$$\min_{\mathbf{W}} \sum_{i=1}^N \|\mathbf{y}_i^{l-1} - \mathbf{W}^l \mathbf{c}_i^{l-1}\|^2 \rightarrow \min_{\mathbf{W}} \|\mathbf{Y}^{l-1} - \mathbf{W}^l \mathbf{C}^{l-1}\|_F^2 \quad \text{Solved by GSVD}$$

$$s.t. \text{rank}(\mathbf{W}^l) \leq k_l$$
- Alternating step II: Fix  $\mathbf{W}^l$  and update  $\{\mathbf{y}_i^{l-1}\}$ 

Rewrite Eq. 2 to 1-dimensional optimization process

$$\min_{\mathbf{y}} (f(\mathbf{y}_i^{l-1}) - f(\mathbf{W}^l \mathbf{c}_i^{l-1}))^2 + \lambda (\mathbf{y}_i^{l-1} - \mathbf{W}^{l-1} \mathbf{c}_i^{l-1})^2 \rightarrow \begin{cases} \mathbf{y}_i^{l-1} = \min(0, \mathbf{z}_i^{l-1}) \\ \mathbf{y}_i^{l-1} = \max(0, \frac{\mathbf{z}_i^{l-1} + f(\mathbf{W}^l \mathbf{c}_i^{l-1})}{2}) \end{cases} \quad (3) \quad (4)$$

Obtain  $\mathbf{y}_i^{l-1} = \mathbf{y}_i^{l-1}$  if  $\mathbf{y}_i^{l-1}$  is smaller than  $\mathbf{y}_i^{l-1}$ , otherwise  $\mathbf{y}_i^{l-1} = \mathbf{y}_i^{l-1}$ .

**(2) Cross-layer Compression via Global Error Reconstruction (Updating):**

- Minimize the global reconstruction error of non-linear responses
 
$$\min_{\mathbf{W}} \sum_{i=1}^N \|\mathbf{a}_i^m - f(\mathbf{W}^m \mathbf{a}_i^{m-1})\|^2 \quad (5)$$

$$s.t. \text{rank}(\mathbf{W}^m) \leq k_m, \quad m = 0, 1, \dots, M-1$$

Where  $\mathbf{a}_i^m = f(\mathbf{W}^{m-1} \mathbf{a}_i^{m-1})$ , and use the solution of Eq. 1 to relax the constrain term of Eq. 5, rewrite Eq. 5 as

$$\mathcal{J}(\mathbf{P}, \mathbf{Q}, \mathbf{X}, \mathbf{A}) = \frac{1}{2} \|\mathbf{P} - \mathbf{A}\|^2$$

$$\mathbf{A}^* = f(\mathbf{P}^* \mathbf{Q}^{m-1}) = \mathbf{P}^* \mathbf{Q}^{m-1} \mathbf{X}^*$$

Initialization by approximate decomposition of  $\mathbf{W}$  solving Eq. 1
- Learn parameters  $\{\mathbf{P}^l\}$  and  $\{\mathbf{Q}^l\}$  by SGD with BP
 
$$\frac{\partial \mathcal{J}(\mathbf{P}, \mathbf{Q}, \mathbf{X}, \mathbf{A})}{\partial \mathbf{P}} = \mathbf{A}^* - \mathbf{P}^T \mathbf{Q}^T \quad (6)$$

$$\frac{\partial \mathcal{J}(\mathbf{P}, \mathbf{Q}, \mathbf{X}, \mathbf{A})}{\partial \mathbf{Q}} = \mathbf{P}^T \mathbf{A}^* - \mathbf{P}^T \mathbf{Q}^T \quad (7)$$

$$\frac{\partial \mathbf{A}^*}{\partial \mathbf{P}} = \frac{\partial f}{\partial \mathbf{A}} \mathbf{A}^* = \mathbf{A}^* \mathbf{A}^{*T} \mathbf{A}^*, \quad \mathbf{A}^* = \mathbf{A}^* \mathbf{A}^{*T} \mathbf{A}^*, \quad \text{otherwise}$$

$$\frac{\partial \mathbf{A}^*}{\partial \mathbf{Q}} = \frac{\partial f}{\partial \mathbf{A}} \mathbf{A}^* = \mathbf{A}^* \mathbf{A}^{*T} \mathbf{A}^*$$

Weekly meeting 9.26



计算机视觉实验室

**Thanks for your attention !**



计算机视觉实验室

# Q&A