

---

# Hearts

---

Kevin Miller

([kmiller4@stanford.edu](mailto:kmiller4@stanford.edu))

---

# Administrivia

---

- GraphViz due tonight at midnight or tomorrow at midnight with 1 late day
  - Office Hours: Tonight 6-9
  - Email [cs106l-aut1314-staff@lists.stanford.edu](mailto:cs106l-aut1314-staff@lists.stanford.edu) for questions
-

# How to Play Hearts

---

A♥	7♥	3♥	J♥	4♣	6♣	K♦	9♦	7♠	6♠	Q♠
----	----	----	----	----	----	----	----	----	----	----

Hearts: 1 point each



# How to Play Hearts

---

A♥	7♥	3♥	J♥	4♣	6♣	K♦	9♦	7♠	6♠	Q♠
----	----	----	----	----	----	----	----	----	----	----

Hearts: 1 point each

Non-Hearts: 0 points each

Queen of Spades: 13 points

# How to Play Hearts

---

1. Leader plays card
  2. Everyone else matches suit if possible
  3. Highest value of leader's suit wins
  4. Winner becomes new leader
-

# Key Point

---

Ordering of players is preserved

- Who goes first changes but play always progresses counter clockwise

# Terminology

---

- Trick: a single event where each player plays a card and the winner takes them
  - Round: 13 tricks
  - Leader: person who plays first card of the trick
  - Match Suit: playing a card of the same suit as the leader
-



# Strategy

---

- Leader plays the lowest card they have left
  - Others plays lowest card possible if they can match suit or highest card otherwise
-

# Quick Enumeration

---

An enumerated type is an int that takes on a specific range and each value has a name

Allows a variable to be a set of predefined constants

---

# Quick Enumeration

---

```
enum Direction {  
    LEFT, //has value 0  
    RIGHT //has value 1  
};
```

```
Direction zoolander = RIGHT;  
int n = 2 * zoolander; //n==2
```

---

# Let's Do It!

---

Coding Time!

---

# random\_shuffle

---

Parameters: iterator begin, iterator end

Return: none

Function: shuffles the elements between begin and end

---

# find\_if

---

**Parameters:** iterator begin, iterator end, bool function isValid

**Return:** iterator to the first element matching comparator or end if no element is found

**Function:** finds an element that isValid if it exists

---

# copy

---

Parameters: iterator begin, iterator end, iterator copy location

Return: none

Function: copies the elements from begin to end to location

---

# copy

---

- Random access iterators can be incremented using `+` and `+=`
  - same as doing `++` a set number of times in a for loop
  - makes accessing particular elements easy
-



# sort

---

Parameters: iterator begin, iterator end, bool comparator function

Return: none

Function: sorts the elements from begin in ascending order

---

# Comparator Function

---

- Many algorithms and containers have a concept of order
  - Ascending order  $\rightarrow n1 < n2 < \dots$
  - A Comparator Function in C++ is a function that determines whether one element is less than another
  - Equivalent to implementing the ' $<$ ' operator
-

# min\_element/max\_element

---

**Parameters:** iterator begin, iterator end, bool comparator function

**Return:** iterator to the min/max element

**Function:** finds the min/max element between begin and end

---

# equal\_range

---

**Parameters:** iterator begin, iterator end, v, bool comparator function

**Return:** a pair of iterators denoting the begin and end of a range of equal value or end if no range exists

**Function:** similar to lower\_bound from city finder. Finds a range that has a certain value

---

# rotate

---

Parameters: iterator begin, iterator middle, iterator end

Return: none

Function: rotates the collection such that middle is now first while preserving ordering

---