

---

# STL Algorithms

---

Reid Watson  
([rawatson@stanford.edu](mailto:rawatson@stanford.edu))

---

# Administrivia

---

- Office hours: Tuesday 6-12, Thursday 8-12
  - Assignment one is still out
  - Qt Creator
-


# STL Algorithms

---

- Iterators and why they exist
  - STL `<algorithm>`
  - Iterator adapters
-

# STL Iterators

---



# STL Iterators

---

## The Blue Pill:

Iterators are an inconvenient way to access all the elements in a set

## The Blue Pill:

Iterators are the building block for accessing, modifying, and using all sorts of collections

---

# STL Iterators

---

- Last class we talked about iterators
  - Iterators allowed us to access all the elements in a container in a linear order, even if the container was unordered
  - This was convenient, but the syntax seemed a bit awkward, especially looking at Stanford foreach or C++11 range based for
-

# STL Iterators

---

Printing the contents of a vector of integers (say the vector was named 'v') using iterators.

```
vector<int>::iterator i = v.begin();  
while (i != v.end()) {  
    cout << *i << endl;  
    ++i;  
}
```

---

# STL Iterators

---

Printing the contents of a vector of integers (say the vector was named 'v') using C++11 range based for.

```
for (int x : v) {  
    cout << x << endl;  
}
```



# STL Iterators

---

Why do we still use iterators if the syntax is so awkward?

---

# STL Iterators

---

Let's introduce a different picture of the STL, in terms of **abstraction**

---

# Abstraction in the STL


---

**abstraction** allows us to express the general structure of a problem instead of the particulars of implementation

---

# Abstraction in the STL

---



# Abstraction in the STL

---

- We began by talking about **basic types**.
  - **char, int, double, string**, others.
  - Each of these types held what was conceptually a "single value"
-

# Abstraction in the STL

---

- Many programs require a number of variables of the same basic type
    - A vector of integers representing student's ages
    - A mapping translating between names and addresses
  - **Containers** allow a programmer to use the same collection regardless of the underlying basic type
  - The same `<vector>` implementation can be used for `ints` as well as `strings`
-

# Abstraction in the STL

---

- The same `<vector>` implementation can be used for `ints` as well as `strings`
  - This means we can use containers to perform various operations on **basic types**, regardless of what the basic type is?
  - Is it possible to perform various operations on **containers** regardless of what the container is?
-

# Abstraction in the STL


---

- Iterators allow us to abstract away which container was used
    - Similar to how containers allow us to abstract away which basic type was used
  - Operations like sorting, partitioning, filtering, searching, etc., can be written to work with a **vector**, **deque**, **set**, or any other data type.
  - We call these operations the STL **algorithms**
-



# Abstraction in the STL

---



# Examples of Algorithms

---

Let's take a look at why this is cool.  
See [AlgorithmFun.pro](http://AlgorithmFun.pro)

---

# Why Algorithm

---

Why do we need this complex model of abstraction?

- Don't **duplicate** code
  - Write **correct** code
  - Write **efficient** code
  - Write **clear** code
-

# Why Algorithm

---

To take a look at what's possible with  
<algorithm>, let's write a quick magic square  
solver.

---

# Why Algorithm

---

A "magic square" is a 3x3 grid in which all rows, columns, and 3-element diagonals sum to the same number.

2	7	6
9	5	1
4	3	8

# Why Algorithm

---

A "magic square" is a 3x3 grid in which all rows, columns, and 3-element diagonals sum to the same number.

2	7	6
9	5	1
4	3	8

# Why Algorithm

---

A "magic square" is a 3x3 grid in which all rows, columns, and 3-element diagonals sum to the same number.

2	7	6
9	5	1
4	3	8

# Why Algorithm

---

A "magic square" is a 3x3 grid in which all rows, columns, and 3-element diagonals sum to the same number.


2	7	6
9	5	1
4	3	8



# Why Algorithm

---

We'll represent a magic square as a linear vector of elements



# Why Algorithm

---

If we could enumerate through every permutation of the numbers 1-9 in a vector, we could find every magic square which uses only the numbers 1-9...

If only we had an `<algorithm>` to do that...

---

# Why Algorithm

---

Let's take a look at some code to solve this in  
MagicSquares.pro

---

# In-depth: `std::copy`

---

To understand iterators and algorithms a bit better, let's take a look at the `copy` function.

```
vector<int> v;  
v.push_back(1);  
v.push_back(650);  
v.push_back(867);  
v.push_back(5309);
```

```
vector<int> vcopy(4);
```

```
copy(v.begin(), v.end(), vcopy.begin());
```

---

# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

0	0	0	0
---	---	---	---

---

# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

1	0	0	0
---	---	---	---

# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------



vcopy:

1	650	0	0
---	-----	---	---

# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

1	650	867	0
---	-----	-----	---





# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

1	650	867	5309
---	-----	-----	------



# In-depth `std::copy`

---

What happens if we didn't allocate enough space?

---

# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

0	0
---	---

# In-depth: `std::copy`

---

v:

1	650	867	5309
---	-----	-----	------



vcopy:

1	0
---	---

# In-depth: `std::copy`

---

v:

1	650	867	5309
---	-----	-----	------



vcopy:

1	650
---	-----

# In-depth: std::copy

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

1	650
---	-----



# In-depth: `std::copy`

---

How can we avoid running into this problem?

---

# Iterator Adapters

---

Sometimes we need to form "weird" iterators.

- We don't just want to iterate over elements, we want to retrieve them from an istream
- We don't just want to iterate over elements we want to add them to a vector



# Iterator Adapters

---

Stream iterators are a fun way to simplify code. When you want to repeatedly read values from an input streams.

You can also form iterators which write values to a stream for you.

It's easiest to explain these with a quick bit of code demonstrating how they work.

---

# Iterator Adapters

---

See code in Sum.pro

---

# Iterator Adapters

---

**Inserters** create an iterator which inserts values into a container for you.

These are useful when using something like `std::copy`.

---

# Iterator Adapters

---

Using a back inserter will push the elements to the end of vcopy, so you don't have to worry about vcopy not having enough space.

```
vector<int> v;  
v.push_back(1);  
v.push_back(650);  
v.push_back(867);  
v.push_back(5309);
```

```
vector<int> vcopy;
```

```
copy(v.begin(), v.end(), back_inserter(vcopy));
```

---

# Iterator Adapters

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

---

# Iterator Adapters

---

v:

1	650	867	5309
---	-----	-----	------



vcopy:

1
---

# Iterator Adapters

---

v:

1	650	867	5309
---	-----	-----	------



vcopy:

1	650
---	-----

# Iterator Adapters

---

v:

1	650	867	5309
---	-----	-----	------



vcopy:

1	650	867
---	-----	-----



# Iterator Adapters

---

v:

1	650	867	5309
---	-----	-----	------

vcopy:

1	650	867	5309
---	-----	-----	------

