

Adapting Level of Traffic Stress for England: A Network-Scale Cycling Infrastructure Assessment in the West Midlands

Zhengpei Xu

Student Number: 25034404

MRes Dissertation (CASA0004)

Supervisor: Prof Duncan Smith

Code and supplementary material:

<https://github.com/zhengpei-xu/...>

Word Count: XX,XXX

August 2026

*This dissertation is submitted in part requirement for the MRes in the Centre for
Advanced Spatial Analysis, Bartlett Faculty of the Built Environment, UCL.*

Abstract

Declaration

I hereby declare that this dissertation is all my own original work and that all sources have been acknowledged. It is XX,XXX words in length.

Zhengpei Xu

August 2026

Acknowledgements

Contents

Abstract	i
Declaration	ii
Acknowledgements	iii
List of Acronyms and Abbreviations	viii
1 Introduction	1
2 Literature Review	3
2.1 Infrastructure Quality, Perceived Safety, and Cycling Participation	3
2.2 LTN 1/20: Design Standards for Cycling Infrastructure in England	4
2.3 Level of Traffic Stress: Origins, Framework, and Applications	6
2.4 Growing Fragmented Cycling Networks	7
2.5 Research Gap and Questions	8
3 Study Area and Data	10
3.1 Study Area: The West Midlands	10
3.2 Data Sources: Overview	11
4 Methodology	13
4.1 Cyclable Network Extraction and Infrastructure Classification	13
4.2 Link-level LTS classification	15
4.3 Junction LTS Classification	15
4.4 Stress-Based Network Connectivity Evaluation	15
4.5 Network Growth Simulation	15
5 Results	16
5.1 Network Composition and LTS Distribution	16
5.2 Data Source Comparison	16
5.3 Fragmentation	16
5.4 Reach and Accessibility	16
5.5 OD Connectivity	16
5.6 Network Growth Simulation	16
6 Discussion	17
6.1 Evaluating the Cycling for All Principle	17

6.2	Junction Stress as a Structural Barrier	17
6.3	Implications for Network Planning	17
6.4	Limitations	17
6.5	Future Work	17
7	Conclusion	18
	Bibliography	19
A	Supplementary Material	27
B	Research Log	28

List of Figures

1	Structure of the LTN 1/20 evaluation framework, comprising the Cycling Level of Service (CLoS) and the Junction Assessment Tool (JAT), and their combined role in determining Active Travel England funding eligibility. Compiled by author from Department for Transport DfT (2020a).	5
2	Study Area: The West Midlands. Left: location within England. Right: population distribution across the seven constituent metropolitan boroughs (Census 2021, 1 dot = 10 people), with hatched areas indicating rural Output Areas (OAs).	10
3	Analytical framework. LTN 1/20 design criteria (left) supply the classification thresholds operationalised on OS NGD Transport data (right) through Sections 4.1–4.3. The classified network is then evaluated against LTN 1/20's "Cycling for All" principle through connectivity analysis (Section 4.4) and network growth simulation (Section 4.5).	13

List of Tables

1	Level of Traffic Stress classification and corresponding population groups.	6
2	Datasets used in this study.	12
3	Highway Dedication types and legal cyclability under UK highway law.	14
4	Facility type classification derived from LTN 1/20 design hierarchy, mapped to OS NGD data sources.	15

List of Acronyms and Abbreviations

AADT	Annual Average Daily Traffic
CLoS	Cycling Level of Service
JAT	Junction Assessment Tool
KDE	Kernel Density Estimation
LCC	Largest Connected Component
LSOA	Lower layer Super Output Area
LTN 1/20	Local Transport Note 1/20
LTS	Level of Traffic Stress
MSOA	Middle layer Super Output Area
OD	Origin–Destination
OS NGD	Ordnance Survey National Geographic Database
OSM	OpenStreetMap
TfWM	Transport for West Midlands
WMCA	West Midlands Combined Authority

1 Introduction

Cycling has been widely recognised as a sustainable mode of urban transport, offering co-benefits across public health, air quality, carbon reduction, and potential congestion alleviation (WHO 2022; IPCC 2023; EU 2024). Central to realising these benefits is the provision of high-quality, connected cycling infrastructure, which is consistently associated with higher cycling participation (Hull and O’Holleran 2014; Pistoll and Goodman 2014; Buehler and Dill 2016; Mölenberg et al. 2019). Reflecting this evidence, the UK Department for Transport published Local Transport Note 1/20, Cycle infrastructure design (LTN 1/20), in July 2020, establishing the most comprehensive national standards for cycling infrastructure design and assessment applicable to England and Northern Ireland to date (DfT 2020a). LTN 1/20’s evaluation tools, the Cycling Level of Service (CLoS) and the Junction Assessment Tool (JAT), give practitioners a rigorous means of appraising individual schemes, assessing road segments and junctions against detailed design criteria through structured manual audit (DfT 2020a). What they do not address is the network-level question: whether compliant segments cohere into a connected whole. Network-level cycling connectivity is a property of whole journeys rather than individual schemes: a single high-stress link or junction can render an otherwise compliant route unusable for the very cyclists the guidance seeks to serve. There is therefore a need for a data-driven, network-level methodology capable of evaluating cycling infrastructure quality across a city or region using standard open and mapping agency data.

The Level of Traffic Stress (LTS) framework offers such a network-level approach, classifying road segments and junctions by the population group willing to tolerate their traffic conditions: from LTS 1, conditions suitable for children and old people, through LTS 2, tolerable to most adults, to LTS 3 and 4, which only progressively smaller and more confident minorities will accept (Mekuria et al. 2012). Because each stress level maps onto a population group, the classification links infrastructure quality directly to mode shift potential: expanding the network usable at lower stress thresholds is what brings the broader population into cycling. LTS-based network analysis has since become the dominant approach in cycling connectivity and equity research (Louro et al. 2026). Its non-compensatory logic, under which a single high-stress attribute determines classification, aligns naturally with how traffic conditions deter potential cyclists. Yet most published LTS criteria were calibrated to North American road design conventions, and applications to British cities have relied on simplified adaptations of these criteria rather than national design guidance (Cervero et al. 2019; Jeong and Smith 2025). No LTS classification grounded in UK design standards has been developed systematically.

The data foundations for such a classification have only recently emerged. The Ordnance Survey National Geographic Database (OS NGD) Transport Theme provides authoritative network

geometry with attributes directly relevant to stress classification, including carriageway width, legal access designation, and probe-derived vehicle speeds. Its Cycle Lane feature collection, which achieved full national coverage in March 2026, records cycle lane width, direction of cycling travel and infrastructure type with facility descriptions aligned to LTN 1/20 terminology (OS 2026a). The simultaneous availability of a statutory design standard and a nationally consistent authoritative dataset creates the conditions under which cycling networks across England can be classified and evaluated against a single national benchmark.

This dissertation develops a directed Level of Traffic Stress classification derived from LTN 1/20 design criteria, operationalises it on OS NGD Transport data, and applies it to evaluate network-level cycling conditions in the West Midlands. The region presents a revealing setting for such an evaluation. Among English regions it combines the highest share of private motorised trips with a cycling mode share of approximately 0.9% (WMCA 2024), yet its transport authority has committed to delivering a 500-mile network of low-stress cycle routes (WMCA 2020). The distance between this ambition and current network conditions is precisely what a standards-based classification is designed to measure. The study, conducted in collaboration with Transport for West Midlands, makes contributions to methodology and data: the first LTS framework calibrated to English design standards systematically, incorporating directed junction assessment and roundabout-specific criteria; and the first independent assessment of the OS NGD Cycle Lane dataset. The classified network is then used to evaluate connectivity against LTN 1/20's own principle of "cycling for all", proceeding from infrastructure supply to the journeys that infrastructure enables: the extent and spatial distribution of low-stress provision, the degree to which low-stress links cohere into connected components rather than isolated fragments, the reach available to residents from where they live, and the proportion of everyday travel demand, for commuting and for access to schools, that the network can carry at each stress threshold. A network growth simulation then examines how the sequence in which high-stress links are upgraded shapes connectivity outcomes, comparing selection strategies that exploit network structure against uninformed investment. Together these analyses illustrate the range of strategic questions that a nationally consistent, standards-based classification can support.

2 Literature Review

This chapter reviews the literature underpinning a standards-based, network-level cycling assessment. Section 2.1 establishes why infrastructure provision shapes participation, locating the mechanism in perceived safety and uneven stress tolerance. Section 2.2 examines LTN 1/20 and the limits of its scheme-level instruments. Section 2.3 introduces the Level of Traffic Stress framework and its applications. Section 2.4 reviews network growth simulation. Section 2.5 identifies the resulting gaps and states the research questions.

2.1 Infrastructure Quality, Perceived Safety, and Cycling Participation

The widely reported positive association between infrastructure provision and cycling participation raises a prior question of why provision should exert this influence (Hull and O’Holleran 2014; Pistoll and Goodman 2014; Buehler and Dill 2016; Mölenberg et al. 2019). A substantial body of work answers this by locating the mechanism in safety, and more precisely in its subjective dimension: whereas objective safety concerns the recorded incidence of crashes and injuries, it is the perceived safety, or how safe cycling is felt to be, that most directly shapes the decision to cycle, particularly for prospective and occasional riders (Chaurand and Delhomme 2013; Sanders 2015; Manton et al. 2016). This distinction between objective and subjective safety is what the language of traffic stress was introduced to capture. Early work characterised the discomfort imposed on a cyclist by the speed, volume, and proximity of adjacent motor traffic as a graded property of the road environment rather than a binary of safe and unsafe (Sorton and Walsh 1994; Landis et al. 1997; Harkey et al. 1998). Framed this way, the stress a cyclist experiences is understood as a systematic response to the traffic conditions a facility exposes them to, so that it can be inferred from the road’s physical and operational characteristics rather than measured directly. The value of the concept is that it makes the deterrent effect of traffic legible in terms of design variables that infrastructure can be built to modify.

Critically, tolerance of this stress is not uniform across the population. Stated-preference studies consistently find that groups currently under-represented among cyclists, women in particular, express stronger preferences for separation from motor traffic than men, with weaker but converging evidence for older adults and for those cycling with children (Aldred et al. 2017). The latent demand that infrastructure investment seeks to convert is therefore concentrated precisely among those least willing to tolerate high-stress conditions. This population corresponds to the widely reported “interested but concerned” segment, individuals who would consider cycling if protected from stressful traffic environments and who represent the largest and most winnable constituency for mode shift (Geller 2009; Mekuria et al. 2012; Dill and McNeil 2013). Consequently, the relevant question is not only whether provision works for those already riding

in traffic, but whether it also extends to the stress-averse users at the other end of the spectrum, on whom further uptake depends.

The relationship between perceived safety and cycling participation cannot be understood solely from the characteristics of individual links. Route choice evidence consistently shows that cyclists are willing to accept substantial detours to avoid stressful links and crossings (Broach et al. 2012; Park and Akar 2019; Berghoefer and Vollrath 2023), indicating that routes are evaluated as integrated wholes rather than as collections of independent facilities. Where no acceptable alternative exists, a single hostile link or crossing becomes a bottleneck that can render an otherwise suitable route unacceptable (Mekuria et al. 2012; Furth et al. 2016; Furth et al. 2018). It follows that the infrastructure quality relevant to the stress-averse majority is a property of connected networks rather than of individual facilities, and that its assessment requires criteria referenced to the populations expected to use them, applied to whole journeys rather than isolated schemes.

2.2 LTN 1/20: Design Standards for Cycling Infrastructure in England

“A travel revolution in our streets, towns and communities will have made cycling a mass form of transit. Cycling and walking will be the natural first choice for many journeys with half of all journeys in towns and cities being cycled or walked by 2030” (DfT 2020b).

This ambitious goal, set out in the Gear Change white paper, marked an unprecedented elevation in UK active travel policy. To translate this political commitment into consistent design practice, the Department for Transport simultaneously published Local Transport Note 1/20 (LTN 1/20), the most comprehensive national guidance for cycling infrastructure design and assessment to date (DfT 2020a). To cater for the broadest range of cyclists and deliver on Gear Change’s ambition of mass cycling uptake, LTN 1/20 establishes as first principle that cycle infrastructure should be accessible to everyone “from 8 to 80 and beyond”, with inclusive design running through all aspects of implementation (DfT 2020a).

To assess whether infrastructure meets this standard, LTN 1/20 organises its evaluation framework around five core design principles derived from Dutch practice (CROW 2016) — Coherence, Directness, Safety, Comfort, and Attractiveness — and introduced two complementary assessment instruments. The Cycling Level of Service (CLoS) tool appraises link-level attributes across 25 subcriteria under these five principles, each scored 0-2 with designated critical failures that override the overall assessment; the Junction Assessment Tool (JAT) complements CLoS at junctions, with its three scoring tiers explicitly anchored to distinct user populations (Figure 1). With the establishment of Active Travel England (ATE) as the national inspectorate in 2022, these instruments became central to a formal compliance process: only schemes achieving a minimum CLoS score of 70%, with no critical failures and no red-scored turning movements under the JAT, are generally considered eligible for Active Travel Fund allocations (DfT 2020a). This mechanism has effectively transformed LTN 1/20 from advisory guidance into a binding

quality threshold for publicly funded cycling infrastructure.




Figure 1. Structure of the LTN 1/20 evaluation framework, comprising the Cycling Level of Service (CLOS) and the Junction Assessment Tool (JAT), and their combined role in determining Active Travel England funding eligibility. Compiled by author from Department for Transport DfT (2020a).

Despite this comprehensive coverage, LTN 1/20's evaluation tools present three structural limitations when considered as a framework for network-wide cycling assessment. Firstly, the CLOS and JAT are scheme-level audit instruments requiring on-site evaluation by trained assessors, an approach that cannot scale to the classification of all cyclable links across an urban network and that risks inconsistency where subcriteria demand qualitative judgement (Hancock and Parkin 2024). Secondly, the CLOS abandons the population-referenced framing that the JAT adopts for its scoring tiers, defining all 25 subcriteria in purely technical terms. This reflects a structural constraint: the subcriteria mix stress-determinant factors that do implicitly delineate population acceptability, such as motor traffic speed, volume, and segregation, with experience-quality factors that do not, such as wayfinding and cycle parking provision. Additive scoring methods of this kind are inherently compensatory, such that strong performance on one set of criteria can arithmetically offset weaknesses in another (Pais et al. 2022; Wang et al. 2022); applied to CLOS, a link may therefore satisfy the 70% threshold through strong performance on the latter while falling short on stress conditions that, though not critical failures, would nonetheless deter the majority of potential cyclists. Thirdly, while the CLOS includes coherence subcriteria that address route-level continuity, these assess attributes of individual links rather than the connectivity of the network as a whole. They cannot answer whether a cyclist can complete a journey from origin to destination entirely within tolerable traffic conditions, yet end-to-end low-stress connectivity between origins and destinations has been identified as the most fundamental determinant of whether a cycling network can attract the widest possible segment of the population (Mekuria et al. 2012; Wang et al. 2016; Lowry and Loh 2017).

2.3 Level of Traffic Stress: Origins, Framework, and Applications

Where LTN 1/20 aspires to design for all from 8 to 80 but operationalises this through a broad composite of design criteria, the Level of Traffic Stress (LTS) framework (Mekuria et al. 2012) makes population acceptability the sole organising principle of its classification. Mekuria et al. operationalised this by adapting Geller's (2009) four-part population typology, the "strong and fearless," "enthused and confident," "interested but concerned," and "no way, no how," validated by Dill and McNeil (2013), into an infrastructure classification. They subdivided Geller's "interested but concerned" to distinguish children from adults, yielding four LTS levels each anchored to a distinct population group: LTS 1 corresponds to children, demanding the greatest separation from traffic; LTS 2 to the mainstream "interested but concerned" adult majority, with criteria anchored to Dutch facility standards; LTS 3 to the "enthused and confident," comfortable with moderate traffic interaction; and LTS 4 to conditions tolerable only by the "strong and fearless" (Table 1). The "no way, no how," who would not cycle regardless of provision, have no corresponding level. To classify segments, LTS draws on the small number of road characteristics most directly associated with cycling stress, notably motor traffic speed, facility type and width, and the nature of intersection approaches and crossings, using readily observable attributes such as the number of traffic lanes as a proxy for variables like traffic volume that are rarely available at network scale (Mekuria et al. 2012; Furth et al. 2016; Furth et al. 2018; Bearn et al. 2018). Classification follows a non-compensatory rule: a segment's LTS is determined by its worst-performing attribute, so that a single high-stress condition is sufficient to determine the classification regardless of other favourable characteristics.

Table 1. Level of Traffic Stress classification and corresponding population groups.

LTS Level	Population Group and Description
LTS 1	Suitable for almost all cyclists, including children cycling independently
LTS 2	Tolerable to the mainstream adult population; anchored to Dutch design standards proven to attract broad demographic participation
LTS 3	Tolerable to experienced cyclists who prefer dedicated space but accept moderate traffic interaction
LTS 4	Tolerable only to the strong and fearless riders willing to integrate with fast or heavy traffic

The original LTS framework proposed systematic network connectivity measures based on the population-anchored classification, quantifying the share of origin-destination pairs connected at each stress threshold and demonstrating how targeted gap closures can substantially multiply low-stress connectivity (Mekuria et al. 2012; Furth et al. 2016). This approach has since been widely adopted: a scoping review by Schön et al. (2024) identified 25 studies employing LTS to classify network links by stress level, primarily to measure cumulative accessibility by quantifying destinations reachable via low-stress links within defined distance or time thresholds (Murphy and Owen 2019; Wasserman et al. 2019; Gehrke et al. 2025). Beyond cumulative measures, LTS-based analysis has been used to evaluate job accessibility through detour-ratio methods that

permit travel on higher-stress links when low-stress routing is substantially longer (Furth et al. 2016; Lowry and Loh 2017; Cabral et al. 2019), to assess transport equity by linking low-stress connectivity to socioeconomic indicators (Tucker and Manaugh 2018; Kent and Karner 2019), and to identify network barriers and prioritise infrastructure investment (Lowry and Loh 2017; Putta and Furth 2019). Collectively, LTS modelling and network filtering have become the dominant approaches in cycling accessibility and equity research (Louro et al. 2026).

Two limitations constrain the applicability of existing LTS implementations to the UK context. Firstly, all published criteria were calibrated to North American road design conventions, speed regimes, and infrastructure types, and no LTS classification grounded in UK design standards has been developed systematically. Although the framework has been applied to British cities (Cervero et al. 2019; Jeong and Smith 2025), these implementations relied on simplified criteria derived from North American conventions rather than national design guidance. Secondly, the progressive simplification of the original criteria for network-scale application has produced considerable methodological divergence, with Harvey et al. (2024) finding substantial disagreement across seven LTS methods applied to the same cities, underscoring the sensitivity of results to variable selection and threshold definitions. These two limitations motivate the approach taken in this study: rather than adapting any single North American LTS variant, the classification is grounded in LTN 1/20, a single national design standard that provides both the threshold structure and the population-acceptability logic needed to anchor an LTS classification to English conditions.

2.4 Growing Fragmented Cycling Networks

Cycling networks in most cities remain sparse and fragmented (Schoner and Levinson 2014; Szell et al. 2022; Reggiani et al. 2023), so how they should expand, and in what order, is a live planning question. Network growth simulation addresses this by modelling expansion as the sequential addition of edges under a selection rule, generating investment trajectories whose connectivity outcomes can be compared (Barthélemy and Flammini 2009; Xie and Levinson 2009; Szell et al. 2022). Approaches to cycling network growth simulation can be divided by direction of construction: forward approaches iteratively add edges, either expanding from an existing network by bridging disconnected components (Natera Orozco et al. 2020), growing from scratch around topologically central seed points (Szell et al. 2022), or prioritising segments on the street network by potential routed cycling demand (Mahfouz et al. 2023). Inverse approaches begin from an idealised complete network and greedily remove the least important edges to generate budget-indexed subnetworks (Steinacker et al. 2022). Both directions can incorporate topological centrality (Szell et al. 2022) or cycling demand to weight edge importance (Steinacker et al. 2022; Mahfouz et al. 2023). A recurring finding is that how a fragmented network is grown matters as much as how much is built. Natera Orozco et al. (2020) show across fourteen cities that small, targeted investments connecting disconnected components rapidly consolidate a bicycle network, far outperforming random, uncoordinated addition, while Szell et al. (2022) find that uninformed

growth needs several times the investment of a flow-based strategy before a connected network emerges.

These studies operate on networks defined by infrastructure presence, in which an edge either belongs to the cycling network or does not, and they deploy growth simulation to identify an optimal expansion sequence. Neither feature carries over to a stress-classified network, where the object of investment is the upgrading of existing high-stress links, and low-stress conditions arise as much from quiet residential streets as from dedicated facilities.

2.5 Research Gap and Questions

The preceding review establishes three gaps at the intersection of design standards, network assessment, and investment planning. First, while LTN 1/20 provides the most comprehensive national design standard for cycling infrastructure in England, its evaluation instruments remain confined to scheme-level audit. The CLoS’s compensatory scoring obscures the population-referenced acceptability that the standard’s “cycling for all” principle implies, and neither the CLoS nor the JAT can assess whether compliant schemes cohere into a network that connects origins to destinations at tolerable stress levels (Section 2.2), despite end-to-end low-stress connectivity being the most fundamental determinant of a network’s capacity to attract the wider population (Mekuria et al. 2012; Lowry and Loh 2017).

Second, the LTS framework supplies precisely the network-level, population-anchored logic that LTN 1/20’s instruments lack, yet no published implementation is grounded in UK design standards. Existing applications to British cities rely on simplified adaptations of North American criteria (Cervero et al. 2019; Jeong and Smith 2025), and applied practice inherits further weaknesses from the Conveyal lineage: undirected max-propagation of junction stress and the absence of any treatment of roundabouts, a junction form both prevalent in the UK and associated with elevated cyclist risk (Section 2.3). The recent completion of the OS NGD Transport Cycle Lane collection removes the principal data barrier to a standards-grounded classification, but as a newly released dataset its completeness and reliability have not been independently assessed.

Third, the network growth literature demonstrates that the sequence of investment shapes connectivity outcomes as strongly as its volume, but existing simulations operate on networks defined by infrastructure presence, in which edges are added rather than upgraded (Section 2.4). Whether these findings transfer to a stress-classified network, where low-stress conditions arise as much from quiet streets as from dedicated facilities and the investment problem is one of reclassifying existing high-stress links, remains untested.

These gaps motivate the overarching aim of this dissertation: to develop and apply a network-level cycling infrastructure assessment grounded in English design standards. Three research questions structure the study:

- RQ1. How can the design criteria of LTN 1/20 be operationalised into a directed, network-scale Level of Traffic Stress classification, including junction and roundabout assessment, using OS NGD Transport data?
- RQ2. To what extent does the West Midlands cycling network deliver the connected, low-stress conditions that LTN 1/20's "cycling for all" principle requires, for the population groups the standard identifies?
- RQ3. How do alternative strategies for upgrading high-stress links compare in their capacity to improve low-stress network connectivity?

3 Study Area and Data

3.1 Study Area: The West Midlands

The study focuses on the West Midlands metropolitan region. Located in central England, it comprises the seven metropolitan boroughs of Birmingham, Coventry, Dudley, Sandwell, Solihull, Walsall, and Wolverhampton. With a population of over 3 million (ONS 2025), the West Midlands is the second biggest and second most populated conurbation in Britain after London (WMCA 2025). As Figure 2 illustrates, the region exhibits a polycentric urban structure, with Birmingham as the dominant core surrounded by smaller but densely populated centres including Wolverhampton, Coventry, and the towns of the Black Country¹. While the southern and eastern portions of Solihull and the fringes of Walsall and Dudley are predominantly rural. This mix of dense urban centres and lower-density peripheral areas presents distinct challenges for cycling infrastructure provision, as routes must negotiate fragmented land uses, varying traffic conditions, and considerable trip distances between centres (Delclòs-Alió and den Hoed 2024).




Figure 2. Study Area: The West Midlands. Left: location within England. Right: population distribution across the seven constituent metropolitan boroughs (Census 2021, 1 dot = 10 people), with hatched areas indicating rural Output Areas (OAs).

The West Midlands has been a centre of British automobile manufacturing since the early twentieth century, accounting for approximately 60% of national car production in the early 1970s (Donnelly et al. 2017). Its urban fabric bears this legacy: post-war interventions such as

¹The Black Country refers to the area immediately west and northwest of Birmingham, comprising the metropolitan boroughs of Dudley, Sandwell, Walsall, and Wolverhampton.

Birmingham’s Inner Ring Road, completed in 1971 as Britain’s first urban motorway (Gunn 2018), entrenched car-oriented mobility across the region, exemplifying what textcitematthioli2020 characterise as a self-reinforcing car-dependent system. National Travel Survey data show that the wider West Midlands region ² consistently records the highest share of private motorised trips among English regions, at 69% in 2024 (DfT 2025a). And cycling accounts for only approximately 0.9% of all trips in the metropolitan area (WMCA 2024), despite 41% of car journeys being under two miles (WMCA 2019).

In response, Transport for West Midlands (TfWM) has set out an ambitious active travel agenda centred on the Starley Network, a planned 500-mile network of traffic-free or physically separated cycle routes (WMCA 2020), aligned with the national Gear Change vision and LTN 1/20 design standards. Yet the gap between this policy ambition and the region’s measurable network-level cycling conditions remains poorly quantified, making the West Midlands a compelling case for the standards-based infrastructure assessment developed in this study.

3.2 Data Sources: Overview

The analytical pipeline draws on four principal data sources. The primary source is Ordnance Survey National Geographic Database Transport (OS NGD Transport), which provides network geometry, road classification, carriageway and cycle lane width, legal access designation, junction type and probe-vehicle-derived average speeds for constructing the directed, stress-classified network (Sections 4.1–4.3). The Cycle Lane feature collection, achieving full national coverage in March 2026 (OS 2026a), makes this study one of the first to incorporate authoritative national cycling infrastructure data into a network-level assessment. Department for Transport road traffic count data supply observed AADT volumes and training observations for minor road volume estimation (Section 4.2). OpenStreetMap (OSM) contributes cycling geometries for Path Link cross-validation, traffic signal locations for junction classification, and school locations for accessibility analysis (Sections 4.1, 4.3, 4.4). Census data from the Office for National Statistics provide MSOA-level commuting flows for OD connectivity and network growth evaluations, and LSOA-level population and boundaries for density and reach analyses (Sections 4.4–4.5). Table 2 summarises each dataset.

²The wider West Midlands region includes the seven metropolitan boroughs as well as the surrounding counties of Herefordshire, Shropshire, Staffordshire, Warwickshire, and Worcestershire.

Table 2. Datasets used in this study.

Dataset	Provider	Key Variables	Spatial Unit	Used In
Road Links	OS NGD	Geometry, classification, description, width	Edge	4.1–4.3
Path Links	OS NGD	Geometry, cycle lane presence	Edge	4.1
Highway Dedication	OS NGD	Legal access designation	Edge	4.1
Cycle Lane	OS NGD	Facility type, width, placement side	Edge	4.1–4.2
Average Speed (RAMI)	OS NGD	Probe-derived average speed	Edge	4.2
Road Node	OS NGD	Node form, geometry, description	Node	4.3
Path Node	OS NGD	Node geometry	Node	4.3
Road Traffic Counts	DfT	AADT by vehicle type	Count point	4.2
Cycling Network	OSM	Highway and cycleway tags	Way	4.1
Traffic Signals	OSM	Signal node locations	Node	4.3
Schools	OSM	Location	Point	4.4
Commuting Flows	ONS	OD pairs within 8 km	MSOA	4.4–4.5
Population	ONS	Resident population	LSOA	4.4
Boundaries	ONS	LSOA/MSOA polygons	Polygon	4.4–4.5

4 Methodology

This section presents the analytical framework for classifying and evaluating the West Midlands cycling network by Level of Traffic Stress (Figure 3). Sections 4.1-4.3 construct the directed, stress-classified network: extracting cyclable segments from OS NGD, assigning link-level LTS, and propagating junction stress with LTN 1/20's criteria. Section 4.4 uses this network to test connectivity against LTN 1/20's "Cycling for all" principle through density, fragmentation, and reach analyses. Section 4.5 compares three network growth strategies to inform upgrade prioritisation.




Figure 3. Analytical framework. LTN 1/20 design criteria (left) supply the classification thresholds operationalised on OS NGD Transport data (right) through Sections 4.1–4.3. The classified network is then evaluated against LTN 1/20's "Cycling for All" principle through connectivity analysis (Section 4.4) and network growth simulation (Section 4.5).

4.1 Cyclable Network Extraction and Infrastructure Classification

The first stage of the classification process extracts all legally and practically cyclable segments from the West Midlands transport network. Cyclable infrastructure is represented in two feature collections under OS NGD Transport Theme: Road Links, which encode the carriageway network where cyclists may share space with motor vehicles (OS 2026f), and Path Links, which encode routes that are topologically independent from the carriageway, captured where they provide connectivity that cannot be inferred from the road network (OS 2026e). The legal cyclability of

segments is firstly checked through the Highway Dedication feature collection, which provides an indication of the type of highway user who has access to each section of the network, recording one of eight designation types (OS 2026d). Five of the seven designation types permit cycling under UK highway law, while ‘Motorway’ and ‘Pedestrian Way Or Footpath’ are excluded as non-cyclable (Table 3).

Table 3. Highway Dedication types and legal cyclability under UK highway law.

Highway Dedication	Cyclable?	Legal Basis
All Vehicles	Yes	Cycling permitted on public roads by default
Cycle Track or Cycle Way	Yes	Cycle Tracks Act 1984
Bridleway	Yes	Countryside Act 1968, s.30
Restricted Byway	Yes	Countryside and Rights of Way Act 2000
Byway Open to All Traffic	Yes	Wildlife and Countryside Act 1981, s.66(1)
Motorway	No	Motorways Traffic (England and Wales) Regulations 1982
Pedestrian Way or Footpath	No	No public right of way for cycling (cf. Highways Act 1835, s.72)

Note: The eighth type, ‘No Dedication Or Dedication Unknown’, is neither cyclable nor explicitly non-cyclable and is addressed through the description-based fallback classification for Road Links.

For Road Links, Highway Dedication covers most of the segments. Where a dedication record is absent or recorded as ‘No Dedication Or Dedication Unknown’, a fallback classification retains segments whose physical description feature indicates a carriageway type (‘Single Carriageway’, ‘Dual Carriageway’, ‘Roundabout’, ‘Slip Road’, ‘Shared Use Carriageway’, ‘Traffic Island Link At Junction’, and ‘Traffic Island Link’). Segments classified as ‘Motorway’ are excluded regardless of dedication status. This process yields 212,551 cyclable Road Links (97.8%), of which 84.2% are identified through Highway Dedication and 15.8% through the description fallback. For Path Links, Highway Dedication coverage is substantially lower, identifying only 10.1% of cyclable paths. A second layer retains paths where the feature data detects cycling infrastructure through its ‘presenceofcyclelane’ attribute, contributing a further 1.0%. No attribute in the OS NGD Path Link schema, however, provides a direct cyclability indicator. The Department for Transport’s transport connectivity metric reflects a comparable data source choice: while it constructs its driving network from Ordnance Survey data, it uses OpenStreetMap for cycling and walking networks, relying on OSM tags to determine which links can be walked or cycled on (DfT 2025b). Following this, a third layer performs spatial cross-validation against the OpenStreetMap cycling network, matching remaining paths without Highway Dedication or cycle lane presence to OSM cycling geometries within a 5-metre nearest-neighbour spatial join and recovering an additional 40,035 paths. Paths with explicitly non-cyclable Highway Dedications are excluded at all layers. This process yields 45,023 cyclable Path Links (40.3% of the total collection). Each segment is then expanded into directed edges, and cycle lane records are joined only to the edge whose travel direction aligns with the lane’s placement side, capturing the inherently asymmetric distribution of cycling infrastructure and avoiding overestimation of facility provision.

Each directed cyclable segment is then classified into one of eight facility types derived from LTN 1/20’s design hierarchy (Table 4). The OS NGD Cycle Lane dataset, whose type definitions

are aligned to LTN 1/20, records dedicated cycling infrastructure as separate features referencing their parent Road Link (OS 2026b; OS 2026c). A Road Link with a matching Cycle Lane record is classified according to its cycle lane description; where multiple records exist for the same link, the more protective facility governs. Road Links without a matching record, or where the cycle lane type is recorded as ‘Unknown Type Of Cycle Track Or Lane’, default to Mixed Traffic. All cyclable Path Links are classified as ‘Off-Road’, as they are topologically independent from the road network and carry no motor traffic speed or volume attributes (OS 2026e). Following classification, Road Links and Path Links are merged into a single unified and directed network for use in the subsequent LTS assessment.

Table 4. Facility type classification derived from LTN 1/20 design hierarchy, mapped to OS NGD data sources.

Facility Type	OS NGD Source	Classification Feature
Off-Road	Path Link	Cyclable Path Links
Shared Use	Cycle Lane	‘Unsegregated Shared Use Cycle Facility’ / ‘Segregated Shared Use Cycle Track’
Fully Kerbed Cycle Track	Cycle Lane	‘Fully Segregated Cycle Track’
Stepped Cycle Track	Cycle Lane	‘Stepped Cycle Track Along Road’
Light Segregation	Cycle Lane	‘Lightly Segregated Cycle Lane On Road’
Mandatory Cycle Lane	Cycle Lane	‘Mandatory Cycle Lane On Road’
Advisory Cycle Lane	Cycle Lane	‘Advisory Cycle Lane On Road’
Mixed Traffic	Road Link (main)	‘Unknown Type Of Cycle Track Or Lane’ or no matching Cycle Lane record

Note: Some facility types overlap conceptually. Off-Road paths may in practice function as shared-use routes or as kerbed cycle tracks. This does not affect the subsequent LTS classification, as all such facilities are fully separated from motor traffic.

4.2 Link-level LTS classification

4.3 Junction LTS Classification

4.4 Stress-Based Network Connectivity Evaluation

4.5 Network Growth Simulation

5 Results

5.1 Network Composition and LTS Distribution

5.2 Data Source Comparison

5.3 Fragmentation

5.4 Reach and Accessibility

5.5 OD Connectivity

5.6 Network Growth Simulation

6 Discussion

6.1 Evaluating the Cycling for All Principle

6.2 Junction Stress as a Structural Barrier

6.3 Implications for Network Planning

6.4 Limitations

6.5 Future Work

7 Conclusion

Bibliography

- Aldred, Rachel, Bridget Elliott, James Woodcock, and Anna Goodman (Jan. 2, 2017). “Cycling Provision Separated from Motor Traffic: A Systematic Review Exploring Whether Stated Preferences Vary by Gender and Age”. In: *Transport Reviews* 37.1, pp. 29–55. ISSN: 0144-1647. DOI: [10.1080/01441647.2016.1200156](https://doi.org/10.1080/01441647.2016.1200156). PMID: 28190905. URL: <https://doi.org/10.1080/01441647.2016.1200156> (visited on 08/01/2026).
- Barthélemy, Marc and Alessandro Flammini (Sept. 1, 2009). “Co-Evolution of Density and Topology in a Simple Model of City Formation”. In: *Networks and Spatial Economics* 9.3, pp. 401–425. ISSN: 1572-9427. DOI: [10.1007/s11067-008-9068-5](https://doi.org/10.1007/s11067-008-9068-5). URL: <https://doi.org/10.1007/s11067-008-9068-5> (visited on 08/02/2026).
- Bearn, Cary, Charlene Mingus, and Kari Watkins (Dec. 1, 2018). “An Adaption of the Level of Traffic Stress Based on Evidence from the Literature and Widely Available Data”. In: *Research in Transportation Business & Management*. Special Issue Title: [RE]EVALUATING HOW WE VALUE TRANSPORTATION 29, pp. 50–62. ISSN: 2210-5395. DOI: [10.1016/j.rtbm.2018.12.002](https://www.sciencedirect.com/science/article/pii/S2210539517301293). URL: <https://www.sciencedirect.com/science/article/pii/S2210539517301293> (visited on 05/21/2026).
- Berghoefer, Frauke Luise and Mark Vollrath (May 1, 2023). “Motivational and Deterrent Effects of Route Attributes in Cyclists’ Route Choice”. In: *Transportation Research Part F: Traffic Psychology and Behaviour* 95, pp. 343–354. ISSN: 1369-8478. DOI: [10.1016/j.trf.2023.04.003](https://www.sciencedirect.com/science/article/pii/S1369847823000785). URL: <https://www.sciencedirect.com/science/article/pii/S1369847823000785> (visited on 08/01/2026).
- Broach, Joseph, Jennifer Dill, and John Gliebe (Dec. 1, 2012). “Where Do Cyclists Ride? A Route Choice Model Developed with Revealed Preference GPS Data”. In: *Transportation Research Part A: Policy and Practice* 46.10, pp. 1730–1740. ISSN: 0965-8564. DOI: [10.1016/j.tra.2012.07.005](https://www.sciencedirect.com/science/article/pii/S0965856412001164). URL: <https://www.sciencedirect.com/science/article/pii/S0965856412001164> (visited on 07/28/2026).
- Buehler, Ralph and Jennifer Dill (Jan. 2, 2016). “Bikeway Networks: A Review of Effects on Cycling”. In: *Transport Reviews* 36.1, pp. 9–27. ISSN: 0144-1647. DOI: [10.1080/01441647.2015.1069908](https://doi.org/10.1080/01441647.2015.1069908). URL: <https://doi.org/10.1080/01441647.2015.1069908> (visited on 05/27/2026).
- Cabral, Laura, Amy M. Kim, and Manish Shirgaokar (June 1, 2019). “Low-Stress Bicycling Connectivity: Assessment of the Network Build-out in Edmonton, Canada”. In: *Case Studies on Transport Policy* 7.2, pp. 230–238. ISSN: 2213-624X. DOI: [10.1016/j.cstp.2019.04.002](https://www.sciencedirect.com/science/article/pii/S2213624X18302554). URL: <https://www.sciencedirect.com/science/article/pii/S2213624X18302554> (visited on 07/03/2026).

- Cervero, Robert, Steve Denman, and Ying Jin (Feb. 1, 2019). “Network Design, Built and Natural Environments, and Bicycle Commuting: Evidence from British Cities and Towns”. In: *Transport Policy* 74, pp. 153–164. ISSN: 0967-070X. DOI: [10.1016/j.tranpol.2018.09.007](https://doi.org/10.1016/j.tranpol.2018.09.007). URL: <https://www.sciencedirect.com/science/article/pii/S0967070X1830101X> (visited on 07/03/2026).
- Chaurand, Nadine and Patricia Delhomme (Jan. 1, 2013). “Cyclists and Drivers in Road Interactions: A Comparison of Perceived Crash Risk”. In: *Accident Analysis & Prevention* 50, pp. 1176–1184. ISSN: 0001-4575. DOI: [10.1016/j.aap.2012.09.005](https://doi.org/10.1016/j.aap.2012.09.005). URL: <https://www.sciencedirect.com/science/article/pii/S0001457512003120> (visited on 08/01/2026).
- CROW (2016). *Design Manual for Bicycle Traffic*. Ede, Netherlands: CROW.
- Delclòs-Alió, Xavier and Wilbert den Hoed (Dec. 1, 2024). “Perceptions of Potential Cycling Infrastructure in a Low-Cycling Context: Evidence from a Medium-Sized Urban Area”. In: *International Journal of Sustainable Transportation* 18.12, pp. 999–1011. ISSN: 1556-8318. DOI: [10.1080/15568318.2024.2424420](https://doi.org/10.1080/15568318.2024.2424420). URL: <https://doi.org/10.1080/15568318.2024.2424420> (visited on 07/23/2026).
- Department for Transport (2020a). *Cycle Infrastructure Design*. United Kingdom: Department for Transport. URL: <https://www.gov.uk/government/publications/cycle-infrastructure-design-ltn-120> (visited on 02/17/2026).
- (Aug. 27, 2025a). *NTS 2024: Mode Share and Multi-Modal Trips*. GOV.UK. URL: <https://www.gov.uk/government/statistics/national-travel-survey-2024/nts-2024-mode-share-and-multi-modal-trips> (visited on 07/23/2026).
 - (Sept. 29, 2025b). *Transport Connectivity Metric*. GOV.UK. URL: <https://www.gov.uk/government/publications/transport-connectivity-metric/transport-connectivity-metric> (visited on 06/20/2026).
- Dill, Jennifer and Nathan McNeil (Jan. 1, 2013). “Four Types of Cyclists?: Examination of Typology for Better Understanding of Bicycling Behavior and Potential”. In: *Transportation Research Record* 2387.1, pp. 129–138. ISSN: 0361-1981. DOI: [10.3141/2387-15](https://doi.org/10.3141/2387-15). URL: <https://doi.org/10.3141/2387-15> (visited on 06/22/2026).
- Donnelly, Tom, Jason Begley, and Clive Collis (Jan. 2, 2017). “The West Midlands Automotive Industry: The Road Downhill”. In: *Business History* 59.1, pp. 56–74. ISSN: 0007-6791. DOI: [10.1080/00076791.2016.1235559](https://doi.org/10.1080/00076791.2016.1235559). URL: <https://doi.org/10.1080/00076791.2016.1235559> (visited on 07/23/2026).
- European Union (2024). *European Declaration on Cycling*. Official Journal of the European Union. URL: https://transport.ec.europa.eu/transport-themes/urban-transport/european-declaration-cycling_en.
- Furth, Peter G, Theja Vvk Putta, and Paul Moser (Oct. 22, 2018). “Measuring Low-Stress Connectivity in Terms of Bike-Accessible Jobs and Potential Bike-to-Work Trips: A Case Study Evaluating Alternative Bike Route Alignments in Northern Delaware”. In: *Journal*

- of Transport and Land Use* 11.1. ISSN: 1938-7849. DOI: [10.5198/jtlu.2018.1159](https://doi.org/10.5198/jtlu.2018.1159). URL: <https://www.jtlu.org/index.php/jtlu/article/view/1159> (visited on 05/24/2026).
- Furth, Peter G., Maaza C. Mekuria, and Hilary Nixon (Jan. 2016). “Network Connectivity for Low-Stress Bicycling”. In: *Transportation Research Record: Journal of the Transportation Research Board* 2587.1, pp. 41–49. ISSN: 0361-1981, 2169-4052. DOI: [10.3141/2587-06](https://doi.org/10.3141/2587-06). URL: <https://journals.sagepub.com/doi/10.3141/2587-06> (visited on 05/31/2026).
- Gehrke, Steven R., Manoj Kumar Allam, Armando E. Martinez, Ty M. Holliday, Brendan J. Russo, and Edward J. Smaglik (Feb. 1, 2025). “Cycling Accessibility to Employment, Schools, and Grocery Stores in Arizona Metropolitan Regions”. In: *International Journal of Sustainable Transportation* 19.2, pp. 180–193. ISSN: 1556-8318. DOI: [10.1080/15568318.2025.2460637](https://doi.org/10.1080/15568318.2025.2460637). URL: <https://doi.org/10.1080/15568318.2025.2460637> (visited on 05/17/2026).
- Geller, Roger (2009). *Four Types of Cyclists*. Portland, OR: Portland Office of Transportation. URL: <https://www.portland.gov/sites/default/files/2022/Four%20Types%20of%20Cyclists%20updated%202009.pdf>.
- Gunn, Simon (Mar. 2018). “RING ROAD: BIRMINGHAM AND THE COLLAPSE OF THE MOTOR CITY IDEAL IN 1970s BRITAIN”. In: *The Historical Journal* 61.1, pp. 227–248. ISSN: 0018-246X, 1469-5103. DOI: [10.1017/S0018246X16000613](https://doi.org/10.1017/S0018246X16000613). URL: <https://www.cambridge.org/core/journals/historical-journal/article/ring-road-birmingham-and-the-collapse-of-the-motor-city-ideal-in-1970s-britain/C47E70E97E52E51E27E60911A307C14A> (visited on 07/23/2026).
- Hancock, Liam and John Parkin (Dec. 1, 2024). “The Challenges of Applying Cycling Design Guidance”. In: *Proceedings of the Institution of Civil Engineers - Transport* 177.7, pp. 494–503. ISSN: 0965-092X, 1751-7710. DOI: [10.1680/jtran.22.00068](https://doi.org/10.1680/jtran.22.00068). URL: <http://www.emerald.com/jtran/article/177/7/494-503/1234772> (visited on 05/12/2026).
- Harkey, David L., Donald W. Reinfurt, and Matthew Knuiman (Jan. 1, 1998). “Development of the Bicycle Compatibility Index”. In: *Transportation Research Record* 1636.1, pp. 13–20. ISSN: 0361-1981. DOI: [10.3141/1636-03](https://doi.org/10.3141/1636-03). URL: <https://doi.org/10.3141/1636-03> (visited on 05/03/2026).
- Harvey, Chester, Daniel A. Rodríguez, and Kevin Fang (Feb. 1, 2024). “Comparing Methods and Data Sources for Classifying Bicycle Level of Traffic Stress: How Well Do Their Outcomes Agree?” In: *Sustainable Cities and Society* 101, p. 105151. ISSN: 2210-6707. DOI: [10.1016/j.scs.2023.105151](https://doi.org/10.1016/j.scs.2023.105151). URL: <https://www.sciencedirect.com/science/article/pii/S2210670723007606> (visited on 03/11/2026).
- Hull, Angela and Craig O’Holleran (Jan. 1, 2014). “Bicycle Infrastructure: Can Good Design Encourage Cycling?” In: *Urban, Planning and Transport Research* 2.1, pp. 369–406. ISSN: null. DOI: [10.1080/21650020.2014.955210](https://doi.org/10.1080/21650020.2014.955210). URL: <https://doi.org/10.1080/21650020.2014.955210> (visited on 05/27/2026).
- Intergovernmental Panel on Climate Change (2023). *Climate Change 2022 – Mitigation of Climate Change*. Cambridge University Press. DOI: [10.1017/9781009157926](https://doi.org/10.1017/9781009157926).

- Jeong, Philyoung and Duncan Smith (2025). *Improving Infrastructure and Accessibility Indicators for Urban Cycling Networks: Measuring the Accessibility Gap for Safer Cycle Routes in London Using Detailed Infrastructure Data and Level of Traffic Stress*. CASA Working Paper 242. Centre for Advanced Spatial Analysis, UCL. URL: <https://www.ucl.ac.uk/bartlett/publications/2025/nov/casa-working-paper-242>.
- Kent, Margaret and Alex Karner (Feb. 7, 2019). “Prioritizing Low-Stress and Equitable Bicycle Networks Using Neighborhood-Based Accessibility Measures”. In: *International Journal of Sustainable Transportation* 13.2, pp. 100–110. ISSN: 1556-8318. DOI: [10.1080/15568318.2018.1443177](https://doi.org/10.1080/15568318.2018.1443177). URL: <https://doi.org/10.1080/15568318.2018.1443177> (visited on 07/02/2026).
- Landis, Bruce W., Venkat R. Vattikuti, and Michael T. Brannick (Jan. 1, 1997). “Real-Time Human Perceptions: Toward a Bicycle Level of Service”. In: *Transportation Research Record* 1578.1, pp. 119–126. ISSN: 0361-1981. DOI: [10.3141/1578-15](https://doi.org/10.3141/1578-15). URL: <https://doi.org/10.3141/1578-15> (visited on 08/01/2026).
- Louro, Thiago, Karst T. Geurs, Anna Grigolon, and André Luiz Cunha (Apr. 28, 2026). “Cycling Accessibility and Equity: A Systematic Literature Review”. In: *Transport Reviews* 0.0, pp. 1–24. ISSN: 0144-1647. DOI: [10.1080/01441647.2026.2664409](https://doi.org/10.1080/01441647.2026.2664409). URL: <https://doi.org/10.1080/01441647.2026.2664409> (visited on 05/17/2026).
- Lowry, Michael and Tracy Hadden Loh (Feb. 1, 2017). “Quantifying Bicycle Network Connectivity”. In: *Preventive Medicine*. Active Living Research - Equity in Active Living 95, S134–S140. ISSN: 0091-7435. DOI: [10.1016/j.ypmed.2016.12.007](https://www.sciencedirect.com/science/article/pii/S0091743516304029). URL: <https://www.sciencedirect.com/science/article/pii/S0091743516304029> (visited on 07/01/2026).
- Mahfouz, Hussein, Robin Lovelace, and Elsa Arcaute (Dec. 1, 2023). “A Road Segment Prioritization Approach for Cycling Infrastructure”. In: *Journal of Transport Geography* 113, p. 103715. ISSN: 0966-6923. DOI: [10.1016/j.jtrangeo.2023.103715](https://www.sciencedirect.com/science/article/pii/S0966692323001874). URL: <https://www.sciencedirect.com/science/article/pii/S0966692323001874> (visited on 03/12/2026).
- Manton, Richard, Henrike Rau, Frances Fahy, Jerome Sheahan, and Eoghan Clifford (Mar. 1, 2016). “Using Mental Mapping to Unpack Perceived Cycling Risk”. In: *Accident Analysis & Prevention* 88, pp. 138–149. ISSN: 0001-4575. DOI: [10.1016/j.aap.2015.12.017](https://www.sciencedirect.com/science/article/pii/S0001457515301688). URL: <https://www.sciencedirect.com/science/article/pii/S0001457515301688> (visited on 08/01/2026).
- Mekuria, Maaza C., Peter G. Furth, and Hilary Nixon (May 1, 2012). *Low-Stress Bicycling and Network Connectivity*. 11-19. Mineta Transportation Institute. URL: <https://rosap.ntl.bts.gov> (visited on 03/12/2026).
- Mölenberg, Famke J. M., Jenna Panter, Alex Burdorf, and Frank J. van Lenthe (Oct. 26, 2019). “A Systematic Review of the Effect of Infrastructural Interventions to Promote Cycling: Strengthening Causal Inference from Observational Data”. In: *International Journal of Behavioral Nutrition and Physical Activity* 16.1, p. 93. ISSN: 1479-5868. DOI: [10.1186/s12966-019-0850-1](https://doi.org/10.1186/s12966-019-0850-1). URL: <https://doi.org/10.1186/s12966-019-0850-1> (visited on 05/27/2026).

- Murphy, Brendan and Andrew Owen (May 1, 2019). “Implementing Low-Stress Bicycle Routing in National Accessibility Evaluation”. In: *Transportation Research Record* 2673.5, pp. 240–249. ISSN: 0361-1981. DOI: [10.1177/0361198119837179](https://doi.org/10.1177/0361198119837179). URL: <https://doi.org/10.1177/0361198119837179> (visited on 07/02/2026).
- Natera Orozco, Luis Guillermo, Federico Battiston, Gerardo Iñiguez, and Michael Szell (Dec. 16, 2020). “Data-Driven Strategies for Optimal Bicycle Network Growth”. In: *Royal Society Open Science* 7.12, p. 201130. ISSN: 2054-5703. DOI: [10.1098/rsos.201130](https://doi.org/10.1098/rsos.201130). PMID: [33489269](https://pubmed.ncbi.nlm.nih.gov/33489269/). URL: <https://pmc.ncbi.nlm.nih.gov/articles/PMC7813224/> (visited on 07/17/2026).
- Office for National Statistics (2025). *Labour Market Profile - Nomis - Official Census and Labour Market Statistics*. Nomis Official Census and Labour Market Statistics. URL: https://www.nomisweb.co.uk/reports/lmp/comb/1853882375/report.aspx?utm_source=chatgpt.com (visited on 07/23/2026).
- Ordnance Survey (Jan. 7, 2026a). *New National Cycle Lane Data / OS*. Ordnance Survey. URL: <https://www.ordnancesurvey.co.uk/news/new-national-cycle-lane-data> (visited on 07/24/2026).
- Pais, Filipe, João Monteiro, Nuno Sousa, João Coutinho-Rodrigues, and Eduardo Natividade-Jesus (May 31, 2022). “A Multicriteria Methodology for Maintenance Planning of Cycling Infrastructure”. In: *Proceedings of the Institution of Civil Engineers - Engineering Sustainability* 175.5, pp. 248–264. ISSN: 1478-4629. DOI: [10.1680/jensu.21.00088](https://doi.org/10.1680/jensu.21.00088). URL: <https://doi.org/10.1680/jensu.21.00088> (visited on 07/01/2026).
- Park, Yujin and Gulsah Akar (Jan. 1, 2019). “Why Do Bicyclists Take Detours? A Multilevel Regression Model Using Smartphone GPS Data”. In: *Journal of Transport Geography* 74, pp. 191–200. ISSN: 0966-6923. DOI: [10.1016/j.jtrangeo.2018.11.013](https://doi.org/10.1016/j.jtrangeo.2018.11.013). URL: <https://www.sciencedirect.com/science/article/pii/S0966692318301078> (visited on 08/01/2026).
- Pistoll, Chance and Anna Goodman (Dec. 1, 2014). “The Link between Socioeconomic Position, Access to Cycling Infrastructure and Cycling Participation Rates: An Ecological Study in Melbourne, Australia”. In: *Journal of Transport & Health*. Walking & Cycling: The Contributions of Health and Transport Geography 1.4, pp. 251–259. ISSN: 2214-1405. DOI: [10.1016/j.jth.2014.09.011](https://doi.org/10.1016/j.jth.2014.09.011). URL: <https://www.sciencedirect.com/science/article/pii/S2214140514000796> (visited on 05/27/2026).
- Putta, Theja and Peter G. Furth (Sept. 1, 2019). “Method to Identify and Visualize Barriers in a Low-Stress Bike Network”. In: *Transportation Research Record* 2673.9, pp. 452–460. ISSN: 0361-1981. DOI: [10.1177/0361198119847617](https://doi.org/10.1177/0361198119847617). URL: <https://doi.org/10.1177/0361198119847617> (visited on 07/03/2026).
- Reggiani, Giulia, Trivik Verma, Winnie Daamen, and Serge Hoogendoorn (Oct. 1, 2023). “A Multi-City Study on Structural Characteristics of Bicycle Networks”. In: *Environment and Planning B: Urban Analytics and City Science* 50.8, pp. 2017–2037. ISSN: 2399-8083. DOI: [10.1177/23998083231170637](https://doi.org/10.1177/23998083231170637). URL: <https://doi.org/10.1177/23998083231170637> (visited on 08/02/2026).

- Sanders, Rebecca L. (Feb. 1, 2015). “Perceived Traffic Risk for Cyclists: The Impact of near Miss and Collision Experiences”. In: *Accident Analysis & Prevention* 75, pp. 26–34. ISSN: 0001-4575. DOI: [10.1016/j.aap.2014.11.004](https://doi.org/10.1016/j.aap.2014.11.004). URL: <https://www.sciencedirect.com/science/article/pii/S0001457514003261> (visited on 08/01/2026).
- Schön, Peter, Eva Heinen, and Bendik Manum (July 3, 2024). “A Scoping Review on Cycling Network Connectivity and Its Effects on Cycling”. In: *Transport Reviews* 44.4, pp. 912–936. ISSN: 0144-1647. DOI: [10.1080/01441647.2024.2337880](https://doi.org/10.1080/01441647.2024.2337880). URL: <https://doi.org/10.1080/01441647.2024.2337880> (visited on 05/27/2026).
- Schoner, Jessica E. and David M. Levinson (Nov. 1, 2014). “The Missing Link: Bicycle Infrastructure Networks and Ridership in 74 US Cities”. In: *Transportation* 41.6, pp. 1187–1204. ISSN: 1572-9435. DOI: [10.1007/s11116-014-9538-1](https://doi.org/10.1007/s11116-014-9538-1). URL: <https://doi.org/10.1007/s11116-014-9538-1> (visited on 07/18/2026).
- Sorton, Alex and Thomas Walsh (1994). “Bicycle Stress Level as a Tool to Evaluate Urban and Suburban Bicycle Compatibility”. In: *Transportation Research Record* 1438, pp. 17–24. ISSN: 0361-1981.
- Steinacker, Christoph, David-Maximilian Storch, Marc Timme, and Malte Schröder (Oct. 2022). “Demand-Driven Design of Bicycle Infrastructure Networks for Improved Urban Bikeability”. In: *Nature Computational Science* 2.10, pp. 655–664. ISSN: 2662-8457. DOI: [10.1038/s43588-022-00318-w](https://doi.org/10.1038/s43588-022-00318-w). URL: <https://www.nature.com/articles/s43588-022-00318-w> (visited on 07/17/2026).
- Survey, Ordnance (Mar. 12, 2026b). *Cycle Lane / OS National Geographic Database*. OS National Geographic Databas. URL: <https://docs.os.uk/osngd/data-structure/transport/transport-network/cycle-lane> (visited on 06/20/2026).
- (Jan. 28, 2026c). *Cyclelanedescriptionvalue / OS National Geographic Database*. URL: <https://docs.os.uk/osngd/code-lists/code-lists-overview/cyclelanedescriptionvalue> (visited on 06/20/2026).
- (Apr. 30, 2026d). *Highway Dedication / OS National Geographic Database*. OS National Geographic Databas. URL: <https://docs.os.uk/osngd/data-structure/transport/rami/highway-dedication> (visited on 06/20/2026).
- (Apr. 29, 2026e). *Path Link / OS National Geographic Database*. OS National Geographic Databas. URL: <https://docs.os.uk/osngd/data-structure/transport/transport-network/path-link> (visited on 06/20/2026).
- (Apr. 29, 2026f). *Road Link / OS National Geographic Database*. OS National Geographic Databas. URL: <https://docs.os.uk/osngd/data-structure/transport/transport-network/road-link> (visited on 06/20/2026).
- Szell, Michael, Sayat Mimar, Tyler Perlman, Gourab Ghoshal, and Roberta Sinatra (Apr. 26, 2022). “Growing Urban Bicycle Networks”. In: *Scientific Reports* 12.1, p. 6765. ISSN: 2045-2322. DOI: [10.1038/s41598-022-10783-y](https://doi.org/10.1038/s41598-022-10783-y). URL: <https://www.nature.com/articles/s41598-022-10783-y> (visited on 05/27/2026).

- Transport, Department for (2020b). *Gear Change: A Bold Vision for Cycling and Walking*. London: Department for Transport. URL: <https://assets.publishing.service.gov.uk/media/5f1f59458fa8f53d39c0def9/gear-change-a-bold-vision-for-cycling-and-walking.pdf>.
- Tucker, Bronwen and Kevin Manaugh (Jan. 2, 2018). “Bicycle Equity in Brazil: Access to Safe Cycling Routes across Neighborhoods in Rio de Janeiro and Curitiba”. In: *International Journal of Sustainable Transportation* 12.1, pp. 29–38. ISSN: 1556-8318. DOI: [10.1080/15568318.2017.1324585](https://doi.org/10.1080/15568318.2017.1324585). URL: <https://doi.org/10.1080/15568318.2017.1324585> (visited on 07/03/2026).
- Wang, Haizhong, Matthew Palm, Chen Chen, Rachel Vogt, and Yiyi Wang (Dec. 1, 2016). “Does Bicycle Network Level of Traffic Stress (LTS) Explain Bicycle Travel Behavior? Mixed Results from an Oregon Case Study”. In: *Journal of Transport Geography* 57, pp. 8–18. ISSN: 0966-6923. DOI: [10.1016/j.jtrangeo.2016.08.016](https://doi.org/10.1016/j.jtrangeo.2016.08.016). URL: <https://www.sciencedirect.com/science/article/pii/S0966692316304616> (visited on 07/01/2026).
- Wang, Kailai, Gulsah Akar, Long Cheng, Kevin Lee, and Meredyth Sanders (Dec. 1, 2022). “Investigating Tools for Evaluating Service and Improvement Opportunities on Bicycle Routes in Ohio, United States”. In: *Multimodal Transportation* 1.4, p. 100040. ISSN: 2772-5863. DOI: [10.1016/j.multra.2022.100040](https://doi.org/10.1016/j.multra.2022.100040). URL: <https://www.sciencedirect.com/science/article/pii/S2772586322000405> (visited on 06/30/2026).
- Wasserman, David, Alex Rixey, Xinyi (Elynor) Zhou, Drew Levitt, and Matt Benjamin (Apr. 1, 2019). “Evaluating OpenStreetMap’s Performance Potential for Level of Traffic Stress Analysis”. In: *Transportation Research Record* 2673.4, pp. 284–294. ISSN: 0361-1981. DOI: [10.1177/0361198119836772](https://doi.org/10.1177/0361198119836772). URL: <https://doi.org/10.1177/0361198119836772> (visited on 07/03/2026).
- West Midlands Combined Authority (2019). *A Common Approach to Cycling and Walking in the West Midlands*. Birmingham: West Midlands Combined Authority.
- (Aug. 11, 2020). *New West Midlands Cycling Network Unveiled*. New West Midlands cycling network unveiled. URL: <https://www.wmca.org.uk/news/new-west-midlands-cycling-network-unveiled/> (visited on 07/23/2026).
 - (Nov. 2, 2024). *WEST MIDLANDS GREENER TOGETHER PANEL*. Birmingham: West Midlands Combined Authority. URL: <https://www.wmca.org.uk/media/101jmw1p/20241102-local-transport-plan-presentation-p1.pdf>.
 - (2025). *West Midlands Growth Plan*. Birmingham: West Midlands Combined Authority. URL: <https://growth.wmca.org.uk/assets/WestMidlandsGrowthPlan.pdf>.
- World Health Organization (2022). *Walking and Cycling, Latest Evidence to Support Policy-Making and Practice*. Copenhagen: World Health Organization. Regional Office for Europe. ISBN: 978-92-890-5788-2.
- Xie, Feng and David Levinson (Sept. 1, 2009). “Modeling the Growth of Transportation Networks: A Comprehensive Review”. In: *Networks and Spatial Economics* 9.3, pp. 291–307. ISSN: 1572-

9427. DOI: [10.1007/s11067-007-9037-4](https://doi.org/10.1007/s11067-007-9037-4). URL: <https://doi.org/10.1007/s11067-007-9037-4> (visited on 08/02/2026).

A Supplementary Material

B Research Log

Date	Type	Summary
------	------	---------