

Chapter 4: General Programming Techniques

Program derivation is not mechanical; in general, it is a challenging activity and it requires creativity. The derivations show where the creativity comes in.

Efficiency and \mathcal{O} -Notation

- Big-O:

The time complexity is a function of the constants in the specification.

$\mathcal{O}(f)$: upper bound of the number of steps (modulo a constant factor).

- Typical time complexities

$\mathcal{O}(2^N)$ exponential

$\mathcal{O}(N^2)$ quadratic

$\mathcal{O}(N)$ linear

$\mathcal{O}(\log N)$ logarithmic

Invariance Theorem

$$\{P\}\mathbf{do} \ B_0 \rightarrow S_0 \ [] \ B_1 \rightarrow S_1 \ \mathbf{od}\{Q\}$$

provided that

- (i) $[P \wedge \neg B_0 \wedge \neg B_1 \Rightarrow Q]$
- (ii) P is invariant under S_0 and S_1 .
 - ▶ $\{P \wedge B_0\}S_0\{P\}$
 - ▶ $\{P \wedge B_1\}S_1\{P\}$
- (iii) bound function t such that
 - ▶ $[P \wedge (B_0 \vee B_1) \Rightarrow t \geq 0]$
 - ▶ $\{P \wedge B_0 \wedge t = C\}S_0\{t < C\}$
 - ▶ $\{P \wedge B_1 \wedge t = C\}S_1\{t < C\}$

How to find a suitable invariant?

Taking Conjunctions as Invariant

$$\{\underline{P}\} \mathbf{do} \ \underline{\neg Q} \rightarrow S_1 \ \mathbf{od} \ \{\underline{P \wedge Q}\}$$

- *Example 1:* Design S meeting

$$\{true\} S \{x \leq y\}.$$

Taking $true$ as invariant P , $x \leq y$ as Q , we have

$$\{true\} \mathbf{do} \ x > y \rightarrow x, y := y, x \ \mathbf{od} \ \{x \leq y\}$$

(Note: (1) $x - y$ is a bound function. (2) $x := y - 1$ is also fine.)

- *Example 2*: Design S meeting

$$\{true\}S\{a \leq b \wedge b \leq c \wedge c \leq d\}.$$

Taking *true* as invariant P , we have

```
{true}
do  $a > b \rightarrow a, b := b, a$ 
    []  $b > c \rightarrow b, c := c, b$ 
    []  $c > d \rightarrow c, d := c, b$ 
od
 $\{a \leq b \wedge b \leq c \wedge c \leq d\}$ 
```

(Why does it terminate?)

- *Example 3.* Design *divmod* meeting the specification:

```
[[  
  con  $A, B : int \{A \geq 0 \wedge B > 0\}$   
  var  $q, r : int$   
  divmod  
   $\{q = A \text{ div } B \wedge r = A \text{ mod } B\}$   
]]
```

Note that according to the definitions of **div** and **mod**, the post-condition R is

$$R: A = q * B + r \wedge 0 \leq r \wedge r < B.$$

What is a suitable invariant?

From the post-condition

$$R : A = q * B + r \wedge 0 \leq r \wedge r < B$$

we may choose as invariant

$$P : A = q * B + r \wedge 0 \leq r$$

and as guard $\neg(r < B)$, leading to a program of the form:

$$\{P\}\mathbf{do} \ r \geq B \rightarrow S \ \mathbf{od}\{R\}.$$

- ▶ Initialization: $q, r := 0, A$, satisfying P
- ▶ Bound function: r
- ▶ Choose S as $r := r - B$.

$$\begin{aligned}
 & P(r := r - B) \\
 \equiv & \quad \{ \text{substitution} \} \\
 & A = q * B + r - B \wedge 0 \leq r - B \\
 \equiv & \quad \{ \text{calculus} \} \\
 & A = \underline{(q - 1)} * B + r \wedge B \leq r
 \end{aligned}$$

Having $q := q + 1$ can keep the invariant, i.e.,

$$P(q, r := q + 1, r - B) \Leftarrow P \wedge r \geq B.$$

This yields the following solution to *divmod*:

```
 $q, r, := 0, A;$   
{invariant:  $A = p * B + r \wedge 0 \leq r$ , bound:  $r$ }  
do  $r \geq B \rightarrow q, r := q + 1, r - B$  od  
{ $R$ }
```

Replacing Constants by Variables

- *Example 1*

Consider the problem of computation of A to the power B for given naturals A and B :

```
[[  
  con  $A, B : int$ ;  
  var  $r : int$ ;  
  exponentiation  
   $\{r = A^B\}$   
]]
```

What is a suitable invariant P ?

We may introduce a *fresh variable* x and choose as invariant

$$P : r = A^x \wedge x \leq B$$

and as bound $B - x$. This yields the following program scheme:

$$r, x := 1, 0 \{P\}; \text{ do } x \neq B \rightarrow S \text{ od} \{r = A^B\}$$

We investigate the effect of increasing x by 1:

$$\begin{aligned} & P(x := x + 1) \\ \equiv & \{ \text{substitution} \} \\ & r = A^{x+1} \wedge (x + 1) \leq B \\ \equiv & \{ A^{x+1} = A^x * A \} \\ & r = r * A \wedge x \leq B - 1 \\ \equiv & \{ \text{calculus} \} \\ & \underline{r = r * A} \wedge x \leq B \wedge x \neq B \end{aligned}$$

We obtain the following solution for *exponentiation*:

```
[[  
  var  $x : int$ ;  
   $r, x := 1, 0$ ;  
  {invariant:  $P$ , bound:  $B - x$ }  
  do  $x \neq B \rightarrow r, x := r * A, x + 1$  od  
  { $r = A^B$ }  
]]
```

- *Example 2*

Derive a solution to *summation*, satisfying the following specification:

```
[[  
  con  $N : int\{N \geq 0\}$ ;  $f : \mathbf{array}\ [0..N) \ \mathbf{of}\ int$ ;  
  var  $x : int$ ;  
  summation  
   $\{x = (\sum i : 0 \leq i < N : f.i)\}$   
]]
```

We may choose as

- ▶ invariant: $P = P_0 \wedge P_1$
 - * $P_0 = \{x = (\sum i : 0 \leq i < n : f.i)\}$, n is a fresh variable
 - * $P_1 = 0 \leq n \leq N$: a bound for n
- ▶ bound function: $N - n$.

- Find initial values satisfying P :

$$x, n = 0, 0$$

- Investigate the effect of increasing n by 1 (according to the termination requirement), and we can get the following:

$$\{P \wedge n \neq N\} \ x, n = x + f.n, n + 1 \ \{P\}$$

- Final solution for *summation*:

```
[[  
  var  $n : int; \{N \geq 0\}$   
   $n, x := 0, 0;$   
  {invariant:  $P_0 \wedge P_1$ , bound:  $N - n$ }  
  do  $n \neq N \rightarrow x, n := x + f.n, n + 1$  od  
]]
```

Strengthening Invariants

- *Example 1*

Derive a program for the computation of Fibonacci function.

```
[[  
  con  $N : int \{N \geq 0\}$ ;  
  var  $x : int$ ;  
  fibonacci  
   $\{x = fib.N\}$   
]]
```

where *fib* is defined by

$$\begin{aligned} fib.0 &= 0 \\ fib.1 &= 1 \\ fib.(n+2) &= fib.n + fib.(n+1) \end{aligned}$$

We may have as invariant $P_0 \wedge P_1$, where

$$P_0 \quad x = fib.n$$

$$P_1 \quad 0 \leq n \leq N$$

which is established by $n, x := 0, 0$. And we may take $N - n$ as bound function.

Notice that

$$\begin{aligned} P_0(n := n + 1; x := E) &= E = fib.(n + 1) \\ &= E = \dots x \dots n \dots? \end{aligned}$$

By strengthening invariant to $P_0 \wedge P_1 \wedge Q$, where

$$Q : y = fib.(n + 1)$$

and assuming $P_0 \wedge P_1 \wedge Q$, we have

$$\begin{aligned} P_0(n := n + 1) &= x = fib.(n + 1) \\ &= x = y \\ P_1(n := n + 1) &= 0 \leq n + 1 \leq N \\ &\Leftarrow P_1 \wedge n \neq N \\ Q(n := n + 1) &= y = fib.((n + 1) + 1) \\ &= y = fib.n + fib.(n + 1) \\ &= y = x + y \end{aligned}$$

So we can obtain the following solution.

```
[[  
  var  $n, y : int; \{N \geq 0\}$   
   $n, x, y := 0, 0, 1;$   
  {invariant:  $P_0 \wedge P_1 \wedge Q$ , bound:  $N - n$ }  
  do  $n \neq N \rightarrow x, y, n := y, x + y, n + 1$  od  
  { $x = fib.N \wedge y = fib.(N + 1)$ }  
]]
```

This program has the complexity of $\mathcal{O}(N)$.

- *Example 2*

Derive, given array $f[0..N)$, a program for S , satisfying the following specification.

```
[[  
  con  $N : int \{N \geq 0\}; f : \mathbf{array}[0..N)$  of  $int$ ;  
  var  $r : int$ ;  
   $S$   
   $\{r = (\#i, j : 0 \leq i < j < N : f.i \leq 0 \wedge f.j \geq 0)\}$   
  ]]
```

Derivation

1. Deriving Invariants.

By replacing constants by variables, we come up with the following invariants:

$$P_0 : \quad r = (\#i, j : 0 \leq i < j < n : f.i \leq 0 \wedge f.j \geq 0)$$

$$P_1 : \quad 0 \leq n \leq N$$

which are initialized by $n, r := 0, 0$.

2. We change $n := n + 1$, and derive programs keeping invariants.

Assuming $P_0 \wedge P_1 \wedge n \neq N$, we have

$$\begin{aligned}
& (\#i, j : 0 \leq i < j < n + 1 : f.i \leq 0 \wedge f.j \geq 0) \\
= & \{ \text{split off } j = n \} \\
& (\#i, j : 0 \leq i < j < n : f.i \leq 0 \wedge f.j \geq 0) + \\
& (\#i : 0 \leq i < n : f.i \leq 0 \wedge f.n \geq 0) \\
= & \{ P_0 \} \\
& r + (\#i : 0 \leq i < n : f.i \leq 0 \wedge f.n \geq 0) \\
= & \{ \text{case analysis} \} \\
& r \quad \text{if } f.n < 0 \\
& r + (\#i : 0 \leq i < n : f.i \leq 0) \quad \text{if } f.n \geq 0 \\
= & \{ \text{introduction of invariant } Q : s = (\#i : 0 \leq i < n : f.i \leq 0) \} \\
& r \quad \text{if } f.n < 0 \\
& r + s \quad \text{if } f.n \geq 0
\end{aligned}$$

For the invariance of Q , we derive, assuming $P_0 \wedge P_1 \wedge Q \wedge n \neq N$,

$$\begin{aligned}
 & (\#i : 0 \leq i < n + 1 : f.i \leq 0) \\
 = & \quad \{ \text{split off } i = n \} \\
 & (\#i : 0 \leq i < n : f.i \leq 0) + \#.(f.n \leq 0) \\
 = & \quad \{ Q \} \\
 & s + \#.(f.n \leq 0) \\
 = & \quad \{ \text{definition of } \# \} \\
 & \quad s \quad \text{if } f.n > 0 \\
 & \quad s + 1 \quad \text{if } f.n \leq 0
 \end{aligned}$$

3. We summarize the above and obtain the following solution.

```

[[
var  $n, s : int; \{N \geq 0\}$ 
 $n, r, s := 0, 0, 0;$ 
{invariant:  $P_0 \wedge P_1 \wedge Q$ , bound  $N - n$ }
do  $n \neq N \rightarrow$ 
    if  $f.n < 0 \rightarrow$  skip
    []  $f.n \geq 0 \rightarrow r := r + s$ 
    fi;
    if  $f.n > 0 \rightarrow$  skip
    []  $f.n \leq 0 \rightarrow s := s + 1$ 
    fi;
     $n := n + 1$ 
od
]]
 $\{r = (\#i, j : 0 \leq i < j < N : f.i \leq 0 \wedge f.j \geq 0)\}$ 

```

Exercises

Derive a solution for the following programming problems.

[Problem 4-1]

```
[[  
  con  $N, X : int \{N \geq 0\}; f : \text{array } [0..N) \text{ of } int;$   
  var  $r : int$   
   $S$   
   $\{r = (\sum i : 0 \leq i < N : f.i * X^i)\}$   
]].
```


[Problem 4-2]

```
[[  
  con  $N : int \{N \geq 1\}; A : \text{array } [0..N) \text{ of } int;$   
  var  $r : int$   
   $S$   
   $\{r = (\text{max } p \ q : 0 \leq p < q < N : A.p - A.q)\}$   
]].
```