

OpenWISP User Management System RESTful API documentation



<i>Document Release Date</i>	<i>OWUMS Version</i>	<i>Release notes</i>	<i>Authors</i>
<i>May 25th, 2012</i>	<i>1.2-rc1</i>	<i>First release</i>	<i>Davide Guerri - d.guerri@unidata.it</i>

Copyright © 2012 OpenWISP.org



Except where otherwise noted, this document is licensed under
[Creative Commons Attribution ShareAlike 3.0 License](https://creativecommons.org/licenses/by-sa/3.0/legalcode)

<http://creativecommons.org/licenses/by-sa/3.0/legalcode>

Table on contents

General information	7
<i>HTTP error codes</i>	7
<i>Application localization</i>	8
<i>Authenticated request</i>	8
Account Session	9
<i>Create</i>	9
Required roles	9
HTTP Request	9
HTTP Response	9
Examples	9
User	11
<i>Create</i>	11
Required roles	11
HTTP Request	11
HTTP Response	11
Examples	11
<i>Read</i>	13
Required roles	13
HTTP Request	13
HTTP Response	13
Examples	14
<i>Update</i>	17
Required roles	17
HTTP Request	18
HTTP Response	18
Examples	18
<i>Destroy</i>	19
Required roles	19
HTTP Request	19

HTTP Response	19
Examples	19
Radius Group	21
Create	21
Required roles	21
HTTP Request	21
HTTP Response	21
Examples	21
Read	22
Required roles	22
HTTP Request - List	22
HTTP Response - List	23
HTTP Request - Show	23
HTTP Response - Show	23
Examples	24
Update	24
Required roles	24
HTTP Request	24
HTTP Response	25
Examples	25
Destroy	26
Required roles	26
HTTP Request	26
HTTP Response	26
Examples	26
Users' Radius Checks	27
External documentation	27
Create	27
Required roles	27
HTTP Request	27
HTTP Response	27
Examples	28

<i>Read</i>	28
HTTP Request - List	28
HTTP Response - List	29
HTTP Request - Show	29
HTTP Response - Show	29
Examples	30
<i>Update</i>	30
HTTP Request	31
HTTP Response	31
Examples	31
<i>Destroy</i>	32
HTTP Request	32
HTTP Response	32
Examples	32
Users' Radius Replies	34
<i>External documentation</i>	34
<i>Create</i>	34
Required roles	34
HTTP Request	34
HTTP Response	34
Examples	35
<i>Read</i>	35
HTTP Request - List	35
HTTP Response - List	36
HTTP Request - Show	36
HTTP Response - Show	36
Examples	37
<i>Update</i>	38
HTTP Request	38
HTTP Response	38
Examples	39
<i>Destroy</i>	39

HTTP Request	40
HTTP Response	40
Examples	40
RADIUS Groups' Radius Checks	41
<i>External documentation</i>	<i>41</i>
Create	41
Required roles	41
HTTP Request	41
HTTP Response	41
Examples	41
Read	42
HTTP Request - List	42
HTTP Response - List	43
HTTP Request - Show	43
HTTP Response - Show	43
Examples	44
Update	44
HTTP Request	44
HTTP Response	45
Examples	45
Destroy	46
HTTP Request	46
HTTP Response	46
Examples	46
RADIUS Groups' Radius Replies	47
<i>External documentation</i>	<i>47</i>
Create	47
Required roles	47
HTTP Request	47
HTTP Response	47
Examples	48
Read	48

HTTP Request - List	48
HTTP Response - List	49
HTTP Request - Show	49
HTTP Response - Show	49
Examples	50
<i>Update</i>	51
HTTP Request	51
HTTP Response	51
Examples	52
<i>Destroy</i>	52
HTTP Request	52
HTTP Response	53
Examples	53

General information

HTTP error codes

The following table list error codes supported by the application.

Result Message	Code	Meanings
Successful results		
OK	200	Operation successfully executed.
CREATED	201	New resource created.
ACCEPTED	202	The request has been accepted for processing, but the processing has not been completed.
Client errors		
BAD REQUEST	400	The request could not be understood by the server due to malformed syntax. The client SHOULD NOT repeat the request without modifications.
AUTHORIZATION REQUIRED	401	An <u>authentication</u> is required for access the addressed resource.
FORBIDDEN	403	Insufficient privileges to access the addressed resource.
NOT FOUND	404	Resource was not found.
NOT ACCEPTABLE	406	The resource identified by the request is only capable of generating response entities which have content characteristics not acceptable according to the accept headers sent in the request.
REQUEST TIMEOUT	408	Timeout accessing the requested resource.
UNPROCESSABLE ENTITY	422	The 422 (Unprocessable Entity) status code means the server understands the content type of the request entity, and the syntax of the request entity is correct (thus a 400 (Bad Request) status code is inappropriate) but was unable to process the contained instructions. For Examples, this error condition may occur if an XML request body contains well-formed (i.e., syntactically correct), but semantically erroneous, XML instructions.
Server errors		

Result Message	Code	Meanings
INTERNAL SERVER ERROR	500	The server encountered an unexpected condition which prevented it from fulfilling the request.

Application localization

Error messages generated by the application are localized.

To retrieve these messages in a particular language the “locale” parameter can be appended to URL parameters.

At present time only “en” (for English) and “it” (for Italian) languages are supported. If no locale is specified, “it” is used.

Examples

```
http://<your server>/<your resource>?locale=en
```

Authenticated request

Resources that require some role will also require an authentication to be accessed are marked with an asterisk. Required roles are specified in each section.

Requested authentication method is the “Basic HTTP Authentication”.

Account Session

Create

Required roles

No role required

HTTP Request

Verb	URLs	XML POSTDATA
POST	/account_session.xml	<pre><account_session> <username>USERNAME</username> <password>PASSWORD</password> </account_session></pre>

HTTP Response

HTTP Code	Meaning	Content
201	CREATED	
401	AUTHORIZATION REQUIRED	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -H 'Content-type: text/xml' -X POST http://localhost:3000/account_session.xml?locale=en -d "<account_session>
  <username>mario</username>
  <password>mario01</password>
</account_session>
"
HTTP/1.1 401 Authorization Required
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Thu, 10 May 2012 14:50:09 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.225505
Content-Length: 102
Cache-Control: no-cache
Set-Cookie: _session_id=8d75fd3d53900ecc8599de64e767949d; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Wrong username or password</error>
</errors>
```

Successful request

```
# curl -i -H 'Content-type: text/xml' -X POST http://localhost:3000/account_session.xml?locale=en -d "<account_session>
  <username>user</username>
  <password>realpassword</password>
</account_session>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Thu, 10 May 2012 14:54:06 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.326763
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=d3be989ee55eeaf2ade5c4f140372d22; path=/; HttpOnly
Set-Cookie: account_credentials=b6001d2a51cf24803d83935d86253091c33e65190005ce5783fe9f22d6e5555d70d278ffa722541efe8f0a159249b936ea8b98556b4eb686146633be3ef76f25%3A%3A1; path=/
```

User

Create

Required roles

users_manager
users_registrant

Depending on the registration method, additional roles are required:

registrant_by_nothing, for no_identity_verification registration method
registrant_by_id_card, for identity_document registration method

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users.xml	<pre><user> <i>User attributes</i> </user></pre>

HTTP Response

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>
201	CREATED	<pre><?xml version="1.0" encoding="UTF-8"?> <user> <i>User attributes</i> </user></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users.xml?locale=en -d "
<user>
  <given-name>MyName</given-name>
```

```

<surname>MySurname</surname>
<address>Via con il vento</address>
<city>Roma</city>
<zip>00100</zip>
<birth-date>1976-05-23</birth-date>
<username>username</username>
<password>password1</password>
<password-confirmation>password1</password-confirmation>
<email>me@email.com</email>
<email-confirmation>me@email.com</email-confirmation>
<verification-method>no_identity_verification</verification-method>
<privacy-acceptance>true</privacy-acceptance>
<eula-acceptance>true</eula-acceptance>
<verified>true</verified>
<active>true</active>
<state>Italy</state>
<radius-group-ids type='array'>
  <radius-group-id>2</radius-group-id>
</radius-group-ids>
</user>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:28:10 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.398303
Content-Length: 153
Cache-Control: no-cache
Set-Cookie: _session_id=5582194a04b7cdc0b8ccaabd12c8465c; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Username has already been taken</error>
  <error>Email has already been taken</error>
</errors>

```

Successful request

```

# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users.xml?locale=en -d "
<user>
  <given-name>MyName</given-name>
  <surname>MySurname</surname>
  <address>Via con il vento</address>
  <city>Roma</city>
  <zip>00100</zip>
  <birth-date>1976-05-23</birth-date>
  <username>username</username>
  <password>password1</password>
  <password-confirmation>password1</password-confirmation>
  <email>me@email.com</email>
  <email-confirmation>me@email.com</email-confirmation>
  <verification-method>no_identity_verification</verification-method>
  <privacy-acceptance>true</privacy-acceptance>
  <eula-acceptance>true</eula-acceptance>
  <verified>true</verified>
  <active>true</active>
  <state>Italy</state>
  <radius-group-ids type='array'>
    <radius-group-id>2</radius-group-id>
  </radius-group-ids>
</user>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:42:22 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.503151
Content-Length: 2001
Cache-Control: no-cache
Set-Cookie: _session_id=fblcf0dc11d16a8568a3cf4f3a6d3538; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<user>
  <address>Via con il vento</address>
  <city>Roma</city>
  <image-file-data type="binary" nil="true" encoding="base64"></image-file-data>
  <created-at type="datetime">2012-05-14T11:42:22+02:00</created-at>
  <last-request-at type="datetime" nil="true"></last-request-at>

```

```
<verified-at type="datetime">2012-05-14T11:42:22+02:00</verified-at>
<zip>00100</zip>
<email-confirmation type="NilClass">me@email.com</email-confirmation>
<notes nil="true"></notes>
<updated-at type="datetime">2012-05-14T11:42:22+02:00</updated-at>
<mobile-prefix nil="true"></mobile-prefix>
<recovered-at type="datetime" nil="true"></recovered-at>
<username>username</username>
<birth-date type="date">1976-05-23</birth-date>
<current-login-ip nil="true"></current-login-ip>
<failed-login-count type="integer">0</failed-login-count>
<id type="integer">11</id>
<mobile-suffix nil="true"></mobile-suffix>
<privacy-acceptance type="boolean">true</privacy-acceptance>
<recovered type="boolean" nil="true"></recovered>
<verification-method>no_identity_verification</verification-method>
<current-login-at type="datetime" nil="true"></current-login-at>
<eula-acceptance type="boolean">true</eula-acceptance>
<login-count type="integer">0</login-count>
<given-name>MyName</given-name>
<last-login-ip nil="true"></last-login-ip>
<verified type="boolean">true</verified>
<last-login-at type="datetime" nil="true"></last-login-at>
<surname>MySurname</surname>
<active type="boolean">true</active>
<email>me@email.com</email>
<state>Italy</state>
<radius-groups type="array">
  <radius-group>
    <name>Users</name>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <notes>Default groups for users</notes>
    <updated-at type="datetime">2012-05-10T12:53:53+02:00</updated-at>
    <priority type="integer">2</priority>
    <id type="integer">2</id>
  </radius-group>
</radius-groups>
</user>
```

Read

Required roles

users_browser
users_finder

HTTP Request

Verb	URLs	POSTDATA (XML)
GET	/users/:id.xml /users:username.xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <user> <i>User attributes</i> </user></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/10.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 09:44:30 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.379873
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=57b95bb2e32b14344613a4fc7185472b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/11.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "c8552fdca13e4b1d199d877d3854ee94"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:44:57 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.374612
Content-Length: 2032
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=fddb1c4ce9b71dc86fd21e4d1c0a86f6; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<user>
  <address>Via con il vento</address>
  <city>Roma</city>
  <image-file-data type="binary" nil="true" encoding="base64"></image-file-data>
  <created-at type="datetime">2012-05-14T11:42:22+02:00</created-at>
  <last-request-at type="datetime" nil="true"></last-request-at>
  <verified-at type="datetime">2012-05-14T11:42:22+02:00</verified-at>
  <zip>00100</zip>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T11:42:22+02:00</updated-at>
  <mobile-prefix nil="true"></mobile-prefix>
  <recovered-at type="datetime" nil="true"></recovered-at>
  <username>username</username>
  <birth-date type="date">1976-05-23</birth-date>
  <current-login-ip nil="true"></current-login-ip>
  <failed-login-count type="integer">0</failed-login-count>
  <id type="integer">11</id>
  <mobile-suffix nil="true"></mobile-suffix>
  <privacy-acceptance type="boolean">true</privacy-acceptance>
  <recovered type="boolean" nil="true"></recovered>
  <verification-method>no_identity_verification</verification-method>
  <current-login-at type="datetime" nil="true"></current-login-at>
  <eula-acceptance type="boolean">true</eula-acceptance>
  <login-count type="integer">0</login-count>
  <given-name>MyName</given-name>
  <last-login-ip nil="true"></last-login-ip>
  <verified type="boolean">true</verified>
  <last-login-at type="datetime" nil="true"></last-login-at>
  <surname>MySurname</surname>
  <active type="boolean">true</active>
  <email>me@email.com</email>
  <state>Italy</state>
  <radius-groups type="array">
    <radius-group>
      <name>Users</name>
      <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
      <notes>Default groups for users</notes>
      <updated-at type="datetime">2012-05-10T12:53:53+02:00</updated-at>
      <priority type="integer">2</priority>
      <id type="integer">2</id>
      <user-id type="NilClass">11</user-id>
      <radius-group-id type="NilClass">2</radius-group-id>
    </radius-group>
  </radius-groups>
</user>
```

Read (find)

Required roles

users_finder

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users/ find .xml	<pre><user> <query>username mobilephone or email</query> </user></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <user> User attributes </user></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/uses/find.xml?locale=en -d "
<user>
  <query>non-existant-user</query>
</user>
"
HTTP/1.1 404 Not Found
Date: Fri, 01 Jun 2012 14:19:28 GMT
Server: Apache
X-Powered-By: Phusion Passenger (mod_rails/mod_rack) 3.0.9
X-Runtime: 0.037239
X-UA-Compatible: IE=Edge,chrome=1
Cache-Control: no-cache
Set-Cookie: _session_id=daec8aef7a61c5b71ca761911ec76357; path=/; HttpOnly
Status: 404
Transfer-Encoding: chunked
Content-Type: application/xml; charset=utf-8
```


Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/uses/find.xml?locale=en -d "
<user>
  <query>test</query>
</user>
"
HTTP/1.1 200 OK
Date: Fri, 01 Jun 2012 14:23:36 GMT
Server: Apache
X-Powered-By: Phusion Passenger (mod_rails/mod_rack) 3.0.9
X-Runtime: 0.321074
X-UA-Compatible: IE=Edge,chrome=1
Cache-Control: max-age=0, private, must-revalidate
ETag: "1c41df7728be0ef8941a875a4a41f4e1"
Set-Cookie: _session_id=f1678f3e0ce55497ff4d49e016e2be28; path=/; HttpOnly
Status: 200
Transfer-Encoding: chunked
Content-Type: application/xml; charset=utf-8

<?xml version="1.0" encoding="UTF-8"?>
<user>
  <mobile-suffix nil="true"></mobile-suffix>
  <verification-method>no_identity_verification</verification-method>
  <address>xxxxxxxxxxxxxxxxxxxxxxxx</address>
  <mobile-prefix nil="true"></mobile-prefix>
  <city>Roma</city>
  <image-file-data type="binary" nil="true" encoding="base64"></image-file-data>
  <last-login-at type="datetime" nil="true"></last-login-at>
  <recovered type="boolean" nil="true"></recovered>
  <username>test</username>
  <last-login-ip nil="true"></last-login-ip>
  <notes></notes>
  <recovered-at type="datetime" nil="true"></recovered-at>
  <created-at type="datetime">2012-05-22T17:18:43+02:00</created-at>
  <surname>Guerra</surname>
  <verified-at type="datetime">2012-05-22T17:18:43+02:00</verified-at>
  <zip>00149</zip>
  <current-login-at type="datetime" nil="true"></current-login-at>
  <privacy-acceptance type="boolean">true</privacy-acceptance>
  <state>Italy</state>
  <verified type="boolean">true</verified>
  <current-login-ip nil="true"></current-login-ip>
  <eula-acceptance type="boolean">true</eula-acceptance>
  <given-name>Davide</given-name>
  <email>davide.guerri@gmail.com</email>
  <id type="integer">1</id>
  <active type="boolean">true</active>
  <login-count type="integer">0</login-count>
  <birth-date type="date">1976-05-23</birth-date>
  <failed-login-count type="integer">0</failed-login-count>
  <last-request-at type="datetime" nil="true"></last-request-at>
  <updated-at type="datetime">2012-06-01T11:11:50+02:00</updated-at>
  <radius-groups type="array">
    <radius-group>
      <notes>Gruppo standard per gli utenti RADIUS</notes>
      <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
      <priority type="integer">1</priority>
      <user-id type="NilClass">1</user-id>
      <id type="integer">2</id>
      <name>Users</name>
      <radius-group-id type="NilClass">2</radius-group-id>
      <updated-at type="datetime">2012-05-22T14:30:11+02:00</updated-at>
    </radius-group>
  </radius-groups>
</user>
```

Update

Required roles

users_manager

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/users/: id .xml /users/: username .xml	<?xml version="1.0" encoding="UTF-8"?> <user> <i>User attributes to be changed</i> </user>

HTTP Response

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<?xml version="1.0" encoding="UTF-8"?> <errors> <error> error1 </error> <error> error2 </error> ... <error> errorN </error> </errors>
200	OK	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/11.xml?locale=en -d
"
<user>
  <email>invalid_email</email>
  <email_confirmation>invalid_email</email_confirmation>
</user>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:56:18 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.425134
Content-Length: 116
Cache-Control: no-cache
Set-Cookie: _session_id=8e0ac4db9962d51416c15e1ced2c2b81; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Email should look like an e-mail address</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/11.xml?locale=en -d
"
<user>
  <radius-group-ids type='array'>
    <radius-group-id>1</radius-group-id>
    <radius-group-id>2</radius-group-id>
  </radius-group-ids>
</user>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "0ce4f7827a074f31dc77a8aa295e7037"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:52:42 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.500385
Content-Length: 1
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=3aef73c5a4dc3e6fc73a6c53b747990c; path=/; HttpOnly
```

Destroy

Required roles

users_destroyer

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/users/: id .xml /users/: username .xml	

HTTP Response

HTTP Code	Meaning	Content
404	NOT FOUND	
200	OK	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/11.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 10:12:59 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.328074
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=8929f422f04d061975524d845e14948b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/11.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:12:43 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.469990
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=5dfa997a7b3921d3d21b5339f1b5a036; path=/; HttpOnly
```

Radius Group

Create

Required roles

radius_groups_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/radius_groups.xml	<pre><radius-group> <name>RADIUS GROUP NAME</name> <notes>NOTES</notes> <priority>PRIORITY</priority> </radius-group></pre>

HTTP Response

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>
201	CREATED	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-group> <name>RADIUS GROUP NAME</name> <created-at type="datetime">CREATION DATE</created-at> <updated-at type="datetime">UPDATE DATE</updated-at> <notes>NOTES</notes> <priority type="integer">PRIORITY</priority> <id type="integer">ID</id> </radius-group></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups.xml?
locale=en -d "
<radius-group>
  <name>Disabled</name>
  <notes/>
  <priority>1</priority>
</radius-group>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:33:00 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.155841
Content-Length: 103
Cache-Control: no-cache
Set-Cookie: _session_id=4aa00c265a928c13700f9b85b773ebc9; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Name has already been taken</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups.xml?
locale=en -d "
<radius-group>
  <name>BadGuys</name>
  <notes/>
  <priority>1</priority>
</radius-group>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:33:37 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.162498
Content-Length: 328
Cache-Control: no-cache
Set-Cookie: _session_id=7f49d252645fbeb3128df72a81112998; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-group>
  <name>BadGuys</name>
  <created-at type="datetime">2012-05-14T12:33:37+02:00</created-at>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T12:33:37+02:00</updated-at>
  <priority type="integer">1</priority>
  <id type="integer">5</id>
</radius-group>
```

Read

Required roles

radius_groups_viewer

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/radius_groups.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-groups type="array"> <radius-group> <created-at type="datetime">CREATION DATE</created-at> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <name>RADIUS GROUP NAME</name> <notes>NOTES</notes> <priority>PRIORITY</priority> </radius-group> ... <radius-group> <created-at type="datetime">Another CREATION DATE</created-at> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <name>Another RADIUS GROUP NAME</name> <notes>Another NOTES</notes> <priority>Another PRIORITY</priority> </radius-group> </radius-groups></pre>

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:id.xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-group> <created-at type="datetime">CREATION DATE</created-at> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <name>RADIUS GROUP NAME</name> <notes>NOTES</notes> <priority>PRIORITY</priority> </radius-group></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/8.xml?
locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 10:38:44 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.129446
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=af82ac737f3493c519171a5bdb81b51b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/5.xml?
locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "a795beb4e52f94ec005a577661a70531"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:37:21 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.181116
Content-Length: 328
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=71c3016bfbld626769a6e0bbd5f66eal; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-group>
  <name>BadGuys</name>
  <created-at type="datetime">2012-05-14T12:33:37+02:00</created-at>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T12:33:37+02:00</updated-at>
  <priority type="integer">1</priority>
  <id type="integer">5</id>
</radius-group>
```

Update

Required roles

radius_groups_manager

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/radius_groups/:id.xml	<pre><radius-group> <name>NEW RADIUS GROUP NAME</name> <notes>NEW NOTES</notes> <priority>NEW PRIORITY</priority> </radius-group></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/5.xml?
locale=en -d "
<radius-group>
  <name>BadGuys</name>
  <notes>This group contains users with limited bandwidth</notes>
  <priority>there are priorities...</priority>
</radius-group>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:46:26 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.169848
Content-Length: 100
Cache-Control: no-cache
Set-Cookie: _session_id=20fa7f99d7cda54638b3362deff009d2; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Priority is not a number</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/5.xml?
locale=en -d "
<radius-group>
  <name>BadGuys</name>
  <notes>This group contains users with limited bandwidth</notes>
  <priority>2</priority>
</radius-group>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:51:47 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.156573
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=bc4d23ac2f5dca6f3b00b74b8cd86e2e; path=/; HttpOnly
```

Destroy

Required roles

radius_groups_destroyer

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/radius_groups/: <i>id</i> .xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/5.xml?
locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 10:48:09 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.075196
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=c8952115c25f7b6a79a1b70f72e38f60; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/5.xml?
locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 11:06:11 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.250730
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=450f4a3117f7972157e83aba0b4afd0c; path=/; HttpOnly
```

Users' Radius Checks

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_checks_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users/: user_id /radius_checks.xml /users/: username /radius_checks.xml	<pre><radius-check> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> <op>RADIUS CHECK OPERATOR</op> <value>RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/radius_checks.xml?locale=en -d "  
<radius-check>  
  <check-attribute>Max-Daily-Session</check-attribute>  
  <op>invalid operator</op>  
  <value>360</value>  
</radius-check>  
"  
HTTP/1.1 422  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/users/1  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Mon, 14 May 2012 15:36:41 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 0.424751  
Content-Length: 162  
Cache-Control: no-cache  
Set-Cookie: _session_id=2db790005fa8bc7245200a4d52bdf5ac; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<errors>  
  <error>Check attribute has already been taken</error>  
  <error>Op is not included in the list</error>  
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/radius_checks.xml?locale=en -d "  
<radius-check>  
<check-attribute>Max-Daily-Session</check-attribute>  
<op>=</op>  
<value>360</value>  
</radius-check>  
"  
HTTP/1.1 201 Created  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/users/1  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Mon, 14 May 2012 15:33:29 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 0.392679  
Content-Length: 440  
Cache-Control: no-cache  
Set-Cookie: _session_id=9da67da731971e07c270729432593f6b; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<radius-check>  
  <radius-entity-type>AccountCommon</radius-entity-type>  
  <created-at type="datetime">2012-05-14T17:33:29+02:00</created-at>  
  <op>=</op>  
  <radius-entity-id type="integer">1</radius-entity-id>  
  <updated-at type="datetime">2012-05-14T17:33:29+02:00</updated-at>  
  <id type="integer">23</id>  
  <value>360</value>  
  <check-attribute>Max-Daily-Session</check-attribute>  
</radius-check>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_checks.xml /users/: username /radius_checks.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-checks type="array"> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> ... <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS CHECK VALUE</value> <check-attribute>Another RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> </radius-checks></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_checks/: id .xml /users/: username /radius_checks/: id .xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/nonexistaetuser/
radius_checks.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 15:03:05 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.466966
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=a9ae5f4ab329f341431e7ac2a882cd18; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/1/
radius_checks.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "93e91e7302837789def657348b326894"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 14:59:42 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.399107
Content-Length: 520
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=1f81bd2e8982861cdb935ae0fa430e9e; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-checks type="array">
  <radius-check>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-10T12:53:16+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-10T12:53:16+02:00</updated-at>
    <id type="integer">22</id>
    <value>3000000000</value>
    <check-attribute>Max-Daily-Session-Traffic</check-attribute>
  </radius-check>
</radius-checks>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/users/: user_id /radius_checks/: id .xml /users/: username /radius_checks/: id .xml	<pre><radius-check> <check-attribute>New RADIUS CHECK ATTRIBUTE</check-attribute> <op>New RADIUS CHECK OPERATOR</op> <value>New RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_checks/23.xml?locale=en -d "
<radius-check>
  <value></value>
</radius-check>
"
HTTP/1.1 422
X-UA-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:44:04 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.527406
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=593306e56c35db97728e579a62c213d0; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_checks/23.xml?locale=en -d "
<radius-check>
  <value>360</value>
</radius-check>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:43:08 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.419544
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f8adbae37924b9f49320ba2cc6b80584; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/users/: user_id /radius_checks/: id .xml /users/: username /radius_checks/: id .xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_checks/24.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:54:07 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.343375
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=46f91545873e861b54a915fc9497643d; path=/; HttpOnly
```


Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_checks/21.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 15:51:51 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.341959
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=816a1e1ff1ea2d4ca0440b24ec128c63; path=/; HttpOnly
```

Users' Radius Replies

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_replies_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users/: user_id /radius_replies.xml /users/: username /radius_replies.xml	<pre><radius-reply> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> <op>RADIUS REPLY OPERATOR</op> <value>RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/
radius_replies.xml?locale=en -d "
<radius-reply>
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>
  <op>invalid operator</op>
  <value>10240</value>
</radius-reply>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:03:22 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.411560
Content-Length: 106
Cache-Control: no-cache
Set-Cookie: _session_id=e1ee668bfd9b7e80e77ce3852068a879; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Op is not included in the list</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/
radius_replies.xml?locale=en -d "
<radius-reply>
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>
  <op>:=</op>
  <value>10240</value>
</radius-reply>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:03:48 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.542533
Content-Length: 447
Cache-Control: no-cache
Set-Cookie: _session_id=0930979d1837e1c67dca3db25b7f09ef; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-reply>
  <radius-entity-type>AccountCommon</radius-entity-type>
  <created-at type="datetime">2012-05-15T10:03:48+02:00</created-at>
  <op>:=</op>
  <radius-entity-id type="integer">1</radius-entity-id>
  <updated-at type="datetime">2012-05-15T10:03:48+02:00</updated-at>
  <id type="integer">13</id>
  <value>10240</value>
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>
</radius-reply>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_replies.xml /users/: username /radius_replies.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-replies type="array"> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> ... <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS REPLY VALUE</value> <reply-attribute>Another RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> </radius-replies ></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_replies/: id .xml /users/: username /radius_replies/: id .xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/nonexistaetuser/
radius_replies.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:07:22 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 9.118337
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=86d79c7234484a1e63bdbc9d87d98853; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/1/radius_replies.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "df84240836109b3053ec5a83630fcf6d"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:07:47 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 1.482649
Content-Length: 1364
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=5dfc93df4bc7ccc3865f4d7e86a144b1; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-replies type="array">
  <radius-reply>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-10T12:51:53+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-10T12:52:05+02:00</updated-at>
    <id type="integer">11</id>
    <value>2048</value>
    <reply-attribute>WISPr-Bandwidth-Max-Down</reply-attribute>
  </radius-reply>
  <radius-reply>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-10T12:52:48+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-10T12:52:48+02:00</updated-at>
    <id type="integer">12</id>
    <value>3600</value>
    <reply-attribute>Session-Timeout</reply-attribute>
  </radius-reply>
  <radius-reply>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-15T10:03:48+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-15T10:03:48+02:00</updated-at>
    <id type="integer">13</id>
    <value>10240</value>
    <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>
  </radius-reply>
</radius-replies>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/users/: user_id /radius_replies/: id .xml /users/: username /radius_replies/: id .xml	<pre><radius-reply> <reply-attribute>New RADIUS REPLY ATTRIBUTE</reply-attribute> <op>New RADIUS REPLY OPERATOR</op> <value>New RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_replies/
11.xml?locale=en -d "
<radius-reply>
  <value></value>
</radius-reply>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:11:36 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.395970
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=0ce8eb422d8c00a231e415d1e09e92e3; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_replies/
11.xml?locale=en -d "
<radius-reply>
  <value>4096</value>
</radius-reply>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:12:17 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.453938
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=31c8c996491c4a1e04e73c8e15b79b28; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/users/: user_id /radius_replies/: id .xml /users/: username /radius_replies/: id .xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_replies/11.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:16:05 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.371625
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=ab83aa46540ba5f98a3d304cc405927b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_replies/11.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:16:02 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.462937
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f43af7dabccb0e4c2cb4c57cbb5804b1; path=/; HttpOnly
```


RADIUS Groups' Radius Checks

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_checks_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/radius_groups/:radius_group_id/radius_checks.xml	<pre><radius-check> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> <op>RADIUS CHECK OPERATOR</op> <value>RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/
radius_checks.xml?locale=en -d "
<radius-check>
  <check-attribute>Max-Daily-Session</check-attribute>
  <op>invalid operator</op>
  <value>360</value>
</radius-check>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/4
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:21:32 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.377727
Content-Length: 106
Cache-Control: no-cache
Set-Cookie: _session_id=5f74dfe82d209d308eff1d394a499e45; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Op is not included in the list</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/
radius_checks.xml?locale=en -d "
<radius-check>
  <check-attribute>Max-Daily-Session</check-attribute>
  <op>=</op>
  <value>360</value>
</radius-check>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/4
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:21:52 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.645789
Content-Length: 438
Cache-Control: no-cache
Set-Cookie: _session_id=8a3556aa0172340bb3592eee2aec1634; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-check>
  <radius-entity-type>RadiusGroup</radius-entity-type>
  <created-at type="datetime">2012-05-15T10:21:51+02:00</created-at>
  <op>=</op>
  <radius-entity-id type="integer">4</radius-entity-id>
  <updated-at type="datetime">2012-05-15T10:21:51+02:00</updated-at>
  <id type="integer">25</id>
  <value>360</value>
  <check-attribute>Max-Daily-Session</check-attribute>
</radius-check>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_checks.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-checks type="array"> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> ... <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS CHECK VALUE</value> <check-attribute>Another RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> </radius-checks></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_checks/:id.xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/
nonexisttaetgroup/radius_checks.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:23:31 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.442479
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f39004aa242f44d51ec71ble7577212e; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/4/
radius_checks.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "2942b479761621604d747d7cc64a6b53"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:24:08 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.251624
Content-Length: 932
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=72b9d101cad2e018f2472bacd3cb6e7d; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-checks type="array">
  <radius-check>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">4</radius-entity-id>
    <updated-at type="datetime">2009-12-28T14:36:50+01:00</updated-at>
    <id type="integer">3</id>
    <value>change_me_please!</value>
    <check-attribute>User-Password</check-attribute>
  </radius-check>
  <radius-check>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2012-05-15T10:21:51+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">4</radius-entity-id>
    <updated-at type="datetime">2012-05-15T10:21:51+02:00</updated-at>
    <id type="integer">25</id>
    <value>360</value>
    <check-attribute>Max-Daily-Session</check-attribute>
  </radius-check>
</radius-checks>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/radius_groups/:radius_group_id/radius_checks/:id.xml	<pre><radius-check> <check-attribute>New RADIUS CHECK ATTRIBUTE</check-attribute> <op>New RADIUS CHECK OPERATOR</op> <value>New RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/4/
radius_checks/3.xml?locale=en -d "
<radius-check>
  <value></value>
</radius-check>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/4
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:26:36 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.661261
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=982ad3058e980e586081f0550d45ea47; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/4/
radius_checks/3.xml?locale=en -d "
<radius-check>
  <value>supercalifragilistichepspiralidoso</value>
</radius-check>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:32:33 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.376108
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f42e30e0d934763b6972397cf3412a9f; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/radius_groups/:radius_group_id/radius_checks/:id.xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/4/radius_checks/111.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:35:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.170062
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=dea94f6593a64304bb9468639abfb884; path=/; HttpOnly
```

Successful request

```
curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/4/radius_checks/3.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:35:59 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.185366
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=2e15b51444c904b4b9af16f624fcfdbb; path=/; HttpOnly
```

RADIUS Groups' Radius Replies

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_replies_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/radius_groups/:radius_group_id/radius_replies.xml	<pre><radius-reply> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> <op>RADIUS REPLY OPERATOR</op> <value>RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
201	CREATED	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/radius_replies.xml?locale=en -d "  
<radius-reply>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
  <op>invalid operator</op>  
  <value>10240</value>  
</radius-reply>  
"  
HTTP/1.1 422  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/radius_groups/4  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Tue, 15 May 2012 09:22:24 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 0.384184  
Content-Length: 106  
Cache-Control: no-cache  
Set-Cookie: _session_id=190339e1c3e3a2fe8b8f4b19190b1e9f; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<errors>  
  <error>Op is not included in the list</error>  
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/radius_replies.xml?locale=en -d "  
<radius-reply>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
  <op>:=</op>  
  <value>10240</value>  
</radius-reply>  
"  
HTTP/1.1 201 Created  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/radius_groups/4  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Tue, 15 May 2012 09:23:10 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 7.255229  
Content-Length: 445  
Cache-Control: no-cache  
Set-Cookie: _session_id=5a0a70a9a7b2c2b506511205608a785c; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<radius-reply>  
  <radius-entity-type>RadiusGroup</radius-entity-type>  
  <created-at type="datetime">2012-05-15T11:23:06+02:00</created-at>  
  <op>:=</op>  
  <radius-entity-id type="integer">4</radius-entity-id>  
  <updated-at type="datetime">2012-05-15T11:23:06+02:00</updated-at>  
  <id type="integer">14</id>  
  <value>10240</value>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
</radius-reply>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_replies.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-replies type="array"> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> ... <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS REPLY VALUE</value> <reply-attribute>Another RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> </radius-replies ></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_replies/:id.xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/
nonexistaetuser/radius_replies.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 11:07:24 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.666754
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=ce548ed493e403289432cf209ec4f3d5; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/3/radius_replies.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "c9120086115377126ff9b0ba31ce83f9"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 11:08:33 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.172419
Content-Length: 916
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=fd72033f69ef410f799105cc7d77c077; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-replies type="array">
  <radius-reply>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">3</radius-entity-id>
    <updated-at type="datetime">2009-12-28T14:36:50+01:00</updated-at>
    <id type="integer">3</id>
    <value>1200</value>
    <reply-attribute>Idle-Timeout</reply-attribute>
  </radius-reply>
  <radius-reply>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">3</radius-entity-id>
    <updated-at type="datetime">2009-12-28T14:36:50+01:00</updated-at>
    <id type="integer">4</id>
    <value>1800</value>
    <reply-attribute>Session-Timeout</reply-attribute>
  </radius-reply>
</radius-replies>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/radius_groups/:radius_group_id/radius_replies/:id.xml	<pre><radius-reply> <reply-attribute>New RADIUS REPLY ATTRIBUTE</reply-attribute> <op>New RADIUS REPLY OPERATOR</op> <value>New RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/3/
radius_replies/3.xml?locale=en -d "
<radius-reply>
  <value></value>
</radius-reply>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/3
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 12:17:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.390501
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=18fc5dfb0f04c4c75596cbe14af4a3e7; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/3/
radius_replies/3.xml?locale=en -d "
<radius-reply>
  <value>testvalue</value>
</radius-reply>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 12:17:57 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.877199
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=ccc1c2453af44ba20f068df3c30515ba; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/radius_groups/:radius_group_id/radius_replies/:id.xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/3/radius_replies/3.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 12:18:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.210340
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=78ce415f4c3a5f0cfc74e8b2762f2657; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/3/radius_replies/3.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 12:18:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.201142
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=9e6cf4a771cbe2f72f843788ef614668; path=/; HttpOnly
```