

Established in collaboration with MIT

50.005 Computer System Engineering

# **NS Lab 1: Internet Routes and Measurement of Round Trip Times**

Name:			
ID:			

#### **Overview**

In this lab exercise, you will learn how to use ping and traceroute to measure round trip times and find network routes.

#### **Learning objectives**

At the end of this lab exercise, you should be able to:

- Understand how the ping and traceroute utilities work.
- Use the ping utility to measure network round trip times.
- Use the traceroute utility to find network routes.
- Observe and understand the effects of varying packet sizes on delays experienced.

#### **Preparation**

You will need ping and traceroute to be installed on your Ubuntu virtual machine. Most Ubuntu installations should already include ping by default. You can install traceroute by running "sudo apt-get install traceroute" from the command line.

### **Deliverables**

Complete the activities and answer the questions in the handout. Submit a report containing your <a href="mailto:name"><u>name</u></a>, <a href="mailto:student ID"><u>student ID</u></a> and <a href="mailto:answers"><u>answers</u></a> to eDimension before <a href="mailto:Tuesday 29 March 2016"><u>Tuesday 29 March 2016</u></a>, <a href="mailto:11:59pm">11:59pm</a> latest. Late submissions will be dealt with according to the course policy.

## Part 1: Measurement of round trip times using ping

The ping utility is one of the most widely-used network utilities. It enables you to measure the time that it takes for a packet to travel through the Internet to a remote host and back.

The ping utility works by sending a short message, known as an *echo-request*, to a remote host using the Internet Control Message Protocol (ICMP). When a host that supports ICMP receives an echo-request message, it replies by sending an echo-response message back to the originating host.

In the first part of this lab exercise, you will use the ping utility to send echo requests to a number of different hosts. In many of the exercises, you will be referring to hosts using their DNS names rather than their IP addresses. For more information about ping, you can look up its manual page by running "man ping" from the command line.

#### **Round trip times**

Use ping to send 10 packets to each of the following hosts. Each packet should have a size of 56 bytes, and there should be an interval of 5 seconds between each packet sent.

```
www.csail.mit.edu
www.berkeley.edu
www.usyd.edu.au
www.kyoto-u.ac.jp
```

*Note:* The size of each packet is 56 bytes by default, but you may observe that the actual size of the packet is larger than 56 bytes. You can look up the manual for ping to understand why such a discrepancy exists.

**Question 1 (10pt):** For each host, record the percentage of packets sent that resulted in a successful response. Record also the minimum, average, and maximum round trip times for the packets that resulted in a response.

Website	Successful Percentage %	Min RTT	Average RTT	Max RTT
www.csail.mit.edu				
www.berkeley.edu				
www.usyd.edu.au				
www.kyoto-u.ac.jp				

Question 2 (10pt): Describe and explain the differences in the minimum round trip time to each of these hosts.

**Question 3 (10pt):** Repeat the exercise using packet sizes of 56, 512 and 1024 bytes. Record the minimum, average, and maximum round trip times for each of the packet sizes. Why are the minimum round-trip times to the same hosts different when using 56, 512, and 1024—byte packets?

Website	Data byte	Successful	Min RTT	Average	Max
	packets	Percentage %		RTT	RTT
www.csail.mit.edu	56				
	512				
	1024				
www.berkeley.edu	56				
	512				
	1024				
www.usyd.edu.au	56				
	512				
	1024				
www.kyoto-u.ac.jp	56				
	512				
	1024				

## **Unanswered pings**

Use ping to send 100 packets to the following host. Each packet should have a size of 56 bytes, and there should be an interval of 5 seconds between each packet sent.

www.wits.ac.za

**Question 4 (10pt):** Record the percentage of the packets sent that resulted in a successful response. What are some possible reasons why you may not have received a response? (Be sure to check the host in a web browser.)

#### Part 2: Understanding Internet routes using traceroute

The traceroute utility is another useful network utility. It enables you to trace the route taken by a packet from your machine to a remote host.

Here is an example of the output produced when traceroute is used to trace the route taken by a packet to www.mit.edu.

traceroute to www.mit.edu (118.215.81.86), 30 hops max, 60 byte packets

```
1 192.168.9.2 (192.168.9.2) 0.221 ms 0.193 ms 0.107 ms
```

- 2 10.12.0.1 (10.12.0.1) 3.363 ms 2.555 ms 3.253 ms
- 3 172.16.1.106 (172.16.1.106) 3.072 ms 3.416 ms 3.418 ms
- 4 172.16.1.210 (172.16.1.210) 4.977 ms 4.712 ms 4.921 ms
- 5 192.168.22.27 (192.168.22.27) 4.806 ms 6.521 ms 6.451 ms
- 6 103.24.77.1 (103.24.77.1) 7.172 ms 3.590 ms 3.187 ms
- 7 201.210-193-8.qala.com.sg (210.193.8.201) 4.312 ms 9.056 ms 7.870 ms
- 8 137.203-211-158.unknown.qala.com.sg (203.211.158.137) 8.904 ms 6.690 ms 6.555 ms
- 9 213.203-211-158.unknown.qala.com.sg (203.211.158.213) 7.710 ms 5.423 ms 5.193 ms
- 10 203.116.10.125 (203.116.10.125) 6.783 ms 6.705 ms 6.440 ms

Each line in the output begins with a host on the route from your computer to www.mit.edu, followed by the round-trip times for 3 packets sent to that host. For more information about traceroute, you can look up its manual page by running "man traceroute" from the command line.


#### **Basics**

**Question 5 (10pt):** Explain how traceroute discovers a path to a remote host. (*Hint:* The traceroute manual will be helpful for answering this question.)


#### **Route asymmetries**

In this exercise, you will run traceroute in two opposite directions. First, you will run traceroute on a remote host to see the route taken to your network. You will also run traceroute from your computer to see the route taken to that host.


**Step 1:** Find out your computer's public IP address. (*Hint:* You can use a website like <a href="http://www.whatismypublicip.com/">http://www.whatismypublicip.com/</a>, or search for "what is my ip" using Google's search engine.)



**Step 2:** Visit <a href="http://tools.pingdom.com/ping/">http://tools.pingdom.com/ping/</a> in your web browser. Enter your computer's public IP address, select the "Traceroute" option and click "Test Now" to start a traceroute to your computer.



**Step 3:** After traceroute finishes running, you should be able to view the route taken from tools.pingdom.com to your network. Record the IP address of the first hop, which will be used in the next step.



**Step 4:** On your computer, run traceroute using the IP address recorded in the previous step as the remote destination.

\$ traceroute <ip address from step 3>

**Question 6 (10pt):** Record the output of traceroute when run in both directions above.

**Question 7 (10pt):** Describe anything unusual you might observe about the output. Are the same routers traversed in both directions? If no, why might this be the case?

#### **Blackholes**

Run traceroute with 18.31.0.200 set as the remote host.

\$ traceroute 18.31.0.200

**Question 8 (10pt):** Record the output of the above command. Describe what is strange about the observed output, and why traceroute gives you such an output. (*Hint:* The traceroute manual will be helpful for answering this question.)