gateway shift_lam4: best allocation at equal budget (secondary)

Equal total budget per arm per seed: B = N × n_steps = 3.2768e+09 walker-steps at every N (h = 2.5e-05, T_N = B h / N); 32 seeds per (N, method). Best ABF N (all N) vs best FR N (N ≥ 2) at equal B; the bootstrap re-selects N in every resample.




```
ABF best N = 128: 0.0506 [0.05, 0.0531]
FR  best N = 128: 0.0686 [0.0674, 0.0734]
FR - ABF: +0.0181 [+0.0151, +0.0228]
relative: +35.7 % [+28.6 %, +45.4 %]
P(best FR < best ABF) = 0
```




```
ABF best N = 128: 0.0328 [0.0327, 0.033]
FR  best N = 128: 0.0494 [0.047, 0.0515]
FR - ABF: +0.0165 [+0.0141, +0.0187]
relative: +50.3 % [+42.9 %, +57.0 %]
P(best FR < best ABF) = 0
```




```
ABF best N = 128: 0.438 [0.395, 0.47]
FR  best N = 128: 0.015 [0.015, 0.015]
FR - ABF: -0.422 [-0.455, -0.38]
relative: -96.6 % [-96.8 %, -96.2 %]
P(best FR < best ABF) = 1
```







gateway shift_lam4 · S8s_best_allocation_secondary · status: all planned (N, seed, method) complete · FR is not defined at N = 1 (ABF only, by design).
Bottom: fraction of bootstrap resamples in which each N is best (seeds resampled within each N, one draw shared by both methods; N tied at the minimum share the credit); 'all cens.' = every N censored in that resample (tau only). tau: common budget grid. A 'REDUCED ladder' line names planned N without data: the minimum is then over fewer N. Text: best values with bootstrap 95 % CIs, the CI of best FR - best ABF (absolute and relative) and the fraction of resamples in which the best FR beats the best ABF.
Source results/final_campaign/expA/shift_lam4/analysis/summary.json (generated 2026-10-11T09:25:19Z, eqb_metrics/2, 10000 bootstrap resamples); plot_synthesis/2.