Toward Impact-resilient Quadrotor Design, Collision Characterization and Recovery Control to Sustain Flight after Collisions

Zhichao Liu   and   **Konstantinos Karydis**

Autonomous Robots and Control Systems Laboratory

University of California, Riverside

Motivations

Quadrotor applications:

- ❖ Deployed in complex, cluttered and partially-known environments
- ❖ Aggressive maneuvers
- ❖ Interactions with environments
- ❖ Swarms

Survive collisions

Image credit: FAST Lab, ZJU

Post-collision freefalls

- ❖ Risk of damaging sensitive onboard devices
- ❖ Unable to land on certain surfaces, e.g., fluidic, high-temperature

Sustain flight after collisions

Challenges & Objectives

Challenges:

- ❖ Impact-resilient mechanical design

- ❖ Rigidity for model-based control in free flight

- ❖ Sensors for rapid and accurate collision detections

- ❖ Sustain post-collision flight

Objectives:

- ❖ A novel collision-resilient quadrotor with a compliant arm design to enable model-based control while allowing for 1 DOF to absorb shocks

- ❖ A novel collision detection method based on Hall sensors and a recovery control to sustain flight after collisions

Related Work

Existing work on collision-resilient UAVs includes:

❖ **Incorporating protective structures to reduce impact**

▪ Cages or protective frames
  e.g., A. Klaptocz et al. 2013, R. Naldi et al. 2014, Y. Mulgaonkar et al. 2017

▪ Rotation or added angular momentum to reject disturbance
  e.g., A. Borid et al. 2014, N. Bucki et al. 2018

▪ Bio-inspired approaches and soft materials to survive crashes
  e.g., S. Mintchev et al. 2017, P. Sareh et al. 2018, J. Shu et al. 2019

❖ Utilizing sensors to detect collisions and recover

Related Work

Existing work on collision-resilient UAVs includes:

❖ Incorporating protective structures to reduce impact

❖ **Utilizing sensors to detect collisions and recover**

▪ Inertial measurement unit (IMU)
  e.g., T. Tomić et al. 2017, G. Dicker et al. 2017, A. Battiston et al. 2019, Y. Mulgaonkar et al. 2020

▪ Motion capture system (MoCap)
  e.g., Y. Mulgaonkar et al. 2017

▪ Hall sensor
 *e.g., A. Briod et al. 2013*

Summary

In this work, we develop or propose:

❖ A novel <u>A</u>ctively <u>R</u>esilient <u>Q</u>uadrotor (ARQ) that incorporates compliance and collision resilience

❖ A collision detection and characterization method based on Hall sensors

❖ A recovery method to generate and track smooth trajectories after collisions

590 mm

380 mm

Safety Tether

Novel Arm Design

❖ Novel arm design consists of:

- Prismatic joint
- Shock absorber
- Hall sensor
- Magnet

❖ Retain rigidity when in free flight while allowing for 1 passive DOF

Hardware Overview

❖ Design is based on of-the-shelf components and custom 3D-printed parts.

❖ Size:
- 380mm from propeller tip to tip
- 590mm from protective cage tip to tip

❖ Weight: 1.42kg with the battery

Wifi Module

Arduino Nano

Odroid XU4

Pixhawk 4 Mini

Magnet

Hall Sensor

Prismatic Joint

Shock Absorber

5x5.3x3 Propeller

JB2208 Motor 2400kv

Power Distribution Board

Electronic Speed Controller (ESC)

Protective Cage

Modeling & Control

❖ Quadrotor equations of motion

$$\dot{\mathbf{x}} = \mathbf{v}$$
$$m\dot{\mathbf{v}} = -mg\mathbf{e}_3 + f\mathbf{R}\mathbf{e}_3$$
$$\dot{\mathbf{R}} = \mathbf{R}\hat{\Omega}$$
$$J\dot{\Omega} + \Omega \times J\Omega = \mathbf{M}$$

❖ Calculate forces for each motor*

$$\begin{bmatrix} f \\ M_1 \\ M_2 \\ M_3 \end{bmatrix} = \begin{bmatrix} 1 & 1 & 1 & 1 \\ 0 & l & 0 & -l \\ -l & 0 & l & 0 \\ c_f & -c_f & c_f & -c_f \end{bmatrix} \begin{bmatrix} f_1 \\ f_2 \\ f_3 \\ f_4 \end{bmatrix}$$

❖ Geometric tracking control (*T. Lee et al. 2010*)

$$f = (-k_x\mathbf{e}_x - k_v\mathbf{e}_v + mg\mathbf{e}_3 + m\ddot{\mathbf{x}}_d) \cdot \mathbf{R}\mathbf{e}_3$$
$$\mathbf{M} = -k_R\mathbf{e}_R - k_\Omega\mathbf{e}_\Omega + \Omega \times J\Omega$$
$$- J(\hat{\Omega}\mathbf{R}^T\mathbf{R}_d\Omega_d - \mathbf{R}^T\mathbf{R}_d\dot{\Omega}_d)$$

*When a collision happens, the arm length shortens, therefore changing the parameters in the equation.
However, ARQ can wait until a collision ends, and the arm length is recovered. In this way, the model can be used
before and after collision.

Collision Detection & Characterization

- ❖ **Objective**: to detect and characterize collision based on Hall sensor readings, e.g., maximum collision intensity, position and start time

- ❖ Calculate projections of Hall sensor readings*

- ❖ Estimate the intensity and position (in the body frame) of the collision

- ❖ Follow an algorithm to find the maximum collision intensity and its position, as well as a time to trigger recovery control (arm length recovered)

* $0 \leq d_i \leq 1$ denotes values from the analog to digital conversions, where 0 means no contact force is detected and 1 indicates that the minimum length of the shock absorber reached.

Recovery & Software

- ❖ **Objective**: to generate and track a smooth and safe trajectory to stabilize the robot after a collision

- ❖ Calculate a safe desired position* (in world frame) based on the collision characterization

- ❖ Generate a minimum-snap trajectory to reach the goal position and stop by solving an optimization with constraints

- ❖ Track the desired trajectory with geometric control to stabilize the robot

Software Architecture

* In the opposite direction of the collision at a distance proportional to the collision intensity.

Experiment

1. Passive collision

❖ ARQ can sustain flight after being passively hit at a collision speed* of 1.3 m/s

* The norm of the vehicle's linear velocity after the collision.

Experiment

1. Passive collision

❖ ARQ can sustain flight after being passively hit at a collision speed* of 1.3 m/s

* The norm of the vehicle's linear velocity after the collision.

Experiment
2. Wall collision

❖ ARQ can recover from wall collision with a single arm in contact at a collision speed of 2.58m/s

Experiment

2. Wall collision

❖ ARQ can estimate the intensity and orientation of the collision based on hour Hall sensors, to recover from wall collision with two arms at a speed of 1.92m/s

❖ One Arm

❖ Two Arms

Experiment

2. Wall collision

❖ One Arm

❖ Two Arms

❖ State Tracking

Experiment

2. Wall collision

❖ **More experiments**:

- Success rate tests in both single-arm and two-arm types at the highest speeds

- Results: 9/10 and 8/10 successful recoveries* for the two types

* Survive collisions and sustain flight.

Experiment

2. Wall collision

❖ **More experiments**:

▪ Compliant arm without recovery controller &
  Rigid arm without recovery controller tests

▪ <u>Results</u>: demonstrate the individual contribution
  of compliance and recovery control

Compliant arm without recovery controller test

Rigid arm without recovery controller test

Experiment

3. Pole collision & 4. Unstructured surface collision

❖ Pole Collision, 2.04m/s

❖ Unstructured Surface Collision, 1.95m/s

❖ ARQ does not require prior knowledge of collision models

Experiment
5. Free Fall

❖ ARQ can survive free falls* from
   1.8 m high, reaching a maximum
   velocity of 5.9 m/s

* The battery is removed. The robot weighs 1.12 kg without
the battery.

Playback speed: 0.2x

Discussion

Limitations:

❖ Collisions in vertical directions

❖ Cylinder obstacles with small diameters

❖ Impact of added weight to free flight performance

Future Work:

❖ Improve protective cage design

❖ Integration with map-based navigation methods

❖ Outdoor environments

Toward Impact-resilient Quadrotor Design, Collision Characterization and Recovery Control to Sustain Flight after Collisions

Thank you!
Any questions?