

Tictactoe Game

Making Game with Python (1)


Zhihong (John) Zeng & Andrew Zeng



Agenda

- Introduction
- Numpy (multi-dimensional arrays)
- Flowchart
- function definition and test
 - create_board, input_player_selection, who_go_first, make_move
 - game_won, column_won, row_won, diag_won
 - Get_available_move, get_player_move, get_random_move
- Main function

Introduction



Numpy

- NumPy is a Python library, adding support for large, multi-dimensional arrays, along with a large collection of high-level mathematical functions
- Installation:
 - Find the python executable path:
 - `import sys`
 - `print(sys.executable)`
 - Pip install
 - Go to the path
 - `python -m pip install numpy`
 - Test
 - `Import numpy`

Numpy (cont): create 2D arrays

- Import numpy as np
- `a = np.full((height, width), value)`
- Size of array: `a.shape` (height, width)
- Exercise:

- Import numpy as np
- `a = np.full((3,3), ' ')`
- `print(a)`
- `print(a.shape)`
- `c = np.arange(6)`
- `print(c, c.shape)`
- `d = c.reshape((2,3))`
- `print(d, d.shape)`

```
A= array([[ 0,  1,  2],  
         [ 3,  4,  5],  
         [ 6,  7,  8],  
         [ 9, 10, 11]])
```

```
A.shape  
# (4,3): height=4, width=3
```


```
print(A[2,1])  
# 7
```

Numpy (cont): access

- `array[y_index, x_index]`
- Exercise:
 - `a = np.arange(6).reshape((2,3))`
 - `print(a)`
 - `print(a[0,1])`
 - `a[0,1] = 9`
 - `print(a)`
- For loop:
- Exercise:

```
for row in a:  
    print(row)  
    for x in row:  
        print(x)
```

Tictactoe (pause to draw the flowchart)



Flowchart

Welcome, input player selection (X or O)

Who go first (random choice)

Create game board

While Loop condition on available_move:
 If turn is player:
 Get_player_move
 If game won:
 Congrats, game over
 If turn is computer:
 Get_computer_move
 If game won:
 Computer won, game over

Game is a tie, game over

Debug: function definition and test

Tictactoc.py: Function definition

```
def game_won():  
    ....
```

tictactoe_test.py

```
print(game_won)  
assert create_board==True, 'Fail'
```



If tictactoe_test.py fails, go to check code

Create game board

```
def create_board(size, value=' '):  
    board = np.full((size,size), value)  
    return board
```

```
print('\n----Test create_board\n')  
print(create_board(3), ' ')  
print(create_board(2), 5)  
print(create_board(4))
```

input_player_selection

```
def input_player_selection():  
    letter = "  
    while letter not in ['X', 'O']:  
        letter = input('Do you want to be X or O?')  
        letter = letter.upper()  
    if letter == 'X':  
        return ['X', 'O']  
    else:  
        return ['O', 'X']
```

```
print('\n----test input_player_letter\n')  
print(input_player_selection())
```

Who go first

```
def who_go_first():  
    ans = random.randint(0,1)  
    if ans:  
        return 'computer'  
    else:  
        return 'player'
```

```
print('\n----test who_go_first\n')  
print(who_go_first())  
print(who_go_first())  
print(who_go_first())
```

Make move

```
def make_move(board, letter, position):  
    board[position[0], position[1]] = letter
```

```
print('\n----test make_move\n')  
board = create_board(3)  
make_move(board, 'X', (0, 0))  
print(board)  
make_move(board, 'O', (2, 2))  
print(board)
```

Check column won

```
def column_won(board, letter):  
    height, width = board.shape  
    for x in range(width):  
        won = True  
        for y in range(height):  
            if board[y, x] != letter:  
                won = False  
                break  
        if won:  
            return True  
    return False
```

```
print('\n----test column_won\n')  
board = create_board(3)  
print(board)  
ans = column_won(board, 'X')  
assert not ans, 'Fail'  
board[0, 0] = 'X'  
board[1, 0] = 'X'  
board[2, 0] = 'X'  
print(board)  
ans = column_won(board, 'X')  
assert ans, 'Fail'
```

Check row won

```
def row_won(board, letter):
    height, width = board.shape
    for y in range(height):
        won = True
        for x in range(width):
            if board[y, x] != letter:
                won = False
                break
        if won:
            return True
    return False
```

```
print('\n----test row_won\n')
board = create_board(3)
print(board)
ans = row_won(board, 'X')
assert not ans, 'Fail'
board[1, 0] = 'X'
board[1, 1] = 'X'
board[1, 2] = 'X'
print(board)
ans = row_won(board, 'X')
assert ans, 'Fail'
```

Check diagonal won

```
def diag_won(board, letter):
    height, width = board.shape
    won = True
    for y in range(height):
        if board[y, y] != letter:
            won = False
            break
    if won:
        return True

    won = True
    for y in range(height):
        if board[y, height-1-y] != letter:
            won = False
            break

    return won
```

```
print('\n----test diag_won\n')
board = create_board(3)
print(board)
ans = diag_won(board, 'X')
assert not ans, 'Fail'
board[0, 0] = 'X'
board[1, 1] = 'X'
board[2, 2] = 'X'
print(board)
ans = diag_won(board, 'X')
assert ans, 'Fail'
```


Check game won

```
def game_won(board, letter):  
    return column_won(board, letter) \  
        or row_won(board, letter) \  
        or diag_won(board, letter)
```

```
print('\n-----test game_won\n')  
board = create_board(3)  
ans = game_won(board, 'X')  
assert not ans, 'Fail'  
board[0, 2] = 'X'  
board[1, 2] = 'X'  
board[2, 2] = 'X'  
ans = game_won(board, 'X')  
assert ans, 'Fail'  
print('\n==== Success====\n')
```

Get available move

```
def get_available_move(board):  
    height, width = board.shape  
    move = []  
    for y in range(height):  
        for x in range(width):  
            if board[y, x] == '':  
                move.append([y, x])  
    return move
```

```
print('\n----test get_available_move\n')  
board = create_board(3)  
board[0, 0] = 'X'  
board[1, 1] = 'O'  
board[2, 2] = 'O'  
ans = get_available_move(board)  
print(board)  
print('available_move: {}'.format(ans))
```

Get player move

```
def get_player_move(board, letter):  
    height, width = board.shape  
    available_move = get_available_move(board)  
    move = (-1, -1)  
    while move not in available_move:  
        ans = input('What is your next move? ')  
        move = ans.split(',')  
        move = list(map(int, move))  
    make_move(board, letter, move)
```

```
print('\n----test get_player_move\n')  
board = create_board(3)  
print(board)  
get_player_move(board, 'X')  
print(board)
```

Get random move

```
def get_random_move(board, letter):  
    print('computer move')  
    available_move = get_available_move(board)  
    move = random.choice(available_move)  
    make_move(board, letter, move)
```

```
print('\n-----test get_random_move\n')  
board = create_board(3)  
get_random_move(board, 'O')  
print(board)  
board = create_board(3)  
get_random_move(board, 'O')  
print(board)
```

Main function

```
def tictactoe():  
    print('Welcom to Tic-Tac-Toe!')  
    player, computer = input_player_selection()  
    print('You are {}, and computer is {}'.format(player, computer))  
    first = who_go_first()  
    print('{} go first'.format(first))  
    board = create_board(3)  
    turn = first
```

Main function (cont)

```
while get_available_move(board):
    if turn == 'player':
        get_player_move(board, player)
        print(board)
        turn = 'computer'
    if game_won(board, player):
        print('Congratulations. You won the game')
        return
    else:
        get_random_move(board, computer)
        print(board)
        turn = 'player'
    if game_won(board, computer):
        print('The computer won the game')
        return
print('The game is a tie')
```

program entry

```
if __name__ == '__main__':  
    tictactoe()
```