

Interactive / complex / 12

IC 1	query	Interactive / complex / 12			
IC 2	title	Expert search			
IC 3	pattern	<pre> graph TD person[person: Person] -- knows --> friend[friend: Person] friend -- hasCreator --> comment[comment: Comment] comment -- replyOf --> Post[Post] Post -- hasTag --> Tag[tag: Tag] Tag -- collect(tag.name) --> TagClass[TagClass] TagClass -- isSubclassOf --> TagClass2[TagClass] TagClass2 -- hasType --> TagClass3[TagClass] </pre>			
IC 4	desc.	<p>Given a start Person, find the Comments that this Person's friends made in reply to Posts, considering only those Comments that are direct (single-hop) replies to Posts, not the transitive (multi-hop) ones. Only consider Posts with a Tag in a given TagClass or in a descendant of that TagClass. Count the number of these reply Comments, and collect the Tags that were attached to the Posts they replied to, but only collect Tags with the given TagClass or with a descendant of that TagClass. Return Persons with at least one reply, the reply count, and the collection of Tags.</p>			
IC 5	params	1	personId	ID	
IC 6		2	tagClassName	Long String	
IC 7	result	1	friend.id	ID	R
IC 8		2	friend.firstName	String	R
IC 9		3	friend.lastName	String	R
IC 10		4	tagNames	{Long String}	A
IC 11		5	replyCount	32-bit Integer	A
IC 12	sort	1	replyCount	↓	
IC 13		2	friend.id	↑	
IC 14	limit	20			
	CPs	3.3, 7.2, 7.3, 8.2			
	relevance	<p>This query starts at a Person, moves to its friends, and then to their Comments and their root Posts. Then, it gets the Tag of each Post and checks whether it (directly or transitively) belongs to the specified TagClass. This can be thought of as a bidirectional search between the Person and the TagClass. The difficulty of this query is determining the optimal direction of this traversal.</p>			