


## Interactive / insert / 1

INS 1	query	Interactive / insert / 1																																																									
INS 2	title	Add person																																																									
INS 3	pattern																																																										
INS 4	desc.	Add a Person <i>node</i> , connected to the network by 4 possible <i>edge</i> types.																																																									
INS 5	params	<table> <tr><td>1</td><td>personId</td><td>ID</td><td></td></tr> <tr><td>2</td><td>personFirstName</td><td>String</td><td></td></tr> <tr><td>3</td><td>personLastName</td><td>String</td><td></td></tr> <tr><td>4</td><td>gender</td><td>String</td><td></td></tr> <tr><td>5</td><td>birthday</td><td>Date</td><td></td></tr> <tr><td>6</td><td>creationDate</td><td>DateTime</td><td></td></tr> <tr><td>7</td><td>locationIP</td><td>String</td><td></td></tr> <tr><td>8</td><td>browserUsed</td><td>String</td><td></td></tr> <tr><td>9</td><td>cityId</td><td>ID</td><td></td></tr> <tr><td>10</td><td>languages</td><td>{String}</td><td></td></tr> <tr><td>11</td><td>emails</td><td>{Long String}</td><td></td></tr> <tr><td>12</td><td>tagIds</td><td>{ID}</td><td></td></tr> <tr><td>13</td><td>studyAt</td><td>{&lt;ID, 32-bit Integer&gt;}</td><td>{&lt;universityId, classYear&gt;}</td></tr> <tr><td>14</td><td>workAt</td><td>{&lt;ID, 32-bit Integer&gt;}</td><td>{&lt;companyId, workFrom&gt;}</td></tr> </table>		1	personId	ID		2	personFirstName	String		3	personLastName	String		4	gender	String		5	birthday	Date		6	creationDate	DateTime		7	locationIP	String		8	browserUsed	String		9	cityId	ID		10	languages	{String}		11	emails	{Long String}		12	tagIds	{ID}		13	studyAt	{<ID, 32-bit Integer>}	{<universityId, classYear>}	14	workAt	{<ID, 32-bit Integer>}	{<companyId, workFrom>}
1	personId	ID																																																									
2	personFirstName	String																																																									
3	personLastName	String																																																									
4	gender	String																																																									
5	birthday	Date																																																									
6	creationDate	DateTime																																																									
7	locationIP	String																																																									
8	browserUsed	String																																																									
9	cityId	ID																																																									
10	languages	{String}																																																									
11	emails	{Long String}																																																									
12	tagIds	{ID}																																																									
13	studyAt	{<ID, 32-bit Integer>}	{<universityId, classYear>}																																																								
14	workAt	{<ID, 32-bit Integer>}	{<companyId, workFrom>}																																																								
INS 6	CPs	9.1, 9.2																																																									


## Interactive / insert / 2

INS 1	query	Interactive / insert / 2													
INS 2	title	Add like to post													
INS 3	pattern														
INS 4	desc.	Add a likes <i>edge</i> to a Post.													
INS 5	params	<table> <tr><td>1</td><td>personId</td><td>ID</td><td></td></tr> <tr><td>2</td><td>postId</td><td>ID</td><td></td></tr> <tr><td>3</td><td>creationDate</td><td>DateTime</td><td></td></tr> </table>		1	personId	ID		2	postId	ID		3	creationDate	DateTime	
1	personId	ID													
2	postId	ID													
3	creationDate	DateTime													
INS 6	CPs	9.2													


### Interactive / insert / 3

INS 1	query	Interactive / insert / 3		
INS 2	title	Add like to comment		
INS 3	pattern			
INS 4	desc.	Add a likes <i>edge</i> to a Comment.		
INS 5	params	1	personId	ID
INS 6		2	commentId	ID
INS 7		3	creationDate	DateTime
INS 8	CPs	9.2		


### Interactive / insert / 4

INS 1	query	Interactive / insert / 4		
INS 2	title	Add forum		
INS 3	pattern			
INS 4	desc.	Add a Forum <i>node</i> , connected to the network by 2 possible <i>edge</i> types.		
INS 5	params	1	forumId	ID
INS 6		2	forumTitle	Long String
INS 7		3	creationDate	DateTime
INS 8		4	moderatorId	ID
		5	tagIds	{ID}
	CPs	9.1, 9.2		

### Interactive / insert / 5

INS 1	query	Interactive / insert / 5		
INS 2	title	Add forum membership		
INS 3	pattern			
INS 4	desc.	Add a Forum membership <i>edge</i> (hasMember) to a Person.		
INS 5	params	1	personId	ID
INS 6		2	forumId	ID
INS 7		3	creationDate	DateTime
INS 8	CPs	9.1, 9.2		


### Interactive / insert / 6

INS 1	query	Interactive / insert / 6		
INS 2	title	Add post		
INS 3	pattern			
INS 4	desc.	Add a Post <i>node</i> to the social network connected by 4 possible <i>edge</i> types (hasCreator, containerOf, isLocatedIn, hasTag).		
INS 5	params	1	postId	ID
INS 6		2	imageFile	String
INS 7		3	creationDate	DateTime
INS 8		4	locationIP	String
		5	browserUsed	String
		6	language	String
		7	content	Text
		8	length	32-bit Integer
		9	authorPersonId	ID
		10	forumId	ID
		11	countryId	ID
		12	tagIds	{ID}
	CPs	9.1, 9.2		

## Interactive / insert / 7

INS 1	query	Interactive / insert / 7			
INS 2	title	Add comment			
INS 3	pattern	<div><div>The parent Message is either a Post or a Comment.</div><div><div><div>Post</div><div><math>id = \\$replyToPostId</math></div></div><div><div>Comment</div><div><math>id = \\$replyToCommentId</math></div></div></div><div><div><div>Country</div><div><math>id = \\$countryId</math></div></div><div><div>Tag</div><div><math>id\ in\ \\$tagIds</math></div></div><div><div>Comment</div><div><math>id \leftarrow \\$commentId</math> <math>creationDate \leftarrow \\$creationDate</math> <math>locationIP \leftarrow \\$locationIP</math> <math>browserUsed \leftarrow \\$browserUsed</math> <math>content \leftarrow \\$content</math> <math>length \leftarrow \\$length</math></div></div><div><div>Person</div><div><math>id = \\$authorPersonId</math></div></div></div><div><div>replyOf</div><div>replyOf</div><div>isLocatedIn</div><div>hasTag</div><div>hasCreator</div></div></div>			
INS 4					
INS 5					
INS 6					
INS 7					
INS 8					
	desc.	Add a Comment <i>node</i> replying to a Post/Comment, connected to the network by 4 possible <i>edge</i> types (replyOf, hasCreator, isLocatedIn, hasTag).			
	params	1	commentId	ID	
		2	creationDate	DateTime	
		3	locationIP	String	
		4	browserUsed	String	
		5	content	Text	
		6	length	32-bit Integer	
		7	authorPersonId	ID	
		8	countryId	ID	
		9	replyToPostId	ID	-1 if the Comment is a reply of a Comment
		10	replyToCommentId	ID	-1 if the Comment is a reply of a Post
		11	tagIds	{ID}	
	CPs	9.1, 9.2			

## Interactive / insert / 8

INS 1	query	Interactive / insert / 8			
INS 2	title	Add friendship			
INS 3	pattern				
INS 4	desc.	Add a friendship <i>edge</i> (knows) between two Persons.			
INS 5	params	1	person1Id	ID	
INS 6		2	person2Id	ID	
INS 7		3	creationDate	DateTime	
INS 8	CPs	9.2			