Interactive / insert / 7

CPs

9.1, 9.2

INS 1		T			
-	query	Interactive / insert / 7			
INS 2	title	Add comment			
INS 3		Person ← hasCreator ←			
INS 5	pattern	id = \$authorPersonId			
INS 6		Post	—replyOf	Comment isLocatedIn	Country
INS 7		id = \$replyToPostId	crea	\$commentId itionDate ← \$creationDate	id = \$countryId
INS 8		Comment	replyOfbrow	tionIP ← \$locationIP vserUsed ← \$browserUsed tent ← \$content hasTag →	Tag
		id = \$replyToCommentId		th ← \$length	id in \$taglds
	desc.	desc. Add a Comment <i>node</i> replying to a Post/Comment, connected to the network by 4 possible types (replyOf, hasCreator, isLocatedIn, hasTag).			ork by 4 possible edge
		1 commentId	ID		
		2 creationDate	DateTime		
		3 locationIP	String		
	params	4 browserUsed	String		
		5 content	Text		
		6 length	32-bit Integer		
		7 authorPersonId	ID		
		8 countryId	ID		
		9 replyToPostId	ID	-1 if the Comment is a reply of	a Comment
		10 replyToCommentId	ID	-1 if the Comment is a reply of	a Post
		11 tagIds	{ID}		