

## BI / read / 12

|         |  |                                      |   |   |  |
|---------|--|--------------------------------------|---|---|--|
| query   | BI / read / 12   |                                      |   |   |  |
| title   | How many persons have a given number of messages   |                                      |   |   |  |
| pattern | <div><div><div>2. personCount = count</div><div><div>Person</div></div><div>count Persons grouped by messageCount value</div></div><div><div>1. messageCount = count</div><div><div>Message</div><div>content not empty and length &lt; \$lengthThreshold and \$date &lt; creationDate</div></div></div><div><div>Post</div><div>language in \$languages</div></div><div><div>«opt» hasCreator</div><div>«opt» replyOf*0..</div></div></div>   |                                      |   |   |  |
| desc.   | <p>For each Person, count the number of Messages they made (messageCount). Only count Messages with the following attributes:</p> <ul style="list-style-type: none"><li>• Its content is not empty (and consequently, the imageFile attribute is empty for Posts).</li><li>• Its length is below the lengthThreshold (exclusive, equality is not allowed).</li><li>• Its creationDate is after date (exclusive, equality is not allowed).</li><li>• It is written in any of the given languages.</li></ul> <div><div>– The language of a Post is defined by its language attribute.</div><div>– The language of a Comment is that of the Post that initiates the thread where the Comment replies to.</div></div> <p>The Post and Comments in the reply tree’s path (from the Message to the Post) do not have to satisfy the constraints for content, length and creationDate.</p> <p>For each messageCount value, count the number of Persons with exactly messageCount Messages (with the required attributes).</p> |                                      |   |   |  |
| params  | <div><div>1</div><div>date</div></div>   | <div><div>Date</div></div>           | <div></div>   |   |  |
|         | <div><div>2</div><div>lengthThreshold</div></div>  | <div><div>32-bit Integer</div></div> | <div>Selected as balanced against date to filter around 30% of the Messages within a language and keep the variance low</div> |   |  |
|         | <div><div>3</div><div>languages</div></div>  | <div><div>{String}</div></div>       | <div>Only the most frequently used languages are selected</div>   |   |  |
| result  | <div><div>1</div><div>messageCount</div></div>   | <div><div>32-bit Integer</div></div> | <div><div>A</div></div>   | <div>Number of Messages created</div>                   |  |
|         | <div><div>2</div><div>personCount</div></div>  | <div><div>32-bit Integer</div></div> | <div><div>A</div></div>   | <div>Number of Persons with messageCount Messages</div> |  |
| sort    | <div><div>1</div><div>personCount</div></div>  | <div><div>↓</div></div>              | <div></div>   |   |  |
|         | <div><div>2</div><div>messageCount</div></div>   | <div><div>↓</div></div>              | <div></div>   |   |  |
| limit   | <div>n/a</div>   |                                      |   |   |  |
| CPs     | <div>1.1, 1.2, 1.4, 3.2, 4.2, 4.3, 8.1, 8.2, 8.3, 8.4, 8.5</div>   |                                      |   |   |  |