

Interactive / complex / 6

IC 1	query	Interactive / complex / 6			
IC 2	title	Tag co-occurrence			
IC 3	pattern	 <pre> graph TD person[person: Person] -- knows*1..2 --> otherPerson[otherPerson: Person] tag[tag: Tag] -- hasTag --> Post[Post] otherTag[otherTag: Tag] -- hasTag --> Post Post -- hasCreator --> otherPerson subgraph count Post end </pre> <p>The diagram illustrates the query pattern. It starts with a person: Person entity (orange box) with a variable <code>id = \$personId</code>. This person is connected via a <code>knows*1..2</code> relationship to an otherPerson: Person entity (orange box). The otherPerson is connected via a <code>hasCreator</code> relationship to a Post entity (red box). The Post entity is also connected via <code>hasTag</code> relationships to two Tag entities: tag: Tag (pink box) and otherTag: Tag (pink box). The tag entity has a variable <code>name = \$tagName</code>. The otherTag entity has a variable <code>name ≠ \$tagName</code>. A <code>count</code> box is shown around the Post entity, indicating that the count of posts is being calculated.</p>			
IC 6	desc.	Given a start Person and some Tag, find the other Tags that occur together with this Tag on Posts that were created by start Person's friends and friends of friends (excluding start Person). Return top 10 Tags, and the count of Posts that were created by these Persons, which contain both this Tag and the given Tag.			
IC 11	params	1	personId	ID	
IC 12		2	tagName	Long String	
IC 13	result	1	otherTag.name	Long String	R
IC 14		2	postCount	32-bit Integer	A
		Number of Posts that were created by friends and friends of friends, which have the Tag otherTag			
	sort	1	postCount	↓	
		2	otherTag.name	↑	
	limit	10			
	CPs	5.1, 8.2			
	relevance	This query looks for paths of lengths three or four, starting from a given Person, moving to friends or friends of friends, then to Posts and finally ending at a given Tag.			