Interactive / complex / 14

title	Trusted connection paths
	Trusted connection paths
pattern	Enumerate all unweighted shortest paths on knows edges from person1 to person2. person1: Person id = \$person2Id Case 1: Replies on Posts, weight += 1.0 × count(c) personA: Person hasCreator c: Comment Post: Post For each edge on the path, calculate a weight based on interactions between the pair of Persons of the edge, are calculated as a sum of cases #1 and #2 for the Persons (both ways), and the sum of these weights determine the total weight of each path. pl knows pry Case 1: Replies on Posts, weight += 1.0 × count(c) personA: Person hasCreator c: Comment replyOf → post: Post For each edge on the path, calculate a weight based on interactions between the pair of Persons (both ways), and the sum of these weights determine the total weight of each path. pl knows pry Case 2: Replies on Comments, weight += 0.5 × count(c1) personA: Person hasCreator hasCreator c1: Comment replyOf → c2: Comment
desc.	Given two Persons, find all (unweighted) shortest paths between these two Persons, in the subgraph induced by the knows relationship. Then, for each path calculate a weight. The nodes in the path are Persons, and the weight of a path is the sum of weights between every pair of consecutive Person nodes in the path. The weight for a pair of Persons is calculated based on their interactions: • Every direct reply (by one of the Persons) to a Post (by the other Person) contributes 1.0. • Every direct reply (by one of the Persons) to a Comment (by the other Person) contributes 0.5. Note that interactions are counted both ways (e.g. if Alice writes 2 Post replies and 1 Comment reply to Bob, while Bob writes 3 Post replies and 4 Comment replies to Alice, their interaction score is $2 \times 1.0 + 1 \times 0.5 + 3 \times 1.0 + 4 \times 0.5 = 7.5$). Return all the paths with shortest length, and their weights. Do not return any rows if there is no path between the two Persons.
params	1 person1Id ID 2 person2Id ID
result	personIdsInPath [ID] C identifiers representing an ordered sequence of the Persons in the path pathWeight 64-bit Float C
sort	1 pathWeight ↓ The order of paths with the same weight is unspecified
CPs	3.3, 5.3, 7.2, 7.3, 7.5, 7.7, 8.1, 8.2, 8.3, 8.6
relevance	This query looks for a variable length path, starting at a given Person and finishing at an another given Person. This is a more complex query as it not only requires computing the path length, but returning it and computing a weight. To compute this weight one must look for smaller sub-queries with paths of length three, formed by the two Persons at each step, a Post and a Comment.
	desc. params result sort CPs