Interactive / insert / 7

9.1, 9.2

CPs

| INS 1 | query | Interactive / insert / 7 | | | |
|-------|---------|--|-------------------|--|----------------------------|
| INS 2 | title | Add comment | | | |
| INS 3 | title | Aud Common | | | |
| INS 4 | | Person | - hasCreator- | | |
| INS 5 | | id = \$authorPersonId | | | |
| INS 6 | | Post | — replyOf — | Comment isLocated | din —> Country |
| INS 7 | pattern | id = \$replyToPostId | | - \$commentId eationDate ← \$creationDate | id = \$countryId |
| INS 8 | | Comment | replyOfbro | ationIP ← \$locationIP owserUsed ← \$browserUsed ontent ← \$content hasTag | g → Tag |
| | | id = \$replyToCommentId | | gth ← \$length | id in \$taglds |
| | | Add a Comment nada ra | alving to a Doot/ | Comment connected to the n | entwork by A possible adag |
| | desc. | Add a Comment <i>node</i> replying to a Post/Comment, connected to the network by 4 possible <i>edge</i> types (replyOf, hasCreator, isLocatedIn, hasTag). | | | |
| | | | iscocateum, nas i | ag). | |
| | | 1 commentId | ID | | |
| | params | 2 creationDate | DateTime | | |
| | | 3 locationIP | String | | |
| | | 4 browserUsed | String | | |
| | | 5 content | Text | | |
| | | 6 length | 32-bit Integer | | |
| | | 7 authorPersonId | ID | | |
| | | 8 countryId | ID | | |
| | | 9 replyToPostId | ID | □ ID −1 if the Comment is a reply of a Comment | |
| | | 10 replyToCommentId | ID | −1 if the Comment is a reply of a Post | |
| | | 11 tagIds | {ID} | | |