

杰理蓝牙参数	
Operation Frequency Range	2402-2480MHZ
Bluetooth Version	5.3+BR+EDR+BLE
(低功耗蓝牙) BLE Channel	40
BLE Channel Separated	2MHz
Modulated Type	GFSK、 $\pi/4$ -DQPSK
(经典蓝牙) Bredr channel	1MHz
(经典蓝牙) Bredr Channel	79
Data Rata	1M、2M、3M (目前AC700N支持3M，其它系列不支持)

支持BR (GFSK)	Peak Power(dBm)(with Tolerance) 6.0 ，不同芯片发射功率不一样	Avg. Power(dBm)(with Tolerance) 4.0
BR (GFSK)+ EDR		
(GFSK + $\pi/4$ DQPSK)		
EDR (GFSK + $\pi/4$ DQPSK)		
支持 BLE(1M)		
支持 BLE(2M)		
支持Dual mode BLE + (BR and EDR)		
Antenna Information	客户自选天线	

Transmitter Details	
Frequency range	2402-2480MHZ
No. of hopping frequency	79
Hopping channel separation, 2402~2403、2441~2442、2479~2480	>25KHz
Adjacent channel separation (In case of multi-channel	25dB
Frequency stability	20ppm
Spurious/ Harmonic radiations	≤-30dbm
Max. Frequency Deviation	500KHz@BLE GFSK 2M、250KHz@BLE GFSK 1M、165@GFSK 1M
Bandwidth of emission	2M@BLE GFSK 2M、1M@others
Base band frequency (In case of multi channel equipment)	2402-2480MHz
Type of modulation to be required	GFSK

Receivers Details	
Frequency range	2402-2480MHZ
Sensitivity	-91dBm@GFSK 1M、-93@dBm@ $\pi/4$ -DQPSK DPSK
Frequency stability	20ppm
Threshold input level	0dBm
Intermediate frequency	3M

支持解码格式	sbc\aac			
延时	250ms左右			
声道分离度	共vcomo：-50dB，共gnd：-100dB			
Mic 采样率	cvsd：8k，msbc：16k			
占用宽带	≤ 3MHz			
发射功率	8db			
core Specification Version	5.3 dual mode			
new features for bluetooth	LE 2M PHY(2x Speed 高速传输)、LE Coded PHY(4x RANG)			
Porduct Type	End Product			
Supported Protocols/底层				
Part	Protocol			
Core Controller	RF/ BB / LMP/			
LE Controller	RF-PHY / LL			
Core Host	L2CAP/ SDP/ GAP/ GATT/ SM			
Support Traditon Profile				
Profile	Version	Role		
A2DP	1.3.2	SINK		
AVRCP	1.6.2	CT		
AVDTP	1.3	Sink		
AVCTP	1.4	Controller(CT)		
HFP	1.8	HF		
HID	1.1.1			
RFCOMM	1.1			
SPP	1.2			
SDP	5.3			
L2CAP	5.3			
PNP	1.3			
RF 经典蓝牙 IXIT for RF				
IXIT Reference	Description	Comment	Value	Unit (if "
RF:P1	Timer for TX power control	TRM/CA/03 Power Control	40	ms
RF:P2	Inband Image frequency	RCV/CA/03 C/I Performance	-3MHz	MHz
		RCV/CA/09 EDR C/I Performance		
RF:P3	Value n for Intermodulation test	RCV/CA/05 Intermodulation Performance	4	Integer
RF:P6	Type of power source	Chapter 6.4, RF Test Specification	4.2	

RF:P7	Nominal power source voltage	Chapter 6.4, RF Test Specification	4.2	V
RF:P8	Operating temperature range	Chapter 6.5, RF Test Specification	37	°C
RF:P9	Extreme power source voltage	Chapter 6.5, RF Test Specification	4.2	V
RF:P10	Antenna gain	Chapter 6.9, RF Test Specification	0	dB

RF-PHY 低功耗蓝牙ICS for RF-PHY				
Item	Bluetooth LE RF Capability	Status	Supported	
1	LE Transmitter (Non-connectable, Broadcaster)	C.1	☒ Yes ☐ No	Note :
2	LE Receiver (Non-connectable, Observer)	C.1	☒ Yes ☐ No	
3	LE Transceiver (Connectable, Peripheral/Central)	C.1	☒ Yes ☐ No	
4	LE 2M PHY	C.2	☒ Yes ☐ No	Note :
5	Stable Modulation Index - Transmitter	C.3	☒ Yes ☐ No	
6	Stable Modulation Index - Receiver	C.4	☒ Yes ☐ No	
7	LE Coded PHY	C.2	☒ Yes ☐ No	
Item	Bluetooth LE RF Capability	Status	Supported	
1	HCI Test Interface	C.1	☐ Yes ☐ No	
2	UART Test Interface	C.1	☐ Yes ☐ No	

C.1: Mandatory to support at least one of these capabilities.

RF-PHY 低功耗蓝牙 IXIT for RF				
IXIT Reference	Identifier	Sub-Identifier (Optional)	Value	Units (if applicable)
RF-PHY:P1:1	Inband Image frequency	Low frequency	-3	MHz
RF-PHY:P1:2		Middle frequency	-3	MHz
RF-PHY:P1:3		High frequency	-3	MHz
RF-PHY:P2:1	Value n for Intermodulation test	Low frequency	4	Integer
RF-PHY:P2:2		Middle frequency	4	Integer
RF-PHY:P2:3		High frequency	4	Integer
RF-PHY:P4	Type of power source	Nominal (NOC)	4.2v	V
RF-PHY:P5	Operating temperature	Nominal (NOC)	25	°C

RF-PHY:P6:1	Air humidity range (relative)	Maximum	80	%
RF-PHY:P6:2		Minimum	70	%
RF-PHY:P6:3		Air humidity level for NOC/EOC	70	%
RF-PHY:P7:1	Test interface implementation	HCI or 2-wire	0	
RF-PHY:P7:2		Datarate	115200	bps
RF-PHY-PHY:P8	Antenna gain		0	dBi
RF-PHY:P9:1	Maximum TX packet		255	Bytes
RF-PHY:P9:2	Maximum RX packet length		255	Bytes
RF-PHY:P9:3	Maximum TX packet length		255	Bytes
RF-PHY:P9:4	Maximum TX packet length		255	Bytes
RF-PHY:P9:5	Maximum TX packet length		255	Bytes
RF-PHY:P9:6	Maximum RX packet length		255	Bytes
RF-PHY:P9:7	Maximum RX packet length		255	Bytes
RF-PHY:P9:8	Maximum RX packet length		255	Bytes
RF-PHY:P10:1	Maximum TX mode output power		6	dBm
RF-PHY:P11:1	Inband Image Frequency (2Ms/s)	Low frequency	-3	MHz
RF-PHY:P11:2		Middle frequency	-3	MHz
RF-PHY:P11:3		High frequency	-3	MHz
RF-PHY:P12:1	Value n for Intermodulation test (2Ms/s)	Low frequency	4	Integer
RF-PHY:P12:2		Middle frequency	4	Integer
RF-PHY:P12:3		High frequency	4	Integer
RF-PHY:P13:1	Inband Image Frequency (Stable Modulation Receiver)	Low frequency	-3	MHz
RF-PHY:P13:2		Middle frequency	-3	MHz
RF-PHY:P13:3		High frequency	-3	MHz
RF-PHY:P14:1	Value n for Intermodulation test (Stable Modulation Receiver)	Low frequency	4	Integer
RF-PHY:P14:2		Middle frequency	4	Integer
RF-PHY:P14:3		High frequency	4	Integer
RF-PHY:P15:1	Inband Image Frequency (Stable Modulation Receiver, 2Ms/s)	Low frequency	-3	MHz
RF-PHY:P15:2		Middle frequency	-3	MHz
RF-PHY:P15:3		High frequency	-3	MHz
RF-PHY:P16:1	Value n for Intermodulation test (Stable Modulation Receiver, 2Ms/s)	Low frequency	4	Integer
RF-PHY:P16:2		Middle frequency	4	Integer
RF-PHY:P16:3		High frequency	4	Integer

音频解码格式	A2DP SBC AAC			
	A2DP : SBC AAC			
	HFP:CVSD MSBC			