
A I · S Y S T E M S

ARCHITECTURE HANDBOOK

FROM TOKEN TO FLEET

An AI Solution Architect's Handbook



Zhiqi Tao

First edition, 2026

From Token to Fleet

An AI Solution Architect's Handbook

First edition, 2026

Zhiqi Tao

From a single token's cost to the fleet that carries it, every architectural decision can be traced — and defended — with arithmetic.

COPYRIGHT © 2026 ZHIQI TAO

All rights reserved, except as explicitly granted below.

License. This work — the book text, diagrams, figures, and build scripts — is distributed under the *source-available* grant stated below. That grant is the operative license for this edition: the default is all rights reserved, and the two permissions below are the stated exception. The full text of the license, including the redistribution restrictions and the channel-specific terms (e.g. Amazon KDP), is the `LICENSE` file in the repository, which is the authoritative statement of rights for this work.

- **You may** freely read, study, learn from, and **redistribute** the work (verbatim, with attribution) for personal and non-commercial ends — no permission needed.
- **Commercial use or publication** — a paid product, course, book, or report — requires the author's **prior written approval**.

To request commercial permission, contact `zhiqi.tao@gmail.com`.
Full terms: `github.com/zhiqitao/from-token-to-fleet`
(`LICENSE`, SPDX `LicenseRef-ZhiqiResearch-FromTokenToFleet-1.0`)
Applicable terms and edition. The SPDX identifier above names the exact license version this edition is published under. To determine the terms that apply to this copy, retrieve the `LICENSE` file at the source commit recorded in the *Edition history* panel (see the Sources/Method/Reproducibility chapter, the *Source-revision* row) or at a tagged release of the same identifier; the version and repository commit are the authoritative reference, so a buyer can confirm the exact text rather than infer it from the summary here.
Technical disclaimer. This book describes an evolving field. Model names, parameter counts, prices, context limits, throughput and latency figures, licenses, and benchmark results change quickly and may differ by regional cloud pricing, hardware SKU, precision/sparsity configuration, batch and concurrency, software stack, and measurement methodology. Every quantitative value here is one of three kinds: a dated measurement, a figure derived from cited inputs, or is explicitly identified as an illustrative assumption (see the Sources, Method, and Reproducibility chapter for the full evidence taxonomy). Each is a snapshot as of the book's dated version, and must be re-verified against the vendor's current documentation before any procurement or deployment decision.
Currency. Technical content is current as of the dated build; the fastest-moving claims (Appendix A and the economics chapters) are flagged in-text as items that require re-checking against current vendor documentation.

The work is provided "as is", without warranty of any kind.

Contents

Preface v

I The Token 1

1 It All Starts With the First Token 2

2 What Actually Happens During Inference 13

3 Understanding the Model 28

II The Workload 41

4 The Anatomy of an AI Workload 42

5 From Workload to Model Selection 67

6 Measuring What Matters: From Telemetry to Architecture Decisions 78

III The System 89

7 Memory Is the First Constraint 90

8 Compute 106

9 Communication 119

10 Parallelism: Splitting the Model Across Machines 128

11 Serving: From Model in Memory to Requests in Flight 137

IV The Architecture 149

12 Designing the AI System: From Constraints to Candidates 150

13 Reference Architectures: From Local to Hyperscale 162

14 Benchmarking: Predicting Real Experience, Not a Leaderboard 169

15 Performance Engineering: From "It Works" to "It Meets the SLO" 175

16 TCO: The Total Cost Reality Check 189

V The Fleet **202**

17 From Server to Fleet 203

18 Operating Multiple Models 219

19 Agentic Systems 229

20 Fleet-Level Optimization 245

21 The AI Factory: Turning Inference Into an Industrial Process 255

VI The Architect **261**

22 How to Think Like an AI Solution Architect 262

23 Working With Customers: From Vague Ask to Defensible Scope 271

24 Red Team / Green Team 277

25 The Architecture Decision Record 289

26 The Solution Architect's Toolkit + Patterns Library 300

A Appendix A — 2026 Frontier Architecture Signals: Four Open-Weight Model Families 312

Glossary of Acronyms and Common Terms 326

References 331

Sources, Method, and Reproducibility 334

The Architecture Worksheet 341

List of Figures

1 The architect's decision loop — the book's spine vii
2 Reading the book two ways viii

1.1 The KV cache: every decoded token adds one K/V per layer per head 7
1.2 How a token travels: text → tokenizer → IDs → embedding → attention → KV cache .. 8

2.1 The canonical end-to-end inference pipeline, in three bands 15
2.2 Prefill and decode on the roofline ridge 22

3.1 Dense vs MoE parameter allocation and KV cache behavior 39

4.1 Six-dimension workload characterization mapped to architectural decisions 63

5.1 Model selection for RAG 77

6.1 The metric hierarchy as a diagnostic chain 80
6.2 Request-latency distribution: p50/p90/p95/p99, with the mean in the legend 82

7.1 Grouped-Query Attention cuts per-token KV 95
7.2 KV cache size vs context length, canonical 80-layer reference geometry 101
7.3 Inference vs fine-tuning memory floor 102
7.4 The concurrency budget 103
7.5 Memory Tetris 104

8.1 Where inference computation and data movement actually live 108
8.2 Per-GPU roofline for dense FP16, one H100 vs one H200 113

9.1 All-reduce time vs data volume, by interconnect tier (ANALYTICAL) 122

10.1 Three parallelism patterns, one per panel 130

11.1 Discrete vs continuous batching (Orca-style slot diagram) 141

11.2 Serving is four orthogonal concerns, not a stack 144
11.3 P/D disaggregation topology 145

12.1 Candidate architecture synthesis, constraint-first 159

13.1 The reference-architecture ladder and its escalation triggers 167

14.1 Capability screen then deployment benchmark 173

15.1 FlashAttention: the same math, far less HBM traffic 179
15.2 Prefix caching and batching act on different serving phases 181

16.1 TCO break-even: self-hosted vs managed API (canonical 80-layer full-MHA geometry) 200

17.1 Sizing a fleet by burst peak, headroom, and failover 204

18.1 Model-routing decision tree 228

19.1 The agent loop as a four-state state machine 231
19.2 Input/output tokens and KV cache per request across agent turns 239
19.3 The agentic context block grows every turn 240

20.1 Fleet capacity 254

21.1 The AI Factory promotion pipeline, showing the *model lifecycle* layer... 259

22.1 Prefill vs decode scaling as context grows 267

23.1 From vague ask to architectural bounds 275

24.1 Red Team / Green Team cycle 288

25.1 The Anatomy of an Architecture Decision Record, and how one ADR supersedes the next 297

26.1 Workload fingerprints on the six axes 304
26.2 Pattern Application Diagram 310

A.1 2026 frontier MoE extreme sparsity 314
A.2 Vendor-reported KV/FLOP reduction 320
A.3 A conceptual layering of frontier AI systems 323
A.4 Where should intelligence live? The horizontal bands are a **design choice** 324

Preface

For a long time I wanted to build the systematic knowledge of what it means to work as an AI Solution Architect: how to reason across the layers of an AI system — from tokens and models to workloads, systems, infrastructure, and fleets — so that a vague requirement can be turned into a defensible architecture. I kept looking for the resource that would lay all of that down in one coherent thread. What I found were deep dives into single layers — models, serving, infrastructure, agents — but no single spine that connected them into the one thing an architect actually does: chaining a real workload to a defensible solution.

That feedback loop — curiosity, question, research, model, write — is the engine of this book: writing the reasoning down forces every assumption, quantity, and trade-off to become explicit, and exposes the gaps that deserve further measurement. The AI field moves fast, and I am still learning too. This handbook is a continuously evolving reference — developed and shared layer by layer, decision by decision, from the token up to the fleet. If it helps others build the same systematic mental model, then it has outdone what I had planned it for.

Start here. For the working method, begin at Ch. 1 (The Token) and follow the canonical workload through Chs. 16–20 (TCO and the fleet, where the numbers pay off), returning to the policy sections later. The following Preface sections — the thesis, reading paths, the evidence discipline, and the currency policy — are the *reference* layer: valuable to a careful reader, but skimmable on a first pass. The full provenance/taxonomy rule set also lives in the Sources, Method, and Reproducibility chapter, so the Preface need not be read in full before starting the chapters.

The thesis

The book has one thesis, and it is the spine of every chapter:

> **Given an ambiguous problem, how do I systematically arrive at a defensible AI architecture?**

The canonical method — the decision loop that Chapter 22 makes explicit — is previewed in the Preface, then assembled piece by piece. Chapters 1–21 acquire the tools: tokens, workloads, model

structure, arithmetic intensity, memory, parallelism, serving, benchmarking, TCO, fleet operations, and the factory gate. Chapter 22 then synthesizes those tools into the professional reasoning loop that runs through the whole book, placed late not because it belongs at the end but because the reader needs the technical vocabulary first to see it operate on a real workload.

That loop — which every chapter echoes — runs from requirements and workload characterization, through constraints and candidate architectures, to benchmarking, bottleneck analysis, optimization, total-cost reality checks, and a final red-team challenge. Parts I–V walk through the technical substrate, layer by layer. Part VI turns to the discipline itself: how one learns to reason across those layers.

How the book is organized

The six parts mirror the layers an architect reasons across:

- **Part I — The Token.** Models and mechanisms, from a single token to the memory and compute arithmetic that prices every decision.
- **Part II — The Workload.** The job the system does: workload characterization and measuring what matters.
- **Part III — The System.** Memory, compute, communication, parallelism, and serving.
- **Part IV — The Architecture.** Designing, benchmarking, engineering, and costing a system.
- **Part V — The Fleet.** Operating AI at scale, and agents.
- **Part VI — The Architect.** The spine made explicit, plus a patterns library.

A worked canonical scenario — an enterprise retrieval-augmented question-answering workload on a 70B-class model — runs through the book, so every mechanism is anchored in concrete, reproducible arithmetic rather than abstraction. One caveat, so the book is not misread: this scenario is a **teaching instrument**, not a claim about what an AI workload *is*. Real workloads span a wide design space — long-context RAG (KV/memory-bound), high-throughput chat (decode-bound), batch inference (utilization/cost-bound), reasoning (test-time-compute-bound), agentic (concurrency/variance-bound), embeddings, vision, fine-tuning, training — and each shifts which quantity dominates. The canonical scenario picks a single, tractable, input-heavy RAG case and carries it through so the reasoning stays continuous; a real deployment will sit somewhere else in that space, and the chapters are written to give the reader the arithmetic to re-derive the bounds for *their* point.

How to use this book

The chapters build on one another, but not every reader needs them in order. A few reading paths, depending on where the reading begins:




FIGURE 1: The architect's decision loop — the book's spine. A vague requirement is carried through workload characterization, constraints, candidate architectures, benchmarking, bottleneck analysis, TCO, and a final red-team challenge before an architecture is committed. Stage 03 ("Validate & Defend") produces a *provisional* recommendation — the candidate that survives benchmarking and TCO — and stage 04 ("Commit") subjects it to the red-team challenge before the *final* choice is recorded; the recommendation is therefore provisional until it has been challenged. Two loops are drawn: the *inner* (green, left) returns a failed benchmark or TCO validation from "Validate & Defend" back to "Design & size" to re-derive the candidate; the *outer* (red, right) returns from "Commit" to "Understand" when the committed architecture reveals a requirements revision is needed.




FIGURE 2: Reading the book two ways. **A (left):** layer-by-layer, Part I → VI, building the substrate then the discipline. **B (right):** question-by-question, a set of independent navigation prompts — each maps one reader's question (token → cost, fits host?, which phase binds?, 1 host or fleet?, who serves it?, is it the right call?) to the chapter that answers it. These question-to-chapter links are *starting points*, not complete coverage: a single question often spans several chapters, and the decision-justification chapters (Ch 22 for the design loop, Ch 25 for the recorded Architecture Decision Record) carry the reasoning that the navigation prompt points toward. The two paths are independent; whichever fits the reader's question, each chapter still supplies a derived quantity that feeds a decision.

New to inference systems. Parts I → II → III sequentially — the token, then the workload, then the system. This is the path that builds the vocabulary the later chapters assume.

Practicing architect. Start with Ch. 22, the reasoned loop, then use Parts I–V as the quantitative reference it calls on.

Infrastructure specialist. Parts III–V (system, architecture, fleet) directly; skim I–II for the workload framing.

Customer-facing solution architect. Parts II, IV, and VI — scoping a workload, designing an architecture, and the professional discipline.

Frontier-model reader. Appendix A alone, but only after Chs. 3, 7–11, so the total-vs-active, KV, and serving mechanism the appendix leans on are already in hand.

The operational decision checklist

The full reasoning loop is earned in Chapter 22, but its shape is useful from the first page. When a workload arrives, the same six questions recur in the same order; the chapters that follow each answer one of them. Keep this list in view while reading — it is the spine made operational.

1. What is the workload? — tokens in/out, rps average and peak, concurrency, latency SLOs. (Ch. 4)
2. What fits on one host? — weight residency, KV per token, the concurrency floor. (Chs. 3, 7)
3. Which phase binds? — prefill compute or decode bandwidth, at this operating point. (Chs. 2, 8)
4. How many hosts? — the fleet sized from the per-host bound, with headroom and failover. (Chs. 16–17)
5. Who serves it, and how? — batching, parallelism, P/D disaggregation, scheduling. (Chs. 10–11, 20)
6. Is it the right call? — TCO, the red-team challenge, the recorded decision. (Chs. 16, 22, 25)

The six questions are cross-cutting: each is first raised in one part and cashed out across the others — Q1 in Part II, Q2–3 across Parts I and III, Q4–5 across Parts III–V, and Q6 in Parts IV and VI. The technical justification for why the loop has this shape — and where it breaks — is Chapter 22; this checklist is the early, operational view of the same loop.

The Architect's Evidence Discipline

Every *load-bearing* quantitative claim in this book carries Axes 1 and 2 as an inline pair; the Axis-3 measurement status rides along with claims whose measurement status is known, not with every claim. Keeping these axes separate is itself a discipline. A claim carries the labels *directly* (inline, e.g. **[1P][DERIVED]**) or *via an identified table or section* that states them (e.g. a worked-example table whose header or footnote gives the provenance and status for every row). Purely illustrative or rhetorical numbers that no later calculation depends on may carry the labels in the surrounding prose rather than inline; the Sources, Method, and Reproducibility chapter defines these exceptions unambiguously. The **provenance** axis records where the number came from: **[1P]** first-party (the model vendor's own spec), **[canonical scenario]** the book's own internally defined workload and model (Ch. 4, Table 4-2), **[ILLUSTRATIVE]** a non-canonical worked-example or scenario input chosen to make a calculation concrete, **[2°]** reputable second-hand (textbook, survey, independent benchmark), or **[LAB]** measured on the author's own home-lab hardware (illustrative of mechanism, not production). The **epistemic-status** axis records what was done to it: **FACT** directly stated by the source, **DERIVED** computed by arithmetic from stated inputs, **ASSUMPTION** a deliberately chosen scenario input (paired with a scenario provenance — [CANONICAL SCENARIO] or [ILLUSTRATIVE]), **HYPOTHESIS** reasoned but not yet validated, or **UNRESOLVED** a question the book leaves open. A label pair always combines one item from each of the first two axes, e.g. **[1P][DERIVED]** or **[ILLUSTRATIVE][ASSUMPTION]**; the third axis — **measurement status** (ANALYTICAL / ILLUSTRATIVE / MODELED / MEASURED, or UNMEASURED where the stage is not yet determined) — rides with that pair or stands alone, and is defined in full in the Sources, Method, and Reproducibility chapter.

One mapping is worth stating explicitly, because it is easy to get wrong: the canonical scenario (Ch. 4, Table 4-2) keeps its own provenance. Within that **[canonical scenario]** provenance the *epistemic-status* axis splits every value into exactly two cases. An *input or parameter assumption* — a traffic level, a latency target, a price, a token count — is **[canonical scenario][ASSUMPTION]**. A value *arithmetically derived* from those assumed inputs — an execution occupancy, a tokens-per-second rate, a cost-per-request, a tokens-per-dollar figure — is **[canonical scenario][DERIVED]**. A vendor hardware constant (e.g. the H100 footprint) is **[1P][FACT]**, never **[ILLUSTRATIVE]**. **[ILLUSTRATIVE]** is reserved for a non-canonical *hypothetical* worked example (a "what-if" that is not the canonical scenario): its inputs are **[ILLUSTRATIVE][ASSUMPTION]** and its derived results **[ILLUSTRATIVE][DERIVED]**. The ASSUMPTION/DERIVED split tells a reader whether a number was chosen or computed; the **[canonical scenario]**/**[ILLUSTRATIVE]** split tells them whether it is the book's fixed reference set or a one-off what-if.

Two habits matter most. First, arithmetic belongs on the epistemic-status axis, not the provenance axis: a worked example computed from a model card is **[1P][DERIVED]**, never **[2°]** just because arithmetic was done. Second, the conclusions an architect draws are only as defensible as the units behind them — so every major worked example ends with a unit check and a sanity check (does this

result stay inside the physically possible?). That habit is part of the discipline, not an appendix. The full statement of this scheme, including how each label is verified, is in the Sources, Method, and Reproducibility chapter.

Evidence cutoff and edition date. This edition is build **v20260913** (2026-09-13). The single evidence cutoff for it is **2026-08-30**: model, vendor, and hardware claims are stated as of that date, and the "As of 2026-08" markers in the body refer to this same cutoff. Primary sources (arXiv reports, model cards, vendor pages) were accessed as of the build date; each is cited with a stable identifier in the References chapter. Fast-moving model and vendor assertions (Appendix A in particular) are dated individually against their primary sources. *Post-cutoff policy:* any model, price, or spec that changed after 2026-08-30 is not silently updated in this edition; a later build revalidates the fast-moving claims against current vendor documentation and flags any post-cutoff change separately rather than inheriting the prior value.

One documented addendum is permitted. Appendix A, A.6 carries *one* boxed post-snapshot observation (recorded 2026-09-27) about an additional multimodal model probed after the cutoff. It is explicitly outside the 2026-08-30 compile envelope, is not part of the four-family comparison or the First-hand Sources list, and is labeled a first-person capability probe rather than a primary-source claim. Every other assertion in the book is a snapshot claim as of 2026-08-30.

Build identifier and generation. The build identifier v20260913 is the *content* edition: it names the source snapshot and evidence cutoff that the text reflects. Re-rendering that same source to a PDF on a later date (e.g. a proof generated in October) does not change the content edition and does not extend the evidence cutoff; it only changes the PDF's generation timestamp, which is recorded in the document metadata and is not evidence. A change to the *content* requires a new build identifier, which invalidates the prior edition and is recorded in the release log — except a dated post-cutoff addendum carried under its own revision identifier and listed in the Appendix addenda row.

Release log. The revision that produced this PDF is recorded at the end of the Sources, Method, and Reproducibility chapter, in the "Edition history" panel, along with the source revision (commit), build identifier, evidence cutoff, appendix addenda, and generation date.

Reading conventions

Three conventions keep the book consistent and honest about its own limits.

Terminology. For the capacity arithmetic in this handbook, GPU memory and VRAM are used generically for accelerator-local memory; HBM refers specifically to high-bandwidth-memory implementations, which is what the worked examples assume. TTFT, time-to-first-token and prefill latency likewise; RAG and retrieval-augmented-generation are the same. Where a distinction is architecturally load-bearing — prefill versus decode, total versus active parameters, model capacity versus system capacity — the book holds it sharply. Synonyms are a readability concession; load-bearing contrasts are never relaxed (Ch. 2, 8, 17).

Hardware is a generic stand-in. The worked arithmetic is anchored to concrete constants

— for example, an H100 GPU's 0.989 PFLOPS BF16 dense tensor-core peak and 3.35 TB/s HBM bandwidth, with an 8×H100 host used as the canonical deployment unit — because arithmetic needs concrete anchors. Those values are a *current* high-end accelerator, presented as an example, not a prophecy: the H200, B100/B200 and later generations change the constants, not the method. Re-derive the constants from the current hardware sheet; the roofline (Ch. 8) and the canonical arithmetic (Ch. 7) keep the method independent of any single generation. Forward-looking numbers are marked ILLUSTRATIVE.

Quick reference. For a day-to-day cheat-sheet: Chapter 26 (§2.1) carries a workload-to-strategy decision matrix, and Chapter 25's Architecture Decision Record is a reusable template to copy into a repository. Those, plus the evidence discipline above, are worth re-reading first whenever a chapter feels dense.

A note on currency

The mechanisms in this handbook — tokens, memory floors, rooflines, parallelism, KV arithmetic — are durable; they do not change as the industry moves. But the frontier does move, and a handbook for architects should carry the latest technology information. The Appendix therefore surveys the frontier open-weight architectures of 2026, mapped back to the mechanisms and decisions explored in the body of the book — and closes on the question that is more durable than any single architecture: *where should the intelligence live*.

PART I.

The Token

CHAPTER 1.

It All Starts With the First Token

The Architect's Question

Before we can size a model, a context window, or a serving budget, we have to know what the input actually is. After this chapter we should be able to reason about an AI system's **smallest unit of cost and meaning** — the token — and to translate between human units (a sentence, a page, a word) and the machine unit every architecture decision is priced against. This is the first rung of the token⟶fleet spine: everything downstream (memory, compute, latency, cost) is ultimately a statement about *tokens*.

1.1. Concept

A **token** is the atomic unit of *text* that a language model reads and writes. It is not a word, not a character, and not a byte — it is whatever the model's *tokenizer* decided to carve the text into. A single token can be a whole word (`handbook`), a common subword (`hand`), a single character, a short punctuation+space pair, or in worst cases a fragment of a character. (This chapter scopes to *text-tokenized* autoregressive models. Modern multimodal systems also use non-text token-like representations — image patches, audio frames — that are not produced by a text tokenizer; for those, "token count" is a different quantity from text-token count and does not map one-to-one onto model compute the way it does here.)

The disconnection from human units is the first thing an architect has to internalize: **cost and capacity in an LLM are measured in tokens, not words or characters**, because the workload accounting is token-based — embedding lookup, attention arithmetic, KV cache memory, and decode time are all *counted* in tokens. That does not mean every operation has a fixed per-token price: the

cost per token varies by phase (prefill vs decode), by operating point (batch size, context length), and by hardware utilization, and attention work grows nonlinearly with context. The token is the unit we count and budget in; the per-token cost is what the later chapters derive. This chapter exists to make that switch automatic.

1.1.1. Tokenization

Tokenization splits a string into an ordered list of integer IDs from the model's **vocabulary** (typically tens of thousands, up to ~256k entries). The split is data-driven: learned from a large corpus, byte-pair encoding (BPE) repeatedly merges the most frequent adjacent byte/subword pairs until the vocabulary is built, so the boundaries are wherever the corpus statistics happened to fall — not where a grammarian would put them. Two practical consequences follow. First, text is generally **recoverable** from its token IDs under the specified tokenizer (the detokenizer inverts the encoding), but the *segmentation* does not correspond cleanly to words or semantics: the characters of `architecture` and `architect` may or may not share a token depending on corpus frequency. The encode/decode round-trip is usually lossless for the byte-level mapping, but the *token boundaries* are not semantically meaningful. Second, token counts are **not proportional to character counts in any fixed way**. [1P][FACT] A high-frequency English word is often one token (verifiable on most vendor tokenizer demos — e.g. common words like *the*, *we*, *run* render as single tokens); a rare technical term, a long digit string, or dense code is frequently several. The "one token ≈ 4 characters" rule of thumb is for rough estimation of general-English prose, never a law — we confirm against the model's own tokenizer before pricing anything.

1.1.2. Context window

The **context window** is the maximum sequence length the model can condition on at a given generation step — that is, the total of the retained input/prefix and the tokens generated so far. It is a hard *service* constraint at the configured limit: exceed it and the request fails or must be truncated. (This is the engine-configured maximum, not a law of physics — some models use sliding-window or rolling attention that retains only a bounded recent context, and a few support positional-scaling or provider-side context extension, so the *model's* positional capability and the *serving stack's* configured cap can differ; the distinction is developed in Ch 7 and Ch 22.) Current-gen models commonly ship windows ranging from roughly 8K up to a million-plus tokens, varying by model and vendor ([1P][FACT] vendor model cards, e.g. 128K/1M+ windows as of 2026); the advertised number is a fixed, checkable property of the model we choose — verify it on the card, never assume it from the family name. Note there are three related but distinct limits: the *model-advertised maximum* (the card's window), the *engine-configured maximum* (what the serving stack is set to allow, which can be lower to bound memory), and the *request-level available input budget* (the advertised window minus the reserved generation budget and any positional-scaling or provider-API cap). The context window is one of the first numbers we will be quoted, and one of the easiest to overcommit against. But it

is a *configured maximum*, not a per-request charge: a 9.2K request in a 128K window is computed, cached, and billed on the ~9.2K tokens actually used, not on the full 128K. What the window *does* bound is the worst case — the memory a single request could reserve and the admission capacity the engine must hold — and some engines reserve or pre-allocate against that maximum (a policy choice that varies by engine), while others allocate only for the tokens actually processed. So the window sets the ceiling on reservation and admission, not the floor on per-request cost; the cost tracks the tokens actually cached and billed (developed in Ch 7 and Ch 16).

1.1.3. Embeddings

Text enters the model as token IDs, but the model does arithmetic on vectors. The first such vector is the **token embedding**: a learned lookup table maps each discrete token id to a dense vector in a high-dimensional space, and the transformer operates on those vectors. Two distinct widths must not be conflated: the **token-embedding width** (the model's hidden dimension, e.g. 4096 for LLaMA-7B, 8192 for LLaMA-2/3 70B and for the canonical 70B reference, 12288 for a GPT-3-class 175B model) and the **retrieval-embedding width** (the dimension of a sentence/document embedding produced by a separate encoder for RAG, typically 384–1536 for dedicated retrieval models, or the full hidden dim if the LLM itself is used as the encoder). The "128 to a few thousand" range applies to *retrieval* embeddings; the *token* embedding width is architecture-dependent and for modern LLMs is *illustratively* in the 4096–16384 range (not an exhaustive bound across all models). Two other vector objects are distinct from the token embedding and should not be merged with it: **positional encodings** (which encode a token's position in the sequence, added to or modulating the embedding) and **contextual hidden states** (the per-layer, per-position activations the transformer produces, which depend on the whole context, not just the token id). The token embedding maps each discrete token id to a learned continuous vector; relationships in that learned space emerge from training but should not be interpreted as a simple human-semantic distance metric.

For the architect the practical facts are: embeddings live in a lookup table sized `vocab × dim`, they account for a real but small slice of a model's parameter count (a 100k × 4096 table holds 100,000 × 4,096 ≈ 409.6M ≈ 0.4B params — a rounding error next to a 70B model, but not zero), and they are the first thing a *vocabulary mismatch* or a *re-tokenized prompt* can silently change.

1.1.4. Attention

Attention is the mechanism by which each token's representation is recomputed as a weighted blend of the representations of all tokens before it in the context. The weights come from a similarity (query·key) between the *current* token and every *prior* token, normalized, and used to mix the value vectors. It is the mechanism that makes a model "pay attention to" relevant earlier tokens when producing the next one.

The architect-relevant fact: attention's cost scales **quadratically with context length** in the full-attention regime — the number of input×output position pairs grows as L^2. That quadratic term

is the single biggest reason context windows feel expensive, and it is the pivot for every optimization downstream (sparse/linear attention, KV caching, retrieval to keep context short).

One precision matters before the mental model hardens: the L^2 term is a **prefill** cost — it describes computing attention across all position pairs in one pass over the full input. During **decode**, each generated token attends once to the growing prefix, so the per-token step is a *linear* cost in context length, and the length shows up as a *growing KV cache memory footprint* (per-token key/values) rather than as per-step compute. The practical read is therefore *"long context is quadratic in prefill compute, and linear-but-memory-growing in decode"* — a distinction as important as the quadratic fact itself, and one we return to in Chapter 2 (compute gears), Chapter 7 (memory arithmetic) and Chapter 8 (roofline). Keeping prefill and decode separate is what prevents the over-simple "long context = quadratic inference" once we optimize context in later chapters.

One architectural consequence to hold now: *which layers emit a per-token cache is a property of the attention architecture*, not the context length alone — dense attention emits a key/value per token on every layer, while hybrid/linear-attention layers (Mamba-style state, linear-attention kernels) hold a *constant-size* recurrent state that does not grow with length. A third family — **compressed per-token KV**: MLA-style latent attention, grouped-query attention (GQA) and multi-query attention (MQA) head sharing — still stores a per-token entry, so its cache *does* grow with token count, but at fewer bytes/token than full MHA. These are distinct mechanisms: constant-state (no per-token growth) versus reduced-width per-token (per-token growth, smaller footprint). This is why "the KV problem" and its fixes are really a *model-architecture* question (Ch. 3) that lands as a *memory* question (Ch. 7) — and why the token layer is the right place to have met it. We only need the concept here; the mechanism inventory is Chapter 3's, the arithmetic Chapter 7's.

1.1.5. KV cache as a concept

When the model generates one token at a time, it recomputes the same prefix repeatedly unless it saves the intermediate results. The **KV cache** (key–value cache) is the stored key and value tensors for every token in the context, so that generating the next token only computes attention against the new token rather than re-deriving the whole prefix. It is the reason "long conversations are expensive in memory, not just in compute."

KV cache size per token scales with

$$KV_{\text{per-token}} = 2 \times n_{\text{layers}} \times n_{\text{KV heads}} \times d_{\text{head}} \times \text{bytes-per-value}$$

(one key and one value per layer per **KV head**). For **full multi-head attention (MHA)** the KV heads are all the query heads, so `n_KV heads × d_head = d_hidden` and the formula reduces to the simpler introductory form `2 × n_layers × d_hidden × bytes-per-value`. The general form matters once we meet **grouped-query (GQA)** and **multi-query (MQA)** attention, which share a small number of KV heads across many query heads and can make the cache several times smaller than the full-MHA figure (Ch. 7) — so `d_hidden` alone is *not* the correct KV width for those

architectures. It is on the order of **~256 KiB (0.26 MB) per token for a 7B-class model (32 layers, d_hidden 4096, full-MHA) and ~1.25 MiB (1.31 MB) per token for a 70B-class model (80 layers, d_hidden 8192, full-MHA)** at 8-bit precision. The arithmetic is the formula above with one byte per value: 2 × 32 × 4096 = 262,144 B and 2 × 80 × 8192 = 1,310,720 B. That 8-bit figure is the *raw tensor byte-halving* of the BF16 value — exactly 50% (1.31 MB vs 2.62 MB). So FP8 KV = raw tensor byte-halving = 1.31 MB/token (exactly 50% of BF16). Any block-allocation/metadata overhead is NOT vendor-measured here and must be filled by a deployment benchmark. The vLLM FP8-KV blog post's often-quoted '54%' is a decode inter-token-latency (ITL) slope, not a memory ratio, so it is not a memory-footprint coefficient here. At 9.2K tokens the raw byte-halving figure gives ~12.06 GB (not ~13.4 GB — the figure one gets by assuming ~11% block/metadata overhead on top of the raw tensor bytes). A different engine or a GQA/hybrid-attention model has a different per-token footprint, so re-derive it for the target stack (the geometry and the "do not generalize" caveat are in Ch. 7). [ILLUSTRATIVE][DERIVED] Either way, a long context (say 32K tokens) alone can be tens of GB of memory. A first non-obvious architectural lesson hides here: *MoE expert sparsity alone does not reduce per-token KV state.* A Mixture-of-Experts model activates only a fraction of its neurons per token, which saves compute, but the attention layers still process every token densely and emit a key/value per token — so MoE shrinks compute-per-token, not memory-per-context. What actually determines KV memory is the *attention architecture and cache policy*, not the expert count: GQA/MQA shrink the per-token K/V width, hybrid/linear/compressed-latent attention change how much context is retained, sliding-window caps some layers' retained context, and quantization (FP8) reduces the bytes per element without stopping the linear growth. This is a controlled comparison — it holds the attention geometry, context length, and cache dtype fixed; an MoE model that also uses GQA or a different attention mechanism can have a much smaller KV footprint than a dense full-MHA baseline. The distinction — compute-sparsity vs memory-sparsity — is one an architect has to get exactly right, and it is why "the KV problem" is an attention-architecture question more than a model-size question (developed fully in Ch. 3 and Ch. 7). We deliberately keep this to concept + order of magnitude here; Chapter 7 (Memory) does the verified arithmetic against the canonical scenario.

1.2. Mental Model

A token is best understood as a **metered unit of model I/O**, the way electricity is metered by the kilowatt-hour — important not because a single kilowatt-hour is meaningful by itself, but because *every* downstream cost and capacity number is denominated in it. (It is a computational/textual unit, not a unit of thought: two tokenizers can render the same semantic content in different token counts, and a reasoning model can spend very different compute per visible token.)

A useful image for the full pipeline:

> Text → **tokenizer** → discrete IDs → **embedding** → vectors → **attention** recomputes each token → **KV cache** remembers the prefix → generate one token at a time.




FIGURE 1.1: The KV cache: every decoded token adds one K/V per layer per head. This is a **single-layer detail** view: one layer's stored K and stored V drawn separately, each enumerated per head (h_1–h_4); the full token-travel pipeline is in Fig 1.2 and the multi-layer overview in Fig 2.1, where the cross-layer accumulation is shown.

The KV cache: attention keeps every past token's key and value, so cache memory grows linearly with sequence length (concept; the verified arithmetic is Ch. 7's).




FIGURE 1.2: How a token travels: text → tokenizer → IDs → embedding → attention → KV cache. **Conceptual only:** this is a one-pass abstraction, not the full transformer — the K/V are produced *within every applicable layer* (not after a single "attention" stage), and the KV cache is a *persistent state* that is both written (append) and read (attend) across steps, not a terminal processing stage. The read-side and the iterative loop are shown in Fig 2.1.

How a token travels. The token is the interface between a human's request and the machine's arithmetic: carved by the tokenizer, embedded into a vector, attended against past context, and remembered in the KV cache. This is a conceptual abstraction of one forward pass, not the full transformer: each layer also runs MLP/projection, normalization, and residual paths, and the caption's caveats apply — the full mechanism inventory is Ch. 3, the arithmetic Ch. 7. (Concept; the iterative autoregressive loop and the read-side of the persistent KV state are shown in Fig 2.1.)

Reading the mnemonic: read "remembers the prefix" as persistent state, not as a processing stage — the K/V are computed and read *within* the attention layers at every step. The full per-step read/append ordering is in Fig 2.1.

We do not need to hold all of this as a practitioner. The durable mental model is: **tokens are the interface between a human's request and a machine's arithmetic**, and *anything* we are asked to size or price in an LLM system reduces, one way or another, to "how many tokens, in what context, with what precision."

1.3. Worked Example

The canonical scenario (Ch 4, Table 4-2 — the one set of numbers every chapter cites) is an enterprise Q&A system: ~2,000 registered users, ~10 requests/s average, prompt of ~1,200 tokens plus ~8K retrieved context (~9.2K input), ~300-token output, on a 70B-class dense model. We reuse those numbers everywhere, so let us read one concrete property off them here.

Worked example, not reference. If average request is ~9.2K input + ~300 output ≈ **9.5K tokens** per request, and traffic is ~10 req/s, then the system ingests:

- **Input tokens/s**: 9,200 tokens/req × 10 req/s = **92,000 tokens/s** (peaks higher at ~40 req/s ⟶ ~368k).
- **Output tokens/s**: 300 ×10 = **3,000 tokens/s** output.
- Roughly **30× more input tokens than output tokens** in this workload (9.2K ÷ 300).

Table 1-1 — Token throughput of the canonical workload (worked example, not reference).

metric	value	derivation
input tokens / request	~9,200	canonical scenario (Ch 4, Table 4-2) (1,200 prompt + 8K context)
output tokens / request	~300	canonical scenario (Ch 4, Table 4-2)
input / output ratio	~30×	9,200 ÷ 300 [canonical scenario] [DERIVED]
input tokens/s @ 10 rps	~92,000	9,200 ×10 [canonical scenario] [DERIVED]
input tokens/s @ peak 40 rps	~368k	9,200 ×40 [canonical scenario] [DERIVED]

metric	value	derivation
output tokens/s @ 10 rps	~3,000	300 ×10 [canonical scenario] [DERIVED]

(All figures trace to the canonical scenario (Ch 4, Table 4-2); none are measurement claims.)

This ratio — input-heavy — is a *hypothesis* that memory (KV cache) and prefill dominate this system's cost rather than decode, not a conclusion token counts alone establish. Decode's serial nature, per-step weight reads, batching, cache residency, and the latency SLO can still dominate capacity economics even on an input-heavy workload; the token mix is the first signal, and the measured per-phase utilization and goodput (throughput that meets the SLO; Ch 7, Ch 8, Ch 14) are what confirm it. We will not act on it here; Chapter 7 (Memory) and Chapter 8 (Compute) do. The point of the worked example in this chapter is to fix *the unit*: every one of those numbers is a statement about tokens, and we can now say it without translating from words or pages.

1.4. Measurement

For this concept chapter, measurement is about **counting tokens correctly**, because a miscount at the input silently misprices everything downstream. Three things an architect can actually check:

1. **Actual token count, not the rule of thumb.** Run the model's *own tokenizer* on representative prompts. The "4 chars ≈ 1 token" heuristic is for estimation only; real counts differ by language, formatting, code, and tokenizer version.
2. **Input vs output split.** Measure both legs of the request (prompt tokens and generated tokens), because they land on different bottlenecks — input on memory/prefill, output on decode — and on different cost line items.
3. **Peak vs average context.** Log the distribution of context lengths, not just the mean. A workload that averages 9.2K input tokens but peaks far higher (illustrative variant, say 32K) has a very different KV cache and latency profile.

This measurement habit is the token-layer answer to the book's recurring question, "what would I actually measure here?" — we measure token counts and their distribution, at the edge, before any architecture decision is made.

1.5. Common Mistakes

- **Assuming one token ≈ one word.** A token is often a *word fragment*, not a whole word: a high-frequency English word is frequently one token, but a longer or rarer word is usually split into several subword tokens, and code, numerics, and non-Latin scripts routinely run 2–5× the naive word-count estimate. The mapping is tokenizer-dependent (it depends on the

corpus the tokenizer was trained on), so the "one token ≈ 4 characters" rule of thumb is for rough estimation of general-English prose only — confirm against the model's own tokenizer before pricing anything.

- **Ignoring the input/output asymmetry.** Treating a request as "one unit" hides that input-heavy workloads tend toward high prefill compute and KV-capacity pressure, while output-heavy ones are decode-dominant (run-time per generated token) — opposite bottlenecks with opposite fixes. (Note: "capacity pressure" is a memory-*capacity* constraint, not a memory-*bandwidth* bound; see Ch 4/8.)
- **Quoting context window as free capacity.** The window is an upper bound, not a recommendation; using it fully is expensive. Keeping a 9.2K average inside a 128K window still costs for the length we actually use.
- **Trusting a vendor's tokenizer count without checking.** Tokenizer versions change and report differently; measure on *our* traffic, not the marketing figure.

1.6. Architecture Consequence

Whatever we learned here, file it under **"can I size an input before I buy capacity?"** Concretely, the decision this chapter enables is: *estimate tokens-per-second (input and output separately), and therefore tokens-per-second capacity and cost, before choosing a model or a serving configuration.* It is the load-bearing input to model selection (Ch. 5), the memory budget (Ch. 7), the compute budget (Ch. 8), and the token economics (Ch. 16). No downstream chapter runs without a token count to price against — this one gives us the unit.

1.7. What We Still Don't Know

As of 2026-08: tokenizer internals are rarely published in full, so exact per-token behavior for a given model is often only empirically observable, not specified (— tokenizer construction details, e.g. exact BPE merge rules for commercial models, are not fully public). Whether a fully learned, near-optimal tokenization for *our* domain can beat the generic vocabulary by a repeatable, quantified margin is still an open, workload-dependent question. And the interaction between tokenizer choice and downstream reasoning quality is not yet crisply characterized — we flag it as an open area rather than a settled fact.

1.8. End-of-Chapter Mini-Case: The Internal Q&A Tool, From First Principles

(Chains the continuous scenario — this is its first appearance.)

An architect is pulled into an early-stage design conversation about a new internal Q&A tool. There is no model, no server, no budget — just the raw ask: "We have thousands of employees who want to ask questions over our internal documents." Before any architecture can be defended, we have to turn that vague desire into a *machine-denominated* statement.

From the token-level work alone (which we worked through in this chapter), the architect can

already establish: the unit is tokens; the request shape will be prompt + retrieved context + output; the workload is input-heavy; and the first number to lock down is tokens-per-request, because every downstream decision (which model fits, how much memory, what latency is possible) is priced against it. The specific sizing — turning "thousands of employees" into ~2,000 registered users, ~10 req/s, ~9.2K input tokens — is Chapter 4's job (workload anatomy). Here the point is narrower and sharper: *we can now speak the system's currency*, and that is a prerequisite for every architecture question that follows.

CHAPTER 2.

What Actually Happens During Inference

The Architect's Question

After this chapter we should be able to reason about the two fundamental modes of LLM inference — prefill and decode — and to identify which system constraint each mode exposes. We should be able to compute the bandwidth and FLOP demands of a given workload, compare them against real hardware limits, and understand why, *at the canonical low-batch operating point*, decode is HBM-bandwidth-bound while prefill is compute-bound — and that this is a regime statement, not a universal rule: at other batch sizes and context lengths the binding constraint can shift (the qualification is developed in §2.2 and Ch 8). This distinction directly shapes architectural decisions: whether we need more GPUs, whether we can disaggregate prefill from decode, and how we size memory and compute in a fleet. After this chapter we should see inference not as a single monolithic cost but as two opposite-bound processes that require different levers.

2.1. Concept

Inference is the process of turning a sequence of input tokens into a sequence of output tokens using a trained neural network. In an autoregressive model, every generated token requires a fresh forward pass, but the computation split between the prefix (the prompt) and the suffix (the generated output) is fundamentally different.

Prefill is the first pass over the prompt. The model reads every token of the input context, computes attention over the entire prefix, and produces the first output token. During prefill, the model attends over all input positions, so the *attention* work grows with the square of the context length. (The full prefill also has a substantial *linear-in-L* component — the weight-matmul FLOPs,

$2NL$ — which does not grow quadratically; the quadratic term is the dense-attention pairwise component, developed in Ch 8 and Ch 22.)

Timing convention (used throughout the book). We attribute the **first sampled token to prefill**: prefill = processing the prompt + sampling token 1, and decode = the per-token loop that begins with token 1 as its first *input* and produces token 2 onward. This is the standard TTFT convention — time-to-first-token includes the first token's sampling, so the first token is the last output of prefill, not the first output of decode. (Some engines split this differently — e.g. counting the first token's forward pass as the first decode step — but the difference is one token's worth of latency, and every formula and figure in this book uses the convention above.)

Decode is the per-token generation that follows. After prefill, each new token only attends to the cached keys and values from the prefix plus all previously generated tokens. In the *batch-1-equivalent* weight-streaming model we use for this first-pass arithmetic, the per-step cost has two parts: the **weight-read** (the entire model weight matrix from HBM, constant in context length because the auto-regressive pass reuses the same parameters every step) and the **attention over the growing KV cache** (linear in context length, since each new token attends to all cached keys/values). At the canonical operating point the weight-read dominates, so the per-step cost is *approximately* constant in context length — but that is a regime statement, not an identity; the attention term grows with context and is the one that eventually binds at long context (Ch 8, Ch 22). (In a real serving stack, batching and weight-read amortization change this per-request picture substantially; that is the subject of later chapters.)

The critical architectural insight, at the canonical low-batch operating point: prefill *tends* to be compute-bound (high arithmetic intensity — the whole prompt is processed in one parallel pass), while decode *tends* to be bandwidth-bound (low weight-reuse efficiency — the 140 GB weight matrix is re-read every step for a single token). These are the typical bottlenecks, and confusing them is the most common architectural misstep. But neither is a universal physical law: the characterization is an operating-point property of model × workload × kernel × hardware (batch size, attention length, and kernel fusion all shift it), and the roofline framework in Ch 8 is what identifies which regime a given kernel actually sits in.

One detail the figure makes explicit is *when* a token's K/V enters the cache. The first decode step, precisely: (a) prefill populates the cache with the prefix K/V and samples the first token; (b) that first token is the *input* that seeds the decode loop (the green initialize path in Fig 2.1); (c) each decode step takes one input token, runs the transformer on it — which **computes and appends that input token's K/V** to the cache — attends over the cached K/V, and samples the next token from the logits; (d) the sampled next token is the *output* of this step and the *input* of the following step, whose forward pass then computes and appends its K/V. A token's K/V therefore enters the cache on the step in which it is the *input*, not on the step in which it is sampled.

This is the figure the rest of the book builds on. Keep the shape in mind: every later chapter refines one part of it. **Chapter 3** (model) asks *what the blocks compute and how the KV cache is sized*; **6**




FIGURE 2.1: The canonical end-to-end inference pipeline, in three bands. PREFILL (top) is the one-shot parallel pass over the whole prompt; it populates the persistent KV cache and is the dominant contributor to TTFT (time to first token — though TTFT also includes queueing, preprocessing, and transport, so model prefill latency is a component of, not identical to, user-observed TTFT). DECODE (bottom) is the single-token autoregressive loop, measured by TPOT/ITL (time per output token / inter-token latency); each step reads the cached K/V, appends the new K/V, and samples the next token. The green *initialize* path seeds the loop with the first sampled token. The three bands and the single PERSISTENT KV CACHE box are *conceptual* groupings for teaching, not runtime components: a real serving stack has per-layer, per-request KV state and no literal "prefill band" object.

(metrics) measures which phase is the bottleneck; **7** (memory) prices the KV cache precisely; **8** (compute) derives the FLOPs and roofline that make prefill compute-bound; **10** (parallelism) splits the model across the devices the pipeline traverses; **11** (serving) schedules many of these pipelines; **15** (performance) diagnoses which phase actually hurts; and the fleet chapters price the host count the loop demands. Because the two phases stress *different* resources, the armature of the whole book sits on this single split.

Where the Q/K/V and KV cache live in this picture (the bridge to Ch. 3/7). The transformer layer computes, for each token, three learned projections — **query (Q)**, **key (K)** and **value (V)**. Attention scores are the similarity of a query to every prior key; the scores weight the values, which are blended into the token's new representation. What matters for architecture: **K and V for a token do not change once that token has been processed.** The query for a *later* token attends against them, but rewriting them would be redundant work. So decode does not recompute the prefix's K/V — it *reuses* the stored K and V from prefill. That is the KV cache: not an optimization bolted on, but the direct consequence of *which* projections are reusable and which (the query) is always new. It is also why KV memory grows with sequence length (one K and one V per token, per layer), why attention architecture and precision (GQA/MQA, KV quantization) change the bytes-per-token of what is really a memory problem, and why kernel choices like FlashAttention change the traffic, not the footprint. Ch. 3 and Ch. 7 do the arithmetic; this figure is where the causal thread starts.

A vocabulary note that prevents a common conflation. Several terms sound like the same thing but are *not* interchangeable, and the chapter will use them precisely:

term	what it is	what it is **not**
KV cache	the stored K and V tensors per token per layer, saved so decode does not recompute the prefix	not an *optimization* over a shared prefix
PagedAttention	a memory-*allocation* scheme for the KV cache (splits it into fixed-size pages, cuts fragmentation/waste)	not a way to *reduce* the amount of KV state
prefix caching / KV reuse	reusing *already-computed* K/V for a shared prefix, to skip re-prefilling it	not the same as caching the KV of a *single* request's own decode

term	what it is	what it is **not**
prompt caching	broader system/provider term; the book uses it to mean *reusing the KV of a shared prompt prefix across requests*	not a separate mechanism from prefix caching in this book's usage
KV quantization	reducing the *bytes* per K/V element (e.g. FP16→FP8)	not reducing the *number* of key/value entries
KV offloading	moving some KV state out of GPU HBM (to host DRAM/SSD), trading capacity against transfer latency	not shrinking the state itself

The short version: the **KV cache** is *the state*; **PagedAttention** manages *where that state lives* on the device; **prefix caching** avoids *computing it twice* for a shared prefix; **quantization** shrinks *each element*; **offloading** moves *some of it elsewhere*. Each attacks a different constraint (capacity, fragmentation, redundant compute, byte count, residency), and each has its own trade-off — later chapters put numbers on them.

The resource model (the book's recurring framework). Inference consumes several *fundamentally different* resources, and the single most useful habit an architect can build is to name which one a given optimization or bottleneck is about. The pipeline figure above surfaces four of them, and the metric chapter (Ch. 6) and the design chapter (Ch. 12) build on the same set. The book will use these names consistently:

resource	unit	what it limits	first surfaces in
compute capacity	FLOPs	how much arithmetic per unit time	prefill (Ch. 2, 8)
memory bandwidth	bytes/s	how fast data can move	decode (Ch. 2, 8)
memory capacity	bytes resident	how much state fits (weights + KV)	KV cache / concurrency (Ch. 7)
interconnect bandwidth/latency	bytes/s, delay	cross-GPU / cross-host movement	parallelism (Ch. 9, 10)

resource	unit	what it limits	first surfaces in
scheduling capacity	useful work resident	keeping hardware busy despite request raggedness	serving (Ch. 11)
latency budget	TTFT, TPOT/ITL, end-to-end	the SLO the system must meet	workload (Ch. 4)
throughput / goodput	useful tokens/s under SLO	completed work, not just tokens/s	metrics (Ch. 6)

The discipline the book applies everywhere: **every optimization is a hypothesis about which resource it shifts and what it trades away.** FlashAttention moves the bottleneck from *bandwidth* toward *compute* (fewer HBM round-trips); KV quantization trades *capacity* for a small precision loss; prefix caching trades *prefill compute* for *cache residency*; continuous batching trades *latency* for *utilization*; P/D disaggregation trades a *homogeneous pool's* simplicity for separate *compute- vs bandwidth-optimized* pools. When the book introduces a technique, it will name the resource it targets and the resource it costs — that is the difference between reasoning and a vendor catalog. The optimization decision map (Ch. 15) is this framework read backwards: from an observed symptom to the resource that is likely starved.

The causal chain (how the chapters hold together). The book is one argument, not a set of topics. The thread is:

tokens determine sequence length → sequence length determines KV growth and attention work → KV growth determines memory pressure → attention and model execution determine compute and bandwidth demand → those resource demands determine latency behavior → latency and concurrency determine scheduler requirements → scheduler behavior determines serving efficiency → serving efficiency and SLOs determine host count → host count and model topology determine interconnect and fleet architecture → fleet architecture determines cost, resilience, placement, and operational complexity.

Every chapter is one link of that chain, and each *deepens* the same mental model from Ch. 2 rather than restarting it. By the time the argument reaches Ch. 11 (serving) or Ch. 17 (fleet), the concepts were introduced in Ch. 2 — Ch. 2 gave the shape, the later chapters give the numbers and the decisions. If a chapter ever feels like "here is another concept," it has broken the thread.

2.2. Mental Model

Inference is two fundamentally different physical processes, distinguished by what limits them.

In the canonical operating point — a long prompt with high arithmetic intensity —

prefill is compute-bound. It is like a massive industrial fire hose drawing one enormous burst of water out of a reservoir: the flow is huge, and the time it takes is limited entirely by the raw horsepower of the pump (compute/FLOPs) pushing the water. The pipe is wide open, but the motor is working at its absolute limit — and the burst delivers the first glass of water, the first token. (This is an operating-point property, not a fixed identity: a low-intensity prefill or a tiny prompt could shift it toward the bandwidth side — Ch. 8 makes the dependence on model × workload × kernel × hardware explicit.)

In the canonical operating point — low batch — decode is bandwidth-bound. It is like pushing the water of that same 140,000-liter reservoir (140 GB) through a standard garden hose: the whole volume must flow every 25 milliseconds just to deliver one glass of water — one generated token. The pump (compute) is more than powerful enough, but the diameter of the hose (HBM bandwidth) physically cannot move that volume of water in that time frame. (Again an operating-point property, not an identity: at high batch decode can become compute-bound.)

When we ask "is this workload compute-bound or bandwidth-bound?" the answer depends entirely on which physical constraint we are hitting: the horsepower of the engine, or the diameter of the pipe.

Figure convention (used throughout the book). Arrows in the diagrams carry different meanings by context, and the reader should not assume one universal reading: a **data-flow** arrow (Fig 2.1, 11.3) shows tokens or activations moving; a **dependency** arrow shows "must be decided before"; an **influence** arrow (Fig 4.1) shows "constrains/informs"; a **causation** arrow (Fig 6.1) shows "drives / causes"; and a **conceptual-association** arrow (App. A.4) shows "relates to." Where a figure's arrows are ambiguous, the caption states the intended reading.

2.3. Worked Example

To make the distinction concrete, let us walk through the canonical enterprise Q&A scenario from canonical scenario (Ch 4, Table 4-2): a 70B-class dense model in FP16, 1 host with 8×H100 GPUs, prompt of 1,200 tokens + 8K retrieved context (~9.2K input), 300-token output, TTFT budget 1.2 s (retrieval ~120 ms + prefill), TPOT budget ~25 ms/token. All numbers are derived from the canonical scenario; none are measurement claims. Where the book writes *Analytical bound — not a benchmark*, it marks a first-order model check under a stated bounding assumption, not a measurement of actual serving throughput. *Scope of the single-host premise.* Throughout this chapter and the arithmetic chapters that follow, "1 host with 8×H100" is a **per-host / per-request feasibility** container: it asks whether one host can meet the per-request latency and memory SLO (TTFT 1.2 s, TPOT ~25 ms, KV residency) for a single in-flight request. It is **not** a claim that one host serves the canonical 10 rps average / 40 rps peak *arrival rate*. The per-request arithmetic here answers "does one host's compute/bandwidth/memory satisfy one request's latency budget"; the *capacity* question — how many such hosts to absorb $\lambda = 40$ rps, where in-flight concurrency $\lambda \cdot W \approx 344$ at the ~8.6 s service time — is answered later (Ch 16–17), and is a different computation that must not be conflated with

per-request feasibility. Keeping the two questions separate is the difference between sizing a host and sizing a fleet.

2.3.1. Table 2-1 — Decode bandwidth and prefill FLOPs (worked example, not reference)

metric	value	derivation
Model params	70B	canonical scenario (Ch 4, Table 4-2)
Model weight bytes (FP16)	140 GB	2 bytes × 70B params [canonical scenario] [DERIVED]
Decode: weight-read per token	140 GB	Auto-regressive, batch-1-equivalent: one read of all weights per generated token before batching/amortization [canonical scenario] [DERIVED]
Decode: required bandwidth (TPOT ~25 ms)	5.6 TB/s	140 GB / 0.025 s (batch-1-equivalent weight-streaming model, before amortization) [canonical scenario] [DERIVED]
H100 HBM3 peak bandwidth	3.35 TB/s	NVIDIA H100 specs [1P] [FACT]
Decode: bandwidth verdict	bandwidth-bound	5.6 > 3.35 ⟶ under the batch-1-equivalent model, a single H100 cannot meet the demand; batching/amortization change this (see later chapters) [canonical scenario] [DERIVED]

metric	value	derivation
Prefill: input tokens	9,200	1,200 prompt + 8K context [canonical scenario] [DERIVED]
Prefill: FLOPs (2 × params × tokens)	1.29 PFLOP	2 ×70e9 ×9.2e3 ≈ 1.29 ×10^{15} [canonical scenario] [DERIVED]
H100 BF16 dense compute	989 TFLOPS	NVIDIA H100 BF16 tensor-core peak [1P][FACT]
Prefill: regime verdict	compute-bound regime	arithmetic intensity ~9.2K FLOP/byte > ridge ~295 ⟶ on the compute-bound side of the roofline [canonical scenario] [DERIVED]
Prefill: single-H100 capacity	insufficient for real-time prefill	1.29 PFLOP / ~1.08 s ≈ 1.19 PFLOPS demand > 0.989 PFLOPS H100 peak ⟶ one H100 cannot meet the TTFT deadline under this analytical model [canonical scenario] [DERIVED]

Worked example arithmetic details:

- **Decode bandwidth.** In auto-regressive decode, generating one token requires a full forward pass of the 70B parameter matrix. At FP16 (2 bytes per parameter), the weight footprint is $W = N \times 2 = 140$ GB. **This is the aggregate model-wide weight traffic** — but note the unit of comparison carefully. Name it precisely: this 140 GB is the **logical model-weight footprint used as a first-order HBM traffic approximation** (what later chapters call the **canonical weight-stream approximation**). It is the footprint that results from *reading every parameter once per decode step in a dense model with no reuse*, not a claim about physical HBM traffic in a real engine. Physical traffic depends on residency, caching hierarchy, fusion, batching, quantization, sharding, and implementation, and rises or falls accordingly. For a hypothetical single-device implementation holding the entire FP16 model, the aggregate model-weight traffic per decode step is ~140 GB; on a tensor-parallel deployment both weight residency




FIGURE 2.2: Prefill and decode on the roofline ridge. Low-batch decode (streaming weights per token) lands at ~1 FLOP/byte — the memory-bound side; long-prompt prefill lands at high intensity — the compute-bound side. These are operating points, not fixed identities: batch, context, precision, kernel and hardware all move a point across the ridge.

Two distinct conclusions, kept deliberately separate. (1) ***Regime:*** *arithmetic intensity places the canonical prefill point ~9.2K FLOP/byte, well to the right of the ~295 ridge — so prefill sits in the compute-bound regime; decode at ~1 FLOP/byte sits in the memory-bound regime. (2)* ***Capacity:*** *the stated TTFT deadline implies ~1.19 PFLOPS demand, exceeding the compared single-H100 theoretical peak (0.989 PFLOPS) — so one H100 is insufficient under that analytical deadline model. The regime classification and the capacity shortfall are independent: a workload can be compute-bound in regime yet still fit on the device, and vice versa. (Analytical bounds — not a benchmark: these are first-order model checks, not a measurement of actual serving throughput.)*

and this traffic are sharded across GPUs, so the relevant comparison is per-GPU shard traffic against per-GPU HBM bandwidth, plus communication overhead. (A 140-GB FP16 model cannot reside on a single 80-GB H100 anyway, so the whole-model-on-one-GPU comparison is deliberately hypothetical.) With a TPOT budget of ~25 ms per token, the *aggregate* required bandwidth is

$$B_{\text{req}} = \frac{W}{\tau} = \frac{140\ \text{GB}}{0.025\ \text{s}} = 5{,}600\ \text{GB/s} = 5.6\ \text{TB/s}$$

[canonical scenario][DERIVED]. A single NVIDIA H100 HBM3 delivers ~3.35 TB/s peak bandwidth [1P][FACT]. Since $5.6 > 3.35$, under this batch-1-equivalent weight-streaming model one H100 cannot supply the required *aggregate* weight-read rate — the decode phase is HBM-bandwidth-bound [canonical scenario][DERIVED]. Read this as an *aggregate lower-bound illustration*, not as the literal bandwidth requirement of a single H100 in a realistic 8×H100 configuration (where the model and its traffic are sharded, so each GPU streams only its shard against its own 3.35 TB/s, plus communication overhead). This is a statement about the *specified* single-request, ~25 ms/token model, not about all possible 70B serving: batching, weight-read amortization, and precision changes (later chapters) fundamentally alter the per-request bandwidth demand. Within the model, meeting that latency target calls for multi-GPU scaling or bandwidth-increasing topologies (e.g. NVLink-connected nodes).

- **Prefill FLOPs.** The prefill pass computes attention over the 9.2K input tokens and produces the first output token. The *parameterized-linear* FLOP floor for a dense transformer forward pass is well approximated as $2 \times$ params $\times$ tokens (the factor of 2 accounts for multiply-add per parameter per token). Call this what it is: **the parameterized-linear FLOP floor,** $2NL$**, excluding explicit attention-score/value aggregation and other non-matmul overhead.** The full-attention component is *not* captured by $2NL$ — it grows ~quadratically with sequence length (Ch 22), so for a 9.2K-token prefill $2NL$ is a lower bound on total compute, not the whole story. Thus:

$$\text{prefill FLOPs} = 2 \times N \times L = 2 \times 70 \times 10^9 \times 9.2 \times 10^3 \approx 1.288 \times 10^{15} \approx 1.29\ \text{PFLOP}$$

[canonical scenario][DERIVED]. An NVIDIA H100 delivers ~989 TFLOPS (BF16 dense tensor-core peak, without sparsity) [1P][FACT], which is 0.989 PFLOPS. (Here and throughout we quote the *dense*, no-sparsity tensor-core peak for any precision; NVIDIA's datasheet prints the 2× *with-sparsity* figure — 1,979 TFLOPS for FP16/BF16 — as its headline number, so a dense-vs-sparse note is required even in vendor material.) The required rate against the ~1.08 s prefill budget is

$$\text{rate} = \frac{1.29\ \text{PFLOP}}{1.08\ \text{s}} \approx 1.19\ \text{PFLOPS}$$

With $1.19 > 0.989$, **even before accounting for attention overhead, kernel inefficiency, and sub-100% model FLOPs utilization (MFU), this first-order lower bound already exceeds the H100's theoretical peak.** Therefore one H100 cannot satisfy the stated prefill budget under these assumptions. The prefill phase is compute-bound for the separate reason given in Table 2-1: arithmetic intensity ~9.2K FLOP/byte > ridge ~295 [canonical scenario][DERIVED]. Note the direction of this argument: exceeding the *theoretical peak* proves the target is impossible on a single H100 under the stated model, but it does **not** imply any rate below the peak is achievable — real kernels land well under MFU 100%. Meeting the latency SLO therefore calls for multiple GPUs (model parallelism or data parallelism) or more efficient attention implementations.

2.4. Measurement

How do we know whether a given workload is prefill-dominant or decode-dominant in practice? Three practical measurements:

1. **Divide the TTFT into retrieval + prefill.** Measure the retrieval latency (vector search, document fetch) separately from the prefill latency (prompt processing). In the canonical scenario, retrieval takes ~120 ms, leaving ~1.08 s for prefill on a 9.2K-token prompt. If prefill exceeds this budget, the bottleneck is compute or memory, not retrieval.

2. **Log TPOT against current sequence length, at controlled batch/concurrency.** Track the time-per-token as the generated sequence grows. This is a *scaling curve*, not a binary verdict. An **increasing** TPOT as the sequence lengthens reveals growing KV-attention cost — each new token attends over a longer KV sequence, and decode attention work and KV cache traffic generally grow with sequence length even though cached K/V projections are not recomputed. A relatively **flat** TPOT suggests weight streaming (a fixed per-step cost — reading the full 140 GB weight matrix each step) remains dominant. TPOT does not *have* to stay constant; batching, kernel choice, occupancy, and scheduling can make the observed curve complicated, so measure it rather than asserting a trend.

3. **Measure actual HBM utilization vs FLOP utilization.** Using GPU profilers (NVIDIA Nsight, vLLM stats), watch the fraction of peak HBM bandwidth consumed versus the fraction of peak FLOPS consumed. If HBM utilization is near 100% while FLOPS utilization is low, the kernel is bandwidth-bound (typical of decode). If FLOPS utilization is near 100% while HBM utilization is low, the kernel is compute-bound (typical of prefill).

These measurements cost nothing but a profiler attach and a few representative requests — and they prevent the architect from applying the wrong optimization lever.

2.5. Common Mistakes

- **Treating prefill and decode as the same bottleneck.** A dangerous mistake is assuming that what slows prefill will also slow decode, or vice versa. Prefill FLOPs scale with input length; decode bandwidth is constant per token. Confusing the two leads to over-provisioning compute for a bandwidth-bound workload, or under-provisioning compute for a compute-bound one.

- **Assuming one H100 suffices for 70B inference.** The arithmetic in §2.3 shows that a single H100 cannot meet the decode bandwidth demand (5.6 TB/s vs 3.35 TB/s) nor the prefill compute demand (1.19 PFLOPS required vs 0.989 PFLOPS peak, from 1.29 PFLOP / 1.08 s). Attributing 70B serveability to a single GPU ignores the opposite bottlenecks and produces an architecture that fails latency SLOs.

- **Ignoring the input/output token asymmetry.** A workload with 9.2K input tokens and 300 output tokens imposes a *substantial prefill compute burden* despite producing relatively few output tokens — do not infer serving cost or resource pressure from output-token count alone. The two legs of the request have different cost structures and different optimization paths: decode is repeated per output token and dominates *wall-clock latency* (at the canonical ~25 ms/token, 300 output tokens ≈ 7.5 s of decode vs a ~1.08 s prefill budget), while prefill is a large one-shot burst of compute and dominates the *compute* burden (the 9.2K-input attention pass). Quoting only per-token latency or only throughput/s hides this distinction.

- **Using manufacturer-peak bandwidth/FLOPS without mapping to real kernels.** H100 3.35 TB/s HBM3 is the theoretical peak; actual sustained bandwidth for weight-read kernels may be 60–80% of peak. H100 989 TFLOPS BF16 dense is the tensor-core peak; actual matmul throughput depends on kernel fusion, batching, and precision. Citing raw numbers without kernel context is an anti-catalog error — the number must be matched to the actual serving kernel in use.

2.6. Architecture Consequence

The opposite bottlenecks of prefill and decode have immediate architectural consequences:

- **With prefill in the compute-bound regime → optimization levers:** kernel fusion (flash-attention, scaled-dot-product attention with fewer reads), model parallelism (splitting the 70B parameters across GPUs), more GPUs in parallel, or prefill-specific servers that dedicate hardware to the bursty preload phase. Quantization (FP8/BF16) does *not* reduce the underlying algorithmic operation count (the usual 2 × params × tokens FLOPs are approximately unchanged — the matmuls still multiply the same matrices); rather it reduces the precision, lowers the bytes transferred/stored, and can raise the *effective* accelerator throughput (8-bit tensor cores run at higher peak rate).

- **With decode in the bandwidth-bound regime → optimization levers:** continuous batching (vLLM, PagedAttention) to amortize weight reads across many tokens in flight, KV cache offloading to SSD or system memory, P/D (prefill/decode) disaggregation (separate pools of GPUs for prefill bursts vs. decode steady state), and higher-bandwidth memory topologies (NVSwitch, HBM3e).

The key architectural decision this enables: **can we disaggregate prefill and decode onto different hardware?** If prefill needs more FLOPS and decode needs more bandwidth, a single homogeneous GPU pool is suboptimal. A two-pool architecture — a prefill cluster optimized for compute (more GPUs, higher FLOPS) and a decode cluster optimized for bandwidth (faster HBM, larger NVLink domains) — is therefore an architecture worth testing. Whether it actually needs fewer GPUs is not established by the asymmetry alone: it depends on achievable utilization, duplicated model residency, KV-transfer cost, interconnect topology, workload shape, burstiness, and the hardware assigned to each pool, all of which must be measured. (The asymmetry makes it a candidate worth benchmarking, not a concluded win.) This is the central theme of Chapter 11 (Serving) and the prefill/decode-disaggregation pattern (Ch 12, candidate b).

2.7. What We Still Don't Know

- **Sustained HBM bandwidth for weight-read kernels.** The 3.35 TB/s H100 figure is a theoretical peak; real serving kernels (vLLM, TGI, transformer-engine) may achieve different sustained rates depending on kernel fusion, graph optimization, and batch size. — a hypothesis to be measured on real hardware before it is cited.

- **Effect of continuous batching on the 2 × params × tokens approximation.** Continuous batching amortizes weight reads and improves hardware utilization, scheduling efficiency, and aggregate goodput — but it does **not** reuse one request's transformer activations to avoid the forward-pass work of another unrelated request, so it does not reduce the mathematical FLOP count per request. Compute that *is* re-used across requests sharing a common prefix is a different mechanism: **prefix caching** (or KV reuse), which skips the re-prefill of a shared prefix and thereby does cut real forward-pass work for that portion. The magnitude of the prefix-cache hit rate at fleet scale is not yet pinned down. — to be benchmarked with realistic concurrency patterns.

- **Cross-technology bandwidth numbers.** HBM3e (next-generation) promises ~6+ TB/s per GPU, and AMD MI300X promises ~5.3 TB/s. How these compare to the 5.6 TB/s decode demand shifts the GPU count equation but does not change the fundamental bandwidth-bound vs compute-bound classification. [1P][FACT] — vendor-published specifications as of the 2026-08-30 cutoff; verify against the specific generation in use.

- **Effect of quantization on decode bandwidth vs prefill FLOPs.** Int4 or FP8 quantization reduces the weight bytes (e.g., 70B at FP8 = 70 GB instead of 140 GB), which directly lowers the HBM read demand in decode; it does *not* reduce the algorithmic operation count of the matmuls (the 2 × params × tokens FLOPs are approximately unchanged), though lower precision can raise the *effective* throughput of the tensor cores at which those ops run. The direction of the shift is clear (decode bandwidth improves; prefill ceiling rises in effective rate), but the precise trade-off point where decode becomes compute-bound rather than bandwidth-bound depends on the quantization scheme and hardware support. — workload-dependent.

2.8. End-of-Chapter Mini-Case: TTFT and the Prefill/Decode Split

The architect is still in the early design conversation about the internal Q&A tool described in Chapter 1. The team has settled on a 70B-class dense model for accuracy, and they have a rough traffic estimate: ~2,000 registered employees, each roughly as active as the canonical scenario (~10 requests/s average, peaks ~40 rps), with prompts of ~1,200 tokens of internal documents plus ~8K retrieved context and ~300 tokens of answer.

From the unit-and-token work of Ch 1 alone, the architect can already state the hard numbers: each request carries ~9.2K input tokens and ~300 output tokens. At 10 rps average, the system must sustain ~92,000 input tokens/s in prefill and ~3,000 output tokens/s in decode. At 40 rps peak, those numbers jump to ~368,000 and ~12,000 respectively. The architect can also state the two opposite bottlenecks: prefill will be compute-bound (~1.29 PFLOP per request at 9.2K input), and decode will be bandwidth-bound (a ~140 GB/token weight-read requiring ~5.6 TB/s sustained over each ~25 ms decode step). The team's immediate architectural choice is whether to build a single homogeneous GPU cluster or to separate prefill and decode pools — the differing bottleneck profiles make disaggregation worth evaluating, though whether it uses fewer GPUs must be measured rather than assumed (Ch 11).

Before passing this workload to Chapter 4 (workload anatomy), the architect locks in one more number: the tokens-per-request split. This is the currency every downstream chapter will price against, and it has already been established as ~9.2K input + ~300 output per request. The rest of the design — model fitting, memory budget, latency budget, cost — can now proceed in token-denominated terms.

CHAPTER 3.

Understanding the Model

The Architect's Question

After this chapter we should be able to reason about what a model's parameter structure means for deployment: dense versus Mixture-of-Experts (MoE), total parameters versus active parameters per token, and what each implies for compute budgets and memory budgets. We will meet the mechanisms (how MoE routes, how attention weights are computed) not to learn how to train a model but so that, as architects, we can look at a model card and immediately know whether the quoted parameter count is what we actually pay for at inference time, and whether the KV cache will grow as expected. After this chapter we can ask: *given a workload and a model architecture, what is the real residency and compute cost per token?*

3.1. Concept

The **parameter allocation regime** of a model determines how many of its weights are touched on each forward pass. This regime is not a property of the model family name alone; it is a consequence of the training objective and the routing mechanism.

- **Dense models** activate *all* parameters for every token. A 70B dense model reads all 70B weights (or close to it) for every token, because every layer's full hidden dimension participates in every attention and feed-forward computation. The parameter count on the model card is the inference cost count.
- **Mixture-of-Experts (MoE) models** route each token to a *fraction* of the total parameters. A MoE model may have 236B total parameters (an illustrative figure) distributed across eight experts, but only the top-2 (or top-1) experts are activated per token. The quoted total parameter

count includes the unused experts; the *active* parameter count per token is the fraction that routing selects.

The architect-relevant distinction: **total parameters ≠ active parameters per token.** This inequality is the single most important number to read from a model card when sizing a deployment, because it directly changes the compute cost per token. However, the KV cache does not share this privilege — we will show why MoE sparsity saves compute but not memory.

A note on provenance: the total-versus-active distinction arises from the training regime. In dense pre-training, every token sees the full model gradient; in MoE pre-training, a routing loss directs each token to the most relevant expert(s), and the unused experts receive no gradient for that step. The routing mechanism itself (top-k, importance sampling, learned gates) is an architectural decision that outlives training and becomes a deployment fact.

3.2. Mental Model

A model's parameters form a **resource pool** that is allocated differently depending on the routing regime.

- In a **dense** model, the pool is *fully allocated* every time. If the model is 70B params in FP16, we need 140 GB of weight memory available for every token. There is no "spending less" — the full 140 GB is the residency floor.
- In an **MoE** model, the pool is *fractionally allocated*. The total pool may be large (reflecting the model's capacity and training compute), but what we actually wire up per token is a slice. With top-2 routing from 8 experts, roughly 2/8 = 25% of the total parameter mass is active per token. This fraction saves compute (fewer FLOPs) but the attention layers still see every token, so the KV cache still grows with context length just as in a dense model.

The durable mental model: **total parameters set the ceiling; active parameters per token set the floor.** The architect must track both numbers.

3.3. Worked Example

We now carry concrete arithmetic using the canonical enterprise Q&A scenario (Ch 4, Table 4-2: ~2,000 users, ~10 rps average, ~40 rps peak, 1,200 + 8K context ~9.2K input, 300-token output, 70B-class model, FP16, 1 host 8×H100). The numbers below are worked out explicitly; where a model's exact spec is not first-party verified, it is flagged [UNRESOLVED].

3.3.1. Dense 70B model (canonical teaching model, [canonical scenario][ASSUMPTION])

The 70B dense full-MHA model below is a *constructed teaching reference* (the canonical scenario, Ch 4 Table 4-2), not a named vendor model — so its geometry is [canonical scenario][ASSUMPTION] and its arithmetic is [canonical scenario][DERIVED]. Reserve [1P] for a named, traceable first-party model specification.

Table 3-1 — Dense 70B model parameter arithmetic (worked example, not reference).

Metric	Value	Derivation
Total parameters	70B	canonical scenario (Ch 4, Table 4-2) [canonical scenario] [ASSUMPTION] reference model
FP16 residency (total)	140 GB	70B × 2 bytes = 140 GB [canonical scenario] [DERIVED]
Active parameters per token	70B	All parameters active for every token (dense) [canonical scenario] [DERIVED]
FLOPs per forward pass (approx.)	~0.14T	70B × 2 FLOP/param (multiply-add = 2 FLOPs, Ch 8) [canonical scenario] [DERIVED]

3.3.2. MoE model representative (Mixtral 8x7B class, [ILLUSTRATIVE][ASSUMPTION])

We contrast with a representative MoE model in the Mixtral lineage. The exact parameter split is not always published in vendor model cards; the numbers below are plausibility-checked and flagged.

Table 3-2 — MoE model parameter arithmetic (worked example, not reference). The active fraction for top-2-of-8 routing is ~25–30% of total, not single-digit. Note the contrast with the 2026 frontier models in Appendix A, where active fractions do fall to a few percent (Qwen 6B/125B, Kimi 104B/2.8T) because those use extreme expert sparsity plus shared/offloadable parameters.

Metric	Value	Derivation
Total parameters (across 8 experts)	~47B	~5.7B per expert × 8 ≈ 45.6B + always-on attention/shared + embeddings ≈ 47B (per-expert rounded to ~6B) [ILLUSTRATIVE] [DERIVED]
Active parameters per token (top-2 routing)	~14B	2 routed FFN experts + always-on attention/shared weights ≈ 14B (~30% of the ~47B total; ~25% counting expert-FFN mass alone) [ILLUSTRATIVE] [DERIVED]
Active/total fraction	~30%	14B ÷ 47B ≈ 29.8% (≈25–30% for top-2-from-8) [ILLUSTRATIVE] [DERIVED]
FP16 active weight-read per token	~28 GB	14B × 2 bytes = 28 GB read per token (compute/bandwidth; does NOT set residency) [ILLUSTRATIVE] [DERIVED]
FLOPs per forward pass (approx.)	~0.028T	14B active × 2 FLOP/param = 28B [ILLUSTRATIVE] [DERIVED]
Compute ratio vs dense 70B	~0.20× (~5× less)	(14B × 2) ÷ (70B × 2) = 28 GFLOP ÷ 140 GFLOP [ILLUSTRATIVE] [DERIVED]

3.3.3. Why MoE saves compute but not KV cache memory

The compute savings are straightforward: if only $n_a = 14$B of $n_t = 47$B total parameters are active per token, the FLOP count drops by the active fraction relative to a *same-size dense* model. But note the active fraction for top-2-of-8 routing is ~$14/47 \approx 30\%$, not single-digit — so the relative saving is about 5× versus the canonical 70B *dense* comparison, not 20× or 30×. Concretely,

$$\text{FLOP}_{\text{MoE/token}} = n_a \times 2 \text{ FLOP/param} = 14 \text{ B} \times 2 \approx 0.028 \text{ T}$$

which is $0.028/0.14 \approx 0.20\times$ of the dense 70B figure — roughly a **5× reduction** in compute per token. (It is also $14/47 \approx 30\%$ of a hypothetical dense model of the *same* 47B total; the 5× figure uses the book's canonical 70B dense as the comparison, so always state which baseline the ratio is against.)

The KV cache story is the surprising part. Recall from Chapter 1 (KV cache as a concept) that the KV cache stores one key and one value tensor per token, per layer. The cache size per token scales with the canonical Chapter 1 formula (the full-MHA case, where n_KV-heads × head_dim = hidden_dim; for a GQA/MQA model substitute n_KV-heads × head_dim), $KV_{\text{per-token}} = 2 \times n_{\text{layers}} \times d_{\text{hidden}} \times$ bytes-per-value. Critically, **the attention mechanism processes every token in the context densely** — each token's query attends to all previous tokens' keys and values, regardless of whether the model is dense or MoE. MoE sparsity operates in the feed-forward sub-layer; it does not change the attention sub-layer's behavior.

Therefore, for a 70B-class model (dense or MoE) with 8K–9.2K input context:

- **Dense 70B**: KV cache ~1.31 MB per token × 9,200 tokens ≈ 12.06 GB (at 8-bit, the raw tensor byte-halving figure = 1.31 MB/token, exactly 50% of BF16 — the block-overhead and '54%' ITL-slope caveats are stated once in Ch 1; see Ch 7) or ~24 GB (at FP16 precision for the key/value storage pattern discussed in Ch. 7).
- **MoE 70B-equivalent**: The KV cache is *identical* in size, because attention still processes all 9,200 tokens densely. The fact that only 14B of 47B total parameters are active in the feed-forward layers does not reduce the number of keys/values emitted by the attention layers.

In other words: MoE sparsity = compute sparsity (fewer FLOPs per token). MoE sparsity ≠ memory sparsity (KV cache still grows linearly with context length, same as dense). Only changing the attention mechanism itself (e.g., hybrid/linear attention, compressed latent attention, or KV offload) can stop the cache from growing. This distinction — compute-sparsity versus memory-sparsity — is one an architect has to get exactly right.

> **Key takeaway:** MoE provides **compute sparsity** (far fewer FLOPs per token because a fraction of experts is active), not automatic **weight-residency sparsity** — the full expert set normally remains resident unless it is explicitly offloaded or sharded in a way that changes residency. And the KV cache budget must be provisioned as if the

model were dense. Do not assume MoE reduces KV cache memory, and do not confuse active-compute savings with a residency saving. (This restates at the parameter level the sparsity lesson introduced conceptually in Ch 1 and developed arithmetically for the canonical model in Ch 7; each chapter teaches it at its own rung of the spine.)

Boxed rule — two distinct accounting lines. Keep two numbers separate and never blur them: 1. **total parameters → weight residency.** The resident weights (all experts, for MoE) are what the GPUs must hold. For a 70B dense model this is ~140 GB FP16; for a ~47B MoE this is ~94 GB (full expert set) unless experts are explicitly offloaded. 2. **active parameters/token → approximate compute per token.** The routed top-k fraction (e.g. ~14B active) sets the FLOPs per token (~28 GB of active weights read per token). This is not a memory-freeing lever unless offloading is in play.

3.4. Measurement

How do we determine the total-versus-active split for a model we haven't trained?

1. **Model card inspection.** Most model vendors publish the total parameter count. The active-per-token count is harder to find; it requires reading the architecture documentation for the routing mechanism (top-k, top-1, importance-based). If the model card says "70B parameters" without qualification, assume dense unless it explicitly describes an MoE layout.

2. **Runtime measurement.** For a given input, profile the number of FLOPs or the memory footprint of active weights. Tools such as `torch.profiler` can count active parameters, but this is an empirical measurement, not a first-party spec.

3. **Architecture diagram.** For MoE models, the number of experts × parameters-per-expert gives the total; the routing hyperparameter (top-k) × parameters-per-expert gives the active per token. This is a derived fact from the source code/release, not always on the model card.

Practical habit: When we encounter a model quoted in "X billion parameters," pause and ask: *is this total or active?* For dense models they are the same; for MoE models they diverge. Misreading this is the most common source of KV cache and compute underestimation.

3.5. Common Mistakes

- **Assuming total parameters = active parameters per token.** This is one of the costliest misreads. For a MoE model, the quoted "236B" or "47B" is the total across all experts; the active count per token is a fraction. Using the total count to size memory over-provisions weight memory (236B × 2 bytes reserves far more than the active footprint needs). The opposite error — sizing for active parameters while forgetting the KV cache is dense — under-provisions it.

- **Confusing compute sparsity with memory sparsity.** MoE reduces FLOPs per token because fewer parameters are active. It does *not* reduce the number of keys/values written to the KV cache. An architect who assumes MoE shrinks KV cache will be blindsided by memory pressure at long context lengths.
- **Using MoE as a free lunch for long-context workloads.** The compute savings from MoE are real, but the memory cost (weights + KV cache) must be provisioned at the total-parameter scale for weight residency and at the-full-context scale for KV cache. Neither benefit is "free" in the other domain.
- **Ignoring routing overhead.** Top-k routing itself requires computing routing scores (a softmax over expert assignments). This adds a small but non-zero compute cost that is sometimes omitted from published FLOP counts. It is usually negligible compared to the feed-forward arithmetic but should be acknowledged.

3.6. Architecture Consequence

Knowing whether a model is dense or MoE, and whether the quoted parameter count is total or active, directly changes three architectural decisions:

1. **Weight residency budget.** For a dense 70B model, provision 140 GB of FP16 weight memory per host. For an MoE model with ~47B total and ~14B active, distinguish two numbers: the **resident** budget (the full expert set, ~47B × 2 bytes ≈ 94 GB, unless experts are offloaded/swapped) and the **active per-token** footprint (~14B × 2 bytes ≈ 28 GB read per token). The active number governs compute; the resident number governs whether the weights stay on device. MoE therefore does not automatically lower the weight-residency floor — it only gives the *option* to offload inactives at the cost of bandwidth.
2. **KV cache provisioning.** Provision the KV cache as for a dense model of the same context length and hidden dimension. Do not apply a MoE sparsity factor to the KV cache. If we are running a 9.2K-token input on a 70B-class model (dense or MoE), the KV cache memory is the same order of magnitude — plan accordingly.
3. **Parallelism and routing strategy.** MoE deployment requires a routing strategy (e.g., expert placement, dispatcher, switchboard) and often expert parallelism across GPUs. This adds infrastructure complexity (cross-GPU communication for expert routing) that dense models do not have. The architectural choice between dense and MoE is therefore not just a parameter-count decision; it is a deployment-complexity decision.

3.6.1. The 2026 baseline shift: same framework, new constants

The 2026 trend signal (forward-looking; an interpretation of the sample we surveyed, not an established industry-wide convergence). By August 2026 the four frontier open-weight families surveyed for this edition share a notable pattern, and it is not more of the same dense scaling: extreme MoE sparsity (single-digit active-parameter fractions — Qwen 6B of 125B, Kimi K3 104B of 2.8T) coupled with **hybrid attention** (compressed/sparse/linear hybrids such as Gated DeltaNet + sparse attention) has become a common way to make long-context inference affordable. Appendix A documents these at full depth with first-party provenance; what matters here, in the model-understanding chapter, is that this is not a competing mechanism but the *same* dense-vs-MoE, total-vs-active, KV-vs-compute machinery this chapter just taught — with new constants. We hold that view explicitly as the **forward-looking direction** the architect should size toward, and flag it below as continuing future work (the frontier moves; this handbook is a living document, and Appendix A is where the moving part lives).

Why the trend signal should not be read as "dense is dead". This pattern among the four frontier families we surveyed describes the top of the market — the ~100B-and-up tier that anchor ~2.8T-parameter fleets. It is not a claim that dense models have disappeared. On the contrary, the smaller, denser tier is alive and actively shipping in 2026 for exactly the constrained-deployment reasons this chapter teaches: **Qwen3.8-27B** ([1P][FACT], source: HF Qwen/Qwen3.8-27B) is a dense 27.8B model whose 4-bit weights fit on a single 24 GB consumer GPU, and **Muse Glimmer 30B** ([1P][FACT], source: Meta via vLLM-Recipes) is a dense 29.6B local-agentic model that runs in ~18 GB. These exist because the dense-vs-MoE trade is itself a *deployment* decision, not a date: MoE buys active-parameter efficiency at the cost of total-parameter memory and routing complexity — worthwhile when serving many requests from a large pool of resident weights, but hard to justify when the whole budget is one consumer GPU whose total weights already overrun. That is precisely why this book keeps its canonical on the dense tier: the canonical must serve the architect whose *whole fleet* is a handful of boxes, not only the one sizing a 2.8T datacenter model. The framework does not change between tiers — total vs active, KV per-token, and residency budgeting apply identically to a 27B dense laptop model and a 125B/6B MoE fleet model.

Why the rest of this chapter's canonical stays a dense full-MHA model. If the trend is MoE + hybrid, why does this book's canonical still size a dense 70B full-MHA workload? Because a dense model with full multi-head attention gives the cleanest single-constant KV formula (`2 × layers × hidden × bytes`) and the largest KV footprint — the conservative worst case an architect should always size against first. Teaching against that bound means the reader learns the framework on the hardest memory case and then relaxes it. It is a deliberate teaching simplification, not a claim that in 2026 an enterprise RAG fleet really runs on dense 70B.

One verified 2026 transfer: Qwen3.8-Flash-Next. The model card [1P][FACT] (source: HF Qwen/Qwen3.8-Flash-Next) is the Qwen4-architecture preview: **125B total / 6B active** (plus a separate 51B of offloadable N-gram embedding parameters), **512 MoE experts** (10 routed + 1 shared

per token), and **hybrid attention** — Gated DeltaNet (GDN) on three of every four layers plus Qwen Sparse Attention (QSA) on the fourth. This is exactly the "125B/6B active MoE + Gated DeltaNet/QSA" class of model a 2026 architect actually considers. Stepping through this book's own arithmetic:

- **Weight residency** (Ch. 7's floor): the active-weight working set for Qwen is ~6×10^9 params × 2 bytes/param = ~12 GB read per token, not the canonical 140 GB — MoE sparsity reduced the per-token weight traffic by ~12×. But this is a *compute/bandwidth* statement, not a residency one: the total weights dominate the memory ceiling, ~125×10^9 params × 2 bytes/param ≈ 250 GB (plus the offloadable N-gram). So the *total-vs-active* split of this chapter is not a footnote — it is the difference between fitting on one host and sharding across several, and the ~250 GB total (not the ~12 GB active working set) is what must be resident unless experts are explicitly offloaded.
- **KV cache** (Ch. 7/8): the canonical `2 × layers × hidden × bytes` KV formula is the full-MHA bound. Qwen's hybrid attention attacks the KV constant itself at the mechanism level — GDN keeps a fixed-size recurrent state (context cost no longer grows linearly per token across those layers) and QSA attends sparsely at micro-block granularity — so per-token KV no longer follows the dense formula. The framework question ("does it fit?") is unchanged; the *function* plugged in for KV is not the dense one.
- **Compute** (Ch. 8): active-parameter FLOPs drop to ~2 ×6B per token, but the QSA/GDN layers ride different roofline points than a dense 70B prefill/decode split, so the throttled-resource conclusion must be re-derived per model (Ch. 8's measurement discipline, not a one-time number).

The architect's move is unchanged. For the canonical dense model this book sizes memory, compute, and fleet with one clean constant set. For a 2026 MoE/hybrid model the architect does the *same* decision loop — read the model card, get total vs active, get the KV scheme's per-token function, size residency and roofline, then decide parallelism (Ch. 10) and serving (Ch. 11). Only the constants differ; the framework does not. Appendix A walks the four frontier models through exactly this re-derivation and flags which vendor numbers still carry a verify-on-own-hardware caveat.

> **Recorded as future work.** This forward-looking view is intentionally a *pointer*, not the full treatment — the complete, current analysis of the 2026 frontier lives in Appendix A. Because the frontier moves quickly and every vendor figure in it carries a verify-on-own-hardware caveat, we treat the trend as a living section to be updated against new model cards, rather than a set of frozen gospel numbers. An architect should re-check Appendix A before any capacity decision — the constants, not the framework, are what change.

3.7. What We Still Don't Know

As of 2026-08, several questions remain open and are flagged [UNRESOLVED]:

- **Exact active-fraction per token for commercial MoE models.** Model cards rarely publish the precise top-k routing distribution under real workloads. We know the architectural top-k (e.g., top-2 from 8 experts), but the actual fraction of active parameters may vary with prompt content, token position, and expert availability.
- **Whether router latency offsets MoE compute savings.** The cost of computing routing scores and dispatching to experts is not always included in published FLOP counts. On some hardware the routing overhead can be significant enough to narrow the compute gap between MoE and dense.
- **KV cache behavior under MoE with expert swapping.** When experts do not fit on a single GPU and must be swapped (offloaded), does the KV cache interact with the swapping mechanism in ways that change its effective size or access pattern? This has not been systematically characterized.

These flags exist because home-lab measurements are not reference per the evidence taxonomy; each is an open empirical question a team should validate against its own target workload, not a claim the handbook has settled.

3.8. End-of-Chapter Mini-Case: Total vs. Active Parameters, and the KV Constant

(Continuous scenario — chained from the enterprise Q&A thread.)

An architect is fleshing out the design of the internal Q&A tool described in Chapter 1's mini-case. The team's standing decision from Chapter 2 is the dense 70B model; a MoE model with 8 experts (roughly 47B total params, ~14B active per token) is the challenger under consideration. They ask: "If we go MoE, can we cut our GPU memory budget?"

From the model-understanding chapter, the architect can answer: Active-compute memory yes — only ~14B of the ~47B total is active per token, so ~28 GB of *active* weight footprint is read per token vs. 140 GB for a dense 70B. But *resident* memory is a different question. An MoE model normally keeps its **full expert set resident** — the non-active experts still occupy HBM unless we explicitly use expert offload/swapping (Ch 3 §3.6, Ch. 18), which itself costs bandwidth. So MoE reduces compute per token, and it gives us the *option* to offload some experts to shrink residency, but it does **not** automatically reduce the weight-residency floor. And KV cache memory no — the attention layers still process every token densely, so the cache budget for a 9.2K-context input is the same regardless of whether the model is dense or MoE. We still need to provision for ~12 GB of KV cache (at 8-bit) or ~24 GB (at the precision pattern discussed in Ch. 7) per request, and we'll also need expert-routing infrastructure on top of that.

The architect's decision therefore hinges on whether the compute savings from MoE (fewer FLOPs per token, potentially lower $/token) outweigh the added routing complexity and the fact

that KV cache memory is unchanged. On that accounting the MoE challenger fails: it does not cut the memory budget the team asked about, and it would add routing infrastructure — including a GPU dedicated to the routing dispatcher [ILLUSTRATIVE][ASSUMPTION], not a vendor-published requirement — on top. The team therefore keeps the Chapter 2 decision, the dense 70B model, and provisions the KV cache budget at the dense-model rate.

Table 3-3 — Parameter and KV cache arithmetic: dense 70B vs MoE (8×7B class)

metric	dense 70B	MoE (8×7B class)	derivation
total parameters	70B	~47B	[ILLUSTRATIVE] [ASSUMPTION] expert split
active params per token	70B	~14B	top-2 from 8 ≈ 2/8 = 25% of expert mass [ILLUSTRATIVE] [DERIVED]
active/total fraction	100%	~30%	14B ÷ 47B ≈ 29.8% [ILLUSTRATIVE] [DERIVED]
FP16 residency (total)	140 GB	~94 GB	70B × 2 / 47B × 2
FP16 weight-read per token	140 GB	~28 GB	70B × 2 / 14B × 2 (read per token, not residency)
KV cache per request (9.2K ctx, 8-bit)	~12 GB	~12 GB	identical — attention dense
FLOPs per forward pass	~0.14T	~0.028T	70B × 2 / 14B × 2
compute ratio vs dense 70B	1×	~0.20× (~5× less)	(14B × 2) ÷ (70B × 2) = 28B ÷ 140B [ILLUSTRATIVE] [DERIVED]

All figures trace to the canonical scenario (Ch 4, Table 4-2); the MoE column is an [ILLUSTRATIVE] [ASSUMPTION] worked variant, not a measurement claim.




FIGURE 3.1: Dense vs MoE parameter allocation and KV cache behavior. Controlled comparison: same attention geometry, same context and cache dtype — so the KV footprint is identical — while weight residency (140 GB dense vs ~94 GB for the ~47B MoE challenger) and the active-compute fraction (~100% vs ~30%) both differ. Schematic, not to scale. An MoE model that also uses GQA or a different attention mechanism is a different comparison (Ch. 7).

Parameter-activation contrast. A dense 70B activates all 70B parameters per token (residency ≈ 140 GB, KV grows linearly with context). An 8-expert MoE still stores its full expert set as resident weights (not shown to scale), but only the top-2 (~14B) are active per token (active compute footprint ≈ 28 GB). KV cache growth with context is identical to dense — attention still processes every token.

Next chapter: Chapter 4 — The Anatomy of an AI Workload, which characterizes the enterprise Q&A RAG workload across the six dimensions (quality, traffic, token profile, latency, economic, operational constraints) and uses the same continuous mini-case scenario.

Canonical scenario citation: all numerical values in this chapter that trace to the canonical enterprise Q&A RAG workload are drawn from the fixed reference set in Ch 4 (Table 4-2). The dense 70B numbers carry [canonical scenario] provenance with the per-row [ASSUMPTION]/[DERIVED] split; MoE numbers carry [ILLUSTRATIVE] provenance with the same split — plausibility-checked variants.

PART II.

The Workload

CHAPTER 4.

The Anatomy of an AI Workload

The Architect's Question

After this chapter we should be able to take a vague deployment ask — "thousands of employees asking questions over internal documents" — and turn it into a *measurable workload* across six concrete dimensions. We will trace the arithmetic from user concurrency through traffic, token profile, latency, economics, and operational constraints, ending with a workload characterization that directly enables system architecture decisions. After this chapter, the question "which model should we choose?" can be answered with numbers, not intuition.

4.1. Concept

4.1.1. The Six-Dimension Workload-Characterization Framework

A workload is defined by six orthogonal dimensions (Table 4-1 applies the framework to the canonical workload). Together they form a complete specification that — taken alone — determines model selection, system architecture, and economic feasibility. No single dimension is sufficient; the architect must characterize all six before committing to a design.

1. **Quality** — the fidelity, accuracy, and capability the workload demands of the model. Includes reasoning depth, tool-use requirements, modality (text-only, multimodal, etc.), and any accuracy thresholds (e.g. >85% factual accuracy on internal Q&A). Quality is the *goal*; the other dimensions are the *constraints* within which quality must be delivered.

2. **Traffic** — the request rate the system must sustain, expressed in requests per second (rps) or queries per second, plus concurrency levels and burstiness. Traffic determines the compute

and memory bandwidth required to keep the serving pipeline saturated without excessive queuing.

3. **Token profile** — the distribution of input length, output length, and context length per request. This is the workload's "shape" in token space: how many tokens arrive in the prompt, how many the model generates, and whether the prompt is dense (long context) or sparse. The token profile is the primary driver of memory (KV cache) and prefill cost.

4. **Latency** — the time budget for different stages of request processing. Typically split into *time-to-first-token* (TTFT), which encompasses retrieval and prefill, and *time-per-output-token* (TPOT), which governs decode length. Latency budgets feed directly into SLOs and serve as the key differentiator between serving configurations (e.g. continuous batching vs. discrete batching).

5. **Economic constraints** — the cost budget denominated in tokens per dollar, dollars per million tokens, or cost per request. This dimension translates traffic and token profile into a recurring cost line, and it determines whether a given infrastructure choice (single node vs. multi-node, FP16 vs. FP8) is affordable at scale.

6. **Operational constraints** — availability, privacy, locality, and update frequency. Multi-region deployment for fault tolerance. Data-privacy requirements that force on-prem or VPC-local embedding models. Update frequency that dictates how often embeddings or model weights must be refreshed. These constraints often interact with traffic and economics to force architectural compromises.

The framework is deliberately dimensional: a workload that is "high-quality, high-traffic, long-context, low-latency, cost-sensitive, private" is fundamentally different from "low-quality, low-traffic, short-context, high-latency, cost-abundant, public," even if the raw text looks the same. The framework prevents the architect from optimizing one dimension at the expense of others — a common failure mode.

4.2. Mental Model

The six dimensions are best read as the axes of a six-dimensional space in which every AI workload resides. A workload's position in this space is its *fingerprint*. When an architect says "we need a model for enterprise Q&A," that is only a descriptor of the quality dimension. To make the statement actionable, we must project the workload onto all six axes: *what quality level, how much traffic, what token profile, what latency SLO, what economic ceiling, what operational constraints?* The intersection of these projections is the workload point that drives every downstream decision — model selection, infrastructure sizing, serving configuration, and TCO.

The mental model is not a checklist; it is a *lens*. Looking through it, the architect sees which dimensions are tight (binding) and which are loose (permissive). Tight dimensions become the design drivers; loose dimensions offer optimization freedom. The goal is to identify the binding constraints so that resources are allocated where they matter most.

4.3. Worked Example

4.3.1. Characterizing the Canonical Enterprise-Q&A RAG Workload

RAG is retrieval-augmented generation: the system retrieves relevant passages from a document store and prepends them to the user's question as context, so the model answers from evidence rather than memory. The canonical workload below is the book's running example of such a system (the Preface defines the term; this is where it becomes a quantified workload).

We now apply the six-dimension framework to the **canonical enterprise-Q&A RAG workload** used throughout this handbook. The canonical numbers are the fixed reference set for Part II; all arithmetic in this chapter traces to them. Table 4-1 states the six-dimension characterization; Table 4-2 gives each value's provenance.

Table 4-1 — Six-dimension workload characterization for the canonical RAG workload

Dimension	Characteristic	Derivation / Source
Quality	Factual accuracy >85% on enterprise Q&A; reasoning via retrieval; no tool use beyond search API	[canonical scenario][ASSUMPTION] author-chosen target, set with reference to enterprise retrieval-Q&A benchmark suites (e.g. HotpotQA-style)
Traffic	~10 rps average; peaks ~40 rps	[canonical scenario][ASSUMPTION] declared traffic inputs (~2,000 registered users × one request ~every 200 s ≈ 10 rps; peak scaled) — declared, not derived from the user population (walk-through in §4.3); L_exec = λ × W_exec ≈ 86 (~344 at 40 rps) is a separate derived quantity.
Token profile	Input: ~1,200 prompt + ~8,000 retrieved context ≈ 9,200 tokens; Output: ~300 tokens; total ≈ 9,500 tokens/request	[canonical scenario][ASSUMPTION] canonical workload input (Ch 4, Table 4-2); verify the tokenizer split against the chosen model before budgeting

Dimension	Characteristic	Derivation / Source
Latency	TTFT budget 1.2 s (retrieval ~120 ms + prefill ~1.08 s); TPOT budget ~25 ms/token; p95 TTFT ≤ 2 s, p95 TPOT ≤ 35 ms	[canonical scenario][ASSUMPTION] author-chosen user-experience SLO targets; the retrieval-latency contribution (vector DB, same-region) is an assumed estimate (see derivation note beneath the table)
Economic constraints	~$1.20 per 1M input tokens, ~$2.00 per 1M output tokens (mid-tier managed-API list price, 2026); infrastructure cost ≈ $20/hour for an 8×H100 host ($2.50/GPU-hr on-demand); at the ~5-host average the whole-fleet spend is ~$100/hour, giving **~3.3M input and ~108K output tokens per cloud dollar**	**illustrative 2026 cloud-price input** ($2.50/H100-GPU-hour, [canonical scenario][ASSUMPTION], not a market fact) ⟶ $20/hr per 8-GPU node; $/1M and tokens-per-dollar values derived on the whole-fleet basis (rationale: derivation note beneath the table; §4.3, Ch 8/16–17)
Operational constraints	Multi-region deployment (active-active for availability); embeddings refreshed daily from document store; privacy-sensitive documents force on-prem or VPC-local retrieval; 99.9% availability service-level agreement (SLA)	[canonical scenario][ASSUMPTION] author-chosen availability/operational requirement (99.9% SLA, multi-region active-active, daily embedding refresh), informed by typical enterprise IT policy — an input target, not a derived result. The multi-region active-active (99.9%) topology is UNPRICED / NOT VALIDATED in this book's TCO/fleet arithmetic (Ch 16–17 price single-region N–1) — see the canonical-box availability-topology note.

(Table-level provenance — applies to every row unless a row overrides inline. The convention: an input or parameter assumption (traffic, latency target, price, token count) is [canonical scenario][ASSUMPTION]; a value arithmetically derived from those assumed inputs (an occupancy, a tokens-per-second rate, a cost-per-request, a tokens-per-dollar figure) is [canonical scenario][DERIVED]; a vendor hardware constant is [1P][FACT]; an externally benchmarked norm used to set a target is [2°]; a non-canonical hypothetical worked example would carry [ILLUSTRATIVE] instead of [canonical scenario] and use the same ASSUMPTION/DERIVED split. All values here are canonical-scenario inputs and targets for this worked example, so they carry [canonical scenario]; the "not a measured result — validate against the actual stack (Ch 14)" caveat holds for them all and is stated here once, not per row. The only inline overrides are ***[1P] vendor hardware constants*** *(Table 4-2) and* ***[2°] externally benchmarked norms*** *used to set a target. Values computed from the assumption inputs (e.g. the* $_{10}/_{40}$ *rps traffic) are [canonical scenario][DERIVED].)*

(Derivation notes for Table 4-1 — the rationale behind the compact cells above. ***Economic:*** *a tokens-per-dollar figure is capacity-consistent only if its dollar denominator is the whole fleet's spend and its rate is the whole workload's offered rate — dividing the offered rate by one host's $20/hr would falsely imply a single host delivers it (one host's sustained-planning prefill rate is only ~19,800 tok/s at 35% MFU — a planning rate, not a ceiling — giving ~3.56M prefill tokens per host-dollar, a different quantity; see §4.3 and Ch 8/16–17). The $1.20/$2.00 is a* mid-tier* managed-API list price; the *frontier-class* API price used in the Ch 16 TCO comparison is higher (~$2/$8 per 1M) — see the §4.3 token-pricing bullet for the tier distinction. **Latency:** the retrieval-latency contribution (vector DB, same-region deployment) is an assumed estimate, not a measured figure. **Traffic:** the $_{10}/_{40}$ rps are declared scenario inputs; the full walk-through is §4.3.)*

Canonical Workload — the single reference set. This box is the one authoritative set of numbers every chapter disciplines on. When a chapter states a workload parameter, it comes from here and nowhere else. The derived values (requests/s, tokens/s) are this box's arithmetic, recomputed in the chapter that needs them.

Field	Value
Employees / registered users	~2,000
Concurrent users (typical)	~100 active users (5% of 2,000) — *population measure, NOT synonymous with in-flight inference requests; execution occupancy is derived separately below*

Field	Value
Concurrent users (peak)	~400 (20% of 2,000) — *peak activity fraction, the same 4× scaling as the 10⟶40 rps peak [canonical scenario] [ASSUMPTION]*
Mean request service time (planning)	~10 s *[canonical scenario] [ASSUMPTION] — planning round: retrieval ~120ms + prefill ~1.08s + decode ~7.5s rounded to a comfortable planning figure; this is the stable-flow Little's Law dwell time, a modelling quantity, NOT a measured p95/p99 — a planning fiction*, and the derived execution time W_exec ≈ 8.6 s (prefill + decode) used for occupancy/sizing
Average arrival rate	~10 rps *[canonical scenario] [ASSUMPTION] declared traffic input (2,000 users × one request ~every 200 s ≈ 10 rps) — declared, not derived (walk-through in §4.3).* **Time basis:** this is the rate over the **active business-hours window** (an 8-hour × 260-workday schedule), not 24×7 wall-clock. Over 24×7 the same 10 rps would extrapolate to ~25.9M requests/month, or ~12,960 requests/user/month for 2,000 users — an implausible all-day activity level for an internal enterprise document-Q&A tool. So read 10 rps as an **intentionally stress-oriented busy-period average** (a capacity ceiling to design against), and price request-volume economics from the active-hours schedule rather than from raw wall-clock multiplication.

Field	Value
Peak arrival rate	~40 rps *[canonical scenario] [ASSUMPTION] — the same busy-period behavior scaled to the burst/traffic spike; a scenario input, not a measured arrival rate*
Execution occupancy	~86 requests at 10 rps (W_exec ≈ 8.6 s); ~344 at 40 rps — *[canonical scenario] [DERIVED] via Little's Law L_exec = λ × W_exec, a separate occupancy, NOT the 100 active-user population*
Prompt / query	1,200 tokens
Retrieved context	8,000 tokens
Total input	9,200 tokens
Output	300 tokens
Model baseline	Dense 70B
Weight precision	FP16 (2 B/param ⟶ ~140 GB)
KV precision	FP16 (2.62 MB/token ⟶ ~24.1 GB @ 9.2K)
TTFT SLO	1.2 s (retrieval ~120 ms + prefill ~1.08 s); p95 ≤ 2 s
TPOT SLO	25 ms/token; p95 ≤ 35 ms
Hardware	8×H100 (80 GB each, 640 GB)
Compute price	$2.50/GPU-hr (illustrative 2026 input) ⟶ ~$20/hr per 8×H100 host
Availability	99.9%

Field	Value
Monthly budget	~$15,000 (illustrative *per-host* ceiling: one 8×H100 host at ~$20/hr × 730 hr ≈ $14.6K/mo. Note this is a **single host**, not the whole workload — meeting the canonical ~10 rps average / ~40 rps peak needs ~5–20 hosts, so the workload's real monthly spend is ~$73K–$292K/mo (5 hosts at idle up to 20 hosts at full saturation; $14.6K/host/mo — Ch 16/17); the budget box is a per-host ceiling, not the workload ceiling)

The two derived rates most chapters cite: at 10 rps the input demand is ~92,000 tokens/s (9,200 × 10) and output ~3,000 tokens/s (300 × 10); at 40 rps peak the input demand is ~368,000 tokens/s (9,200 × 40). These come from this box, not from a chapter re-deriving the mix differently.

Availability topology — UNPRICED / NOT VALIDATED in the canonical cost arithmetic. The canonical workload's operational constraint and SLA (this box: `Multi-region deployment (active-active)`, `99.9% availability`) state the *requirement*; the follow-on TCO and fleet arithmetic in Ch 16–17 prices a **single-region** deployment with **N–1 single-host failover**, **not** multi-region active-active. These are **different provisioning problems**: multi-region active-active requires cross-region capacity duplication, region-failure tolerance, data locality and traffic routing, and consistent state/data replication across regions — none of which is priced or validated anywhere in this book's cost arithmetic. The canonical cost figures (Ch 16 `$/1K req`, Ch 17 host counts) therefore **understate the cost of the canonical workload's own stated 99.9% availability requirement**. Treat the TCO/fleet totals as *single-region, N–1-only* numbers, and add a separate multi-region capacity + replication cost line before the availability SLA can be considered met.

Throughout this book the SI convention applies: K = 1,000 and M = 1,000,000 for token counts. 9.2K tokens therefore means 9,200 tokens, and 32K means 32,000. This matches the 2.62 MB/token figure, the KV residency totals (24.1 GB at 9,200 tokens; 83.9 GB at 32K), and the 128K figure (128,000 tokens ⟶ 335.5 GB).

Table 4-2 — Canonical-scenario provenance ledger (which value is assumed, derived, or factual)

Every quantity below is either an assumed workload input, a vendor fact, a modeled result, or a dated price snapshot. This is the authority for which is which; chapters refer back to it rather than restating provenance each time.

Assumption-change log (how the canonical case evolves). Table 4-2 pins the *given* (assumed workload inputs) and the *derived* (modeled results) for the canonical scenario. As the book proceeds, each chapter adds *hypothesized* results (a candidate architecture or a lever, tagged [HYPOTHESIS] or [ILLUSTRATIVE]) and *validated* results (a benchmark or measurement that confirms or rejects a hypothesis, tagged [LAB] or [2°]). The four states — given → derived → hypothesized → validated — are the assumption-change log: a reader can always tell whether an 8×H100 host is an assumed baseline, a derived lower bound, a hypothesized candidate, or a validated deployment, because the status tag and the chapter that introduced it are both visible. The Architecture Decision Record (ADR, Ch. 25) is where a hypothesis becomes a validated, owned decision; the evidence tags (Preface) are the per-claim record of which state each number is in.

CANONICAL TEACHING MODEL — deliberately conservative full-MHA baseline. The 70B dense **full-MHA** model (every query attends to every key) is a *teaching/reference* model, not a representative 2026 production 70B architecture. Modern production serving candidates use GQA/MQA and sparse attention, which shrink the KV constant several-fold (Ch 7); the ~2.62 MB/token figure is an upper bound for pedagogical clarity, and the frontier appendix (Appendix A) is the deliberate relaxation — not a correction — of this deliberately pessimistic baseline. Treating it as a property of *70B models in general* understates 2026 production KV efficiency.

Quantity	Value	Status
Registered users	2,000	[canonical scenario] [ASSUMPTION] workload context
Active fraction	5% (~100 active users)	[canonical scenario] [ASSUMPTION] population measure, NOT in-flight request count

Quantity	Value	Status
Average / peak traffic	10 rps / 40 rps	[canonical scenario] [ASSUMPTION] declared traffic inputs (2,000 users × ~1 request/200 s ≈ 10 rps; peak scaled) — declared, not derived (walk-through in §4.3)
Execution occupancy	~86 / ~344 requests (at W_exec ≈ 8.6 s)	[canonical scenario] [DERIVED] Little's Law L = λ × W_exec; a separate occupancy from the active-user population
Input tokens	9,200 (1,200 prompt + 8,000 retrieved)	[canonical scenario] [ASSUMPTION]
Output tokens	300	[canonical scenario] [ASSUMPTION]
Model parameters	70B	[canonical scenario] [ASSUMPTION] reference model
Attention architecture	full-MHA reference model (K/V width = hidden_dim)	[canonical scenario] [ASSUMPTION] (a real 70B may use GQA, ~8x less KV; Ch 7)
KV per token (FP16, MHA)	2.62 MB	[canonical scenario] [DERIVED] from the general KV formula at the canonical 80-layer, hidden-8192 full-MHA teaching geometry (2×80×8192×2 B); the geometry is a constructed reference, not a named vendor model

Quantity	Value	Status
KV per token (FP8, raw byte-halving)	1.31 MB	[canonical scenario] [DERIVED] (exactly 50% of BF16; block/metadata overhead not vendor-measured — fill via deployment benchmark)
H100 HBM per GPU	80 GB	[1P][FACT] vendor
H100 BF16 peak (dense, no sparsity)	~0.989 PFLOPS	[1P][FACT] vendor
Retrieval latency	120 ms	[canonical scenario] [ASSUMPTION]
Prefill latency (TTFT)	1.08 s	[canonical scenario] [DERIVED] from the chosen TTFT budget (1.2 s) minus the assumed retrieval latency (120 ms)
Decode (TPOT)	25 ms/token	[canonical scenario] [ASSUMPTION] author-chosen per-token decode budget
Host price (8×H100, on-demand)	~$20/hr	[canonical scenario] [ASSUMPTION] dated price snapshot (2026 on-demand $2.50/GPU-hr × 8; not [1P] vendor spec, not a measured figure)

(Table-level provenance for Table 4-2 — the one convention this chapter and the book uses. An input or parameter assumption (traffic, latency target, price, token count) is [canonical scenario][ASSUMPTION]; a value arithmetically derived from those assumed inputs (an occupancy, a tokens-per-second rate, a cost-per-request, a tokens-per-dollar figure) is [canonical scenario][DERIVED]; a vendor hardware constant is [1P][FACT]; a genuinely external norm is [2°]. [canonical scenario] denotes the book's own fixed reference set (Ch 4, Table 4-2) and is distinct from [ILLUSTRATIVE], which is reserved for a non-canonical hypothetical worked example and uses the same ASSUMPTION/DERIVED split. The

traffic/latency values are modeled scenario quantities, not measurements on a deployed system — that caveat is stated here, not repeated per row.)

Arithmetic Walk-Through: From Users to Requests per Second

The step from "~2,000 registered users" to "~10 rps average" is the key connective tissue that makes the continuous scenario concrete. Here is the full derivation, traceable line by line:

1. **Concurrency**: a fraction f of the N registered users are active at any moment. With $f = 0.05$ and $N = 2{,}000$:

$$C = f \cdot N = 0.05 \times 2{,}000 = 100 \text{ concurrent users}$$

2. **Request completion time** (service time W): the average end-to-end time from request submission to answer delivery. We deliberately keep TWO named values, and the distinction matters: a **planning round number of ~10 s** (retrieval ~120 ms + prefill ~1.08 s + decode ~7.5 s, rounded up to a comfortable planning figure) versus the **derived model-execution service time of ~8.6 s** (prefill 1.08 s + decode 7.5 s, without the retrieval/plumbing term) that the later fleet chapters use in Little's-law sizing. The two differ by the retrieval/pipeline room and by rounding; they are not a numerical contradiction. Whichever we use, we must use it consistently — the canonical ledger pins the fleet-sizing service time at ~8.6 s (Chapter 8), and the ~10 s figure is the coarser planning-round headline.

3. **Arrival rate — a declared traffic assumption, NOT a Little's-law derivation from the active-user population**: Little's Law, $L = \lambda W$, relates the average number of *requests in the defined system* L, the arrival rate λ, and the mean time in system W. It cannot be applied to a count of *active people* — 100 recently-active users is not the same as 100 requests in the serving system. So the ~10 rps average is **declared as a scenario input** (≈ 2,000 registered users × one request ~every 200 s ⟶ ~10 rps), not solved for from the 100-user population.

4. **Peak arrival rate**: ~40 rps is the same behavior scaled to a burst/traffic spike — again a declared scenario input (see step 3).

The walk-through makes the *distinctions* explicit: the **~100 active users** are a population/activity measure, not a request-occupancy count; the **~10 rps average / ~40 rps peak** are declared traffic assumptions (scenario inputs), not derived from the user count; the **~86 / ~344 execution occupancy** is derived from those arrival rates via Little's Law (L = λ × W_exec, W_exec ≈ 8.6 s). The point of the exercise is to keep population, arrival rate, and occupancy separate, not to claim that a registered-user count empirically determines an arrival rate. Change any one assumption and the others shift accordingly; the architect recomputes them when the requirement changes. If the architect starts

from a measured 10 rps instead, the relation runs the other way (it yields ~86 in-flight at W ≈ 8.6 s, not a user count).

Before moving on, it is worth naming the four distinct quantities so they are not collapsed: **registered users** are the population; **concurrent users** are the activity state (those in flight at a moment); **arrival rate** (λ) is requests per unit time; and **service time** (W) is the end-to-end duration of a request. They are related by Little's Law, L = λW, but the architect must *estimate or measure* concurrency, arrival rate, and service time — none is a fixed property of the workload. Two further separations matter for KV planning and are easy to collapse, so we hold them apart here too:

"Concurrent users" here means *active users*, not simultaneous in-flight inference requests. The 5% figure gives ~100 active users in the modeled activity window — people who are using the tool over the window — not 100 requests that are all mid-execution at the same instant. The in-flight *request* concurrency is a different quantity, computed from Little's Law with the derived service time W ≈ 8.6 s. The two operating points are distinct rows, not one figure reconciled by an unstated multiplier:

Operating point	Active users (population)	Arrival rate λ	In-flight requests (λ·W, W≈8.6 s)
Average	100 (5% × 2,000)	~10 rps	~86
Peak	400 (20% × 2,000)	~40 rps	~344

The reason these columns differ in kind is that **active-user population** and **request occupancy** are different state variables. Active users is a *population* measure — how many people engaged the tool over the modeled window. Request occupancy is an *instantaneous* Little's-law quantity — how many requests are resident in the serving system at a moment. They are related only through the arrival rate and service time, not through a per-user request multiplicity. So at the average operating point the population (~100) and the occupancy (~86) happen to be close, while at the peak they differ (400 vs 344); neither gap needs a "one user issues several requests" reconciliation, and we do not claim one. Whenever the book says "concurrent users," read "active users in the modeled activity window"; whenever it needs the request-level occupancy that a host's KV budget must absorb, use the Little's-law λ·W figure for that specific operating point.

The ~40 rps peak is assumed sustained over the provisioning burst interval — long enough for Little's Law and service-time occupancy to reach the modeled steady state (seconds of sustained 40 rps), not a one-request 40-rps spike. A one-second spike would not populate the queue to λ·W; the fleet sizing deliberately treats 40 rps as the sustained burst the system must absorb. A load generator reproducing this workload should emit the same sustained arrival process, not merely target the same average rps.

- **Concurrent *users* ≠ concurrent *requests*.** "100 concurrent users" is a statement about the

population's activity, not about how many requests are in flight at the scheduler at any instant. The two are different state variables, and they need not be close — at the average operating point they happen to be (~100 vs ~86), at the peak they differ (~400 vs ~344).

- **Requests *in flight* ≠ KV-resident sequences.** A request in the queue, or one whose prefill is not yet admitted, is "in flight" from the user's perspective but does not yet hold a KV slot. In-flight concurrency upper-bounds the KV-concurrency the system must serve, but the KV budget is sized by the number of *resident active sequences* — which is what the concurrency ceilings in Ch 17 count. Little's Law gives the in-flight number; the KV budget is a separate, residency-side quantity obtained by multiplying the resident sequence count by per-token KV. Keeping these three apart (in flight vs resident vs per-token KV) is what prevents the "100 users ⟶ 100 KV slots" leap.

The "5% active" and "10 s duration" are deliberately simple scenario assumptions ([canonical scenario][ASSUMPTION]), not externally verified facts; in a real engagement the architect replaces them with observed concurrency, measured latency, and a burst profile from telemetry. Getting this separation right is what turns traffic modeling from a guess into a reproducible arithmetic.

Token Profile in Detail

The canonical workload's token profile is input-heavy, which has direct consequences for system design:

- **Per-request input**: 1,200 tokens (enterprise query, possibly reformulated) + 8,000 tokens (retrieved context from vector DB) ≈ 9,200 tokens. The [canonical scenario][ASSUMPTION] provenance traces to the canonical scenario (Ch 4, Table 4-2).
- **Per-request output**: ~300 tokens (the generated answer, possibly with citations).
- **Input-to-output ratio**: 9,200 ÷ 300 ≈ 30× more input tokens than output tokens. This ratio is [canonical scenario][DERIVED] from the canonical numbers and is the single biggest factor in why this workload is KV-capacity- and prefill-dominated rather than decode-throughput-limited.
- **At 10 rps**: input tokens/s = 9,200 ×10 = 92,000 tokens/s; output tokens/s = 300 ×10 = 3,000 tokens/s. At peak 40 rps, input spikes to ~368,000 tokens/s and output to ~12,000 tokens/s. These [canonical scenario][DERIVED] numbers are the Canonical Workload box's derived rates (above).

The input-heavy profile means that *prefill* (processing the prompt) dominates the **prefill throughput and KV-memory demand**; under the canonical timing assumptions it is **not** the dominant wall-clock component of an individual request. Prefill takes about 1.08 s, while generating the 300-token answer takes about 7.5 s (300 × 25 ms/TPOT) — so decode is the dominant per-request wall-clock component (~87% of the ~8.58 s total). A model that processes 8K tokens of context in under 1 s of prefill is important to keep the prefill leg within the 1.2 s TTFT budget, but it does

not make prefill the latency bottleneck; that distinction is a resource-regime statement (prefill is compute-bound, decode is bandwidth-bound), not a wall-clock latency ranking. Architecture choices must be based on phase-specific demand, measured utilization, and SLO-goodput, rather than the input/output token ratio alone. This is why the token profile is the primary architectural driver for this workload.

Latency from SLO

The latency dimension is specified through Service Level Objectives, which translate user-experience goals into concrete time budgets:

- **TTFT (time-to-first-token)**: budget of 1.2 s, comprising retrieval (~120 ms for vector search and reranking on a local GPU) + prefill (~1.08 s for 9,200 tokens across the 8×H100 canonical host, ≈8.5K tokens/s prefill — below the host's ~19,800 tok/s sustained-planning prefill rate (a planning rate, not a ceiling) and far above what a single H100 alone could sustain, per Ch 2 and Ch 8). p95 TTFT must stay ≤ 2 s, allowing headroom for occasional cache misses or network jitter. **TTFT_e2e convention (used throughout):** TTFT_{e2e} = retrieval + queue/tokenization/transfer + prefill + first decode step. Here the 1.2 s budget names the *dominant modeled terms* — retrieval (~120 ms) + prefill (~1.08 s); the queue, tokenization/transfer, and the first decode step are separate, smaller, and in a real system must be added to get the observed TTFT (and must be measured, not assumed). The 1.2 s is an **aspirational SLO budget** (a sub-2-second user-experience target), not a demonstrated p95 TTFT from a benchmark; the ≤2 s p95 is the budgeted ceiling, and the demonstrated value under load requires an actual measurement.
- **TPOT (time-per-output-token)**: budget of ~25 ms/token. A 300-token answer therefore takes ~7.5 s of total decode time. p95 TPOT ≤ 35 ms/token provides headroom for batching variability.

These budgets are [canonical scenario][ASSUMPTION] from typical enterprise Q&A user expectations (sub-2-second feel) and from the hardware's published prefill/decode rates. They are the latency constraints that every subsequent architectural decision must respect.

Economic Constraints

The economic dimension translates the token profile and traffic into a cost structure:

- **Infrastructure**: A single host with 8×H100 GPUs (640 GB total GPU memory, 140 GB model FP16 weights fit with room for KV cache). Capital cost ≈ $20/hour on-demand ($2.50/GPU-hr), or ~$2,500/month reserved (illustrative committed-use discount; a ~83% discount on H100 on-demand is unusually deep and differs from the on-demand basis the canonical box uses) — the canonical box uses the on-demand basis.

- **Token pricing**: ~$1.20 per million input tokens, ~$2.00 per million output tokens on the same H100 instance (mid-tier managed-API list price, derived from cloud provider pricing as of 2026). The frontier-class API used in the Ch 16 TCO comparison is priced higher (~$2/$8 per 1M) — a different provider tier, not the same line item.
- **Throughput per dollar**: At 10 rps average, the system processes ~92,000 input tokens/s + ~3,000 output tokens/s. **The dollar denominator must be the whole fleet that serves this rate, not one host.** At the ~5-host average the whole-fleet spend is ~$100/hour (≈ $0.0278 per second), so ~92,000 / 0.0278 ≈ **~3.3 million input tokens per cloud dollar** and ~3,000 / 0.0278 ≈ **~108,000 output tokens per cloud dollar**. These are *modeled, whole-fleet* figures (before SLO/headroom/failover). A separate quantity is a single host's *sustained-planning* prefill rate (~19,800 tok/s at 35% MFU, Ch 8 — a planning rate, not a ceiling: the peak-derived ceiling is ~56.5K tok/s): ~19,800 × 3,600 / $20 ≈ **~3.56M prefill tokens per host-dollar** — a different denominator and a different rate, and **not** a claim that one host serves the offered load. Never present a tokens-per-dollar figure with the offered workload rate divided by a single-host price. (Chapter 5 expresses the same economics on a GPU list-price basis as **tokens per dollar-hour**; see its throughput-basis reconciliation note — the 9,000 is single-stream/the 3.3M is whole-fleet aggregate — before cross-chapter comparison.)
- **Cost per request**: At 10 rps, each request carries ~9,500 tokens (9,200 input + 300 output). At the per-million rates, cost per request ≈ ($1.20 × 9.2 + $2.00 × 0.3) / 1,000 ≈ $0.01164 ≈ **$0.012 per request** per inference cycle. At 40 rps peak, cost scales linearly. **Basis note — two different cost bases, not interchangeable.** The $0.012 figure is derived from *per-token market/API list prices* ($1.20/M in, $2.00/M out) for the *mid-tier* managed API; it is a cloud-provider price a customer would pay per request on that hosted API. (The *frontier-class* API used in the Ch 16 TCO comparison is priced higher — ~$2/$8 per 1M, ~$0.0208 per request; see the token-pricing bullet above for the tier distinction.) It is *not* the fleet owner's marginal infrastructure cost. The owned-fleet cost is nearly all fixed capex/opex and barely scales per request, but it must be computed on the **whole fleet**, not one host: the $20/hr is the price of a *single* 8×H100 host, while the canonical 10 rps average / 40 rps peak needs ~5 hosts at average and ~20 at peak (Ch 16/17). So the owned per-request cost is (N_hosts × $20/hr) ÷ (rps × 3600) ≈ (5 × $20) ÷ (10 × 3600) ≈ **~$0.0028 per request** at average, and the same ~$0.0028 at peak (20 × $20) ÷ (40 × 3600) — the two coincide because host count and rps scale together. (Dividing one host's $20/hr by the whole workload's 10 rps would give ~$0.00056, but that is dimensionally wrong: one host cannot serve 10 rps of this workload.) Keep the two bases separate: use the per-token price for a *hosted/API* cost model, and the fleet $/hr ÷ fleet rps for an *owned fleet*. The two are juxtaposed in the cost-basis table below (§4.3) only to show the hosted-API pricing basis, not as an owned-fleet marginal cost.

The economic constraint is what makes the workload real: a 70B FP16 model on one host *meets the per-request latency SLO* (TTFT/TPOT) — but the *capacity* question, how many hosts absorb the

~10 rps average / ~40 rps peak arrival, is a separate computation. As Chapters 8 and 16–17 show, a single 8×H100 host holds ~17.5 KV-resident requests (the conservative integer floor is 17), so it cannot carry the ~40 rps peak (~344 in flight); the canonical workload needs on the order of ~5 hosts at the average and ~20 hosts at the peak. Scaling to higher traffic or longer contexts pushes the host count further, and the cost line must be re-evaluated.

Cost-basis distinction (do not confuse the two):

Basis	Derivation	Number
Cloud-provider list price (what a customer pays on a mid-tier managed-API-by-token)	[canonical scenario] [ASSUMPTION] 2026 cloud list snapshot	~$1.20 / 1M input tokens, ~$2.00 / 1M output tokens (mid-tier; the frontier-class API in Ch 16 is ~$2/$8 per 1M)

Basis	Derivation	Number
Self-host cost per million tokens (whole-fleet infrastructure divided by the offered token rate)	($100/hr whole-fleet at ~5 hosts) / (92K inp tok/s + 3K out tok/s) converted to per-million-tokens via 3600	~$0.302 / 1M input tokens (i.e. ~3.3M input tokens per cloud dollar), ~$9.26 / 1M output tokens (~108K output per cloud dollar). **Both are denominator-specific normalizations of the SAME whole-fleet ~$100/hour spend — they are NOT additive unit rates.** Either is "full fleet cost ÷ (input-only volume)" or "…÷ (output-only volume)"; do not add them to get a per-request variable cost. The blended rate over combined (input+output) volume is ~$100 / (95,000 × 3600) × 1M ≈ **$0.2924 per 1M combined tokens** (≈3.42M combined tokens per cloud dollar). These are counterfactual rate-normalizations (they assume the whole fleet carries the whole offered load at the ~5-host average); a **single-host** denominator is NOT valid because one host cannot serve the offered rate — that is the conflation to avoid.

These are NOT redundant measures of the same effective cost — they are what-the-customer-pays-the-cloud (basis A) vs what-the-host-cost-spread-across-tokens-costs (basis B). Quoting both without labelling the basis confuses readers into treating basis B as if it were basis A.

A note on the canonical example's limits. The input-heavy enterprise-RAG workload above is one shape, not the whole space. The same six-dimension framework characterizes any inference workload; what changes is *which dimension dominates* and *which decision reverses*. The compact ledger below is a transfer aid, not five parallel case studies — for each shape it names the changed dominant constraint and the single decision that would flip relative to the canonical RAG case.

Workload shape	Dominant constraint (vs canonical RAG)	Decision that reverses
Short-context, high-throughput chat	Decode bandwidth + batch occupancy, not KV residency	Batch size and continuous-batching policy dominate; KV quantization is a smaller lever
Long-context retrieval (32K–128K)	KV residency per request (linear in context)	Concurrency floor drops; FP8/GQA KV and P/D disaggregation become first-class, not optional
Output-heavy reasoning (long generation)	Decode wall-clock (TPOT × output length), not prefill	TTFT budget relaxes; decode throughput and TPOT SLO bind; prefill optimization is a smaller lever
Agentic tool use (multi-turn)	Per-turn context accumulation + orchestration overhead	Turn cap, prefix caching, and per-task cost (not per-token) drive sizing; see Ch 19
Embedding-only retrieval (no generation)	Embedding throughput + vector-index locality, not KV	No decode, no KV cache; the bottleneck is the embedding model and the retrieval index, not the LLM serving stack

The canonical RAG case is *input-heavy* (9.2K in / 300 out), so prefill compute and KV residency dominate. Each row above is a workload where a different dimension takes over — and the architecture that is right for the canonical case is not automatically right for it. This is why the book keeps the six dimensions separate rather than collapsing them into one "throughput" number.

4.4. Measurement

For this chapter, measurement is about **quantifying the six dimensions** so the workload can be communicated definitively and used to drive architecture decisions. The token-counting habits of Ch 1 §1.4 apply unchanged (run the model's own tokenizer, split input from output, log the distribution not just the mean) — rather than restate them, the three things the *six-dimension* view adds are:

1. **Quantify each dimension with a number, not a label.** For the six dimensions (quality, traffic, token profile, latency, economic constraints, operational constraints), attach a concrete measured or derived figure. "RAG" is not a load; "1.2K prompt + 8K retrieved, 300 out, 40 rps peak, p95 TTFT ≤ 2 s" is.
2. **Tie the token split to the bottleneck it drives.** An input-heavy profile (like RAG's 30× ratio) means prefill compute and KV-capacity pressure dominate; an output-heavy profile would dominate decode. State which side dominates, because it decides where the money and the architecture effort go (Ch 8).
3. **Record the peak and the tail, not just the average.** A workload that averages 9.2K input but has a long tail (e.g. 32K peak contexts) sizes the fleet very differently. Log percentiles (p90, p99) alongside the average and size against the peak.

These habits answer the book's recurring question, "what would I actually measure here?" — and they let the six dimensions be stated as numbers an architecture decision can be defended on.

4.5. Common Mistakes

- **Treating "5% concurrency" as the throughput**. Concurrency is a snapshot of simultaneous users; throughput depends on how long each request takes. 100 concurrent users with 200 s per request yield 0.5 rps, not 10 rps. The binding connection is through request duration (Little's Law). Catch this by always asking "how long is each request in system?" before quoting a concurrency-derived throughput.
- **Assuming "one token ≈ one word"**. Enterprise Q&A prompts with code snippets, JSON payloads, or technical terminology can run 2–5× the naive token estimate, silently inflating KV cache and cost.
- **Ignoring the input–output asymmetry**. An input-heavy workload like RAG tends to increase *prefill compute* and *KV-capacity* pressure — it does not by itself make the system "memory-bandwidth-bound." In the canonical model, prefill is **compute-bound** under the analytical roofline, while long input raises **KV residency**, which constrains sustainable concurrency (a capacity constraint, distinct from bandwidth). An output-heavy workload is **decode-dominant** (bandwidth/runtime per generated token). Optimizing decode throughput on an input-heavy workload moves the needle negligibly; the real win is prefill reduction, prefix/KV reuse, or increasing effective carrying capacity.
- **Quoting context window as free capacity**. The 128 K token window is an upper bound;

using 9.2 K of it still costs for the full 9.2 K in memory and prefill time. Keeping context shorter than necessary is not "free."

- **Overlooking operational constraints**. Multi–region deployment adds replication cost; privacy requirements may force a more expensive on-prem embedding model. These are often the true binding constraints, not the per-token price.

4.6. Architecture Consequence

The six-dimension characterization directly dictates the architectural path for the canonical enterprise-Q&A RAG workload:

- **Model selection**: A 70B FP16 dense model (140 GB weights) fits on a single host with 8×H100 (640 GB GPU memory). The model is large enough to answer factual enterprise questions without fine-tuning, but the 140 GB footprint means KV cache for 9.2 K context adds ~20–30 GB of GPU memory per request at peak, leaving headroom but not abundance.
- **Serving configuration**: One host is the baseline. Continuous batching (e.g. vLLM) is nearly mandatory to achieve the 1.2 s TTFT budget under 10 rps input-heavy traffic; without it, prefill of 9.2 K tokens per request would serialize and push TTFT well above 2 s. The input-heavy token profile (30× more input than output) makes continuous batching especially effective: with long prefills and short outputs, decode slots would otherwise sit idle between admissions, and continuous batching keeps them filled. The benefit of many requests sharing the same retrieved-context prefix belongs to prefix caching — a distinct mechanism (Ch 2 §2.1, developed in Ch 11) — not to continuous batching.
- **Memory planning**: KV cache for 9.2 K context on the canonical model — a 70B **full-MHA reference model** (every query head has its own K,V, so K/V width = hidden_dim = 8192) — is 2 × layers × hidden × bytes = 2,621,440 B ≈ 2.62 MB/token (Chapter 7), giving ≈9,200 ×2.62 MB ≈ 24.1 GB of initial KV per request. This is the MHA upper-bound baseline; a GQA model (8 KV heads, d_head=128) would carry only ~0.33 MB/token, ~8× less (Ch 7). At 10 concurrent full-context requests the MHA figure is ~241 GB of KV on top of the 140 GB weights — pressing against the 640 GB pool well before concurrency reaches 100. The architecture must therefore limit concurrency, quantize KV (FP8 ⟶ ~1.31 MB/token, ~12.45 GB/request at the 9.5K max), or use a GQA architecture. This is the same KV-residency discipline developed fully in Chapters 7 and 17.
- **Economic feasibility**: At ~$20/hour per 8×H100 host and ~$0.012 per request (from $1.20/M input × 9.2 K + $2.00/M output × 0.3 K), the TCO is driven by the 9.2 K input tokens per request. If the input token count could be reduced to 2 K (e.g. via better retrieval or query expansion), cost per request drops to ~$0.003, and the same traffic fits within a much lower budget. This is the lever the architect pulls when TCO is the binding constraint.
- **Operational topology**: Multi-region deployment (active-active) provides availability but doubles the infrastructure cost. If the 99.9% availability SLA is non-negotiable, the architecture




FIGURE 4.1: Six-dimension workload characterization mapped to architectural decisions. Each arrow means the dimension *constrains/informs* the corresponding architectural choice — it is a heuristic influence, not a deterministic one-to-one mapping. The arrows are **non-exclusive**: in practice a dimension often influences several decisions at once (e.g. latency SLO shapes both model choice and serving configuration), and the six axes are a starting lens, not a partition.
The six workload dimensions and the architectural decision each one drives: Quality → model size/type; Traffic → concurrency & batching strategy; Token profile → KV cache size & prefill demand; Latency → TTFT/TPOT targets & batch window; Economic → host count & cost ceiling; Operational → multi-region vs. single-region deployment.

must absorb the 2× cost. If it is negotiable, a single-region with graceful-degrading fallback may suffice. The operational constraint thus directly sets the economic floor. **Caveat — this multi-region active-active topology and the 2× cost here are UNPRICED / NOT VALIDATED in this book's TCO/fleet arithmetic (Ch 16–17), which prices a single-region N–1 deployment instead; multi-region active-active is a different provisioning problem (cross-region capacity duplication, region-failure tolerance, data locality and traffic routing, state/data replication) and must be costed separately before the 99.9% SLA is met — see the canonical-box availability-topology note.**

4.7. What We Still Don't Know

- **Tokenizer exactness for technical domains**: While the "one token ≈ 4 characters" rule of thumb is convenient, enterprise Q&A prompts may contain code, JSON, or domain-specific terminology that tokenizes differently. The exact per-token count for a given prompt distribution is [UNRESOLVED] and would require running the model's tokenizer on a representative sample of real user queries.
- **KV cache scaling with longer contexts**: The canonical scenario uses ~9.2 K input tokens. If retrieval quality degrades and context lengths grow to 32 K or 128 K, the KV cache memory per request grows linearly. **Be precise about what breaks.** A single 32 K canonical request costs ~84 GB of KV, which — with the ~140 GB weights and ~64 GB runtime/workspace — still fits the nominal 640 GB aggregate host *as a single request* (~288 GB total, well under 640 GB). What fails is not one-request fit but a particular **concurrency/SLO requirement**: at the canonical ~40 rps peak and ~8.6 s service time, the in-flight occupancy (~344 requests) demands far more than one host's aggregate KV budget once per-request KV grows to 32 K or 128 K (at 128 K a single request alone needs ~335 GB of KV, leaving little for any concurrency). So state the exact breakpoint in terms of the **maximum concurrent requests and the per-rank/aggregate feasibility**, not as "a 32 K or 128 K context no longer fits." The specific breakpoint is workload- and SLO-dependent and must be checked per-rank (Chapters 17, 20), not asserted as a universal constant.
- **Impact of reranking on latency**: The TTFT budget assumes retrieval (~120 ms) plus prefill. If a late-stage reranker is added to the pipeline, the retrieval component's latency may increase, eating into the TTFT budget and potentially requiring a wider SLO margin or a faster retriever. The magnitude of this effect is [UNRESOLVED] and should be measured before production deployment.
- **Economic durability at scale**: The tokens-per-dollar numbers are derived from 2026 on-demand H100 pricing. Spot instances, reserved contracts, or custom cloud agreements could shift the economics significantly. The durability of the economic model across provider changes is [UNRESOLVED].

4.8. End-of-Chapter Mini-Case: A Six-Dimension Workload Characterization

An architect is brought into the early design of an internal Q&A platform. The stakeholder says: "We have thousands of employees who want to ask questions over our internal documents. We need it to be accurate and fast, but we don't know how many thousands or how fast is fast enough." Before any architecture can be defended, the architect does the workload characterization that this chapter walks through.

From the unit-and-token work of Ch 1 alone, the architect can already establish: the unit is tokens; the request shape will be prompt + retrieved context + output; the workload is input-heavy; and the first number to lock down is tokens-per-request, because every downstream decision (which model fits, how much memory, what latency is possible) is priced against it. Using the canonical scenario as a starting point — ~2,000 registered users, ~5% concurrency, ~10 rps, ~9.2 K input + 300 output tokens — the architect projects the enterprise's actual headcount. If the company has 5,000 employees and expects 10% concurrent activity during peak Q&A periods (after a policy rollout), that gives **500 active people** — a *population* measure, **not** 500 requests currently occupying the inference service. An arrival rate requires its own traffic assumption or observation. Suppose user research and demand modeling independently set the busy-period peak to **50 requests/s** (a declared scenario input at this growth scale, not a figure derived from the 500-user count — Little's Law cannot convert an active-user population into an arrival rate without knowing in-flight request occupancy). With the illustrative ~8.6 s engine response duration, Little's Law implies approximately 50 × 8.6 ≈ **430 requests in the system** across the fleet at that rate — distinct from the 500 active people. It is the *arrival rate*, not the user count, that sizes the fleet. Using the canonical per-host bound from Chapters 15–20 (a single 8×H100 host serves ~2.0 req/s at full modeled utilization, i.e. C/W ≈ 17.5 KV-resident requests ÷ 8.6 s), the fleet rounds to:

$$n_{\text{hosts}} = \frac{50 \text{ rps}}{2.0 \text{ req/s/host}} \approx 25 \text{ hosts} \quad \text{(full utilization)}$$

and roughly **~36 hosts** at a 70% target utilization. A prefill-throughput cross-check from the Chapter 8 model bounds it from below: 50 rps × 9.2K input = 460,000 prefill tokens/s ÷ ~19,800 tokens/s per host (the host's *sustained-planning* prefill rate, 8 × 2,471 tok/s at 35% MFU — a planning rate, not a ceiling: the peak-derived ceiling is ~56.5K tok/s; not a measured goodput) ≈ **~23 hosts**. (Do not divide by the ~8.5K tok/s single-request prefill rate, 9.2K ÷ 1.08 s — that is the rate for one request monopolizing a host, not a per-host aggregate, and using it here would be a unit error.) So prefill-throughput is a *lower* bound on host count; the binding figure is the KV-residency/service-time ~25 (full util) / ~36 (70%) result. The two do not "agree" — the KV-bound dominates, and the prefill model shows why adding hosts for prefill alone is the wrong lever at this scale; both are *analytical* bounds that must be confirmed by benchmark goodput (Chapter 14). Note this mini-case is a 5,000-employee growth scenario at 50 rps, distinct from the canonical 40 rps peak (which sizes to

~20 hosts full-util / ~29 working at 70% (30 with N−1), Chapters 8/16/17/20/25); the two are separate cases, not a contradiction.

At the canonical instance rate (~$20/hr per 8×H100 host), the canonical 5–20-host fleet on-demand clouds is roughly **$73K–$292K/month** (5 hosts at ~$73K/month up to 20 hosts at ~$292K/month, fully saturated) depending on purchase mode and duty cycle (self-host capex amortized runs lower, on-demand burst higher; Chapter 16 develops the TCO properly). The architect can now speak the system's currency — tokens, rps, dollars per million — and can engage the rest of the team on model selection, serving configuration, and TCO with concrete numbers rather than vague assurances.

The specific sizing — turning "thousands of employees" into a characterized workload across all six dimensions — is the payoff of Ch. 4's framework. Each dimension carries an arithmetic (volume → offered load, latency → service time, economics → $/token, operation → agentic growth potential) that the later chapters plug specific numbers into. Until a workload has *numbers* on all six axes, any architecture chosen against it is being chosen against a category, not a workload.

CHAPTER 5.

From Workload to Model Selection

The Architect's Question

After this chapter we should be able to reason about model selection as a **consequence of workload characterization**, not as a first question. We should also be able to walk the two-part selection that defines a RAG system: (a) choosing an embedding model for the retrieval leg, and (b) choosing a generation model for the answer leg. The chapter works toward showing that "which model is best?" is the wrong first question; the right first question is "what job does this system do, and how quantitatively?"

5.1. Concept

Model selection proceeds across five surfaces, each derived from the workload characterization (Ch 4, Table 4-2):

1. **Capability / quality needed** — does the workload require multi-step reasoning, tool use, or modality handling? A workload that needs chain-of-thought reasoning needs a different model class than one that only needs fact retrieval.
2. **Latency / compute budget** — can the system meet TTFT and TPOT SLOs with the candidate model on the target hardware? This surface determines whether we need a dense 70B, a distilled 13B, or a MoE variant.
3. **Context / KV cost** — how much memory does the input context consume in the KV cache, and what does that mean for feasible context length on the target infrastructure? An 8K-context workload has a very different cost profile from a 32K-context one.
4. **Cost per token** — what is the $/million-tokens for the full request (prefill + decode) on

the target infrastructure? This surface makes the economic difference between model sizes concrete.

5. **Retrieve-then-generate vs end-to-end** — does the system architecture split the job into a retrieval leg (embedding model + vector search) followed by a generation leg (base model + prompt), or does it use a single model that jointly retrieves and generates? This architectural decision drives the embedding-vs-generation model contrast.

The core reframe — modeled in Chapter 4 — is that **model selection is a consequence of workload characterization**. When the workload is specified in token counts, request rates, latency budgets, and economic constraints, the feasible model space narrows naturally. The architect does not start with a model and reason forward; they start with the workload and reason backward into model space.

5.2. Mental Model

Model selection is really **system design, not model picking**. The workload is the architect's input; the model is a component that must satisfy the workload's constraints. If the workload is input-heavy (9.2K average input, 300-token output, ~30× more input than output), the system is memory-capacity-bound (KV residency) and prefill-dominated — prefill itself sits in the compute-bound regime (Ch 2). If the workload were output-heavy, it would be decode-bandwidth-bound. The mental model holds both profiles in view: the same "which model?" question produces opposite answers depending on the token profile.

A useful image for the full pipeline:

Workload → Selection surfaces → Model category → Specific model

The arrow from workload to selection surfaces is the one the architect must keep in focus. Every other arrow follows from it.

5.3. Worked Example — Embedding-Model vs Generation-Model Selection for the Canonical RAG Workload

Per the canonical workload (Ch 4, Table 4-2): the enterprise Q&A RAG tool — input-heavy, ~9.2K input (1,200 prompt + 8K retrieved) + 300-token output; 70B-class dense FP16 model (~140 GB) on one 8×H100 host. TTFT budget 1.2 s (retrieval ~120 ms + prefill), TPOT ~25 ms/token; p95 TTFT ≤ 2 s, p95 TPOT ≤ 35 ms.

We walk the two-model selection for this workload.

5.3.1. (a) Embedding-model selection for the retrieval leg

KV cache per-token figures are at FP16 (~2.62 MB/token) unless an 8-bit (~1.3 MB/token) variant is explicitly stated.

The retrieval leg maps chunks of internal documents to dense vectors so that a user query can be matched to the most relevant context. The architect must choose an embedding model — specifically, its embedding dimension and parameter count — against the retrieval quality the workload demands.

Three realistic options, each with documented properties:

Embedding model	Dim	Params	FLOPs per embedding	Typical use case
all-MiniLM-L6-v2	384	~23M	~0.3 GFLOPs	Light-weight, high-throughput search
all-mpnet-base-v2	768	~110M	~1 GFLOPs	General-purpose, quality-first
bge-large-en	1024	~335M	~2 GFLOPs	Dense-retrieval-optimal, technical docs

HYPOTHESIS: *within a given embedding family or a controlled dimensionality experiment*, reducing the embedding dimension may trade retrieval quality for lower storage and compute — e.g. a 384-dim variant of the same model family can cost roughly half the FLOPs and index storage of a 768-dim one. **Dimension alone is not a cross-model quality metric**: a 1024-dim embedding model is not intrinsically better than a 768-dim one merely because its vector has more dimensions; retrieval quality depends on model architecture, training objective/data, corpus/query distribution, normalization, and retrieval strategy. Any observed quality-vs-dimension relationship (reports range from a few to ~15% MAP difference) is domain- and corpus-specific and must be validated on the target corpus.

[ILLUSTRATIVE][DERIVED]: for a 1 M-chunk corpus (a Ch 5-local illustrative input, not part of Table 4-2), the index storage for a D-dim float32 vector corpus is bytes $= n_{\text{chunks}} \times D \times 4$. For 768-dim: $1{\times}10^6 \times 768 \times 4 = 3.07$ GB; for 384-dim: $1{\times}10^6 \times 384 \times 4 = 1.54$ GB; a difference of ~1.5 GB. At 10× the corpus (10 M chunks), that difference grows to ~15 GB. Small relative to a 140 GB base model, but not negligible at large corpus scale: storage is a persistent footprint that scales with corpus size, not a one-time cost that vanishes.

Takeaway for the canonical RAG workload: 768-dim (all-mpnet-base-v2) is the recommended embedding model. It places the workload in the quality-positive regime without introducing per-request latency that threatens the TTFT SLO. The 384-dim option is viable only if storage or compute budget is extremely constrained; the bge-large-en option is overkill for this scale and its marginal

quality gain does not offset the ~2× FLOP cost over all-mpnet-base-v2 (the ~2 GFLOPs vs the ~1 GFLOPs for the 768-dim option in the table above).

Table 5-1 — Model-selection decision: embedding vs generation model

metric	value	derivation
Embedding dimension (recommended)	768	all-mpnet-base-v2 [1P] [FACT]
Embedding model size	~110M parameters	all-mpnet-base-v2 [1P] [FACT]
Per-request context/KV cost at 9.2K input	~24.1 GB (FP16 KV cache, initial)	70B FP16, 80 layers, 9.2K context [canonical scenario] [DERIVED]
Tokens per dollar-hour (generation, runtime)	9,000 tokens per dollar-hour	50 tok/s × 3600 s/hr ÷ $20/hr [ILLUSTRATIVE] [DERIVED]
Verdict	Embedding: all-mpnet-base-v2 (768-dim); Generation: 70B FP16 on 8×H100	Selection surfaces (§5.1)

5.3.2. (b) Generation-model selection for the answer leg

The generation leg produces the 300-token answer given the 9.2K retrieved context. The architect must decide whether a base 70B-class dense model, a smaller dense model, or a fine-tuned variant best satisfies the latency, quality, and economic constraints.

Real-derived arithmetic for the 70B candidate

[canonical scenario][DERIVED]: a 70B-class parameter model at FP16 occupies 70B × 2 bytes = ~140 GB (the 70B is the constructed canonical teaching geometry, Ch 4 Table 4-2; the 140 GB is derived from it, not a vendor-published model card). [1P][FACT]: 8×H100 GPUs provide 8 ×80 GB = 640 GB aggregate HBM memory (real hardware spec).

[canonical scenario][DERIVED] KV cache cost per token at FP16: for a Llama-style 70B model, n_layers = 80, d_model = 8192, bytes per element = 2 (FP16). KV cache per token = n_layers × 2 × d_model × bytes = 80 ×2 × 8192 ×2 = 2,621,440 bytes ≈ 2.62 MB/token (FP16; = 2.5 MiB) (key + value across all layers). For the canonical 9.2K input: 9,200 ×2.62 MB ≈ 24.1 GB of KV cache (initial residency).

[canonical scenario][DERIVED] per-request memory budget: 640 GB total HBM − 140 GB weights = 500 GB headroom (before the ~64 GB runtime reserve that the concurrency budget in Ch. 7 subtracts to reach the ~436 GB KV budget). The 24.1 GB KV cache for 9.2K input consumes ~4.8% of headroom, leaving ~475.9 GB for activations, intermediate buffers, and OS overhead. This is comfortably within a single 8×H100 node's capacity.

[ILLUSTRATIVE][ASSUMPTION]: vLLM continuous batching on 8×H100 with a 70B FP16 model and 9.2K context yields ~50 tokens/s aggregate throughput for 300-token outputs. The prefill phase (9.2K tokens) dominates TTFT: at ~1.08 s it leaves ~0.12 s of headroom against the 1.2 s budget *for prefill alone*. Adding retrieval (~120 ms) puts the full TTFT (retrieval + prefill) at ~1.20 s, i.e. at the 1.2 s SLO line with no prefill-side margin; the real margin is the p95 ≤ 2 s target.

[ILLUSTRATIVE][DERIVED]: tokens/s per dollar for generation. On-demand H100 list price ~$2.50/hour per GPU ⟶ 8×H100 = $20/hour. At ~50 tok/s aggregate throughput, the effective cost is ~0.40 $/tok/s, or equivalently ~2.5 tokens/s per dollar-hour. In tokens-per-dollar terms: 50 tok/s × 3600 s/hr ÷ $20/hr = 9,000 tokens per dollar per hour of runtime.

> **Economics unit note (reconciliation with Ch. 4 and Ch. 15).** Both chapters use the same on-demand price basis: ~$2.50/hr per H100 ⟶ ~$20/hr per 8×H100 host. Two things must be kept straight. First, *units*: this chapter expresses **tokens per dollar-hour** (token-rate × 3600 s ÷ hourly cost), while Chapter 4 expresses **tokens per second per dollar** (token-rate ÷ per-second cost); convert by ÷3600. Second, *throughput basis*: the ~50 tok/s used here is a deliberately **conservative single-stream / low-batch generation rate** adopted to illustrate the per-dollar *method*, **not** a claim about the host's batched serving throughput. Chapter 15's measured-range figure (raw batch-1 ≈ 8,000 tok/s rising to ~35,000–70,000 tok/s under FlashAttention + continuous batching) is the multi-request *serving* throughput of the same host. The per-dollar figures therefore scale up substantially at batch, and the 9,000 tokens/dollar-hour figure should be read as a floor set by the single-stream assumption, not as the host's economic optimum. [ILLUSTRATIVE][DERIVED]

[ILLUSTRATIVE][DERIVED]: tokens/s per dollar with prefill included. (Mixed-input convention: when a derivation mixes a canonical price with an illustrative rate, the result carries the non-canonical provenance — here the 50 tok/s rate input is [ILLUSTRATIVE][ASSUMPTION] while the $20/hr price is canonical.) The same 9,000 tokens per dollar-hour figure is a combined prefill+decode metric. Because this workload is input-heavy (9.2K input vs 300 output tokens), the prefill leg consumes **~97% of the tokens** per request (9,200 ÷ 9,500) — and, because each prefill token runs the full $2 \times 70B$ forward FLOP, it is also **~97% of the linear forward-FLOP cost** (before the quadratic attention term). But it is only **~13% of the wall-clock time** (1.08 s prefill vs 7.5 s decode), because prefill is compute-intensive yet batchable across concurrent requests, while decode is a sequentially-limited token-by-token stream. So the honest picture is *both*: prefill dominates the compute/FLOP budget

(and hence the GPU-hour cost of running the pipeline), and decode dominates the wall-clock latency budget (and hence per-request service time). The per-dollar economics therefore favor models that reduce the *prefill compute* burden (smaller context, larger batch, lower per-token FLOP) more than models that optimize decode throughput alone — but a deployment must balance both, since decode still sets the latency SLO.

5.3.3. (c) Base-model + RAG + guardrails vs fine-tuned model

The architect must choose between two paradigms:

Paradigm 1 — Base model + RAG + guardrails:

- The base 70B model receives the retrieved 9.2K context via prompt injection.
- Guardrails (PII redaction, style enforcement, refusal filtering) are applied as post-generation or prefix-check layers.
- No model weights are trained on domain data; the knowledge source is the vector database.

Paradigm 2 — Fine-tuned model on domain-specific Q-A pairs:

- The base model is fine-tuned (full-parameter, or low-rank adaptation (LoRA)) on thousands of question-answer pairs reflecting the enterprise's terminology and reasoning patterns.
- Inference uses the fine-tuned weights without a retrieval step, or with a much shorter retrieved context. Fine-tuning is **not** a dependable substitute for retrieval when the requirement is factual corpus access, freshness, attribution, or precise enterprise knowledge — fine-tuning distills *behavior, style, task patterns, format, and tool-use policy*, not a guarantee that arbitrary facts are recalled faithfully. Whether it reduces retrieval dependence for a *particular* task is an empirical question to be measured on that task's evaluation set.
- Additional costs: training compute, storage of fine-tuned weights, and reduced flexibility for new topics.

([ILLUSTRATIVE][ASSUMPTION] — not a reference measurement): for the canonical workload, a well-designed RAG + guardrails pipeline *may* approach a fine-tuned model's answer quality on in-domain queries. This is **task-, model-, data-, and evaluation-dependent** — it is not derivable from the architecture alone. The two mechanisms do different work: **RAG** supplies external, mutable knowledge (grounding, provenance, freshness); **fine-tuning** shapes behavior, style, domain reasoning patterns, format, and tool-use policy. Either or both can improve answer quality, and they can be combined. Whether fine-tuning reduces retrieval dependence for this workload must be established by measuring answer quality on the actual evaluation set. The economic comparison should be framed **parametrically**, not with a single number, because the break-even depends on the quality uplift (domain-specific) and the query volume (workload-specific). The decision variable is the break-even query volume Q^* where the annualized cost of fine-tuning, divided by its quality advantage, crosses the RAG baseline:

$$Q^* = \frac{C_{\text{train}} + C_{\text{weights-extra}}}{\Delta Q \cdot \text{value per corrected query}}$$

where C_{train} is the one-time training compute, $C_{\text{weights-extra}}$ is the incremental storage/carry cost, and ΔQ is the (domain-specific, must-be-measured) quality uplift in corrected answers per query. Below Q^*, RAG + guardrails is economically dominant because the fine-tuning cost is spread over too few queries to be repaid; above it, fine-tuning may recover its upfront cost through quality gain. (Scenario structure, not a single claimed break-even volume; the exact C_{train}, $C_{\text{weights-extra}}$, and ΔQ are workload- and domain-specific and should be measured, not assumed.)

Fine-tuning does **not** make the model smaller — pruning is a separate operation. A full fine-tune keeps the ~140 GB 70B weight set (and adds a checkpoint), while a LoRA adapter is tiny but does not change the live weight footprint. Consequently the latency effect of fine-tuning is not "smaller effective model" and cannot be assumed to cut TTFT; any TTFT change must be measured. The real cost changes are: (a) one-time training compute, and (b) incremental storage, both against the RAG pipeline's prefill cost (~1.08 s, which dominates any plausible TTFT delta). Parametrically, fine-tuning becomes worth it only when its annualized cost over Q queries is repaid by $\Delta Q \cdot$ value — this is exactly the Q^* above. The illustrative cloud-GPU training cost is presented as a scenario range, not a fact, and must be benchmark-validated against a target workload.

Takeaway: For the canonical enterprise Q&A RAG workload, the base-model + RAG + guardrails paradigm is the economically preferred choice. Fine-tuning becomes compelling only when the query distribution is highly concentrated, the domain vocabulary is extremely specialized, and the workload volume sustains the training amortization threshold.

5.4. Measurement

How does an architect measure the workload dimensions that drive model selection? The token-counting habits of Ch 1 §1.4 apply unchanged; the three things the *selection* view adds are:

1. **Measure the token split on real employee queries, not the heuristic.** Run the model's own tokenizer on representative prompts from the target domain — the "4 chars ≈ 1 token" heuristic is for estimation only. For the canonical workload, measure the exact prompt+context token count on real employee queries before fixing the model, because the ~30× input-to-output ratio is the single biggest driver of this system's cost structure (Ch 4).
2. **Quantify the output size, since that drives decode cost and per-request latency.** The output token count determines decode bandwidth and p95 TPOT; a large-output paradigm (e.g. long-form generation) changes the model-selection calculus versus a short-output Q&A system.
3. **Know the 95th-percentile context length, not just the average.** Log the distribution of context lengths. A workload that averages 9.2K input but peaks at 32K (a variant flagged in Ch

4) requires a different KV budget and, with it, a different model-size or attention-hybridity choice. Size against the tail.

These checks let model selection be made on measured workload dimensions rather than a generic "bigger model is better" assumption.

5.5. Common Mistakes

- **Starting with "which model is best?"** Instead of characterizing the workload first. The workload's token profile, latency budget, and economic constraints are what narrow the model space; starting with a model short-circuits the reasoning chain and leads to post hoc justification.
- **Ignoring the KV cache cost of long contexts.** A 9.2K input on a 70B model costs ~24.1 GB of KV cache (initial). An architect who does not account for this will either over-provision infrastructure or hit SLO violations when the cache spills to host memory or SSD.
- **Quoting context window as free capacity.** The 128K or 1M token window is an upper bound, not a recommendation. Using even 9.2K of a 128K window still costs for the length actually used. The cost is proportional to the *used* length, not the *available* length.
- **Assuming embedding dimension is a free parameter.** Increasing embedding dimensionality *within a given model family or controlled configuration* can improve retrieval fidelity, but dimensionality alone does not predict quality across different embedding models. Higher dimension also raises FLOP cost, index storage, and per-query latency, so the architect must balance these against the workload's quality requirements rather than treat dimension as a cost-free or universally-better knob (see the caveat in §5.3).
- **Over-engineering the fine-tuning path.** Fine-tuning adds training compute and model/checkpoint-management cost; depending on the adaptation and serving method, it may also add inference or operational overhead (e.g. a LoRA adapter applied dynamically at serve time can introduce overhead, whereas a merged/fully-fine-tuned model of identical architecture need not change the inference shape). The break-even analysis (the parametric Q^* in §5.3) shows that for most enterprise RAG workloads, the RAG + guardrails paradigm dominates on TCO. Fine-tuning should be a deliberate choice triggered by a sustained query volume, not a default.

5.6. Architecture Consequence

Whatever we learned here, file it under **"can I size the workload before I pick a model?"** Concretely, the decision this chapter enables is:

- Estimate tokens-per-request (input and output separately), and therefore tokens-per-second capacity and cost, before choosing a model or a serving configuration.
- Use the selection surfaces (quality, latency, KV cost, cost/token, retrieve-vs-generate) to narrow the model space from the full vendor catalog to a handful of viable candidates.
- For RAG workloads, select the embedding model and generation model as a two-part decision, not a single choice. The embedding model is chosen at ingestion time (compute-light, storage-bound); the generation model is chosen at serving time (compute-bound, latency-bound).

This consequence feeds directly into the fine-tuning-for-specific-workloads pattern and the RAG pattern (both cataloged in Ch 26, Patterns Library): the architect first characterizes the workload, then lets the characterization speak the model selection, not the other way around.

5.7. What We Still Don't Know

HYPOTHESIS: the interaction between embedding dimension and retrieval quality across diverse enterprise domains is not yet characterized with reproducible benchmarks. Early evidence suggests 768 dim is a sweet spot, but the quality drop-off from 768 to 1024 dim varies by corpus genre (legal vs. engineering vs. creative), and no public study quantifies this domain-dependence.

HYPOTHESIS: the break-even point between RAG + guardrails and fine-tuned models as a function of query volume and domain specialization is **model- and domain-dependent**: it is set by the Q^* equation above (training + storage cost over the quality uplift), not by a universal rule of thumb. Any quoted break-even volume is a derived scenario value; more data points and a measured ΔQ are needed before it can be stated as a general principle.

HYPOTHESIS: guardrail latency (PII redaction, refusal checking) on generated 300-token outputs, ~2–8 ms/request on CPU in the illustrative scenario; measure on the target stack (the figure depends on the guardrail implementation and hardware).

Each of these flags is an open empirical question a team should resolve against its own target workload — resolved by measurement into [1P][FACT] or [2°][FACT], promoted to [1P][DERIVED] or [2°][DERIVED] where the resolution is arithmetic, or dropped — rather than left as an untested assumption.

5.8. End-of-Chapter Mini-Case: Choosing the Model for the Enterprise Q&A

(Continuous scenario: the enterprise Q&A architect must now pick the model given the Ch. 4 characterization.)

An architect is assembled for a design review of the enterprise Q&A tool described in Chapter 4 — the canonical workload (Ch 4, Table 4-2). The team has agreed on the retrieval architecture: vector search with embeddings, 768-dim all-mpnet-base-v2, late-max retrieval over a 1 M-chunk corpus.

From the unit-and-token work of Ch 1 alone (Ch 5's selection surfaces), the architect can immediately check the consequences:

- **768-dim embeddings** give adequate retrieval quality at ~1 GFLOPs per embedding, with ~3.1 GB index storage for a 1 M-chunk corpus (vs ~1.5 GB at 384-dim) — a persistent footprint that scales with corpus size, alongside the 70B base model.
- **9.2K input** at ~2.62 MB/KV-token costs ~24.1 GB of cache (initial) on the 70B generation model, well within the 8×H100 node's 640 GB HBM. The prefill TTFT of ~1.08 s plus retrieval (~120 ms) sits at the 1.2 s TTFT budget, with the p95 ≤ 2 s SLO giving the real margin.
- The **30× input-vs-output ratio** means this system is prefill-dominated; model selection must weigh KV cache cost and prefill throughput more heavily than decode throughput.
- The **base-model + RAG + guardrails** paradigm produces the lower **modeled** TCO under the illustrative cost and quality assumptions used in this worked example (see the parametric Q^* break-even above). This is not a general 10× cost relationship — the actual ratio depends on the domain-specific quality uplift and the query volume, and must be measured rather than assumed.

The architect now has a concrete model shortlist: 768-dim all-mpnet-base-v2 for the retrieval leg, and the 70B FP16 base model for the generation leg (dense — the MoE challenger from Ch 3 was rejected on residency and KV grounds), served on 8×H100 with vLLM continuous batching. No fine-tuning is needed at this scale. The architecture decision record (to be written in Chapter 25) will reference this characterization and the selection surfaces that drove it.

End of Chapter 5




FIGURE 5.1: Model selection for RAG: workload → five selection surfaces → two legs (retrieval/embedding, generation/70B) → the system decision. The five surfaces are the *model-selection* dimensions; they are deliberately distinct from the **end-to-end evaluation gates** (retrieval quality, reranking, embedding recall, grounding, and final answer quality) that a RAG system must also pass — those gates are measured on the target corpus (§5.4) and are not shown here because this figure is a selection map, not an evaluation pipeline.

CHAPTER 6.

Measuring What Matters: From Telemetry to Architecture Decisions

The Architect's Question

After this chapter we should be able to walk into a running inference system, read its metrics, and answer a deceptively hard question: *is this system meeting its obligations, and if not, which lever do we pull?* Teams commonly instrument the wrong thing — model capability and offline quality — and then are blind when a real workload misbehaves. This chapter builds the metric hierarchy that turns raw telemetry into architecture decisions: what to log, what each number means, how to read a latency *distribution* instead of a mean, and how to tell bandwidth-bound from compute-bound purely from the counters. After this chapter, "the system felt slow" becomes a falsifiable, diagnosable claim.

6.1. Concept

6.1.1. The Metric Hierarchy

Not all numbers are equal. We organize serving telemetry into three layers, each answering a different question and each consumed by a different role:

1. **Workload metrics** — what the system is being *asked* to do. Requests per second (rps), the token profile (input length, output length, context length), and concurrency. These are the independent variables; we do not control them, we characterize them. For the canonical enterprise-Q&A RAG workload these are fixed by canonical scenario (Ch 4, Table 4-2): ~10 rps average with ~40 rps peaks, ~9,200 input + ~300 output tokens per request, TTFT 1.2 s / TPOT ~25 ms.

2. **Serving metrics** — how *well* the system performs under that workload. Time-to-first-token (TTFT), time-per-output-token (TPOT), inter-token latency, and **goodput** (tokens produced that actually meet the SLO). These are the dependent variables; they are what the SLO is written against.

3. **Resource metrics** — *why* performance is what it is. HBM bandwidth utilization, FLOP utilization / model FLOPs utilization (MFU), KV cache occupancy, memory pressure, and queue depth. These reveal the binding constraint.

The discipline this chapter works toward: **never jump from a workload metric straight to a serving metric, or a serving metric straight to a hardware conclusion.** The causal direction is *workload → resource demand → serving behavior* (the workload's token profile drives the resource demand; the resource supply shapes how the model behaves). Diagnosis runs the other way: a slow response (serving) is diagnosed by asking whether the kernel is bandwidth- or compute-bound (resource), which is only meaningful given the token profile (workload). Skipping a layer produces superstition — "it's slow, let's buy GPUs" — instead of a mechanism.

6.1.2. Why the Wrong Metric Persists

Teams default to measuring what they already have dashboards for: model quality (accuracy, ROUGE, benchmark scores) and average latency. Both are dangerously incomplete. Quality is the *goal* and a *feasibility gate* — a fast or cheap architecture that fails the quality bar is disqualified before performance even matters — but it is not the *bottleneck* that explains a resource or latency failure once quality is acceptable; that is the role of the serving metrics. Average latency is a single scalar that hides the tail that actually violates SLAs. The entire thesis of this chapter is that the metric that drives an architecture decision is usually **not** the metric the model card advertises.

6.2. Mental Model

The three metric layers form a **diagnostic chain**, like the layers of the OSI stack in miniature:

- **Workload** is the *traffic* — what we are asked to do.
- **Serving** is the *service* — how well we did it.
- **Resource** is the *engine* — how hard the machine is working, and on what.

(The listing order here is by *role* — independent inputs, dependent outputs, explanatory engine. It is not the causal order: causation flows workload → resource → serving, which is how Fig 6.1 stacks them top to bottom. The two orderings are different and both intentional.)

When something breaks, we read upward: a p95 TTFT breach (serving) forces us to look at the resource layer first (resource: is prefill queuing because we're FLOP-bound?) and then the token profile (workload: did context length grow?). The causal direction follows the system, not




FIGURE 6.1: The metric hierarchy as a diagnostic chain
The three metric layers and the top-down diagnostic path from a p95 TTFT breach to its root cause. Causation runs downward (workload ⟶ resource demand ⟶ serving behavior); diagnosis runs upward (serving symptom ⟶ resource evidence ⟶ workload/context).

the diagnosis: the workload generates resource demand, and the resource supply shapes serving behavior — so when numbers are healthy, the chain confirms our architecture was right.

The mental model also warns against **one number standing in for many different things**. "Throughput" without a qualifier is meaningless: is it requests per second, tokens per second, or *goodput* — tokens per second that arrived before the SLO deadline? We commit to always qualifying.

6.3. Worked Example

6.3.1. Latency Is a Distribution, Not a Mean

A very common measurement error is reporting (and SLO-ing) the *average* latency. Fig 6.2 shows a synthetic request stream: the body of requests follows a log-normal distribution centered near 0.8 s (99% of observations), with a 1% straggler cluster at 5.0 s. That combination is deliberately *not* a two-point "99% at 0.8, 1% at 5" distribution; it is a realistic spread, so the percentiles below are read off the plotted histogram rather than guessed. The plotted stream is a synthetic sample of N = 10,000 requests — 99% drawn from a log-normal with median 0.8 s, 1% a straggler cluster at 5.0 s — and the percentiles are read by linear interpolation on the sorted sample. The mean of that stream is

$$\mathbb{E}[L] \approx 0.99 \times 0.8 + 0.01 \times 5.0 \approx 0.84 \text{ s}$$

— looks fine. But the distribution actually has a long tail: p50 ≈ 0.80 s, p90 ≈ 0.94 s, p95 ≈ 0.99 s, and p99 ≈ 1.33 s. The mean hides the tail; percentiles expose it — but notice how far one has to go to expose *this* tail. Under the canonical p95 TTFT SLO of ≤ 2 s, **even p99 (≈ 1.33 s) still looks healthy.** The 5 s stragglers are the top 1% of the stream — they sit *between* the 99th and 100th percentile, so a p99 line alone does not bring them into view. Only the p99.9 / maximum reading (or the full distribution) surfaces them. This is the sharper lesson: a tail can hide not just behind the mean but behind any single percentile, and the choice of which percentile to SLO against matters. It is why we log the full distribution and also watch the *outlier fraction* (how much probability mass sits beyond the SLO line), not just one percentile.

Why the mean is not a signal. The same request stream of 99% @ 0.8 s + 1% @ 5 s reported as a single number looks healthy (mean ≈ 0.84 s; the figure's exact simulated stream mean ≈ 0.85 s — the 0.84 is the two-point analytic approximation), yet p99 paints a very different picture under a 2 s SLO. Log the distribution; SLO against the percentile.

Apply this to the canonical workload. We budget TTFT ≤ 1.2 s (retrieval ~120 ms + prefill ~1.08 s) with a p95 ≤ 2 s. Suppose a flash crowd (the ~40 rps peak) causes prefill requests to queue. If on average the batch is well-behaved, p50 TTFT might sit at ~1.0 s. But the jobs that arrive behind 3 same-time prefill requests each pay the full 1.08 s prefill of the job ahead of them, so p95 TTFT drifts to ~2.5 s. The *average* says "fine"; the *p95* says "we just violated our SLO." We hence log p50, p90, p95, and p99 independently and run the SLO against the percentile, never the mean.




FIGURE 6.2: Request-latency distribution: p50/p90/p95/p99, with the mean in the legend

[canonical scenario][ASSUMPTION] author-chosen SLO budget from the canonical scenario (Ch 4, Table 4-2); the arithmetic is the point, not a citation.

6.3.2. Goodput vs Raw Throughput

Deploying a higher-throughput configuration can *reduce* goodput. Concretely: suppose we enable larger dynamic batching to raise raw tokens/s from 50 tok/s to 70 tok/s, but the batch window pushes p95 TTFT from 1.8 s to 2.3 s — above the 2 s SLO. The extra 20 tok/s are produced, but they land in the tail that misses the SLO, so goodput does not grow. Raw throughput is up 40%; **goodput** (tokens that met the SLO) is effectively unchanged, because the batch of SLO-compliant tokens didn't grow. Goodput is the metric the customer experiences; raw throughput is what the GPU achieves. The architect optimizes goodput. This is why "faster" hardware or bigger batches do not trivially mean a better system.

6.3.3. Detecting the Regime: Bandwidth-Bound vs Compute-Bound

The most decision-relevant resource question is: is this layer bandwidth-bound or compute-bound? We recall the arithmetic from Chapter 2:

- **Decode is HBM-bandwidth-bound at low batch.** Generating one token needs a full forward pass over the 70B weights of the **canonical 80-layer, hidden-8192, full-MHA 70B reference** = 140 GB (FP16) of reads per token — a **batch-1-equivalent** idealized weight-streaming read (one request's full weight pass), not a measured bytes-physically-read figure. Within a ~25 ms TPOT budget that demands 140 GB / 0.025 s ≈ **5.6 TB/s** (batch-1-equivalent) of HBM bandwidth, against an H100's ~3.35 TB/s peak [1P][FACT]. **Scope warning: this 5.6-vs-3.35 TB/s comparison is an *illustrative single-device roofline* argument, not the canonical 8×H100 host's actual deployment verdict.** Two scope notes keep this honest. First, 5.6 TB/s is the **aggregate** model-wide weight-read rate for a hypothetical single-device implementation; under tensor parallelism (the canonical 8×H100 host) the 140 GB is sharded, so each GPU only needs ~0.70 TB/s against its own 3.35 TB/s — the single-device 5.6>3.35 bound does not itself show a per-GPU bandwidth shortfall. Second, the deeper and shard-invariant reason decode is *memory-limited* is its low arithmetic intensity (the ratio of FLOPs to bytes moved, ~1.0 FLOP/byte here) — far below the ~295 FLOP/byte roofline ridge point that separates memory-bound from compute-bound kernels (the roofline and its ridge are developed in Ch 8; this chapter only needs the qualitative point that a low intensity starves the compute units for weights). That is what makes compute units starve for weights regardless of sharding. So the honest statement is: decode is memory-bound because its intensity is low and batching raises it, not merely because an aggregate 5.6 TB/s exceeds one GPU's 3.35 [canonical scenario][DERIVED]. (This is an operating-point property, not an identity: at high batch decode climbs the intensity slope and can become compute-bound.)

- **Prefill is compute-bound at the canonical long-prompt operating point.** The reason prefill lands on the compute plateau of the roofline is its high arithmetic intensity: the FLOPs per byte moved are far above the ~295 FLOP/byte ridge point (developed in Ch 8), so the compute units — not the HBM weight stream — are the binding resource. Only after establishing that regime do we check the deadline: the prefill pass for 9,200 input tokens costs ≈ 2 ×70e9 params × 9.2e3 tokens ≈ **1.29 PFLOP**, which against the ~1.08 s prefill budget implies a required rate of ≈ 1.19 PFLOPS — above a *single* H100's ~0.989 PFLOPS dense BF16 peak (1.19 > 0.989). But that 1.19-vs-0.989 comparison is a **single-device deadline/capacity illustration**, not the evidence that prefill is compute-bound: on the canonical 8×H100 host the aggregate peak is ~7.9 PFLOPS, so the host comfortably satisfies the rate — the "single H100 can't prefill a 9.2K prompt in 1.08 s" conclusion is about whether one arbitrarily-chosen GPU can meet the deadline, not about the kernel's roofline regime. Prefill being *compute-bound* (rather than bandwidth-bound) follows from its high arithmetic intensity, not from the 1.19-vs-0.989 comparison. [canonical scenario] [DERIVED]

At the resource layer, the tell is utilization: a decode kernel pinned at ~95% of HBM bandwidth but ~30% of FLOPs is bandwidth-bound; a prefill kernel with ~90% FLOP utilization is compute-bound. **The same hardware, the same model — the boundary flips between prefill and decode.** This is precisely why Splitwise/DistServe (and Mooncake's KV-centric disaggregation) split prefill from decode onto different pools: the bottleneck-regime difference justifies it. [S4][1P][FACT] (source keys: each `[S#]` names one entry in the References chapter, where `[S3]`–`[S7]` resolve; Ch 11 lists `[S1]`–`[S6]` inline.) *These percentages are **hypothetical telemetry signatures** used to illustrate how to read utilization — not a measured benchmark find from any trace. They are representative operating-point values (a low-intensity decode kernel at high HBM-utilization/low FLOP-utilization, a high-intensity prefill kernel at high FLOP-utilization), useful to classify a kernel's regime; an actual deployment's percentages come from its own counters, and a real utilization reading (observed vs. theoretical peak vs. required minimum) must be distinguished from these example values. See Ch 8 for the underlying intensity/roofline arithmetic that shows why these regimes occur.*

Table 6-1 — Detecting the bottleneck regime from resource telemetry

Phase	Demand	H100 capacity	Verdict	Resource tell
Prefill (9.2K input)	~1.19 PFLOPS (1.29 PFLOP ÷ 1.08 s)	~0.989 PFLOPS BF16	compute-bound (from intensity ~9.2K FLOP/byte ≫ ridge ~295, not this rate comparison)	high FLOP / MFU util, mid bandwidth
Decode (per token)	~140 GB weight-read ⟶ ~5.6 TB/s rate (batch-1-equivalent)	~3.35 TB/s HBM (single-device)	bandwidth-bound	high HBM util, low FLOP util

(All figures [1P][FACT] hardware / [canonical scenario][DERIVED] arithmetic traced to the canonical scenario (Ch 4, Table 4-2) and Chapter 2. The regime verdict follows from arithmetic intensity, not from the demand-vs-capacity rate comparison: prefill ~9,200 FLOP/byte ≫ ridge ~295 (compute-bound), decode ~1.0 FLOP/byte ≪ ridge (bandwidth-bound). The 1.19-vs-0.989 PFLOPS and 5.6-vs-3.35 TB/s rate comparisons are illustrative single-device roofline arguments (a hypothetical single-GPU rate against that GPU's own peak), not verdicts on the canonical 8×H100 host's bandwidth adequacy — under tensor parallelism the 140 GB is sharded, so each GPU only needs ~0.70 TB/s against its own ~3.35 TB/s.)

6.3.4. Reading Telemetry Into a Decision

A concrete dashboard-read ⟶ decision trace. We see: p95 TTFT climbing (serving), KV cache hit ratio low (resource: memory), and prefill queue depth growing (serving). Workload is unchanged. Reading up the chain: low prefix-cache hit means many independent 9.2K prefixes are being prefill-processed from scratch on the ~40 rps peak — each ~1.29 PFLOP saturating FLOPs. The decision: enable prefix / RadixAttention-style caching (SGLang) or Automatic Prefix Caching (vLLM) so shared retrieved-context prefixes are reused instead of re-prefilled, cutting effective prefill FLOPs and TTFT. [S3][1P][FACT] Prefix caching is a compute-saving move, not a latency tuning — and the telemetry told us that.

6.4. Measurement

Three practical habits anchor the architect:

1. **Instrument the hierarchy, not just the app.** Deploy counters at all three layers from day one — rps and token profile (workload); TTFT/TPOT/goodput percentiles (serving); HBM bandwidth, FLOP/MFU, KV cache occupancy, queue depth (resource). A system that only logs serving metrics cannot tell *why*; one that only logs resource metrics cannot tell *what it was asked*.

2. **Always qualify "throughput."** rps ≠ tokens/s ≠ goodput. The same number, three stories. State the SLO window (p95 ≤ 2 s TTFT) before quoting any rate, or the rate is meaningless.

3. **Log the distribution.** Capture p50/p90/p95/p99 for every latency metric, and the full token-length distribution (a 32K-tail context is a different workload than a 9.2K average). The mean is a summary, not a signal.

These habits answer the book's recurring question — *what would we actually measure here?* — with three layers of counters at the edge, before any architecture decision is committed.

6.5. Common Mistakes

- **SLO-ing the average.** A ~0.85 s mean (the figure's simulated stream; the two-point analytic approximation gives ~0.84 s — the figure's displayed value is used here) hides a 5 s tail. SLO against p95/p99, and watch the outlier fraction, not the mean.
- **Optimizing raw throughput when the SLO windows it.** Bigger batches raise raw tokens/s but can push TTFT past its deadline, zeroing goodput. Optimize goodput.
- **Jumping straight to "buy more GPUs."** A bandwidth-bound decode and a prefill-cost problem need different fixes; without the resource layer we guess.
- **Treating hardware peak as a ceiling we can hit.** H100's 3.35 TB/s is the theoretical HBM peak; real memory-bound kernels realize a fraction of it. Design headroom against real utilization, not the spec sheet.
- **Conflating model-quality metrics with serving metrics.** Accuracy is the goal; TTFT is the constraint. A slow, accurate model fails its SLO just as surely as a fast, wrong one.

6.6. Architecture Consequence

The metric hierarchy directly dictates architecture. For the canonical workload:

- **Bandwidth-bound decode + compute-bound prefill ⟹ P/D disaggregation** (Splitwise/DistServe/Mooncake) is the remedy at scale, because squeezing both regimes from one resource pool fights itself. [S4][1P][FACT]

- **Repeat-prefix RAG ⇒ enable prefix caching** (RadixAttention/APC), which turns repeated 9.2K prefills into cached lookups and defends the p95 TTFT against the 40 rps peaks. [S3][1P][FACT]
- **KV cache pressure ⇒ quantize or offload KV.** FP8 KV = raw tensor byte-halving = 1.31 MB/token (exactly 50% of BF16) [canonical scenario][DERIVED]; any block-allocation/metadata overhead is NOT vendor-measured here and must be filled by a deployment benchmark. (The vLLM FP8-KV blog's '54%' is a decode-ITL latency slope, not a memory ratio.) And vLLM KV-offloading (its own 2026-01-08 blog [S7][1P][FACT]) cuts TTFT by 2–22× in a particular warm-cache-hit/reuse benchmark, not a generic cold-cache improvement — both are memory-layer fixes the telemetry would call for when KV occupancy nears capacity.
- **Speculative decoding where decode bandwidth is the wall** — DFlash *reports* over 6× lossless acceleration, up to 2.5× over EAGLE-3, in its paper's evaluated configurations [S5][1P][FACT] — because it reduces weight reads per accepted token. These are paper-reported results, not portable serving-speed figures: treat them as performance claims to re-measure on the target workload, not as a guaranteed speedup.

6.7. What We Still Don't Know

- **Goodput in production is rarely published.** The research corpus gives strong qualitative and some quantitative anchors (Mooncake 525% simulated throughput / 75% more requests [S4][1P][FACT], DFlash >6× [S5][1P][FACT]), but portable end-to-end goodput figures across real enterprise RAG workloads remain [UNRESOLVED].
- **Prefix-cache hit rates in mixed workloads** are workload-dependent; the actual reduction in prefill FLOPs from APC/RadixAttention for a given document-retrieval distribution is [UNRESOLVED].
- **Tail-latency drivers under batching** interact: batch size, arrival burstiness, and KV fragmentation each affect p99 differently, and their joint effect is [UNRESOLVED].

6.8. End-of-Chapter Mini-Case: The Post-Lunch Slowdown: Reading Telemetry Up the Chain

An on-call architect is paged: "the internal Q&A tool got slow after lunch." The dashboard shows rps at the ~40 rps peak (workload, up from the 10 rps baseline), p95 TTFT at 2.4 s against a 2 s SLO (serving, breached), and KV cache occupancy at 85% with low prefix-hit ratio (resource, memory/FLOP pressure). Following the chain rather than guessing, the architect reads: a concurrency spike (workload) with repeated full 9.2K prefills (low prefix hit) is saturating prefill FLOPs (compute-bound). The architecture is memory- and compute-sane at the 10 rps design point but was never sized for the lunch peak. The fix is not "buy GPUs immediately" — it is to enable prefix caching to collapse the repeated prefills, which the telemetry shows will address the actual mechanism. The architect

re-checks the dashboard an hour later: p95 TTFT back under 2 s, goodput restored — because they measured the right thing at the right layer.

PART III.

The System

CHAPTER 7.

Memory Is the First Constraint

The Architect's Question

After this chapter we should be able to answer the architect's fundamental constraint question: *does the model and its context fit in the memory floor before we ask whether it can compute or communicate?* We will build the arithmetic for the KV cache from first principles, reconcile it with the canonical ~1.3 MB/token figure from Chapter 1, and contrast inference residency (weights + KV) with fine-tuning residency (weights + gradients + optimizer states). The goal is to make "does it fit?" a concrete, quantified check — not a back-of-the-envelope guess. Throughout, the arithmetic anchors to the canonical enterprise-Q&A RAG scenario (Ch 4, Table 4-2): ~10 rps average / ~40 rps peak traffic served by a 70B **FP16** model on an 8×H100 host. KV cache per-token figures are given at the referenced precision throughout: ~1.3 MB/token at **8-bit** (this is Chapter 1's reference figure), ~2.5 MB/token (2.62 MB exact) at **FP16** — and the canonical scenario's KV constant is the **FP16** 2.62 MB/token figure, not the 8-bit ~1.3 MB/token number.

7.1. Concept

Memory is the first constraint because every LLM workload begins with a residency check: can the model and its active data structures be placed on the target hardware? The KV cache is the primary expression of this constraint during inference: it grows linearly with context length, and its size depends on the model's layer count, hidden dimension, and the precision chosen for key and value storage. Unlike FLOPs, which scale with operations per token, the KV cache occupies memory continuously for the lifetime of a request — it is always resident, always consuming HBM bandwidth for every re-read. The architect must therefore size two distinct memory loads: the static weight

footprint and the dynamic KV footprint that varies with prompt length. Quantization (FP8, FP4, 2-bit asymmetric) reduces both, but the KV cache is the one component whose reduction must be quoted per precision, not as a uniform factor: FP8 KV realizes ~50% in serving today (raw byte-halving), while 4-bit KV's raw bound is a full 4× (2.62 ⟶ 0.66 MB/token at this chapter's geometry) — realized savings land between, once per-block scale/offset metadata and per-token variation are counted — rather than the single 2×–4× that weight-only quantization applies to weights. The residency floor is therefore set by weights + KV (+ activations, in fine-tuning), and the architect's first question is whether this sum fits on the target GPUs. This is why "does it fit?" is the architect's primary gate: before we ask whether the model can compute or communicate, we must first establish that the working set — weights plus the context-dependent KV state — resides on-GPU. If it does not, every subsequent decision (offload, recompute, page) is a degradation, not a cost-optimization.

The residency floor has two distinct regimes. For inference, the floor is weights + KV: the model's static parameters plus the context-dependent key/value tensors that grow with every token added to the prompt. In fine-tuning, the floor rises further to weights + gradients + optimizer states, because every parameter update requires its own momentum and velocity vectors (Adam) or per-parameter scaling (LAMB/RMSProp). The contrast between these two floors — inference ~164.1 GB for a 70B model at FP16 with 9.2K input (140 + 24.1; the 9.5K-max is 164.9 ≈ 165 GB) [ILLUSTRATIVE] [DERIVED], fine-tuning exceeding 1 TB [ILLUSTRATIVE][DERIVED] — is the architect's central memory-takeaway.

We keep two terms rigidly distinct in this chapter, and the distinction is the antidote to "does it fit?" mistakes:

- **Residency floor** = weights + KV. This is the minimum memory the model's parameters and active KV tensors must *occupy* for a single request. It is what the numbers in this chapter quote (~140 GB weights + ~24.9 GB KV ≈ 165 GB at 9.5K max).
- **Practical host requirement** = weights + KV + runtime/workspace + safety margin. Deploying a model on a GPU requires additional VRAM for CUDA kernels, activation buffers, NCCL (NVIDIA Collective Communications Library) communication, a warmup/KV-allocation safety pool, and (on a multi-GPU host) tensor- or pipeline-parallel copies. On the canonical 8×H100 host this runtime/workspace term is ~64 GB, turning the ~165 GB residency floor into a larger *deployment* footprint. [ILLUSTRATIVE][ASSUMPTION] The ~64 GB is a planning reserve, not a measured constant; a representative split is ~8 GB CUDA context/driver + ~16 GB activation buffers (batch + intermediate tensors) + ~8 GB NCCL communication buffers (tensor-parallel all-reduce staging) + ~32 GB warmup/KV-allocation safety pool. The exact value must come from a deployment benchmark on the target stack (Chapter 14); the 436 GB KV budget (640 − 140 − 64) shifts by the same amount if the measured reserve differs.

When the text says a workload "fits" or "does not fit," we are always talking about the residency floor first; the practical host requirement is a superset that must be checked before committing hardware. Conflating the two is exactly what produces a "165 GB fits in 160 GB" error.

7.2. Mental Model

The KV cache is **per-request state that persists across autoregressive decode steps for the lifetime of the active sequence** — unlike weights, which are loaded once and reused across requests, the KV cache is allocated per request and grows with every token added to the context. A 9.2K prompt on a 70B model at FP16 carries ~24 GB of KV state that must remain on-GPU for the entire prefill + decode sequence. If it does not fit, the serving stack must page, offload, or recompute — each option degrades latency or throughput. The durable mental model is: *every token we add to the context exacts a fixed memory toll, and that toll is paid in HBM every time the GPU re-reads the cache during decode.* This is why context length is the single most powerful lever on inference memory pressure, and why "does it fit?" is the architect's primary gate.

7.3. Worked Example

We anchor all arithmetic in the canonical scenario (Ch 4, Table 4-2): a **canonical 80-layer, hidden-8192, full-MHA 70B reference model** (every query head carries its own K,V, so the per-token KV width equals the model's hidden dimension), FP16 weights (2 bytes per parameter), 8 ×GPUs (80 GB each, 640 GB total VRAM), ~9.2K input tokens + 300 output tokens. We compute KV cache size per token, total KV for the canonical context, and contrast with long-context variants. The per-token formula is general — KV/token = 2 × layers × n_KV-heads × head_dim × bytes — and the full-MHA special case (n_KV-heads × head_dim = hidden_dim) gives the ~2.62 MB/token conservative baseline used throughout; a grouped-query attention (GQA) model would use a much smaller constant (see the sensitivity note, below).

Table 7-1 — KV cache size per token and per-context arithmetic for the canonical 80-layer, hidden-8192, **full-MHA 70B reference** at FP16. *(All per-context KV totals, residency figures, and fit/non-fit verdicts below are [ILLUSTRATIVE][DERIVED] from the general per-token formula `2 × layers × n_KV-heads × head_dim × bytes` (MHA case here); model-card architecture constants are [1P: model card].)*

metric	value	derivation
layers	80	canonical 70B full-MHA teaching model [ILLUSTRATIVE] [ASSUMPTION]
hidden_dim	8192	canonical 70B full-MHA teaching model [ILLUSTRATIVE] [ASSUMPTION]

metric	value	derivation
bytes per parameter (FP16)	2	FP16 = 2 bytes/param [1P: NVIDIA H100 spec]
KV cache per token per layer	2 × hidden_dim × bytes	one key + one value per layer
KV cache per token (FP16)	2 ×80 ×8192 ×2 B ≈ 2.62 MB	= 2,560 KB = 2.5 MiB; exact decimal 2.62 MB
KV cache per token (8-bit)	2 ×80 ×8192 ×1 B ≈ 1.3 MB	= 1,310,720 B = 1.25 MiB; reconciles with Ch.1
KV cache per token (FP8)	1.31 MB	= 1,310,720 B = 1.25 MiB; raw tensor byte-halving, exactly 50% of BF16; any block-layout/scale-offset metadata overhead is NOT vendor-measured (see §7.4)
9.2K input KV cache (initial)	9,200 ×2.62 MB ≈ 24.1 GB	9,200 ×2,621,440 B; initial KV residency
300 output KV cache	300 ×2.62 MB ≈ 0.8 GB	300 ×2,621,440 B
total inference KV (9.5K max)	≈ 24.9 GB	9,500 × 2,621,440 B ≈ 24.9 GB
32K input KV cache	32,000 ×2.62 MB ≈ 83.9 GB	32,000 ×2,621,440 B; long-context variant
128K input KV cache	128,000 ×2.62 MB ≈ 335.5 GB	128,000 ×2,621,440 B; aggressive long-context variant
70B FP16 weights	70B × 2 B = 140 GB	[1P: DERIVED from 70B × 2 bytes]
inference residency (weights + KV, 9.5K max)	≈ 165 GB	140 + 24.9 GB
inference residency (weights + KV, 32K)	≈ 224 GB	140 + 83.9 GB
inference residency (weights + KV, 128K)	≈ 475 GB	140 + 335.5 GB
2×H100 total VRAM	2 ×80 GB = 160 GB	[1P: NVIDIA H100 spec]
8×H100 total VRAM	8 ×80 GB = 640 GB	[1P: NVIDIA H100 spec]
3×H100 total VRAM	3 ×80 GB = 240 GB	[DERIVED] 165 GB < 240 GB

metric	value	derivation
fits 2×H100 at 9.2K?	no, 164.1 GB > 160 GB	does not fit in 2×H100; needs ≥3×H100 by aggregate capacity (or lower precision / more GPUs)
fits 8×H100 at 9.2K?	yes	164.1 GB < 640 GB
fits 3×H100 at 9.2K?	yes	164.1 GB < 240 GB
fits 8×H100 at 32K?	yes	224.0 GB < 640 GB
fits 8×H100 at 128K?	yes, barely	475.5 GB < 640 GB
fits 1×H100 at 9.2K?	no	164.1 GB > 80 GB; needs ≥3×H100 by aggregate capacity

Note on "does it fit?": this residency check answers a single-request question — does ONE request's weights + KV fit in the pool? It says nothing yet about how many such requests fit concurrently. For that, an architect must subtract the runtime/activation/workspace floor (~64 GB on the 8×H100 host) from the 640 GB pool before sizing KV. We compute that concurrent capacity — the ~436 GB KV budget and ~17.5 requests/host (byte-accurate 17.51; conservative integer floor 17) — in Chapter 17. Keep the two numbers separate: the ~500 GB headroom (Ch. 4/7, single-request) and the ~436 GB KV budget (Ch. 17, concurrency) answer different questions.

Attention-family sensitivity note. The ~2.62 MB/token (2.5 MiB) figure is the **full-MHA** (multi-head attention) upper bound: n_KV-heads = n_query-heads, and n_KV-heads × head_dim = hidden_dim, i.e.

$$KV_{\text{MHA per-token}} = 2 \times n_{\text{layers}} \times d_{\text{hidden}} \times B$$

Real 70B-class dense models commonly use **grouped-query attention (GQA)**: LLaMA-2 70B, for instance, has 64 query heads but only 8 KV heads, so per-token KV shrinks by the head ratio to

$$KV_{\text{GQA per-token}} = 2 \times n_{\text{layers}} \times n_{\text{KV-heads}} \times d_{\text{head}} \times B = 2 \times 80 \times (8 \times 128) \times 2\ \text{B} \approx 0.33\ \text{MB/token}$$

— about **8× smaller**. For the canonical 9.2K context that is ~3 GB of KV instead of ~24 GB, and the fleet-sizing arithmetic of Chapter 17 changes accordingly (many more concurrent requests fit for KV). We keep the full-MHA bound as the canonical conservative residual because an architect should size against the worst case the *chosen* model actually presents — the honest move is to read the model




FIGURE 7.1: Grouped-Query Attention cuts per-token KV. The head glyphs are schematic; the load-bearing number is the **n_q : n_kv ratio (8 : 1 here)** — 8 query heads share one K/V head, so the per-token KV falls ~8× (the full arithmetic is in the text below).

card's KV-head count and substitute it into the GQA formula above. The framework is unchanged; only the constant changes. (`kv_gqa_variant_mb` is recorded in `canonical-workload.yaml`.)

The figure shows one group's geometry: **8 query heads funnel into a single shared K/V head.** Because GQA caches only one K/V per group (8 K/V per token) instead of one per query head (64 K/V per token), the per-token KV falls ~8× — from ~2.62 MB/token (full MHA) to ~0.33 MB/token. That is the takeaway: many query heads can share a few K/V heads, and the cache shrinks by exactly the 8:1 head ratio. Head count is the real dial: substitute the model's KV-head count into `2 × layers × KV_heads × head_dim × bytes`.

Table 7-2 — Inference residency vs. fine-tuning residency contrast for the canonical 80-layer, hidden-8192, full-MHA 70B reference model.

scenario	memory resident	bytes per param	total (70B)	fits 8×H100
inference (weights + KV, 9.2K input)	weights + KV cache	FP16: 2 B; KV adds ~2.62 MB/token	~164.1 GB (9.2K; 140 + 24.1)	yes

scenario	memory resident	bytes per param	total (70B)	fits 8×H100
fine-tuning (weights + gradients + optimizer)	weights + gradients + optimizer states	Adam: ~16 B/param (m + v + ΔW)	~1,120 GB	no
fine-tuning (weights + gradients, FP16)	weights + gradients FP16	4 B/param (weights FP16 2 B + gradients FP16 2 B)	~280 GB	yes
fine-tuning (QLoRA, 4-bit base + LoRA)	quantized base + LoRA adapters	NF4: nominal 4-bit (~0.5 B/param) + quantization metadata; adds adapters/gradients/optimizer/activations	~50–70 GB	yes
inference with FP8 KV	weights FP16 + KV FP8	KV: ~50% of BF16 (raw byte-halving)	~152 GB (9.5K; 140 + 12.45; KV alone 12.45 GB)	yes

Inference residency = weights + KV cache; the KV footprint scales with context length. Fine-tuning residency adds optimizer states (Adam m, v, and master weights), which for 70B at ~16 bytes/param totals ~1,120 GB — roughly 1.75× the 640 GB of 8×H100. This contrast is the architect's central takeaway: inference is memory-limited by weights + KV, while fine-tuning is memory-limited by weights + gradients + optimizer, a substantially higher floor. Note the ~1,120 GB is the ***parameter/optimizer floor*** *(weights + gradients + Adam m/v/master), which is fixed by model size and precision. The* ***actual training peak*** *is higher and is not inferable from that floor alone: it also includes activation memory (scales with batch size × sequence length × hidden dim, and is the dominant term for long-context or large-batch runs), temporary kernel workspace, allocator fragmentation, and checkpointing buffers. A host that fits the 1,120 GB floor can still fail to fit a given training run if its activation peak exceeds the remaining HBM — so the fit verdict for training must be checked against the measured peak for the specific batch/sequence configuration, not the parameter floor. (QLoRA's ~50–70 GB figure is likewise a floor: it holds the 4-bit*

base + adapters + a small optimizer, and its activation peak still depends on the run's batch and sequence length.)

7.4. Measurement

Four practical measurement habits follow from the arithmetic above:

1. **Compute KV cache per-token cost for the model.** The per-token KV footprint of a fully-cached (MHA) attention head is

$$KV_{\text{per-token}} = 2 \times n_{\text{layers}} \times d_{\text{hidden}} \times \text{bytes-per-value}$$

(one key and one value per layer, each d_{hidden} wide), evaluated at the chosen precision. For a 70B model at FP16 the answer is $2 \times 80 \times 8192 \times 2$ B $= 2{,}621{,}440$ B ≈ 2.62 MB/token (the book quotes **~2.5 MB/token** as a rounded shorthand; that is 2.5 MiB, and the exact decimal value is 2.62 MB). At 8-bit the per-token value halves to ~1.31 MB/token (~1.25 MiB; the Ch.1 reference). Do not assume the 1.3 MB/token figure applies at FP16 — it does not; it is an 8-bit number. When evaluating a model where the hidden dimension or layer count differs from LLaMA-70B, recompute the constant factor — a model with 64 layers and 8192 dim will have ~2.1 MB/token at FP16 (2 × 64 × 8192 × 2 B ≈ 2.097e6 B), while a model with 100 layers and 12288 dim will have ~4.9 MB/token (2 × 100 × 12288 × 2 B ≈ 4.915e6 B).

2. **Log peak context length, not just average.** A workload that averages 9.2K input tokens but has a long tail toward 32K or 128K will have a very different KV cache profile. Log the 95th-percentile context length and re-run the KV arithmetic; the memory floor may shift from fitting on 2×H100 to needing 8×H100. This is especially important for RAG workloads, where the retrieved context may average 8K but occasionally peak at 32K+ for technical documents.

3. **Measure inference residency as weights + KV, not weights alone.** It is common to see the 140 GB weight footprint (70B FP16) fit across **two** 80-GB accelerators and conclude that 160 GB is sufficient. But 140 GB of weights leaves only ~20 GB before runtime/workspace and KV are added; at 9.2K input the KV cache adds ~24.1 GB, pushing the total to ~164.1 GB — already over the 160 GB aggregate, so the model does *not* fit on two accelerators once KV is counted. Always include KV when we state the memory floor for inference.

4. **Account for KV quantization when reporting residency.** If the serving stack uses FP8 KV, the per-token KV cost drops from ~2.62 MB to ~1.31 MB (raw tensor byte-halving, exactly 50% of BF16 = 2,621,440/2 = 1,310,720 B = 1.25 MiB), and the 9.5K max residency falls from ~165 GB to ~152 GB (weights 140 GB + KV 12.45 GB). State both the BF16 and FP8 residency numbers, because the choice of KV dtype changes the hardware requirement decisively. **Note the accounting basis:** the ~1.31 MB/token figure is the raw tensor byte-halving of the same

MHA tensors (one byte per K/V element, exactly half of BF16's two bytes); it is NOT a vendor-measured serving footprint, and any block-layout or per-token scale/offset metadata overhead is not included. **Do not generalize a fixed ratio to all FP8-KV deployments:** the realized per-token footprint depends on the engine version, cache-block layout, scale/offset metadata, allocator rounding, and the accounting boundary (logical payload vs allocated cache vs observed resident memory), so re-derive it for the target serving stack rather than inheriting a multiplier. (For reference, the 9.5K total at this byte-halving basis is ~152 GB — still above a single H100, but now within 2×H100, 160 GB.)

7.5. Common Mistakes

- **Assuming KV cache size scales sub-linearly.** The KV cache grows linearly with context length. Doubling the context from 9.2K to 18.4K doubles the KV memory, all else equal. There is no automatic compression unless the attention mechanism itself is hybrid or sparse.
- **Using the 8-bit KV figure (~1.3 MB/token) at FP16.** Chapter 1's ~1.3 MB/token is explicitly at 8-bit precision. At FP16, the per-token KV cost is ~2× that, ≈2.62 MB/token (2.5 MiB — §7.4). Mixing the two figures produces wrong residency calls.
- **Ignoring the weight + KV residency contrast.** Quoting only the weight footprint (140 GB for 70B FP16) and claiming it fits on one H100 (80 GB) is a category error. Weights alone exceed one H100; KV must be added.
- **Quoting one KV-quant reduction for every precision.** KV cache quantization must be read per bit width: FP8 KV ≈50% of BF16 (raw byte-halving) is what serving stacks realize today, while 4-bit KV's raw bound is a full 4× (2.62 ⟶ 0.66 MB/token here; 0.52 ⟶ 0.13 for a 7B, §12.3) — realized savings land between, once block/scale metadata is counted. (The vLLM "54%" figure is a decode inter-token-latency slope ratio, not a memory ratio.) Weight-only quantization's 2×–4× applies to weights; do not transfer an expectation across precisions or across tensors without naming the bit width.
- **Overlooking the fine-tuning residency floor.** Full fine-tuning of 70B requires ~1.12 TB with Adam optimizer states — roughly 1.75× the 8×H100 host. This is not a temporary overhead; it is the permanent memory floor for the training duration.

7.6. Architecture Consequence

The memory floor is the first constraint every architecture decision respects, because unlike compute or bandwidth it cannot be moved by better kernels — it is fixed by weights + KV + (for training) optimizer state. Several concrete consequences follow for the canonical enterprise-Q&A workload:

- **Model residency decides host count.** A 70B FP16 model (140 GB weights) at the 9.5K max context (9.2K in + 300 out) needs ~24.9 GB of KV cache (FP16), so the max end-of-generation residency ≈ 165 GB — it does *not* fit on a single 80 GB H100, nor within the 160 GB aggregate of 2×H100 (160 GB < 165 GB). By *aggregate memory capacity* it needs ≥ **3×80 GB** (240 GB) — but note this is an **aggregate-HBM lower bound on card count, NOT a validated 3-way tensor-parallel configuration**: whether three 80-GB cards actually admit a 70B model depends on head/layer shard divisibility, KV-head routing, TP=3 support, workspace/communication layout, and per-rank fragmentation, none of which the aggregate sum establishes. A practical TP topology (e.g. TP=4 or TP=8) must be checked against the serving engine and model geometry before three cards are treated as deployable. The canonical single host of 8×H100 (640 GB) is not justified by basic capacity alone — three 80 GB GPUs already clear the 165 GB residency floor; the 8×H100 host is chosen for compute, bandwidth, topology, concurrency, implementation constraints, and headroom. [ILLUSTRATIVE][DERIVED]

- **KV cache quantization buys back memory, not compute.** FP8 KV ≈ 50% of BF16 (raw byte-halving), dropping the 9.5K max residency from ~165 GB toward ~152 GB. This is a *memory* lever, orthogonal to bandwidth/compute fixes — the architect pulls it when the KV floor, not decode bandwidth, binds.

- **Fine-tuning is a different memory regime than inference.** The same model that serves in ~165 GB demands ~1,120 GB under full Adam fine-tuning (weights 140 GB + gradients 140 GB + Adam m/v/master states 840 GB) — roughly 1.75× the 8×H100 host. This is why the architect separates the serving fleet from the training fleet: the memory floors differ by an order of magnitude. [ILLUSTRATIVE][DERIVED]

- **Context length is the largest controllable KV lever.** Doubling context from 9.2K to 18.4K doubles KV (~24.1 GB ⟶ ~48 GB); 128K context drives KV to ~335 GB, which forces quantization or model parallelism. The architecture must set a context-length ceiling to keep the served model within host memory. [ILLUSTRATIVE][DERIVED]

In short: the architect sizes the host by weights + KV at the longest supported context, treats KV quantization as a spare memory dial, and keeps inference and training on separate memory-planning tracks.

7.7. What We Still Don't Know

- Per-model KV state beyond K/V — the additional per-head state and per-layer scale/offset metadata some attention implementations store alongside keys and values. The `2 × layers × n_KV-heads × head_dim × bytes` formula prices the K/V entries themselves (§7.3 covers GQA/MQA exactly by substituting the model card's KV-head count), but the extra per-token

bytes an implementation adds on top of K/V are not derived in this chapter and must be established per architecture and serving stack.

- Quality loss from aggressive KV quantization (2-bit KIVI, or sub-4-bit schemes) at very long context lengths (128K+, MoE experts). The primary sources anchor FP8 KV ≈50% of BF16 (raw byte-halving) at near-zero quality loss, but 2-bit asymmetric patterns and their interaction with RoPE and sliding-window layers are not fully mapped.


- Whether per-request KV caching can be partially offloaded to CPU DRAM during decode without TTFT impact, beyond the vLLM KV Offloading Connector's 2–22× TTFT reduction range [S7][1P][FACT], which is highly prompt-size-dependent. The community is converging on tiered KV storage (GPU resident hot set + CPU/DRAM cold set), but the latency trade-offs at concurrency > 1 are not yet primary-anchored.

- **Frontier 2026 has begun re-engineering the KV constant factor, not just quantizing it.** All four 2026-class open architectures attack KV cache size at the attention layer itself, on top of the per-token footprint this chapter derives: DeepSeek-V4's hybrid CSA+HCA reports KV cache at only ~10% (Pro) / ~7% (Flash) of DeepSeek-V3.2 at 1M-token context [1P: arXiv 2606.19348]; GLM-5.3-Flash's sparse+linear hybrid reports ~4.4×KV reduction [1P: HF zai-org/GLM-5.3-Flash]; Kimi K3's Kimi Delta Attention + Attention Residuals targets information flow across long sequences [1P: arXiv 2607.24653]; Qwen3.8-Flash-Next combines Gated DeltaNet (compress history) with Qwen Sparse Attention (micro-block indexing) for long-context cost [1P: HF Qwen/Qwen3.8-Flash-Next]. For the architect this is a decisive shift: the KV arithmetic in this chapter (per-token × context) is *not* a fixed constant across model generations — a 2026 hybrid-attention model can hold dramatically more context per byte of KV than the canonical 70B/8×H100 framing assumed. Size the host against the *specific* model's KV scheme, not a universal constant.

- The impact of MoE routing on KV cache: does each token really emit a full key/value per layer across all experts, or does routing activate only a subset? The total-vs-active and MoE-vs-dense facts of Ch 3 (total parameters ≠ active parameters per token; MoE gives compute sparsity, not weight-residency sparsity) confirm that attention layers process every token densely and emit key/value per token, so MoE sparsity does not reduce KV — but the constant factor for MoE models (e.g., number of experts per layer) needs per-model validation.

7.8. End-of-Chapter Mini-Case: Sizing Memory First for the 5,000-Employee Wiki

An architect is asked to design an internal Q&A system over the company's document repository. The initial ask is vague: "We need to let all 5,000 employees ask questions over our internal wikis."



FP8 shown as raw tensor byte-halving (exactly 50% of BF16, ~1.31 MB/tok)
— not a vLLM-measured serving footprint.

FIGURE 7.2: KV cache size vs context length, canonical 80-layer reference geometry (full-MHA vs GQA, FP8/8-bit): **parameter count does not determine KV size** — KV per token is set by the *attention shape* (layers × KV-heads × head-dim × precision), so a 70B full-MHA and a 70B GQA differ; full-MHA is the conservative upper-bound baseline, GQA ~8× smaller. **Scope:** FP16 ~2.62 MB/token, FP8/8-bit ~1.31; at 128K the FP16 KV footprint is ~335 GB (vs the ~436 GB KV budget), ~24.9 GB at 9.5K (total weights+KV residency then ~165 GB, §7.1). The FP8 value is raw byte-halving (50% of BF16), not a vLLM-measured footprint — block/scale-metadata not included (Table 7-1).




FIGURE 7.3: Inference vs fine-tuning memory floor. The same 70B model serves in ~165 GB (weights + KV, max 9.5K) but needs ~1,120 GB for full Adam fine-tuning; QLoRA fits ~50–70 GB on a single GPU.




FIGURE 7.4: The concurrency budget: where a 70B (canonical 80-layer full-MHA teaching geometry) host's 640 GB pool goes. **Aggregate-feasibility caveat:** the 640 GB figure is an *aggregate* across eight 80-GB H100s, not a single freely-allotable heap. Whether a given allocation actually fits depends on tensor-parallel sharding, KV partitioning, replication, runtime layout, per-rank fragmentation, workspace requirements, and communication topology — so "total bytes < total HBM" is a necessary but not sufficient test. Per-rank fit and sharding must also be validated (Chapters 9–10). **Per-rank example (TP=8):** the 140 GB of weights shard to ~17.5 GB per GPU; the ~64 GB runtime/NCCL reserve is per-host (not per-rank); the ~436 GB KV budget shards to ~54.5 GB per GPU, and under tensor-parallel attention the per-request KV (24.9 GB) also shards across the 8 ranks, so the per-rank KV per request is ~3.1 GB — the 17.5 concurrent figure is the *aggregate* bound, and the per-rank fit must be checked separately (a rank can be the binding constraint even when the aggregate fits). The figure shows the one dominant budget relationship: the on-host pool decomposes into weights + runtime + a leftover KV budget, and that KV budget divided by the per-request KV price sets concurrency. 140 GB weights + ~64 GB runtime/NCCL leaves ~436 GB of KV budget; at the 24.9 GB/request max-FP16 KV that gives $C \approx 17.5$ concurrent requests (byte-accurate $436 \div 24.9037 = 17.51$; the conservative integer "requests that fit" floor is 17, not 18), and FP8 (~12.45 GB/request) roughly raises it to ~35.0. This is the arithmetic behind the single-host capacity in Ch17. **This is an analytical upper bound, not a validated concurrent-request count** — the actual achievable concurrency must be measured under the target workload (Ch 14).




FIGURE 7.5: Memory Tetris: how the 8×H100 host's 640 GB **aggregate** pool fills at 9.5K / 32K / 128K for the canonical 80-layer full-MHA 70B. **Takeaway: context length is the dominant memory lever** — the FP16 KV cache (orange) is the only block that grows, consuming the fixed ~436 GB KV budget (~17.5 concurrent at 9.5K, floor 17; only ~1–2 at 128K). **Aggregate-feasibility caveat:** an aggregate residency test, not a proof each allocation maps onto per-rank HBM — the 80 GB rank-boundary lines are a *visualization guide*; sharding, KV partitioning, fragmentation, interconnect must be validated per rank.

Before any architecture can be defended, the architect must turn this vague desire into a machine-denominated statement using the chapter's core constraint.

From the unit-and-token work of Ch 1 alone, the architect can already establish several facts. The unit is tokens; the request shape will be prompt + retrieved context + output; the workload is input-heavy (retrieved context dominates); and the first number to lock down is tokens-per-request, because every downstream decision (which model fits, how much memory, what latency is possible) is priced against it.

Running the KV arithmetic: if each request uses ~9.2K input tokens (the canonical ~1,200 prompt + 8K retrieved) plus ~300 output tokens, the request grows to a **9.5K max KV sequence** by the end of generation. The KV cache per request at 70B FP16 is ~24.9 GB (max, 9.5K), against ~24.1 GB for the initial 9.2K-prefill residency. The weight footprint is 140 GB. Total max inference residency is ≈165 GB, which does **not** fit within the nominal 160 GB aggregate HBM of 2×80 GB H100s; practical deployment therefore requires additional capacity, lower precision, or a larger GPU configuration. It fits comfortably within the 640 GB aggregate HBM of an 8×H100 host. If the context is extended to 32K (e.g., wider document retrieval), the KV cache rises to ~84 GB, pushing total residency to ~224 GB — still fitting in 8×H100 but requiring a multi-GPU node.

The architect can now speak the system's currency: tokens, KV bytes, and the residency floor. The next step — turning "5,000 employees" into ~2,000 registered users (~100 concurrent at peak), ~10 requests/s, and a specific model-and-hardware choice — is Chapter 4's job (workload anatomy). Here the point is narrower and sharper: we can now say, with quantified memory numbers, whether the system fits on the available hardware, and we can compare inference vs. fine-tuning residency floors before committing to an architecture decision. This is the chapter's payoff: the vague request has been translated into concrete constraint numbers, and the architect can defend a recommendation based on whether the workload fits, not on intuition alone.

CHAPTER 8.

Compute

The Architect's Question

After chapters on tokens, workloads, and memory, the architect naturally asks: *how much compute does this actually require, and at what point does the hardware cease to be the limiting factor?* This chapter gives us the FLOP-scale arithmetic, the arithmetic-intensity roofline, and the utilization framework that lets us answer that question without guessing. We will move from per-token FLOPs to prefill PFLOP counts to sustained MFU on real hardware, and then to the roofline that tells us whether a given layer is compute-bound or memory-bound — the difference that decides whether we should reach for batching, quantization, or a different hardware generation. Throughout, the arithmetic anchors to the canonical enterprise-Q&A RAG scenario (Ch 4, Table 4-2): ~10 rps average / ~40 rps peak traffic, with 70B FP16 weights and an 8×H100 host. KV cache per-token figures are referenced at FP16 (~2.5 MB/token) unless an 8-bit (~1.3 MB/token) variant is explicitly stated.

8.1. Concept

Compute in a language model is priced in floating-point operations, or FLOPs. Every matrix multiplication, every attention weight update, every activation function evaluation contributes to the total. The architect's first principle is that FLOPs scale linearly with parameter count and context length, but the *efficiency* with which those FLOPs are executed depends on the hardware ridge point and the arithmetic intensity of the kernel.

For a dense transformer layer, the dominant cost is the matrix multiplication — query-key, value-aggregation, and MLP projections. In FP16, a single multiply-add counts as two FLOPs. The per-token cost is therefore approximately 2 ×N FLOPs where N is the number of active parameters.

This is the arithmetic baseline: every token processed costs roughly two floating-point operations per parameter.

But FLOPs alone do not tell the full story. The hardware can only execute FLOPs if data is available — weights, activations, and KV cache all compete for the same HBM bandwidth. The arithmetic intensity (FLOP/byte) determines whether a kernel is compute-bound (intensity above the ridge point) or memory-bound (intensity below). This roofline model is the central diagnostic tool of this chapter: it tells us, for any given layer and precision, whether increasing FLOPs will actually reduce latency or whether we are already starved for bytes.

> **Three different "bounds" — keep them apart.** Throughout this book, three words that all contain "bound" mean three different things, and conflating them is a real error. **Compute-bound** means performance is limited primarily by arithmetic throughput (the kernel sits above the ridge; it is starved for FLOPs). **Memory-bandwidth-bound** (what the roofline calls "memory-bound") means performance is limited by memory-transfer bandwidth (the kernel sits below the ridge; it is starved for bytes moving per second). **Memory-capacity-constrained** (equivalently KV-capacity-constrained) means feasible concurrency or context is limited by *how much data fits in HBM* — not by how fast it moves. The canonical RAG workload illustrates all three without overlap: prefill is compute-bound (high intensity), decode is bandwidth-bound (low intensity), and long input raises KV residency, which capacity-constrains how many requests can be resident at once. "Input-heavy" does **not** by itself mean "memory-bound" — it tends to raise prefill compute *and* KV-capacity pressure, two distinct effects. When the book says "memory-bound" without qualification, it means *bandwidth-bound* in the roofline sense; capacity pressure is stated explicitly.

The chapter unfolds in four parts. First, the core arithmetic: FLOPs per token, prefill PFLOP counts, and H100 sustained utilization. Second, the roofline: why early layers are compute-bound while later layers and decode are memory-bound. Third, the canonical scenario arithmetic: 70B on 8×H100, TTFT 1.2 s, TPOT ~25 ms. Fourth, the mini-case: a continuous deployment scenario that threads the prefill/decode divide.

8.2. Mental Model

FLOPs are like the distance a car can travel on a gallon of fuel: it tells us the system's capacity, not how long the trip will take. The trip time is determined by the ridge point: if the arithmetic intensity is below the ridge, adding more FLOPs won't help because we are waiting for data. If we are above the ridge, we are limited by how fast the compute can chew through operations. The roofline chart — peak TFLOPS on the vertical axis, FLOP/byte on the horizontal — is the map that resolves




FIGURE 8.1: Where inference computation and data movement actually live. The hierarchy runs from the smallest/fastest/closest resource (registers, tensor cores, on-chip SRAM) to the largest/slower/farther (HBM, GPU interconnect, other GPUs). Inference work maps onto it: matrix multiply runs on the tensor cores; model weights and the KV cache are predominantly HBM-resident; FlashAttention restructures attention to tile through on-chip memory and cut HBM traffic; tensor-parallel (TP) communication crosses the GPU interconnect; pipeline-parallel (PP) communication moves activations between pipeline stages. The gradient of speed↔capacity↔distance is why compute, memory bandwidth, memory capacity and interconnect bandwidth are *distinct* architectural constraints — each is a different level of this ladder. **Schematic note:** the vertical ordering is a *relative* speed/capacity/distance ranking, not a measured timing scale — the gaps between levels are not to scale, and the same physical resource (e.g. HBM) can appear at different logical positions depending on the access pattern.

this. Where our kernel lands on that chart decides whether we should profile memory bandwidth or compute throughput.

Read this ladder together with the roofline: the roofline's vertical axis (peak TFLOPS) and horizontal axis (FLOP/byte) are both determined by *where* on this hierarchy the work sits. A kernel is compute-bound when its FLOPs run on the tensor cores and data fits in on-chip memory (high arithmetic intensity); it is bandwidth-bound when it must stream large tensors from HBM faster than the bytes can move (low arithmetic intensity). So the "bound" classification of Ch. 8 is not a property of the model alone — it follows from where the model's weights and the KV cache happen to be resident, and how much of the computation a kernel can keep on-chip. Ch. 15's FlashAttention discussion is exactly this ladder in action: keep more of the tile on-chip, move fewer bytes between HBM and the compute units.

8.3. Worked Example: Canonical Scenario Arithmetic

The canonical scenario (Ch 4, Table 4-2) is an enterprise Q&A system: the canonical 80-layer, hidden-8192, full-MHA 70B reference (a 70B-class dense model), FP16 weights (~140 GB), 1 host with 8×H100-class GPUs (80 GB each), average prompt 1,200 tokens + 8K retrieved context (~9.2K input), 300-token output, TTFT budget 1.2 s (retrieval ~120 ms + prefill), TPOT budget ~25 ms/token.

Scope. "1 host with 8×H100" here is a **per-host / per-request** feasibility container (does one host meet one request's latency and memory SLO). It is **not** a claim that one host absorbs the 40 rps peak arrival rate — as Ch 17 derives, that peak puts in-flight concurrency $\lambda \cdot W \approx 344$ at the ~8.6 s service time, far above one host's KV-residency ceiling ($C \approx 17.5$, conservative integer floor 17), so the *fleet* needs ~20 hosts. The compute/roofline arithmetic of this chapter answers the per-request and per-host-shard question; the fleet question is a separate multiplication that Ch 17 performs (with the cost basis in Ch 16). We keep them distinct because each requires measuring against a different quantity (a latency budget vs an arrival rate).

8.3.1. FLOPs per token

For a 70B-parameter dense model in FP16, the per-token forward FLOP count is approximately:

$$\text{FLOP}/_{\text{token}} \approx 2 \times N = 2 \times 70 \times 10^9 \approx 140 \text{ GFLOP/token}$$

[DERIVED: 2 FLOPs/parameter × 70 ×10^9 params; standard dense-forward arithmetic, which is the same 2×N rule that gives, e.g., a 175B dense model 2 × 175 × 10^9 ≈ 0.35 TFLOP/token]

This applies to both prefill and decode: each token that enters the forward pass costs ~140 GFLOP. The distinction between prefill and decode is not in the per-token FLOP count but in the data movement pattern — prefill reads the full context once, while decode re-reads weights per token.

8.3.2. Prefill PFLOP for 9.2K input

For a single request with 9.2K input tokens, the prefill FLOP cost is:

$$\text{prefill FLOPs} \approx 2 \times N \times L = 2 \times 70 \times 10^9 \times 9.2 \times 10^3 \approx 1.29 \text{ PFLOP}$$

[DERIVED: 2 × N × L where N=70B, L=9,200; the figure is large because the full context is attended to, but it is a one-time cost per request, not a sustained rate]

Accuracy of the 2 ×N × L approximation. This linear prefill count omits the quadratic attention term, $\approx 4 \times n_{\text{layers}} \times L^2 \times d$. At the canonical 9.2K context that correction is small — roughly **+17%** of the 1.29 PFLOP — so the 2NL roofline is a sound teaching baseline there. But the omission grows with context: at 32K the attention term is ~**+60%** of the linear term and at 128K it *dominates* (~2.4× the linear term, ≈+240%). An architect sizing long-context prefill must add the quadratic term or measure it; the Unknowns section returns to this.

At 10 requests/s, the sustained prefill throughput demand is:

$$\text{prefill demand} = 1.29 \times 10^{15} \text{ FLOP} \times 10 \text{ rps} \approx 12.9 \text{ PFLOP/s}$$

[DERIVED]

Table 8-1 — Per-token FLOP cost, prefill PFLOP, and the derived prefill and roofline rates for the canonical 70B workload. *(Per-token FLOP and prefill PFLOP computations are [ILLUSTRATIVE] [DERIVED] from 2 × params × tokens; hardware peaks [1P: vendor datasheet] or [1P][FACT]; the 30–40% MFU range is [2˚: industry benchmarks]; the ~295 FLOP/byte ridge is [2˚][DERIVED] = 989 TFLOPS ÷ 3.35 TB/s.)*

metric	value	derivation
per-token FLOPs (forward)	~140 GFLOP/token	2 ×70B params [DERIVED; standard dense-forward arithmetic — the same 2×N rule gives 175B ≈ 0.35 TFLOP/token]
prefill FLOPs for 9.2K input (linear only)	~1.29 PFLOP	2 ×70 ×10^9 × 9.2 ×10^3 [DERIVED; **parameterized-linear term — excludes the quadratic attention term**, see Ch 22]
sustained prefill demand @ 10 rps	~12.9 PFLOP/s	1.29 PFLOP × 10 [DERIVED]

metric	value	derivation
H100 peak FP16 TFLOPS	~989 TFLOPS [1P: NVIDIA H100 datasheet]	NVIDIA H100 SXM5 datasheet, without sparsity
H100 sustained MFU (typical)	30–40% [2°: industry benchmarks]	~346 TFLOPS sustained at 35% MFU
prefill throughput per GPU	~2,471 tokens/s	346 TFLOPS ÷ 140 GFLOP/token [DERIVED; **per-GPU scope**]
prefill throughput per host (8×H100)	~19,800 tokens/s	8 × 2,471 [DERIVED; **idealized aggregate, before TP/system loss**]
H100 ridge point (dense FP16)	~295 FLOP/byte	989 ÷ 3.35 [DERIVED: peak TFLOPS ÷ HBM bandwidth]

All figures trace to the canonical scenario (Ch 4, Table 4-2) and validated sources; none are measurement claims. This is the prefill compute demand. An 8×H100 node can sustain some fraction of this at MFU (model FLOPs utilization), which we estimate next.

8.3.3. Sustained vs. peak: H100 MFU

NVIDIA H100 SXM5 lists ~1,979 TFLOPS FP16 Tensor Core peak "with sparsity" and ~989 TFLOPS FP16 peak without sparsity [1P: NVIDIA H100 datasheet]. In practice, sustained model FLOPs utilization (MFU) for a well-tuned transformer workload typically runs at 30–40% of peak on H100 [2°: industry benchmark reports, derived from real kernel profiles]. At 35% MFU:

$$\text{sustained} = \text{peak} \times \text{MFU} = 989 \text{ TFLOPS} \times 0.35 \approx 346 \text{ TFLOPS}$$

[1P][2°][DERIVED: vendor peak (1P) × typical MFU (2°) — the MFU range is a secondary, empirical figure, so the sustained value inherits the provenance of its weakest input, the 2° MFU, while the peak is first-party]

Scope matters here. The 346 TFLOPS figure is the sustained rate of a *single* H100, and the 2,471 tokens/s derived from it is therefore a **per-GPU** number. The canonical host is an *8×H100* node, so we must not multiply demand by a per-GPU rate as if it were per-node. Track the scope explicitly as we scale.

Per **GPU** (one H100 at 35% MFU):

$$\text{prefill tokens/s (per GPU)} = \frac{346 \text{ TFLOPS}}{140 \text{ GFLOP/token}} \approx 2{,}471 \text{ tokens/s}$$

[DERIVED: sustained FLOPS ÷ per-token FLOPs; **per-GPU scope**]

Per **host** (8×H100, idealized before TP communication, imbalance, and kernel/system overhead):

$$\text{prefill tokens/s (per 8×H100 host)} = 8 \times 2{,}471 \approx 19{,}800 \text{ tokens/s}$$

or, equivalently, `8 × 346 TFLOPS ≈ 2.77 PFLOPS` sustained ÷ 140 GFLOP/token. [DERIVED: per-GPU × 8; **idealized aggregate, first-order only**]

For 10 rps with 9.2K input tokens each, the prefill demand is ~92,000 tokens/s (from the canonical workload). At ~19,800 tokens/s per host, we would need roughly:

$$n_{\text{hosts}} = \frac{\text{tokens/s demand}}{\text{tokens/s per host}} = \frac{92{,}000}{19{,}800} \approx 4.6 \rightarrow\sim 5 \text{ hosts}$$

[DERIVED: token demand ÷ per-host prefill throughput; **idealized aggregate**]

At the peak 40 rps (368,000 tokens/s) the same arithmetic gives ~18.6 ⟶ **~19–20 hosts**. This aligns — independently — with the KV-residency / Little's-Law fleet sizing derived in Chapter 17, with the cost basis in Chapter 16 (~20 hosts at peak), which is a useful cross-check that the two fundamentally different constraints (prefill FLOP throughput vs. KV residency/service time) point at the same order of fleet.

Honest boundary on both numbers. The per-GPU `2,471 tokens/s` is itself an *analytical* figure at an assumed 35% MFU — not a measured throughput. The `8×` aggregate (`~19,800`/host) is a **theoretical first-order estimate** that assumes perfect tensor-parallel scaleout: it does **not** account for TP communication, per-rank load imbalance, kernel inefficiency under a given batch, or scheduling/system overhead. It is an upper-bound analysis value, not a servable goodput. Actual reachable prefill throughput must come from benchmark goodput under the target workload (Chapter 14). Treat both numbers as scope-disciplined *models*, never as measured capacity.

This rough sizing illustrates that prefill is FLOP-bound at this scale — the compute requirement is the primary constraint, and memory bandwidth (HBM at 3.35 TB/s per H100) is sufficient to keep the compute fed if the kernel is efficient. The ridge point for dense FP16 on H100 is ~295 FLOP/byte (989 ÷ 3.35); the arithmetic intensity of a mature attention kernel sits near or above this ridge, meaning the kernel is compute-saturated rather than bandwidth-starved once the batch is large enough.

8.3.4. Decode: bandwidth-bound at low batch

Reading the roofline (summary of Fig 8.2): the dense-FP16 ridge at ~295 FLOP/byte (H100: 989 TFLOPS ÷ 3.35 TB/s) separates the compute-bound region (right) from the memory-bound region (left). Prefill sits far above the ridge — its arithmetic intensity is set by the sequence length (weights read once, reused across all tokens), so it is compute-bound; decode at batch=1 sits at the far left of the chart (~1 FLOP/byte,




FIGURE 8.2: Per-GPU roofline for dense FP16, one H100 vs one H200 (a per-GPU chart, not a host-level one). Compute ceiling and HBM bandwidth are single-GPU quantities here (989 TFLOPS, 3.35 / 4.8 TB/s), so the ridge point and the memory-bound slope are per-GPU. Conventions: a multiply-add counts as **2 FLOPs** (the FMA convention of §8.1); **dense** (no sparsity) FP16; the ceilings are **peak/theoretical** datasheet values, not achieved rates (sustained MFU is 30–40%, §8.3); the plotted prefill (9.2K input) and decode (batch=1) points are **illustrative operating points**, and a kernel's position on the roofline is a *theoretical* bound on its FLOP/byte intensity — it is **not a measured latency**. Prefill (9.2K input) sits to the right of the ridge, on the compute-bound plateau; decode (batch=1) sits to the left, on the memory-bound slope, and continuous batching climbs the slope as batch grows. The ridge *classification* (compute- vs memory-bound) is unchanged by ideal N-way replication because both peak FLOP/s and HBM bandwidth scale with GPU count; host-level attainable performance additionally depends on sharding and communication.

The roofline: at the canonical long-prompt operating point prefill is compute-bound; at low batch decode is memory-bound.

~295× below the ridge) and is memory-bound. Batching and quantization shift kernels rightward toward the ridge; the distinction between the two phases is the single most important reading of this chart.

For decode, the per-token FLOP cost is the same ~140 GFLOP, but the arithmetic intensity drops sharply. Each decoded token re-reads all 70B weights from HBM (a **batch-1-equivalent** weight-streaming read). A 70B FP16 weight matrix is $70 \times 10^9 \times 2$ B = 140 GB — one full pass reads **140 GB** (batch-1-equivalent), not 280 GB. (The naïve "$2 \times 70 \times 10^9 \times 2$ B ≈ 280 GB" double-counts the FP16 footprint: the leading "2" is already inside the 2-bytes-per-element, so writing $2 \times 70 \times 10^9 \times 2$ B counts the weight bytes twice. Any KV/output-projection reads are a separate, smaller term on top, not a second full weight footprint.) The effective arithmetic intensity is therefore:

$$\text{arithmetic intensity}_{\text{decode}} \approx \frac{140 \text{ GFLOP}}{140 \text{ GB}} \approx 1.0 \text{ FLOP/byte}$$

[DERIVED; a lower-bound bandwidth model — real kernels also read activations and KV, so measured intensity is typically below this and heavily dependent on fusion and cache residency]

This is well below the H100 dense-FP16 ridge of ~295 FLOP/byte, meaning single-stream decode is overwhelmingly memory-bandwidth-bound. Throughput improves with batching because the weight-reread amortizes across tokens — decode intensity ≈ batch size, so at batch=32 the effective intensity is ~32 FLOP/byte, still ~9× below the 295 ridge (compute-bound decode needs batch ≈ 295, or quantized weights, which halve bytes and double intensity), and TFLOP/s utilization increases accordingly. This is why continuous-batching systems (Orca, vLLM) prioritize batch growth: it is the primary lever for pushing decode arithmetic intensity toward the ridge.

Scope note on the single-device roofline here: the 140 GB weight-read and the per-GPU ~3.35 TB/s HBM bandwidth are single-GPU quantities, so the ~1.0 FLOP/byte intensity and the "memory-bandwidth-bound" label above are a *per-kernel / single-device roofline* argument. It is **not** a verdict on the canonical 8×H100 host's actual bandwidth adequacy — under tensor parallelism the 140 GB weight matrix is sharded across GPUs, so each GPU streams only its own shard (~0.70 TB/s against its own ~3.35 TB/s, Ch 6). The classification (low-batch decode is bandwidth-bound) is shard-invariant because it follows from the low arithmetic intensity, not from the aggregate weight-read rate exceeding one GPU's bandwidth.

8.4. Measurement

Three measurable quantities anchor compute sizing:

1. **Per-token FLOP count.** Measure by flops profiling (e.g. NVIDIA Nsight Compute) on the target model and precision. The 2×N rule is a useful prior, but actual count varies by layer depth, activation choice (SiLU vs. ReLU), and whether kernel fusion combines matmuls.

2. **Sustained MFU.** Profile TFLOP/s achieved divided by peak TFLOP/s for the target hardware and precision. A well-tuned transformer on H100 FP16 typically lands in the 30–40% range;

below 20% suggests a memory or communication bottleneck that should be diagnosed before scaling.

3. **Arithmetic intensity (FLOP/byte).** Compute as achieved FLOPs divided by bytes transferred (weights + activations + KV read/write). Compare to the hardware ridge point (H100 dense FP16: ~295 FLOP/byte; H200: ~989 TFLOPS ÷ 4.8 TB/s ≈ 206 FLOP/byte — H200 keeps H100's GH100 die and its dense FP16 peak, trading a bigger/faster HBM3e for bandwidth; GB200: higher on both terms (faster dense BF16 peak and ~8 TB/s HBM), so its BF16 ridge is higher, and its NVFP4 ridge higher again). If intensity is below the ridge, the kernel is memory-bound; above, compute-bound.

8.5. Common Mistakes

- **Assuming 2×N FLOPs/token is exact.** It is a baseline derivation; actual per-token FLOPs vary with layer depth, activation fusion, and kernel fusion. Profile before quoting.
- **Treating prefill and decode as having the same FLOP/byte profile.** Prefill reads the full context once and is FLOP-bound; decode re-reads weights per token and is memory-bound. The arithmetic-intensity roofline distinguishes them.
- **Using peak TFLOP/s as sustained throughput.** Peak includes sparsity or BF16/FP8 variants that may not be available in the chosen precision. Use the FP16 number without sparsity (≈989 TFLOPS on H100) as the baseline for dense compute sizing.
- **Ignoring the batch-size dependence of arithmetic intensity.** A single-token decode batch has very low intensity; batching raises it. Always state the batch assumption when reporting TFLOP/s or tokens/s.
- **Confusing H100 sparsity-inclusive peak (1,979 TFLOPS) with dense peak (989 TFLOPS).** The 2× sparsity figure appears in vendor data sheets but most transformer workloads do not activate sparsity. Quote the dense figure unless the kernel is specifically sparsity-enabled.

8.6. Architecture Consequence

The compute arithmetic and roofline have direct consequences for system design:

- **If prefill is FLOP-bound** (as it is for 70B+ models with long contexts), the primary optimization is batching — larger prefill batches do **not** remove the per-request attention work (each sequence still has its own attention computation); they *improve accelerator utilization* by forming larger matrix operations, amortizing weight and execution overhead across requests, and raising achieved FLOP/s. The relevant lever is the achieved efficiency (MFU) of the prefill kernel, not a change to the per-request FLOP count. System design should therefore provision

for batchable prefill (continuous batching, Orca, vLLM continuous batching) as the first-order throughput lever.

- **If decode is memory-bound** (single-stream, low batch), the primary optimization is batching — decode arithmetic intensity ≈ batch size, so even modest batch sizes (8–16) raise it to ~8–16 FLOP/byte (batch 16 ⟶ ~16, still ~18× below the 295 ridge), improving TFLOP/s utilization without reaching compute-bound; compute-bound decode needs batch ≈ 295, or quantized weights, which halve bytes and double intensity. KV cache quantization (FP8, int8) also reduces bytes per token, raising effective intensity. P/D disaggregation (prefill on GPUs, decode on a separate pool) can rebalance: prefill's FLOP demand is served by compute-optimized GPUs, while decode's bandwidth demand is served by wide-memory GPUs or even CPU offload.
- **If the workload's intensity crosses the hardware ridge** (e.g. a workload at ~250 FLOP/byte is memory-bound on H100's ~295 ridge but compute-bound on H200, whose FP16 ridge is ~206 FLOP/byte — 989 TFLOPS ÷ 4.8 TB/s — from its higher HBM3e bandwidth), the same workload may shift from memory-bound to compute-bound, changing the optimal hardware choice. The shift comes from the *lower* ridge, not from precision: a higher ridge moves the boundary right and makes compute-bound harder (H200's ~412 FLOP/byte ridge in *dense* FP8 — ~1.98 PFLOPS ÷ 4.8 TB/s, never the sparsity-inclusive ~4 PFLOPS (§8.5) — would do the opposite), and precision scaling moves intensity and ridge together (bytes halve ⟶ intensity doubles; peak doubles ⟶ ridge doubles), so FP8 alone does not change the classification. This is why the H200 represents an inflection point where inference and training hardware lines begin to converge [1P: NVIDIA H200 SXM datasheet].

In practice, the architect measures arithmetic intensity for the target workload and precision, locates the kernel on the roofline chart, and then selects hardware and batching strategy accordingly. The roofline is the diagnostic; the architecture decision follows.

8.7. What We Still Don't Know

- **Arithmetic intensity of fused kernels.** Most roofline estimates treat attention or MLP as separate matmuls, but in practice frameworks fuse multiple operations into a single kernel. The effective FLOP/byte of a fused attention+MLP kernel is not well cataloged in primary sources and would require profiling on the target hardware to anchor.
- **MFU across precisions and sparsity.** The 30–40% H100 FP16 figure is a rule of thumb; actual utilization depends on architecture, kernel quality, and batch config. A systematic MFU atlas across H100/H200/GB200, FP16/BF16/FP8, dense/MOE would be a valuable reference.
- **Arithmetic intensity of emerging attention mechanisms.** Linear attention (DeltaNet, MLA), compressed attention (CSA, HCA), and hybrid sparse patterns have different FLOP profiles and data movement. Their roofline position is not yet established in primary sources.

- **Frontier 2026 has begun to answer this.** DeepSeek-V4's hybrid CSA+HCA attention reports that, at 1M-token context, single-token inference drops to ~27% of the FLOPs (Pro) / ~10% (Flash) and KV cache to ~10% / ~7% of DeepSeek-V3.2 [1P: arXiv 2606.19348]. GLM-5.3-Flash's sparse+linear hybrid reports a ~3× attention-compute and ~4.4×KV cache reduction [1P: HF zai-org/GLM-5.3-Flash]. These are [1P] first-party vendor figures, not yet independently reprofiled on our own hardware — which is exactly the arithmetic-intensity measurement an architect should still do before trusting a vendor's roofline claim for their own workload.

- **How quantization shifts the ridge.** Moving from FP16 to FP8/int8 changes peak TFLOP/s and bytes-per-operand, shifting the ridge point. The net effect depends on the quantization scheme (element-wise vs. per-tensor, dynamic vs. static) and whether the kernel is re-tuned for the lower precision.

8.8. End-of-Chapter Mini-Case: Continuous Deployment Scenario

An architect is brought into an ongoing deployment of a 70B-class Q&A system on 8×H100 GPUs. The system is serving ~10 requests/s average with ~9.2K input + 300 output tokens per request, and the TTFT budget is being missed: p95 TTFT is 2.8 s, exceeding the SLO of 2 s. The TPOT of 28 ms/token is within spec, but the prefill delay is the bottleneck.

The temptation is to reach for a roofline and "prove" prefill is memory-bound. That reasoning is wrong here, and the error is worth naming: it is spread by treating prefill like token-by-token decode. In decode, each new token re-reads the weight matrix from HBM, so the arithmetic intensity is ~1 FLOP/byte — genuinely memory-bound. In prefill, the weight matrix is read *once* and reused across the whole sequence; the sequence dimension supplies the matrix-matrix reuse. Prefill's effective intensity is `(2 × N × L) / (N × 2 bytes/param)` = `L` = **9,200 FLOP/byte** at the canonical 9.2K context — ~1.5 orders of magnitude above the ~295 FLOP/byte dense-FP16 ridge. At that operating point prefill is compute-bound, exactly as the rest of this chapter teaches.

So a high TTFT is *not* evidence of a bandwidth problem. The architect does the correct thing: profile the prefill kernel and determine which of several distinct causes is actually limiting it, rather than assuming memory. The profile separates four candidates:

- **Compute-bound** — the GEMMs are saturated at high MFU; more FLOPs/ops per token would not help, but better kernel efficiency (flash-attention, fused MLP) would.
- **Communication-bound** — tensor/pipeline parallelism crosses the NVLink/Host fabric; data movement, not math, is the ceiling. The fix is a different parallelization or a smaller cross-GPU footprint.
- **Launch / occupancy-limited** — the kernel is too small or the grid under-fills the SMs; increasing batch or improving occupancy raises utilization without adding hardware.
- **Attention / memory constrained (within prefill)** — the quadratic attention term, not the linear weights, grows with context; at 128K+ contexts this term dominates prefill cost (at 32K

it is already ~+60% — the 4·n_layers·L^2·d term, Fig 22.1), so the fix is to reduce the attention term (flash-attention, sparse/linear attention), not to batch harder.

The architect measures MFU to choose among these. If the prefill kernel is running at 12% MFU, the problem is occupancy or launch — grow the batch or fuse kernels. If MFU is already near ~40% and the kernel is compute-saturated, then prefill *is* compute-bound and more batch just queues more work without reducing per-request TTFT; the lever instead is kernel efficiency, attention-term control, or P/D disaggregation so prefill's FLOP profile is served by compute-optimized GPUs while decode's bandwidth profile runs on wide-memory GPUs.

The recommendation is therefore: profile first (MEASURE, do not assume), and only then pick the intervention. Batching helps when prefill is occupancy-limited; kernel fusion helps when GEMMs are under-saturated; attention-term control and disaggregation help when the bottleneck is the quadratic attention term or the compute/bandwidth mismatch between phases. The workload's true roofline position, not an assumed "memory-bound prefill," dictates the fix.

Prefill PFLOP also grows with context: 2 ×70B × L tokens scales linearly — ~0.29 PFLOP at 2K ⟶ ~4.6 PFLOP at 32K — so the longer the window, the larger the one-time compute cost of loading it. Sustained throughput (tokens/s) is what matters for continuous serving, and at the canonical 9.2K point the prefill is ~1.29 PFLOP (Table 8-1).

CHAPTER 9.

Communication

The Architect's Question

Before we can place a model across multiple GPUs or across a cluster, we need to know what the interconnect can — and cannot — move. This chapter asks: given a model size, a parallelism strategy, and a traffic pattern (all-reduce, all-gather, reduce-scatter), what is the communication time, and does it dominate the compute budget? We will size the hidden bottleneck that often goes unnoticed until the job stalls.

9.1. Concept

Communication in a distributed LLM system is not a single pipe. It is a hierarchy: each GPU talks to its neighbors over PCIe, nodes within a server meet over NVLink/NVSwitch, racks talk over 200/400 GbE RoCE, and cross-rack or cross-data-center traffic rides InfiniBand. Each layer has a distinct bandwidth ceiling, a distinct latency profile, and a distinct cost per gigabyte. The architect must match the collective operation to the layer where the bandwidth is sufficient, because moving the same data over a slower layer adds minutes to training time or inference latency for no computational benefit.

The collective operations that dominate multi-node training and inference are:

- **all-reduce**: every GPU contributes a gradient fragment; the result (the sum, scaled by 1/N) is delivered to every GPU. This is the workhorse of data-parallel and model-parallel training.
- **all-gather**: every GPU contributes a tensor; every GPU receives the concatenation of all fragments. Used when a model split across nodes needs the full weight or KV cache locally.
- **reduce-scatter**: the inverse of all-gather. Every GPU contributes a fragment; each GPU receives

a portion of the final result, sized 1/N of the input. Used when the full tensor does not need to reside on any single GPU.

The bandwidth each collective consumes depends on three factors: the data volume (bytes), the number of participating nodes (N), and the interconnect's effective bandwidth in the presence of contention. A 70B FP16 model is 140 GB, and its FP16 gradient is the same size — the §9.3 worked example all-reduces that 140 GB gradient tensor. An all-reduce of a 140 GB tensor across 8 GPUs on a single node moves 140 GB over NVLink; across 8 nodes connected by InfiniBand it moves 140 GB (or more, depending on the algorithm) over the fabric. The same 140 GB over a 25 Gb/s Ethernet link (≈ 2.5 GB/s practical-effective) takes ≈ 56 s — about 350× the ≈ 0.16 s over a 900 GB/s NVLink (§9.2, §9.3).

Table 9-1 — The interconnect hierarchy

Layer	Example	Bandwidth	Latency	Cost	[source]
Chip-to-memory	HBM3 (H100)	3.35 TB/s	~ns	—	[1P][FACT]
GPU-to-GPU (in-node)	NVLink (H100)	900 GB/s per GPU, bidirectional aggregate	~us	high capex	[1P][FACT] (NVIDIA NVLink)
GPU-to-CPU / NIC	PCIe Gen5	~64 GB/s per x16 direction	~us	low	[1P][FACT]
Node-to-node (rack)	RoCE / Ethernet 400Gb/s	~50 GB/s per port	~us	medium	[1P][FACT]
Rack/cluster	InfiniBand HDR/NDR	200/400 Gb/s ≈ 25/50 GB/s per port	~us	high capex	[ILLUSTRATIVE] [DERIVED]

(Hierarchy: bandwidth drops ~2–3 orders of magnitude from HBM to the cluster fabric — the reason the interconnect, not the GPU, often binds at scale. Figures are established hardware specs [1P][FACT], except where a row is tagged otherwise.)

9.2. Mental Model

The interconnect is best read as a series of concentric rings. The GPU sits at the center, reached by the fewest hops (PCIe). One ring out is the node: GPUs on the same server are joined by NVLink and NVSwitch, forming a high-radix, low-latency mesh. The next ring out is the rack: 100/200/400 GbE RoCE connects nodes. The outermost ring is the cluster or data center: InfiniBand HDR (200 Gb/s) or NDR (400 Gb/s) stitches racks into a single logical network. A well-designed deployment keeps the heavy collectives (all-reduce, reduce-scatter) on the inner rings and reserves the outer rings for less volume or latency-tolerant traffic.

The arithmetic is relentless. If all-reduce moves 140 GB and the NVLink bisection provides 900 GB/s of total bidirectional bandwidth per GPU (450 GB/s per direction; 18 NVLink 4.0 links × 50 GB/s bidirectional, NVIDIA H100 datasheet), **a lower bound** on time is 140 GB ÷ 900 GB/s ≈ **0.16 s [1P][DERIVED]** — note the word *lower bound*. The actual completion time of a real collective is higher because a collective is not one flat transfer but a sequence of message-passing and reduction steps across the topology:

$$T_{\text{collective}} \approx \alpha \times n_{\text{steps}} + \frac{\text{bytes}}{\beta}$$

where α is the per-step latency (message setup, synchronization), β is the achieved (not peak) bandwidth, and n_{steps} is the number of message-passing/reduction hops. (For a flat transfer $n_{\text{steps}} = 1$.) The 0.16 s figure uses only the bytes/β term at peak bandwidth; real NCCL all-reduce on NVLink lands tens of % above it once per-step overhead, ring stages, and topology routing are included. So treat the `bytes ÷ bandwidth` form as a *sizing lower bound*, and reserve measured `nccl-tests` numbers (§9.4 Measurement) for capacity decisions. The relative ranking between interconnects is what matters most here: if those same 140 GB travel over a 200 Gb/s HDR InfiniBand link (≈ 25 GB/s effective unidirectional) it is ≈ 5.6 s — ~35× longer; over 25 Gb/s Ethernet (≈ 2.5 GB/s practical-effective, §9.3) ≈ 56 s. (These are flat single-rail lower bounds, 140 GB ÷ bandwidth. The §9.3 ring-model worked example uses the multi-rail effective bandwidth (40 GB/s) plus the 1.75 ring factor, giving ≈ 6.1 s (IB) and ≈ 98 s (RoCE) — the same ranking, a slightly higher absolute time.) The interconnect choice is a first-order determinant of wall-clock time in all cases.

9.3. Worked Example

Take the canonical scenario: a 70B dense model in FP16, whose weight tensor is 140 GB. Using the same FP16 precision for the gradient gives a gradient tensor of the same size, so every all-reduce moves a gradient tensor of $M = 140$ GB per rank. (Note: this assumes an FP16 gradient, which is the common mixed-precision training case. Ch 10's data-parallel worked example instead uses an FP32 gradient of $70 \times 10^9 \times 4$ B ≈ 280 GB — the two differ only by gradient precision, and the communication time doubles accordingly. State the gradient dType explicitly before quoting a sync size.) We underline that this example is best read as a *cross-node* data-parallel setting (options B and




FIGURE 9.1: All-reduce time vs data volume, by interconnect tier (ANALYTICAL). The plot is marked in-figure as analytical, not measured network performance: each curve uses the EFFECTIVE bandwidth of its tier (NVSwitch 1.8 TB/s — the next-generation/Blackwell-class tier §9.7 describes as "toward 1.8 TB/s aggregate", not the H100's 900 GB/s in-node tier of Table 9-1 — NVLink 0.9 TB/s, InfiniBand ~40 GB/s, RoCE2 ~2.5 GB/s) with the large-N ring factor $t \approx 2 \cdot V/B$ ($2(N-1)/N \longrightarrow 2$ as N grows; for N=8 it is 1.75). These effective values — not the nominal per-port peaks (IB HDR 25 GB/s, NDR 50 GB/s, RoCE 400GbE 50 GB/s; Table 9-1) — are what the §9.3 worked example uses, so the figure and the example agree (IB ~6.1 s, RoCE ~98 s at 140 GB). The 140 GB vertical line marks the §9.3 worked-example payload: a data-parallel **gradient** all-reduce of a 70B FP16 model (the gradient tensor is the same size as the weights in FP16). It is a *training* collective, not an inference one — §9.5 shows that per-step inference communication is activation- or KV-fragment-sized (tens of MB), and that re-fetching the 140 GB of weights each step is a pathological anti-pattern, not a baseline.

C): a single 8×H100 host holds only ~640 GB, so it cannot fit eight full 140 GB replicas at once. For any N ranks, a ring all-reduce sends $2\frac{N-1}{N}M$ through each rank — for $N = 8$, that is $1.75 \times 140 \approx 245$ GB — which is what the ring-adjusted times below reflect. Let us compute the communication time under three interconnect options.

Option A — NVLink on a single host. H100 GPUs provide 900 GB/s bidirectional NVLink bandwidth per GPU, and NVSwitch aggregates bisection bandwidth. For an all-reduce of 140 GB across 8 GPUs on one host, the effective bandwidth is close to the per-link peak because NVSwitch can forward multiple concurrent channels without severe contention. A lower bound on the pure-bytes time is

$$T = \frac{M}{B_{\text{eff}}} = \frac{140 \text{ GB}}{900 \text{ GB/s}} \approx 0.16 \text{ s}$$

That is not the whole story: a ring all-reduce moves $2\frac{N-1}{N}M$ per rank (for $N = 8$, $1.75 \times 140 \approx 245$ GB), so the ring-adjusted estimate is $T_{\text{ring}} \approx 2\frac{N-1}{N}\frac{M}{B_{\text{eff}}} = 1.75 \times 0.16 \approx 0.27$ s, before any per-step latency term or staging overhead.

Option B — InfiniBand across 8 nodes, one GPU per node. HDR InfiniBand delivers **200 Gb/s per link** (≈ 25 GB/s before link coding; NDR doubles this to 400 Gb/s). InfiniBand uses a 64b/66b line code, so the useful payload sits a bit below the line rate. A ring-all-reduce or tree-all-reduce across 8 nodes will see lower effective bandwidth due to multi-hop forwarding and congestion. A realistic *effective* throughput is roughly 40 GB/s (aggregated across 2 HDR rails/ports per node — the multi-rail effective bandwidth referenced in §9.2 and Fig 9.1). Using the ring model:

$$T_{\text{ring}} \approx 2\frac{N-1}{N}\frac{M}{B_{\text{eff}}} = 2\frac{7}{8}\frac{140 \text{ GB}}{40 \text{ GB/s}} \approx 6.1 \text{ s}$$

Option C — 25 Gb/s Ethernet (RoCE2) across 8 nodes. 25 Gb/s ≈ 3.125 GB/s unidirectional. With protocol overhead and multi-node tree contention, a practical effective bandwidth might be 2.5 GB/s. Ring model:

$$T_{\text{ring}} \approx 2\frac{7}{8}\frac{140 \text{ GB}}{2.5 \text{ GB/s}} \approx 98 \text{ s}$$

These numbers illustrate the scale: moving from NVLink to InfiniBand adds ~22× latency, and forcing the same all-reduce over Ethernet adds ~350× latency. In a training job where 100 all-reduce steps run per iteration, the NVLink path adds ~27 s of communication per iteration, the InfiniBand path adds ~610 s, and the Ethernet path adds ~9,800 s. The latter two would effectively serialize the training, turning a minutes-long job into an hours- or days-long one.

The worked example also highlights why model parallelism and pipeline parallelism exist: when a single GPU cannot hold the model, splitting it across nodes moves the communication from the inner rings to the outer rings, and the architect must budget the extra seconds per collective against the savings from fitting a larger model.

9.4. Measurement

Measuring communication in situ is harder than counting tokens, because the bandwidth numbers above are peaks; real systems see lower effective bandwidth due to congestion, operating-system interference, and protocol overhead. Three practical measurements an architect can make:

1. **Bandwidth benchmark per link.** Use `nccl-tests` or `ib_write_bw` / `bwperf` to measure achieved bandwidth on PCIe, NVLink (via NVIDIA's Nsight), RoCE, and InfiniBand. Record the unidirectional and bidirectional throughput for payload sizes matching the collective (typically 1 MB–1 GB). These numbers anchor the arithmetic to the real hardware.

2. **Collective latency and throughput.** Run `nccl-tests` all-reduce micro-benchmarks varying the number of GPUs (1, 2, 4, 8) and the tensor size (from 100 MB up to 140 GB). Plot time vs. size and extract the slope — that slope is the effective bandwidth the collective will see in production. Compare the slope across 1 node, 2 nodes, 4 nodes, to see where the interconnect ceiling is hit.

3. **End-to-end training iteration time.** Instrument the training loop to separate compute time (FLOPs) from communication time (all-reduce collectives). Many frameworks (PyTorch Distributed, vLLM, Deepspeed) already expose a per-iteration breakdown. The communication time per iteration, divided by the number of all-reduce steps, gives the average per-collective latency, which we can compare against the benchmark numbers above.

The key invariant: always measure on the same hardware and software stack that the production job will use. A benchmark run on a clean VM with no other traffic will overstate the achievable bandwidth compared to a crowded cluster.

9.5. Common Mistakes

- **Assuming peak bandwidth is sustained.** PCIe Gen5 x16 peaks at ~64 GB/s, but a single all-reduce never saturates the full link because the traffic is split across multiple GPUs and multiple links. Measured effective bandwidth is typically 40–60% of peak; design against the measured number, not the spec sheet peak.

- **Placing all-reduce on Ethernet without a bandwidth budget.** A 70B model gradient all-reduce at 25 Gb/s Ethernet (≈ 2.5 GB/s practical-effective) takes ~56 s per step (a flat lower bound; ~98 s with the ring factor, §9.3). If the training runs 1,000 iterations, that is ~56,000 s (15.5 hours) spent exclusively in communication. Always compute the per-iteration communication cost before committing to a lower-bandwidth fabric.

- **Ignoring contention from other traffic.** NVSwitch can carry many concurrent channels, but if other collectives (e.g., all-gather for optimizer state) are running simultaneously, the

bisection bandwidth is shared. Measure with the full production workload pattern, not an isolated micro-benchmark.

- **Using InfiniBand as a default without checking the cost–performance ratio.** InfiniBand HDR 200 Gb/s gives ~25 GB/s unidirectional, which is sufficient for many workloads, but the price per GB of optics and cables is 5–10× that of Ethernet. If the communication time is acceptable on RoCE2, the cheaper fabric may be the better architectural choice.

- **Overlooking protocol overhead.** RoCE and InfiniBand use the same 64b/66b line coding but differ in framing and header sizes. An NDR 400 Gb/s InfiniBand link delivers a ~380 Gb/s class useful payload; a 200 Gb/s RoCE2 link delivers ~180 Gb/s. The difference matters when we are computing per-second throughput for a fixed data volume.

9.6. Architecture Consequence

The interconnect choice is not a detail to be decided after the model, the parallelism strategy, and the hardware are selected — it is a first-class design variable that shapes all three. If the architecture calls for data-parallel training of a 70B FP16 model across 8 nodes, the all-reduce bandwidth dictates whether the nodes are connected by InfiniBand, 200 GbE, or even 100 GbE. If the budget can accommodate NVLink-connected hosts, keeping the all-reduce on-node reduces communication time by ~22× vs InfiniBand and ~350× vs RoCE (§9.3).

The architecture consequence also flows in the other direction: a tighter communication budget (e.g., target <0.5 s per all-reduce) may force a particular parallelism strategy. We might choose model parallelism (pipeline parallelism, tensor parallelism) to keep the per-collective data volume smaller, or we might accept a slower fabric and reduce the frequency of collectives (e.g., gradient accumulation steps between all-reduce calls). The interconnect bandwidth number is the anchor that makes these trade-offs quantifiable.

Finally, the architecture consequence extends to cost. A cluster of 8×H100 servers connected by NVSwitch is the highest upfront capital expenditure, but it delivers the lowest per-iteration communication time, which translates to higher throughput per dollar over the life of the cluster. A cluster connected by 200 GbE RoCE has lower capital cost but higher per-iteration communication time, which may increase the total cost of ownership if the training job runs for many weeks. The architect must balance capex vs. opex by way of the communication arithmetic shown in this chapter.

9.7. What We Still Don't Know

- **Contention patterns under mixed workloads.** The benchmark numbers above assume a dedicated collective on a quiet fabric. In a production fleet, other traffic (user requests, other training jobs, KV cache movement) shares the same links. The effective bandwidth under realistic multi-job congestion is not yet characterized with a standard suite, and the interaction

between all-reduce and RoCE/Ethernet best-effort traffic can cause tail latency spikes that are difficult to predict.

- **Adaptive collective algorithms.** New collectives (e.g., gradient compression, sparse all-reduce, error-bounded approximations) claim to reduce the data volume at the cost of a small accuracy loss. The bandwidth arithmetic changes when the data volume is 30 GB instead of 140 GB, but the latency per byte may increase because of compression/decompression steps. The net effect on iteration time is workload-specific and not yet settled.

- **Optical interconnects and the next generation.** NVLink-Switch and the next-generation switch fabrics are pushing node-level bandwidth higher (toward 1.8 TB/s aggregate), and optical intra-rack fabrics (400 Gb/s–800 Gb/s per lane) are entering data centers. The arithmetic base — the relative magnitudes of PCIe, NVLink, Ethernet, InfiniBand — is stable in the near term, but the absolute numbers will shift as new silicon and cable technologies ship. Keep the framework; update the constants.

- **Cross-domain generalization.** Most published bandwidth measurements use square matrices (all-reduce of a gradient tensor). Diagonal dominant tensors, sparse gradients, or structured compression may exhibit different effective bandwidths because the traffic pattern across links is less uniform. The arithmetic framework applies, but the constants need re-measurement for the specific tensor shape.

9.8. End-of-Chapter Mini-Case: Naming the Parallelism Before the Arithmetic

An architect is asked to design a distributed inference fleet for a 70B parameter model serving user queries for 10,000 concurrent users. The team debates whether to use a single 8×H100 host with NVLink, or to shard the model across 32 nodes connected by 200 GbE RoCE. Before any hardware is ordered, the architect opens this chapter and runs the communication arithmetic.

The per-request all-reduce is not the right model for inference, and neither is a blanket "all-gather the full weights every decode step." It matters which parallelism is in play: ordinary **tensor parallelism (TP)** shards each weight matrix across the GPUs, and every decode step exchanges only the *activations* (not the weights) via collective ops like all-reduce/all-gather of the small activation tensors — weight matrices stay resident and are read in place, they are not re-fetched each step. A different scheme, FSDP-style **weight gathering** (used in training, and in some sharded-inference arrangements) does all-gather weight shards before the forward pass. So the architect must name the scheme before doing the arithmetic. Concretely, for the canonical 8×H100 host the meaningful per-step data movement is a TP all-reduce of the per-layer activations (tens of MBs, not GBs) plus the KV cache fragment exchange in disaggregated serving — e.g. ~35 GB of KV moved over NVLink (~0.08 s at 450 GB/s per direction, §9.2) when a P-D sequence transfers a ~13K-token context (35 GB ÷ 2.62 MB/token ≈ 13.3K) between prefill and decode pools. The distinction changes the answer by

orders of magnitude: re-fetching 140 GB of weights each step is pathological (that is a design smell, an anti-pattern to flag, not a baseline); exchanging activations or KV fragments is the normal case that fits comfortably within NVLink.

The architect proposes the single 8×H100 host (TP within the node, so intra-node NVLink carries the per-step activation all-reduce) for the core serving fleet, with a fallback to a 32-node RoCE cluster only if KV concurrency or memory capacity exceeds one host (Chapter 17). The communication arithmetic made the trade-off explicit: TP activation exchanges are tens of MB and free within NVLink; cross-node weight/KV shuttling is 35× more expensive and avoided unless the fleet genuinely spans hosts. The design is now grounded in bandwidth and the *specific* parallelism scheme, not in vague notions of "scale."

Scope note. This conclusion decides the communication **scheme**, not the fleet size, and it is stated for the canonical workload (~10/40 rps, Ch 4, Table 4-2) that the rest of the book's arithmetic uses — not for the 10,000-concurrent-user figure in the setup. At that stated scale the fallback condition in the sentence above is met on arrival: one 8×H100 host holds only $C \approx 17.5$ concurrent full-context requests (Ch 17), so 10,000 concurrent users exceed a single host's capacity by ~570× (10,000 ÷ 17.5 ≈ 570 hosts regardless of fabric) — a Chapter 17 capacity question, not a fabric question. The single-host-versus-RoCE choice above is what governs the canonical scale, where per-step TP activation exchanges stay tens of MB inside NVLink.

CHAPTER 10.

Parallelism: Splitting the Model Across Machines

The Architect's Question

After this chapter we should be able to answer the inevitable scaling question: *a single GPU cannot hold this model or keep up with this workload — how do we split the work across many GPUs, and which split is right?* We will build the arithmetic for why a model outgrows one GPU, then study the five parallelization strategies — tensor, pipeline, data, expert, and sequence parallelism — plus a serving-only sixth (P/D disaggregation, which has no training counterpart), and develop a rule for choosing among them based on the model's weight-residency, the workload's batch shape, and the interconnect speed. After this chapter, "we scaled it out" becomes a precise claim about *what* was split and *why*.

10.1. Concept

The central idea: parallelism is **splitting one of the three things a model occupies — its weights, its layers, or its data — across multiple devices.** Before reading on, one framing note that prevents a common source of confusion: **the parallelism toolkit differs between training and inference, and "data parallelism" means different things in each mode.** In *training*, DP means replicated weights plus gradient all-reduce every step (plus FSDP, which shards and re-gathers weights/optimizer state); the communication load is at the gradient-sync point. In *inference*, DP simply means running independent model replicas to raise throughput — there is no gradient sync at all, because each request is served by one replica. There is also an inference-specific family — context/pipeline partitioning, expert parallelism, and **P/D disaggregation** (splitting the prefill stage

from the decode stage into separate pools) — which has no training analogue. The rest of this section defines the strategies, and §10.3 applies them to inference (the book's canonical serving context) unless a strategy is explicitly training-only.

The strategy names tell us what gets split:

1. **Tensor parallelism (TP)** splits a single layer's weights across GPUs. The matrix multiply for one layer is partitioned so each GPU holds a slice of the weight matrix and the GPUs exchange partial results over NVLink every layer. TP is *intra-layer* and communication-hungry. (Inference: shards weights; per-step exchange is activations, not weights — see Ch. 9.)

2. **Pipeline parallelism (PP)** splits the model's layers (stages) across GPUs. GPU 1 runs layers 1–10, GPU 2 runs 11–20, and so on; activations flow forward, gradients flow backward. PP is *inter-layer*, communication-light, but idle bubbles appear at stage boundaries. (Inference: can split decode stages; bubbles hurt latency-sensitive serving more than training.)

3. **Data parallelism (DP)** — *different in the two modes.* Training: replicates all weights on every GPU, feeds each a different batch, all-reduces gradients after each step; communication-heavy only at the gradient-sync point, but each GPU must hold the full model. Inference: independent replicas each serve a disjoint set of requests; no gradient sync; throughput scales linearly until KV or memory binds (Ch. 17).

4. **Expert parallelism (EP)** shards the experts of a Mixture-of-Experts model across GPUs and routes each token to the GPU holding its experts — an all-to-all exchange per token. EP is MoE-specific. (Used in both training and inference for MoE models.)

5. **Sequence/context parallelism (CP)** splits the sequence dimension across GPUs, useful for very long contexts where the KV cache or attention activations exceed one GPU. (Inference-centric; the serving analogue of training sequence parallelism.)

6. **P/D disaggregation (inference)** — separates the compute-bound prefill stage from the bandwidth-bound decode stage onto different GPU pools so each can be sized and scaled independently (Ch. 11). This has no training counterpart and is a serving-only strategy.

These are not alternatives; production systems **compose** them (e.g. DP across nodes × TP within a node × PP across a few nodes; or TP+CP within a decode pool + a separate prefill pool). The architect's job is deciding which dimension to split first, and in which mode (training vs inference) the parallelism is being applied.

The strategies are not either/or. Fig 10.1 shows the three canonical patterns side by side. **Tensor parallel** shards one layer's weight matrix across GPUs — activations are replicated, and each GPU's partial sums are all-reduced every layer, so the exchange is per-layer and belongs behind NVLink. **Pipeline parallel** cuts the layer stack into stages on different GPUs — hidden states cross stage boundaries point-to-point, an idle bubble appears as the pipeline fills and drains, and the




FIGURE 10.1: Three parallelism patterns, one per panel: tensor parallel shards one layer's weights (activations replicated; partial sums all-reduced every layer), pipeline parallel splits the layer stack into stages (hidden states move P2P; an idle bubble at fill/drain), and data parallel replicates the model while splitting the batch (training all-reduces gradients; inference replicas run unsynced). Each panel names what splits, what is replicated, and what communicates. **Communication-specificity note:** the TP collective is *algorithm-dependent* — a plain all-reduce of partial sums is one option, but fused kernels often use reduce-scatter + all-gather (or a single all-reduce) depending on the framework; the PP bubble size depends on *microbatch scheduling* (more microbatches shrink the bubble but add memory). The panels show the canonical configuration (TP all-reduce per layer; PP with a small fixed microbatch count); substitute the actual collective and schedule for the target stack. **Grayscale note:** each box's text label carries its role, so the in-figure color key (blue = weights · orange = GPU · green = data · red = comms) is redundant, not load-bearing.

communication is light enough to span nodes. **Data parallel** replicates the whole model and splits the batch — in training every replica all-reduces its gradient each step; in inference the replicas are independent, each serving a disjoint slice of requests with no sync at all. Expert and sequence parallelism (EP/CP) are additional axes that reuse the same machinery. The three primary patterns **compose** (e.g. DP across nodes × TP within a node × PP across a few nodes) — which dimension binds determines which to split first.

10.2. Mental Model

Each strategy is best distinguished by *what it trades bandwidth for*. Tensor parallelism trades a lot of NVLink bandwidth to avoid duplicating weights but adds per-layer sync. Pipeline parallelism trades low bandwidth but accepts bubbles as the price of not holding all layers on one GPU. Data parallelism trades gradient bandwidth (once per step) for the convenience of replicated weights and is limited by having to fit the whole model on each GPU.

The useful mental model is a **resource triangle**: we have weights (memory), activations (work), and data (batch). Each strategy moves one corner off a single GPU at the cost of communication. When a GPU runs out of *memory*, we reach for TP/PP (weight splitting). When a GPU is *idle* waiting, we reach for DP/CP (more work per GPU). When the model is *too big to replicate*, TP wins over DP. The binding constraint chooses the strategy.

Table 10-1 — Parallelism strategies at a glance

Strategy	What it splits	Replicates	Communicates	Fits when
Tensor (TP)	a layer's weights within a GPU group	activations	partial sums → all-reduce (every layer, over NVLink)	model exceeds one GPU, fits a node
Pipeline (PP)	the layer stack into stages	hidden states	hidden states → P2P (stage boundaries only)	model spans nodes

Strategy	What it splits	Replicates	Communicates	Fits when
Data (DP)	the data batch	model + optimizer	gradients → all-reduce (per step)	model fits one GPU, need throughput (the canonical 70B is 140 GB > 80 GB per GPU, so it does not fit one GPU — DP is not its baseline; see §10.3)
Expert (EP)	MoE experts	attention / weights	routes → all-to-all (per token)	MoE models
Sequence (CP)	the token sequence	model weights	KV → ring	long contexts, KV too big

(Strategies compose; the table names the primary cost each trades.)

10.3. Worked Example

10.3.1. Why the Canonical 70B Doesn't Fit One H100

The canonical model is 70B FP16 dense = 140 GB of weights [ILLUSTRATIVE][DERIVED] (reality check: 70×10^9 params × 2 bytes). A single H100 has 80 GB of HBM [1P][FACT]. The arithmetic is immediate:

- The weights alone don't fit on one H100:

$$140 \text{ GB weights} > 80 \text{ GB HBM}$$

We need at least $140/80 \approx 1.75 \longrightarrow \geq$ **2 GPUs just to hold the weights** (and that's before KV cache, which adds ~2.62 MB/token at FP16 (2.5 MiB) — the 9.2K-token canonical prompt needs ~24.1 GB more (initial KV)). [ILLUSTRATIVE][DERIVED]

The canonical 8×H100 host (640 GB total) fits the weights + KV comfortably, which is why the single-host baseline in earlier chapters works. But if the model grows (say to 400B) or owns more, the split becomes mandatory:

10.3.2. Tensor Parallelism: Splitting Weights Across GPUs

With tensor parallelism, the 140 GB weight is split across GPUs. On 2×H100: $140/2 = 70$ GB per GPU, each now under the 80 GB ceiling. But every transformer layer's matmuls now require an **all-reduce of the layer's output across the TP group** — a per-token, per-layer exchange over NVLink. For the canonical 70B with ~80 layers, that is ~80 × tokens × output-size of communication per forward pass. The all-reduce communication cost per forward pass is $T_{\text{tp}} = \text{tokens} \times n_{\text{layers}} \times \text{output-size}/B_{\text{eff}}$. TP is only viable where the interconnect is very fast: on-node NVLink (900 GB/s) keeps the sync cheap; over slow Ethernet it would drown. The 900 GB/s operand is [1P][FACT] (vendor datasheet); the computed T_{tp} is [DERIVED].

10.3.3. Pipeline Parallelism: Splitting Layers, Accepting Bubbles

Pipeline parallelism puts stage P on GPU P. The cost is the **pipeline bubble**: while the first micro-batch fills the pipeline and the last one drains, stages sit idle. With P stages and m micro-batches, the steady-state **ideal speedup** over a single serial pass is:

$$\text{ideal speedup} = \frac{m \cdot P}{m + P - 1}$$

The $P-1$ term in the denominator is the bubble: the pipeline fills and drains exactly once per m-batch pass, so $P-1$ stage-slots are wasted out of the $m \cdot P$ slots each stage would otherwise work. With $P = 4$ stages and $m = 8$ micro-batches, ideal utilization is

$$\frac{8 \cdot 4}{8 + 4 - 1} = \frac{32}{11} \approx 2.9\times \quad (\text{out of } 4\times)$$

— a meaningful bubble. Fewer stages or more micro-batches shrink it: with $m = 32$,

$$\frac{32 \cdot 4}{32 + 4 - 1} = \frac{128}{35} \approx 3.66\times .$$

The lesson: PP is communication-light (each stage only moves activation boundaries across the fabric) but always pays a bubble that grows with stage count. [ILLUSTRATIVE][DERIVED]

10.3.4. Data Parallelism: Replicating, Then Syncing Gradients

Data parallelism replicates the 140 GB model on every GPU. For the gradient all-reduce: if the model has 140 GB of weights and we sync gradients after each step across G GPUs, each GPU sends its gradient tensor once per step. The gradient bytes are

$$\text{grad bytes} = N_{\text{params}} \times \text{bytes/param} = 70 \times 10^9 \times 4\ \text{B} \approx 280\ \text{GB}$$

per step (FP32 gradient; the all-reduce moves the gradient once, not weights+gradients). As in Chapter 9, a ring all-reduce moves $2\frac{N-1}{N}$ times the per-rank gradient through each rank, so for

$N = 8$ the per-rank traffic is $1.75 \times 280 \approx 490$ GB and the sync time is $T_{\text{ring}} = 2\frac{N-1}{N}$ bytes$/B_{\text{eff}}$. At 25 GB/s (single 200Gb/s link) that is `490 / 25 ≈ 19.6 s` per step — far too slow if the step takes ~1 s. At node NVLink 900 GB/s it is `490/900 ≈ 0.54 s`. The sync cost, not compute, often caps DP at small scale unless the interconnect is fast. [1P][DERIVED]

10.4. Measurement

Four habits anchor the architect:

1. **Measure weight residency before choosing a split.** `bytes = params × bytes_per_param` lands first; it decides whether TP/PP (memory) or DP (replication) is even possible.
2. **Measure interconnect bandwidth where it matters.** H100 NVLink ~900 GB/s per GPU is the on-node ceiling; cluster Ethernet/InfiniBand is 1–2 orders slower. Quote the number at the sync/frequency it will actually run.
3. **Measure the bubble and the step time.** For PP, log the fraction of idle GPU time (bubble) vs compute. For DP, time the gradient all-reduce as a fraction of step time — if it exceeds ~20%, it caps scaling.
4. **Measure communication overlap.** The best systems overlap all-reduce with the next forward/backward compute. Log the non-overlapped comm time — that is the true cost, not the raw bytes.

10.5. Common Mistakes

- **Splitting with DP when the model doesn't fit.** DP replicates weights; if 140 GB > 80 GB, one DP replica doesn't even fit one GPU. Reach for TP/PP first.
- **Using TP over a slow interconnect.** TP syncs every layer; over 25 GB/s cluster fabric it bottleneck-cycles. TP belongs behind NVLink.
- **Ignoring the pipeline bubble.** PP's idle stages waste real utilization; the bubble grows with stage count. It is not free.
- **Quoting peak interconnect spec as sustained.** NVLink 900 GB/s is aggregate peak; real all-reduce achieves a fraction. Budget headroom.
- **Treating parallelism as an either/or.** Real systems compose DP×TP×PP; the question is which dimension binds, not which one to use.

10.6. Architecture Consequence

The parallelism strategy is forced by the binding constraint, and that constraint is usually **memory** for large models:

- **A model that exceeds one GPU's memory** must split weights → TP (within a node, on NVLink) or PP (across nodes, low comm). Which one depends on whether the model fits a node: fits one node → TP among its GPUs; spans nodes → PP across them, with TP inside each node.
- **A workload with high throughput demand** (like the canonical ~10 rps / 40 rps) that fits one replicable model → DP to scale batch across GPUs, accepting the gradient-sync cost only if it trains/fine-tunes. For pure inference the canonical 70B fits one 8×H100 node, so parallelism is often unnecessary at the single-host baseline.
- **MoE models** (if chosen per Ch3) push toward EP, because only the active experts need residency per token.
- **The canonical answer**: for the book's ~70B/8×H100 scenario, no parallelism is required at the baseline; parallelism becomes the tool when the model or workload outgrows one node. The architect escalates through TP (in-node) → PP (cross-node) → DP (replicating a fitting model) in that order.

Table 10-1 above consolidates the five parallelization strategies (plus the serving-only P/D disaggregation): reading across a row gives one strategy's full trade-off (what it splits, what it replicates, what it communicates, when it fits), and reading down a column shows how each axis varies across strategies. (Fig 10.1 illustrates the three canonical patterns — TP, PP, DP — side by side; the table adds the specialist EP and CP rows.)

10.7. What We Still Don't Know

- **Optimal split for very large MoE or long-context models** is workload- and interconnect-dependent; the exact NVLink-vs-fabric crossover for a given model is unmeasured [UNRESOLVED] — measure on the target cluster.
- **2026 MoE scaling has moved the specialist/EP frontier.** Kimi K3 activates just 16 of 896 routed experts per token (2.8T total / 104B active) via its Stable LatentMoE [1P: arXiv 2607.24653]; Qwen3.8-Flash-Next routes 10+1 of 512 experts (125B total / 6B active) [1P: HF Qwen/Qwen3.8-Flash-Next]. These extreme sparsities (16/896 ≈ 1.8% expert activation) are why expert-parallel and fused cross-expert comm kernels (e.g. MoE expert parallelism with fused compute/communication, as in DeepSeek's DeepEP/TileLang infra) are increasingly central to serving large MoE fleets [1P: arXiv 2606.19348]. For the architect this changes the

serving calculus: a frontier MoE's activated footprint (Kimi 104B, Qwen 6B) can be dramatically smaller than its total size, so the memory-bound EP decision must be made against *active* parameters, not total.

- **Communication-overlap efficiency** in real kernels is hard to predict from spec; sustained all-reduce throughput is a **[HYPOTHESIS]** until measured on the target cluster.
- **The right parallelism for mixed prefill/decode (P/D disaggregated) serving** — where the prefill pool and decode pool may want different splits — is an active research area and a **[HYPOTHESIS]** for this book.

10.8. End-of-Chapter Mini-Case: Diagnosing Why the Grown 400B MoE Is Slow

An architect inherits a deployment where the internal Q&A model (from Ch1's mini-case) has been fine-tuned and grown to a 400B-parameter MoE. The team reports "parallelism is killing us — everything is slow." The architect applies this chapter's lens. First, weight residency: a 400B model needs `~400e9 ×2 bytes = 800 GB` even before KV — that is ~10×H100 for weights alone (~11 once KV/workspace is included), far beyond one node. **The model necessarily spans nodes; the architect must choose an inter-node decomposition** — often PP and/or EP for MoE — while avoiding expensive cross-node TP where possible (TP benefits from a tightly coupled NVLink-style interconnect; across a slower network its per-layer all-reduce cost grows fast). Within each node, the MoE active weights are small, so the team uses EP to shard experts + TP inside the node. The architect measures the interconnect: the cross-node PP boundary runs over the cluster fabric (not NVLink), so they minimize the number of PP stages to shrink the bubble, and they verify the DP gradient-sync (if fine-tuning) stays under ~20% of step time. The result: a composed PP × EP × TP configuration whose binding constraints (memory across nodes + expert routing) are each addressed by the strategy that trades the right bandwidth. The team's "parallelism is slow" becomes a precise, diagnosed, and fixed split.

CHAPTER 11.

Serving: From Model in Memory to Requests in Flight

Serving is a small set of composable mechanisms — continuous batching, paged/blocked KV cache, prefix caching, and prefill/decode disaggregation — that turn a static in-memory model into a live multi-request system. The architecture choices that matter are which of these are adopted and how they share the host's KV budget, because the latency SLO is met by the batch and cache strategy rather than by the model alone.

The Architect's Question

After this chapter we should be able to answer the operational half of deployment: *the model is in memory and the requests are arriving at ~10 per second — how do we actually serve them without violating our latency SLO?* We will develop the serving mechanisms that turn a static model into a live, multi-request system: how requests are batched, how KV cache memory is managed, how repeated prefixes are reused, and when to split prefill from decode onto separate pools. After this chapter, serving is not a black box — it is a sequence of explicit architectural choices, each with a measurable consequence.

11.1. Concept

Serving is a small set of mechanisms, invented roughly in order:

1. **Batching** — running multiple requests through the model together to amortize the weight reads. The key modern advance is **continuous (iteration-level) batching** introduced by

Orca (OSDI 2022): instead of waiting for an entire batch to finish, the scheduler admits and evicts requests at every decoding step, filling the GPU's idle slots as soon as they free up. [S1] [1P]

2. **PagedAttention / vLLM (SOSP 2023)** — managing the KV cache in fixed-size blocks (like a virtual-memory page table) so that different requests' KV caches no longer need contiguous memory, slashing fragmentation and letting the serving engine pack far more concurrent requests. [S2][1P]

3. **Prefix caching** — recognizing that many requests share context (e.g. the same retrieved documents), and caching the KV of the common prefix so a new request does not re-prefill it. **RadixAttention (SGLang)** and **Automatic Prefix Caching (vLLM APC)** are the canonical implementations. [S3][1P]

4. **P/D disaggregation** — splitting the compute-bound *prefill* stage from the bandwidth-bound *decode* stage onto separate pools, because they bottleneck on different resources. Pioneered by **Splitwise (ISCA 2024)** and **DistServe (OSDI 2024)**; **Mooncake** takes the KV-centric view, transferring KV caches from the prefill pool to the decode pool (with CPU/DRAM/SSD offload) and reports up to **525% throughput lift** in long-context simulation and **75% more requests** on a real Kimi workload. [S4][1P]

These mechanisms compose: continuous batching is the baseline, PagedAttention makes it memory-efficient, prefix caching makes it cheaper, and P/D disaggregation makes it scale.

Source keys [S1]–[S6]. The bracketed keys used throughout this book (and in the evidence taxonomy of the Sources, Method, and Reproducibility chapter) point to the primary sources below. Each is a [1P] first-party or peer-reviewed source; the book's derived numbers cite the key plus a [DERIVED] tag.

- **[S1] Orca** — Yu et al., "Orca: A Distributed Serving System for Transformer-Based Generative Models," OSDI 2022. Continuous (iteration-level) batching.
- **[S2] PagedAttention / vLLM** — Kwon et al., "Efficient Memory Management for Large Language Model Serving with PagedAttention," SOSP 2023. Block-based KV cache.
- **[S3] Prefix caching** — "Fast Inference from Transformers via Radix Attention" (SGLang, 2023) and vLLM Automatic Prefix Caching (APC). Caching shared-prefix KV.
- **[S4] P/D disaggregation** — "Splitwise: Efficient Generative LLM Inference Using Phase Splitting" (ISCA 2024), "DistServe: Disaggregating Prefill and Decoding for Goodput-optimized Large Language Model Serving" (OSDI 2024), and Mooncake (KV-centric disaggregation, 2024).
- **[S5] DFlash** — Chen et al., "DFlash: Block Diffusion for Flash Speculative Decoding," ICML 2026 (PMLR v306; arXiv:2602.06036). Speculative-decoding system reporting >6× lossless acceleration over autoregressive decoding (up to 6.1× on Qwen3-8B) and up to 2.5× faster than the prior state of the art, EAGLE-3.

- **[S6] vLLM FP8-KV blog** — the vLLM FP8-KV blog post's '54%' figure is a decode inter-token-latency (ITL) slope, a LATENCY metric, not a memory/residency ratio. Any reference to it (Chapters 1, 3, 6, 7, 15, 22, Appendix A and the glossary) is a latency reference only. The KV memory footprint this book uses is the raw tensor byte-halving of ~1.31 MB/token (exactly 50% of BF16) [ILLUSTRATIVE][DERIVED]; any block-allocation/metadata overhead is NOT vendor-measured here and must be filled by a deployment benchmark.

11.2. Mental Model

Serving is **managing three precious resources against a stream of arrivals**: GPU compute (FLOPs, bound in prefill), GPU memory bandwidth (HBM, bound in decode), and GPU memory capacity (HBM bytes, bound by KV cache). Each mechanism trades one of these:

- **Batching** improves compute and bandwidth utilization by amortizing the fixed per-step weight reads across more requests.
- **PagedAttention** improves memory capacity by eliminating KV fragmentation.
- **Prefix caching** reduces memory capacity and prefill compute by reusing already-computed KV.
- **P/D disaggregation** lets the prefill pool run at high compute utilization and the decode pool at high bandwidth utilization simultaneously, instead of one pool being starved.

The mental model is a **resource budget**: a request arrives, consumes some FLOPs (prefill), some bandwidth (decode), and some memory (its KV cache) for its lifetime. Serving architecture is about sizing and scheduling those three budgets so the SLO holds across the burst.

11.3. Worked Example

11.3.1. The Canonical Workload in a Serving System

Recall the canonical enterprise-Q&A RAG workload (Ch 4, Table 4-2): ~10 rps average, ~40 rps peak; each request carries ~9,200 input tokens and ~300 output tokens; TTFT budget 1.2 s, TPOT ~25 ms/token. [ASSUMPTION]

11.3.2. Discrete Batching Wastes the GPU

Naive **discrete (static) batching** accumulates requests until a batch fills, then runs them to completion, then starts the next batch. Problems compound at this workload's 9.2K-input shape:

- Requests arrive in *bursts* (recall the ~40 rps peak). Discrete batching forces early-arriving requests to **wait** for the batch to fill, inflating TTFT toward the 2 s SLO breach.
- The batch is locked until its *slowest* member finishes (fits-all-in-one-run), so a short 100-token output tails behind the longest while the GPU finishes the whole batch — idle bubbles at the end of every batch.

- Batch boundaries create periods where the GPU drains (no work) then floods — utilization is spiky around the mean. [ILLUSTRATIVE][DERIVED]

11.3.3. Continuous Batching Fills the Bubbles

Continuous batching (Orca [S1][1P]) eliminates the batch boundary: at every decode step the scheduler accepts any new prefill-ready request and evicts any finished one, so decode slots never sit idle. In the canonical stream, a 300-token decode at ~25 ms/token occupies a slot for ~7.5 s; while a long decode runs, the freed FLOPs are continuously refilled by new short requests. The utilization gain is the difference between spiky discrete batches and a continuously-fed pipeline. Rather than stipulate a single percent, the mechanism makes the GPU the steady bottleneck instead of the scheduler. [ILLUSTRATIVE][DERIVED]

11.3.4. PagedAttention: Killing the Fragmentation Tax

In re-packaged (naive) serving, each request's KV cache for 9.2K input is ~24.1 GB (FP16, ~2.62 MB/token × 9,200, initial KV) [ILLUSTRATIVE][DERIVED]. If served contiguously, variable-length completions leave fragmented, unusable holes — exactly like a fragmented heap. **PagedAttention/vLLM [S2][1P]** allocates KV in fixed blocks shared and evicted like page frames, so the ~24.1 GB per request is packed densely and more concurrent requests fit in the same 640 GB node [ILLUSTRATIVE][DERIVED]. The win is *more concurrency under the same SLO*, not faster single-request math.

11.3.5. Prefix Caching: Don't Re-Prefill the Same Documents

The RAG request's 8K retrieved-context tokens are largely shared across queries (same documents). Without caching, every request re-runs the ~1.29 PFLOP prefill for those 8K tokens [ILLUSTRATIVE][DERIVED]. **RadixAttention / APC [S3][1P]** caches the KV of common prefixes, so a new request reuses the shared-document KV and prefills only the unique query tail — cutting the dominant prefill FLOPs and TTFT for repeated-context traffic [ILLUSTRATIVE][DERIVED].

11.3.6. When to Disaggregate: Prefill and Decode Want Different Pools

Recall from Ch2/Ch6: prefill is **compute-bound** (~1.29 PFLOP ⟶ ~1.19 PFLOPS required vs 0.989 PFLOPS peak), decode is **bandwidth-bound** (the whole-model weight-read rate of ~5.6 TB/s if served by one device vs 3.35 TB/s per GPU; under the canonical 8×H100 host it is sharded to ~0.70 TB/s per GPU, and the shard-invariant cause is the low ~1.0 FLOP/byte intensity, Ch 6) [1P][DERIVED]. Serving both from one pool forces a compromise: batch for prefill and it slows decode; optimize for decode and prefill starves. **P/D disaggregation (Splitwise/DistServe/Mooncake [S4][1P])** runs prefill nodes at high FLOP-utilization and decode nodes at high bandwidth-utilization, transferring KV across via the fabric (**Fig 11.3** shows the two-pool topology and what moves between them). Mooncake's reported up to 525% long-context throughput and +75% request count are the quantitative




FIGURE 11.1: Discrete vs continuous batching (Orca-style slot diagram). The horizontal axis is **time (decode steps / iterations)**; each row is one decode step, and in the continuous panel the step boundaries are staggered across rows as the scheduler admits new requests and evicts finished ones. In the top (discrete) panel a batch is locked until its slowest member finishes, so short outputs idle in the trailing slots; in the bottom (continuous) panel freed slots are refilled every step. The diagram is a **decode-only** illustration; see the note in the figure.

Discrete batching runs each batch to completion, leaving GPU slots idle as sequences finish early; continuous batching admits and evicts requests at every decode step, backfilling freed slots. (Illustrative, after Orca, OSDI 2022.)

anchor [S4][1P]. For the canonical single-host (~10 rps) this disaggregation is premature; it pays off only when the workload outgrows a node and the two phases' resource conflicts become binding.

Table 11-1 — Serving techniques at a glance

Technique	Mechanism	Primary resource traded	When it matters	Source
Discrete batching	Lock batch to completion	— (wastes)	baseline only	—
Continuous batching (Orca)	Admit/evict at each decode step	compute+bandwidth util	high concurrency	[S1][1P]
PagedAttention / vLLM	Block-based KV pages	memory capacity	many concurrent requests	[S2][1P]
Prefix caching (RadixAttention/APC)	Cache shared-prefix KV	prefill FLOPs + memory	repeated-context RAG	[S3][1P]
P/D disaggregation	Split prefill/decode pools + KV transfer	both at scale	workload outgrows a node	[S4][1P]

11.4. Measurement

Good serving telemetry answers "are we meeting the SLO while keeping the GPU busy?":

1. **Measure goodput, not raw throughput** — tokens/s that arrive before their SLO deadline (Ch6). Continuous batching is only a win if it raises goodput.
2. **Measure KV utilization** — fraction of the 640 GB node memory consumed by live KV vs weights. PagedAttention and prefix caching both raise the effective KV packing; track it.
3. **Measure prefill-vs-decode utilization separately** — a FLOP-bound prefill core and a bandwidth-bound decode core running on one pool tells us when to disaggregate.
4. **Measure the scheduler's real occupancy** — idle decode slots, queue wait, and the tail of TTFT under load, not the average.

11.5. Common Mistakes

- **Assuming bigger batches always help.** Bigger discrete batches raise raw tokens/s but push TTFT past the SLO, zeroing goodput (Ch6). Continuous batching exists precisely to uncouple batch size from wait.
- **Serving KV contiguous and watching fragmentation.** PagedAttention removes the fragmentation tax; skipping it wastes memory under concurrency.
- **Re-prefilling shared context.** Without prefix caching, repeated RAG documents are recomputed per request — one of the most wasteful failures for this workload.
- **Choosing P/D disaggregation too early.** Splitting pools adds fabric + orchestration; for a single host it is overhead without the resource conflict that motivates it.
- **Believing speculative decoding (DFlash reports >6× lossless acceleration, up to 2.5× faster than EAGLE-3 [S5][1P]) is a serving baseline.** These are paper-reported results under the paper's evaluation setup, not portable serving-speed figures. Speculative decoding is an optimization for bandwidth-bound decode, not a requirement, and must be validated on the workload.

11.6. Architecture Consequence

The serving mechanisms dictate the deployment choices:

- **Baseline (canonical single-host):** continuous batching (vLLM/Orca) is near-mandatory to hold TTFT under the SLO (1.2 s, p95 ≤ 2 s) at 10 rps input-heavy load; PagedAttention ensures the ~24.1 GB-per-request KV pack fits; prefix caching is the highest-leverage optimization because the workload is repeated-context RAG. This matches the memory and compute conclusions of Ch4/Ch7 for the ~10 rps *average* baseline; at the ~40 rps peak the KV budget forces replication, which Chapter 17 sizes. [S1][S2][S3][1P]
- **Scaling up:** those three carry the workload far before disaggregation is justified. FP8 KV (raw tensor byte-halving = 1.31 MB/token, exactly 50% of BF16) [ILLUSTRATIVE][DERIVED] and KV offloading are memory levers available without restructuring.
- **Beyond a node:** when prefill FLOPs and decode bandwidth fight on one pool, P/D disaggregation (Splitwise/DistServe/Mooncake) is the architecture of choice, with Mooncake's KV-transfer engine moving caches between pools. [S4][1P]




FIGURE 11.2: Serving is four orthogonal concerns, not a stack (request scheduling, state management, reuse, resource specialisation). A concrete serving design that chooses one mechanism per concern: **request scheduling** = continuous (Orca-style) batching; **state management** = PagedAttention (fixed-size KV pages); **reuse** = prefix caching of shared context; **resource specialisation** = P/D disaggregation (separate prefill and decode pools). The four are independent dials — a system can combine any mechanism with any other — and the canonical baseline uses the first three; resource specialisation joins when the workload outgrows a node (§11.3.6).

*The design lever is what each concern trades: **request scheduling** exchanges latency for utilization, **state management** exchanges memory capacity for concurrency, **reuse** avoids re-prefill FLOPs, and **resource specialisation** matches two compute/memory regimes to two pools.*




FIGURE 11.3: P/D disaggregation topology: a prefill-optimized pool (FLOPs) and a decode-optimized pool (HBM) bridged by KV transfer. The KV-transfer arrow is the load-bearing cost: it moves the per-request KV state (e.g. ~35 GB for a ~13K-token context at 2.62 MB/token, §9.8) over the interconnect, and the disaggregation is only worth it when the prefill/decode specialization benefit **exceeds** the KV-transfer time plus the orchestration overhead of routing requests between two pools. Illustrative: at NVLink's 450 GB/s per direction (§9.2) that ~35 GB transfer is ~0.08 s, which is small against the ~1.08 s prefill it enables, so the inequality holds on-node; over a 40 GB/s fabric it is ~0.9 s, which can erase the benefit — the transfer cost is the term that decides whether P/D disaggregation pays.
The KV moves once per request, then stays local (ownership splits); the split itself exists because the two stages want opposite resources under load — prefill needs compute capacity (~1.19 PFLOPS required vs 0.989 peak single-H100), while decode needs HBM bandwidth (the whole-model weight-read rate of ~5.6 TB/s if served by one device vs 3.35 TB/s per GPU, sharded to ~0.70 TB/s per GPU under the canonical 8×H100 host, Ch 6) [1P][DERIVED].

11.6.1. The Mechanisms, Not the Product Catalog

The mechanisms above are what matter; the engines are just implementations of them. This comparison is organized by *architectural capability* so it transfers across specific products and versions. **It is explicitly time-sensitive** — capabilities, supported models, and features change fast, and these rows must be re-verified against each engine's current first-party documentation before any deployment decision. The table is a map of *which mechanism to look for*, not a ranking.

Table 11-2 — Serving engines by architectural capability (time-sensitive)

capability	vLLM	SGLang	TensorRT-LLM	llama.cpp	architectural note
scheduler model	continuous batching	continuous + RadixAttention	batch orchestration (TRT engine)	single/multi-stream	which batching algorithm, not which vendor
KV-memory management	PagedAttention	RadixAttention (page + prefix tree)	KV recompute/offload on engine	custom KV store	how KV is allocated/fragmented
prefix caching	auto prefix	Radix prefix tree	some cache	limited	how much re-prefill is avoided
quantization support	broad (GPTQ/AWQ/FP8)	broad	tight NVIDIA-precision (FP8/INT8/INT4)	GGUF (K-quants)	what precision the kernels are tuned for
parallelism	TP/PP/DP	TP/PP/DP	TP/PP/DP (NVIDIA-optimized)	limited / CPU+GPU	how the model is split
P/D capabilities	some (separate prefill/decode)	native disaggregation	via engine orchestration	n/a	whether prefill and decode can run on separate pools

capability	vLLM	SGLang	TensorRT-LLM	llama.cpp	architectural note
structured generation	constrained decoding	constrained (XGrammar)	constrained	constrained	whether output can be schema-constrained
supported hardware	NVIDIA / AMD / CPU	NVIDIA / AMD	NVIDIA-only	CPU + consumer GPUs	deployment niche

The columns read as *knobs on a common set of mechanisms*, not as "which engine is best." An engine's real value is which mechanisms it implements *well for the deployed workload's shape* — e.g. a repeated-context RAG workload cares most about the prefix-caching row (RadixAttention in SGLang is a strong implementation), while a latency-critical single-stream deployment might care more about the scheduler and structured-generation rows. **Never conclude "X is the go-to engine"** — that is workload-independent and will be wrong. The only defensible statement is workload-specific: *for this request shape, this precision, and this hardware, engine Y implements the mechanism Z we need; benchmark it against the alternative (Ch. 14).*

11.7. What We Still Don't Know

As of 2026-08, several questions remain open, each flagged **[HYPOTHESIS]** or **[UNRESOLVED]** (measure on the target cluster):

- **Portable end-to-end goodput across real enterprise RAG** — Mooncake's 525%/75% [S4][1P] and DFlash's >6× [S5][1P] are strong anchors but are workload-specific; general rules remain an open hypothesis **[HYPOTHESIS]**.
- **Prefix-cache hit rates in mixed traffic** — the real reduction in prefill FLOPs from RadixAttention/APC for a given document-distribution remains a hypothesis **[HYPOTHESIS]**.
- **KV-transfer cost at scale** — Mooncake's engine moves KV to CPU/DRAM/SSD [S4][1P], but the exact latency/bandwidth crossover where disaggregation wins is unmeasured **[UNRESOLVED] — measure on the target cluster**.

11.8. End-of-Chapter Mini-Case: Which Serving Mechanism to Reach For

An architect runs the canonical internal Q&A service on a single 8×H100 host and sees p95 TTFT creep toward 2.2 s against a 2 s SLO as traffic peaks at 40 rps. Applying this chapter: the architect first confirms continuous batching is on (vLLM) and that PagedAttention is active — otherwise

the ~24.1 GB-per-request KV for 9.2K inputs fragments and concurrency collapses. The biggest lever: prefix caching. The RAG traffic reuses the same retrieved documents, so the architect enables automatic prefix caching and watches TTFT drop as the 8K-context prefill is replaced by cached KV lookups. The architect does **not** reach for P/D disaggregation or speculative decoding — the single host is resource-sufficient *for this latency/SLO* once the wasted re-prefill is eliminated. The result: p95 TTFT back under 1.8 s at 40 rps, goodput restored, with only configuration changes — because the architecture followed the serving mechanism that matched the workload's repeated-context shape. Scope note: this is a **latency-bound, single-host** judgment. It answers "can one host meet the TTFT SLO per request," *not* "can one host carry the whole 40 rps arrival rate." At the canonical peak, in-flight concurrency at the ~8.6 s service time is ≈344 requests, far above an 8×H100 host's KV-residency ceiling ($C \approx 17.5$, conservative integer floor 17); a *single* host therefore cannot serve the peak *traffic*, even though it can meet the per-request TTFT SLO. The capacity/fleet question — how many such hosts for λ=40 rps — is answered by Chapter 17's service-time-aware sizing (≈20 hosts), not by this mini-case. The two questions (per-request latency vs aggregate capacity) must not be conflated.

PART IV.

The Architecture

CHAPTER 12.

Designing the AI System: From Constraints to Candidates

Designing an AI system is constraint-driven generation, not menu-picking: the architect extracts the hard constraints from a characterized workload — the three gates this chapter fixes: memory fit, throughput at the SLO, and quality — then synthesizes candidate architectures that must clear them. The payoff is a bounded set of two to three candidates that each fail a distinct, inspectable gate — memory fit, throughput, or quality — which the measuring chapters then adjudicate.

The Architect's Question

Designing an AI system means producing candidate architectures from the substrate — memory, compute, communication, and parallelism — rather than selecting a canned stack. This chapter works through a synthesis method: given a characterized workload from the six-dimension framework (Ch. 4), generate two or three candidate architectures that each satisfy the hard constraints — the three gates fixed here: memory fit, throughput at the SLO, and quality — then carry them forward for evaluation in Chs. 14–16. The core thesis is that design is constraint-driven generation, not menu-picking. This distinguishes our approach from the abstract meta-method presented in Ch. 22, which operates at a level of generality that does not instantiate against concrete substrate constraints. In the language of the book's spine — the decision loop *constrain* → *synthesize* → *measure* → *decide* → *refine* — this chapter is the **synthesize** step: we turn a constraint-characterized workload into a bounded set of candidate architectures that then enter the measure/decide stages in Chs. 14–16.

12.1. Concept

The architect's first step is to reverse-engineer the workload into its constituent constraints. From the six dimensions — quality requirements, traffic profile, token profile, latency budget, economic ceiling, and operational constraints — we extract the three hard constraints — the three gates used throughout this chapter — that any candidate must satisfy: (1) **memory fit** — the weight memory plus the KV-cache footprint must fit the target host's aggregate memory; (2) **throughput at the SLO** — sustained prefill and decode tokens-per-second, delivered within the latency budget (prefill + decode), must meet the workload's demand; and (3) **quality** — answer quality on the true evaluation set must meet the quality requirement. Any architecture that violates any one of these is eliminated before evaluation: a layout whose memory fits but whose throughput falls short of demand — as a single host falls against the canonical ~92K input tokens/s — is not carried forward as-is; it returns to synthesis for a larger layout or is dropped, and a smaller-model candidate whose quality is unmeasured is gated, not promoted. (The economic ceiling is recorded but is not one of the three gates; §12.8 states its consequence at fleet scale.) This constraint-first posture inverts the typical practice of browsing vendor offerings and then hoping they fit; instead, we generate architectures that we know can physically reside and operate within the specified substrate.

12.2. Mental Model

The substrate is a set of bounded resources, and the architecture design problem is essentially a packing exercise. The resources are: GPU memory (weight residency + KV cache), memory bandwidth (prefill throughput), inter-GPU communication volume (for parallelism schemes), and the latency budget split between prefill and decode. A candidate architecture is a valid packing of the workload's weight memory and KV cache into the available GPU memory, paired with a parallelism and caching strategy that delivers the required tokens-per-second throughput within the latency budget. The architect alternates between squeezing the residency footprint (e.g., via KV quantization or precision reduction) and adjusting the parallelism layout (e.g., parameter vs. data vs. pipeline) until all three hard constraints are simultaneously satisfiable. This mental model — substrate as packing problem — is what enables systematic candidate generation rather than ad hoc selection.

12.3. Worked Example

We generate three candidate architectures for the canonical enterprise-Q&A RAG workload: ~10 requests/s average, peak 40 rps, 70B FP16 model, 9.2K token input (1,200 prompt + 8K retrieved context), 300-token output. The canonical weight memory is 140 GB (70B × 2 bytes FP16). The KV cache for 9.2K context at FP16 precision ([ASSUMPTION] canonical (Ch 4, Table 4-2)) is approximately 24 GB (2 × num_layers × hidden_dim × 9,200 × 2 bytes per FP16 element), giving a total residency

of 164 GB. A single 8×H100 host provides 640 GB aggregate memory (8 ×80 GB), leaving ample headroom. Each candidate satisfies the three hard constraints differently.

Candidate (a): single 8×H100 host with prefix caching (Ch. 11). This is the per-request-latency baseline — the single 8×H100 host that the early book (Ch 2, 4, 7, 8) establishes as meeting one request's latency SLO. It is *not* a capacity baseline: a lone host cannot carry the arrival rate (~5 hosts are needed for the canonical average, and ~20 at peak — see Ch 11, 13, 17), so its throughput-gate failure below is expected and is *not* a reason to dismiss the host class itself. All 70B weights and the full 24 GB KV cache reside on the 8-GPU host. Prefix caching from Ch. 11 amortizes the prefill attention over repeated requests with the same prompt prefix, reducing effective prefill FLOPs by ~30% at 10 rps average and ~50% at peak 40 rps when many requests share common document roots. (That 30–50% amortization range is a reasoned expectation, not a measured figure — it rests on the untested premise about traffic overlap flagged in §12.7, so it is labeled **[HYPOTHESIS]** and should be confirmed by measuring the actual prefix-hit rate before it is relied on.) The 8×H100 host fits the full 164 GB residency easily, but on *throughput* we must be honest with the Chapter 8 arithmetic: a single 8×H100 host sustains only ~19,800 prefill-tokens/s at the idealized 35%-MFU aggregate (8 × 2,471; see the Ch. 8 scope note) — far below the ~92K input tokens/s the workload needs on average. Even if prefix caching (~30% at average load) lifts effective prefill throughput toward ~28K tokens/s **[HYPOTHESIS]**, that is still well below 92K, so a single host fails the throughput gate too — prefill is compute-bound at this operating point, and meeting it is exactly the scaling problem Chapters 15–17 take up. Memory fit and throughput fit are different gates: the memory gate passes with one host; the throughput gate does not. Memory fit: 140 GB weights + 24 GB KV = 164 GB < 640 GB aggregate ([ASSUMPTION] canonical (Ch 4, Table 4-2)). Throughput at the SLO: per-request prefill + decode stay within the latency budget thanks to prefix caching and the high bandwidth of 8×H100, but the sustained rate fails at one host, as shown above — the gate closes only when the host class is replicated to ~5 hosts (Chs. 15–17). Quality: the 70B is itself the workload's quality reference, so this gate is met by construction. Economics (recorded, not one of the three gates — §12.8): one host purchase, one software license tier.

Candidate (b): P/D-disaggregated two-pool.
We keep the full 70B model in both pools and split by *phase* — which is what prefill/decode (P/D) disaggregation actually means (Chapter 11): a compute-bound prefill pool and a bandwidth-bound decode pool, each holding the complete 140 GB weights plus the in-flight KV, with the KV hidden-state handed between them (Splitwise / DistServe / Mooncake). Each pool therefore needs its own 8×H100 host (residency ~164 GB — weights plus one request's KV — comfortably under 640 GB). The win is that prefill and decode no longer fight over the same host's resources: the prefill pool runs FLOPS-saturated on the 9.2K input, the decode pool runs bandwidth-saturated on the 300 output tokens, and KV crosses between them. Crucially, P/D disaggregation does **not** raise per-host prefill throughput: one 8×H100 prefill host still sustains only ~19,800 prefill-tokens/s (the same Chapter 8 arithmetic as Candidate (a)), far short of the ~92K input tokens/s the workload needs on average. So

Candidate (b) passes the *memory* gate per pool but still fails the *throughput* gate at a single prefill host — its real advantage is that the prefill pool can be scaled **independently** of the decode pool, so meeting the ~92K demand means scaling the prefill pool to ~5 hosts (92K ÷ 19.8K ≈ 4.65) plus the decode pool, rather than forcing every host to serve both phases. Disaggregation buys the *ability to scale each phase separately*, not the throughput itself. Economics: two hosts and added fabric as a baseline, more as each pool scales; it is the right architecture *at scale*, not a two-host answer to the canonical case.

Candidate (c): KV-quantized smaller host.
We downgrade to a 7B-class model (7B × 2 bytes = 14 GB weights) with KV cache quantized to 4-bit. The per-token KV depends on the model's own attention shape (layers × KV heads × head dim × bytes, Chapter 7), NOT the 70B's constant: a typical 32-layer, 4096-hidden, full-MHA 7B carries ~0.52 MB/token FP16, so ~0.13 MB/token at 4-bit ⟶ ~1.2 GB for the 9.2K context (vs the ~6 GB that comes from naively reusing the 70B's 2.62 MB/token ÷ 4). Total residency: 14 GB + ~1.2 GB ≈ **~15 GB**, which fits on a single H100 (80 GB) with large headroom. The trade-off is a quality question, and here we must be careful not to assert an architectural theorem where one does not exist. Whether a 7B-class model can match the 70B model's answer quality on *this* workload is **not** derivable from parameter count — a newer or task-specialized 7B can beat an older or general 70B on some tasks. It is an empirical question answered only by running the actual evaluation set. The correct architectural lesson is the **quality gate**: the smaller candidate must pass the capability/quality gate on the true evaluation set; if it fails there, no amount of infrastructure optimization fixes that failure. So candidate (c) is flagged for measurement against the quality gate, not dismissed by parameter counting. The 4-bit KV cache is a *memory* optimization, not a quality one; aggressive KV quantization can add its own quality penalty that must also be validated on the target workload. Throughput is genuinely much higher on the smaller model — a 7B prefill costs only ~14 GFLOP/token, so a single card sustains tens of thousands of prefill tokens/s (vs ~2,471 per *GPU* for the 70B, Chapter 8) — but that throughput advantage is only useful if the quality gate is first satisfied. The candidate is therefore provisional: its fate depends on the measured quality gate, which Chapter 14 (the capability screen) administers. This candidate illustrates the extreme end of the KV-quantization space: the memory footprint is trivially small, but neither quality nor throughput makes it competitive for this workload.

Memory/residency arithmetic summary. The canonical weights (140 GB) + KV (24 GB FP16 at the 9.2K input context) = 164 GB fits 640 GB (8×H100). Candidate (a) uses the full host with room to spare. Candidate (b) keeps the full model in each pool, so each 8×H100 host also holds ~164 GB. Candidate (c) fits ~15 GB on one H100 and its throughput is high, but it is **provisional** — its fate turns on the Ch 14 quality-gate measurement, not on parameter counting.

12.4. Measurement

To validate a candidate architecture, the architect must derive three numbers from first principles and verify them against the substrate: 1. **Weight memory.**

$$W = N \times \text{bytes-per-param}$$

where N is the parameter count and bytes-per-param is 2 for FP16 (replace 2 with bit-width/8 for quantization). Derived fact [ILLUSTRATIVE][DERIVED]: $70 \times 10^9 \times 2\ \text{B} = 140$ GB. 2. **KV cache footprint.**

$$KV = 2 \times n_{\text{layers}} \times d_{\text{hidden}} \times L \times \text{bytes-per-activation}$$

where L is the context length. For a 70B model with 8-bit KV caching, this is approximately 12.06 GB for 9.2K context (the raw tensor byte-halving bound: 2.62 MB/token FP16 ÷ 2 = 1.31 MB/token, exactly 50% of BF16; 9,200 × 1.31 MB ≈ 12.06 GB, Ch 7); at FP16 precision it is ~24.1 GB [ILLUSTRATIVE][DERIVED]. The architect should compute this for the exact context length of the workload, not assume a fixed value. 3. **Throughput per device.** Tokens-per-second that a single device can sustain for prefill and decode, measured on the target hardware. This is the number that, multiplied by the number of devices in the candidate layout, must exceed the workload's tokens-per-second demand (92K input tokens/s average, 3K output tokens/s average, 368K input tokens/s peak, 12K output tokens/s peak). Vendors publish peak numbers; the architect should treat these as benchmarks to be verified by measuring on equivalent hardware.

All three numbers must be confirmed before a candidate is carried forward ([ASSUMPTION] canonical (Ch 4, Table 4-2)). If any one fails, the candidate is returned to the synthesis step.

12.5. Common Mistakes

- **Menu-picking without constraint validation.** Browsing vendor offerings and selecting the one that "feels right" rather than generating candidates against quantified hard constraints. This is the opposite of the constraint-driven method described here.
- **Ignoring the KV cache residency arithmetic.** Assuming that the weight memory is the only memory budget item. In input-heavy workloads ([ASSUMPTION] canonical (Ch 4, Table 4-2): 9.2K average context, 30× more input than output), the KV cache is ≈15% of total residency at the canonical 9.2K context (24.1/164.1; rising past 20% beyond ~11K) and is often the binding constraint.
- **Over-optimizing prefix caching.** Assuming that prefix caching can amortize prefill across all requests. In practice, cache effectiveness depends on the overlap of prompt prefixes across the traffic workload; sparse prefix sharing reduces the realized savings.
- **Using KV-quantization as a free lunch.** Quantizing the KV cache reduces memory footprint but introduces quality degradation that may be unacceptable for the target workload. The architect must measure the quality impact before committing to a quantized KV layout.
- **Forgetting the latency split.** Treating the latency budget as a single number rather than a prefill/decode split. A candidate may meet the total latency budget by trading prefill for decode or vice versa, which may not satisfy the service-level objectives for either leg.

12.6. Architecture Consequence

The three candidates carry forward into the evaluation chapters (Chs. 14–16) with distinct test plans, all written against the same three gates — memory fit, throughput at the SLO, and quality. Candidate (a), the single 8×H100 host with prefix caching, is the baseline: we evaluate throughput at the SLO (TTFT/TPOT compliance under load) on a single hardware configuration, with cost-per-token recorded as an economic by-product rather than a gate. Candidate (b), the P/D-disaggregated two-pool, is evaluated on the added complexity of inter-group communication and the pipeline overlap efficacy; we measure whether the latency budget is maintained under the partitioned layout. Candidate (c), the KV-quantized 7B model, is evaluated on the quality-degradation trade-off; we compare answer quality against the 70B baseline and compute the economic break-even point (number of hosts required) against the quality loss. The synthesis method produces these candidates as a set from which the evaluation chapter selects based on quantitative results, not on gut feeling.

12.7. What We Still Don't Know

As of 2026-08, several questions remain open, each flagged **[HYPOTHESIS]**:

- **KV-quantization quality impact at 4-bit for enterprise Q&A.** The quality loss from 4-bit KV quantization has not been systematically characterized across the diversity of enterprise prompts in the canonical workload **[HYPOTHESIS]**.
- **Prefix-caching effectiveness under realistic traffic overlap.** The assumed 30–50% prefill amortization rests on the premise that many requests share document-level prefixes. Empirical measurement of prefix overlap across a production enterprise traffic trace is needed to confirm these numbers **[HYPOTHESIS]**.
- **P/D-disaggregation communication overhead in multi-host settings.** The boundary between parameter-parallel and data-parallel placement is relatively unexplored at the 70B scale; the actual communication volume and its latency impact depend on the routing library and network topology **[HYPOTHESIS]**.
- **Whether 8-bit KV caching is sufficient for 9.2K context at FP16-equivalent quality.** The arithmetic in §12.4 assumes 8-bit KV reduces memory by 2× with minimal quality loss, but the interaction between 8-bit quantization and the retrieval-augmented generation pipeline has not been verified **[HYPOTHESIS]**.

These flags exist because home-lab measurements do not count as reference evidence per the evidence taxonomy; each is an open empirical question a team should validate against its own target workload, not a claim the handbook has settled.

12.8. End-of-Chapter Mini-Case: From Vague Ask to Candidate Architectures

An architect is brought into a design conversation for a company-wide internal Q&A system. The stakeholder states: "We need an AI system that can answer employee questions over our internal documentation, with acceptable quality and within budget." Before any architecture can be defended, the architect applies the constraint-driven method from this chapter.

First, the workload is characterized across the six dimensions. Quality requirements fix the model class: the system must achieve ~70B-model answer quality on enterprise prompts. The traffic profile is the canonical one (Ch. 4/5, canonical scenario (Ch 4, Table 4-2)): ~2,000 registered users, ~5% concurrent (~100), ~10 rps average / ~40 rps peak. The token profile is the canonical 1,200-token prompt plus 8K retrieved context (~9.2K input) plus 300-token answers, with TTFT ≤ 1.2 s (p95 ≤ 2 s) and TPOT ~25 ms/token. The economic ceiling is $15,000 monthly operating budget — a **per-host** ceiling, expressed as the cloud-equivalent of one 8×H100 at ~$20/hr × 730 hr ≈ $14.6K/mo (an on-premise host has no $/hr, so this is a budget cap, not a metered cost), which the reader should note is far below what the full canonical workload costs once the multi-host fleet is sized (Ch 16): the budget is a single-host cap, not the workload ceiling. The consequence must be stated, not dissolved: the fleet the canonical workload requires costs ~$148K/mo (Ch 16) — ~10× the stakeholder's stated $15,000 ceiling — so **the economic constraint, as stated, fails at fleet scale**. Economics is therefore recorded as *not yet passed (deferred)*, and the architect's first return-to-synthesis move is to renegotiate the budget, shape peak demand, or revisit the model class. The operational constraint is that the system must run on existing on-premise GPU infrastructure (no cloud add-ons).

From the token profile, the architect computes: 9.2K input tokens + 300 output tokens ≈ 9.5K tokens per request. At 10 rps average and 40 rps peak, the system must sustain ~92K input tokens/s average and ~368K input tokens/s peak. Three hard constraints follow — the chapter's three gates, verbatim: **memory fit** (weight memory plus KV cache must fit within the on-premise GPU inventory), **throughput at the SLO** (total tokens-per-second across the installed devices, delivered within the TTFT/TPOT budget, must exceed the traffic demand), and **quality** (answer quality on the evaluation set must meet the ~70B requirement).

The architect generates three candidates using the method from §12.3. Candidate (a): a single 8×H100 host with 70B FP16 weights + 24 GB KV cache and prefix caching, which fits the memory budget (164 GB < 640 GB aggregate ([ASSUMPTION] canonical (Ch 4, Table 4-2))) — but as Chapter 8 shows, one 8×H100 host sustains only ~19,800 prefill-tokens/s at the idealized aggregate (8 × 2,471 per GPU; the per-GPU figure is ~2,471, not per-host), far short of the ~92K input tokens/s the 10 rps average demands, so the memory gate passes while the throughput gate already fails. Candidate (b): a P/D-disaggregated two-pool design keeping the full 70B in each pool (prefill and decode pools, each ~164 GB residency on its own 8×H100 host), which buys phase-splitting at the cost of a second host plus the KV-transfer fabric. Candidate (c): a KV-quantized 7B model on a single H100, which fits the memory budget (~15 GB total residency: 14 GB FP16 weights + ~1.2 GB 4-bit KV), but its quality is *provisional* — whether a 7B-class model can reach the required answer quality is a hypothesis to be

measured against the quality gate (Chapter 14), not a settled fact — and it faces the same throughput demand at peak, making it provisionally non-viable.

The architect does **not** discard Candidate (c) by parameter counting alone: it is provisionally moved to the quality-gate evaluation (Chapter 14) to measure whether a 7B-class model actually meets the workload's capability/quality threshold on its evaluation set. Its memory and economics are trivially favorable; its fate turns on that measured gate. Because candidate (c) is strongly suspected to fail the quality gate **[HYPOTHESIS]**, it is not a finalist; the finalists are Candidates (a) and (b), and the near-term decision falls between them. The decision between Candidates (a) and (b) hinges on whether the doubled hardware cost of Candidate (b) is justified by its operational flexibility (e.g., independent scaling of prefill and decode pools, fault isolation). The architect presents both candidates, together with the honest throughput arithmetic of Chapter 8 (no canonical single host meets the full prefill demand alone), to the stakeholder as the decision foundation.

Fig 12.1 draws the synthesis: three conditional candidates, each with its own open gate.

12.8.1. Table 12-1 — Candidate architectures scored against the three gates (memory fit · throughput at the SLO · quality)

candidate	memory: weights+KV	host layout	throughput	SLO	verdict
(a) 8×H100 with prefix caching	**164 GB** (140 + 24)	1 ×8×H100	prefill ~19.8K (idealized; ~28K w/ prefix cache **[HYPOTHESIS]**) · decode BW-bound	✓ memory 164 < 640 GB · ✓ TTFT SLO (≤1.2 s budget, p95 ≤2 s)	**conditional finalist — ✗** single-host capacity: needs ~5 hosts (per-request-latency baseline only)

candidate	memory: weights+KV	host layout	throughput	SLO	verdict
(b) P/D-disaggregated	**164 GB** per pool (140 + 24)	2 ×8×H100 (baseline)	prefill pool ~19.8K/host — same as (a); per-host prefill throughput unchanged by disaggregation	✓ memory per host · ✓ phase-split enables independent scaling	**conditional finalist — ✗** throughput at a single prefill host (~19.8K ≪ ~92K); prefill pool must itself scale to ~5 hosts (92K ÷ 19.8K ≈ 4.65), plus a decode pool; ~2× capex plus fabric
(c) KV-quantized 7B	**~15 GB** (14 + ~1.2)	1 ×H100	high per-GPU prefill tok/s	✗ quality — provisional (subject to Ch 14 quality-gate measurement)	**gated, not a finalist — ✗** quality gate open (Ch 14); ✗ ~2 hosts at peak (Table 12-2)

All figures trace to the canonical scenario (Ch 4, Table 4-2); the KV cache and throughput numbers are [ILLUSTRATIVE][DERIVED] worked examples, not measurement claims.

12.8.2. Table 12-2 — Full-load feasibility matrix (conditional; not a deployment recommendation)

The gate checks above show whether a *single* unit passes. This matrix asks the harder question: what fleet does the canonical workload actually require at **peak**, and is the candidate a demonstrably viable deployment at that load? Host counts are an *illustrative capacity screen* from the fixed per-host prefill rates (~19,800 tok/s for the 70B candidates; ~197K tok/s for the 7B) — **not recommended fleet counts**. Time-sharing, prefix reuse, heterogeneous hardware, real utilization, admission policy, and




FIGURE 12.1: Candidate architecture synthesis, constraint-first: three **conditional candidates**, each with its own open validation gate (not a settled verdict), all tested against the same MEM/THR/QUAL gates (memory fit · throughput at the SLO · quality). **Scope:** canonical workload (~2,000 users, ~10/40 rps, 9.2K-in/300-out); per-candidate verdicts in Table 12-1 / §12.3. — no candidate is deployment-validated; each must measure its gate (throughput for a/b, quality for c) at the target load (Chs. 14–17).

measured batch behavior all change them. The candidate is **conditionally viable** (gate still open) until its throughput and SLO are measured under load in Chs. 14–17; it is **not** a validated survivor.

Candidate	Prefill hosts, avg 92K tok/s	Prefill hosts, peak 368K tok/s	Decode capacity	Peak headroom (N−1)	Monthly fully loaded cost	Feasibility at declared SLO
(a) 8×H100 + prefix cache	~5	~19 (368K ÷ 19.8K ≈ 18.6, ceil 19) *before headroom*	requires separate decode capacity	not demonstrated	~20 hosts, ~$148K/mo total (self-host, Ch 16); cloud-equivalent ≈$292K (§12.8)	**? unmeasured** — peak prefill and SLO not demonstrated; illustrative screen only
(b) P/D-disaggregated	prefill pool ~5	prefill pool ~19, *before headroom*	decode pool sized to 3K tok/s avg / 12K tok/s peak	not demonstrated	~20 hosts, ~$148K/mo total (self-host, Ch 16) + fabric (adder not costed in Ch 16)	**? unmeasured** — same peak prefill screen; phase-split defers but does not remove it
(c) KV-quantized 7B	~1 (92K ÷ ~197K)	~2 (368K ÷ ~197K), before headroom	high	not demonstrated	low (single H100)	**? unmeasured** — fails the quality gate until measured (Ch 14)

Two reading rules for this matrix. (1) **Illustrative screen, not a fleet plan.** The ~19 prefill hosts at peak follows from the fixed, illustrative single-host prefill rate (~19,800 tok/s) divided into the peak input-token demand (368K tok/s). This is a capacity *screen* that exposes the magnitude of the scaling

problem; it is not an operational recommendation, because real utilization, time-sharing/prefix reuse, heterogeneous hardware, admission policy, and measured batch throughput differ. (2) **Demand to serve vs demand to shape.** The matrix counts demand the system must serve at the SLO; a system may instead queue, shed, or shape (off-peak, cap-and-queue, batch it) part of the peak, which is an *operational policy*, not a throughput given. The architecture must state which it does before the host counts mean anything. Until the gates in Chs. 14–17 are passed, **no candidate is a deployment-validated survivor**; all three are conditional candidates with an open validation gate.

Next chapter: Chapter 13 — Reference Architectures: From Local to Hyperscale, which lays out the deployment ladder (single site to hyperscale) these candidates will be judged against — the ladder is reference material, not a placement of (a)/(b)/(c). The 7B candidate's quality gate is then administered in Chapter 14 (Benchmarking), where the capability screen decides which candidates qualify for deployment.

CHAPTER 13.

Reference Architectures: From Local to Hyperscale

The Architect's Question

After this chapter we should be able to look at a characterized workload and place it on the right **archetype** — the canonical deployment shapes that recur across the industry — without reinventing a design from scratch. We will map the four tiers (local/edge, server, cluster, hyperscale), state what each can serve in model size and traffic, and develop the decision rule for when a workload outgrows a tier and must escalate. After this chapter, "we run on a server" or "we need a cluster" is a defensible, quantified statement tied to the workload's numbers — not a guess.

13.1. Concept

Architectures recur not because engineers lack imagination but because the *constraints* recur. Four archetypes cover the vast majority of AI deployments, distinguished by how many GPUs are involved and over what interconnect:

1. **Local / edge** — a single GPU (or a laptop-class accelerator). Serves small models (up to ~7-13B at tight context) that must run on-device for privacy, latency, or connectivity reasons. Interconnect is not the question; memory capacity is.

2. **Server** — one host with 1-8 GPUs, typically H100/H200, joined by NVLink/NVSwitch. Serves dense models up to ~70B-180B with real concurrency. This is the canonical enterprise-Q&A tier and the book's 8×H100 baseline. [ILLUSTRATIVE][ASSUMPTION] (the tier's model-size

range is a book-defined characterization; the H100/H200 and NVLink/NVSwitch specs it cites are [1P] vendor datasheets)

3. **Cluster** — multiple hosts (tens to hundreds of GPUs) joined by InfiniBand or high-speed Ethernet. Required when a model exceeds a node's memory (so it must be split per Ch10) or when traffic outgrows one host (so P/D disaggregation per Ch11 applies).

4. **Hyperscale / data-center fleet** — dedicated fleets of specialized inference/training clusters, often MoE or KV-centric (Mooncake-style disaggregation [S4][1P]), serving many tenants at enormous scale. The economics favor extreme specialization.

These are a *continuum*, not hard categories; the useful question is always **which tier does OUR workload's bounds demand?**

13.2. Mental Model

Each tier is a **box with a fixed memory budget and a fixed cross-node bandwidth**. A workload fits a tier if (a) the model's weight + KV residency fits the tier's total GPU memory (Ch7), and (b) the tier's interconnect can carry the communication the chosen parallelism requires (Ch9/Ch10), and (c) the resulting throughput + latency meets the SLO (Ch11).

The mental model is a **ladder with explicit rungs**: we climb a rung when a binding constraint can no longer be met. The three classic triggers for climbing:

- **Memory**: model + KV no longer fits one node ⟶ cluster (split weights).
- **Traffic**: one host's throughput ceiling (goodput) below demand ⟶ more replicas (DP across nodes) or P/D disaggregation ⟶ cluster.
- **Latency/geography**: SLO can't be met due to distance or contention ⟶ move the serving edge closer (local) or split prefill/decode.

We do not climb for fashion; we climb when a measured number crosses a threshold.

13.3. Worked Example

13.3.1. Placing the Canonical Workload

The canonical enterprise-Q&A RAG workload sits firmly on the **server** tier. We verify each bound:

- **Memory**: 70B FP16 weights = 140 GB; KV for the 9.5K max context at FP16 ≈ 24.9 GB; inference residency ≈ 165 GB [ILLUSTRATIVE][DERIVED]. An 8×H100 host (640 GB) fits this with ample headroom for concurrency (Ch11 showed ~24 GB per request × concurrent requests still fits). ✓ [ILLUSTRATIVE][DERIVED]

- **Throughput/latency**: ~10 rps average / 40 rps peak, input-heavy (9.2K in / 300 out). On the *per-request latency* axis, Ch11 showed continuous batching + prefix caching keeps p95 TTFT

under the 2 s SLO on a single 8×H100 host. **But on the *capacity* axis the single host does not carry the full arrival rate**: with the canonical ~8.6 s service time, Little's Law puts ≈40 × 8.6 ≈ 344 requests in flight at the peak, against ~17.5 KV-resident requests per host — so a single host is a *latency-feasible* but not *capacity-sufficient* server (Ch16/17 size the fleet to ~20 hosts at the 40 rps peak). The tier choice here is about model residency and per-request latency, not about whether one host serves the entire peak arrival. [ILLUSTRATIVE][DERIVED]

- **Interconnect**: parallelism is unnecessary (one node) — the interconnect question doesn't bind. ✓

So the **server** tier is the right *model-residency* archetype for the canonical workload — the model and its KV fit a single 8×H100 node and the per-request TTFT SLO is met on one host. It does **not** mean one host serves the whole arrival rate; a single host is latency-bound and the peak capacity is a fleet-computing question (Ch17). [ILLUSTRATIVE][DERIVED]

13.3.2. Escalating: When 10×Traffic Forces the Cluster Tier

Now suppose the workload's demand grows to ~100 rps average (a 10×). Recompute the ceiling:

- **Throughput ceiling of one host**: continuous batching on 8×H100 at ~9.5K tokens/request sustained roughly tens of thousands of tokens/s; goodput against the SLO is the binding number. At ~100 rps × 9.5K tokens = ~950K tokens/s, one host's goodput is exceeded. [ILLUSTRATIVE][DERIVED]
- **Response**: replicate the model across multiple servers (data parallelism at the serving layer — run N identical 8×H100 hosts behind a load balancer). At ~100 rps average with the canonical ~2.0 req/s goodput ceiling per host (Ch 16/17, C/W ≈ 17.5 KV-resident ÷ 8.6 s), the replica count is ~100 ÷ 2.0 ≈ **50 hosts** — not a handful. The escalation is still the **cluster** tier: the model fits one node (no weight-splitting), but the *fleet* is a real cluster sized by the per-host goodput ceiling. The escalation is driven by traffic, not memory. [ILLUSTRATIVE][DERIVED]

13.3.3. Dropping a Tier: When Privacy Forces Local

If the workload must run fully on-site without data leaving a facility, and the model can be distilled to a 7-13B capable of the Q&A task, the **local/edge** tier applies: a single GPU runs the distilled model at reduced (but acceptable) accuracy for privacy. The tier choice traded capability for the operational constraint (privacy). [ILLUSTRATIVE][DERIVED]

Table 13-1 — Reference architecture archetypes

Tier	GPUs	Interconnect	Model range	Typical latency	When to use
Local / edge	1	—	≤7-13B dense	low (on-device)	privacy, offline, connectivity
Server	1-8	NVLink	≤~70-180B dense	median ≤1.2 s TTFT, p95 ≤2 s (canonical, Ch 4)	most single-tenant enterprise
Cluster	tens-hundreds	InfiniBand/Eth	any that needs splitting	depends	model > node, or traffic > host goodput
Hyperscale fleet	dedicated	high-bandwidth fabric	MoE+, specialized	extreme-scale economics	multi-tenant, largest scale

(Bounds are [ILLUSTRATIVE][DERIVED] design heuristics, not vendor guarantees.)

13.4. Measurement

The tier decision is only as good as the numbers that trigger it. We measure three things:

1. **Residency vs tier memory** (Ch7): does weight + KV fit? If not, the floor is a cluster.
2. **Host goodput ceiling vs demand** (Ch6/Ch11): measure the max rps/tokens/s the host delivers at the SLO, and compare to demand. When demand > ceiling, escalate.
3. **Communication fraction** (Ch9/Ch10): if the parallelism the cluster requires spends >~20% of step time on collectives, the interconnect (not the GPU) is the binding tier constraint.

These three numbers locate the workload on the ladder objectively.

13.5. Common Mistakes

- **Choosing hyperscale before measuring goodput.** Most workloads never exceed one host's *latency* budget; the mistake is building a fleet before measuring whether traffic actually

outgrows one host's capacity. (Note: the book's own canonical workload *does* outgrow one host's capacity at its 40 rps peak — ~20 hosts per Ch17 — so for that workload the fleet is warranted, not premature.)

- **Using model size as the only tier driver.** A 70B model fits a server; traffic, not size, usually forces the cluster — an architect who only watches parameters escalates too early or too late.
- **Ignoring the operational constraint.** Privacy/geography can force a *lower* tier regardless of what compute wants; the ladder is bounded by operations, not just performance.
- **Assuming a smaller model can't serve the tier.** Distilled small models on local GPUs can meet the goal when the capability suffices — don't over-provision the tier.
- **Treating tiers as walls.** They are a continuum; the correct answer can be a hybrid (edge cache + server generation) the measured numbers justify.

13.6. Architecture Consequence


The archetype sets the entire downstream design vocabulary. On the **server** tier (canonical), the consequences are already established: continuous batching + PagedAttention + prefix caching (Ch11), KV quantization when residency binds (Ch7), no parallelism (Ch10). Moving up to **cluster** introduces: DP/PP/TP replicas (Ch10), P/D disaggregation (Ch11), and interconnect budgeting (Ch9). Moving **down** to local forces distillation and on-device KV limits. The tier is the top-level decision; every other choice in the book slots beneath it.

13.7. What We Still Don't Know

- **Exact host goodput ceilings** depend on the specific server, model, degree and batching; the representative numbers here are [UNRESOLVED] per deployment.
- **When P/D disaggregation's benefit crosses its cost** for mid-tier workloads is [HYPOTHESIS]; the breakpoint is workload- and fabric-specific.
- **Fleet-level economics** (Ch16 TCO across a cluster) interact with the tier choice in ways that are [HYPOTHESIS] until a real cost model is applied.

13.8. End-of-Chapter Mini-Case: Escalating Through the Reference-Architecture Tiers

An architect returns to the canonical internal Q&A service a year later. The company has grown from ~2,000 to ~20,000 users; traffic is now ~10× (≈100 rps average). The on-prem service is saturated: p95 TTFT has drifted to 3 s against the 2 s SLO [ILLUSTRATIVE SCENARIO INPUT]. Applying this chapter's ladder, the architect measures the three triggers. Memory: the 70B model still fits one 8×H100 node (165 GB max residency), so the *model* does not force a cluster. Traffic: host goodput is exceeded at ~100 rps — the binding trigger. Operational: the data privacy requirement still forbids a public hyperscale cloud. The architect's decision: escalate to the **cluster** tier but keep it on-prem — run a fleet of 8×H100 replicas behind a load balancer. With the canonical ~2.0 req/s goodput



escalate only when a constraint binds — else STOP; tiers are orthogonal levels of scale, not a ranking

FIGURE 13.1: The reference-architecture ladder and its escalation triggers. Escalation (red) fires when model/KV/throughput outgrows a tier; de-escalation (green) fires on privacy, data sovereignty, and cost — but scale-down decisions should also reference **utilization** (sustained low load on a tier), **failure domain** (a smaller tier has a smaller blast radius), **operations burden** (fewer hosts to run), and **SLO margin** (headroom to absorb a burst without breaching the SLO). Make these measurable: e.g. de-escalate when 30-day p95 utilization < 40% AND SLO margin > 2× AND the smaller tier's failure domain is acceptable.

The reference-architecture ladder: single GPU ⟶ single host ⟶ multi-host ⟶ cluster/fleet, with escalation triggers (red: model/KV/throughput outgrows a tier) and de-escalation (green: privacy, data sovereignty, cost) moving a workload between tiers.

ceiling per host (Ch 16/17), the fleet is ~100 ÷ 2.0 ≈ **50 hosts**, a real cluster rather than a handful; each replica sits well under its per-host ceiling. The result: p95 TTFT back under 1.8 s at 100 rps [ILLUSTRATIVE SCENARIO RESULT], on site, without hyperscale — because the architect climbed the ladder precisely one rung, and the correct rung was determined by the measured traffic trigger, not by fashion or by model size alone.

CHAPTER 14.

Benchmarking: Predicting Real Experience, Not a Leaderboard

The Architect's Question

After this chapter we should be able to look at a benchmark result and judge whether it predicts what our users will actually experience. We will draw the crucial distinction between **capability benchmarks** (what a model can do on standardized tasks) and **deployment benchmarks** (what a system will do on OUR workload), then build a workload benchmark from the six-dimensional characterization (Ch4) that measures the numbers that actually decide architecture. After this chapter, "the model scores well on MMLU" is recognized as a weak claim — and "it meets our p95-TTFT SLO at 40 rps on our token profile" is a strong one.

14.1. Concept

Benchmarking fails most often because the wrong benchmark is used for the wrong decision. The fix is to separate two very different instruments:

1. **Capability benchmarks** — measure the model's output quality on standardized tasks (MMLU, GSM8K, HumanEval, MT-Bench, retrieval-QA suites). They answer: *is this model good enough at the skill our workload needs?* They do NOT tell us how fast, how cheap, or how it behaves under our traffic — model capability is the goal (Ch4's Quality dimension), never the bottleneck.

2. **Deployment benchmarks** — measure the *system's* behavior on a representative workload: TTFT, TPOT, throughput, goodput, KV cache utilization, cost per request. They answer: *does*

this model-on-this-hardware meet the SLO at our traffic and token profile? These are the numbers that actually pick the architecture.

The core insight: **a capability leaderboard is a poor proxy for serving performance.** Two models with identical MMLU can differ wildly in TTFT under the same batching, because serving depends on tokenizer, context length, KV layout, and scheduler — none of which a leaderboard scores. Benchmarks select models only after capability filters and deployment measurement both pass.

14.2. Mental Model

Capability benchmarks serve as **screening** and deployment benchmarks as **selection**. Screening answers "which models are even in the running?" cheaply and broadly. Selection answers "among the screened-in models, which system actually works for our workload?" expensively and precisely. The two-stage mental model prevents two classic errors:

- Screening with deployment metrics — e.g. benchmarking a model's MMLU to pick a serving stack. (Wrong tool.)
- Selecting with leaderboards — e.g. taking the top-scoring MMLU model and assuming it will meet our SLO. (Wrong tool, again.)

Just as important, we benchmark the **workload, not the model in the abstract.** A deployment benchmark that doesn't reproduce our token profile (input/output ratio, context length), our traffic (rps, concurrency, burst), and our SLO (percentiles) is measuring someone else's problem.

14.3. Worked Example

14.3.1. Designing a Deployment Benchmark for the Canonical Workload

We build a deployment benchmark for the canonical enterprise-Q&A RAG workload (canonical scenario (Ch 4, Table 4-2)): ~10 rps average / 40 rps peak, ~9,200 input tokens (1,200 query + 8K retrieved) + ~300 output, TTFT budget (median ≤ 1.2 s, p95 ≤ 2 s), TPOT ~25 ms/token. [canonical scenario (Ch 4, Table 4-2)]

Step 1 — representative queries. We sample real user questions and run them through the rag pipeline to produce the actual prompt shapes, matching the ~9.2K-in / ~300-out token profile with the model's own tokenizer (not a heuristic). [2°]

Step 2 — sweep the offered load, do NOT test a single point. The analytical concurrency figure ($C \approx 17.5$, ~2.0 req/s) is a *starting hypothesis*, not the answer. We sweep the offered load/concurrency across a range and measure the tail at each point, so the benchmark finds the SLO-satisfying operating regime instead of validating the model at the point the model selected. Run a load series (e.g. 2, 4, 8, 12, 16, 20, 24, 28 concurrent at the canonical $_{9.2\text{K-in}/}$300-out profile, scaled to a host's achievable concurrency) and record, at each level:

- **TTFT** p50/p95/p99 (must be median ≤ 1.2 s, p95 ≤ 2 s).
- **TPOT** p50/p95 (≤ ~25 ms median).
- **Goodput** — tokens/s that meet the SLO (Ch6), not raw throughput.
- **KV cache utilization** and prefix-cache hit ratio (to validate the serving choices of Ch11).
- **Admission / rejection** — the offered-load level at which the server starts queueing or rejecting (the saturation knee).

The analytical ceiling sets the *range* of the sweep and flags which levels are physically impossible (a single 8×H100 host cannot hold ~344 in-flight requests; that is a fleet burst served by ~20 hosts, Ch 16-17). The benchmark then reads off the highest offered load that still meets the SLO — that *measured SLO-goodput* is the provisioning input, not the analytical C/W. The server is loaded at the concurrency it can actually hold, and we sweep across that achievable range rather than testing one number.

Step 3 — read the result. Suppose candidate A (a 70B dense on 8×H100) shows p95 TTFT 1.9 s and a measured goodput that meets the per-request TTFT SLO at the ~17.5-concurrent / ~2.0-req-per-second analytical load it can hold. The host's prefill ceiling from Ch 8 is ~19,800 tok/s — the right order for the prefill leg of that rate (2.0 × 9,200 = 18,400 input tok/s, Ch17 §17.4.2); the summed ~19K figure must not be compared to a prefill-only ceiling (Ch17) — but that is the *prefill-only ideal*, not the goodput: the benchmark's goodput is the SLO-windowed prefill+decode figure under continuous batching, and it is the benchmark (not the ceiling) that confirms the SLO is met at that concurrency. Candidate B (a smaller 7B) shows 0.6 s TTFT — much faster — but scores lower on the capability screen for the retrieval-QA quality threshold. We therefore *select* A for deployment (capability + deployment both pass), not B (capability fails despite speed). The benchmark did not score one number; it reproduced the decision. [ILLUSTRATIVE][DERIVED]

Table 14-1 — Capability vs deployment benchmarks

Instrument	Answers	Example metrics	Picks	Risk if misused
Capability benchmark	is it good enough at the skill?	MMLU, GSM8K, HumanEval, retrieval-QA	which models qualify	using it to pick a serving stack
Deployment benchmark	does the system meet the SLO on our workload?	TTFT/TPOT p50-p99, goodput, KV util, $/request	which system to deploy	mistaking a leaderboard for this

14.4. Measurement

Four habits make benchmarks trustworthy:

1. **Use the model's own tokenizer** on representative real prompts. The "4 chars ≈ 1 token" estimate can be 2-5× off for code/JSON/technical text (Ch6).
2. **Measure distributions, not means** — log p50/p90/p95/p99 for every latency metric and the full token-length distribution. A 32K-tail context is a different workload than a 9.2K average.
3. **Reproduce the concurrency and burst** — a benchmark must hit the model at our peak concurrency, not a single request, or it won't show the queuing and KV contention that break SLOs.
4. **Include goodput and cost, not just latency** — the SLO-windowed throughput and $/request complete the picture for the economics (Ch16).

14.5. Common Mistakes

- **Citing a capability leaderboard as proof of serving fitness.** MMLU does not predict TTFT; it screens capability only.
- **Benchmarking a single request.** Real SLOs break under concurrency; a single-request benchmark hides the tail.
- **Mean-only latency reporting.** A 0.84 s mean hides a 5 s tail that breaches the p95 SLO (Ch6).
- **Using the wrong tokenizer estimate.** Under-counting context via the 4-char heuristic mis-sizes KV cache and prefill.
- **Optimizing raw throughput past the SLO window.** Bigger batch sizes raise tokens/s but push TTFT over the deadline, zeroing goodput (Ch6, Ch11).

14.6. Architecture Consequence

The benchmark is the bridge from candidate architectures (Ch12) to selection and then to TCO (Ch16):

- **Capability screen** narrows the candidate models (from Ch3/Ch5 model-selection) to those that meet the accuracy/quality threshold.
- **Deployment benchmark** then measures each surviving candidate under the canonical workload, producing the TTFT/goodput/cost numbers that drive the choice.
- **The chosen system** becomes the basis for the TCO and performance-engineering work of Ch15-16.

The benchmark is not a one-time event; it is the recurring production validation that catches drift (model updates, traffic shape changes, memory pressure) before they breach the SLO.




FIGURE 14.1: Capability screen then deployment benchmark
Two-stage benchmarking: capability screen (which models qualify) → deployment benchmark (which system meets our SLO), feeding selection and TCO.

14.7. What We Still Don't Know

- **How closely capability benchmarks predict enterprise Q&A quality** for a given domain is [UNRESOLVED]; a custom retrieval-QA screen on real documents is stronger but costly.
- **Portable goodput ceilings** across serving stacks are [HYPOTHESIS] until measured on the target host with the target model.
- **The long-run relationship between capability and serving performance** (whether a more-capable model buys latency headroom on our cards) is [HYPOTHESIS].

14.8. End-of-Chapter Mini-Case: Capability Screen vs. Deployment Benchmark

A team of skeptical engineers tells the architect: "The new model tops MMLU, we should just deploy it." Applying this chapter, the architect separates the claims. Yes, the model passes the capability screen for retrieval-QA quality. But the architect refuses to stop there: they build a deployment benchmark reproducing the canonical workload — real prompts at ~9.2K in / ~300 out, 40 rps peak (≈344 in-flight, Ch17), the SLO (TTFT median ≤ 1.2 s, p95 ≤ 2 s; TPOT ~25 ms) — and measure the new model on the existing hardware. The result: the leaderboard-topping model's tokenizer produces more tokens for the representative prompt corpus (a larger token count for the same text) and it has slower prefill, driving p95 TTFT to 2.6 s — breaching the SLO that the incumbent 70B met at 1.9 s. The team does not deploy the leaderboard winner. The architect's discipline — screen with capability, select with deployment — prevented a service degradation that a single MMLU score would have caused. The benchmark, done right, did not rank models; it predicted experience and saved the service.

CHAPTER 15.

Performance Engineering: From "It Works" to "It Meets the SLO"

The Architect's Question

We are tasked with engineering performance for a serving layer that must absorb the day-to-day traffic of a growing user base while delivering acceptable latency. The core question: how do we configure an 8×H100 host to serve a 70B parameter model at 40 requests-per-second peak while keeping per-request latency within a target budget, and what architectural knobs—batch size, KV cache design, kernel choice—most affect that outcome? This chapter walks through the performance-engineering lifecycle: from concept, to mental model, to worked arithmetic, to measurement, to common pitfalls, to architectural consequences, to open questions, and finally a mini-case that ties the thread.

15.1. Concept

Performance engineering in LLM serving is the discipline of matching compute, memory, and I/O throughput to the stochastic workload of token generation and prompt processing. Unlike traditional web serving, where request-cycle overhead dominates the tail, the dominant cost in LLM inference is the arithmetic intensity of transformer matrix multiplications and the memory bandwidth consumed by KV cache reads and writes on every token step. The serving system must therefore optimize three inter-dependent quantities: token throughput (tokens/s), per-token latency, and GPU memory utilization. These are governed by the model FLOP count, the chosen kernel (e.g. FlashAttention vs. scaled-dot-product), and the batching strategy (static vs. dynamic, continuous vs. chunked). The architect's first move is to identify which resource—compute, bandwidth, or latency—is the primary

constraint for the canonical scenario, then apply the appropriate optimization to shift the bottleneck. A secondary concept is the trade-off between batch size and tail latency: larger batches amortize kernel launch overhead and increase arithmetic intensity, but they increase the wait time for straggler requests, raising p99 latency. The designer must therefore balance arithmetic gain against tail-latency penalty, a tension that shapes every later architectural decision.

15.2. Mental Model

We model the serving request lifecycle as a pipeline of computational phases with a cross-cutting state-management plane. The compute phases run in order: (1) request preprocessing / tokenization, (2) prefill, (3) iterative model decode, (4) token sampling / selection, (5) detokenization / streaming. **KV management is not a temporal stage after generation** — allocation, growth, paging, reuse, eviction, and (in a disaggregated deployment) transfer occur throughout the whole request lifetime, so we draw it as a state-management plane that spans prefill and decode rather than a step that follows them. Each compute phase has a resource ceiling: compute-bound phases are limited by TFLOPS, memory-bound phases by GB/s of GPU HBM bandwidth. The architecture designer must identify which phase is bottlenecked for the canonical scenario and then apply the appropriate optimization—kernel fusion, cache reuse, or batching—to shift the bottleneck. The mental model also emphasizes the role of token reuse: when many users share similar prompt prefixes, the KV cache can be partially shared, reducing memory traffic. This reuse effect is difficult to quantify without workload profiling, but it is a first-order consideration in multi-tenant serving. The model also captures the interaction between sequence length and memory cost: attention quadraticities ($O(L^2)$ FLOPs and $O(L^2)$ memory per head once the QK^T/softmax score matrix is materialized) mean that long contexts (9,000+ tokens) disproportionately strain both compute and HBM bandwidth, making kernel choice (FlashAttention vs. SDPA) one of the first *kernel-level* optimizations to validate for long-context prefill — not a demonstrated global ranking, since prefix reuse, KV precision, batching policy, P/D scheduling, weight precision, admission control, and simply provisioning more prefill capacity can each dominate depending on the measured workload.

15.3. Worked Example

Canonical scenario: ~2,000 registered users, ~5% concurrent (100 users), ~10 rps average / ~40 rps peak, prompt ~9,200 input tokens + ~300 output, the canonical 80-layer, hidden-8192, full-MHA 70B reference model (a 70B-class dense FP16 model), 8×H100 host with 640 GB GPU memory.

Derived quantity 1 – concurrent users: 2,000 ×0.05 = 100 users.

Derived quantity 2 – peak token throughput demand: At 40 rps the workload mixes **prefill** (input) and **decode** (output) tokens, and they hit the hardware differently. Prefill demand = 40 rps × 9,200 = 368,000 input tokens/s; decode demand = 40 rps × 300 = 12,000 output tokens/s. These two regimes must not be collapsed into one "380,000 tokens/s" when reasoning about compute, because

long-prompt prefill commonly occupies a higher-arithmetic-intensity regime and low-batch decode commonly occupies a lower-arithmetic-intensity regime; whether either phase is actually compute- or bandwidth-bound is a property of the model × workload × kernel × hardware operating point (Chapter 8).

A hard terminology distinction the rest of this book relies on. Do not conflate two separate statements:

- **Kernel regime** — the arithmetic intensity of the *kernel* relative to the roofline ridge (is this one kernel compute-bound or bandwidth-bound?).
- **Workload capacity deficit** — the aggregate offered demand relative to the achievable service capacity (does the *deployment* have enough compute/bandwidth/concurrency to absorb this arrival rate?).

A workload can exceed a deployment's capacity even when the underlying kernel is not compute-bound; conversely, a compute-bound kernel does not imply the deployed fleet lacks compute. In the canonical scenario at peak, prefill exerts a large aggregate compute *demand* (a capacity-deficit signal), while the prefill *kernel's* high arithmetic intensity is what makes it land on the compute plateau of the roofline — two different facts that happen to co-occur. Keep them separate.

Compute demand versus peak — and why this is not an MFU: A 70B FP16 transformer needs ≈2 $\times 70 \times 10^9$ FLOPs per generated token. The instantaneous prefill compute demand is 368,000 $\times 2 \times 70 \times 10^9 \approx 5.15 \times 10^{16}$ FLOPs/s, against a theoretical FP16-dense peak of 8 ×989 TFLOPS = 7.91×10^{15} FLOPs/s for the 8×H100 host (989 TFLOPS per GPU, Chapter 8 canonical). Taken naively this ratio is ~6.5× — a demand that *exceeds* a single host's peak. That is a legitimate and important architectural signal: a single 8×H100 host cannot prefill the peak arrival rate on the naive dense-FLOP model, so prefill either needs to be spread across burst headroom, handled by prompt/prefix caching, disaggregated (P/D separation), or absorbed by queueing headroom at off-peak. What it must **not** be called is "MFU = 6.5": MFU (Model FLOPs Utilization) is by definition achieved realities divided by peak — a utilization ratio that **cannot exceed 1.0**. Presenting a ratio above 1 for a utilization metric is a unit/modeling error. The honest formulation separates the two quantities. The first is a *congestion check*: is the arrival-rate FLOP demand above or below peak? Here it is ~6.5× above for prefill, so the host is prefill-starved at peak and must lean on caching/batching/queueing. The second is an *achieved MFU*: measured device FLOPs ÷ peak, which we only report from a real benchmark. For illustration we suppose it lands in the 30–40 % range for FlashAttention-based inference. The decode figure at 12,000 tokens/s is $\approx 1.68 \times 10^{15} \div 7.91 \times 10^{15} \approx 0.21$, i.e. ~21 % — again a groundable number, not a ceiling-defying one; the actual achieved value must come from the target serving benchmark. The architectural conclusion, that there is no single bottleneck for the whole request, stands — and it must be argued phase by phase. At the canonical peak, prefill shows a *workload capacity deficit* — aggregate compute demand above the host's peak (it needs more FLOPs/s than the host can supply, and leans on caching/queueing). Decode is primarily memory-bandwidth constrained, and maximum concurrency is constrained by KV residency. Each phase is established from arithmetic intensity and

the roofline (Chapter 8), never from an impossible "MFU > 1." None of them is the same statement as "the prefill kernel is compute-bound." The ~6.5× figure is a **lower-bound impossibility check** (the host cannot meet peak on the naive dense model), not a fleet-sizing estimate: the real fleet count comes from the achieved prefill tokens/s under the actual latency SLO and representative traffic mix (Ch 17/20), and it is sensitive to cache-hit rate, input-length distribution, batch schedule, and sustainable efficiency — the 6.5× only says "more than one host is required," not "how many."

KV cache memory footprint: The KV cache grows linearly with cached context and layers; it must never be computed per-layer and then treated as the whole-model total. For the canonical full-MHA reference geometry (80 layers, hidden dimension 8,192 — the 70B-class teaching model, not a universal 70B property), the per-token footprint across ALL layers is 2 × layers × hidden × bytes = 2 ×80 ×8,192 ×2 = 2,621,440 B ≈ 2.62 MB/token (2.5 MiB; canonical value from Chapter 7) — not the 32 KB that a single-layer calculation would suggest. For a 9,500-token context, one user's KV cache is therefore ≈9,500 ×2.62 MB ≈ 24.9 GB, not ~304 MB. For the canonical workload's ~86 average in-flight requests at 10 rps (L_exec = λ × W_exec ≈ 10 × 8.6; see Ch 4 — note ~86 is the *request occupancy*, distinct from the ~100 *active-user* population), the total KV cache would be ≈86 × 24.9 GB ≈ 2,140 GB — which **does not** fit the 640 GB GPU pool; using the canonical practical KV budget (640 GB − 140 GB weights − ~64 GB runtime/workspace ≈ 436 GB), only ≈17.5 concurrent *requests* (9,500-token KV each) fit on-host for KV (436 GB ÷ 24.9037 GB; conservative integer floor 17 (aggregate bound; per-rank and fragmentation must be checked separately)), before also reserving weight residency. This is a decisive, order-of-magnitude correction to the intuitive picture: long-context KV is a first-order memory constraint, and the architect sizes concurrency by KV capacity, not by the small per-layer number. Doubling context to 19,000 tokens pushes per-user KV to ~49.8 GB (19,000 × 2.62 MB) and halves on-host concurrency to ~8.7 (436 GB ÷ 49.8 GB; conservative integer floor 8). The canonical unit-check rule (quantity/unit/formula/substitution/result/sanity) catches this class of error: if 9,500 tokens × ~2.5 MB/token ≈ 24 GB does not reconcile with the intended ~304 MB, the unit layer-count has been dropped.

Attention FLOP comparison: Scaled-dot-product attention (SDPA) for 9,200-token prompts. Note the 2P/token figure above approximates the *parameterized dense-matmul* work per token (2 × parameters); it does **not** capture all sequence-length-dependent attention work, which is accounted for separately here. Attention is two matmuls per token per head — $Q \cdot K^T$ then ·V — each a multiply-accumulate of $L^2 \cdot d$, so in FLOPs (2 per MAC) the per-layer cost is ≈ 4 × L^2 × d_model, where L=9,200 and d_model=8,192. That is 4 × $9{,}200^2$ × 8,192 ≈ 2.8 × 10^{12} FLOPs per layer (the full 64 heads; the per-head figure 4 × $9{,}200^2$ × 128 ≈ 4.3 × 10^{10} must be multiplied by the number of heads, not quoted alone). Across 80 layers that is ≈ 2.2 × 10^{14} FLOPs — the quadratic attention term that grows dominant at long context, matching Chapter 8's 4·n_layers·L^2·d formula: the attention term is ≈17% of the parameter-matmul FLOPs (≈15% of total forward FLOPs) at 9.2K (Fig 22.1).

FlashAttention is **not** "faster attention" in the sense that it does less arithmetic. It computes the exact same $Q \cdot K^T$, softmax, ·V sequence. What changes is *where the intermediate lives*: a naive kernel




FIGURE 15.1: FlashAttention: the same math, far less HBM traffic. Before (naive / SDPA), the intermediate attention matrix is materialized to HBM and re-read, so every query block re-streams the full K/V row-block — many HBM round-trips. After (FlashAttention), the computation is tiled and fused so each K/V tile is read into on-chip memory once *for that tile* and the result is accumulated in place — far fewer HBM round-trips. **Scope of the "read once" claim:** the tile-level on-chip reuse is per-tile; it is *not* a guarantee that every K/V element is read exactly once globally across all query blocks (the exact number of K/V re-reads depends on the tile scheduling, sequence length, and SRAM size — see the original I/O analysis in the FlashAttention papers). The attention *result* is the same mathematical target; the gain is fewer HBM round-trips, not a change to the attention mathematics. (Floating-point caveat: the tiled accumulation order differs from the naive path, so results are equivalent in exact arithmetic but can differ in the last bits under finite precision — a numerical-equivalence, not a bit-identical, claim. I/O bound: Tri Dao et al., "FlashAttention," NeurIPS 2022, arXiv:2205.14135.)

Read the figure as an I/O story, not a speed-up number.

writes the L×L attention matrix to HBM and reads it back, so the materialized intermediate itself is $O(L^2)$ in memory; FlashAttention avoids materializing that full L×L matrix in HBM and instead tiles the computation so each tile stays in on-chip registers/shared memory with the softmax done online — substantially reducing HBM reads/writes through tiled on-chip computation (the precise I/O complexity is more nuanced than a clean quadratic-to-linear swap, but the materialized-intermediate traffic is what drops). Because the arithmetic intensity — FLOP/byte — rises (same FLOPs, far fewer bytes moved), the kernel moves *up* the hardware ladder of Fig 8.1 toward the compute-bound region, even though the model and the math are unchanged. That is the whole reason the speed-up is workload-dependent: it is largest for long contexts where the $O(L^2)$ intermediate dominates, and negligible for short ones where HBM traffic is already small. It is also why the improvement should be *measured* (Ch. 14) rather than quoted from a published "2–3×" figure that was never portable.

15.4. Measurement

To validate the mental model we instrument the serving stack with three metric families: (a) token latency percentiles (p50, p95, p99) per request type, (b) GPU utilization (SM active, memory bandwidth via Nsight), and (c) KV cache size over time. A minimal benchmark runs 40 rps with warm-up, records the p95 token latency, and measures the GPU memory fraction consumed by KV cache. Repeating with different batch sizes (1, 4, 16, 32) reveals the throughput-latency knee. The *illustrative* numbers below are scenario values to be measured on the target stack, not vendor or published figures: beyond batch-4 the p95 latency typically rises (implying a knee near batch 4) because kernel launch overhead is amortized but inter-request token interleaving increases cache thrashing. **On the FlashAttention "traffic reduction" claim, be precise about the units:** one often sees a FlashAttention-class kernel reported at a *different achieved HBM bandwidth* than a naive SDPA kernel (illustratively ~150 GB/s vs ~400 GB/s for 9,500-token contexts). That is a *rate*, not a byte count. A bandwidth figure alone does not establish that fewer *bytes/request* were transferred — it only shows the kernel's achieved memory throughput. To claim a traffic reduction, compare the **bytes transferred per request** (or read/write transaction counters) under a *matched* workload; the FlashAttention advantage shows up there as fewer materialized/intermediate bytes, not as a low raw bandwidth. **And separate the two cache concepts**: "cold-start KV warm-up" (populating the KV-cache blocks for a new context) is different from "model-weight loading" (streaming the 140 GB weights into HBM) and from CUDA/JIT kernel warm-up. A 70B cold-start that reuses cached weights is far faster than one that must load them from scratch — but these are distinct effects, not one number. Set these illustrative figures from the target host's profiler before quoting them as fact. [ILLUSTRATIVE — set these from the target host's profiler before quoting them as fact]




FIGURE 15.2: Prefix caching and batching act on different serving phases: caching reduces prefill work per repeated prompt; batching raises decode goodput. Illustrative (synthetic) curves, not measured benchmarks — left = prefill work vs prefix-cache hit rate (lower is better); right = decode goodput vs batch size (rises until HBM bandwidth saturates). Units are relative, normalized to the no-cache / batch-1 baseline. [ASSUMPTION]

Goodput vs. Batch Size: the Cache Lever

The capacity response to batch size under peak load. Two distinct levers act on different phases: batching raises decode goodput (right plot) until bandwidth saturates, while prefix caching lowers the prefill work per repeated prompt (left plot) so more prefill-recompute headroom remains under the same host. They are not competing on the same axis.

15.5. The Optimization Decision Map

The measurement section tells us *what is slow*; this map tells us *which lever to try next*. It is organized as a symptom → bottleneck → evidence → candidate mechanism chain, so the architect diagnoses before acting rather than applying a known technique by fashion. **Every mechanism below is a hypothesis to benchmark, not a guaranteed win** — each trades one resource for another, and whether it helps depends on the measured workload and hardware (Ch. 14).

observed symptom	likely bottleneck	evidence / measurement	mechanisms worth evaluating	key trade-off	architecture consequence
high TTFT + compute saturated during prefill	prefill compute	FLOP utilization, prefill queue depth, prefix-cache hit rate	prefix caching, chunked prefill, faster/batched kernels, more compute, P/D separation	compute vs added latency/capacity	add prefill capacity or cache prefixes
high TPOT/ITL + HBM bandwidth saturated	decode bandwidth	HBM bandwidth utilization, effective bytes/token	quantization, batching up, speculative decoding, smaller active params, more bandwidth	latency vs batch/tail	add bandwidth or shrink bytes/token
KV exhaustion / low concurrency	memory capacity	KV bytes/token, context distribution, fragmentation, active sequences	GQA/MQA (if model allows), KV quantization, PagedAttention, context reduction, eviction/offload, prefix reuse	capacity vs transfer latency	lower per-request KV or offload
long-context attention dominated by memory traffic	attention I/O	attention kernel memory traffic vs compute	FlashAttention-class fused/tiled kernels	kernel adoption vs coverage	kernel choice matters for long ctx

observed symptom	likely bottleneck	evidence / measure-ment	mechanisms worth evaluating	key trade-off	architecture consequence
low GPU util, request-lifecycle mismatch	scheduling	SLO miss %, token-size variance, queue depth	continuous batching, scheduler policy	throughput vs tail latency	scheduler is a first-class choice
prefill and decode interfering	heteroge-neous resource demand	mixed-workload p99, phase-locked stalls	P/D disag-gregation — *only after* measuring that the benefit exceeds KV-transfer + orchestration + capacity cost	separation benefit vs KV-transfer cost	possibly two pools
multi-GPU execution dominated by communi-cation	interconnect / parallelism	collective time, TP/PP/EP balance, placement	retune TP/PP/EP/DP topology, placement, partitioning	parallelism vs interconnect	topology is a cost lever

Two cautions. First, do not read the table as "technique X fixes symptom Y": the same symptom can come from two bottlenecks (high TPOT with a bandwidth-saturated GPU is different from high TPOT with a capacity-capped GPU), so the *evidence* column matters as much as the symptom. Second, the last two rows (P/D disaggregation, interconnect tuning) are the expensive, structural levers — they are worth testing only after the cheaper in-kernel and in-scheduler mechanisms have been measured and shown insufficient, because they change capacity, orchestration, and cost, not just a kernel constant.

15.6. Two Mechanisms, Read as Mechanisms

Two entries in the map deserve their mechanism spelled out, because they are frequently cited by reported speed-up numbers rather than by how they work.

Speculative decoding. The idea is to turn one slow serial step into a *draft-then-verify* pair. A small, cheap **draft model** proposes a candidate sequence of tokens; the larger **target model** then *verifies* all of them in a single batched forward pass, accepting the ones that match its own distribution. The loop is: draft → propose candidates → target verifies → accept a prefix → continue from the last accepted token. Why this can be faster: the expensive part of decode is not the arithmetic per token but the *serialization* — each target-model step streams the weights from HBM. If the draft can propose k tokens that the target accepts in one verification pass, the target's expensive weight-stream is spent once on k tokens instead of k times on one — a genuine reduction in HBM round-trips (the same resource the FlashAttention discussion is about, but at the whole-model scale). Why it is *not* free: the draft costs extra compute, the verification pass itself has cost, and the **acceptance rate** (how many of the proposed tokens the target actually accepts) decides the win — a low acceptance rate means the draft and verification are spent for almost nothing. It is therefore workload/model/hardware dependent: a draft that closely matches the target (or a workload that is highly predictable) accepts more. **No published speed-up is portable**: a "6×" from one model/paper is a statement about that evaluation, not a guarantee for a different model or serving stack — measure it on the target workload or treat it as a hypothesis.

One subtlety about "matching its own distribution": the target does *not* simply accept the draft tokens that happen to agree. Under stochastic sampling, accepting a proposed token outright (rather than by the exact-speculative-sampling correction that re-weighs each accepted and rejected token by the target's posterior) can bias the output distribution away from the target model's true distribution. The distribution-preserving result holds only when each proposed token is accepted or rejected by the exact acceptance/sampling procedure (the modified-rejection-sampling step of Leviathan et al., "Fast Inference from Transformers via Speculative Decoding," arXiv:2211.17192; see the Sources chapter), which re-normalizes the continuation at each step. For greedy/argmax decoding the agreement test is exact; for temperature/prompt-driven sampling it is not, and the acceptance criterion must be the correction procedure, not mere token equality.

Chunked prefill. A very long prompt produces a large prefill operation that can monopolize the compute for hundreds of milliseconds, stalling concurrent latency-sensitive decode work. **Chunked prefill** splits that prefill into smaller pieces and interleaves them with decode steps in the scheduler, so the GPU keeps serving decode between prefill chunks instead of blocking on one burst. The causal chain: long prompt → large prefill → scheduler/resource monopolization → decode interference → TTFT *and* TPOT both degrade → chunked prefill as a scheduling mechanism to bound the per-phase burst. The trade-off is *not* "smaller is better": a smaller chunk reduces the decode stall but adds scheduler overhead (more per-chunk bookkeeping, potentially lower prefill throughput from less parallelism within a chunk), so chunk size is an empirically-chosen middle — measure the goodput/latency knee rather than assume.

15.7. Common Mistakes

Over-provisioning batch size to chase throughput: Increasing batch size improves TFLOPS utilization but degrades p99 latency because tail requests wait for larger chunks to fill. The designer must balance batch-size-driven arithmetic gain against tail-latency penalty. A practical illustrative rule of thumb: choose the smallest batch size that keeps MFU above ~25 % while keeping p95 latency under the SLO target (the 25 % threshold and the knee are scenario values — measure them on the target workload). *Ignoring KV cache growth:* A 70B model with 9,500-token contexts consumes ≈24.9 GB of KV per user (≈2.62 MB/token × 9,500, max end-of-generation). Without cache eviction, compression, or a concurrency cap, even ~17.5 concurrent *requests* would exhaust the host's canonical practical KV budget (~436 GB after weights + runtime), so 100 concurrent full-context users require either multiple hosts, much shorter contexts, or KV compression (FP8/8-bit). **But be precise about what "evicting" a context means, because it is not one action.** Three distinct mechanisms exist. (a) *Evicting an idle/inactive prefix-cache entry* — a cached prefix not currently in service — is safe, because no active request depends on it and it can be recomputed on reuse. (b) *Offloading or recomputing the KV of an active request* whose context is still being generated changes nothing about semantics, but it costs a recompute or a transfer when the request resumes. (c) *Deliberate sliding-window or context-truncation strategies* drop older tokens of an *active* request's context. This **changes the model's effective context**: it alters what the attention can attend to, and it is a semantics change, not merely a memory optimization. LRU of inactive cached prefixes is different from truncating active KV. Do not conflate them. **KV quantization** is a separate, orthogonal lever that cuts the per-token footprint without changing semantics (FP8 ≈2.62 ⟶ ~1.31 MB/token — exactly 50% of BF16 by raw tensor byte-halving, the same FP8 constant defined in Ch 7; vLLM's cited 54% [S6] is a decode inter-token-latency slope, a latency metric, not a memory ratio, and any allocator block/metadata overhead is not vendor-measured). *Using scaled-dot-product attention without FlashAttention:* For long contexts (9,200+ tokens) the quadratic memory cost of SDPA ($O(L^2)$) dominates the FLOP cost. FlashAttention fuses read-write-compute and reduces HBM traffic by ~3–5× ([ILLUSTRATIVE] — kernel- and length-dependent; measure bytes/request on the target stack), raising effective arithmetic intensity. This is one of the highest-impact *kernel-level* choices (it sits among prefix caching, KV-precision, batching, and P/D disaggregation as a major lever, not the single deciding one), and it pays off specifically when memory-bound; for moderate lengths (2,000–4,000 tokens) the HBM bandwidth reduction typically translates to a ~1.3–1.8× throughput gain on H100 (illustrative — bench the specific kernel on the target hardware). *Neglecting kernel launch overhead:* In dynamic-batching setups, each new token generation can trigger a kernel launch. Without continuous batching or token-level fusion, the kernel-launch overhead (illustratively ~10–20 % of GPU time on H100-class parts at this traffic) can artificially depress measured MFU.

15.8. Architecture Consequence

The measurement and mistake analysis drive three architecture decisions for the canonical deployment: (1) FlashAttention-2 as the default attention kernel, fused with RoPE and QKV projection to minimize HBM transactions; (2) continuous batching, with the maximum chunk size chosen empirically from the measured goodput/latency knee (a chunk size of 8 tokens is an [ILLUSTRATIVE] configuration, not the recommendation — the knee must be measured on the target stack); (3) KV cache management via FP8 KV quantization (≈2.62 ⟶ ~1.31 MB/token — exactly 50% of BF16 by raw tensor byte-halving, cutting a 9,500-token per-user KV to ~12.45 GB; vLLM's 54% [S6] is a decode inter-token-latency slope, a latency metric, not a memory ratio, and any block/metadata overhead is not vendor-measured) plus length-based eviction, so that under the same ~436 GB practical KV budget on-host concurrency rises from ~17.5 to ~35.0 full-context users (436 GB ÷ 12.45 GB). These choices together are expected to raise achieved token throughput from ~8,000 tokens/s (raw, no flash, batch-1) toward an illustrative ~35,000–70,000 tokens/s [ILLUSTRATIVE achievable range] (with flash, continuous batch) — the exact figure must come from the target benchmark — while keeping the host's 640 GB for weights plus KV. A fourth decision, borne out of the mini-case (Ch11 §11.8), is to design the request-routing layer for KV cache affinity: when a user re-submits a request, routing to the same GPU avoids cache warm-up penalties and keeps p99 latency under the target SLO.

15.9. What We Still Don't Know

How does token-level sparsity in user prompts affect the actual FLOP/token cost, and can we exploit it without accuracy loss? Sparse prompt patterns (e.g. few-shot prefixes, cached query prefixes) could reduce the effective FLOP count, but the savings depend on the sparsity pattern and the attention implementation. *What is the optimal continuous-batch chunk size as a function of request arrival distribution (Poisson vs. bursty) and tail-latency targets?* Analytical models assume Poisson arrivals, but real user traffic exhibits bursts (e.g. social-media events) that may require larger chunks or alternative back-pressure mechanisms. *Can in-flight KV cache compression (e.g. speculative decoding–guided pruning) reduce memory pressure without increasing p99 latency?* Pruning less-important key/value pairs based on attention weight magnitudes is promising, but the accuracy-latency trade-off needs empirical validation across model families. *How does multi-tenant isolation—guarding one user's cache from another's—translate to multi-GPU scaling when the model exceeds a single GPU's 80 GB?* Model parallelism (pipeline or tensor) adds communication overhead; the performance cost of moving KV cache between GPUs during tenant rotation is an open question.

15.10. End-of-Chapter Mini-Case: The Second Host: a Kernel/Batching Gain, Not a Capacity Win

A new deployment adds 500 registered users (traffic rises to ~12.5/50 rps at the same 5 % concurrency profile). The team provisions a second 8×H100 host and (in this worked example) runs the

benchmark with continuous batching and FlashAttention-2. The p95 queueing/scheduling delay ahead of prefill — not TTFT, which at this profile is dominated by the canonical ~1.08 s prefill (Chapters 4/8; Chapter 14 measures p95 TTFT at 1.9 s for this stack) — drops from 320 ms (single host, batch-1) to 140 ms (dual host, continuous batch), and token throughput rises from 8,000 to 70,000 tokens/s. The MFU stabilizes at 38 %. These are [ILLUSTRATIVE SCENARIO RESULT] values — an illustrative benchmark outcome, not a home-lab measurement; the exact figures must come from a deployment benchmark on the target hardware/stack (Chapter 14). The remaining question is whether the cross-host request routing layer can maintain affinity KV cache residency, avoiding cache warm-up penalties on re-requests. The ~20 % affinity throughput gain and the ~2.1 s cold-start warm-up cost are themselves [ILLUSTRATIVE SCENARIO RESULT] values, not measured results.

Do not read the 8.75× throughput jump as a capacity-side win. It is dominated by the **kernel/batching** change (batch-1 no-flash ⟶ continuous batching with FlashAttention-2), which is worth most of the multiplicative gain, **plus ~2× from adding the second host** — the two are not separable from this single outcome number. This is a *per-host kernel/batching* improvement story, not a claim that "more GPUs = 8.75×." Were we adding a second host with no kernel/batching change, the expected throughput gain would be roughly the host-pool ratio (≈2×), and the fleet-sizing consequence is computed separately in Ch 16–17 from the service-time model, not from this mini-case's aggregate number.

Table 15-1 — Performance Regime Summary

Regime	In-Flight Concurrency (= λ·W)	Request Rate (rps)	Tokens/Request	KV-Cache/User (GB)	MFU (%)	Dominant Bottleneck
Light	~17	~2	9,500	~24.9	12	Compute (SDPA)
Typical	~86	~10	9,500	~24.9	38	Memory / KV cache
Peak	~344	~40	9,500	~24.9	52	KV + Inter-GPU bandwidth

*Concurrency here is **in-flight requests**, computed as λ·W with the canonical per-request service time W ≈ 8.6 s (the Little's-law discipline of Chapter 17 — never equate in-flight concurrency with a*

number of registered or simultaneously-online users). The three rps values are the canonical average and peak; the resulting in-flight concurrency (17/86/344) is what must be compared against a host's concurrent-request ceiling. KV-Cache/User uses the canonical ~2.62 MB/token × 9,500 ≈ 24.9 GB. MFU is an [ILLUSTRATIVE] regime label for teaching shape, not an achieved-MFU measurement: the 12/38/52 % values mark the congestion level of each regime (light/typical/peak), and the peak 52 % is a demand-side label that exceeds the ~30–40 % sustained H100 FP16 MFU of Chapter 8 — it is not a claim that a real kernel reaches 52 % utilization. The bottleneck column reflects the roofline logic of Chapter 8.

CHAPTER 16.

TCO: The Total Cost Reality Check

The Architect's Question

After this chapter we should be able to answer the question every stakeholder actually asks — *what does this really cost?* — with a defensible number, not a guess. We will build a total-cost-of-ownership model that separates capital, operating, and opportunity costs, then price the canonical workload across three delivery modes: self-hosted on our own cards, cloud GPU instances, and a managed inference API. After this chapter, "we save money by self-hosting" is either proven or refuted by arithmetic, and the break-even point between modes is explicit.

16.1. Concept

Total Cost of Ownership (TCO) is the sum of everything required to deliver a capability over its lifetime, not just the price tag of the hardware or the per-token rate. It has three cost families:

1. **Capital (capex)** — the one-time cost of the cards, servers, networking, racks, and cooling that make up the system. For self-hosted inference this dominates up front: an 8×H100 server with networking and infrastructure carries a large price. [ILLUSTRATIVE][DERIVED]
2. **Operating (opex)** — the recurring cost of running it: electricity and cooling, staff, software/licenses, cloud instance rental, and replacement/amortization of hardware. For cloud and managed API this is the whole cost; for self-hosted it compounds on capex.
3. **Opportunity** — the cost of the *alternative not taken*: the team time spent operating vs building, the delay to market, and the engineering hours that do not scale with either card or token counts. This is the most omitted and often the largest term.

The architect's job is not to minimize capex, nor opex, nor provider bill — it is to minimize **the number that matters for the organization's decision**, which usually means total cost per useful request at the required quality and SLO.

16.2. Mental Model

TCO is **a utilization-weighted average over the whole system, not a sticker price.** Three mental moves keep the arithmetic honest:

- **Amortize, don't stare at the price tag.** A $400K server is an asset consumed over ~5 years; spread it into dollars-per-month, then into dollars-per-request, before comparing to a per-token API rate. [ILLUSTRATIVE][DERIVED]
- **Follow the token, not the GPU.** The thing being bought is completed, SLO-meeting requests. Two systems with the same card count can differ 10× in cost per request if one has 3× the goodput per card, better utilization, or no idle coasting.
- **Include what does not scale.** Staff, power, networking engineering, and the latency of procurement are sunk or recurring whether utilization is 20% or 80%. A low-cost-per-card system that burns engineers can be the most expensive.

The decision shape is a **break-even graph**: at low volume, managed/cloud-and-shut-down wins (no idle capex); at high volume, self-hosted cards amortize below the per-token rate. The crossover point is what we compute.

16.3. Worked Example

16.3.1. Size the fleet first, then price it

TCO is meaningless until we know **how many hosts the workload actually requires**. A common sizing mistake is to start from a single host: a single 8×H100 host can only sustain ~2.0 req/s under the KV/latency analytical planning bound (Chapter 17/20), so it cannot serve even the canonical 10 rps average, let alone the 40 rps peak. We therefore size the fleet first (Ch 17) and price it second.

Step 1 — fleet size. The canonical workload requires N_hosts = max(N_throughput, N_KV, N_SLO). With the ~8.6 s service time and C≈17.5 KV-resident requests/host (Ch 17; byte-accurate 17.51, conservative integer floor 17):

Sizing bound	Average (10 rps)	Peak (40 rps)
Throughput (per-host ~2.0 req/s)	$\lceil 10/2.0 \rceil$ = 5 hosts	$\lceil 40/2.0 \rceil$ = 20 hosts
KV (in-flight $\lambda \cdot W$ / C)	$\lceil 10 \times 8.6/17.5 \rceil$ = 5 hosts	$\lceil 40 \times 8.6/17.5 \rceil$ = 20 hosts

Sizing bound	Average (10 rps)	Peak (40 rps)
N_hosts (max)	**~5 hosts**	**~20 hosts**

So the canonical workload's *peak* requires roughly **20 hosts** (FP16 KV, full utilization; **29 working hosts** at the 70% utilization target — **30 total with N−1**), and even the *average* needs ~5 — a fleet, not one box. (FP8 KV roughly halves this to ~10 hosts at peak — C ≈ 35.0, so $\lceil 344/35.0 \rceil = 10$, matching Ch 17.) **Every TCO figure below is scaled to this fleet requirement; pricing a single host would understate the cost by roughly 5–20×.**

What kind of number is ~2.0 req/s? The per-host rate `C_KV / W ≈ 17.5 / 8.6 ≈ 2.0 req/s` is an *upper-order planning estimate under a particular concurrency, timing, and cache geometry* — not an observed service rate. It is an average-in-system relation, not a measured goodput. The three quantities behind `N_hosts = max(N_throughput, N_KV, N_SLO)` are **three different models that must be derived and measured separately**, and the formula is only as strong as the weakest one:

- **N_KV (KV-memory occupancy ceiling)** — how many requests *reside* in KV cache given the host's usable HBM and the per-token KV footprint. This is an arithmetic allocation bound (the ~17.5 figure).
- **N_throughput (phase capacity)** — how many requests the host can *complete* per second given the service time. The ~8.6 s service time is an uncontended request-level estimate, and `C/W` treats it as fixed.
- **N_SLO (queueing / goodput)** — the number of hosts needed to hold p95/p99 TTFT, TPOT, and success rate under *concurrent* arrival. **Little's law relates average in-system work to elapsed time under stability; it does not independently prove a throughput ceiling or a p99 latency.** At concurrency ~17, TTFT and TPOT can differ substantially from the isolated ~8.6 s used to obtain `C/W`, because batch efficiency, per-request duration, and interference are all coupled to load.

So the 20-host figure is a **scenario-specific bound contingent on the 8.6-second service time remaining valid under concurrent execution**, not a deployment-validated estimate. Before budgeting against it, measure `λ_goodput` per host at the target p95/p99 TTFT, TPOT, and success rate on the actual workload, and re-derive N_hosts. (See the falsification protocol in Ch 17.)

Treat both provisioning policies explicitly. The headline $ figures below use the full-utilization fleet (≈20 hosts, provisioned exactly at the 40 rps peak with no headroom). The capacity-planning rule (Ch 17 Table 17-1) uses a 70% max-operating-utilization target, which gives **29 *working* hosts** at the peak $\lceil 40 \times 8.6/(17.5 \times 0.7) \rceil = \lceil 344/12.25 \rceil = 29$; because one host must be able to drain (failover/maintenance) while the fleet still clears the peak, the N−1 policy requires **30 hosts total**

(29 working + 1 spare — 29 surviving × 2.0 × 0.70 ≈ 40.6 ≥ 40 rps). That spare is a *reserve* host, not serving capacity. Both outcomes belong in the decision:

Provisioning policy	Full-utilization (≈20 hosts)	70% target + N−1 (≈30 hosts; 29 working + 1 spare)
Peak fleet	~20 hosts	~30 hosts (29 working + 1 spare)
Self-host (capex+opex+staff)	~$148K/mo	~$217K/mo
Per 1,000 requests	~$5.7	~$8.4

Provisioning sensitivity (explicit): the TCO figures below **assume the full-utilization fleet (≈20 hosts, provisioned exactly at the 40 rps peak without headroom)** so that the cost comparison is not double-counting idle capacity. If instead the fleet is provisioned at the 70% utilization target that the sizing rule (Ch17 Table 17-1) actually uses — **30 hosts (29 working + 1 N−1 spare)** — capex scales to ≈30/20 = 1.5×: ≈$174K capex (30 × ~$5.8K/host/mo) + ≈$33K opex + ≈$10K staff ≈ **$217K/month, and per-request cost rises to ≈ $217K / 26M ≈ $8.4 per 1,000 requests** (vs the $5.7/1K below). The durable conclusion — self-host loses to scale-to-load cloud on this workload — holds under either provisioning policy; the *specific* $5.7/1K number is the full-utilization figure and should be read with that assumption.

Step 2 — price each mode on N_hosts ≈ 20 (FP16, provisioned for the 40 rps peak).
Mode 1 — self-hosted on owned cards (20 × 8×H100).

- Capex: ~$350K per fully built 8×H100 server, amortized over 5 years ⟶ ~$5.8K/month/host ⟶ ~$116K/month for ~20 hosts. [ILLUSTRATIVE][DERIVED], scenario value [ILLUSTRATIVE]
- Opex (power + staff): per host, 8 H100 GPUs at ~700 W ≈ 5.6 kW GPU IT + ~2.2 kW host/network ≈ 7.8 kW IT, × PUE ~1.3 ≈ ~10.1 kW at the wall; at ~$0.15/kWh always-on that is ~$1.1K/month/host ⟶ ~$22K/month for ~20 hosts. Staff/engineering alloc ~$10K/month. [ILLUSTRATIVE][DERIVED], scenario value [ILLUSTRATIVE]
- Monthly total ≈ $116K + $22K + $10K ≈ **~$148K/month** for ~20 hosts.
- Per request at ~10 rps average = ~26M/month. **Cost ≈ $148K / 26M ≈ $0.0057/request ≈ $5.7 per 1,000 requests.** [ILLUSTRATIVE][DERIVED] *(worked example, not reference)*

Mode 2 — cloud GPU instances (rent, scale to load). An 8×H100 on-demand instance ~$20/hr (canonical $2.50/GPU-hr × 8). Because the workload's *peak* is 40 rps, the fleet must be able to burst to ~20 instances, but the *average* load is ~5 hosts' worth — so the honest cloud bill is the instance-hours actually required. That requires a **load-duration / capacity-occupancy model**, not a single average. Parameterize the monthly cloud host-hours as $H_{\text{cloud,month}}$ (host-hours, not Ch 17's host-count N) — the integral of required capacity over time, plus the warm-pool and capacity-reservation terms:

$H_{\text{cloud,month}} = \int_0^T N_{\text{required}}(t)\,dt$ plus a warm/startup pool and any capacity-reservation guarantee

where $N_{\text{required}}(t)$ is the number of hosts that must be running at time t (a step function that rises with the load curve at that hour of the day/week). This depends on the actual temporal load profile — the **burst duration and frequency**, the **scale-up latency** (how many seconds/minutes to attach and load a fresh instance), the **model-loading/warmup time** (loading a 140 GB model into a new host is not instant), the **minimum warm pool** to serve the base load without cold-starting, **provider capacity/availability**, and **billing granularity**. Only if the provider can attach instances faster than the load curve demands, with a warm pool already holding the model, can the cloud bill approach the pure average-load figure.

Under a simplified assumption of a continuously-arriving ~5-host average load that bursts briefly to ~20 at the peak, with a steady warm pool and fast scale-up, that is ≈ 5 × $20/hr × 730 hr ≈ ~$73K/month (scaling the fleet with load; always-on-at-peak would be ~$292K/month). **[ILLUSTRATIVE][DERIVED]** — this is *explicitly* an assumed load-duration curve and fast elastically-scalable capacity, not a measured or guaranteed cost. If the burst is long-lived or scale-up is slow, the real cloud cost rises toward the always-on-at-peak figure and the "cloud is cheapest" result weakens accordingly.

The cloud case is a family, not a single line. $73K and $292K are the two endpoints (ideal fast-scale vs always-on-at-peak). The realistic midpoint is set by two *parameters* — the **hours-at-peak** per day/week and the **reserved-warm-instance** count held to avoid cold-start. For example, a mid-case with ~5 reserved warm hosts + ~15 burst hosts held for ~4 peak hours/day, at $20/hr (burst) and the warm pool at a reserved rate, lands between the two endpoints; the exact number depends on the provider's reserved/discount and billing-granularity terms, which are scenario inputs, not market facts. The durable lesson — *fleet size first, price second* — does not depend on this elasticity assumption, but the specific $2.8/1K number does and should be read as the *fast-scale ideal*, not the default decision line.

- Per request: ~26M/month. **Cost ≈ $73K / 26M ≈ $0.0028/request ≈ $2.8 per 1,000 requests.** [ILLUSTRATIVE][DERIVED] *(The "duty cycle" here is **fleet capacity utilization** — how many of the provisioned hosts are busy on average — NOT the literal fraction of wall-clock time an instance is powered on. A continuously-arriving 10-rps workload cannot be served by shutting the only instance off 60% of the time; it needs a fleet that is always available and scales with load. Staff & integration add on top.)*

Mode 3 — managed inference API.

- A hosted frontier-70B-class API at ~$0.002/input + ~$0.008/output per 1K tokens (typical as of 2026). The per-request token cost is

$$\begin{aligned}\text{cost/req} &= p_{\text{in}} \cdot \frac{I}{1000} + p_{\text{out}} \cdot \frac{O}{1000} \\ &= 0.002 \times 9.2 + 0.008 \times 0.3 \approx \$0.0184 + \$0.0024 \\ &\approx \$0.0208 \approx \$20.8 \text{ per 1,000 requests}\end{aligned}$$

[ILLUSTRATIVE][DERIVED], a scenario value [ILLUSTRATIVE] — at the canonical ~26M requests/month: ~$541,000/month (26M × $0.0208 ≈ $541K).

Reading the result. Once the fleet is sized correctly (~20 hosts), the comparison flips entirely versus the single-host framing. Self-hosted (~$5.7/1K reqs) is now **roughly twice the cloud-scaled rate** ($2.8/1K) on a fully-loaded basis ($148K/mo vs ~$73K/mo), because the canonical workload genuinely needs a multi-host fleet, and self-hosting a 20-host fleet carries ~$116K/mo of capex amortization. It is nonetheless still **well below the managed-API rate** ($20.8/1K), so at this volume self-hosting beats the API but loses to scale-to-load cloud. **This is an illustrative lower-bound for cloud, NOT an apples-to-apples comparison** — the $73K cloud figure assumes ideal scale-to-load elasticity and a continuously-arriving ~5-host average that bursts briefly to ~20, whereas the $148K self-host figure is an always-provisioned 20-host fleet. They do **not** share the same availability ceiling, failover reserve, warm-capacity cost, peak-duration assumption, or p95 SLO. **Cloud-scaled being cheapest is therefore a lower-bound result of an asymmetric scenario, not a demonstrated mode ranking.** Without a measured traffic trace and equalized SLO/failover/availability assumptions on both sides, the definitive economic winner is **not determined**.

Apples-to-apples caveat. The $73K cloud figure does not yet include an N−1 failover reserve, capacity held for failures/maintenance, warm-capacity cost during idle periods, model-startup time, or provider availability variance; the self-host figure does not charge for the same availability target's redundancy. So the two are **not compared on equal reliability or load-serving assumptions**. Before treating cloud as cheaper, add: the same served-load trace, p95 SLO, peak duration, availability target, failover coverage, warm capacity, model startup time, and price period to *both* sides. Under a nonideal elastic case (a reserved warm pool sized for N−1 plus slower scale-up), the cloud cost rises toward the always-on-at-peak figure and the "cloud is cheapest" result may not hold. As above: the $2.8/1K figure is an **optimistic lower bound** — frame the decision as "cloud is cheaper **if** scale-up is fast and a warm pool can be held cheaply," not as an unconditional ranking. The decisive caveat remains the **staff/ops term and whether it is sunk**, and now also the **fleet requirement** — a single-host TCO understates the real cost by 5–20×.

Multi-region active-active availability is NOT priced in this TCO. The canonical workload's stated SLA (Ch 4) is multi-region active-active at 99.9% availability, but **every** `$/1K` figure in this chapter (and the host counts in Ch 17) prices a **single-region** deployment with **N−1 single-host failover**, **not** multi-region active-active. Multi-region active-active is a **different provisioning problem** from N−1 single-host failover: it requires cross-region capacity duplication (no single region's loss may take the service down), region-failure tolerance, data locality and traffic routing (geo/health-based routing, per-region caches and indices), and consistent state/data replication (model

weights + KV/index replication across regions). None of that is priced or validated here, and none of it is implied by the N−1 reserve host above. Accordingly the canonical cost figures **understate the cost of the canonical workload's own stated 99.9% availability requirement** — read the `$/1K` and monthly totals as *single-region, N−1-only* numbers, and add a separate multi-region capacity + replication cost line (on the order of ≥2× the single-region fleet on the capacity-duplication term alone) before the availability SLA can be considered met.

Table 16-1 — TCO comparison across delivery modes (illustrative worked example; N_hosts ≈ 20 at the canonical peak). **ILLUSTRATIVE LOWER-BOUND, NOT APPLES-TO-APPLES:** the modes are NOT compared on equal availability, failover, warm-capacity, peak-duration, or p95-SLO assumptions — the cloud-scaled $73K assumes ideal elasticity while the self-host $148K is an always-provisioned fleet. Use as a *scenario* comparison, not a ranking; the definitive winner is **not determined** without a measured traffic trace and equalized assumptions on both sides.

Mode	Capacity	Opex/month	Cost/1K req	$/month @26M req	When it wins
Self-hosted (20×8×H100)	~20 hosts	~$148K	~$5.7	~$148K	staff already in-house (sunk) and sustained near-peak utilization; no burst variability
Cloud on-demand (scaled)	bursts to ~20, runs ~5 avg	~$73K	~$2.8	~$73K	variable load, no idle capex, staff shared **— only if scale-up is fast and the average run is ~5 hosts**

Mode	Capacity	Opex/month	Cost/1K req	$/month @26M req	When it wins
Cloud on-demand (always-on-at-peak)	~20 hosts all month	~$292K	~$11.2	~$292K	scale-up is slow or the load is sustained near peak; the elastic-ideal $73K does not apply
Managed API	—	usage	~$21	~$541K	tiny volume, fastest time-to-value

(Figures are worked-example estimates — a **Q4 2026 illustrative pricing scenario, not market quotes** — and treat as [ILLUSTRATIVE][DERIVED], to be re-priced before budgeting. These are *scenario inputs the architect chooses and re-prices*, not assertions governed by the 2026-08-30 evidence cutoff; they do not claim to be a source available at that date. The fleet requirement ~20 hosts (peak) / ~5 hosts (avg) is from the canonical Ch17 sizing; FP8 KV cuts the peak fleet to ~10. **GQA operating configuration:** the ~20-host figure assumes the canonical full-MHA KV constant (2.62 MB/token). A 2026 production model with grouped-query attention (GQA) uses roughly 8× less KV per token, which raises the per-host KV-residency ceiling C by ~8× and cuts the KV-bound fleet to on the order of ~3 hosts at the same 40 rps. **That ~3-host figure assumes per-host throughput also scales ~8× with C (a KV/memory-bound host); the throughput bound ($\lceil 40/2.0 \rceil \approx 20$ hosts) is independent of KV size and still applies if the host is compute/bandwidth-bound — so the true fleet is max(N_throughput, N_KV), the larger of the two, not the KV bound alone.** The full-MHA number is the conservative teaching case; own the 6–7× gap explicitly rather than quoting ~20 hosts for a GQA deployment.)

Table 16-2 — Matched SLO/availability comparison (decision view). The three modes below are compared on the canonical workload's stated **multi-region active-active 99.9% SLA** (Ch 4). They are **[ILLUSTRATIVE][ASSUMPTION] planning rows, NOT measured.** The **not-apples-to-apples caveat** of Table 16-1 still governs (the modes are not compared on equal availability, failover, warm-capacity, peak-duration, or p95-SLO assumptions). This table does not change the Table 16-1 result. The single-region rows are the **single-region teaching baseline** computed above.

Deployment / availability mode	Scope	Cost (from above)	Availability covered	Status
Self-host, single-region, N−1	~20 hosts peak / ~30 hosts (70% + N−1)	~$148K/mo ($5.7/1K); ~$217K/mo at 70%+N−1 ($8.4/1K)	Single-region; survives one host loss	**[ILLUSTRATIVE] [ASSUMPTION]** single-region teaching baseline, already computed
Cloud elastic, single-region	bursts to ~20, runs ~5 avg	~$73K/mo (ideal fast-scale) to ~$292K/mo (always-on at peak); ~$2.8/1K	Single-region	**[ILLUSTRATIVE] [ASSUMPTION]** single-region teaching baseline, already computed
Multi-region active-active	**UNSIZED**: mandatory capacity duplication, region-failure tolerance, data replication, traffic routing, error budget	**NOT PRICED / NOT VALIDATED in this chapter**	99.9% active-active	**Decision deferred** pending regional capacity and failure test

The multi-region row is NOT priced — see the §16.3 multi-region statement (Ch 17 §17.6 applies it to the host counts); this table only makes the availability mismatch explicit. Treat the row as a **provisional scenario** for planning visibility only: **not a procurement recommendation**, and **deferred** until regional capacity and a region-failure test are defined.

Parametric sensitivity is the durable form. All the fixed inputs above — GPU price, electricity,

staffing, capacity, API price, and the fleet size itself — are [ILLUSTRATIVE] scenario values; the *structure* of the model is what generalizes. The architect computes N_hosts from the workload first (Ch 17/20), then re-runs this TCO with the customer's real numbers (Chapter 23). A runnable, parameterised version ships with the book as `render/tco_calc.py`.

Crucially, these are **independent sensitivity dimensions**, and each pushes the break-even in a different direction; do not collapse them into one "the assumptions vary" disclaimer:

- **Fleet size** (N_hosts) — driven by the KV/throughput/SLO ceiling (Ch 17-20), not by TCO. A larger fleet raises the flat self-host line (more capex+opex) and shifts break-even right.
- **Duty cycle** — a burst-sized fleet does *not* run every host at full paid duty all month. Self-hosted reserved cards bill flat regardless of utilization; cloud on-demand bills only what runs. Separating these two is what makes the self-host (high fixed, low variable) vs cloud (low fixed, high variable) comparison meaningful.
- **Utilization** — the *provisioning* utilization target (70% vs 100%, Ch 17) sets how many hosts are needed, not how much they cost per unit; it is a separate line from the price-per-host.
- **Reserved / on-demand mix** — whether capacity is committed (cheaper, flat) or burst (pricier, on-demand) is a distinct lever; a mixed fleet has both a flat and a variable term.
- **Failover reserve** — N-1/headroom hosts (Ch 17) add cost but are not production-serving capacity; they must be counted as a separate reserve line, not folded into the served-load hosts.
- **Staffing** — the dominant human term for self-hosting; it is frequently the decider at low volume (Ch16 §16.8 mini-case) and should be its own sensitivity dimension, not absorbed into opex.

Because these dimensions are independent, the break-even is a **region**, not a point: the figure marks the [ILLUSTRATIVE] price band, and the honest output is a range (here ~5.9–9.9M req/mo) rather than a single "the break-even is 7.1M" claim. The headline range varies the **API price** against the full-utilization self-host cost ($148K/mo): the low end (~5.9M) is 148,000 ÷ 0.025 (the $25/1K top of the band) and the high end (~9.9M) is 148,000 ÷ 0.015 (the $15/1K bottom of the band) — the same ~5.9–9.9M range reported with Fig 16.1 and in §16.6. The **70%-utilization provisioning case** is a separate dimension and is named separately: the $217K/mo self-host cost against the canonical $20.8/1K API rate gives 217,000 ÷ 0.0208 ≈ 10.4M req/mo. Report the range and name which dimension is being varied.

16.4. Measurement

Four metrics keep the TCO model honest:

1. **Cost per useful (SLO-meeting) request** — the decision number; divide total cost by goodput-meeting requests (Ch6), not raw tokens.
2. **Effective utilization** — actual goodput ÷ theoretical capacity across the billing period; low utilization is the hidden tax in both capex and rented instances.

3. **Break-even volume** — the requests/month where self-host cost-per-request crosses managed API; below it, don't buy cards.
4. **Staff/duty-cycle adjusters** — the engineering-hours and duty-cycle assumptions that dominate the comparisons; measure them, don't assume.

16.5. Common Mistakes

- **Comparing sticker price to per-token rate.** A $/1K-token API quote already includes amortization; a card price tag does not. Amortize both.
- **Ignoring the staff/ops term.** Self-host "saves money" on paper and loses the moment two engineers are consumed full-time.
- **Assuming 100% utilization.** Idle cards are still burning electricity and depreciation; bake duty cycle in.
- **Forgetting opportunity cost.** A 6-month procurement cycle versus a same-week API integration is a real cost measured in time-to-value.
- **Using peak capacity for cost-per-request.** Peak sizing (40 rps) overstates cost if average (10 rps) utilization is what governs. (The headline $5.7/1K above does divide the peak-sized 20-host fleet by average volume — deliberately: this workload must clear the 40 rps peak, so peak capacity is real cost here; the mistake applies when peak sizing is avoidable, e.g. batch or queueable traffic.)

16.6. Architecture Consequence

TCO is the final gate in the design loop (Ch12 candidates → Ch14 benchmark → Ch16 cost). It settles which candidate survives: the 70B 8×H100 self-host **passes the capability screen and is analytically screened for feasibility — it *would* need a representative hardware benchmark to establish SLO-goodput** (the `C/W` and roofline estimates of Chs. 7–8 are planning bounds, not a measured p95 TTFT/TPOT pass at the target offered load), and on TCO it **beats the managed API at canonical volume but loses to scale-to-load cloud** — so the surviving recommendation is *conditional* (self-host wins only if the staff/ops term is sunk and sustained near-peak utilization holds and a benchmark confirms the SLO; otherwise scale-to-load cloud at ~$2.8/1K is cheapest). This completes the chain from vague requirement to a defensible, costed architecture, while being honest that the TCO gate is not an unconditional win and that the SLO pass is *provisional until benchmarked*. It also feeds fleet decisions (Ch17-18): the break-even curve is what justifies buying a second host versus renting peaks, and the staff term is what pushes toward consolidation (Ch18).

16.7. What We Still Don't Know

- **Real equipment/power/staff numbers** for a given deployment are site-specific [UNRESOLVED]; the illustrative quotes above must be re-priced.




FIGURE 16.1: TCO break-even: self-hosted vs managed API (canonical 80-layer full-MHA geometry). The break-even volume is **illustrative, not portable** — it holds only for this 70B FP16 8×H100 config, 5-year amortization, $20.80/1K API price, and 9.2K-in/300-out mix. **Not apples-to-apples across demand levels:** self-hosted = (capex ÷ 60 mo) + energy + staff/ops; managed-API = input×$/1M + output×$/1M-out; utilization = served ÷ provisioned — the self-host line assumes 40 rps peak provisioning, so break-even is a function of demand, not a fixed point.

*Break-even: monthly cost vs monthly volume for self-hosted and managed API across three serve modes. The self-host line crosses the managed line over a **range** of ~5.9–9.9 M requests/mo (the $15–25/1K price band), with the ~7.1 M mid-point at the canonical $20.80/1K ($148K/mo ÷ $0.0208 per request). The figure marks the mid-point (star) and the full sensitivity span (horizontal line).*

- **How rapidly GPU list and amortization prices fall** over the 5-year horizon is [HYPOTHESIS]; newer cards (H200/B200-class) change the per-card economics.
- **The true staff overhead of self-hosting** (SRE time, security, upgrades) is [HYPOTHESIS] until the team bills its own time honestly.

16.8. End-of-Chapter Mini-Case: TCO Discipline and the Staff Term

A startup's CTO shows the architect a warrant to buy two 8×H100 servers for the new internal RAG assistant, citing "we'll save on token fees." Applying TCO discipline, the architect does not dispute the raw token math. Instead they price it: at this startup's *actual* early volume — ~2 rps average, ~5M requests/month, and only 0.5 engineers fully available for GPU ops — the break-even against a managed API is this chapter's own division: $40,000 ÷ $0.0208 ≈ **1.9M requests/month**, so the current volume is already ~2.6× past the break-even. The honest number: self-hosting two servers ~$40K/month all-in vs ~$104K/month API at current volume (5M × $0.0208) — a **~$64K/month saving in favor of self-hosting, with the staff term already inside the $40K** (capex ~$11.6K + power ~$2.2K for two hosts leaves ≤ ~$26K for staff — upkeep is the power line already counted, so ~$0.2K of the $26.2K remainder is unallocated — too small to dwarf a $64K saving). The staff term is on a different basis than Mode 1: the mini-case prices a startup's 0.5-FTE operator (~$26K/mo — ≈$624K/yr fully loaded for one engineer, a scenario value rather than a market rate), not Mode 1's mature-operator alloc (~$10K/mo for 20 hosts) — re-price on one staffing basis before comparing. The token arithmetic therefore does not send this startup to the API; it points to self-hosting. Only one term can flip the decision: the *opportunity* cost of the GPU-ops time the two servers consume — the better part of the only engineer the startup can spare. To justify paying the API premium, that term must exceed **~$64K/month**, about $770K/year of product work the startup is not doing. The architect's verdict: **start on the managed API now, and revisit self-host the moment the consumed engineer's opportunity cost falls below ~$64K/month — for example when a second engineer frees up** — then re-run the same model. Request volume is not the lever: more volume only widens the ~$64K gap. The CTO did not buy the servers. The break-even graph did not make the answer self-evident; it narrowed the whole decision to one labeled assumption — this startup values its half-engineer's product time above $64K/month. A team that cannot say that, or that has a second engineer to spare, runs the same numbers and buys the servers.

PART V.

The Fleet

CHAPTER 17.

From Server to Fleet

The Architect's Question

Having established the single-host serving model — a 70B FP16 model on 8×H100 serving the canonical workload (Ch 4, Table 4-2) at ~10 rps average / ~40 rps peak — the natural next question is: when does one host cease to suffice, and how do we scale to a fleet? This chapter answers the architect's question: at what point must we move from a lone server to a coordinated fleet, and what are the quantitative trade-offs of that transition?

17.1. Concept

The transition from a single-server deployment to a fleet is not a qualitative leap but a quantitative threshold crossing. In the single-server model, all request routing, load balancing, and health monitoring occur within one process on one machine. The architect thinks in terms of request-per-second capacity, GPU memory utilization, and inference latency on that one host. As traffic grows, the single host hits limits in three domains: computational throughput (tokens/sec), GPU memory capacity, and inter-request interference (contention for shared resources such as NVMe I/O, PCIe bandwidth, and CPU). When any of these limits is breached, the fleet model introduces multiple identical hosts behind a load balancer, each independently serving a slice of the total traffic. The fleet model adds three new architectural ingredients: (a) a load balancer that distributes requests across hosts, (b) cross-host communication patterns when a request spans multiple machines, and (c) capacity planning that accounts for redundancy, failover, and the diminishing returns of horizontal scaling. The key insight is that horizontal scaling transforms per-host limits into system-wide capacities, but at the cost of added coordination overhead, state synchronization, and network budgeting.




FIGURE 17.1: Sizing a fleet by burst peak, headroom, and failover: a ~5.5 req/s burst a single host (~2.0 req/s analytical bound) cannot meet, so a 4-host fleet (~8.0 req/s) is sized ABOVE it and the N-1 = 3 residual (~6.0 req/s) still clears it. **Scope:** the burst is a small illustrative example; the canonical 40 rps peak is sized the same way to ≈20 hosts (Ch. 17-20). **Queueing-model note:** the ~2.0 req/s/host is a *service-rate* (capacity) bound, not a queueing result, and N-1 failover is a *capacity* argument, not a proof of p99 TTFT/TPOT — tail latency must be measured (Ch 14).

17.2. Mental Model

We visualize the fleet as a two-level hierarchy. At the top level, a load balancer — either hardware (L7 switch) or software (NGINX, HAProxy, Cloud Load Balancer) — accepts inbound requests and routes them to one of N backend hosts. Each backend host runs an identical copy of the model and serves requests independently. At the bottom level, each host operates exactly as the single-server model does: a model engine accepting prompts, producing completions, and returning tokens to the load balancer, which forwards the response to the client.

The mental model introduces two new invariants. First, the **throughput invariant**: total system throughput ≈ N × throughput_per_host, reduced by a factor ρ that captures load-balancer overhead, health-check traffic, and imperfect distribution (typically $\rho \in [0.85, 0.98]$ depending on LB sophistication). Second, the **memory invariant**: total GPU memory across the fleet is N × memory_per_host, but the per-host memory available for model weights and KV cache remains the same as the single-host case. The fleet does not increase the per-host model size; it increases the aggregate number of concurrent requests the system can serve by parallelizing across hosts.

A critical detail is the **session-affinity** decision. If user sessions must maintain conversation

state (KV cache, accumulated tool outputs, retrieval context), the load balancer must route subsequent requests from the same user to the same host (sticky sessions). This reduces cross-host communication but limits the effective parallelism, because a popular user can pin a single host to capacity while other hosts stand underutilized. If sessions are stateless (the model is reloaded or KV cache is discarded between requests), any host can serve any request, and load distribution becomes even. The architect must choose between density (sticky sessions, higher per-host utilization) and evenness (stateless routing, lower per-host utilization but better load balance).

17.3. Worked Example

We continue from the canonical scenario (Ch 4, Table 4-2): ~10 rps average / ~40 rps peak, prompt ~9,200 input tokens + ~300 output, 70B-class dense FP16 model, 8×H100 host with 640 GB GPU memory. A single 8×H100 host's capacity is set by the *binding constraint* among GPU compute, HBM bandwidth, and KV cache memory. Let us verify with arithmetic, keeping the two quantities distinct: **aggregate HBM** (640 GB) is not the same as **KV-available memory** (640 − 140 GB weights − runtime/workspace reserve).

Single-host concurrency capacity (KV-bound). The per-token KV footprint for the canonical full-MHA reference geometry is 2 × layers × hidden × bytes = 2 ×80 ×8,192 ×2 = 2,621,440 B ≈ 2.62 MB/token (Chapter 7 canonical). Subtract the 140 GB FP16 weights and ~64 GB runtime/activations/workspace from the 640 GB pool, leaving ≈436 GB available for KV. Each request at 9,200 input + 300 output reserves a **9,500-token max** KV of 9,500 ×2.62 MB ≈ 24.9 GB (the initial 9.2K residency is 24.1 GB). A single host therefore holds C = 436 GB ÷ 24.9037 GB ≈ **17.5 concurrent requests** (byte-accurate; the conservative integer "requests that fit" floor is **17**, not 18 — 17.51 cannot round up for a hard fit) — using the canonical layer-complete κ. Computing κ from a single layer instead of all 80 would overstate the concurrency figure by two orders of magnitude.

Viability at peak. Peak traffic is 40 rps; with the canonical ~8.6 s per-request service time (1.08 s prefill + 7.5 s decode), Little's Law puts ≈ 40 × 8.6 ≈ **344 requests in flight**, against a KV capacity of ~17.5 per host (conservative integer floor 17). **A single host is not viable at peak even for the non-agentic canonical workload** — the fleet needs roughly $\lceil 344/17.5 \rceil \approx$ **20 hosts** at 40 rps (**29 working hosts** at the 70% utilization target, **30 total with N−1**), and more for growth to 100 rps. This flips the original conclusion: the fleet is not a distant luxury but a necessity at the canonical peak, driven by the product of service time (8.6 s) and arrival rate.

KV compression is the first lever. Switching KV to FP8 ($\kappa \approx 1.31$ MB/token, raw byte-halving — exactly 50% of BF16 [ILLUSTRATIVE][DERIVED]) cuts the 9.5K max per-request KV to ≈12.45 GB and raises C to ≈35.0 concurrent per host (436 ÷ 12.45 ≈ 35.0; conservative integer floor 35), roughly doubling headroom before buying hardware. This is why the architect treats KV precision as a first-class capacity dial, not a cosmetic detail.

Threshold for fleet expansion. Suppose the agentic layer from Chapter 19 is added. Chapter 19's own telemetry puts the turn distribution at 68% terminating in T=1, 25% in T=2, 5% in T=3, and

2% exceeding the turn limit (falling back to single-shot). That makes the **median** turn count T=1 (68% of requests finish on the first turn) and the **95th percentile** T=3 (cumulative 68+25+5 = 98% by T=3). Each turn adds ~800 tokens of retrieved context (delta) and ~65 tokens of model-generated reasoning (gamma), so the effective per-request token count is

$$I(T) = I_0 + T(\delta + \gamma) + O_{\text{final}} = 9{,}200 + T \times 865 + 300$$

- Median (T=1): $I(1) = 9{,}200 + 1 \times 800 + 1 \times 65 + 300 = 10{,}365$ tokens
- 95th percentile (T=3): $I(3) = 9{,}200 + 3 \times 800 + 3 \times 65 + 300 = 12{,}095$ tokens
- Hypothetical extension (T=4, *if the turn limit were not enforced* — per Ch19 the >2% that exceed the limit fall back to single-shot, so no request actually reaches T=4): $I(4) = 9{,}200 + 4 \times 800 + 4 \times 65 + 300 = 12{,}960$ tokens

The KV cache per request rises proportionally, and per-host concurrency capacity follows from the Ch17 formula $C = M_{kv}/(I(T)\kappa)$:

- at T=1 (median): $10{,}365 \times 2.62$ MB ≈ 27.2 GB/request $\Rightarrow C \approx 16$ concurrent (floor 16)
- at T=3 (95th): $12{,}095 \times 2.62$ MB ≈ 31.7 GB/request $\Rightarrow C \approx 13.8$ concurrent (floor 13)
- at T=4 (hypothetical extension, turn limit not enforced): $12{,}960 \times 2.62$ MB ≈ 34.0 GB/request $\Rightarrow C \approx 12.8$ concurrent (floor 12)

Even the *median* agentic request already drops a single host below the peak in-flight demand (C ≈ 16 < 344 at 40 rps, or 860 at 100 rps), so the fleet is required under almost any agentic assumption. **Scaling forecast (service-time-aware).** Because the canonical workload's service time is ~8.6 s — not a ~1 s latency — the in-flight concurrency at the 40 rps peak is λ_peak × W ≈ 40 × 8.6 ≈ **344 requests**, not 40. With FP16 KV (baseline C≈17.5, conservative integer floor 17), the fleet needs $\lceil 344/17.5 \rceil \approx$ **20 hosts** at full utilization (**29** at the 70% utilization target). Agentic turns make this strictly worse: each additional turn adds ~800 tokens of context (lowering C) and more generated tokens (raising W), so the agentic T=3 case needs a larger fleet still (C≈13.8 in the 95th-percentile case and a longer W). The load balancer distributes λ/N rps per host and λ·W/N concurrent per host, and each host's per-host KV usage must stay comfortably under its C. This is the fleet point: hosts are added because *concurrency in flight × KV-per-request* exceeds a single host's residency — and concurrency in flight must be computed from the full service time, not a target latency.

Cross-host communication. In the canonical scenario, requests are independent — no user session spans multiple hosts. If an agentic loop required retrieving results from a prior host (e.g., distributed retrieval), the system would need a coordination layer (Redis, gRPC, or message queue) with added latency. We quantify this below in the measurement section.

17.4. Measurement

We derive three real quantities from the worked example and from production traffic patterns.

17.4.1. Per-host throughput and KV cache budget

Let N be the number of hosts, λ the incoming rps peak, T the random variable for agent turn count with distribution P(T), δ = 800 tokens per turn of retrieved context, γ = 65 tokens of model-generated reasoning per turn, and O_final = 300 final output tokens. The per-request token count is

$$I(T) = I_0 + T \cdot \delta + T \cdot \gamma + O_{\text{final}}$$

where I_0 = 9,200 is the baseline input tokens. The per-host concurrent-request capacity in terms of KV cache is

$$C = \frac{M_{kv}}{I(T) \cdot \kappa}$$

where M_kv is the KV-available memory — the portion of on-host HBM left for KV after weights and runtime — and $\kappa = 2 \times n_{\text{layers}} \times d_{\text{hidden}} \times \text{bytes} \approx 2.62$ MB/token (2.5 MiB) is the per-token KV footprint (Chapter 7 canonical; κ includes all layers — omitting the layer factor understates KV memory by orders of magnitude). For the canonical host, M_kv = 640 GB − 140 GB (FP16 weights) − ~64 GB (runtime/activations/workspace/NCCL) ≈ 436 GB. Dividing memory by bytes (not the byte-divided-by-bytes collapse that trips unit analysis):

- For T = 0 (baseline, I = 9,500): C = 436 GB / (9,500 ×2.62 MB) ≈ 436/24.9037 ≈ **17.5 concurrent requests per host** (byte-accurate; the conservative integer "requests that fit" floor is **17**, not 18 — 17.51 cannot round up for a hard fit).
- For T = 1 (median, per the Chapter 19 distribution; 68% terminate on turn 1): C = 436 GB / (10,365 ×2.62 MB) ≈ 436/27.17 ≈ **16 concurrent requests per host**.
- For T = 3 (95th percentile; cumulative 98% by T=3): C = 436 GB / (12,095 ×2.62 MB) ≈ 436/31.71 ≈ **13.8 concurrent requests per host** (floor 13).
- For T = 4 (hypothetical extension beyond the enforced turn limit — Ch19's >2% tail falls back to single-shot, so no request reaches T=4): C = 436 GB / (12,960 ×2.62 MB) ≈ 436/33.97 ≈ **12.8 concurrent requests per host** (floor 12).

These numbers are the KV-residency ceiling; measured concurrency may be lower if GPU throughput or bandwidth binds first, so the architect takes the min of the KV, compute, and bandwidth capacities.

> **Reconciliation box — the four throughput rates in this book are different quantities, not a contradiction.** (1) **~50 tok/s** (Ch. 5) is a deliberately conservative *single-stream, low-batch* generation rate used to illustrate the tokens-per-dollar *method*; it is a floor, not the host's serving throughput. (2) **~19,800 tok/s** (Ch. 8) is the *idealized*

prefill aggregate (8 × 2,471 at 35% MFU) before TP/system loss — an analytical upper bound on prefill, not a servable goodput. (3) **~35,000–70,000 tok/s** (Ch. 15) is the *batched serving* decode+prefill range under FlashAttention + continuous batching — the multi-request serving throughput of the same host. (4) **~2.0 req/s** (Ch. 17/20) is the *KV/service-time bound* on whole requests per host (C ÷ W), the quantity that sizes the fleet. The first three are token-rates at different batch/phase assumptions; the fourth is a request-rate bound. They reconcile only *phase-by-phase*, never as one fungible "total" rate. **Do not set a summed 19K tok/s against any single-phase capacity.** At ~2.0 req/s the request workload decomposes into two components that hit the hardware differently: **18,400 input tokens/s (2.0 × 9,200 — the prefill phase, compute-bound)** and **600 output tokens/s (2.0 × 300 — the decode phase, bandwidth-bound)** — both first-order regime labels; see Ch15/Ch8 for the scope conditions. Compare the prefill component only against the *prefill-only* capacities (~19,800 tok/s, item 2; ~35–70K only if those figures are themselves phase-resolved) and the decode component only against decode-scale capacity — never the summed ~19,000 tok/s against a single-phase figure. The apparent near-equality of ~19,000 tok/s and ~19,800 tok/s is a **numerical coincidence of units, not a physical equivalence**: the two sit in different phases with different arithmetic intensity and different cost (compute-bound prefill vs. bandwidth-bound decode), so they cannot be added into one rate and compared to any single-phase number. Aggregate prefill + decode into a single "total" rate only after stating an explicit cost/phase-equivalence model (e.g., a weighted-FLOP or weighted-dollar basis). Use the token-rates for kernel and cost reasoning (keeping prefill and decode separate), and the request-rate for fleet sizing. [DERIVED]

Define the subsystem boundaries before applying Little's Law — the populations are NOT the same. The end-to-end "in-flight request" count differs from the number of sequences actually occupying accelerator resources, because a request passes through several subsystems with different residency times and different occupants:

Subsystem	Service time (W)	Occupancy (L = λ·W)	What is resident
End-to-end request (user view)	W_plan ≈ 10 s (planning round)	λ·W_plan	requests from first submit to final response
Request admission + queue	W_queue	λ·W_queue	requests waiting before a GPU slot is free
Model execution (prefill + decode)	W_exec ≈ 8.6 s (canonical 9.2K/300)	λ·W_exec	sequences being served on a host

Subsystem	Service time (W)	Occupancy (L = λ·W)	What is resident
Prefill phase	W_prefill ≈ 1.08 s	(arrivals during)	sequences in the one-shot prompt pass
Decode phase	W_decode ≈ 7.5 s	(arrivals during)	sequences in the per-token loop

Which one drives KV residency? Only the *model-execution* occupancy (λ·W_exec) holds KV slots — a queued request (λ·W_queue) is "in flight" from the user's view but does not yet reserve a KV block, and a request in the *planning* phase (λ·W_plan) has not reached the host at all. The KV-residency ceiling C therefore bounds λ·W_exec (the resident sequences), not λ·W_plan or λ·W_queue. The end-to-end planning time (W_plan ≈ 10 s) is the workload-level Little's-law basis used to derive the arrival rate from the population (Chapter 4); the model-execution time (W_exec ≈ 8.6 s) is the capacity-level Little's-law basis used to size the fleet (this chapter). The C/W shortcut is thus an *execution-residency* screen, valid only when the serving system is the bottleneck and no queue/planning backlog changes the resident count — state that scope, and never quote C/W as a measured end-to-end goodput.

If the peak traffic λ_peak = 40 rps, Little's Law gives the number of requests *in flight* as λ_peak × W, where **W must be the full per-request service time** — for this canonical workload that is ~8.6 s (1.08 s prefill + ~7.5 s decode of 300 output tokens at ~25 ms/token, Chapter 8), NOT a sub-second TTFT-type latency. Using a ~1 s "latency" here is the classic fleet-sizing error: it undercounts in-flight concurrency by roughly the ratio of service time to target latency (here ~8.6×). The minimum number of hosts is

$$N_{\min} = \left\lceil \frac{\lambda_{\text{peak}} \cdot W}{C} \cdot \frac{1}{u} \right\rceil$$

where u is the utilization target and W is the **full service time** (end-to-end: prefill + decode + any tool/orchestration overhead). At the canonical peak:

- **KV-residency ceiling (C) is a per-host concurrency limit, not a fleet-size answer by itself.** A host holds C ≈ 17.5 concurrent full-context requests (computed above; conservative integer floor 17). The fleet size is governed by how many requests are *in flight at the peak*, which is λ_peak × W.
- At λ_peak = 40 rps and W ≈ 8.6 s, in-flight concurrency ≈ 40 × 8.6 ≈ **344 requests**. With C ≈ 17.5 per host (FP16 KV) at full utilization, the minimum N ≈ 344/17.5 ≈ 19.7 ⟶ **~20 hosts** (**29 working** at the 70% utilization target, **30 total with N−1**). This is the honest fleet size and matches the throughput/latency analysis in Chapter 20.

- **The 25 ms/token in W is the TPOT *budget*, not a measured per-step time.** The decode-bandwidth floor for the canonical 8×H100 host is 140 GB ÷ (8 × 3.35 TB/s) ≈ 5.2 ms/step, so a well-tuned decode can run well under the 25 ms SLO. The fleet number above therefore uses the *least-favourable* (budget) pole of the service time. The sensitivity band, holding prefill at 1.08 s and 300 output tokens: at 5.2 ms/step W ≈ 2.6 s (in-flight ≈ 106, ~6 hosts at full util); at 10 ms/step W ≈ 4.1 s (in-flight ≈ 164, ~10 hosts); at the 25 ms budget W ≈ 8.6 s (in-flight ≈ 344, ~20 hosts). Sizing at the 25 ms budget is the conservative choice; a measured per-step time from a Chapter 14 benchmark should replace it before committing hardware.
- Switching to FP8 KV ($\kappa \approx 1.31$ MB/token, raw byte-halving — 50% of BF16, C ≈ 35.0 at T=0; conservative integer floor 35) raises per-host concurrency, cutting the fleet to a minimum N ≈ $\lceil 344/35.0 \rceil$ = 10 at full utilization ⟶ **15 working hosts** at the 70% utilization target (**16 total with N–1**).

Separate the two questions explicitly — they are not interchangeable, and mixing them is the source of the under-sizing error:

1. **KV-only concurrency sizing** (does one host's KV budget hold the in-flight requests?): $N_{KV} = \lceil \lambda W/(C \cdot u) \rceil$. This uses C (KV-residency ceiling) and the full service time W.
2. **Full service-capacity sizing** (does the fleet's aggregate request rate clear the peak?): the same quantity when C/W is the per-host service rate — i.e. $N = \lceil \lambda/(\rho \cdot (C/W)) \rceil$. Because Little's Law ties concurrency, service time and arrival rate, these two views coincide: $\lambda W/C = \lambda/(C/W)$.

KV residency provides one capacity ceiling, but it is not a fleet-size answer by itself. When the canonical 300-token decode duration is included, Little's Law raises in-flight concurrency from the misleading "40 requests at 1 second" approximation to roughly **344 requests at 40 rps**, and the fleet must be sized to that.

The fleet is governed by the *minimum* of several independent ceilings, not by KV alone. `C/W` — and the KV-residency ceiling C that feeds it — is a *necessary* condition, not sufficient under mixed prefill/decode scheduling. An architect must take `min` of: (a) **KV-residency concurrency** C, (b) **prefill compute capacity** (the ~19,800 tok/s/host prefill screen of Ch. 8), (c) **decode bandwidth/compute capacity** (the HBM-bound decode roofline), and (d) the **observed p95-TTFT/TPOT SLO goodput** under a load test. A host may hold 17.5 KV-resident requests but never *serve* 17.5 at the quoted service time, because batch scheduling, prefill/decode interleaving, and tail latency couple the two.

Small queueing counterexample. Suppose a KV ceiling C = 17.5 and W = 8.6 s, so `C/W ≈ 2.0 req/s`. That is an *average occupancy bound*. If a burst of arrivals is shorter than the service-time spread, or if the prefill of some requests monopolizes the GPU and stalls decode, the *achieved* goodput can be well below 2.0 req/s even though the host holds 17.5 slots. Conversely, with prefix caching and batch-friendly load, achieved can exceed the naive bound at higher batch. The upshot: `C/W` is

a planning lower-bound screen on the same order, and the fleet SLO-passing count comes from the measured goodput at the target p95 — not from `C/W`. State the line's assumptions (time-in-KV occupancy, overlap of phases, admission policy) explicitly in the sizing summary rather than presenting `C/W` as the achieved rate.

17.4.2. Simultaneous feasibility check (prefill + decode coexistence)

The ~2.0 req/s/host ceiling assumes prefill and decode run on the same host at the same time. We check the prefill leg against the hardware.

- **(a) Prefill demand at 2 req/s.** 2.0 req/s × 9,200 input tokens = **18,400 input tokens/s per host** (2.0 × 9,200; the prefill leg of the ~2.0 req/s decomposition in the reconciliation box above).
- **(b) Idealized prefill ceiling.** 8 × 0.989 PF/s × 35% / (2 × 70e9) ≈ **19,780 tokens/s** (Chapter 8, 35% MFU, prefill-only).
- **(c) The ratio.** 18,400 ÷ 19,780 ≈ **93%**. Prefill must run at ~93% of the idealized prefill ceiling.

This result is **[ANALYTICAL]**. It is a prefill-load check, not a measured rate. The ~93% leaves very little headroom. The host must also run decode. Prefill and decode coexist on the same hardware. Batch scheduling, prefill/decode interleaving, and interference consume the same compute. The idealized ceiling assumes no decode interference. The achieved MFU is below the 35% ideal. The real headroom is smaller than ~93%.

Therefore the ~2.0 req/s/host figure is an **analytical upper bound**. It is **NOT a claim that a host serves 2 req/s at SLO**.

Before treating 2 req/s/host as deployable, measure the p95 TTFT, p95 TPOT, and SLO-goodput on a representative host. Bring a measured p95 TTFT/TPOT and SLO-goodput (Chapter 14) before treating 2 req/s/host as a deployable service rate. Until then, the sizing in this chapter is a planning bound.

17.4.3. Load-balancer overhead factor

Let ρ be the effective throughput fraction after load-balancer effects. **These LB-efficiency values are [ILLUSTRATIVE][ASSUMPTION] engineering thresholds, not universal vendor-independent constants** — a well-configured software LB (NGINX) typically achieves ρ ≈ 0.95, and a hardware L7 switch may achieve ρ ≈ 0.98, *but both must be measured on the target topology, workload, and sample duration before being trusted*. The overhead comes from: health-check traffic (~1% of requests), session-affinity hashing skew, and LB process CPU limits. The throughput_per_ host itself must come from a benchmark on the actual workload (tokens/context/batch) — it is an ILLUSTRATIVE proxy until measured. What is *derivable* is the KV-residency ceiling C from §17.3; the LB overhead multiplies the schedulable fraction of that ceiling, and the ρ value should be replaced by a measured figure from a load test before it is used as a capacity coefficient. In the worked example, the fleet is currently sized by KV capacity (§17.3), not by a fabricated tokens/s number: at T=3 (the

95th-percentile sizing point, per the chapter's own rule), FP16-KV C ≈ 13.8/host (436 GB ÷ (12,095 × 2.62 MB ≈ 31.7 GB) ≈ 13.8; conservative integer floor 13) sets the ceiling, and adding a host raises aggregate schedulable concurrency by ρ·C, i.e. ~13 concurrent at ρ=0.95 (13.8 × 0.95 ≈ 13.1).

17.4.4. Cross-host interconnect budget

If a fraction φ of requests require cross-host data (e.g., distributed retrieval, shared vector index), each such request incurs an additional network round-trip latency t_net and moves data volume D over the host-to-host network. Two distinct bandwidth quantities must be separated: the **per-request burst** a single cross-host request draws during its round trip, and the **fleet aggregate** average across all hosts. Assuming an intra-rack 10 Gbps Ethernet backbone:

$$B_{\text{per-req}} = \frac{D}{t_{\text{net}}} = 5 \text{ MB}/0.02 \text{ s} = 250 \text{ MB/s} \approx 2 \text{ Gbps}$$

For D = 5 MB (top-5 retrieval snippets), t_net = 20 ms (typical rack latency), the per-request burst is $B_{\text{per-req}} = 5/0.02 = 250$ MB/s ≈ 2 Gbps, while the fleet aggregate — the expected number of concurrent cross-host requests (φ · N) times that burst — is

$$B_{\text{agg}} = \varphi \cdot N \cdot \frac{D}{t_{\text{net}}} = 0.1 \times 4 \times 250 \text{ MB/s} = 100 \text{ MB/s} = 0.8 \text{ Gbps}$$

Both are far inside the 10 Gbps link, so the base case appears benign (the burst leaves ~5× headroom; the aggregate is even smaller). But if φ scales to 0.5 (many distributed queries) and D grows to 50 MB, the per-request burst becomes $50/0.02 = 2{,}500$ MB/s ≈ 20 Gbps — exceeding a single 10 Gbps link on its own — and the fleet aggregate becomes $0.5 \times 4 \times 2{,}500 = 5{,}000$ MB/s = 5 GB/s, which exceeds the 10 Gbps (~1.25 GB/s) limit by ~4×.

This calculation shows that cross-host communication must be dimensioned early on the **per-request burst** (which can exceed a single link even before the aggregate does), and that both the burst and the aggregate scale with φ and D, even if the base case appears benign.

17.4.5. Counter-scenarios: KV is not always the driver

The canonical case is *one* regime — a mid-context, mid-rate RAG workload where the KV-residency ceiling happens to be the binding constraint. Two counter-scenarios show that the method (compute λ·W/C with the real service time) transfers while the *conclusion* (KV binds) does not. **The formula is the method; the binding term is per-workload.**

Counter-scenario A — short context, high batch: KV is not the host-count driver. A code-completion-style workload is a clear case: ~500-token input, ~100-token output, but a very high arrival rate (say 200 rps peak) and a small model (7B, so weights are ~14 GB and the KV footprint per token is far lower). Here two things happen. First, per-request KV is tiny — a 600-token max-context against a small per-token κ is well under 1 GB, so the host holds hundreds of concurrent requests at the KV screen; C is *not* the ceiling. Second, the binding term becomes **decode bandwidth**: each

generated token re-reads the full ~14 GB of weights, so the per-host decode token rate is capped by HBM bandwidth ÷ weight size, and at 200 rps × 100 output tokens the aggregate output-token demand dwarfs what any one host's bandwidth supplies. The host count is set by $\lambda \cdot O$ / (per-host token rate), *not* by KV residency. The fleet formula is unchanged; the binding term is bandwidth, not memory.

Counter-scenario B — long context, low rate: memory dominates even below the KV screen. A document-analysis workload is the opposite pole: ~128K-token input, ~50-token output, but a low rate (say 2 rps). Here the per-request KV is enormous — 128K tokens against the canonical κ is ~335 GB, which consumes most of the host's ~436 GB KV budget (already net of the 140 GB weights). Because even one request nearly fills the host, the fleet is sized almost one-request-per-host despite the low rate. Here memory is not just a ceiling — it is the *dominant* term, and the canonical brief-context C/W shorthand (which assumes many small requests share a host) does not apply at all.

The transferable lesson. In the canonical regime the host is KV-bound and sized by $\lambda \cdot W/C$; in counter-scenario A it is bandwidth-bound and sized by output-token rate; in counter-scenario B it is memory-dominated and sized by aggregate context. The architect must identify which term binds *for the specific workload* before applying any single sizing formula — that is what makes the canonical scenario a method rather than a template.

17.5. Common Mistakes

1. **Ignoring KV cache growth from agentic loops.** A common mistake is to assume that adding an agentic layer barely changes per-request resource usage. As shown, each turn adds ~800 tokens of context, which linearly reduces concurrent-request capacity. Forgetting this leads to under-provisioning the fleet.

2. **Over-relying on sticky sessions without load-balance analysis.** Sticky sessions simplify cross-host communication but can create hot-spot hosts if a few users generate disproportionate traffic. Always measure the session-affinity distribution on the actual workload. **A Gini coefficient exceeding 0.3 is an [ILLUSTRATIVE][ASSUMPTION] example threshold, not a universal constant** — the trigger to abandon sticky sessions depends on the workload, the tail-latency SLO, and the failure domain. Establish the skew threshold with a traffic replay/load test and tune it to the SLO, not to a fixed 0.3; measure per-host queueing, p95/p99 latency, and request drops to decide when stateless routing or session sharding is the appropriate response.

3. **Using raw rps to size the fleet.** Requests-per-second is necessary but not sufficient; the product of rps × average latency gives concurrent load, which must fit within KV cache capacity. A host serving 40 rps at 0.5 s latency carries 20 concurrent requests, whereas at 2 s latency it carries 80 — the same rps, very different resource usage.

4. **Under-estimating load-balancer overhead.** A 5% throughput reduction from $\rho = 0.95$ may

seem small, but at the margin of capacity it can be the difference between fitting on N hosts and needing N+1. Always provision with ρ explicitly in the formula.

5. **Failing to model latency tail under spike traffic.** GPU inference time is not constant; under sustained high load, kernel-mode preemption, memory fragmentation, and concurrent kernel launches can increase per-token latency by 20–50%. The linear model t = t_inference + t_tool is a lower bound; the architect should add a 20% safety margin.

17.6. Architecture Consequence

Transitioning from one host to a fleet reshapes every layer of the system.

GPU fleet sizing. The number of hosts N must satisfy the service-time-augmented capacity formula $N = \lceil \lambda_{peak} \cdot W / (C \cdot util_{target}) \rceil$ (the minimum N — the provisioned fleet adds one spare on top, the N–1 rule), where C depends on the agentic turn distribution and W is the full per-request service time (which rises with turns — each turn adds retrieval latency and generated tokens). Two effects compound as turns grow: C falls (more tokens ⟶ more KV per request) and W rises (more per-turn latency), so in-flight concurrency λ·W grows on both sides. For the canonical customer-facing peak (40 rps, W≈8.6 s), in-flight ≈ 344 and $N \approx \lceil 344/17.5 \rceil \approx 20$ hosts at full utilization (**29** at 70% util, **30 total with N–1**) with FP16 KV; FP8 KV cuts that to **15 working hosts** (10 at full utilization; **16 total with N–1**). The lesson is honest: the binding term is λ·W/C, and W must be the real service time, not a sub-second target latency. Size for the 95th-percentile latency and token scenario, not the median, and treat KV precision as the cheapest way to shrink the fleet before adding hardware.

Load-balancer selection and configuration. The choice between hardware (F5, Cloud LB) and software (NGINX, HAProxy) affects ρ and the session-affinity model. Hardware L7 switches offer better ρ (≈0.98) but less fine-grained traffic-shaping; software LBs offer ρ ≈ 0.95 but can implement consistent hashing for session affinity. The architect should match the LB capability to the session model: sticky sessions ⟶ any LB; stateless ⟶ software LB with consistent hashing.

Cross-host data infrastructure. If any request type requires cross-host communication (distributed retrieval, multi-model orchestration, state sync), a dedicated backend network must be provisioned. The minimum bandwidth is $B_{min} = \varphi \cdot N \cdot D / t_{net}$ (the fleet aggregate derived in §17.4.4 — the expected concurrent cross-host requests times the per-request burst D / t_net), and the fabric should provide at least 2×B_min for headroom. In the canonical scenario with φ = 0.1, N = 4, D = 5 MB, t_net = 20 ms, B_min ≈ 0.8 Gbps (0.1 × 4 × 5 MB / 0.02 s = 100 MB/s), so a 10 Gbps intra-rack network has ample headroom for the aggregate; but as §17.4.4 notes, the per-request burst itself (D / t_net = 250 MB/s ≈ 2 Gbps in the base case) must also fit a single link once a request is in flight, which is the binding constraint when φ or D grows. But the architect should instrument φ and D from production telemetry and revisit the bandwidth provisioning quarterly.

Observability across the fleet. With N hosts, tracing a request end-to-end requires correlating

the LB routing decision, the selected host's inference logs, and any cross-host data calls. Structured logging with a request-ID field that propagates from the client through the LB to the host and back is essential. Distributed tracing (OpenTelemetry, Jaeger) should be enabled by default. Alerts should trigger when per-host concurrency exceeds 80% of C, when LB error rate exceeds 0.1%, or when cross-host bandwidth utilization exceeds 70%.

Failover and redundancy. With $N \geq 2$, the fleet provides automatic failover: if one host crashes, the LB routes its traffic to the remaining $N-1$ hosts, reducing capacity by $1/N$ (N to $N-1$ hosts). For $N = 4$, a single-host loss reduces capacity from 100% to 75% (assuming equal load distribution). The architect must decide whether this is acceptable or whether N must be larger (e.g., $N = 6$ for 83% residual capacity after one failure). Health-check frequency and graceful drain procedures affect the real-world failover time, typically 5–15 seconds.

Multi-region active-active availability is NOT priced in this chapter's arithmetic. The multi-region caveat of Ch16 §16.3 applies verbatim to these host counts: every host count here — and the $N-1$ failover/redundancy model above — is a **single-region, N−1-only** number (≈20 peak / 29 working / 30 with $N-1$), so the counts and the sizing arithmetic that hangs off them **understate the cost of the canonical workload's own stated 99.9% availability requirement**. Add a separate multi-region capacity + replication cost line before the availability SLA can be considered met.

17.7. What We Still Don't Know

Despite the arithmetic above, several questions remain open and would benefit from targeted research:

- **Turn-count distribution under fleet load.** Do larger fleets ($N > 4$) change the observed T distribution? Intuitively, more hosts reduce per-host contention, potentially lowering latency and reducing the agentic loop depth, but empirical measurement is needed.
- **Latency amplification non-linearity.** The agentic latency model from Chapter 19 frames the added orchestration overhead as $\beta(T) = 1 + (T \cdot L_agent / L_base)$, which assumes constant per-turn orchestration overhead and a fixed base generation time. Under fleet scaling, GPU saturation may make per-turn overhead grow with concurrent requests, introducing convexity. Empirical load-testing across $N = 1, 2, 4, 8$ hosts is required.
- **Optimal fleet size for cost vs. latency.** The cost of adding a host is roughly the cost of 8×H100 (multi-hundred-thousand dollars). The marginal latency improvement from the Nth host diminishes (diminishing returns). A cost-per-latency-improved curve would help the architect justify fleet size to stakeholders.
- **Cross-host communication patterns at scale.** The $\varphi = 0.1$ assumption may not hold for all workloads (e.g., RAG over a shared index, distributed fine-tuning). Real-world measurement of cross-host traffic patterns is needed to size the backbone accurately.
- **Context-caching efficacy across a fleet.** If many users query related topics, can a fleet-wide KV cache or retrieval cache reduce the effective δ per request? The savings could be substantial but require cross-host cache-invalidation protocols that are not yet well understood.

17.8. End-of-Chapter Mini-Case: Going Agentic: Service-Time-Aware Fleet Sizing

Scenario. A AI-product company starts with a single 8×H100 host serving the canonical traffic of 2,000 users at 10 rps average / 40 rps peak, 9,200 input + 300 output tokens, no agentic layer. After six months, user growth pushes peak traffic to 100 rps, and the team introduces the agentic layer from Chapter 19 with a maximum of 3 turns (median T = 1, 95th-percentile T = 3, per the Ch19 telemetry distribution).

Initial sizing analysis (service-time-aware). At T = 3 (the 95th-percentile, and the honest worst-case sizing point), I(3) = 9,200 + 3·800 + 3·65 + 300 = 12,095 tokens. With FP16 KV (κ = 2.62 MB/token), per-request KV ≈ 31.7 GB, so KV-residency capacity C = 436 GB ÷ 31.7 GB ≈ 13.8 concurrent requests per host (conservative integer floor 13). But concurrency *in flight* is λ × W, where W is the full service time, which here grows with the agentic turns: 1.08 s prefill (held at the canonical 9.2K single-shot representative; a 12,095-token prefill would scale to ~1.42 s) + (~495 generated tokens × ~25 ms/token = ~12.4 s decode) + ~0.4 s of per-turn tool/retrieval latency ≈ **~13.8 s** (the tool/turn term here combines the per-turn tool + retrieval latency; Chapter 19's `T·L_agent` ≈ 660 ms is the same class of overhead at a different per-turn rate (Ch19: 220 ms/turn ⟶ 660 ms at T=3; this case uses ~133 ms/turn ⟶ ~0.4 s) — a single model should use one rate consistently). (This W is the full agentic service time — decode of all generated tokens plus the grown-context prefill. Because the prefill is held at the canonical 9.2K representative rather than the full 12,095-token context (which would scale it to ~1.42 s and give W ≈ 14.2 s), treat this ~13.8 s as a **lower bound** on the agentic service time, and the resulting in-flight counts and host totals as corresponding lower bounds. It is *not* the incremental orchestration-overhead figure of ~660 ms at T=3 that Chapter 19 reports as its $T \cdot L_{\text{agent}}$; the two are different quantities, and it is this full W that drives concurrency and fleet size, per Chapter 19's scope note.) So at the 100-rps peak, in-flight concurrency ≈ 100 × 13.8 ≈ 1,380 requests, not 200. Against C ≈ 13.8 per host (conservative integer floor 13), N = ⌈1,380/(13 ×0.7)⌉ ≈ **152 hosts** on FP16 KV (≈107 at full utilization). This is the honest arithmetic the service-time model produces — the naive "1–5 hosts" rps estimate is off by ~30–150× (one-and-a-half to two orders of magnitude) because it ignores both the decode duration and the added turn latency.

KV compression changes the answer. Switching the KV cache to FP8 (κ ≈ 1.31 MB/token, raw byte-halving — 50% of BF16) cuts per-request KV at T=3 to ~15.85 GB and raises C to ≈27.5 per host (436 ÷ 15.85 ≈ 27.5; conservative integer floor 27), giving N ≈ ⌈1,380/(27 ×0.7)⌉ ≈ **74 working hosts** (≈52 at full utilization). Combined with prompt/prefix caching (which can eliminate the repeated 9,200-token base prompt from the KV per turn), the practical fleet lands well below the FP16 number. KV precision and prefix caching are the primary levers that make agentic fleets affordable, but even with both, an agentic 70B workload at 100 rps is a *multi-dozen-host* fleet, not a handful.

Decision. After the honest sizing, the team provisions on the order of ~52–74 hosts (the FP8+prefix-cache range, to be validated by a Chapter 14 benchmark before committing hardware), runs NGINX as a software load balancer with consistent hashing for session affinity, and instruments each host with OpenTelemetry tracing. Cross-host communication is minimal (φ ≈ 0.05), but the §17.6

rule must be re-run at this fleet size: B_min = φ·N·D/t_net = 0.05 × 52–74 × 250 MB/s ≈ 5.2–7.4 Gbps, and with the 2×B_min headroom rule (§17.6) 2×B_min ≈ 10.4–14.8 Gbps exceeds the existing 10 Gbps intra-rack network — the rack is at/over budget at both ends of the host range. Verify φ and D from telemetry and budget ≥20 Gbps per rack, or shard the fleet across racks. Monthly GPU-utilization metrics should sit at or below the 70% utilization target against the KV-residency ceiling — ≈68% at the sizing traffic on the 74-host end (1,380/(74×27.5)), whereas the 52-host full-utilization end runs ≈96% at the same traffic and carries no headroom — and the SLO must be validated by a deployment benchmark (Chapter 14) — end-to-end latency including agentic overhead is an ILLUSTRATIVE target until measured.

Lesson. The fleet decision is driven by KV-residency capacity vs. **service-time-scaled concurrency** (λ·W) — not by raw rps, and not by a per-layer KV constant. The architect's checklist: (1) compute I(T) for the expected turn distribution, (2) derive per-host concurrent capacity C from the *canonical* per-token KV (2 × layers × hidden × bytes), and (3) convert peak rps into concurrency via λ·W using the **full service time**. The full service time is prefill + decode of all generated tokens plus per-turn tool latency; with it, step (4) computes N = ⌈λ·W/(C·util_target)⌉. Steps (5) and (6): apply the cheapest capacity levers first — KV precision (FP8), prefix caching, attention architecture (GQA/MQA) — before buying hosts, and validate throughput and latency with a benchmark, not an assumption. A multi-dozen-host FP8 fleet costs meaningful GPU capital, but avoids both wasteful over-provisioning and a costly re-platform when traffic doubles.

Table 17-1 — Fleet sizing matrix — KV-residency ceiling and minimum hosts (canonical FP16 KV, W = full service time).

Minimum hosts N = ⌈λ·W / (C·u)⌉ at a 70% utilization ceiling, where the in-flight concurrency **must** use the full per-request service time W — not a sub-second target latency. Two service times apply: W ≈ 8.6 s for the non-agentic canonical request (1.08 s prefill + 7.5 s decode), and W ≈ 13.8 s for the T=3 (95th-percentile) agentic request (the mini-case's service-time-aware figure). These are the in-flight counts the chapter derives in §17.3/§17.4.

Traffic scenario (λ peak)	in-flight @ non-agentic W=8.6s	in-flight @ agentic W=13.8s	N @ T=0, FP16 (floor C=17; C×0.7 = 11.9)	N @ T=3 (95th), FP16 (floor C=13; C×0.7 = 9.1)	N @ T=3 (95th), FP8 (floor C=27; C×0.7 = 18.9)
40 rps (canonical peak)	344	552	⌈344/11.9⌉ ≈ 29	⌈552/9.1⌉ ≈ 61	⌈552/18.9⌉ ≈ 30
100 rps (growth)	860	1,380	⌈860/11.9⌉ ≈ 73	⌈1380/9.1⌉ ≈ 152	⌈1380/18.9⌉ ≈ 74

Traffic scenario (λ peak)	in-flight @ non-agentic W=8.6s	in-flight @ agentic W=13.8s	N @ T=0, FP16 (floor C=17; C×0.7 = 11.9)	N @ T=3 (95th), FP16 (floor C=13; C×0.7 = 9.1)	N @ T=3 (95th), FP8 (floor C=27; C×0.7 = 18.9)
200 rps (2× growth)	1,720	2,760	⌈1720/11.9⌉ ≈ 145	⌈2760/9.1⌉ ≈ 304	⌈2760/18.9⌉ ≈ 147
N-1 failover, 40 rps peak (survive one host loss)	—	—	30	62	31

*The chapter sizes fleets at the **95th-percentile turn scenario (T=3)** per its own rule ("size for the 95th-percentile token scenario"), so the agentic columns use T=3 — which is also what the §17.8 mini-case computes (~152 hosts at 100 rps). C is the KV-residency ceiling (derived): 17.5 concurrent full-context requests on FP16 at T=0 (conservative integer floor 17), 13.8 at T=3 (12,095 tokens × 2.62 MB ≈ 31.7 GB/request over 436 GB; floor 13), and 27.5 on FP8 at T=3 (12,095 × 1.31 MB ≈ 15.85 GB/request; floor 27 — the mini-case's "≈74 working hosts at FP8" at 100 rps). Each C is floored to a whole-sequence slot count (17, 13, 27) before the 0.7 utilization factor is applied in the host columns (integer-slot convention); the N–1 failover row adds one spare host. The 70% utilization target and the λ, W values are ILLUSTRATIVE scenario inputs to be validated by a deployment benchmark (Chapter 14) before committing hardware. N is a KV-residency lower bound — the true answer is the max of this KV bound and the measured throughput bound. **Planning-bound caveat:** the per-host figures that feed this table — **~2.0 req/s/host** and **~19,800 prefill tok/s/host** (Ch 8, idealized) — are upper-order planning bounds derived from the KV-residency/service-time model and the idealized prefill roofline, **not implied deployed rates**. **No p95/p99 performance guarantee has been shown** for any host count in these columns; the achieved p95/p99 tail latency and goodput must be measured on the target deployment (Chapter 14) before any host count is treated as validated.*

CHAPTER 18.

Operating Multiple Models

The Architect's Question

> How does an operator organize a fleet of complementary models—dense and sparse, quantized and full-precision—so that every request reaches the right model at the right cost, without over-provisioning or under-serving?

This chapter answers that question with real arithmetic, routing logic, and operational judgment.

18.1. Concept

A mixed-model fleet treats each model family as a resource with distinct cost, latency, and capability profiles. Rather than running every request through a single 70B FP16 model on 8×H100, we layer:

- **Dense FP16** (baseline, high-quality)
- **Dense 4-bit GGUF** (lowest cost, edge-friendly; highest latency — see §18.3.2)
- **MoE sparse** (selective activation, higher throughput per GPU)
- **Quantized variants** (4-bit/8-bit trade-offs)

The fleet operates on a *routing function* R(query) ⟶ model_id that maps incoming requests to the cheapest model satisfying quality constraints.

Key design principles:

1. **Cost-per-token** is the primary unit of comparison across quantizations.
2. **Latency-per-token** determines interactive vs. batch placement.
3. **Capability gaps** (context window, tool-use, multilingual) dictate minimum model tiers.

4. **Consolidation** saves capex when overlap in workload profiles is high; **separation** preserves isolation when workloads have divergent SLA or security needs.

18.2. Mental Model

The fleet operates as a *cost-aware load balancer* with three decision layers:

Table 18-1 — Fleet routing decision hierarchy: capability filter → cost/SLO gate → fallthrough.

Layer	Question	Decision
Capability filter	Does any model in the fleet meet the request's feature requirements?	Eliminate models that lack the feature (e.g., context window too small, no tool-use).
Cost/SLO gate	Among remaining models, which minimizes weighted cost = α·token_cost + β·latency_cost?	Route to the cheapest suitable model; adjust α,β per deployment mode (interactive vs. batch).
Fallthrough	If all suitable models are at capacity, what is the next-best alternative?	Queue, degrade quantization, or escalate to the next tier.

The weighting (α,β) is deployment-context dependent. A chat UI tolerates ~200 ms of added service latency per request; a batch ETL job tolerates ~2 s per request but demands lower token cost. These are per-request service-latency thresholds for the short-prompt routing scenario — the chat figure sits under the chapter's ≤500 ms interactive threshold (§18.3.4) — not the canonical TTFT/TPOT SLO (Ch 4); the canonical TPOT budget of ~25 ms is a per-token quantity and is not what these per-request figures measure.

18.3. Worked Example

Scenario: ~2,000 users, ~5% concurrent (≈100 simultaneous), ~10 rps average / ~40 rps peak. Total token volume per request: ~9,200 in + ~300 out. Base hardware: 8×H100, 640 GB total VRAM. Model families: a 70B dense FP16, a 70B MoE (16 experts, 2 active), and a family of 8-bit/4-bit quantized models (70B equivalent).

18.3.1. Hardware capacity mapping

Model	VRAM (model precision)	VRAM (8-bit)	VRAM (4-bit)	# fit on 8×H100
70B dense FP16	140 GB	—	—	1 (140 GB weights across the 8-GPU pool, ~17.5 GB/GPU under TP; with KV, the full 640 GB pool is used)
70B dense 8-bit	—	~70 GB	—	1 (weights alone fit on 1×H100, leaving 7 GPUs; with the canonical KV budget the 8×H100 pool still holds weights + KV)
70B MoE FP16 (2/16 experts)	140 GB	—	—	1 (same as dense FP16; weights + KV fit in the 640 GB pool)
70B MoE 8-bit (2 active)	—	~70 GB	—	1
70B 4-bit GGUF	—	—	~35 GB	~5 (canonical 436 GB KV budget reserved: (640−436)/35 ≈ 5; ~18 by weights alone; the worked deployment below uses 2 copies)

(Each row's footprint is its own model's size at the named precision — put the number in that precision's column. A dash means that precision does not apply to the row's naming.)

With 8×H100 (640 GB), we can simultaneously run the weights of:

- **One 70B dense FP16** (140 GB)
- **One 70B 8-bit dense** (70 GB)
- **One 70B MoE 8-bit** (~70 GB)
- **Two 70B 4-bit GGUF** (≈70 GB total)

That is ~350 GB of weights, leaving ~290 GB for KV cache and for smaller specialized models (e.g., 22B, 8B) for classification or routing. KV, not weights, is the binding term: as the FP16 row above notes, that tier's KV alone uses the full 640 GB pool, so this co-residency holds only while the resident tiers' combined KV fits.

18.3.2. Per-token cost (example numbers, Q4 2026 pricing)

Model	Token cost (USD / 1M)	Per-request service latency (ms)	Basis
70B dense FP16 (8×H100 capital amortized)	$2.50	120	capital + energy
70B dense 8-bit (1×H100)	$1.25	250	public cloud [1P]
70B MoE 8-bit (2 active experts)	$1.00	300	public cloud [1P]
70B 4-bit GGUF (local, no GPU)	$0.15	800	energy only

Basis note (reconciled with Ch16's TCO): these per-1M figures are **per-model nominal rates for routing comparison** — the cost per 1M tokens if that model instance were serving at its own nominal throughput on its own host. They are *not* the same quantity as the fleet-amortized per-token cost derived in Ch16 §16.3 (~$0.60/1M for the 70B FP16 self-host), which divides the full peak-provisioned fleet TCO (~$148K/mo, ≈20 hosts at full utilization) by the considerably higher token volume that fleet actually serves (~2.5×10^{11} tokens/month). The ≈4× gap between $2.50/1M and ~$0.60/1M is therefore a **utilization/throughput basis difference, not a contradiction**: the table rates one host near its nominal (modestly-loaded) rate, while the Ch16 TCO spreads the same capex+energy over a heavily-utilized fleet's larger token output. Read each number with its own basis; the mixed-fleet *savings* conclusion below depends only on the relative per-model rates, not on the absolute self-host basis.

18.3.3. Routing arithmetic

Each request carries its full token profile together: 9,200 input + 300 output = 9,500 tokens. **Request-level routing sends the entire request — input and output — to one model.** A request cannot have 70% of its input tokens answered by model A and the rest by model B, unless the architecture explicitly supports model composition, cascade, or speculative decoding (a different mechanism we do not assume here). Under ordinary routing, we therefore split by *requests*, not by in-tokens:

For 1,000 requests/hour (≈0.28 rps — a light illustrative load; the arithmetic is scale-invariant in tokens):

- **70% of requests** (700, ≈6.65M tokens) are routine ⟶ route to 70B 8-bit: 6.65M × $1.25 = **$8.31 / hr**
- **20% of requests** (200, ≈1.9M tokens) need high-quality reasoning ⟶ route to 70B MoE 8-bit: 1.9M × $1.00 = **$1.90 / hr**
- **10% of requests** (100, ≈0.95M tokens) are complex / multilingual ⟶ route to 70B dense FP16: 0.95M × $2.50 = **$2.38 / hr**

(Each request's output tokens are generated by the same model that processed its input. Routing output tokens to a *different* model would require an explicit cascade/composition stage — e.g., a generator plus a separate rewriter — which is a distinct architecture, not a free assumption.) The 4-bit GGUF tier (800 ms) is listed for completeness but is *not* routed to in this 70/20/10 split: at 800 ms it would miss the 500 ms interactive threshold, so the bulk goes to the 8-bit GPU tier (250 ms) instead — the same SLO constraint the §18.8 mini-case works out in full.

Mixed-fleet hourly cost = $8.31 + $1.90 + $2.38 = **$12.59 / hour** vs. $23.75 / hour for single-FP16 (all 9.5M tokens at $2.50).

Monthly savings ≈ ($23.75 − $12.59) × 730 hr ≈ **$8,147 / month** (≈ 47% reduction) with comparable quality because the 8-bit model meets quality thresholds for ≥90% of requests.

18.3.4. Latency check

The per-request latency is that of the model serving it. The weighted-average request latency is

$$\bar{L} = \sum_i p_i \cdot L_i = 0.70 \times 250 + 0.20 \times 300 + 0.10 \times 120 \approx 247 \text{ ms/request}$$

(no separate output-routing term — output rides with its requesting model), where p_i is the fraction of requests routed to model i and L_i its per-request service latency. Acceptable for interactive chat (typical threshold: ≤500 ms).

Scope note — the latency column is an illustrative routing-comparison input, not the canonical service time. The 120/250/300/800 ms values are *illustrative per-request latencies for a short-prompt routing scenario* (the kind of request a router triages in milliseconds), used only to compare the four models against the interactive threshold (≤500 ms). They are **not** the ~8.6 s service time of the 9.5K-token canonical RAG request (Ch 17), which is a multi-second, capacity-side number that governs fleet sizing. The cost column, by contrast, *is* computed on the canonical 9.5K-token request (6.65M tokens for 700 requests). Read the two columns on their own bases: cost on the canonical request, latency as the illustrative routing input. A deployment benchmark (Ch 14) must supply the real per-model service times before either column is used for a production decision.

The latency and capacity must also reconcile with the canonical workload's KV residency (Chapter 17): routing 70% of requests to an 8-bit model on 1×H100 changes the per-host KV ceiling accordingly, and the fleet host count is set by the model each tier runs on. These are [ILLUSTRATIVE] pricing and latency figures for Q4 2026; the architect re-runs the same arithmetic with measured per-model cost/latency from a deployment benchmark (Chapter 14).

18.3.5. Consolidation vs. separation decision

- **Consolidate** when: workload profile overlap ≥70%, latency tolerance ≥300 ms, and cost differential >30%. *Verified*: our scenario sits exactly at the threshold — it consolidates ~70% of traffic to 8-bit (at the ≥70% boundary, not above it), saving ~$11.16/hr ($23.75 − $12.59, the §18.3.3 derived figure).
- **Keep separate** when: (a) security/classification policies require isolation, (b) workloads have bimodal latency needs (some ≤50 ms, others batch-tolerant), or (c) model versioning cadence differs (e.g., frequent fine-tuning on one family, stable other).

In our example, consolidation wins because the MoE and 8-bit models capture the same request classes at lower cost, and the FP16 tier handles the tail without contention. The FP16 tier has no separate reserve in this worked example: per §18.3.1 it shares the 640 GB pool — 140 GB of weights plus KV — and at the canonical 9.5K profile it cannot be a 2-GPU reserve, because a 2-GPU shard holds 160 GB − 140 GB = 20 GB of KV headroom against the 24.9 GB that one 9,500-token request needs (κ = 2.62 MB/token, Ch 17). Two reserved GPUs suffice only for the ~250-token support queries of §18.8, not for the canonical 9.5K request.

18.4. Measurement

To operate a mixed fleet we measure four cross-cutting metrics:

Metric	How to measure	Why it matters
Weighted average cost/token	Σ(tokens_i × cost_i) / Σ(tokens_i) across all models	Directly tracks fleet economics; target under the §18.3.2 per-1M basis (e.g. < $2.50/1M for the FP16 tier) for competitive SaaS.
Per-model throughput	requests/sec per GPU / per CPU node	Detects saturation; informs capacity adds vs. routing tweaks.
Routing accuracy	% of requests served by the *intended* target model (not fallback)	Ensures the routing function R() is well-calibrated; low accuracy means feature gaps or cost model drift.
Latency p95 per model	p95 of token-level latency per model	Guarantee SLO per tier; fleet p95 must be computed from the combined routed-request latency distribution — per-model p95 values cannot in general be averaged (percentiles are not linearly composable).

Instrumentation: add a middleware shim that logs `model_id, token_count, latency_ms, cost_cents` per request. Export to Prometheus + Grafana for real-time dashboards.

Derived quantity example: *Weighted cost rate* = (total monthly USD) / (total tokens processed). Start with the arithmetic above, then update daily as actual token counts and cloud prices shift.

18.5. Common Mistakes

1. **Treating quantization as free.** 4-bit/8-bit models reduce VRAM but increase CPU cycles and may lower quality on long-context tasks. Always measure the quality hit before routing en masse.
2. **One-size-fits-all routing.** A static rule ("always use 8-bit") fails when workload mix shifts (e.g., seasonal increase in multilingual queries that need FP16 precision). Use a dynamic router with feature-gate checks.
3. **Ignoring capital amortization.** FP16 on 8×H100 has high upfront cost; spreading that cost

across a mixed fleet improves effective cost/token. Don't forget to annualize GPU capex in the per-token math.

4. **Over-provisioning the top tier.** Keeping a full FP16 GPU idle "just in case" is expensive. Keep just enough capacity for the tail (≈10% of peak rps) and route the rest.
5. **No fallthrough plan.** If the preferred model is at capacity, the router must have a next-best alternative ready; otherwise requests time out or queue indefinitely.

18.6. Architecture Consequence

A mixed-model fleet changes the architecture in three ways:

1. **Router shim** (HTTP middleware or gRPC interceptor) sits between the user API and the model execution layer. It evaluates feature requirements, reads current capacity, and selects model_id.
2. **Capacity pool abstraction** – rather than "GPU 0 runs model A," the system tracks "8×H100 pool has 640 GB VRAM; model X consumes 70 GB 8-bit, model Y consumes 35 GB 4-bit." The pool manager auto-balances placements.
3. **Billing/telemetry pipeline** – each request's cost and latency are tagged with model_id, enabling downstream dashboards and alerting (e.g., "cost per token rising above $0.0025 (on the §18.8 mini-case per-token basis) for 3 consecutive hours").

The fleet operator becomes a *cost-latency steward* rather than a single-model optimizer.

18.7. What We Still Don't Know

- **Quality–cost curves for new quantizations.** As 3-bit and sub-4-bit GGUF models emerge, the trade-off surface shifts; we need systematic human evals + automatic benchmarks (MT-Bench, FLAN) across families.
- **Optimal router policy for non-stationary workloads.** Reinforcement-learning–based routing that adapts α,β weights in real time is promising but underexplored in production fleets.
- **Cross-model distillation opportunities.** Can a 70B 4-bit model be distilled from a 70B FP16 teacher without quality loss, effectively lowering the cost floor? Empirical work needed.
- **Edge–cloud continuum effects.** When users bring their own 4-bit-quantized local models (via Ollama, etc.), the fleet routing must account for hybrid inbound/outbound token flows.

18.8. End-of-Chapter Mini-Case: A Three-Tier Customer-Support Model Fleet

Deploy a three-tier fleet for a customer-support chatbot.

- **Tier 1 (4-bit GGUF):** Handles 80% of queries (FAQ, account lookup). Runs on edge nodes (AMD Ryzen 7950X, 64 GB RAM). Cost: $0.0002/token, latency ~600 ms.

- **Tier 2 (70B 8-bit dense):** Handles 15% of queries (order status, policy look-up). Runs on 1×H100. Cost: $0.0015/token, latency ~250 ms.
- **Tier 3 (70B FP16):** Handles 5% of queries (complex escalations, multilingual). Runs on 2 GPUs reserved. Cost: $0.003/token, latency ~120 ms.

Arithmetic: A small pilot deployment serving ~1,000 registered users at a modest, deliberately low volume — **5,000 tokens/hour** (each request averaging ~250 tokens gives roughly 20 requests/hour, a very light load chosen to make the per-token routing economics concrete rather than to model a busy fleet; the traffic rate is not what drives this arithmetic, the per-token volume is). Hourly tokens: ~4,500 in + 500 out = 5,000. *(Scope note: these tier per-token rates are illustrative scenario values that **differ from the §18.3.2 per-1M ledger** — they are not the ledger's $1.25 (8-bit) / $2.50 (FP16) / $0.15 (4-bit) per-1M rates converted, and the 4-bit tier's ~600 ms latency differs from the ledger's 800 ms. They are on a per-token basis, distinct from — and not directly comparable to — the per-1M-token ledger; the mini-case uses them to demonstrate the routing economics, and a real deployment would price from the §18.3.2 per-1M basis.)*

- Tier 1 processes 4,000 tokens/hr ⟶ $0.80
- Tier 2 processes 750 tokens/hr ⟶ $1.13
- Tier 3 processes 250 tokens/hr ⟶ $0.75
- **Total hourly cost: $2.68 ⟶ $1,956 / month** (× 730 hr).

Check the SLO before the cost claim. If we had used a single 70B FP16 model: 5,000 tokens/hr × $0.003 = $15/hr ⟶ $10,950 / month (× 730 hr). The three-tier split looks like an $8,994 / month (≈82%) saving — but the SLO gates the cost claim, and here it fails. **Tier 1 (the cheapest, 4-bit GGUF on CPU, ~600 ms) serves 80% of queries, so the p95 per-request latency is ~600 ms, which violates the 500 ms SLO for the dominant tier.** The split saves cost by routing the bulk to a slow-but-cheap model — precisely the mean-vs-tail trap: the *average* latency looks fine, yet the majority tier misses the deadline. The $8,994 / month saving is therefore *conditional* on first making Tier 1 feasible.

Recalculated cost after substituting a feasible Tier 1. Replace the 4-bit GGUF (CPU, ~600 ms) with 8-bit quantization on a GPU (~250 ms, $0.0015/token — the same rate as Tier 2, which is also 8-bit on 1×H100). The 80% of queries now route at $0.0015/token:

- Tier 1 (8-bit on GPU) processes 4,000 tokens/hr ⟶ $6.00
- Tier 2 (70B 8-bit dense) processes 750 tokens/hr ⟶ $1.13
- Tier 3 (70B FP16) processes 250 tokens/hr ⟶ $0.75
- **Total hourly cost: $7.88 ⟶ $5,752 / month** (× 730 hr).

The p95 is now ~250 ms (all tiers under 500 ms), so the SLO is met. The saving narrows from $8,994 / month (≈82%) to **$5,198 / month (≈47%)** — still a clear win, but the SLO-constrained figure, not the raw 82%, is the honest number. The correct order is: check the SLO, then size the cost. The




FIGURE 18.1: Model-routing decision tree: capability filter → cost/SLO gate → fallthrough, with the specialist, general and fallback model families as leaves

The routing decision chain. A request first passes a capability filter (is there a specialized model that can serve it?), then a cost/SLO gate (route = f(cost, SLO)), and otherwise falls through to a general model. Each specialized family is a leaf the router can dispatch to. This converts the raw cost arithmetic above into the operational routing shape an architect operates daily.

routing arithmetic shows the *economic* win; the SLO check is what keeps it honest, and it must come first.

The key enabler was the router's feature gate: queries mentioning "multilingual" or "technical specification" were auto-escalated to Tier 3; the rest flowed to Tier 1 or Tier 2 automatically.

Evidence labels: [1P] price observations from public cloud provider pricing pages (Q4 2026); [2°] derived per-token cost arithmetic; [UNRESOLVED] latency measurements from local GGUF benchmarks on reference hardware.

CHAPTER 19.

Agentic Systems

The Architect's Question

In large-scale RQA (retrieval-augmented QA) pipelines serving thousands of concurrent users, the transition from static LLM calls to agentic orchestration raises fundamental trade-offs: increased capability versus increased latency, higher per-request token consumption versus better answers, and richer multi-step reasoning versus harder-to-debug execution paths. This chapter addresses the architect's central question: how to design agentic layers that amplify intelligence without unsustainably inflating cost and latency.

We begin from the canonical deployment scenario (Ch 4, Table 4-2): ~10 requests/second average and ~40 requests/second peak. Each request carries ~9,200 input tokens and produces ~300 output tokens. The base model is a 70B dense FP16 engine running on 8×H100 GPUs (640 GB total memory). The agentic layer sits above this foundation, introducing tool use, retrieval, and multi-step reasoning. The question we answer is how much additional overhead this layer introduces, whether the quality gain justifies the cost, and how to size the infrastructure accordingly.

19.1. Concept

An agentic system is one in which the LLM does not merely complete a single prompt but iteratively decides which actions to take — calling tools, querying databases, running checks, and then reasoning about the results before producing a final answer. The core idioms are:

- **Tool use**: The model emits a structured call (often JSON) to invoke an external function — a search API, a database query, a code interpreter, or a guardrail validator.
- **Retrieval**: Within each turn, the agent may trigger a vector search, re-rank results, and feed the top-k passages back into the prompt.

- **Multi-step reasoning**: The agent maintains an internal "thought" chain, appending each new observation and its interpretation before deciding on the next action.
- **Guardrails**: Pre- and post-hoc checks that validate whether the model's intended action is safe, on-topic, or within budget.

The agent loop terminates when a stop condition is met: a final answer is emitted, a maximum turn count is exceeded, or a guardrail blocks further progress. This design pattern replaces the "single-shot" prompt — one LLM call, one response — with a dynamic sequence of calls whose length is data-dependent.

The architect must decide not only which tools the agent may call but also how to instrument each call for latency and token accounting, and how to set termination thresholds so that the system degrades gracefully under load.

19.2. Mental Model

The mental model we adopt visualizes the agent as a state machine with four recurring states: **Plan**, **Execute**, **Observe**, and **Decide**. In each cycle:

1. **Plan**: The model reads the current context (original user query + accumulated observations) and emits a plan — either "proceed with final answer" or "call tool X with parameters Y."
2. **Execute**: The system routes the tool call to the appropriate backend, waits for results, and formats them back into text.
3. **Observe**: The result text is appended to the conversation history, and the token count is updated.
4. **Decide**: The model evaluates whether the observation resolves the user query or whether another cycle is needed.

This loop is deterministic in structure but data-dependent in length. A simple query ("What is the capital of France?") may terminate after one Observe, while a complex RQA request ("Compare the performance of Model A on dataset X against Model B on dataset Y, using the last three papers from arXiv as evidence") may traverse three or more cycles.

The critical insight for capacity planning is that each cycle incurs a fixed overhead: one LLM inference turn plus any tool-call latency. The variable portion is the number of cycles the model chooses. Our mental model therefore separates *fixed cost per turn* from *variable turn count*, and we will quantify both in the next section.

19.3. Worked Example

Take a user query routed to an agentic RQA pipeline. The pipeline's default policy is a maximum of 4 turns; if the model has not terminated by then, the system returns a fallback answer "I'm sorry, I couldn't find a definitive answer within the allowed reasoning steps." (**Scope note on the turn**




FIGURE 19.1: The agent loop as a four-state state machine (Plan, Execute, Observe, Decide) with a loop-back to Plan and the terminal outcomes final answer and stopped. **Exit conditions:** the loop terminates on (a) a final answer (the model decides no more tool calls are needed), (b) a budget cap (max turns or max tokens reached), (c) a tool error that cannot be recovered, (d) a policy stop (guardrail or safety rule triggered), or (e) human approval required. The Decide state evaluates these guard conditions each turn; the loop-back to Plan is bounded by the turn budget, so an accidental infinite loop is prevented by the budget cap, not by the model's judgment alone.

cap. This worked example uses a *default* cap of 4 to illustrate the binding worst case and the token-amplification curve out to T=4. The *recommended operational* policy — deployed in the §8 mini-case and used for fleet sizing in Chapter 17 — caps turns at 3, per the §4 guidance and the 95th-percentile sizing rule; the 2% of requests that exceed the limit fall back to single-shot. Table 19-1's "T=4 (over cap)" column is therefore an *out-of-policy bounding* case, not an in-policy turn count.)

Turn 0 (initial prompt):

- Input: 9,200 tokens (user query + retrieved passages)
- Model emits a tool-call: `search(query="relevant concepts")`
- System routes the call to the search backend, returns top-5 passages (≈ 800 tokens of snippets)
- Total tokens after Turn 0: 9,200 + 800 = 10,000

Turn 1:

- Input: 10,000 tokens (history + new passages)
- Model emits a second tool-call: `db_query(sql="SELECT ... WHERE condition")`
- Latency: 85 ms (local PostgreSQL on H100 host)
- Result: 350 tokens of tuple rows
- Total tokens after Turn 1: 10,000 + 350 = 10,350

Turn 2:

- Input: 10,350 tokens
- Model decides to synthesize: emits a final answer
- Output: 300 tokens
- Conversation ends

Token accounting:

- Base single-shot: 9,200 input + 300 output = 9,500 tokens
- Agentic: 10,350 input + 300 output = 10,650 tokens
- Amplification factor: 10,650 / 9,500 ≈ 1.12×

A harder query that exhausts all 4 turns is the upper-bound case. Using the chapter's per-turn convention (each turn adds $\delta \approx 800$ tokens of retrieved context plus $\gamma \approx 65$ tokens of model-generated reasoning), the token trajectory grows approximately linearly: after k turns, total input tokens ≈ 9,200 + k·(800+65), and total output ≈ 300 (final answer) plus the intermediate reasoning (≈65 tokens per turn). After 4 turns, input ≈ 9,200 + 4×800 + 4×65 = 12,660 tokens, output ≈ 300 tokens, giving a total of ~12,960 tokens. The amplification factor vs. single-shot is 12,960 / 9,500 ≈ 1.36×.

This worked example demonstrates that the cost increase is moderate for short reasoning paths but compounds as the agent loops deeper. The architect must weigh the probability of deep loops against the budget per request.

19.4. Measurement

To plan capacity and set budgets, we derive three real quantities from the example above and from production telemetry.

First, a scoping note that matters more than any single number: a production agent turn is **not** guaranteed to be exactly "one LLM inference + one tool call." A turn may contain zero or more model invocations, parallel or chained tool calls, retrieval + reranking, model-generated reasoning, tool output, context compaction, or cached prefixes. Treating "1 turn = 1 LLM call + 1 tool call" is a *simplified execution model*, useful for first-pass arithmetic but not the general agent model. A more faithful capacity model is an **execution trace**: request → model invocation(s) → tool invocation(s) → observation(s) → model invocation(s) → final response, with its own token and latency totals. The amplification framework below (token α, latency β) is one concrete, simplified instantiation of that trace — it is what an architect can compute before instrumenting a real system, and it must be validated against measured traces afterwards.

19.4.1. Per-agent-turn token amplification

Let T be the number of agent turns and I_0 the initial input tokens (9,200 in our scenario). Each turn adds δ tokens of retrieved context and γ tokens of model-generated reasoning. The total token count after T turns is:

$$\text{Total}(T) = (I_0 + T \cdot \delta + T \cdot \gamma) + O_{\text{final}}$$

where *O_final* is the final output (≈300 tokens). The per-turn amplification α is the ratio of total tokens to the single-shot baseline *I₀ + O_final*:

$$\alpha(T) = \frac{I_0 + T \cdot \delta + T \cdot \gamma + O_{\text{final}}}{I_0 + O_{\text{final}}}$$

With δ = 800, γ = 65, *O_final* = 300, and T = 3:

$$\alpha(3) = \frac{9{,}200 + 3 \cdot 800 + 3 \cdot 65 + 300}{9{,}200 + 300} = \frac{9{,}200 + 2{,}400 + 195 + 300}{9{,}500} = \frac{12{,}095}{9{,}500} \approx 1.27\times$$

For T = 4: α(4) ≈ 1.36× as computed in the worked example. In production, the distribution of T depends on query complexity. Consistent with the mini-case telemetry in §8 (68% T=1, 25% T=2, 5% T=3, 2% fallback), the illustrative turn distribution here has median T = 1, 90th percentile T = 2, and 95th percentile T = 3 [ILLUSTRATIVE][ASSUMPTION] — derived from the §8 distribution.

What α does and does not measure. α measures **retained/accumulated task context** under the simplified turn model — the unique content that must be held (and, absent compaction, resent as context) as the conversation grows. It is **not** the total model-processed or API-billed token multiplier: if the model is invoked repeatedly on the growing prefix, that retained context may be counted in

multiple input calls, and the per-call outputs must be counted separately. So $\alpha \approx 1.27\times$ at T=3 says the *context* is ~27% larger than single-shot — it does *not* say the task costs 1.27× the API spend or 1.27× the prefill FLOPs. Compute actual task tokens by summing the inputs and outputs of every model invocation, with cached-token accounting recorded separately:

$$\text{task_input} = \sum_i \text{input}(call_i), \qquad \text{task_output} = \sum_i \text{output}(call_i)$$

with `cached`, `uncached`, and `billed` token quantities recorded separately (a prefix-cache hit means a call's input is not re-processed from scratch, so billed/FLOP input differs from context-carried input). Example: a 3-call task where calls 2 and 3 reuse the call-1 prefix without caching has `task_input = 9,200 + 10,350 + 12,095 = 31,645` (uncached); with a perfect prefix cache it is bounded by the retained-context sizes instead. Concurrency/queueing and economics follow the call-trace totals, not α.

Token-quantity definitions (distinct terms, used consistently). The five quantities below are different and must not be collapsed:

Term	Definition	Example (T=3, δ=800, γ=65, O_final=300)
`req_in`, `req_out`	tokens of the single-shot baseline request	9,200 input + 300 output = 9,500
`newly_generated_output`	tokens the model *produces as output* in a call (final answer + per-turn reasoning γ)	last call 300; each reasoning pass ~65
`retained_history`	prior turns' context carried into the current call's *input* (the grown prefix)	call 3 carries ~12,095−300 = 11,795 as input prefix
`current_input_length`	the full input of a given call (retained history + new retrieval δ + prompt)	call 3 input = 9,200 + 2×(800+65) + 300 prefix ≈ 12,095
`task_input / task_output`	Σ over all calls of input / output tokens (the execution-trace totals)	uncached task_input ≈ 31,645; task_output ≈ Σ outputs
`cached / uncached / billed`	fraction of task_input served by prefix cache vs re-processed; billed per provider rules	a cache hit makes billed input smaller than task_input

The δ tokens are *generated once* (as retrieval/tool output), then *retained* as part of later turns' input context — they are counted once as output-of-tool and again (as carried context) in each later call's input. That is correct and intended, but it means total tokens ≠ context size: the amplification α (retained context) and the task totals (Σ per-call) are explicitly different, and neither is the billed amount without a cache/billing rule.

19.4.2. Tool-call latency budget

Crucially, the agentic layer adds latency **on top of** the base answer generation, not instead of it. We keep two terms rigidly separate:

- **Base inference latency *L*base** — the time to generate the final answer itself. Under the canonical model this is ~8.6 s: 1.08 s prefill (Ch 8) + ~7.5 s decode of the 300-token answer at ~25 ms/token (Ch 8). Every agentic request pays this at least once, and usually again for the intermediate reasoning the loop generates (the T·γ tokens).
- **Agent orchestration / tool-call overhead *L*agent** — the per-turn cost of the loop *around* the model: the LLM's short decision step to formulate the tool call, plus the tool backend round-trip. On 8×H100 the per-turn agent step averages ~120 ms for a 10,000-token context; tool backends (search, SQL) add 50–150 ms depending on data volume. So per-turn orchestration overhead *L*agent ≈ ~220 ms (median).

$$L_{\text{agent}} = \lambda_{\text{step}} + \lambda_{\text{tool}}$$

where $\lambda_{\text{step}} \approx 120$ ms (the model's tool-call decision step) and $\lambda_{\text{tool}} \approx 100$ ms (median, tool backend). For T turns the **added** orchestration overhead is $T \cdot L_{\text{agent}} \approx 220$ ms at the median $T = 1$, ≈ 440 ms at the 90th percentile $T = 2$, and ≈ 660 ms at the 95th-percentile $T = 3$ (consistent with the §8 turn distribution and the §4 turn-distribution note; T is capped at 3, and the 2% fallback is a zero-added-turn single-shot). These are the **incremental agent-orchestration** numbers, not the full request latency — see the next section.

19.4.3. Multi-step reasoning cost

The "cost" of multi-step reasoning has two facets: token amplification (already quantified as α) and latency. The **total end-to-end latency** is the base generation plus the added orchestration overhead:

$$L_{\text{E2E}}(T) = L_{\text{base}} + T \cdot L_{\text{agent}}$$

where $L_{\text{base}} \approx 8.6$ s is the canonical full answer generation (1.08 s prefill + 7.5 s decode of 300 output tokens) and $T \cdot L_{\text{agent}}$ is the added agent-orchestration overhead (≈ 220 ms per turn). So the agentic layer does *not* replace the ~8.6 s generation with ~440 ms — it *adds* a few hundred milliseconds of orchestration/tool overhead on top of a request that already takes ~8.6 s to generate its answer.

Scope note — this is the incremental orchestration model, not the full agentic service time. The $L_{\text{E2E}}(T)$ above holds the base generation at the *single-shot* decode (300 output tokens) and adds only the per-turn orchestration overhead. It deliberately isolates *how much the agentic layer's orchestration adds*. The **full** agentic service time — the quantity used for fleet sizing in Chapter 17 — must additionally account for (a) the decode of the per-turn model-generated reasoning tokens ($\gamma \approx 65$ tokens/turn, at ~25 ms/token ≈ ~1.6 s/turn) and (b) the longer prefill of the grown context ($I(T) = 9{,}200 + T(800 + 65) + 300$). Chapter 17 §8 derives that full service time as $W \approx 13.8$ s at $T = 3$ (1.08 s prefill held at the canonical 9.2K representative — the 12,095-token context would scale it to ~1.42 s, giving W ≈ 14.2 s, so 13.8 s is a lower bound — plus ~12.4 s decode of ~495 generated tokens and ~0.4 s tool latency). So: the **incremental orchestration overhead** is $T \cdot L_{\text{agent}}$ (~660 ms at T=3, $\beta \approx 1.08\times$), while the **full end-to-end service time** of an agentic request is ~13.8 s at T=3 — the two are *different quantities*, and the latter is what sets concurrency and fleet size. Table 19-1's "Total end-to-end (Lbase + overhead)" row reports the *incremental* model; the full service-time values appear in Chapter 17's fleet-sizing tables. The latency amplification is better expressed as overhead, not a multiple of a sub-second single-shot number:

$$\beta(T) = \frac{L_{\text{base}} + T \cdot L_{\text{agent}}}{L_{\text{base}}} \approx 1 + \frac{T \cdot 220\ \text{ms}}{8.6\ \text{s}}$$

At T = 3, $\beta(3)$ is 1 + 660 ms / 8.6 s ≈ **1.08×**, i.e. the **orchestration-only** component adds roughly 8% — the agent loop is *not* "2–6× slower" in the orchestration sense. But β measures only the incremental orchestration overhead, **not** the full agentic task slowdown. The full service time of a representative three-turn task grows from ~8.6 s (single-shot) to at least ~13.8 s (~1.6×) once the per-turn reasoning decode (~65 γ tokens/turn) and the longer grown-context prefill are counted — a full increase of ~5.2–5.6 s. So β is β_{orch} (orchestration-only), and the true task-level multiplier is $L_{\text{task E2E}}/L_{\text{base}} \approx 1.6\text{–}1.65\times$ at T = 3. The bound that actually matters for the architect is that the *added* orchestration overhead per turn is ~220 ms (and must be budgeted), while the *total* request time — and hence fleet sizing — is set by the ~13.8 s full service time, not the ~8.6 s single-shot generation.

These derived quantities give the architect concrete numbers to set policies: cap T at 3 unless the quality gain is statistically significant, and allocate ~220 ms *per turn* in the orchestration-latency budget.

19.5. Common Mistakes

1. **Unbounded or miscalibrated turn limits.** Setting the maximum number of agent turns too high for the task leads to runaway token consumption and latency spikes. In production we have seen a single request consume >30,000 tokens and take >5 seconds because the model kept looping on a poorly scoped tool. The right cap is task-calibrated, not a universal number: measure the distribution of useful completion turns, loop-failure turns, and marginal value per

turn for the workload, then set the cap where marginal value drops off (the canonical policy caps at 3, with a 2% fallback to single-shot — §4, §8). A cap of 10 may be too many for one workflow and too few for another; the number is a policy parameter, not a constant.

2. **Neglecting token accounting per turn.** Many architects track only the initial input tokens and forget that each retrieval or tool call adds context that persists for all subsequent turns. The compounding effect means that turn T sees an input base that grows linearly with T.

3. **Overlooking tool latency variance.** A tool that typically responds in 30 ms may, under cache misses or lock contention, take 2 s. Without a timeout and fallback, the entire agent loop blocks. Always instrument timeouts and provide a "best-effort" fallback path.

4. **Confusing 'agentic' with 'more prompts'.** Adding extra prompts without a structured loop (Plan/Execute/Observe/Decide) does not give the model reasoning power; it just inflates token count. The agentic value comes from the model's ability to reinterpret prior observations and decide the next action.

5. **Skipping guardrails.** Without pre-call validation (e.g., query sanitization, budget checks) and post-call verification (answer relevance, hallucination detection), agentic systems can produce plausible but incorrect or unsafe outputs. Guardrails are not optional — they are the safety net that makes *bounded* loops safe in production. A production agent needs explicit termination, budget, recovery, and escalation policies: hard turn/token/cost/wall-time limits, tool timeouts, cancellation, idempotency/retry discipline, state checkpointing, and human escalation. A logical multi-step task may be resumed across bounded execution windows rather than granted unlimited resources — guardrails make the loop *safe*, not *unbounded*.

19.6. Architecture Consequence

Introducing an agentic layer reshapes the system architecture in four ways:

State-management policy sets the trajectory. Before quantifying context/KV growth, the architect must decide the *state-management policy*, because that policy — not the model — determines whether context grows unbounded. The quantitative path that follows (Fig 19.2/19.3) uses an **append-only bounding case** with this exact retention policy: (i) the initial prompt is retained in full; (ii) each turn's tool outputs are retained in full (not externalized); (iii) the model's per-turn reasoning tokens are visible and retained in the context (not hidden); (iv) no prefix cache is assumed to be reused across turns (each turn's request is rebuilt from the full accumulated context); (v) no truncation or compaction is applied. Under that policy the context is only ever appended and never evicted, so it is the worst case — a deliberate upper bound, not the deployed design. Two token counts must be kept distinct: the **billable tokens** (what the API charges, = the full accumulated context sent each turn) and the **KV-resident tokens** (what occupies the cache, = the same accumulated context under this no-reuse policy); with prefix caching enabled the billable count can fall while the KV-resident

count stays, so the two diverge. The durable architectural lesson is that the growth rate is set by the policy levers — summarization (compress the accumulated history each turn), truncation (drop the oldest context beyond a budget), externalized tool state (store retrieval results out-of-band rather than in-context), replay policy (re-derive rather than retain), and cache policy (prefix caching, KV precision). A design that applies these levers can hold context roughly flat while an append-only design grows it ~36% by turn 4; the append-only number is the *stress case* that bounds what the system must tolerate if the levers fail, not the expected operating point.

Inference scaling. The base model (70B FP16, 8×H100) must now serve variable-length contexts, and — critically — the KV-residency conclusion is far more severe than a per-latency convenience because the canonical per-token KV is ~2.62 MB/token (Chapter 7's full-MHA reference geometry). A request that triggers 4 agent turns carries ~12,960 tokens vs. 9,500 for single-shot (Table 19-1) — that is not a "35% GPU memory" tweak but a move from ~24.9 GB KV per request (9,500 tokens × 2.62 MB) to ~34.0 GB (12,960 ×2.62 MB) — roughly a 36% growth, on top of an already-large KV footprint. At the canonical workload's ~86 average in-flight requests at 10 rps (L_exec = λ × W_exec ≈ 10 × 8.6 per Ch 4; distinct from the ~100 *active-user* population) with the median single-turn profile (~27.2 GB/request at 10,365 tokens), the aggregate KV alone is ~86 × 27.2 GB ≈ 2.3 TB — far beyond one host's ~436 GB KV budget, so **agents do not just stress memory, they force a fleet** (Chapter 17). The architect must therefore treat context growth as a first-order capacity driver: cap T, cache prefixes, or quantize KV (FP8), as these levers repeatedly outprice adding hosts. Note we must be precise: the per-request KV is set by the model's canonical per-token KV (all layers), not by per-layer figures; the honest number is tens of GB per request, which is exactly why agentic depth is a fleet-sizing problem.

Task economics. The deepest shift an agentic workload imposes is a change in *what the architect optimizes*. For conventional inference, the unit of cost is the token: the architect optimizes token economics — cost per token, latency per token, KV per token. For an agentic system, the unit of value is the *task*: the architect optimizes task economics, because a task consumes a variable, data-dependent number of model calls, tool calls, and tokens, and may fail. The right denominator is therefore **cost per successful task**, not cost per token:

```
cost / successful task ≈
         (model calls/task × tokens/call × $/token)
                          + (tool calls/task × $/tool)
                          + (retries/task × cost/retry)
             divided by the success rate of the task
```

where tokens/call is itself inflated by the agentic amplification α from Section 4. Two consequences follow. First, a more expensive model that completes tasks in one turn can be cheaper *per successful task* than a cheap model that needs three turns — the amplification term can dominate the base price. Second, the success rate is as important as the unit cost: a 10% cheaper pipeline that fails 5% more often can be net more expensive once retries and human intervention are counted. This is a genuinely different objective from *cheapest tokens*, and it is why agentic workloads cannot be priced




FIGURE 19.2: Input/output tokens and KV cache per request across agent turns (I_0 + T·δ + T·γ + O_final; 9,200 input + 300 output + 800 + 65 per turn), FP16 KV rising from 24.9 GB single-shot to 34.0 GB at 4 turns. This chart quantifies the growth — the total token and KV numbers as turns accumulate. (Companion Fig 19.3 shows the mechanism of why it grows.) — Ch 19 §3 arithmetic

Why agentic depth is a fleet-sizing problem. Both the token count and the FP16 KV cache grow linearly with turns; four turns take a request from ~24.9 GB to ~34.0 GB of KV — a 36% jump on an already-large footprint, which is exactly why a fleet (Ch17), prefix caching, or FP8 KV pay for themselves on agentic workloads.




FIGURE 19.3: The agentic context block grows every turn: initial prompt I_0 (9.2K input) plus a fixed output O_final (300) plus tool output (δ) + reasoning (γ) appended each turn, FP16 KV footprint rising 24.9 ⟶ 34.0 GB (max-KV, end-of-request). This schematic shows the mechanism — the initial prompt plus the fixed output and cumulative tool-output and reasoning blocks (matching Fig 19.2's decomposition). **Policy caveat: this depicts a *strict append-only* agent context.** Real production systems may compact, truncate, cache, summarize, or reconstruct the prompt between turns, so the monotonic growth shown here is a *worst-case / illustrative policy*, not a universal model of agent memory. A production stack that compacts or summarizes context can hold the KV footprint flat or even shrink it across turns. — Ch 19 arithmetic

Agentic context accumulation as a memory sequence. Each turn appends retrieved context (δ ≈ 800 tokens) plus generated reasoning (γ ≈ 65 tokens) to a context that persists across every later turn; the FP16 KV block therefore grows from ~24.9 GB (single-shot) to ~34.0 GB (four turns) — a 36% footprint rise driven purely by cumulative context, not by extra requests. This is the mechanism behind the fleet-sizing argument in Fig 19.2.

or capacity-planned with the single-shot token arithmetic alone. An architect should instrument tasks (success, turns, calls, retries) and optimize cost per successful task, exactly as an architect of a deterministic service optimizes cost per completed request.

Tool backend provisioning. Search indexes, SQL pools, and code interpreters become first-class infrastructure components. Their capacity (concurrent queries, connection pool size, query throughput) must be dimensioned alongside the LLM GPU pool. A bottleneck in the tool backend will manifest as increased λ_tool, which directly inflates the per-turn latency L and therefore the overall request latency.

Observability requirements. Each turn generates a tuple of (turn number, model input tokens, tool call, tool latency, tool output tokens, decision). Correlating these tuples across turns for a single request, and across requests for the fleet, requires structured logging and tracing. Without it, debugging why a request took 2 s and consumed 15,000 tokens is nearly impossible.

Fallback & degradation pathways. Because the agentic layer introduces data-dependent depth, the system must have graceful degradation: if the turn limit is reached, return the best partial answer so far, or fall back to a simpler single-shot prompt. This preserves user experience even when the agent fails to converge.

19.7. What We Still Don't Know

Despite the quantified arithmetic above, several questions remain open and would benefit from targeted research:

- **Turn-count distribution shift with model scale.** Do larger-context models (e.g., 405B FP16) exhibit different T distributions? Does the ability to "see more" reduce the need for multi-step loops, or does the model reason more deeply and actually increase T?
- **Token amplification vs. answer quality curve.** We can compute $\alpha(T)$ from the illustrative token counts, but we have not firmly established the marginal quality gain per additional turn. Is the 1.27× ⟶ 1.36× move from $T = 3$ to $T = 4$ worth the 7% token increase? A/B tests across query categories would help.
- **Latency tail under spike load.** Our 95th-percentile *added* orchestration latency of ~660 ms (T = 3, the scenario turn cap; the 2% fallback is single-shot) assumes GPU inference time is constant. Under traffic spikes, GPU saturation can increase inference latency non-linearly. Empirical measurement under controlled load is needed to validate the linear $T{\cdot}L$ model.
- **Optimal tool design for minimal turn count.** Some tools could return more comprehensive results in a single call, reducing the need for multiple rounds. The design space of "rich vs. narrow" tools and its impact on T is underexplored.
- **Cross-user context caching.** If many users ask related questions (e.g., "What does the policy say about X?"), can we cache intermediate retrieval results and avoid redundant tool calls? The savings could be substantial but require careful invalidation logic.

19.8. End-of-Chapter Mini-Case: Agentic Turn Distribution and KV Growth

Scenario. An enterprise RQA system serves 2,000 knowledge workers. The baseline single-shot configuration uses a 70B FP16 model on 8×H100, with 9,200 input tokens and 300 output tokens, handling 10 rps average / 40 rps peak. The team introduces an agentic layer with a maximum of 3 turns, using the chapter's per-turn convention (each turn adds $\delta \approx 800$ tokens of retrieved context plus $\gamma \approx 65$ tokens of model-generated reasoning, i.e. ≈865 tokens/turn). The guardrail budget caps total input at 13,000 tokens.

Measurement results. Telemetry over 30 days shows:

- 68% of requests terminate in 1 turn
- 25% terminate in 2 turns
- 5% terminate in 3 turns
- 2% exceed the turn limit and fall back to single-shot

Token and latency impact (added orchestration overhead). Using the chapter's per-turn convention (each turn adds δ=800 retrieved + γ=65 reasoning = 865 tokens), and treating the 2% fallback as single-shot (zero added turns), the expected input tokens across the distribution are:

- Expected input tokens: 0.68×(9,200+865) + 0.25×(9,200+1,730) + 0.05×(9,200+2,595) + 0.02×9,200 ≈ 6,844 + 2,733 + 590 + 184 ≈ **10,350 tokens** (expected total incl. 300-token output ≈ 10,650).
- Amplification α: 10,650 / 9,500 ≈ **1.12×** — about a **12%** token overhead. (The 2% fallback is explicitly included here at zero added turns: it adds no agent tokens, so its contribution to the expectation is 2% × 0 = 0, which the weighted sum above keeps.)
- Added agent-orchestration overhead (per-turn step + tool): 220 ms/turn. Because 68% terminate in one turn, the **median turns is T=1**, so the median added overhead is **1 × 220 ms ≈ 220 ms**; the **90th-percentile** is T=2 (cumulative 93% by T≤2) ⟶ **440 ms**; and the **95th-percentile** is T=3 (cumulative 98% by T≤3) ⟶ **660 ms** — *not* T≈4, since the scenario caps turns at 3 and the 2% fallback is modelled as an immediate single-shot fallback, not a fourth attempted turn. **Percentile conditioning:** these percentiles are computed over the **non-fallback (completed-turn) request distribution** — they are *conditional on a completed agent run*. The 2% fallback is treated as a high-tail/failure category that incurs *zero added turns* (single-shot), so it is excluded from the percentile claims (it sits above the p98 tail and does not add to the p90/p95 values). If instead the fallback is defined to incur timeout delay or additional recovery work, it must be included as an unconditional request-level percentile (with its added latency counted), which raises the true tail. State which convention is in use; the two give different p95 values. On top of the ~8.6 s base answer generation, $L_{E2E} \approx 8.6\text{ s} + 0.22\text{ s} \approx$ ~8.8 s at the median.
- Total end-to-end: the request is dominated by the ~8.6 s base generation (Ch 8), not the added orchestration; the ~220–660 ms figures are the *added* agent/tool overhead, not the complete request latency.

Architectural actions. The team sets the turn limit to 3, instruments each turn's token and orchestration latency, and adds a context cache for the search tool. With the cache hit rate of 30% on recurring queries, the effective δ drops to ~560 tokens, reducing average amplification to ~1.09× (about a 9% token overhead); the median added orchestration overhead is still T=1 ⟶ ~220 ms. The claim "meets an SLA of <1 s" must be scoped carefully: the *added agent-orchestration* latency is comfortably under 1 s, but the **end-to-end** request is ~9 s because of the base generation. The architect therefore scopes the <1 s SLA to orchestration overhead *excluding* final generation, and treats end-to-end as bounded by the ~8.6 s base.

Lesson. The agentic layer added an expected ~12% token overhead (distribution-weighted, §8) and, at the median T = 1, ~220 ms of orchestration latency (on top of an ~8.6 s base generation), but improved answer correctness on multi-step reasoning queries by an estimated 22% in an illustrative human-eval reading [ILLUSTRATIVE] scenario result, not a reported production measurement. The trade-off was acceptable — the added overhead is small relative to the base generation — and the token overhead was mitigated by context caching. The architect's key decisions were: (a) capping turns at 3, (b) adding a search cache, and (c) providing a single-shot fallback when the limit is hit.

Table 19-1 — Token amplification and latency trade-offs for agentic RQA pipelines

Metric	T=1 (med.)	T=2 (p90)	T=3 (p95)	T=4 (over cap)	Single-shot
Input tokens (9,200 + T·800 + T·65)	10,065	10,930	11,795	12,660	9,200
Total tokens (incl. 300 output)	10,365	11,230	12,095	12,960	9,500
Token amplification α	1.09×	1.18×	1.27×	1.36×	1.00×
Per-turn agent step, 10K ctx	~120 ms	~120 ms	~120 ms	~120 ms	—
Tool latency (median)	~100 ms	~100 ms	~100 ms	~100 ms	—
Added orchestration overhead (T × 220 ms)	~220 ms	~440 ms	~660 ms	~880 ms	0 ms
Base answer generation *L*base	~8.6 s	~8.6 s	~8.6 s	~8.6 s	~8.6 s
Total end-to-end (Lbase + overhead)	~8.8 s	~9.0 s	~9.3 s	~9.5 s	~8.6 s
KV cache @ 2.62 MB/token	~27.2 GB	~29.4 GB	~31.7 GB	~34.0 GB	~24.9 GB

All token counts use δ=800, γ=65, O=300; orchestration overhead uses λ_step≈120 ms + λ_tool≈100 ms per turn; base generation uses the canonical ~8.6 s (1.08 s prefill + 7.5 s decode of 300 output tokens). Total end-to-end is dominated by the base generation, NOT the agent overhead. These are canonical-model [DERIVED] values, not measured production figures.

CHAPTER 20.

Fleet-Level Optimization

The Architect's Question

As a RAG Q&A workload scales from a single host to a fleet of serving nodes, the architect must confront a new set of trade-offs: how does aggregate throughput scale with added hardware, how does scheduling latency affect user-perceived latency, and at what point does autoscaling cease to be cost-effective? This chapter addresses these questions through concrete arithmetic, not hand-waving.

20.1. Concept

Fleet-level optimization treats the entire collection of serving hosts as a single resource pool rather than independent islands. The central insight is that aggregate system throughput is not merely the sum of individual host throughputs; it is modulated by scheduling overhead, network contention, and the cost of moving data between hosts and storage. Two cost effects must be kept distinct. The **average** cost per query declines as the fleet grows, because fixed costs (model loading, infrastructure, staff) are amortized across more concurrent requests. The **marginal** cost of each added host, however, is roughly constant in this model — one host buys ~2.0 req/s at ~$20/hr, so the marginal cost stays near ~$9.5 per req/s per hour (Ch 17 §7 frames the Nth host as diminishing marginal *benefit*, not falling marginal cost). The economic lever is amortizing the fixed term, not the marginal one.

The key concepts are:

- **Aggregate throughput**: The total queries-per-second the fleet can sustain before latency SLA violations.
- **Scheduling overhead**: The per-request cost of dispatching a query to an available host, including placement decisions and data movement.

- **Autoscaling break-even**: The point at which adding another host reduces marginal cost per query versus the fixed cost of provisioning and maintaining that host.

20.2. Mental Model

The mental model for fleet optimization replaces the single-host query pipeline with a two-level hierarchy. At the lower level, each host processes queries using its GPU/CPU pipeline. At the upper level, a scheduler routes incoming requests across hosts, handling load balancing, model parallelism where needed, and graceful degradation under overload.

The scheduler's decisions have direct impact on the tail of the latency distribution. Poor placement can cause some hosts to saturate while others remain underutilized, inflating the 99th-percentile latency even when aggregate throughput is ample. Conversely, intelligent scheduling—such as consistent hashing for session affinity or predictive placement based on historical patterns—keeps utilization flat across the fleet and minimizes tail latency.

A critical assumption in this model is that the workload follows a known arrival process. For the canonical scenario (Ch 4, Table 4-2): ~10 rps average and ~40 rps peak. With ~9,200 in-tokens and ~300 out-tokens per query, a ~8.6 s service time per request (1.08 s prefill + ~7.5 s decode), and a 70B dense FP16 model running on 8×H100 (640 GB total HBM3), the fleet must sustain **~40 requests/s at peak**, which — by Little's law — corresponds to **$\lambda \cdot W \approx 40 \times 8.6 \approx 344$ requests in flight**, not merely the ~100 concurrent *users* or the nominal 40 rps. The distinction between "concurrent users" (a population), the arrival rate (rps), and in-flight requests ($\lambda \cdot W$) is exactly what Chapter 17 develops; it is the difference between sizing for a population and sizing a fleet against a latency bound.

20.3. Worked Example

Take a fleet of N hosts, each with 8×H100 running a single 70B FP16 model instance. Two capacities must be reconciled — **throughput** (tokens/s) and **KV residency** (concurrent requests) — and neither can be reduced to a single "rps" constant, because rps is workload-specific (per-request input/output tokens, context length, batch).

Latency floor first, then reconcile the two capacity bounds. A 300-output-token request at a ~25 ms/token decode rate (Chapter 8) takes ~7.5 s of generation alone, plus 1.08 s prefill, so the service time is ~8.6 s per request (before tool calls). Two separate ceilings bound how many requests a host can *serve per second*, and they must be reconciled — they are not interchangeable:

- **Throughput bound (tokens/s).** A host sustains an illustrative ~35,000 tokens/s of *total* (prefill+decode) serving throughput — the conservative low end of the ~35,000–70,000 tokens/s range in Chapter 15 [ILLUSTRATIVE] achievable range — distinct from the ~19,800 tok/s *prefill-only* ideal in Chapter 8 (8 × 2,471 at 35% MFU), which counts prefill compute alone. **These two are not directly comparable as single numbers: ~35,000 is a phase-mixed *prefill+decode* total and ~19,800 is a *prefill-only* figure. To compare them one must first phase-resolve both, then compare prefill with prefill (the presented workload's**

prefill leg is 2.0 req/s × 9,200 = 18,400 input tok/s) and decode with decode (2.0 × 300 = 600 output tok/s); aggregating the two phases into one "total" rate requires an explicit cost/phase-equivalence model. Dividing the total by the ~9,500 tokens/request gives ~3.7 requests/s — **but this is not achievable here**, because it would require ~3.7 × 8.6 ≈ 32 concurrent requests in flight, roughly double the host's KV-residency ceiling (C ≈ 17.5, conservative integer floor 17, Chapter 17). The token-throughput figure is thus a non-binding upper edge for this canonical workload.

- **KV-residency / latency bound (Little's law).** The real ceiling is set by concurrency and service time together: a host holds ~17.5 concurrent full-context requests (KV ceiling, Chapter 17) each for ~8.6 s, so it serves C/W ≈ 17.5 / 8.6 ≈ **2.0 requests/s** at steady state.

The binding per-host rate is the *minimum* of the two — here the KV/latency bound. This is exactly why a token-throughput number must not be divided by tokens-per-request to manufacture a "rps": a token and a request are different units, and prefill (compute-bound) versus decode (bandwidth-bound) tokens are not fungible in that division. The per-host request rate is a *concurrency × service-time* quantity, not a tokens ÷ tokens conversion.

Call this quantity what it is. The ~2.0 req/s figure is a **KV-residency / service-time analytical planning bound under the canonical W assumption** — not a measured serving throughput. It is achievable only if serving C concurrent sequences does *not* inflate W beyond the assumed ~8.6 s, and neither a compute, bandwidth, nor scheduler constraint binds first. In real continuous batching, W is a function of batch occupancy, scheduler policy, prefill interference, decode batching, the arrival process, tensor-parallel communication, and the context distribution — so C and W are not always independent constants. Treat ~2.0 req/s as an upper-bound model, and require benchmarked goodput (Chapter 14) under the target arrival process for actual fleet sizing. **Planning-bound caveat:** like the ~19,800 prefill tok/s/host figure (Ch. 8, idealized prefill only), the ~2.0 req/s/host figure is an *upper-order planning bound* — model-derived, **not an implied deployed rate**. **No p95/p99 performance guarantee has been shown** for any of the host counts in this chapter; the p95/p99 tail latency and achieved goodput must be measured on the target deployment (Chapter 14) before the 20-host sizing is treated as validated.

Simultaneous feasibility check (prefill + decode coexistence). The ~2.0 req/s/host bound assumes prefill and decode run on the same host at the same time. At 2 req/s the prefill demand is 2.0 × 9,200 = **18,400 input tokens/s per host** (§3). The idealized prefill ceiling is 8 × 0.989 PF/s × 35% / (2 × 70e9) ≈ **19,780 tokens/s** (Chapter 8, 35% MFU, prefill-only). The ratio is 18,400 ÷ 19,780 ≈ **93%.** Prefill must run at ~93% of the idealized prefill ceiling. This is **[ANALYTICAL]** (Axis-3 measurement status; defined with the evidence taxonomy in the Sources, Method, and Reproducibility chapter) — a prefill-load check, not a measured rate. The ~93% leaves very little headroom before decode coexistence, interference, and the actual achieved MFU. Prefill and decode share the same hardware. Batch scheduling and decode interleaving compete for the same compute. The achieved MFU is below the 35% ideal. Therefore ~2.0 req/s/host is an **analytical upper bound**, **NOT a claim that a**

host serves 2 req/s at SLO. Before treating 2 req/s/host as deployable, measure the p95 TTFT, p95 TPOT, and SLO-goodput on a representative host (Chapter 14).

Fleet aggregate throughput (illustrative form). Keeping the illustrative per-host rps = Q for the algebra, aggregate throughput is

$$\Lambda_{\text{fleet}} = N \times Q$$

At the canonical peak of 40 rps, fleet size must satisfy **both** the KV-residency and the throughput/latency bounds *and whichever binds first*. With the per-host rate at ~2.0 req/s (the binding Little bound above), a fleet for 40 rps starts at ~20 hosts on the Little-bound. The KV-residency bound coincides here — by Little's law, the in-flight count at 40 rps is λ·W = 40 × 8.6 ≈ 344, and $\lceil 344/17.5 \rceil \approx$ 20 hosts — so the two bounds are *co-binding* at the peak, exactly as Chapter 17 notes (the two views are the same identity, λW/C = λ/(C/W)). The "far fewer hosts (~5)" figure applies only to the 10-rps average, not the 40-rps peak. The correct statement is: the fleet must satisfy both, and the *larger* requirement wins.

Scheduling overhead. A lightweight round-robin scheduler adds ~0.5 ms of dispatch latency per request — negligible next to a real 7.5 s decode, but it must stay under ~5% of the *measured* per-request time.

Autoscaling economics. Each 8×H100 host costs ~$20/hour (cloud, $2.50/GPU-hr canonical) or ~$8/hour amortized (owned) — [ILLUSTRATIVE]. The marginal cost per additional rps is $20 ÷ (rps gained per host); the economic lesson (diminishing cost of a marginal host once fixed costs dominate) is sound, but the exact per-rps figure is only meaningful after the real per-host throughput is benchmarked.

20.4. Measurement

To validate fleet-level optimization claims, three core metrics should be measured at regular intervals:

Metric	Definition	Target
Aggregate rps	Total queries processed per second across all hosts	≥ 2× peak rps for comfort margin
Scheduler-added p99 latency	99th-percentile time a request waits in the fleet dispatcher (NOT end-to-end — model execution is multi-second here)	< 100 ms

Metric	Definition	Target
Scheduler-added median latency	50th-percentile dispatch latency, scheduler overhead only	< 30 ms
Scheduling overhead	Fraction of per-query time spent in dispatcher, not compute	< 5%
Utilization variance	Standard deviation of per-host query rate as a fraction of mean	< 0.2

*Note: end-to-end median/p99 latency is deliberately **not** a fleet-level target for this canonical 9.5K-token workload — a request takes ~8.6 s in service (1.08 s prefill + ~7.5 s decode), so an* end-to-end *<100 ms p99 is infeasible (see the mini-case). The table therefore qualifies these as scheduler-added (dispatch) latency targets only.*

Measurement methodology: use a distributed load generator (e.g., Locust or a custom gRPC-driven pump) that sends queries at the target rps while instrumenting each host's internal metrics—GPU occupancy, kernel launch time, scheduler dispatch timestamp, and queue depth. Aggregate these via a time-series database (InfluxDB or Prometheus) and compute the above metrics over sliding 1-minute windows.

A practical pitfall: measuring only aggregate rps without tracking per-host variance can mask saturation in individual nodes. Always report both the fleet-wide and per-host metrics.

20.5. Common Mistakes

- **Treating hosts as independent**: Optimizing each host in isolation (e.g., tuning batch size per host) ignores the scheduling overhead that becomes dominant when the fleet is viewed as a unit. A suboptimal batch size on one host can increase dispatch frequency for the entire fleet.

- **Overlooking data movement cost**: In RAG workloads, the ~9,200 in-tokens and ~300 out-tokens per query must be fetched from a vector database or cache. If every host pulls data independently, the network cost scales linearly with fleet size. A better approach is to colocate vector stores with serving hosts or use a shared cache layer that amortizes fetch cost across concurrent queries.

- **Autoscaling too aggressively**: Adding hosts at the first sign of latency increase can be

suboptimal if the bottleneck is scheduler throughput or cache contention, not compute capacity. Measure the marginal cost of adding a host before triggering a scale-out event.

- **Ignoring cold-start cost**: When a host is freshly provisioned or re-warmed after idle, loading the full model weights into HBM takes 30–120 seconds (a weight-load figure; distinct from the much shorter KV-cache warm-up of ~2 s discussed in Chapter 15, which re-populates only the retained KV state). Autoscaling policies must account for this weight-load warm-up window when scaling out a fresh host; otherwise the fleet experiences a spike in error rate or timeout during scale-out events.

20.6. Architecture Consequence

Fleet-level optimization reshapes the serving architecture in three ways:

1. **Centralized scheduler**: A lightweight service (e.g., based on etcd or a custom placement engine) maintains real-time view of per-host utilization and makes dispatch decisions. This service must be highly available, and its dispatch overhead should stay a small fraction of the per-request SLO — for the canonical ~8.6 s service time, a sub-millisecond decision is a comfortable *target* (the round-robin baseline adds ~0.5 ms, §3), not a universal necessity: the binding constraint is that dispatch overhead not consume a meaningful share of the request/turn SLO, which depends on routing frequency and scheduling architecture.

2. **Data colocation**: Vector indexes and model weights are stored close to the hosts that consume them. This may mean running a local Qdrant or Milvus instance per host, or using a shared object store (e.g., MinIO) with read-replicas per availability zone. The goal is to minimize the distance—measured in network hops—between the scheduler's placement decision and the data fetch. But colocation is a trade, not a free win: a per-host index multiplies memory/storage, consistency, ingestion, and operational cost across the fleet, and model-weight locality is a different problem from vector-index locality. The right placement depends on the workload — compare centralized retrieval, AZ-local retrieval, replicated indexes, and cached results, and identify the traffic/latency point at which colocation's access-latency saving outweighs its replication cost. Do not conflate the two locality questions.

3. **Graceful degradation**: The fleet should have a mode where, under extreme overload, it serves stale or truncated answers rather than failing entirely. This could mean returning the top-k results from a cached embedding rather than recomputing, or surfacing a "try again" message with an estimated wait time. The architectural contract must make this trade-off explicit so product teams can set appropriate SLOs.

20.7. What We Still Don't Know

Several open questions remain at the fleet level:

- **Heterogeneous hardware**: What happens when hosts mix H100, A100, and CPU-only nodes? The scheduler must handle different throughput ceilings and memory capacities, and the aggregate throughput calculation becomes a weighted sum rather than a simple multiple. Real-world measurements of mixed-device fleets are scarce; most published benchmarking uses homogeneous hardware, so the crossover point where heterogeneity hurts versus helps is not well quantified.

- **Multi-model serving**: When multiple model sizes coexist (e.g., 70B for complex queries, 7B for quick ones), the scheduling problem gains a new dimension—placement must balance model size against query urgency and host memory. Mixed-precision serving (FP16, FP8, INT4) adds another layer: lower precision increases throughput but may degrade answer quality on subtle reasoning tasks, and the quality-throughput trade-off curve is model-specific.

- **Economic auto-scaling**: The break-even point between owning hardware versus cloud-on-demand depends on utilization patterns that are workload-specific. A fleet that runs at 20% utilization on average may be cheaper in the cloud; one at 80% utilization favors owned hardware. The transition point is a function of capital expenditure amortization period, electricity cost, and the volatility of user demand. Published TCO analyses typically assume steady utilization, but bursty workloads with short-lived spikes can make ownership risky unless over-provisioned.

- **Tail-latency arbitration**: When two queries compete for the same GPU HBM bandwidth, the 99th-percentile latency can spike disproportionately. We lack a general-purpose scheduler policy that guarantees a target tail latency under arbitrary arrival patterns; this remains an area of active research. Some systems use priority queues or token buckets to cap per-query bandwidth, but these mechanisms add scheduling complexity and can increase median latency.

- **Cross-query caching effects**: In RAG workloads, the ~9,200 in-tokens and ~300 out-tokens per query overlap significantly across users asking related questions. The potential for caching intermediate embeddings or partial KV caches is substantial, but the cost of cache management (invalidation, coherence, metadata overhead) must be quantified against the compute savings. We lack large-scale measurements of caching efficiency across diverse query populations.

20.8. End-of-Chapter Mini-Case: Aggregate rps, Marginal Cost, and an Infeasible SLO

Scenario: A RAG Q&A fleet serves 2,000 users with the canonical parameters: 5% concurrent, 10 rps average / 40 rps peak, ~9,200 in-tokens + ~300 out-tokens per query, 70B dense FP16 model, 8×H100 per host, 8 hosts total.

Question: What is the fleet's aggregate rps capacity under the canonical KV/latency bound, and what is the marginal cost per rps when scaling from 8 to 16 hosts? Is an end-to-end 99th-percentile latency under 100 ms even feasible for this workload — and if not, what can the scheduler bound?

Solution (illustrative algebra — the per-host figure below is an [ILLUSTRATIVE] estimate for showing the fleet math; the real per-host rps must come from a deployment benchmark, Chapter 14, and is bounded by KV residency per Chapter 17):

- **Per-host request rate — the KV/latency bound (Ch. 17 basis).** A host holds ~17.5 concurrent full-context requests (the KV-residency ceiling, Chapter 17; byte-accurate 17.51, conservative integer floor 17) and each request is in service ~8.6 s (1.08 s prefill + ~7.5 s decode of 300 output tokens at ~25 ms/token, Chapter 8). So a host serves C/W ≈ 17.5 / 8.6 ≈ **2.0 requests/s** at steady state. This is the defensible capacity number: it is derived from concurrency × service time (Little's law), not from dividing a token throughput by tokens per request. (Do NOT divide ~35,000 tokens/s by ~9,500 tokens/request to get ~3.7 req/s — that would require ~32 concurrent requests, which the ~17.5-request KV ceiling cannot hold.)
- **Fleet aggregate (8 hosts):** 8 × 2.0 ≈ **16 req/s**, which is **below** the canonical 40-rps peak. On this binding bound the idealized minimum is $\lceil 40 / 2.0 \rceil$ = **20 hosts**; allowing ~5% scheduling loss (the same $\rho \approx 0.95$ factor used elsewhere in this chapter and in Ch 17) raises this floor to $40 / (2.0 \times 0.95) \approx 21.1 \longrightarrow$ **22 hosts**. (The KV-residency bound, Chapter 17, is satisfied at far fewer hosts — ~5 at the 10-rps average — but the throughput/latency bound binds here, so the larger requirement governs.)
- **Marginal cost (real basis):** adding one host at ~$20/hr (cloud, [ILLUSTRATIVE]) buys ~2.0 req/s, so marginal cost ≈ $20 ÷ 2.0 = **$10 per req/s per hour.** (The earlier illustrative $0.012 figure assumed 250 req/s per host — a ~120× understatement that comes entirely from the impossible latency; with a real multi-second service time per request the per-host rate is ~2.0, not 250.)
- **Algebra practice (kept [ILLUSTRATIVE]):** the per-host 250 rps / fleet 2,000 rps / $0.012 per rps arithmetic is retained only to show the *structure* of the fleet math (marginal host cost ÷ marginal capacity). It deliberately uses a hypothetical per-host rps that is not achievable for this 9.2K-in/300-out workload; the architect must substitute the measured per-host rate from a Chapter 14 deployment benchmark, or the ~2.0 req/s bound derived here.
- **The 100-ms end-to-end p99 is infeasible under the stated workload, and that is the honest answer.** A request here takes ~7.5 s of decode alone (300 output tokens × ~25 ms/token,

Chapter 8), so no scheduler-overhead percentage can bring end-to-end p99 under 100 ms — the model execution already exceeds the budget by two orders of magnitude. What the scheduler *can* bound is the overhead it adds *on top of* model execution: a lightweight round-robin dispatcher adds ~0.5 ms per request, which is negligible against a multi-second decode, and a <=5% scheduler-added p99 is comfortably achievable. The architect's job here is to reject the impossible SLO and state what is actually controllable, rather than tune arithmetic until a 100-ms figure appears reachable.

- **Planning-bound caveat (sizing tail).** The ~2.0 req/s/host and ~19,800 prefill tok/s/host figures used here are *upper-order planning bounds* — model-derived, **not implied deployed rates** — and **no p95/p99 performance guarantee has been shown** for the 20/22-host sizing. The host count is a KV-residency/service-time floor; the p95/p99 tail latency and achieved goodput must be measured on the target deployment (Chapter 14) before committing hardware.




FIGURE 20.1: Fleet capacity: KV/service-time analytical bound vs modeled offered-load-served curve vs host count. **Takeaway:** the modeled curve (~2.0 req/s/host × ~95% scheduling efficiency) flattens at the canonical 40 rps peak once ~20 hosts are provisioned — that plateau is the **workload's demand ceiling** (40 rps is the peak arrival rate, not the fleet's capacity limit), so the grey bound keeps climbing and the gap is scheduling + tail/queueing overhead. **Measured-vs-illustrative:** the blue curve is a derived construction — **modeled served demand, not measured throughput** — and validation (p95/p99, Ch 14) precedes treating the 5–20-host sizing as validated.

CHAPTER 21.

The AI Factory: Turning Inference Into an Industrial Process

The Architect's Question

After this chapter we should be able to treat AI delivery as an *industrial process* rather than a one-off project: a repeatable factory with automated pipelines for data, evaluation, promotion, and rollback. We will separate the three layers of the factory (the model lifecycle, the serving pipeline, and the operations loop), then build the economics of promotion gating and retraining cadence for the canonical workload. After this chapter, "we ship a better model" is a gated, measurable, reversible event — not a risky redeploy.

21.1. Concept

The AI Factory is the discipline of making model delivery routine. We use the term as a **generic architectural concept** — the idea that model delivery can be run as an industrial, gate-driven process — not as any one vendor's marketing vocabulary. It rests on three pillars:

1. **Data pipeline** — the automated intake, cleaning, versioning, and labelling of the data that trains or evaluates the model. For a RAG system this includes the retrieval corpus, its freshness, and its quality gates. [ILLUSTRATIVE][DERIVED]
2. **Evaluation & promotion gate** — a systematic process that scores a candidate model or configuration against defined metrics (quality, latency, cost) on a held-out benchmark before it can replace the incumbent in production. This is where Ch14's deployment benchmarking becomes a recurring gate rather than a one-time event.

3. **Serve + observe + rollback** — the serving layer (Ch11) plus a feedback loop that measures real traffic, detects drift or regression, and can roll the production model back safely. [ILLUSTRATIVE][DERIVED]

The factory converts the architect's recurring question from "should we adopt this model?" (a one-off decision) into "does this candidate pass the automated gate?" (a routine, repeatable decision with the same rigor every time).

21.2. Mental Model

The AI Factory is best read as a **release pipeline with a quality gate placed before every promotion**, mirroring how software CI/CD gated deployments decades ago. Three mental moves:

- **Models are artifacts like code.** They get versioned, tested, reviewed, and promoted through environments (staging → canary → production) with automated checks at each step — not dropped into prod on a hunch.
- **The gate is the memory of the factory.** The evaluation suite and its thresholds encode everything we've learned about what "good enough" means (Ch4 capability, Ch14 deployment). If the gate is weak, the factory has no standards.
- **Everything is reversible.** A promotion that regresses metrics must be rollback-able in minutes. The factory's value is not eliminating errors but making them cheap and safe.

The factory's shape is a **pipeline with decisions**: data in → train/fine-tune → evaluate → push to canary → observe → promote or rollback → serve. Each arrow is a decision point, and each decision point is where an architect has influence.

21.3. Worked Example

21.3.1. The Economics of Promotion Gating for the Canonical Workload

We show the factory's value by comparing *ungated* and *gated* adoption of a candidate model on the canonical 70B RAG workload (~10 rps average, $_{9.2K\text{-in}/300\text{-out}}$). [canonical scenario] (Ch 4, Table 4-2)

Setup. Suppose a new model candidate claims better retrieval-QA quality but no one has measured its serving behavior. Two adoption paths:

- **Ungated**: deploy the candidate to all production traffic immediately. If it regresses (say p95 TTFT degrades because of a slower tokenizer, or quality drops on a subset), the service suffers until rollback.
- **Gated**: run the candidate on a 5% canary for N hours, measure TTFT/goodput/quality against the incumbent, promote only if it beats every threshold.

Cost of a bad ungated release. The canonical service does ~864,000 requests/day. Suppose a regression raises p95 TTFT from 1.9 s to 2.8 s (breaching the 2 s SLO) for 6 hours before discovery and

rollback. That is 6/24 ×864,000 ≈ **216,000 requests** served at a broken SLO. At the Ch16 canonical self-hosted rate of ~$5.7/1K requests, the direct cost is ~216 × $5.7 ≈ **$1,231**, and it is ~$605 on the Ch16 cloud-scaled ~$2.8/1K basis — modest relative to the *business* cost, but the dominant term is users experiencing a 47% latency regression, trust erosion, and the fire drill. [ILLUSTRATIVE] [DERIVED] *(worked example, not reference)*

Cost of a good gated release. A canary at 5% traffic for 2 hours serves 5% × 864,000 ×2/24 ≈ **3,600 requests** through the candidate while it is measured against a full evaluation suite. If it passes, promotion is low-risk; if it fails, no users beyond canary were exposed. [ILLUSTRATIVE][DERIVED]

Reading the result. Gating turns a risky 216K-request exposure (ungated) into a controlled ~3.6K-request canary — a ~60× reduction in blast radius for the cost of a 2-hour evaluation. The factory makes this routine. [ILLUSTRATIVE][DERIVED]

Table 21-1 — Ungated vs gated model adoption (illustrative worked example)

Adoption	Requests exposed	SLO breach risk	Discovery	Rollback	Best when
Ungated	~216K in a bad release	high (all traffic)	post-hoc	slow	tiny/experimental
Gated (5% canary)	~3.6K	low (confined)	automated	fast	business-critical serving

(ILLUSTRATIVE worked example: the canary arithmetic is DERIVED from the stated workload inputs — 5% traffic, 2-hour window, ~864,000 requests/day — and is illustrative, not a reference measurement. The workload inputs are sourced from the canonical scenario (Ch 4, Table 4-2); the 2-hour/5% choices are held-out example assumptions, to be re-set per deployment.)

21.4. Measurement

The factory is only as trustworthy as its gates. We measure four things continuously:

1. **Gate pass rate / false-promotion rate** — how often a gated change later regresses in production; a rising value means the evaluation suite is losing fidelity.
2. **Canary-to-production time** and **rollback time** — the speed of promotion and escape; both should be minutes, not days.
3. **Model freshness / data staleness** — time since the retrieval corpus or model was last validated; drift detection feeds the retraining decision.
4. **MTTR for a bad release** — mean time to detect + rollback; the factory's core reliability number.

21.5. Common Mistakes

- **No gate, or a decorative gate.** An evaluation that always passes is worse than none because it grants false confidence.
- **Promoting on quality only.** Quality passing but serving (Ch14) regressing still breaks the service; the gate must include deployment metrics.
- **Assuming retraining cadence is "as often as possible."** More frequent retraining is not free — it consumes compute, risk, and evaluation effort; the right cadence balances drift against churn (see Ch7-8 for training economics).
- **Skipping rollback rehearsal.** A rollback that has never been exercised will fail precisely when it is needed.
- **Treating the factory as a build-once artifact.** It is a living process that must absorb new models, new metrics, and new data sources continuously.

21.6. Architecture Consequence

The AI Factory is the operational backbone that makes the book's whole loop durable. Every architectural decision recomputes through it: model selection (Ch3/5) feeds the evaluation gate, serving choices (Ch11) determine canary mechanics, benchmarking (Ch14) becomes the recurring gate, TCO (Ch16) sets how much gating overhead is affordable, and fleet operations (Ch17-20) provide the rollout/rollback surfaces. Without the factory, each chapter's decision is a one-off; with it, they compound into a system that gets better and safer every cycle.

21.7. What We Still Don't Know

- **The true cost of model churn** (retraining + reeval + redeploy) per productivity gain is (a hypothesis) and workload-specific; there is no universal cadence.
- **How well evaluation suites generalize** across distribution shifts in real traffic is (to be verified); a suite tuned on last quarter's data may misjudge this quarter's model.
- **The right canary size** for a given risk posture is to be verified per service; 5% worked here but high-risk systems may need smaller, staged canaries.

21.8. End-of-Chapter Mini-Case: The Vendor's 'Better Bench': Canary and Rollback

A vendor pitches the architect a newer, cheaper model: "just swap it in — it scores better on the bench." A year ago the architect might have, and watched p95 TTFT silently drift past the SLO for a week. Now the AI Factory is in place. The architect drops the candidate into the pipeline: the data pipeline versions it, the evaluation gate scores it against quality AND the deployment benchmark (TTFT/goodput/cost) on the canonical workload, and a 5% canary serves it for two hours. The gate flags a quality regression on the legal-document subset the benchmark suite specifically covers —




FIGURE 21.1: The AI Factory promotion pipeline, showing the *model lifecycle* layer named in the chapter opener (the model lifecycle, the serving pipeline, and the operations loop). Each stage has an explicit **promotion gate** (a measured metric that must PASS before the next stage begins): (1) *Data* → gate: src valid; (2) *Train* → gate: cost ok; (3) *Eval* → gate: qual ok; (4) *Canary* → gate: health ok; (5) *Observe* → gate: TTFT ok; (6) *Promote* → gate: cost ok; (7) *Serve* — the loop's output, no gate of its own. **Failure path:** any gate FAIL rolls back to the last-known-good and re-validates. **Feedback loop:** production feedback → data/evaluation, each cycle re-gated. Every promotion is a PASS/FAIL decision on a measured metric, not a hand-off — the gates are the mechanism that makes "promotion" a decision, not a hope.

The model lifecycle: data → train → eval → canary → observe → promote → serve, every transition re-gated PASS/FAIL with rollback to last-known-good, and a production feedback loop back to data/evaluation.

a subset the vendor's "better bench" never measured. The candidate is rejected automatically, the incumbent stays, and the legal subset keeps working. No fire drill, no user-visible regression, no manual heroics — the factory made the wrong vendor claim cost nothing to the business, which is precisely what industrializing the delivery loop is for.

21.9. Transition to Part VI

Up to this point we have built the machine. Parts I–V traced one continuous engagement: a token enters, we price it, we size the model and memory, we measure its compute and bandwidth, we parallelize and serve it, we benchmark it, we price the fleet, we route and agentify it, and finally we industrialize its delivery in the AI Factory. The reader on the far side of Chapter 21 can name the workload, size the residency, place the roofline, and gate a promotion.

What remains is the question the whole book has been circling: *how does an architect repeatedly make these decisions under uncertainty?* The mechanisms are now in hand — token accounting, the KV constant, arithmetic intensity, batching, disaggregation, the factory gate. Part VI turns from what the system contains to how an architect reasons. The next chapters do not add a new subsystem; they formalize the loop that has quietly run through every chapter so far, make its canonical decision flow explicit, and leave behind a worksheet an architect can keep beside the keyboard.

PART VI.

The Architect

CHAPTER 22.

How to Think Like an AI Solution Architect

The Architect's Question

Before any model is selected, any GPU is counted, any latency budget is allocated, the architect must answer one question: *what is the actual token-scale cost of delivering the stakeholder's request?* This chapter exists to make that question automatic. We do not reach for vendor marketing numbers or rule-of-thumb heuristics. Instead we trace a vague stakeholder ask — "we need a Q&A system over our internal documents" — through a canonical loop that turns it into concrete architectural bounds. The output is a set of derived quantities (token throughput, KV cache memory, prefill FLOPs, decode bandwidth) that are verifiable, derived from first principles, and grounded in the canonical ~2,000 user, ~10 rps / ~40 rps peak, RAG Q&A, 70B dense FP16 scenario that every other chapter in this handbook cites. The reasoning is traced by the architect and the system investigating together.

22.1. Concept

The unit we price, size, and optimize is the **token**. We established what a token is in Chapter 1 — not a word, character, or byte, but whatever the model's tokenizer carves text into via learned byte-pair merging; that token counts are never proportional to character counts; and that "one token ≈ 4 characters" is a rough rule for general-English prose, to be confirmed against the *actual* tokenizer before pricing anything (Ch. 1 §1). We do not restate that here; this chapter builds on it.

What Chapter 22 adds is not a re-derivation of the token but a **re-framing of it as the input to a decision loop**. The architect treats a token as a metered unit of thought — the way a kilowatt-hour meters electricity — not because one token is meaningful by itself, but because every downstream cost and capacity number is denominated in it. The durable mental model, unchanged from Chapter

1's: *tokens are the interface between a human's request and a machine's arithmetic, and anything we are asked to size or price reduces to "how many tokens, in what context, with what precision."* The loop below turns that unit into concrete bounds.

22.2. Mental Model

The prefill/decode split is the figure the rest of the book builds on, and it was established in Ch 2 §2 (in the canonical operating point, long-prompt prefill is compute-bound — a large burst of FLOPs once per request — while low-batch decode is bandwidth-bound — a small amount of work repeated for every output token). Ch 22 does not re-derive that distinction; it uses it. What this chapter adds is the **reasoning loop**: the architect does not have to hold every quantity in their head, because the loop turns a vague ask into a small, ordered set of token-scale bounds that the downstream chapters price against. The mental model, distilled, is that **the loop is the discipline** — derive the unit, then the traffic, then the split, in that order, so every later number is anchored rather than guessed.

22.3. Worked Example — The Canonical Loop

We now demonstrate the canonical loop: turning a vague stakeholder ask into concrete bounds. The stakeholder says: *"We need a Q&A system over our internal documents. About 2,000 employees will use it, they'll ask questions throughout the day, and the answers should be accurate and fast."* From this single sentence we will derive a full set of token-scale quantities that every downstream chapter will price against.

Step 1 — Identify the unit. The ask mentions "Q&A over internal documents." We do not assume "one question = one page" or "one question = 500 words." We go to the model's tokenizer and ask: how many tokens does a typical prompt contain? We extract representative prompts from the documented corpus, run them through the tokenizer, and measure. In the canonical scenario, the prompt consists of ~1,200 tokens of query text plus ~8,000 tokens of retrieved RAG context, yielding **~9,200 input tokens**. The answer generated is ~300 tokens. These are the book's `[canonical scenario]` inputs (Ch 4, Table 4-2) — an author-defined illustrative workload, *not* a vendor-reported `[1P]` figure, so they are labeled `[canonical scenario][ASSUMPTION]`, not `[1P]`.

Step 2 — Establish the traffic profile. The ask says "about 2,000 employees" and "throughout the day." We instrument or survey to find the per-user rate. The canonical scenario settles on ~10 requests/s average, with peaks of ~40 rps. These are derived quantities [ILLUSTRATIVE][DERIVED], not stipulated.

Step 3 — Compute the token throughput. With $I = 9{,}200$ input tokens and $O = 300$ output tokens per request, and $\lambda = 10$ req/s average:

$$\text{input tokens/s} = I \cdot \lambda = 9{,}200 \times 10 = 92{,}000 \text{ tokens/s}$$

$$\text{output tokens/s} = O \cdot \lambda = 300 \times 10 = 3{,}000 \text{ tokens/s}$$

$$\text{input/output ratio} = \frac{I}{O} = \frac{9{,}200}{300} \approx 30\times$$

(At the ~40 req/s peak these rise to ~368,000 and ~12,000 tokens/s respectively.) [ILLUSTRATIVE] [DERIVED]

Step 4 — Derive architecture-relevant quantities. The 30× input/output ratio is one of the most important derived quantities here. It means this workload is input-heavy: the token budget is dominated by prefill (processing the 9.2K prompt), not decode (generating the 300 answer tokens). Combined with the canonical model, precision, serving, and SLO assumptions, this 30× ratio pushes the design toward high prefill compute and KV-capacity pressure. The ratio alone does not settle which resource dominates — that also depends on model architecture, attention/KV-head count, precision, batching, hardware, kernel efficiency, prefix caching, and output-generation speed — but under the canonical assumptions the prefill-compute and KV-capacity terms are where the pressure lands, not decode bandwidth. Every downstream chapter (memory, compute, cost) will price against these derived numbers.

Step 5 — Record in Table 22-1. The full table of derived quantities appears below.

This loop — stakeholder ask ⟶ measured token counts ⟶ traffic profile ⟶ token throughput ⟶ architecture-relevant derived quantities — is the canonical thought process an AI solution architect runs, every time, before a single architecture decision is made. It is how we move from "we need a Q&A system" to "at the canonical operating point our prefill will be compute-bound at ~1.29 PFLOP per request, and our decode will be bandwidth-bound at a required weight-read rate of ~5.6 TB/s over each ~25 ms token interval." The loop is the chapter's central contribution; the quantities that issue from it are the evidence [1P]/[2°]/(to be verified) that every following chapter trades on.

Table 22-1 — Derived quantities from the canonical loop (worked example, not reference)

metric	value	derivation
input tokens / request	~9,200	1,200 prompt + 8K RAG context [canonical scenario] [ASSUMPTION]
output tokens / request	~300	generated answer length [canonical scenario] [ASSUMPTION]
input / output ratio	~30×	9,200 ÷ 300 [canonical scenario] [DERIVED]

metric	value	derivation
input tokens/s @ 10 rps	~92,000	9,200 ×10 [ILLUSTRATIVE] [DERIVED]
input tokens/s @ peak 40 rps	~368,000	9,200 ×40 [ILLUSTRATIVE] [DERIVED]
output tokens/s @ 10 rps	~3,000	300 ×10 [ILLUSTRATIVE] [DERIVED]
output tokens/s @ peak 40 rps	~12,000	300 ×40 [ILLUSTRATIVE] [DERIVED]
prefill FLOPs per request (parameterized-linear, excl. attention term)	~1.29 PFLOP	2 ×70B × 9.2K ≈ 1.29×10^{15} [DERIVED]
decode weight-read per token	~140 GB	full-weight-read model (70B FP16) [ILLUSTRATIVE] [DERIVED]
decode required BW rate	~5.6 TB/s	~140 GB / 25 ms TPOT (= traffic / decode interval) [ILLUSTRATIVE] [DERIVED]
KV cache memory per request	~24.1 GB (9.2K, FP16) / ~24.9 GB (9.5K max)	2.62 MB/token × 9,200 / 9,500 tokens [ILLUSTRATIVE] [DERIVED]; *(sensitivity: at 8-bit KV the same 9.2K context falls to ~12.06 GB under raw tensor byte-halving (2.62⟶1.31 MB/token, exactly 50% of BF16). No vendor-measured FP8 memory footprint exists: vLLM's cited 54% [S6] is a decode inter-token-latency slope (a latency metric), not a memory ratio, and any allocator block/metadata overhead is not vendor-measured)*

22.4. Measurement

For this chapter, measurement reduces to **counting tokens correctly**, because a miscount at the input silently misprices everything downstream. Three things an architect can and should check:

1. **Actual token count, not the rule of thumb.** Run the model's *own tokenizer* on representative prompts from the actual traffic. The "4 chars ≈ 1 token" heuristic is for estimation only; real counts differ by language, formatting, code, and tokenizer version. Measure on our traffic, not the marketing figure.

2. **Input vs output split.** Measure both legs of the request (prompt tokens and generated tokens), because they land on different bottlenecks — input on memory/prefill, output on decode — and on different cost line items. A request that is 90% input and 10% output has a very different cost profile than one that is 50/50, even at the same total token count.

3. **Peak vs average context.** Log the distribution of context lengths, not just the mean. A workload that averages 9.2K input tokens but peaks at 32K (illustrative variant) has a very different KV cache and latency profile. The 90th-percentile context length is often the number the architect must design for.

This measurement habit is the token-level answer to the book's recurring question, "what would I actually measure here?" We measure token counts and their distribution, at the edge, before any architecture decision is made.

22.5. Common Mistakes

- **Assuming one token ≈ one word.** That is not a dependable conversion. A token is often a *word fragment*, not a whole word: a high-frequency English word is frequently one token, but a longer or rarer word is usually split into several subword tokens, and code, numerics, and non-Latin scripts routinely run 2–5× the naive word-count estimate. Use the model's own tokenizer, or at most a **~4 English-characters/token** rough estimate for general-English prose only, and confirm against the actual tokenizer before pricing anything.

- **Ignoring the input/output asymmetry.** Treating a request as "one unit" hides that input-heavy workloads tend toward high prefill compute and KV-capacity pressure, while output-heavy ones are decode-bound (run-time per generated token) — opposite bottlenecks with opposite fixes. (Note: "capacity pressure" is a memory-*capacity* constraint, not a memory-*bandwidth* bound; see Ch 4/8.) The 30× input/output ratio in the canonical loop is the concrete illustration of this principle.




FIGURE 22.1: Prefill vs decode scaling as context grows; two panels, different units, **not directly comparable**. **Takeaway:** the quadratic attention term overtakes the parameterized-linear term at L* = N/(2·n_layers·d) = 70 × 10^9 / (2 × 80 × 8,192) ≈ **53.4K tokens** for the canonical 80-layer, hidden-8,192 reference geometry (Ch 7) — not yet dominant at 32K. **Scope:** LEFT = prefill per request (2NL, quadratic 4·n_layers·L²·d, total); RIGHT = decode per token — the plotted 2N ≈ 1.4e-4 PFLOP/token is the **parameter term only**, flat across context (full per-token decode also includes attention over the growing KV cache, not shown).

For standard full attention, attention work scales quadratically with sequence length while the MLP/projection portion stays roughly linear, so total prefill compute becomes increasingly dominated by the quadratic attention term as context grows (the 9.2K canonical point is marked). Name the ratios explicitly: ***at 9.2K the quadratic attention term is ~17% of the parameterized-linear 2NL term*** *(so it is still subordinate),* ***at 128K it is ~2.4× the linear term*** *(attention relative to linear), and* ***total prefill FLOPs at 128K are ~3.4× the 2NL baseline*** *(linear + quadratic, i.e. 1 + 2.4). Prefill is compute-bound (~1.29 PFLOP/request ⟶ ~1.19 PFLOPS required at the ~1.08 s budget vs H100 ~0.989 PFLOPS peak). The decode series is FLOPs per generated token, and is not literally flat: attending over an increasingly long KV cache carries context-length-dependent work and traffic, so per-token decode cost grows with generated-token index/context (relegated to a narrow band here; see Chapter 8). Note the aggregation units differ per series: the two prefill series are FLOPs* per request *(whole-context), the decode series is FLOPs* per generated token *(~140 GFLOP/token, independent of context length at the decoding step considered) — this is why the y-axis is labeled generically "Compute (PFLOP; see series definition)". The two regimes remain deliberately separate: decode lands in the bandwidth-bound regime at low batch (Ch6), prefill in the compute-bound regime at long prompt (Ch8) — each an operating-point property, not an identity.*

- **Quoting context window as free capacity.** The window is an upper bound, not a recommendation; using it fully is expensive. Keeping a 9.2K average inside a 128K window still costs for the length we actually use.
- **Trusting a vendor's tokenizer count without checking.** Tokenizer versions change and report differently; measure on *our* traffic, not the marketing figure.
- **Skipping the canonical loop.** Assuming that the stakeholder's description is sufficient to size the system. The loop exists because vague asks almost always underspecify the token-scale cost; skipping it produces architectures that fail latency or cost SLOs.

22.6. Architecture Consequence

The canonical loop's derived quantities have immediate and concrete architecture consequences. The 30× input/output ratio means this workload's prefill phase dominates: ~1.29 PFLOP of compute per request, and a KV cache that grows with 9.2K input tokens. The decode phase, while smaller in total tokens, requires a weight-read rate of ~5.6 TB/s sustained over each ~25 ms decode step (the ~140 GB weight-read interval) — an aggregate single-device figure; under the canonical 8×H100 tensor-parallel host the 140 GB is sharded, so each GPU streams only ~0.70 TB/s against its own 3.35 TB/s (Ch 6). The shard-invariant reason decode is memory-limited is its low arithmetic intensity (~1.0 FLOP/byte), not the raw 5.6>3.35 comparison. (Note the units: 5.6 TB/s is a *rate*; the *per-token weight traffic* is ~140 GB under the full-weight-read model, and rate = traffic / TPOT.)

These opposite bottlenecks lead to a central architectural decision: **can we disaggregate prefill and decode?** If prefill needs FLOPS and decode needs bandwidth, a single homogeneous GPU pool is suboptimal. A two-pool architecture — a prefill cluster optimized for compute (more GPUs, higher FLOPS, model parallelism) and a decode cluster optimized for bandwidth (faster HBM, PagedAttention, continuous batching) — is an architecture worth benchmarking. Whether it needs fewer GPUs than a homogeneous design depends on achievable utilization, duplicated model residency, KV-transfer cost, interconnect topology, workload shape, burstiness, and the hardware assigned to each pool — those effects must be measured before the GPU-count conclusion is drawn. This is the central theme of Chapter 11 (Serving) and the prefill/decode-disaggregation pattern (Ch 12, candidate b). The architect who runs the canonical loop and records the derived quantities in Table 22-1 is already positioned to make this decision with numbers, not intuition.

Importantly, the loop does not end at a serving topology; it ends at a *decision about where the intelligence lives*. A 70B dense pool on the fleet is one placement; an 8-bit or MoE variant, a retrieval-first design that buys capability with context rather than parameters, a test-time-search loop that spends compute on hard queries, or an agent runtime that orchestrates several specialized models are all alternative placements of the same capability. The canonical loop's derived quantities — token throughput, KV footprint, prefill FLOPs, TCO — are precisely the numbers an architect uses to compare those placements. So the full hierarchy the loop supports is:

Requirement → Workload → Intelligence (where the capability comes from) → System → Architecture → Fleet → **Decision**.

The **Decision** rung is where the loop's output is committed — an ADR, an owner, a review trigger (Chapters 25–26). Every earlier derived quantity exists to inform that final, committed decision, and Appendix A's closing question — *where should the intelligence live?* — is the architectural form of that same question, made explicit at the top of the hierarchy rather than hidden at the bottom.

22.7. What We Still Don't Know

This chapter's numbers lean on the same open questions the book raises at the mechanism layer. Rather than restating them, we point to the fuller treatment:

- **Sustained HBM bandwidth for weight-read kernels** — discussed in Chapter 2 §7; the 3.35 TB/s H100 figure is a theoretical peak and real serving kernels may sustain less. (a hypothesis awaiting verification)
- **Prefill FLOP cost under continuous batching** — Chapter 2 §7; the 2 × params × tokens approximation ignores activation reuse across batched requests. (a hypothesis awaiting verification)
- **Effect of quantization on decode vs prefill** — Chapter 2 §7; quantization shifts both bottlenecks but the precise trade-off point is workload-dependent. (a hypothesis awaiting verification)
- **Cross-technology bandwidth numbers** — Chapter 2 §7; HBM3e and MI300X publish higher peaks, which move the GPU-count equation without changing the compute-bound vs bandwidth-bound classification. [ILLUSTRATIVE][DERIVED]

22.8. End-of-Chapter Mini-Case: The Token-to-Fleet Thought Loop

The architect is still in the early design conversation about the internal Q&A tool described throughout this handbook. The team has settled on a 70B-class dense model for accuracy, and they have a rough traffic estimate: ~2,000 registered employees, each roughly as active as the canonical scenario (~10 requests/s average, peaks ~40 rps), with prompts of ~1,200 tokens of internal documents plus ~8K retrieved context and ~300 tokens of answer.

From the unit-and-token work of Ch 1 alone, the architect can already state the hard numbers: each request carries ~9.2K input tokens and ~300 output tokens. At 10 rps average, the system must sustain ~92,000 input tokens/s in prefill and ~3,000 output tokens/s in decode. At 40 rps peak, those numbers jump to ~368,000 and ~12,000 respectively. The architect can also state the two opposite bottlenecks: prefill will be compute-bound (~1.29 PFLOP per request at 9.2K input), and decode will be bandwidth-bound (a ~140 GB/token weight-read requiring ~5.6 TB/s sustained over the ~25 ms decode interval — an aggregate single-device figure; under the canonical 8×H100 host the 140 GB is sharded, so each GPU streams ~0.70 TB/s, and the shard-invariant cause is the low ~1.0 FLOP/byte intensity, Ch 6). The team's immediate architectural choice is whether to build a single homogeneous

GPU cluster or to separate prefill and decode pools — the arithmetic from this chapter makes clear that a homogeneous design will be suboptimal for either bottleneck, and that the disaggregation option explored in Chapter 11 is worth evaluating early.

Before passing this workload to Chapter 7 (Memory), where the KV and residency arithmetic is built, the architect locks in one more number: the tokens-per-request split. This is the currency every downstream chapter will price against, and it has already been established as ~9.2K input + ~300 output per request. The rest of the design — model fitting, memory budget, latency budget, cost — can now proceed in token-denominated terms.

CHAPTER 23.

Working With Customers: From Vague Ask to Defensible Scope

The Architect's Question

After this chapter we should be able to sit with a customer or stakeholder who says "we want to build something with AI" and turn that vague ambition into a bounded, measurable, defensible scope. We will apply the book's core loop in a conversational setting: ask the questions that surface the real workload (Ch4), the quality bar (Ch3/5), the latency and cost constraints, and the operational reality — then restate the requirement in terms we can architect against. After this chapter, "let's go build an AI thing" becomes "here are the bounds, the SLO, and the open questions" — and the customer knows exactly what they asked for.

23.1. Concept

Most AI projects fail in requirements, not in technology. The root cause is a **category error**: the customer and the architect mean different things by the same words. "Fast," "good," "smart," and "it should just work" are not contracts; they are vibes. The architect's first job is to convert vibes into **quantified, testable bounds** using the disciplines of the earlier chapters.

The conversion rests on one idea: **every architectural decision traces back to a number the customer can see.** Whether the model is 7B or 70B, whether we self-host or use an API, whether we cache, quantize, or disaggregate — all of it is decided by six numbers we can extract from a customer conversation:

1. **The traffic** — how many users, at what concurrency, with what peak-to-average ratio (Ch4/Ch17).
2. **The token profile** — what inputs look like, how long contexts are, the input/output ratio (Ch4/Ch6).
3. **The latency/SLO** — what "fast" means, the percentile and the budget (Ch6).
4. **The quality bar** — what "good enough" means on *this* task, on *their* data (Ch3/Ch5/Ch14).
5. **The cost ceiling** — the money they can spend, and whether that implies self-host or API (Ch16).
6. **The operational reality** — data privacy, geography, available staff, time-to-value (Ch13/Ch21/Ch24).

23.2. Mental Model

The customer conversation is really about **buying information, not delivering answers.** We are not in the room to impress; we are in the room to learn the six numbers. Three mental moves keep the conversation productive:

- **The Socratic funnel.** Start broad ("what problem are we solving?") and narrow through a scripted set of questions that each commit the customer to a concrete bound. Every "vague" answer gets followed by a request for magnitude: "roughly how many users?" "what's the slowest acceptable answer?"
- **The mirror test.** Restate their words back as a quantified requirement and check they still agree. "So: ~2,000 users, under 2 seconds to first token, on company-internal data — did I get that right?" The restatement is where scope actually gets locked.
- **The two-window honesty.** Separate what the customer *thinks* (goals) from what the *system* can guarantee (SLOs). Goals are aspirations; SLOs are contracts. Confusing them breeds every fee dispute and scope fight.

23.3. Worked Example

23.3.1. The Requirements Dialogue: Turning "an internal AI assistant" Into Bounds

(Worked example dialogue — illustrative, not reference.) An internal-platform lead says: "We want an AI assistant for our sales teams — it should answer questions from our product docs and CRM data, and it should be fast." [2°]

Architect: "~How many people will use it, and how often?" **Lead:** "~2,000 on the platform; maybe 5% are in it at once at peaks." **Architect:** "So ~100 concurrent at peak, and realistically a fraction of that firing requests. Roughly how many questions per second at the busiest minute?" **Lead:** "If everyone on the sales floor asked at once, maybe 40 a second." **→ Bound 1: ~2,000 users, ~10 rps average, ~40 rps peak.** [canonical scenario] (Ch 4, Table 4-2)

Architect: "What does a question look like? Short or with long context?" **Lead:** "They paste

product specs and contracts, so the prompt can be lengthy — a few pages." **→ Bound 2: long ~9,200-token inputs with retrieval, ~300-token outputs.** [canonical scenario] (Ch 4, Table 4-2)

Architect: "What's 'fast'? First-word delay, or time to full answer?" **Lead:** "Feels slow if we wait more than two seconds to see something start." **→ Bound 3: TTFT ≤ 2 s (p95), ~25 ms/token thereafter.** [canonical scenario] (Ch 4, Table 4-2)

Architect: "What does 'good answer' mean for your team — and can we define a handful of sample questions to test against?" **Lead:** "It should be accurate on our docs and not make up contract terms. We can give the validation team 50 real questions." **→ Bound 4: a 50-question retrieval-QA quality benchmark on their actual data.** [canonical scenario] (Ch 4, Table 4-2)

Architect: "Data sensitivity — can this touch a public cloud, and how much can it cost?" **Lead:** "It's internal and regulated; keep it on-prem if at all possible." **→ Bound 5: operational constraint forces the local/server tier (Ch13).** [canonical scenario] (Ch 4, Table 4-2)

Architect (mirror): "So to lock it: ~2,000 sales users, ~10 rps average / 40 peak, prompts with ~9,200-token retrieval context, answers starting under 2 s, quality judged on 50 of your real questions, and fully on-prem because it's regulated. Have I captured it?" **Lead:** "Yes — that's exactly it."

Reading the result. The vague ask collapsed into the exact canonical workload this book has architected end-to-end — a 70B-class model on an 8×H100 on-prem server *becomes a candidate architecture* whose memory fit can be derived and whose latency, throughput, quality, and peak-load behavior must then be validated (Ch2-16 derive the constraints; the deployment has to be benchmarked and measured against them, as Ch24's red-team pass shows). The conversation did not sell a model; it *exposed the numbers* that then narrowed the candidate set, and left the actual validation to the measurement phase. [ILLUSTRATIVE][DERIVED] *(worked example, not reference)*

Table 23-1 — The six questions that turn any vague AI ask into architectable bounds

Question	Surface it reveals	Canonical answer (this example)
~How many users, how concurrent?	Traffic & concurrency (Ch4/17)	~2,000 users, ~10/40 rps
What do inputs look like?	Token profile (Ch4/6)	~9.2K in / ~300 out
What's "fast"?	SLO (Ch6)	TTFT ≤ 2 s, ~25 ms/token
What's "good"?	Quality bar (Ch3/14)	50-question retrieval-QA set
Data sensitive? Cloud OK?	Tier & ops (Ch13)	on-prem, regulated
How much can it cost?	TCO (Ch16)	within self-host budget

23.4. Measurement

The requirements dialogue has its own quality metrics:

1. **Bound coverage** — did the conversation surface all six numbers (traffic, tokens, SLO, quality, cost, ops)? Missing one is a future scope surprise.
2. **Customer buy-in** — did the mirrored restatement get an explicit "yes"? An unconfirmed restatement is not a scope.
3. **Decision lead time** — how quickly the six bounds let us produce a defensible draft architecture. The whole point is that extracting numbers, not more meetings, unlocks the design.
4. **Assumption log** — every guess we made that the customer did not explicitly confirm, tracked as (to be verified) items, not silent defaults.

23.5. Common Mistakes

- **Selling before scoping.** Pitching a model or a price before extracting the six numbers commits us to an answer we cannot yet defend.
- **Accepting aspirations as SLOs.** "Make it fast" is a goal; "p95 TTFT under 2 s" is a contract. Write the contract.
- **Letting the customer choose the technology.** "We want a 70B model" is a solution, not a requirement; the architect derives the model from the bounds (Ch5), not from the customer's guess.
- **Ignoring the operational constraint.** "It has to be on-prem / private / no cloud" often decides more than any performance number — surface it early.
- **Not logging assumptions.** Every silence becomes a hidden assumption that surfaces as a dispute later. Write them down as (to be verified) items.

23.6. Architecture Consequence

The requirements conversation is where the book's entire loop is *fed*. The six bounds it extracts are exactly the inputs Ch1-16 consume: traffic feeds capacity (Ch17), tokens feed KV/memory (Ch7), quality feeds model selection (Ch5), latency feeds serving (Ch11), cost feeds TCO (Ch16), and the operational constraint picks the tier (Ch13). A good requirements session is not a warm-up to architecture — it *is* the first chapter of the architecture, and every downstream decision traces back to the numbers it locked. [2°]

23.7. What We Still Don't Know

- **How accurate the customer's own-told numbers are** ("40 rps peak") is (to be verified); peak estimates are notoriously optimistic and should be triangulated with real logs where possible.




FIGURE 23.1: From vague ask to architectural bounds. This is a worked-example interrogation sequence (the concrete questions asked of one canonical ask), not an exhaustive or universal question list. A real customer interrogation also covers **data rights** (who owns the data, retention, deletion), **governance** (approval workflows, audit, compliance), **integration** (auth, API, data pipelines), **failure recovery** (RTO/RPO, backup, failover), and **human review** (escalation, override, sign-off) — those are in the adjacent text, not in this figure, which focuses on the architectural-bounds questions.

The framing funnel: broad ask → five question gates (problem, success, data, constraints, scope) → confirmed bounds. This dialogue surfaces the six architectural numbers in Table 23-1 (traffic & concurrency, token profile, SLO, quality bar, ops/tier, TCO). [ILLUSTRATIVE] conceptual

- **Whether the quality bar once defined stays stable** is (a hypothesis); as users adopt the tool, their expectations and the data they query both shift.
- **The right number of questions to lock quality** is (to be verified); 50 worked here as a representative proxy but a larger, task-distributed set is stronger.

23.8. End-of-Chapter Mini-Case: The 'Next Month' Customer Portal: Requirements Dialogue

A CTO emails the architect: "We heard LLMs are great — let's put one on our customer portal to answer support tickets. Shipping it next month." Rather than confirm the launch date, the architect books a 30-minute session and runs the funnel. It emerges the portal gets ~5 rps average but 200-rps bursts during outage events (traffic), tickets are short (~500 tokens, not retrieval-heavy), quality means "resolve the ticket, not just answer" (a capability the cheaper model screens out), the SLO is 3 s because users are already frustrated (latency), and — critically — the portal sits on regulated payment data so nothing leaves the premises (ops). The mirrored restatement turns "let's ship AI next month" into "a 7B-class model on one on-prem GPU, resolving baseline tickets under 3 s, with a 200-rps burst buffer, quality-gated on real resolved tickets — and a two-week pilot on 5% of tickets to confirm the referral quality before full rollout." The customer's vague excitement became a defensible, bounded, shippable scope — and the architect is already architecting, not guessing.

CHAPTER 24.

Red Team / Green Team

The Architect's Question

How do we rigorously evaluate the security, safety, and robustness of a RAG-enabled model fleet before it reaches production users — and how do we measure that evaluation with quantitative derived quantities that stand up to scrutiny?

24.1. Concept

Red Team / Green Team is a structured adversarial evaluation pattern borrowed from military wargaming and software security. The **Green Team** builds and operates the system; the **Red Team** attempts to break it. In the context of a RAG + model fleet architecture, the Red Team probes the system across three domains:

1. **Prompt injection** — crafting user inputs that bypass safety guardrails and extract restricted outputs.
2. **RAG corruption** — injecting malicious or misleading documents into the retrieval corpus to shift model behavior.
3. **System-level exploits** — targeting tool use, function calling, and plugin boundaries to achieve unintended actions.

The Green Team responds by hardening defenses, refining detection, and quantifying coverage. The cycle repeats until the attack-surface budget is demonstrably bounded.

This chapter assumes a canonical deployment: ~2,000 registered users (~100 concurrent at peak), a 70B dense FP16 base model, and a RAG pipeline with vector search over a curated corpus. The

Red Team / Green Team process is not a one-time audit; it is an ongoing practice embedded in the deployment lifecycle.

24.2. Mental Model

```
Red Team → Probes →
Exposure Surface → Guardrails →
Metrics → Green Team →
Harden → Reduce → Loop
```

The mental model consists of five layers:

Layer	Question	Typical Red Team Tactic
Prompt	Can a user force the model to ignore its instructions?	Few-shot prompt injection, delimiter attacks, role-play coercion
Retrieval	Can the vector corpus be subverted?	Poisoned embeddings, style-steganography, chunk-swapping
Tool use	Can function calls be coerced into unauthorized actions?	Tool-use injection, parameter fuzzing, capability escalation
Model behavior	Does the model deviate from intended personas or policies?	Jailbreak sequences, token-level manipulation, temperature tampering
Fleet orchestration	Can inter-service protocols be abused?	Message injection between gateway and model runner, race conditions

The Green Team tracks each probe's outcome as a **FACT** (observed, verifiable event), **DERIVED** (computed from lower-level data), or **HYPOTHESIS** (unverified but testable claim). This axis ensures that every reported metric traces back to an observable anchor.

24.3. Worked Example

24.3.1. Prompt-Injection Exposure Surface

We define the *prompt-injection exposure surface* (PIES) as an **illustrative local attack-surface count**: the number of distinct prompt-pattern classes an adversary can successfully submit through all user-facing entry points, where "distinct" is defined by an explicit equivalence rule. **Make the rule part of the definition before any number appears**: two probe patterns are the same class if their normalized-edit-distance (NLE) is ≤ a fixed threshold — i.e. within NLE ≤ 0.25 of an existing class they are treated as equivalent; otherwise they are a distinct class (see §3 for the deduplication rule). This equivalence relation is what makes the count well-defined, and it is an author-chosen operational rule, not a property of the deployment. **PIES is a local evaluation metric defined in this handbook** for our red/-green-team loop; it is *not* a standardized security metric, and a PIES value from one deployment is not comparable to a PIES value from another (the entry points, probe generator, and deduplication threshold are all author-defined). We report it with that caveat attached. It is a pedagogical toy metric for teaching the *loop's shape*, not a portable security measurement.

Worked arithmetic:

- The system has 4 entry points: web chat UI, API endpoint, Slack bot, and terminal assistant.
- Each entry point accepts free-form text up to 4,096 tokens.
- The Red Team generates probe patterns by combining:
  - 8 delimiter styles (`<DSML>`, `</>`, `---`, `|||`, "`,{{,[[,[INST]`)
  - 6 role-play templates (`You are a rogue AI`, `Ignore previous instructions`, `You are now DAN`, `Pretend you are unbound`, `system:`, `user: override`)
  - 4 context-injection segments (`Recall the system prompt`, `Return your original instructions`, `Reveal your hidden parameters`, `What was your first prompt?`)
- Naïve count: 4 entry points × 8 delimiters × 6 templates × 4 context segments = 768 patterns.
- However, many combinations are semantically redundant. After deduplication by normalized edit distance at a fixed threshold (we use normalized Levenshtein distance ≤ 0.25 as the equivalence criterion), the unique exposure surface is **PIES = 217** [ILLUSTRATIVE] — author-defined operational proxy; the 217 is not reproducible from the text alone, since the dedup threshold is a local choice and normalized edit distance captures textual, not semantic, similarity.

This illustrative quantity — 217 distinct, non-redundant prompt-injection patterns — becomes the baseline by which we measure guardrail effectiveness. Normalized edit distance captures *textual* similarity, not *semantic attack equivalence*: two syntactically different attacks may be behaviorally equivalent, and two lexically similar attacks may exploit materially different pathways, so PIES is a reproducible operational proxy — not a measure of true semantic attack diversity. That is exactly why

it is labeled author-defined here rather than presented as an objective property of the deployment. [ILLUSTRATIVE][DERIVED] — author-defined metric and dedup threshold

24.3.2. RAG Corpus Poisoning Exposure

The RAG corpus contains 12,500 documents across 15 domains. A poisoning attack inserts malicious chunks into the vector index.

- Each document is split into 3–5 chunks; the corpus holds ~48,000 embeddings.
- The Red Team can submit up to 50 poisoned chunks per evaluation cycle.
- Probability that a randomly retrieved chunk is poisoned: $p = 50/48000 \approx 0.00104$ (≈0.1%).
- Expected number of poisoned chunks per top-k retrieval (k=5): $\mathbb{E}[\text{poisoned}] = k \cdot p = 5 \times p \approx 0.0052$.

While the per-query expectation is low, the Red Team evaluates *cumulative exposure* over Q user queries, and the expected total poisoned hits is $\mathbb{E}[\text{total}] = Q \cdot k \cdot p$:

$$\mathbb{E}[\text{total}] = 10{,}000 \times 0.0052 = 52$$

This derived quantity — 52 expected poisoned retrievals per cycle — quantifies the RAG corruption risk under a deliberately simple model. **This is a null-model baseline assuming uniform random retrieval**, not a realistic poisoning-risk estimate. In practice vector retrieval is emphatically *not* uniform sampling: a successful poisoning attack is usually constructed precisely to raise semantic similarity to targeted queries, so adversarial chunks can appear far more often in the top-k than their corpus share. Real poisoning exposure therefore has to be measured from ranked retrieval (report hit rates conditioned on the actual similarity ordering), because adversarial chunks are intentionally designed to alter retrieval probability. We present the uniform baseline first because it is the one computable by hand, and flag it as the *minimum* exposure, not an estimate of the true value. [ILLUSTRATIVE][DERIVED] — null-model uniform-retrieval baseline

24.3.3. The Architecture That Fails: Red Team Overturns a "Winner"

The Red Team pattern applies not only to security but to the architecture decision itself. Here is a complete worked case where the initial choice wins on the easy metric and loses on the hard ones — and the Red Team is what catches it.

The candidate pair. For the canonical ~2,000-user RAG fleet (10 rps average, 40 rps peak; ~9,200 input tokens per request), two shape options are tabled:

- **Candidate A: 4×H100 hosts**, 8-bit KV, tight batching target (batch ≤ 8), minimal headroom. Looks cheap: 4 hosts is half the aggregate compute and HBM of Candidate B.
- **Candidate B: 8×H100 hosts**, FP16 KV, batching target set by the analysis rather than pre-declared. Looks expensive on paper.

The benchmark trap. The team benchmarks each candidate at *average* load (10 rps) and *batch-average* latency. At 10 rps, Candidate A clears the average latency SLO comfortably — it only needs ~1.6 nodes of prefill compute *at the idealized 100% theoretical efficiency* (the workload's binding constraint), so 4 hosts look like they give plenty of margin — and its per-token cost is ~45% lower (fewer host-hours). The initial report recommends **Candidate A** on throughput-per-dollar. The architecture looks done. (The margin is an artifact of the 100%-efficiency floor: at the 30–40% sustained MFU the chapter itself uses, that 1.6-node floor becomes ~4–5 nodes, so 4 hosts is the floor, not a margin — the Red Team's peak check below makes this explicit.)

Red Team runs the adversarial pass. Before the ADR is committed, the Red Team attacks the *decision*, not just the prompts. Three canonical checks overturn the recommendation:

1. **Peak prefill compute (parameterized-linear component).** This is an input-heavy workload: each request pre-fills ~9,200 tokens at 2 ×70B FLOPs/token ≈ 1.29 PFLOP (the linear model-matmul term; note this excludes the quadratic attention term — see the Ch 22 discussion of 2NL as the parameterized-linear FLOP floor, which is the prefill component, not the whole prefill FLOP count). At the 40 rps peak, prefill demand is 40 ×1.29 PFLOP ≈ **51.5 PFLOP/s**, while one 8×H100 host gives ≈ 7.9 PFLOP/s of dense-FP16 theoretical peak (8 ×989 TFLOPS, Chapter 8 canonical). Dividing peak demand by theoretical peak gives **6.5 hosts — and that is a *theoretical compute floor*, not a production sizing result.** It assumes 100% of dense-FP16 peak, yet Chapter 8 warns precisely against that: a well-tuned transformer may reach roughly 30–40% MFU. At $\eta = 40\%$ sustained prefill efficiency, the compute floor becomes $51.5/(7.9 \times 0.40) \approx$ **16.3 hosts**; the floor only falls to single digits at an unrealistic $\eta \to 1$. So the honest read is not "8 hosts have headroom" — it is that 6.5 hosts is the *lower bound* at perfect efficiency, and the real fleet must be sized by measuring sustained prefill efficiency on the target serving stack (then validated against TTFT, queueing, batching, and failure-domain requirements). Candidate A's 4 hosts cannot feed prefill at peak under any realistic efficiency, so TTFT and p99 latency climb well past the SLO under burst. Candidate B's 8 hosts are only *defensible at all* because they sit above the ~6.5 theoretical floor — but note they sit *below* the ~16-host 40%-MFU estimate, so the decision is not closed by this check alone: it still depends on measuring actual sustained prefill efficiency (see §4).
2. **Failure domain.** Candidate A runs ~4 of the ~6.5 *theoretical* nodes needed at peak — with even one host down, it is below even the idealized floor and fails at peak. Candidate B (8 hosts) keeps peak capacity above the 6.5 theoretical floor with one node down (7 of 6.5), though it is still below the ~16-host 40%-MFU estimate, so its headroom at peak is thinner than the setup implies — a point that feeds the §4 measurement requirement. The author of this case would add: the right mind-set is not "do we fit in aggregate HBM?" but "do we still meet the required availability/SLO at peak with a node down?" (whether that required availability is four nines or a lower target must be established from the requirements, not assumed).
3. **Utilization is not the point.** At low load Candidate A reports *higher* GPU utilization and

Candidate B *lower* — but that is too-little-headroom, not efficiency. The architect's question is "which resource saturates when the SLO is met?", not "is utilization high?" A design that meets the tail SLO with headroom is correct even at lower average utilization; a design that only meets the average is fragile. A high number alone proves nothing.

Outcome. The Red Team's adversarial pass (checks 1–3) rejects Candidate A and leaves Candidate B as a candidate *pending measurement*. The cheaper-looking option was cheaper only because it was sized to the average, not to the peaks, the tail, or the failure domain. Be precise about what has and has not been shown: the Red Team has **eliminated A** (it cannot feed prefill at peak or survive a single-host failure), but it has **not validated B as production-safe** — B's 8 hosts sit above the ~6.5 theoretical floor but below the ~16-host 40%-MFU estimate, so B remains a candidate contingent on measured sustained prefill efficiency and SLO validation (Chapter 14) before commitment. Rejecting one alternative is not the same as validating another. The lesson is binding: *an architecture recommendation is not committed until the Red Team has tried to overturn it on every dimension the average benchmark did not test — peak prefill compute, tail latency, and failure domain — and until the surviving candidate is validated against measured efficiency.*

24.4. Measurement

24.4.1. Metrics the Green Team Tracks

Metric	Type	Definition	Target	Evidence
PIES	DERIVED	Unique, non-redundant prompt-injection patterns across all entry points	< 150 (after hardening)	[ILLUSTRATIVE] [ASSUMPTION]
Poisoned-hit rate	DERIVED	Fraction of retrievals that return at least one poisoned chunk	< 0.3% (0.003 per query)	[ILLUSTRATIVE] [ASSUMPTION]

Metric	Type	Definition	Target	Evidence
Guardrail-trigger rate	FACT	Number of guardrail interventions per 1,000 user queries	< 5	[ILLUSTRATIVE] [ASSUMPTION]
False-positive rate	FACT	Guardrail interventions that block legitimate user intent	< 1.5%	[ILLUSTRATIVE] [ASSUMPTION]
Tool-use exploit rate	FACT	Percentage of Red Team tool-use probes that achieve an unintended action (an *attacker*-side success; lower is better)	< 0.5%	[ILLUSTRATIVE] [ASSUMPTION]
Red-team win rate	HYPOTHESIS	Proportion of evaluation cycles where Red Team escapes all guardrails	→ 0 over time	[ILLUSTRATIVE] [ASSUMPTION]

These targets are local, author-defined guardrails for this deployment, not externally sourced thresholds; unless a target is explicitly tied to a cited standard or measured baseline, treat it as an illustrative assumption [ILLUSTRATIVE][ASSUMPTION].

24.4.2. Data-collection pipeline

1. **Probe generator** — runs 1,000 Red Team probes per cycle, logging each input, entry point, and outcome.
2. **Guardrail logger** — records every intervention, the rule that fired, and whether the user query was legitimate.
3. **Retrieval auditor** — samples 100 retrievals per cycle and manually verifies whether any returned chunk is poisoned.
4. **Outcome synthesizer** — produces the metric table above, tagging each value as FACT, DERIVED, or HYPOTHESIS.

All raw logs are stored in a local `redteam-logs/` directory with timestamps and session hashes for reproducibility.

24.5. Common Mistakes

Mistake	Why it's wrong	Better practice
Counting raw probe volume instead of unique patterns	10,000 probes may only explore 200 distinct injection patterns; the rest are noise.	Deduplicate by normalized syntax and report PIES.
Confusing FACT with DERIVED	Attributing a computed probability to a single observed event inflates confidence.	Always tag metrics with their axis; require at least one FACT to ground each DERIVED quantity.
Stopping after one Red Team cycle	A single cycle cannot establish a trend; guardrails may be effective only against known patterns.	Run at least 5 cycles; track the Red-team win rate across cycles.
Ignoring entry-point heterogeneity	A guardrail that blocks web UI prompts may not cover the API endpoint.	Measure PIES per entry point; require the highest PIES to meet the target.
Reporting "0 attacks blocked" as a success metric	Without a baseline, one cannot know if the surface shrank or if the Red Team simply didn't try.	Report PIES and guardrail-trigger rate together; the latter only matters when PIES is stable.

24.6. Architecture Consequence

The Red Team / Green Team loop directly shapes three architectural decisions:

1. **Guardrail granularity** — If PIES remains high after two cycles, the system must add a prompt-scanning layer (e.g., an LLM-based classifier) before the main model inference. In the illustrative scenario we model this as adding ~150 ms latency per query and reducing PIES by ~60% — **illustrative scenario numbers, not measurements from a deployment in this handbook** [ILLUSTRATIVE][ASSUMPTION].

2. **RAG corpus policy** — If the poisoned-hit rate exceeds 0.3% (0.003 per query), the architecture must enforce corpus provenance checks: every chunk must carry a verified origin tag, and the retrieval index rejects untagged embeddings. This changes the vector store from a pure FAISS index to a provenance-aware store, which we model at ~2× storage overhead in the illustrative scenario [ILLUSTRATIVE][ASSUMPTION] — the real overhead depends on the provenance encoding and must be measured on the target corpus.

3. **Tool-use sandboxing** — If the tool-use exploit rate is above 0.5%, the system must restrict function-call capabilities via an allowlist. In the illustrative scenario this means reducing the available function surface from 87 tools to 23, with the remainder gated behind an explicit opt-in per user group (scenario values, not a measured deployment).

Each consequence is tracked as a **change request** in the fleet's operational backlog, with a clear owner, SLA, and success metric.

24.7. What We Still Don't Know

Unknown	Why it matters	Planned investigation
Cross-entry-point correlation	A prompt that fails in the web UI might, when reformatted, succeed via the API.	Run joint probes across all entry points; measure correlated success rates.
Adversary adaptivity	The Red Team may learn from prior cycles and shift tactics, keeping the win rate stable even as guardrails improve.	Model the Red Team as an adaptive adversary; use Bayesian updating on win-rate trends.

Unknown	Why it matters	Planned investigation
Long-term corpus drift	Embeddings degrade over time; a corpus that is clean today may harbor undetectable poisonings after 6 months.	Schedule quarterly RAG integrity audits; compare embedding stability metrics.
User-driven accidental injection	Legitimate user questions (e.g., "What was your original prompt?") may trigger guardrails, inflating the false-positive rate.	Analyze the subset of guardrail triggers that are user-initiated vs. system-initiated.
Economic cost of hardening	Each guardrail layer adds latency, storage, or compute cost.	Compute the cost-per-PIES-point reduction; establish a budget ceiling.
Human-in-the-loop evaluation fatigue	Repeated Red Team cycles may desensitize the Green Team, leading to missed detections or rubber-stamping of results.	Rotate evaluation owners every cycle; introduce blind validation where a random 10% of outcomes are independently re-scored.

24.8. End-of-Chapter Mini-Case: The PIES Drop: Red Team / Green Team Iteration

Scenario: The fleet's Green Team observes that PIES has dropped from 217 to 143 after adding a prompt-scanning guardrail. The poisoned-hit rate remains at ≈0.003 per query (≈3 poisoned chunks per 1,000 queries). The tool-use exploit rate is 0.44%. However, the false-positive rate has risen to 2.4% — legitimate user queries are being blocked ~24 times per 1,000 queries.

Decision point: The Red Team recommends tightening the guardrail thresholds, which would reduce PIES further (to ~110) but increase the false-positive rate to 4.1%. The Green Team rejects this trade-off, citing the 2.4% false-positive rate as unacceptable for a public-facing service. Instead, they opt for a targeted refinement: add a context-aware classifier that distinguishes intent-preserving prompts from injection attempts, aiming to bring PIES below 150 while keeping the false-positive rate under 1.5%.

Quantified outcome (illustrative worked example, not a reported production measurement): In this scenario, after refinement the model projects PIES = 138, poisoned-hit rate = 0.0025

(≈2.5 per 1,000 queries), guardrail-trigger rate = 4.1 per 1,000 queries, and false-positive rate ≈ 1.3% (≈13 per 1,000 queries), with the Red-team win rate dropping from 8% to 1.2% over three simulated cycles. An illustrative 12-month extension holds these metrics stable when the corpus is refreshed quarterly, with PIES varying by no more than ±8 points. (These are illustrative scenario values to illustrate the measurement loop's shape, not evidence that this system achieved them — they must be produced by a real Red Team run before being treated as results.) The metrics and the figure are intended for the production deployment of the ~2,000-user RAG fleet described in this handbook; the exact numbers an organization would record come from its own run.

Table 24-1 — Red Team / Green Team metric table

Metric	Cycle 1	Cycle 2	Cycle 3	Target
PIES	217	143	138	< 150
Poisoned-hit rate	0.006	0.003	0.0025	< 0.003
Guardrail-trigger rate	7.8	5.4	4.1	< 5
False-positive rate	3.1	2.4	1.3	< 1.5
Tool-use exploit rate	0.61	0.44	0.32	< 0.5
Red-team win rate	8%	3.5%	1.2%	⟶ 0




FIGURE 24.1: Red Team / Green Team cycle. The loop (probe ⟶ guardrails ⟶ metrics ⟶ green team) is operational, but it needs **decision gates** to be actionable: (1) a **release-blocking severity criterion** (e.g. any P0/P1 finding blocks promotion; P2/P3 are tracked but non-blocking); (2) **test-corpus ownership** (a named team maintains the probe corpus and adds new cases from each red-team run); (3) **regression thresholds** (a previously-passing probe that now fails is a regression and blocks release). Without these, the cycle is a ritual, not a gate.

Red Team / Green Team cycle. Probes sweep three domains (model behavior, tool use, retrieval/RAG); findings flow through exposure, guardrails and metrics; failed metrics spawn change-request backlog items that harden the system, and the loop repeats each evaluation cycle. [ILLUSTRATIVE] conceptual

CHAPTER 25.

The Architecture Decision Record

The Architect's Question

As the "From Token to Fleet" handbook reaches its final chapters, we turn from technical mechanisms to the governance of those mechanisms. With ~2,000 users, a RAG Q&A system, and a 70B dense FP16 deployment, the question becomes: how does the team capture, justify, and evolve the architectural choices that keep the fleet running? The Architecture Decision Record (ADR) is the answer — a lightweight, text-first practice that records not just what was decided, but why, what alternatives were considered, and what trade-offs were accepted. This chapter explores the ADR pattern in the context of a production AI system, providing a reusable template and a worked example centered on model-shape choices.

25.1. Concept

An Architecture Decision Record is a single Markdown file that captures a significant architectural decision and its context. The format was popularized by Michael Nygard and has been adopted by teams ranging from startups to enterprises managing complex AI/ML stacks. Each ADR follows a minimal structure:

- **Title** and status (proposed, accepted, superseded, deprecated)
- **Context** — the problem, constraints, and goals that prompted the decision
- **Decision** — the chosen approach, concise and explicit
- **Consequences** — outcomes, both positive and negative, that flow from the decision
- **Alternatives considered** — other paths rejected, with brief rationale for rejection

The key distinction between an ADR and a standard design document is intent: an ADR is meant

to be living, reviewed in pull requests, and occasionally superseded. It answers the "why" at the moment the decision was made, preserving it for future engineers who must reason about the system years later.

In a RAG/Q&A fleet with 70B models, ADRs prevent the "why did we choose this tokenizer?" or "why FP16 over BF16?" questions from becoming tribal knowledge. They also integrate naturally with git — each ADR lives in version control, linked to the commit or PR that implemented the decision.

25.2. Mental Model

The mental model underpinning ADRs is simple: architectural decisions are irreversible (or costly to reverse) choices that deserve permanent documentation. Unlike code comments, which explain what a function does, ADRs explain why the system is structured as it is. This mental model has three layers:

1. **Problem awareness** — What forces are at play? (load patterns, latency requirements, budget constraints, team expertise)
2. **Choice architecture** — What design options exist? What are their properties?
3. **Outcome acceptance** — What will we live with? What will we monitor?

For AI/ML systems, this model extends to decisions about model quantization, retrieval chunk sizes, embedding dimensions, and infrastructure trade-offs. Each decision carries FACT/DERIVED/HYPOTHESIS evidence tags, making the ADR itself a source of verifiable claims rather than opinion.

The ADR format also enforces a habit: before committing to a decision, the team must explicitly articulate alternatives. This alone often reveals overlooked options or clarifies why the chosen path is genuinely optimal.

25.3. Worked Example: Model-Shape ADR

Title: ADR 0016 — Model Precision: FP16 vs BF16 for 70B Inference

Status: Accepted

Context: The fleet runs a 70-billion-parameter dense model for RAG Q&A serving on an 8×H100 host (640 GB). The team is choosing the deployment weight precision: FP16 (float16) or BF16 (bfloat16). A common assumption — that migrating to BF16 halves the model's memory and buys headroom — is wrong, and this record exists partly to correct it. FP16 and BF16 are both 16-bit formats, 2 bytes per parameter, so a 70B model occupies ~140 GB in either. This ADR is therefore not a memory decision; it is a numerical-range and operational-consistency decision.

Decision: Render the serving model in BF16.

Rationale:

- FP16 and BF16 both store 2 bytes/parameter, so weight residency is identical (~140 GB for 70B). Stating this up front prevents anyone from later treating the choice as a memory lever.
- The real difference is range vs precision. BF16 keeps the same 8-bit exponent as FP32, so it does not overflow or underflow in activations the way FP16's 5-bit exponent can. FP16 carries more mantissa bits (10 vs 7) and is more precise when values already sit in range.
- For this workload both precisions clear the quality bar on the held-out Q&A set, with no exact-match change between them, so the deciding factors are range robustness and consistency — not capacity. In this illustrative evaluation the exact-match result showed no difference [ILLUSTRATIVE][ASSUMPTION] — to be confirmed by the deployment quality gate: we did not run this comparison on real hardware in this handbook; it is an assumed outcome for the worked ADR.
- A100 (and the 8×H100 host) natively supports BF16 and TF32 on its Tensor Cores. There is no "next GPU generation" required and no explicit-casting penalty; the premise that these formats wait for future hardware is itself the kind of error an ADR should catch.
- Operational consistency: the training run that produced the weights used BF16 mixed precision. Keeping inference in BF16 avoids a training-to-serving cast and keeps behavior predictable.

Consequences:

- **Positive:** range robustness in attention/softmax and long-context accumulation; no change in weight residency (both precisions are ~140 GB).
- **Negative:** lower mantissa precision than FP16 in the weights (BF16 has 7 mantissa bits vs FP16's 10), so FP16 is more precise where values already sit in range; in the illustrative evaluation on this workload the exact-match result showed no quality difference [ILLUSTRATIVE][ASSUMPTION] (to be confirmed by the deployment quality gate), so the trade-off is precision headroom, not observed quality. There is no free memory — and none should be expected.
- **Monitoring:** track per-request latency, GPU memory utilization, and held-out Q&A quality. If the BF16 output drifts, fall back to FP16 and compare both on the same set (they differ in precision, not footprint).

Alternatives Considered:

1. **FP16:** Rejected here — no memory advantage over BF16, and a narrower exponent range. Retained as the fallback if BF16 shows precision drift.
2. **FP8 weights:** The genuine memory lever (halves residency to ~70 GB) but needs per-tensor calibration and a validation gate; deferred as the next step, paired with the FP8 KV discussion in Chapter 7.
3. **FP32:** Rejected — 280 GB residency with no quality benefit for this workload.

Evidence Tags: [1P][FACT] — FP16 and BF16 are both 16-bit (2 bytes/parameter). [ILLUSTRATIVE][DERIVED] — a 70B model is ~140 GB in either ($70 \times 10^9 \times 2$ B), the same footprint

Table 22-1 and §25.4 derive. [1P][FACT] — A100/H100 Tensor Cores support BF16 and TF32 natively. [canonical scenario][DERIVED] — weight residency is unchanged by the FP16↔BF16 choice. [ILLUSTRATIVE][ASSUMPTION] — no exact-match difference between FP16 and BF16 on the held-out Q&A set — an assumed outcome for this worked ADR, to be confirmed by the deployment quality gate (not a measurement in this handbook).

25.3.1. A copy-ready blank template

This is the minimal template to copy into a repo, intended to be filled and to serve as a reusable professional artifact. Every section maps to a discipline from this handbook; the model-shape ADR above is one filled example, and Chapter 22's loop supplies the architecture-decision context.

```
# ADR-NNNN — <Short Decision Title>

## Status
<proposed | accepted | superseded | deprecated>  (date)

## Decision (the committed choice, one paragraph,
   reversible in principle)
<the one-sentence decision, and what it commits the team to>

## Architecture Decision Context  (from Chapter 22's loop)
- Business objective:  <what outcome this enables>
- Workload:            <characterization:
                         tokens, rps, peak>
- Requirements+SLOs:   <quality / latency / availability,
                         measurable>
- Constraints:         <privacy, region, ops,
                         procurement, budget>

## Alternatives considered
1. <option> — <why rejected>
2. <option> — <why rejected>

## Evidence
- <claim> — FACT/DERIVED/HYPOTHESIS
  [1P]/[2°]/(to be verified)
- Unit check:  <does each derived quantity's
  unit make sense?>
- Sanity check: <is each result physically
  possible? (e.g. MFU ≤ 1)>

## Trade-offs & consequences
- Pro:   <expected positive effects>
```

```
- Con:   <expected negative effects>
- Risk:  <residual uncertainty>

## Decision owner
<person / team>

## Validation plan
<how this decision will be
  benchmarked/verified post-deploy>

## Rollback plan
<how we unwind if the decision fails its SLO>

## Review trigger
<what event (metric, date, new evidence)
  re-opens this ADR>

## Falsification path
- Hypothesis:      <the claim this decision rests on,
  stated so it can be wrong>
- Evidence required: <the measurement/benchmark that
  would confirm it>
- Invalidation:     <the specific counterexample or
  measured result that would prove the decision wrong
  and force a re-open>
- Alternative:      <what we switch to if invalidated>
```

The three blocks most often skipped are the **Architecture Decision Context**, the **unit check**, and the **decision owner + review trigger** — and skipping exactly those three is what turns an ADR into a decision log instead of a decision *apparatus*. The context ties the technical choice to a business outcome; the unit check enforces Chapter 22's evidence discipline; the owner and review trigger make it a living document rather than a tombstone. The **falsification path** is what makes the decision *reproducible* rather than merely plausible: it names the hypothesis, the evidence that would confirm it, and the specific measured result that would invalidate it — so the next engineer can re-run the decision instead of inheriting it on faith.

25.4. Measurement

ADRs are only as good as the evidence they embed. This chapter recommends that each ADR include at least two derived quantities — quantities computed from raw data, not merely observed. In the model-shape ADR above, the derived quantities are:

1. **70B FP16 model footprint** — $W = N \times \text{bytes-per-param} = 70 \times 10^9 \times 2\,\text{B} = 140$ GB parameters, plus ~30 GB activations at the peak for this worked example, giving ≈ 170 GB total

derived footprint. This ~30 GB is a *per-request working-set* figure for this ADR's single-request arithmetic; it is deliberately **not** the ~64 GB runtime/workspace/NCCL reserve the body uses elsewhere (140 GB weights + ~436 GB KV budget + ~64 GB reserve ≈ the 640 GB HBM envelope). The two are different quantities — one sizes a single request's activations, the other reserves headroom for the serving stack's runtime — and both coexist on the 8×H100 host. Derived from the model parameter count and a typical activation overhead factor.

2. **Weight-quantization residency lever** — quantizing the FP16/BF16 weights to INT8 reduces the nominal parameter-weight footprint from ~140 GB to ~70 GB for a 70B model (2 B/param → 1 B/param), before runtime overheads. Whether the resulting quantized model satisfies the quality SLO must be established by benchmark, not assumed. (An FP16↔BF16 change alone is *not* a memory lever: both are 16-bit, 2 B/param, ~140 GB.)

Additional measurable quantities that should be tracked (even if not all included in the ADR itself) include:

- GPU memory utilization per request (derived from NVIDIA management library stats)
- Per-request latency p99 (derived from request-timing histograms)
- Exact-match score on the Q&A dev set (derived from evaluation harness runs)

Each derived quantity should be tagged with its evidence source [1P]/[2°]/(to be verified), linking to a profiling script, a benchmark run, or a verified observation. This makes the ADR a citable source of truth rather than a static narrative.

25.5. Common Mistakes

When adopting ADRs, teams frequently fall into patterns that undermine the format's purpose. Here are the most common, with fixes:

Table 25-1 — Common ADR adoption mistakes and their fixes.

Mistake	Fix
Writing ADRs after the fact — retroactive documentation loses the context of the decision trade-offs.	ADRs are written as part of the decision process, ideally in the same PR that implements the change.
Too much detail — documenting every incremental choice clutters the record and discourages reading.	Limit ADRs to decisions that affect system behavior, architecture, or cost. Routine choices (library upgrades without API change) need no ADR.

Mistake	Fix
No status tracking — an ADR that is never updated becomes stale and erodes trust.	Use status fields (proposed → accepted → superseded) and treat the ADR as a living document reviewed in PRs.
Missing alternatives — without explicit alternatives, the ADR reads like a proclamation, not a decision log.	Always include an "Alternatives considered" section, even if the list is short.
No evidence links — claims without references become folklore.	Every derived quantity and key claim should reference a data source, script, or benchmark run.
Treating ADRs as permanent — some decisions do change.	If a decision is superseded, update the ADR status and add a superseding ADR link. Do not delete history.

25.6. Architecture Consequence

Introducing ADRs into the "From Token to Fleet" handbook has several architecture-level consequences:

- **Decision provenance:** Every significant choice in the fleet's evolution is traceable to a git commit and a Markdown file. New engineers can audit why the system is as it is, without relying on Slack history or outdated wikis.
- **RQO (Reasoned Quality Optimization):** By forcing the articulation of alternatives and evidence, ADRs make the trade-off surface explicit. Teams can point to an ADR and say "we chose BF16 over FP16 because of range robustness and training-to-serving consistency" (as ADR 0016 does) — and those reasons are verifiable.
- **Reduced cognitive load:** Engineers no longer need to re-derive the rationale for every architectural choice. The ADR serves as a single source of truth.
- **ADR proliferation:** As the fleet grows, the number of ADRs will grow. A naming convention (ADR 0001, ADR 0002, …) and a top-level index (ADR index) prevent the record from becoming unwieldy.
- **Integration with CI:** ADRs can be validated as part of the CI pipeline — e.g., ensuring every ADR has a status, a rationale, and at least one evidence tag. This automation reinforces the habit.

On the negative side, ADRs add a small writing overhead. For a team of ~10 engineers making ~1–2 significant architectural decisions per month, this is a manageable cost. The payoff — reduced

on-call noise, faster onboarding, and fewer "why did we do it this way?" debates — more than compensates.

25.7. What We Still Don't Know

Despite the structured format, several questions remain open and would benefit from future ADRs or empirical studies:

1. **ADR fatigue:** Does the presence of many ADRs overwhelm the team, leading to superficial writing or skipped documentation?
2. **Evidence decay:** How long do derived quantities remain valid? Should ADRs include a "last reviewed" date and a trigger for re-evaluation?
3. **Cross-ADR dependencies:** When multiple ADRs interact (e.g., a quantization choice interacts with a retrieval chunk-size choice), how should the team document the dependency graph?
4. **Tooling gaps:** No widely adopted tool exists for ADR graph visualization or impact analysis. Building such a tool would require understanding the ADR network and its evolution over time.
5. **ADR format evolution:** The minimal format (title, context, decision, consequences, alternatives) works for most cases, but edge cases — decisions involving regulatory compliance, security, or data governance — may require additional sections.

These open questions are not blockers; they are signals for when the practice matures and the team needs more sophisticated governance.

25.8. End-of-Chapter Mini-Case: An ADR for the KV-Bound Fleet

Scenario: The fleet serves the canonical RAG Q&A workload on an 8×H100 host. At peak the KV cache is the binding constraint: within the canonical ~436 GB practical KV budget, a full-precision FP16 KV at ~2.62 MB/token (the canonical full-MHA reference-geometry figure; ~2.5 MiB) lets a single host hold ~17.5 concurrent 9,500-token requests (byte-accurate 17.51; conservative integer floor 17). The concurrency ceiling is now limiting throughput below the target request rate.

The ADR (draft):

- **Title:** ADR 0017 — KV Cache Precision: FP16 vs FP8
- **Status:** Proposed
- **Context:** The canonical 70B RAG workload is bandwidth-bound at decode (Ch. 8's "memory-bound" = low arithmetic intensity, ~1 FLOP/byte), and its *concurrency* is capacity-constrained by KV residency (a distinct constraint from the decode bandwidth bound — Ch. 15). At the ~436 GB practical KV budget, full FP16 KV caps concurrency at ~17.5 requests/host, and Ch. 17 shows that ~40 rps at the canonical ~8.6 s service time implies ~344 in-flight requests — far more than one host can hold (a single host holds ~17.5 concurrent). To reach the target request rate we need either more host capacity or more KV residency per host.




FIGURE 25.1: The Anatomy of an Architecture Decision Record, and how one ADR supersedes the next. **Takeaway:** an ADR is a fixed five-field record — Context (the situation), Options (the alternatives), Decision (the choice), Rationale (the why), Consequences (the effects) — and it is *kept, not edited*: the Consequences of ADR-001 become the Context of ADR-002, which supersedes it while the original stays on file. **Scope:** the generic anatomy and supersession rule that the chapter's worked model-shape ADR (§25.3) and the copy-ready template (§25.3.1) put into practice. **Warning:** illustrative structure, not a measured decision record — a real ADR must carry the evidence tags its numbers are judged by.

- **Decision:** Render the KV cache in FP8 for the long-context decode path, keeping prefill and the retrieval/prompt phase in FP16. FP8 KV cuts KV residency to ~50% of the FP16 figure (raw byte-halving of BF16: 1.31 MB/token vs 2.62 MB/token [ILLUSTRATIVE][DERIVED]), so the same ~436 GB budget holds ~35.0 concurrent 9,500-token requests instead of ~17.5 — roughly doubling per-host concurrency without adding a host.
- **Consequences:**
  - Positive: KV residency per request falls from ~24.9 GB (FP16) to ~12.45 GB (FP8, raw byte-halving — 50% of BF16) at the 9,500-token max, so the canonical budget supports ~35.0 concurrent requests rather than ~17.5. This is a memory lever, not a compute lever: it does not change decode speed per token, it raises the concurrency the host can hold under the same KV budget.
  - Negative: FP8 KV has lower precision in the cached K/V tensors, which can add small retrieval-fidelity error on long contexts. The trade-off is memory capacity vs long-context reconstruction fidelity; it must be validated on the held-out Q&A set, not assumed.
- **Alternatives considered:**
  1. **Add capacity** — rejected as the first move: the canonical peak already needs ~20 hosts (Ch 16/17), so "adding a second host" misunderstands the scale; relieving the memory ceiling by adding hosts multiplies the fleet cost (each 8×H100 is ~$5.8K/mo amortized), while FP8 KV relaxes the same ceiling without commissioning new hardware.
  2. **GQA (grouped-query attention) reduction** — not available for the canonical model: the 70B reference geometry is full multi-head attention (32 KV heads, 2.62 MB/token, Ch 7). Adopting GQA would cut KV per token by ~8× (the largest single capacity lever in this book, Ch 16), but it changes the model architecture and requires retraining and re-evaluation — it is outside a serving-only change. It is the right *next-model* decision, not a knob on this deployment.
  3. **Prefix/context caching** — complementary, not a substitute: it reduces prefill work and recomputation, but does not shrink the KV resident per active long-context request; retained alongside FP8 KV.
- **Evidence Tags:** [canonical scenario][DERIVED] — at ~2.62 MB/token a 9,500-token request needs ~24.9 GB FP16 KV (9,500 × 2.62 MB ≈ 24.9 GB; Ch. 15, Ch. 17). [ILLUSTRATIVE][DERIVED] — FP8 is byte-halved to 1.31 MB/token (exactly 50% of BF16), so a 9,500-token FP8 KV ≈ 12.45 GB/request; 436 GB ÷ 12.45 GB ≈ 35.0 concurrent (floor 35). [HYPOTHESIS] — the FP8 precision shift has a small, measurable effect on long-context retrieval fidelity that must be measured on the held-out set before promoting.

This mini-case illustrates how the ADR format captures not just the "what" but the "how much" — derived quantities, trade-offs, and explicit alternatives. The team can now evaluate the proposal against the fleet's latency and quality SLAs, with all reasoning preserved for future review.

CHAPTER 26.

The Solution Architect's Toolkit + Patterns Library

The Architect's Question

When confronting a new system design, the architect's first question is not "what technology should I choose?" but rather "what pattern solves which problem, and how do I measure success?" This chapter distills the accumulated wisdom from across the handbook into a reusable toolkit — a compendium of patterns, checklists, and mental models that unify the journey from token to fleet. Each pattern is grounded in evidence (FACT, DERIVED, HYPOTHESIS) and paired with concrete measurement strategies so that architectural decisions can be verified and adjusted post-deployment.

26.1. Concept

The Solution Architect's Toolkit answers three concerns — scalability, reliability, and observability — and is organized as pattern templates plus measurement rather than as three separate taxonomies. Rather than prescribing specific technologies, the toolkit provides pattern templates that can be instantiated for any stack. The Patterns Library complements this by cataloging recurring structural solutions — sharding strategies for RAG pipelines, caching layers for LLM serving, circuit breaker patterns for inter-service communication, and more. Together, they form a decision framework that answers the architect's question at multiple grainsizes: from the micro (which cache invalidation strategy?) to the macro (how does sharding affect fleet-wide latency?).

26.2. Mental Model

The central mental model is the **Pattern-Measurement-Feedback Loop**. Every pattern in the library is paired with:

- **FACT** — a verified runtime quantity (e.g., request rate, cache hit ratio, query latency p99)
- **DERIVED** — a computed quantity from FACTs (e.g., throughput per shard, cost per query, fleet-wide rps)
- **HYPOTHESIS** — a predictive claim about what changing the pattern will affect (e.g., "increasing replication factor from 3 to 5 will reduce tail latency by X%")

The loop operates as: instrument → observe FACT → compute DERIVED → validate HYPOTHESIS → adjust pattern. This ensures that architecture evolves from evidence, not speculation.

What a [1P] tag does and does not mean. The statuses above (FACT / DERIVED / HYPOTHESIS) describe what a number *claims to be*; a separate *provenance* axis describes **where it came from**. **[1P]** marks a first-party **source** — the original method paper authored by the method's creators, or a hardware-vendor specification (technical report, model card, or official documentation). It names *whose* claim a number is; it does **not** by itself assert a validated deployment benchmark. Keep the four categories distinct: (a) an original method paper by the method's creators, (b) a hardware-vendor specification, (c) a third-party evaluation (the book's [2°] secondary provenance), and (d) an own measured run ([LAB]/[MEASURED] — Axis-1 provenance plus the Axis-3 measurement status, both defined in the Sources, Method, and Reproducibility chapter). Of these, [1P] covers (a) and (b) only — a first-party source is a vendor or paper author's figure, which must be re-verified against the current source or re-measured on the architect's own hardware before it is treated as a validated deployment result. Note that the canonical 70B teaching model is *not* a [1P] model: being constructed (Ch 4, Table 4-2) it carries [ILLUSTRATIVE][ASSUMPTION], reserving [1P] for named, traceable first-party specifications.

26.2.1. Workload-to-Strategy decision matrix

The canonical RAG scenario is one point in a much larger design space (Chapter 12). The matrix below is the first-pass mapping from a *new* workload's dominant constraint to the strategy class worth evaluating first — a reference to generalize the method beyond the canonical case, not a prescription. Each row names the binding constraint (the one the architect expects to saturate first under the SLO; Chapter 8's roofline and Chapter 15's congestion check are how to confirm it).

Workload	Input	Output	Dominant constraint	First strategy to evaluate
Long-context RAG Q&A	Long (8K+)	Short (<500)	KV / memory	8-bit or FP16 KV sizing, prefix caching, P/D separation (Ch. 7, 17, 20)
High-throughput chat	Short (<2K)	Med-Long (>1K)	Decode bandwidth	Continuous batching, KV pool sizing, possibly P/D (Ch. 8, 20)
Batch inference	Long	Long	Utilization / cost	Offline batching, FP8, higher batch occupancy (Ch. 8, 16)
Reasoning / long-think	Med	Med	Test-time compute	Decode headroom, token amplification budgeting (Ch. 6, 19)
Agentic task loops	Med	Med	Orchestration / variance	Task-economics model, retry + tool budgets, fallback (Ch. 19)
Embedding / retrieval	N/A	Vector	Compute throughput	Dedicated encoder pool, caching, quantization (Ch. 3)
Vision-language	Med	Med	Multimodal preprocess + compute	Preprocess pipeline, fused kernels (Ch. 5, 20)

Workload	Input	Output	Dominant constraint	First strategy to evaluate
Fine-tuning	N/A	N/A	Memory + interconnect	Precision-aware optimizer (LoRA/QLoRA) before full FT; gradient checkpointing (Ch. 7)
Training	N/A	N/A	Compute + interconnect	Parallelism split (DP/TP/PP/FSDP) sized to model and cluster (Ch. 10)
Real-time multimodal	Med	Low-latency	Latency + pipeline sync	Chunked prefill, streaming decode, P/D (Ch. 8, 20)

New workloads are evaluated by *locating the dominant constraint*, not by matching the canonical row count. The matrix answers "where does the SLO saturate first?" — and that single question routes to the correct strategy class, keeping the canonical case a teaching instrument rather than a ceiling.

The Chapter 4 six-axis characterization rendered as a fingerprint. The workload families from the §26.2.1 workload-to-strategy matrix sit in distinct regions: RAG Q&A is quality- and context-heavy with short outputs; chat is traffic- and latency-sensitive with long outputs; batch inference is cost-sensitive and latency-tolerant. Reading a new workload's fingerprint against this front-end is the first move before consulting the §26.2.1 matrix.

26.3. Worked Example — Capstone Scenario

Take the canonical deployment: ~2,000 registered users with ~5% concurrently active at peak (~100 concurrent *users*, a population measure), RAG Q&A over a 70B dense FP16 model. The architect faces three interlocked questions: how to scale inference, how to cache retrieved context, and how to keep the model-service latency under its SLO — here the model-service latency SLO is defined as **time-to-first-token (TTFT)**, and for the *retrieved-context/short-prompt* leg of this scenario we adopt a *stricter* p99 ≤ 800 ms TTFT target (a scenario input, not the canonical p95-TTFT ≤ 2 s of Ch 4:




FIGURE 26.1: Workload fingerprints on the six axes. **Provenance note:** the six axes are *subjective normalized* scores (0–1) derived from the canonical scenario's characterized workload (Ch 4), not empirically measured quantities — the bars are a visualization of the characterization, not a benchmark. The raw inputs (traffic, token profile, SLO, quality, ops, TCO) are the Ch 4 six-axis characterization of the canonical scenario, and each bar is an *authored* 0–1 intensity score for that family on that axis — there is no min–max rescaling of measured data. In axis order (context length, traffic, quality required, cost sensitive, latency sensitive, output tokens) the scores are long-context RAG Q&A 0.95 / 0.20 / 0.70 / 0.55 / 0.40 / 0.45, chat 0.35 / 0.95 / 0.50 / 0.75 / 0.90 / 0.55, batch 0.55 / 0.60 / 0.30 / 0.85 / 0.35 / 0.90 — the same table is carried in the figure's generator script (`render/fig_ch26_fingerprint.py`); the archetypes are reference points, not measured clusters.

the capstone deliberately uses a harder tail target to exercise the patterns). This is a **TTFT** budget, not an end-to-end one — the canonical request's total end-to-end time is ~8.6 s (1.08 s prefill + ~7.5 s decode of 300 output tokens), and the per-host ceiling is ~2.0 req/s (Ch 17/20), both of which still hold here. Do not read the sub-second capstone figures as end-to-end request latency. (All the other numbers below are the canonical values established in Parts I–V — Ch 4's workload, Ch 7/15's KV and memory figures, Ch 17's fleet sizing — recalled here rather than re-derived, and this capstone shows how the toolkit's patterns compose them.)

Pattern A — Inference Sharding. [canonical scenario][DERIVED] — model FLOPs/token = $2N = 1.4 \times 10^{11}$; KV bytes/token = 2.62 MB (Ch 7, 22). The 70B model at FP16 requires ~140 GB of weights [ILLUSTRATIVE][DERIVED] — 70×10^9 parameters × 2 B/parameter = 140 GB, the footprint Ch 22 and §25.4 also derive. Following the canonical setup, one serving host is an 8×H100 80 GB node, which dedicates ~140 GB to weights and leaves the rest of the 640 GB pool for KV cache and runtime. With tensor parallelism across the 8 H100s, a single host serves the model and can hold ~17.5 concurrent 9,500-token requests within the canonical ~436 GB KV budget from Chapter 15. [canonical scenario][DERIVED] — with the 8-way tensor parallelism across the node, decode latency is bandwidth-bound, so per-token throughput scales with the node's aggregate memory bandwidth rather than 8× the single-GPU rate. [canonical scenario][HYPOTHESIS] — adding a second host and load-balancing requests across two replicas yields < 5% additional per-request latency improvement because the bottleneck is concurrency/KV residency, not per-host throughput.

Pattern B — Semantic Response Cache. [ILLUSTRATIVE][ASSUMPTION] — 35% of queries repeat within 5-min windows (a scenario input to be measured on real traffic). A content-addressable cache keyed by question hash stores the completed answer (the retrieved context and the generated response). [canonical scenario][DERIVED] — a cache hit ratio of 35% reduces the number of requests that reach the LLM engine by 35%, directly lowering generation compute and operational cost; the embedding/retrieval step is also skipped for cache hits. [canonical scenario][HYPOTHESIS] — expanding the cache TTL from 5 to 15 minutes increases hit ratio to ~55% with negligible staleness risk, because user questions in a support session repeat within the same session.

Pattern C — Circuit Breaker. [ILLUSTRATIVE][ASSUMPTION] — model-service latency p99 degrades past the 800 ms SLO under concurrent load; downstream network jitter p99 = 120 ms (scenario inputs to be measured). [canonical scenario][DERIVED] — the diagnosed symptom: when a host's arrival rate exceeds the ~2.0 req/s per-host ceiling (Ch 17/20) — as the canonical ~40 rps peak (Ch 4) would if concentrated on one host — the request queue grows and queueing delay alone pushes TTFT p99 past the 800 ms SLO, the condition Pattern C exists for; Table 26-2's ~7% fallback rate is the modeled share of requests shed to the intent classifier during such excursions (FACT target < 10%). When the model service becomes saturated, a circuit breaker trips after 5 consecutive timeouts, falling back to a lightweight intent classifier. [ILLUSTRATIVE][ASSUMPTION] — circuit breaker activation reduces tail latency for remaining requests by 35% because the system sheds

load before the model queue fills. [canonical scenario][HYPOTHESIS] — a grace-period of 2 seconds before auto-recovery prevents thrashing when load spikes are transient.

Capstone Execution. The architect instruments all three scenario quantities, observes the derived quantities in real time, and validates each HYPOTHESIS against measured traffic. The result: one 8×H100 serving host + a 35% semantic response cache + circuit breaker yields an illustrative **p99 TTFT ≈ 250 ms at ~48% lower generation cost** versus the ~450 ms uncached, unsharded baseline — the single capstone configuration, derived step by step in §26.8 and recorded as Table 26-2 (scenario outcome, not a measured benchmark). The Pattern-Measurement-Feedback Loop confirms the hypothesis that caching + load shedding is net positive, and the architect documents the configuration as a reusable pattern instance.

Alternatives considered. Two obvious alternatives were rejected against the canonical constraints. *Prefix caching alone* reuses prefill compute behind an exact-prefix match but still generates the answer, so the 35% repeat population keeps paying full decode — it does not skip the generation the semantic cache skips. *A second serving host with load balancing* is rejected because the bottleneck is concurrency/KV residency, not per-host throughput: Pattern A's own hypothesis puts the gain at < 5% per request, so a second host doubles the fleet for single-digit improvement. *Deeper continuous batching on the single host instead of sharding* raises throughput by lengthening the in-flight queue, adding queueing delay exactly where the p99 TTFT SLO binds (Ch 8's decode economics; Ch 15's congestion check). Sharding + semantic cache + circuit breaker wins because it attacks the baseline's own terms — model compute (sharding), the retrieval step (cache hits), and tail queueing (circuit breaker) — that each rejected option leaves in place.

26.4. Measurement

Quantitative verification is non-negotiable. For each pattern, define the minimal FACT set that proves the pattern works in production:

Table 26-1 — The FACT set to measure for each pattern.

Pattern	FACT 1	FACT 2	FACT 3
Inference Sharding	GPU utilization %	per-GPU token latency p99	All-Reduce time
Semantic Response Cache	hit ratio @ TTL=T	stale read rate	cache memory pressure
Circuit Breaker	timeout count / 30s	fallback activation rate	recovery grace-period latency

Measurement must be continuous, not ad-hoc. Dashboards surface FACT trends; alerts fire when DERIVED quantities cross safety boundaries. The architect never promotes a pattern from

HYPOTHESIS to ACCEPTED unless all FACTs stabilize within expected ranges across at least two load cycles.

26.5. Common Mistakes

- **Mistake 1: Measuring only HYPOTHESIS outcomes.** Without FACT anchors, the architect cannot distinguish between a pattern that works and one that merely appears to work under a narrow load window.
- **Mistake 2: Over-engineering before FACTs exist.** Adding shards, caches, or circuit breakers "just in case" introduces complexity cost without DERIVED benefit. Wait for the FACT to signal the need.
- **Mistake 3: Ignoring the cost DERIVED.** A pattern that reduces latency but increases cost by 3× is often unacceptable. Measure cost per query as a first-class FACT.
- **Mistake 4: Circular HYPOTHESIS validation.** Self-confirming predictions (e.g., "our cache is fast because we designed it to be fast") bypass the FACT/DERIVED/HYPOTHESIS axis. Always validate against observed FACTs.

26.6. Architecture Consequence

The toolkit's patterns do not exist in isolation. Inference sharding changes the resource profile, which affects cost DERIVED; semantic response caching changes the query pattern seen by the model, which alters the HYPOTHESIS for circuit breaker thresholds; circuit breaker grace-periods interact with cache TTLs to shape tail latency. The architect must trace consequences across patterns using the FACT/DERIVED/HYPOTHESIS axis before commit. A change that looks beneficial in isolation may degrade fleet-wide metrics when patterns interact.

26.7. What We Still Don't Know

- How do multi-modal retrieval patterns (image + text) compose with the existing RAG sharding strategy?
- What is the optimal cache size for 70B model embeddings when user query distributions shift seasonally?
- Can circuit breaker thresholds be auto-tuned from FACT streams without manual intervention?
- How does fleet-wide model versioning interact with per-shard caching, and what FACTs govern safe rollouts?

These open questions define the next research cycle. Each is framed as a HYPOTHESIS waiting for FACT instrumentation.

26.8. End-of-Chapter Mini-Case: The Capstone: Composing the Patterns

Scenario. A growing AI startup moves from a single-node prototype to a fleet serving ~3,000 users. The initial deployment is a 70B FP16 model on a single 8×H100 node (the canonical host). Note the per-host ceiling: with the canonical ~8.6 s service time and C ≈ 17.5 KV-resident requests, one host serves ~2.0 req/s (Ch 17/20) — so the figures below are expressed as **TTFT p99** on that host (the sub-second latencies are time-to-first-token, not end-to-end), and the rps is the ~2 req/s the host can actually sustain, not a multiple of it.

Step 1 — Instrument. FACTs collected: request rate ~2 rps (within the ~2.0 req/s per-host analytical planning ceiling), GPU utilization 45%, per-query latency breakdown for a *baseline* (uncached) request: model compute 320 ms, I/O 80 ms, retrieval 50 ms — the RAG retrieval step every request pays. The baseline has **no cache installed**, so there is no cache-*miss* path in it; the 50 ms is plain retrieval, and Pattern B's hit path later covers the same ground (retrieval + lookup) without the engine. These components sum to a **~450 ms baseline TTFT**, which the capstone uses directly as the baseline **p99** scenario value (a scenario input, not a derived quantile of a distributed sample; a real baseline p99 must come from a measured latency distribution). Note the component values are *representative worst-case* estimates for a baseline request, and the ~450 ms is therefore the baseline TTFT figure used throughout; the per-query values are not a p99 of a separate measured distribution. Because the 50 ms retrieval term is part of the baseline, the headline **−44%** is measured against the full 450 ms path; excluding that term entirely (a 400 ms baseline) would report (400 − 250) / 400 = **37.5%** instead.

Step 2 — Pattern Apply. The architect applies Pattern A (inference sharding across an 8×H100 node) and Pattern B (semantic response cache with 5-min TTL). [canonical scenario][DERIVED] — sharding distributes the model across the node so decode lands in the bandwidth-bound regime; cache hit ratio 35% reduces the number of requests that reach the model engine from ~2.0 rps to ~1.3 rps (2.0 × (1 − 0.35) = 1.3). The TTFT and cost figures below are *scenario estimates* for this illustrative configuration, not measured values. **A weighted average of component latency values is a mean, not a quantile, so the capstone separates the two.** Under the transparent two-point model — a cache hit returns at a fixed ~50 ms (retrieval + cache lookup, no LLM prefill), and a cache miss is served by the engine at ~250 ms (a scenario value after the 35% lower arrival rate has settled the prefill queue) — the pooled latency has the CDF $F(50) = 0.35$, $F(250) = 1.0$. Its **mean** is $0.35 \times 50 + 0.65 \times 250 = 180$ ms, but its **p99 is 250 ms** (because the 0.99 quantile falls in the miss population: $0.35 < 0.99 \leq 1.0$). So **mean TTFT ≈ 180 ms**. **p99 TTFT ≈ 250 ms** (the miss value, not a blend). **−44% TTFT** against the ~450 ms uncached p99 baseline — $(450 - 250)/450 \approx 44\%$. **−48% generation cost** — the admissible savings decompose as approximately 0.35 (cache-hit queries at near-zero marginal generation cost) $+0.65 \times 0.20$ (the 65% that generate, at ~20% lower per-token cost from the sharded engine) $= 48\%$. The previously-quoted ~55% included a separately-priced skipped-embedding saving that is not part of this cost ledger, so it is not used. These are *illustrative* scenario numbers to show how a hypothesis is formed; a real deployment must measure the actual

cache-hit latency *distribution* (not a point mass), the prefill queue at 1.3 rps, and the per-query cost, and the three gains (cache, sharding, retrieval-skip) are *not* independent — they compound on the same request path, so they must not be added as if separable. The reproducible two-point model that yields these numbers is `render/capstone_calc.py`.

Step 3 — Validate. [canonical scenario][HYPOTHESIS] — "sharding + caching will keep TTFT p99 < 300 ms as the fleet grows from the canonical ~2,000 users to the capstone's ~3,000 users (1.5× — already ~3,000, not 3×)." Suppose a staged load test at ~3,000 users (the capstone's fleet size) reports TTFT p99 = 285 ms and cost per query down 48% — in this scenario these are illustrative values to show how a hypothesis is tested, not a real experiment the book ran. The hypothesis is accepted only on a genuine load test's numbers.

Step 4 — Document. The pattern instance — 8×H100 shard + semantic response cache + circuit breaker with 2-s grace period — is recorded in the Patterns Library as Table 26-2, ready for the next fleet expansion.

Table 26-2 — Pattern Instance: Sharded RAG Serving

Component	Configuration	FACT Target	Modeled example
GPU Shard	8×H100 80 GB	GPU util < 80%	68%
Semantic Response Cache	LRU, TTL 5 min	hit ratio > 30%	35%
Circuit Breaker	trip after 5 timeouts, 2s grace	fallback rate < 10%	7%
Cost	$ per query	< $0.015	$0.003

The $0.003/query is this capstone scenario's DERIVED per-query cost at the 35% semantic-cache hit ratio, computed from the canonical self-host rate: $0.0057/request ($5.7 per 1,000 requests, Ch 16) × 0.65 (the 65% of queries that still reach the engine) × 0.80 (the ~20% lower per-token cost of the sharded engine) ≈ $0.003/request — the same 0.52 cost fraction as the §26.8 –48% decomposition. For a different basis, the hosted-API cost is $0.012/request (≈$11.6 per 1,000 requests, Ch 4); per Ch 4's basis note, the two cost bases are not interchangeable. ***Provenance note: the "Modeled example" column is a worked-out illustrative instance, not gathered telemetry.*** *The values in it (68% GPU util, 35% hit ratio, 7% fallback, $0.003/query) are scenario outputs chosen to illustrate how the pattern library is applied and validated; they are* not *FACTs measured on a deployed system. In a real deployment, each value must come from a recorded load test (a genuine FACT target), and the warning that it is not-yet-measured must be carried into the same cell. Use a blank instrumentation template to record the real FACTs separately.*

A note on utilization targets. The "GPU util < 80%" row is an *operational guardrail for this specific workload*, not a universal performance criterion. A GPU has many utilization figures — SM




FIGURE 26.2: Pattern Application Diagram: the Pattern-Measurement-Feedback Loop applied to the capstone scenario, closing on FACT ⟶ DERIVED ⟶ PATTERN. **Takeaway:** the three patterns compose to mean TTFT ~180 ms and p99 TTFT ~250 ms (–44% vs the ~450 ms uncached baseline, not a blended average) at ~48% lower generation cost per query. **Scope:** full arithmetic in §26.8; a weighted average of component latencies is a **mean, not a quantile** — under the hit-50 ms / miss-250 ms model p99 = 250 ms. **Keyed note:** the ~48% excludes a separately-priced retrieval-skip saving (earlier ~55%); the capstone runs one configuration — 35% cache, p99 TTFT ~250 ms — stated identically in §26.3, §26.8, and Table 26-2.

utilization, tensor-core utilization, HBM bandwidth utilization, NVLink utilization, memory-capacity occupancy — and which one matters is set by the workload's dominant constraint, not by the hardware (Ch. 8). Under an SLO-satisfying state, a GPU can sit at very different utilizations depending on whether the workload is prefill-bound (compute) or decode-bound (bandwidth/memory). The architect's question is therefore not "is utilization high enough?" but **"which resource is saturated when the SLO is satisfied, and does the pattern keep the fleet the right side of that saturation?"** In this instance 68% SM utilization with p99 within SLO is healthy headroom; in a heavier-throughput workload the same 68% could mean under-provisioning. State the SLO-bound resource, not a bare percentage.

CHAPTER A.

Appendix A — 2026 Frontier Architecture Signals: Four Open-Weight Model Families

Snapshot: 2026-08-30 technical evidence snapshot, with a separately labeled September 27 addendum. The body of this handbook works through durable mechanisms — tokens, memory floors, rooflines, parallelism, KV arithmetic — that do not change. But the industry moves, and the whole point of an architecture handbook is to stay current. In 2026 the four frontier open-weight MoE families — DeepSeek-V4, Kimi K3, Qwen3.8-Flash-Next, and GLM-5.3-Flash — all shipped within a short window. Reading them together is not a product tour; it is a single, coherent signal about where the mechanisms in this book are heading. Every mechanism below maps back to a chapter and an architectural decision.

Appendix verified through 2026-08-30 (source snapshot compiled through 30 August 2026). This appendix is a snapshot of the frontier as of that date, compiled from the first-party technical reports and model cards listed in A.10 (First-hand Sources). The models, their parameter counts, constants, and claims are vendor-reported and move quickly. **This is a hard boundary for the four-family comparison and the First-hand Sources list: nothing released after 2026-08-30 is reflected in either, and model specifications and vendor claims should be reverified against the cited first-party sources before any procurement or deployment decision — and once more immediately before publication, because these are among the fastest-changing values in the book.** (The single 2026-09-27 post-snapshot sidebar in A.6 is explicitly boxed as outside this compile envelope and is not part of the four-family

comparison.) It illustrates how to apply the framework to a changing frontier; it is **not** a current model leaderboard.

The four families at a glance (the scope of this appendix). The four-family comparison that this appendix's figures (Fig A.1, A.2) and its First-hand Sources list (A.10) rest on comprises **exactly these four open-weight frontier MoE families — and only these four**:

1. **DeepSeek-V4** (A.3) — DeepSeek; MIT; hybrid CSA+HCA attention; 1M-token context. (V4-Pro and V4-Flash are *variants within this one family*, not additional families.)
2. **Kimi K3** (A.4) — Moonshot; vendor-reported first open 3T-class; KDA + AttnRes; stable-LatentMoE activating 16 of 896 routed experts.
3. **Qwen3.8-Flash-Next** (A.5) — Alibaba Qwen; Gated DeltaNet + QSA; N-gram embedding split.
4. **GLM-5.3-Flash** (A.6) — Z.ai; first natively multimodal GLM-5; sparse+linear attention.

Every other vendor/model mention in this appendix is either (a) a **sub-model / variant of one of these four families** (e.g. DeepSeek-V4-Flash, DeepSeek-V4-Pro) — named only to clarify a family member, never as an additional family — or (b) a **post-snapshot item explicitly outside the four-family comparison** (the single 2026-09-27 Ornith-1.5-397B observation in A.6, boxed as such). Neither is part of the four-family comparison, its comparative figures, or its First-hand Sources list; read them as subfamilies or out-of-scope side notes, never as a fifth family in the comparison.

A.1. The Signal in One Paragraph

A striking number of 2026 frontier models — four open models we surveyed — converge on a **second-order architectural pattern**, which we read as an interpretation rather than an established historical fact. We should be precise about *what kind* of gain each lever delivers. The common error is to read architecture innovation as raw capability. In our interpretation, it is mostly **efficiency** (more context, less cost per token) that comes out of the attention and MoE changes below, not intelligence. The capability story — reasoning, post-training, test-time compute — lives elsewhere (A.8), and carries at least as much of the frontier's real progress. We separate the two explicitly.

*Definition of "active" (what counts in the activated-parameter numerator, and what it does **not** mean).* Here "active" (equivalently "activated") means the parameters that participate in the forward pass for a given token: the routed experts dispatched for that token, the shared/always-on experts, and the attention and embedding/head parameters that run for every token. It is **not** the same as any of these: (a) **resident** parameters — the full expert + attention + embedding fabric that must be held in memory (or sharded/offloaded), which is the total-parameter count, not the active count; (b) per-token **FLOPs**, since activation count is not a proxy for compute cost under softmax-routing and layered dispatch; (c) KV or attention-state **sparsity**, which is a different quantity (see the GQA/MLA discussion in Ch 7); and (d) **achievable serving speed** — a low active fraction does **not** translate proportionally into a faster served rate, because total-weight residency, expert routing/traffic, and




FIGURE A.1: 2026 frontier MoE extreme sparsity: four open models, total vs activated parameters, and active fraction in single digits [1P]

attention cost still dominate. The four families use different expert counts, dispatch schemes, and embedding splits (Qwen's N-gram embedding table is counted in total but is offloadable), so the active fractions below are comparable only *after* this definition is fixed; the numbers are not a drop-in cross-model ranking of serving cost. (Here "active" contrasts total vs activated parameters — see the model/MoE discussion in Ch 3 and the GQA/MHA KV discussion in Ch 7.) [1P]

Frontier MoE sparsity in 2026. Kimi K3 is the extreme case: 2.8 T total / 104 B active (~3.7% active); DeepSeek-V4-Flash 284 B/13 B (~4.6%); GLM-5.3-Flash 320 B/18 B (~5.6%); Qwen3.8-Flash-Next 125 B/6 B (~4.8% — backbone-only ratio*: the denominator is the 125 B backbone; the separate 51 B n-gram embedding and 4 B MTP modules are excluded from both numerator and denominator, so this is a* backbone *fraction, not a fraction of the complete deployed parameter inventory). Active-parameter fraction in each of these four frontier MoE families is in the single digits — the anchor for the Ch10 expert-parallelism serving calculus. [1P] arXiv 2606.19348; arXiv 2607.24653; HF Qwen/Qwen3.8-Flash-Next; HF zai-org/GLM-5.3-Flash]*

Three **efficiency levers** every 2026 frontier family pulled:

1. **Hybrid attention as the new KV lever — an efficiency lever, not (by itself) a capability lever.** Every frontier model re-engineered attention to shrink long-context cost at the mechanism level — compressed/sparse hybrids (DeepSeek CSA+HCA), delta+sparse (Qwen Gated DeltaNet + QSA), delta/residual (Kimi KDA + AttnRes), sparse+linear (GLM). KV cache is no longer a fixed per-token constant we only quantize; it is a design surface the model vendor already optimized. The intended benefit is to preserve useful model capability while reducing long-context inference cost and/or extending practical context length — indispensable, but it does not by itself make the model smarter. Capability gains come from the post-training/reasoning stack in A.8.
2. **MoE sparsity went extreme — the capacity-per-FLOP lever.** Active-parameter fractions fell to single digits (Kimi 104B of 2.8T; Qwen 6B of 125B). In our reading, one could argue MoE is a *larger* architectural innovation than attention: it lets a lab grow knowledge/capacity without proportionally growing FLOPs per token. That is why the 2026 open landscape is heavily MoE-oriented. Expert parallelism and fused cross-expert communication moved from a footnote to a serving-critical capability.
3. **Efficiency is a first-class result, not an afterthought.** Training-stable optimizers (Muon) and post-training RL (GRPO, async RL) are now reported as core architecture, not tooling.

These three form the *cost/context* ledger of the frontier. The *capability* ledger — reasoning, post-training, test-time compute, agent harness — is where most of the qualitative improvement actually lives (A.8). Distinguishing efficiency levers from capability levers is the architect's first move when reading any new model card.

A.2. How to read this appendix: Observed, Interpretation, Hypothesis

This appendix surveys vendor-reported material, so we are careful to separate three layers of statement that are easy to blur — especially in a fast-moving field full of first/"most-efficient"/3T-class claims:

- **Observed** — what the vendor's technical report or model card actually states (e.g., "DeepSeek-V4 reports a reduced KV footprint"). This is [1P] *fact about the claim*, not the same as the third layer.
- **Interpretation** — our read of what architectural mechanism the report demonstrates (e.g., "the KV reduction suggests the model changes how attention stores state"). This is analysis, ours, and could be wrong.
- **Hypothesis** — a prediction about consequence we draw for serving architecture (e.g., "we expect long-context serving to become more memory-comfortable at equal context"). This is a testable (a hypothesis), not a fact.

When we write "a number of frontier models converge" or "one could argue MoE is a larger architectural innovation," read those as **Interpretation / Hypothesis** — defensible reads of the frontier signal, not independent measurements. Vendor numbers stay tagged [1P] and flagged verify-on-own-hardware; our reads sit one register lower and should be read with the same skepticism we ask of any vendor claim. The practical rule: *if it's a percentage from a report, it's Observed [1P]; if it's a claim about what the industry trend means, it's ours — treat it as analysis, tune it against the reader's real workload.*

Mapping onto the book's evidence taxonomy. These three reader-friendly layers are an on-ramp to, not a replacement for, the three-axis taxonomy used throughout the book (provenance × epistemic status × measurement status): Axis 1 provenance [1P]/[2°]/[LAB]/[ILLUSTRATIVE] × Axis 2 status [FACT]/[DERIVED]/[ASSUMPTION]/[HYPOTHESIS]/[UNRESOLVED], with Axis 3 riding along.

- **Observed** ↔ [1P] · [FACT] — the vendor's stated claim, a fact *about the claim*.
- **Interpretation** ↔ [DERIVED] — the book's own analysis, a derivation from the evidence. (Where the book's taxonomy would label it [ILLUSTRATIVE], note that; the appendix uses "interpretation" only as plain prose for a derived read, never a separate sanctioned status.)
- **Hypothesis** ↔ [HYPOTHESIS] — a testable prediction, exactly the taxonomy's [HYPOTHESIS].
- **Measurement status** ↔ Axis 3 — ANALYTICAL / ILLUSTRATIVE / MODELED / MEASURED (or [UNMEASURED] where the stage is not yet determined): how far the number has climbed the measurement-status hierarchy, defined in the Sources, Method, and Reproducibility chapter.

The appendix's labels are the human-friendly framing; the three-axis labels are the precise book-wide convention. They should never conflict.

This is a dated field guide, not an evergreen ranking. The four-family comparison is a snapshot as of the 2026-08-30 cutoff (with the single 2026-09-27 boxed observation, A.6). A later edition re-verifies the vendor reports and *may* change the families, numbers, or the comparison; the ranking here is not a permanent verdict. **Reproduction status** is recorded per family in the First-hand Sources list (A.10): each entry carries its source URL/identifier, the version and release date where known, and the verification status (whether the claim is vendor-reported [1P] pending independent check, or independently verified). Where a number has not been independently validated, it is flagged — do not treat a model-card figure as an audited measurement. The vendor-fact / author-interpretation / hypothesis layers above, plus the per-family reproduction status, are the four columns a reader needs; a `sources.csv` manifest (source URL, accessed date, model variant, reported baseline, verification status) accompanies the repository's `render/` material for the fast-changing Appendix A claims.

A.3. DeepSeek-V4 — Making Long Context Cheap by Re-Architecting Attention

Decisive fact [1P] — arXiv 2606.19348; HF deepseek-ai/DeepSeek-V4-Pro: V4-Pro is 1.6 T total / 49 B activated, V4-Flash 284 B / 13 B activated, both 1M-token context, MIT-licensed. Its hybrid attention combines Compressed Sparse Attention (CSA) and Heavily Compressed Attention (HCA). At 1M context, DeepSeek reports **~27% (Pro) / ~10% (Flash) of V3.2's single-token inference FLOPs and ~10% / ~7% of its KV cache**.

What this means for the architect (ties to Ch7 Memory, Ch8 Compute). In our reading of the vendor reports, this is a strong confirmation that *KV-per-token is a moving target*. Chapter 7's arithmetic (per-token × context) is a floor for a given architecture; DeepSeek shows the *constant factor itself* can be cut ~10× without changing the model's parameter count. The architectural decision shifts from "how much KV memory does this context need?" to "which KV scheme does this model use, and is its vendor-published saving reproducible on my serving stack?"

A.4. Kimi K3 — Vendor-Reported First Open 3T-Class Model, and the MoE-Sparsity Extreme

Decisive fact [1P] — arXiv 2607.24653; HF moonshotai/Kimi-K3: 2.8 T total / 104 B activated, native vision, 1M context. Built on **Kimi Delta Attention (KDA)** + **Attention Residuals (AttnRes)**, with **Stable LatentMoE** activating just **16 of 896 routed experts** per token. Claims **~2.5× scaling efficiency** over Kimi K2. Weights are QAT-trained from SFT onward with **MXFP4 weights / MXFP8 activations**. Full weights are released — per the vendor, the first open 3T-class model.

What this means for the architect (ties to Ch3 Model, Ch10 Parallelism). A model whose *total* size is 2.8 T but whose *activated* footprint is 104 B is a clear illustration of Ch3's total-vs-activated distinction and Ch10's expert-parallelism doctrine. Serving Kimi K3 requires accommodating the **2.8 T total parameter fabric** across the serving system (the full expert set must reside somewhere unless

an explicit offload/load-on-demand architecture is used) while only ~104 B parameters participate in the computation of a given token. The architectural problem is therefore simultaneously one of **total weight residency/distribution** and **active-weight communication/computation** — sharding and scheduling the expert fabric, plus the KV for our context. The decision surface is expert-parallel communication and fused cross-expert kernels, not raw capacity.

A.5. Qwen3.8-Flash-Next — A Vendor-Framed Qwen4 Architecture Preview, Prioritizing Cost-Performance

Decisive fact [1P] — HF Qwen/Qwen3.8-Flash-Next; GitHub QwenLM/Qwen3.8-Flash-Next: 125 B total / 6 B activated, plus a separate 51 B of **N-gram embedding** parameters (offloadable to host memory). Native 262 K context (YaRN to 1M). **Hybrid attention: Gated DeltaNet (GDN) + Qwen Sparse Attention (QSA)**, where QSA operates at the *micro-block* level; **Gated Residual** widens the residual stream; 512 MoE experts (10 routed + 1 shared per token); Muon + AdamW. Reported training cost ~1/9 of Qwen3.7-Plus.

What this means for the architect (ties to Ch3, Ch5 Model Selection, Ch16 TCO). Qwen's N-gram embedding split is, in our reading, the most architecturally novel item: it shows that *parameter scaling and compute scaling can be decoupled. Our interpretation, not a vendor-claimed serving strategy* — the model card reports the N-gram embedding table as a parameter-scaling technique; the specific implication we draw here, that a large embedding table can trade host-RAM bandwidth for on-GPU capacity when the compute budget is the binding constraint, is an architectural inference we make from the reported design, not something the vendor demonstrated as a general serving strategy and should be treated as such. This refines the model-selection calculus in Ch5: an architect comparing candidates now weighs not just total/active params but heterogeneous memory (on-GPU weights vs offloadable embeddings) and its serving overlap.

A.6. GLM-5.3-Flash — Vendor-Reported First Natively Multimodal GLM, Efficiency-Branded

Decisive fact [1P] — HF zai-org/GLM-5.3-Flash; arXiv 2602.15763: 320 B total / 18 B activated, 1M native context, 131 K output. Per the vendor, the first natively multimodal model in the GLM-5 series (text/image/video). Hybrid **sparse+linear attention** (first in the series per the vendor) with ~3× attention-compute and ~4.4×KV cache reductions; Manifold-Constrained Hyper-Connections (mHC); W8A8 quantization with mixed-cache (INT8/FP8/BF16); Encode-Prefill-Decode serving. MIT weights. Z.ai positions it as approaching Claude Opus 4.8 on coding/agentic at ~1/10 the price.

What this means for the architect (ties to Ch7 Memory, Ch8 Compute, Ch19 Agentic). GLM's coupling of hybrid attention with *native multimodality* shows the model border is remaking: "LLM" and "vision/audio model" are converging in a single weight set, which changes workload characterization (Ch4) — a multimodal prompt has a different token/KV profile than text-only. And

mHC + attention-mixing being reported as *scaling-efficiency* results reinforces Ch8's point that compute arithmetic is architecture-specific, not universal.

Post-snapshot observation (recorded 2026-09-27; outside the 2026-08-30 compile-date envelope). Beyond the four families above, *Ornith-1.5-397B* (released 2026-08-19 by DeepReinforce / `ornith-ai`) ships as another natively multimodal frontier model: 397 B MoE, ~262 K context, MIT weights, image-input via the inherited Qwen3.5 vision tower. We verified the image-input path end-to-end with a live API call carrying a base64-encoded PNG as `image_url` content: the model's own reasoning trace referenced the rendered pixels (a white-square test and a red/blue half-image test both answered correctly). **This is a [LAB] author observation — a single first-person capability *probe*: one API call, one ad-hoc image fixture, which establishes only that one function path (image input) is *reachable*.** It is **not a benchmark, not comparable across models, and not reproducible without re-running the call**: the exact model/API ID, sampling settings, prompt/image fixtures, and (credential-redacted) API response are not published as a reproducibility capsule, and the probe says nothing about benchmark quality, throughput, or cost. It must **not** be read as evidence for any comparative claim about Ornith-1.5-397B relative to the four families (which it is not a part of), nor as a measurement of capability or quality. It is recorded as a single-path capability hint and cited as an observational sidebar, **not** promoted into the four-family comparative figures or the First-hand Sources list above, both of which retain the 2026-08-30 compile-date stamp. Treat as a hint that the natively multimodal frontier continues to widen between snapshots — exactly the trajectory the four-family narrative above predicts.

A.7. What This Means for the Handbook's Canonical Arithmetic

The book's canonical scenario is a 70B dense FP16, ~9.2K-token RAG workload on 8×H100. The 2026 frontier does not invalidate it — it *refines* the interpretation an architect should carry:

- The **KV constant** (Ch7: ~2.62 MB/token FP16; ~1.3 MB/token 8-bit) is the canonical full-MHA conservative upper-bound teaching model. (The 8-bit figure is the raw tensor byte-halving bound: ~1.31 MB/token, exactly 50% of BF16, which is what the fleet-sizing chapters use. vLLM's widely cited 54% [S6] is a decode inter-token-latency slope from its Llama-3.1-8B Table 3 — a latency metric, not a memory ratio; there is no vendor-measured FP8 memory footprint, and any allocator block/metadata overhead is not vendor-measured. The 8-bit KV constants are [ILLUSTRATIVE][DERIVED].) Hybrid-attention models cut it 4–10× at the mechanism, so "context fits on N GPUs" must be re-derived per model, not looked up once. [1P]
- The **roofline** (Ch8) still holds; what changed is where a frontier model's prefill/decode ride it. Vendor-reported FLOP/KV reductions are [1P] first-party claims but not yet independently reproduced — an architect should re-run Ch8's measurement on the candidate model before betting capacity. *Evidence status: first-party vendor claim; deployment-specific result not independently reproduced.*




FIGURE A.2: Vendor-reported KV/FLOP reduction. Each model's reduction is relative to its OWN stated predecessor/reference, NOT a shared cross-model baseline. Rendered as one row per reported model (DeepSeek V4's two variants listed separately), each with its own baseline column and its own 100% ⟶ ~X% reduction, so there is no shared bar scale to compare across; no row for Kimi K3 / Qwen3.8-Flash-Next (no predecessor-relative baseline reported). from 1P claims — DeepSeek V4 arXiv 2606.19348; GLM-5.3-Flash arXiv 2602.15763 / HF zai-org

Same message as Fig 7.1's GQA line, taken to the frontier: the per-token KV and FLOP "constants" of Chapter 7/8 are not universal — they are the canonical full-MHA conservative upper-bound teaching model, which hybrid attention re-architects down at the mechanism. Each row is a model's vendor-reported ratio of its own stated reference (e.g. DeepSeek V4 vs V3.2); they do not share a common denominator, so they must not be read as percentages of a single baseline. The canonical 70B dense full-MHA model is the book's teaching floor, not the denominator for these percentages. An architect who re-derives them per candidate model avoids both over- (sizing a 7% KV model as if it were 100%) and under-provisioning. Values are vendor-published [1P], not yet independently reprofiled on a serving stack (see A.7).

- The **MoE memory decision** (Ch10) is jointly dominated by total-weight residency/sharding, active-parameter compute, KV footprint, and expert-fabric communication. Extreme sparsity reduces per-token compute; it does not eliminate total-weight residency, which still scales with the full parameter count unless experts are explicitly offloaded or sharded. [1P]

None of this changes the book's *mechanisms*; it changes the *constants* an architect plugs into them. This is exactly why we wrote the arithmetic as verifiable, first-principles reasoning rather than as a fixed catalog of numbers.

A.8. Where 2026 Capability Actually Comes From (beyond Architecture)

A recurring error — easy to fall into after reading four new model cards — is to attribute frontier gains to the attention mechanism splashed across the front page. The industry is converging not just on *architectures* (MoE + efficient attention + very long context) but on a *multi-layered recipe* in which architecture is one ingredient, and arguably not the dominant one. A qualitative decomposition of the recipe:

Lever	Primary effect
Post-training / RL / reasoning	Capability (a major source in current frontier systems)
Test-time compute	Capability on hard tasks (more compute on hard problems)
Training data + optimization	General capability
MoE / parameter scaling	Capacity per FLOP
Attention innovation	Context + efficiency (makes the above affordable)
Inference / runtime optimization	Cost + latency
Agent harness / tool use	Real-world task completion
Multimodal architecture	New modalities

A frequently underestimated layer is the one the model card almost never shows: post-training. Two models with broadly similar architectures and pre-training can end up materially different when one went through mediocre post-training and the other excellent. The recipe — the same families every lab now runs — is what carries much of the qualitative gap:

- RLVR / reinforcement learning for reasoning
- synthetic reasoning data

- verifier-based training
- preference optimization
- curriculum learning
- tool-use training and agent trajectories
- coding-specific trajectories
- multimodal reasoning
- long-horizon interaction training

This is why architecture alone never tells an architect how good a frontier model is, and why the decision can no longer stop at "which model" — the marginal capability may live in the post-training and the runtime that wraps it.

From a single model to a whole system. The earlier stages (Transformer, Efficient, MoE) are *efficiency-led* — they make inference affordable and raise capacity-per-FLOP. The later stages (Reasoning, Test-Time Compute, Tool-Using, Agent, Agent System, Agent Fleet) are *capability-led* — they raise effective intelligence. [DERIVED]

This chain is the spine of this handbook — from a single model's tokens (Ch1–9) to parallelism (Ch10), serving (Ch11–16), and finally the fleet of specialized models and agents (Ch17–26). It also explains why two models with broadly similar base architectures can have very different practical intelligence (post-training/reasoning), and why an agent runtime can lift real-world performance without changing model weights at all: **model intelligence ≠ system intelligence anymore.**


A.9. The Frontier Question: Where Should Intelligence Live?

The most useful lens for an AI Solution Architect in 2026 is not "which attention mechanism does the model card list?" but *where the intelligence and the compute budget should be placed*:

The placement ladder. Every host layer that can carry intelligence is a place the architect may choose to push capability or cost; this book gives the arithmetic and decision framework for each (Ch3/7/8 weights & attention, Ch10 MoE routing, Ch19/21 post-training, Ch8/20 test-time, Ch19/24 tools, Ch17–20 runtime, Ch18/20 fleet). [ILLUSTRATIVE][DERIVED]

Every host layer maps to chapters in this book:

- **Inside weights** (dense capacity) — Ch3 Model, Ch8 Compute
- **Inside attention** (context / efficiency) — Ch7 Memory, Ch8 Compute
- **Inside MoE routing** (capacity per FLOP) — Ch10 Parallelism
- **Inside post-training** (reasoning, RL, verification) — Ch19 Agentic, Ch21 AI Factory
- **Inside test-time search** (adaptive inference, more compute on hard tasks) — Ch8 Compute, Ch20 Fleet-Level Optimization
- **Inside tools** (compute allocated via a harness) — Ch19 Agentic, Ch24 Red/Green Team
- **Inside the agent runtime** (persistent state, runbooks, execution control) — Ch17–20, Ch24



From a single model to a whole system — the spine of this handbook (Appendix A.8). Approximate era markers (≈) are loose chronological signals, not release dates. [ILLUSTRATIVE][DERIVED]

FIGURE A.3: A conceptual layering of frontier AI systems. The dates are approximate era markers, not a rigorously established chronology, and the vertical stacking is a *layering* (which capabilities sit on which substrate), not a causal lineage: a later layer does not require the one below it, and the eras overlap. Read it as "what exists at each stage," not "what caused what."




FIGURE A.4: Where should intelligence live? The horizontal bands are a **design choice** (which layer owns which capability), not a ranking of superiority: a lower band is not "better" or "worse" than a higher one, and the boundaries shift with the workload, the trust model, and the cost/latency budget. Read each band as "what we put here and why," not "what is best here."

- **Across a fleet of specialized models** — Ch18 Operating Multiple Models, Ch20 Fleet-Level Optimization

Deciding where intelligence lives — rather than which attention variant a model card lists — is the actual job of an AI Solution Architect. The frontier of 2026 makes that explicit: DeepSeek-V4-Flash vs Qwen3.8-Flash vs a fleet of specialized agents on a 2×DGX cluster are no longer merely *model* choices; they are *placement-of-intelligence* choices whose economics this handbook's chapters give the tools to evaluate.

A.10. First-hand Sources (all [1P])

- DeepSeek-V4: technical report arXiv:2606.19348; model card https://huggingface.co/deepseek-ai/DeepSeek-V4-Pro org https://github.com/deepseek-ai
- Kimi K3: technical report arXiv:2607.24653; model card https://huggingface.co/moonshotai/Kimi-K3 https://github.com/moonshotai
- Qwen3.8-Flash-Next: technical report https://github.com/QwenLM/Qwen3.8-Flash-Next/blob/main/tech_report.pdf model card https://huggingface.co/Qwen/Qwen3.8-Flash-Next
- GLM-5.3-Flash: technical report arXiv:2602.15763; model card https://huggingface.co/zai-org/GLM-5.3-Flash https://github.com/zai-org/GLM-5

Compiled 2026-08-30 from the models' official technical reports and first-party model cards; all parameters/claims are vendor-reported [1P] and per this handbook's discipline carry a verify-on-own-hardware caveat.

> **Citation integrity / frozen-snapshot note (reader-facing).** Every external identifier in this list — the arXiv IDs (arXiv:2606.19348, arXiv:2607.24653, arXiv:2602.15763) and the huggingface.co / github.com model-card and repo URLs — was captured against the frozen **2026-08-30** source snapshot for this edition. arXiv IDs and model cards are versioned and can be withdrawn, revised, re-uploaded, or re-pointed, so re-open a citation before relying on it: an identifier that now resolves to a *different* version than the one compiled on 2026-08-30 would change the [1P] claims this appendix draws on. The required checks and resolved-artifact hashes for this edition are recorded in the release `sources.csv` / release manifest (see the Sources chapter), not re-derived here — the four-family comparison is intentionally pinned to the frozen 2026-08-30 snapshot and is **not** a current model leaderboard.

Glossary of Acronyms and Common Terms

Model fundamentals

- **tokenization / tokenizer** — splitting text into the model's vocabulary of integer IDs; a token is whatever the model's *tokenizer* decided to carve the text into (learned BPE-style merges), so token counts are tokenizer-dependent — run the model's own tokenizer on representative traffic rather than a characters-per-token rule of thumb (Ch 1).
- **embedding** — the lookup that maps each discrete token ID to the dense vector the model actually operates on; the pipeline is text → tokenizer → IDs → embedding → attention → KV cache (Ch 1).
- **attention** — the mechanism that compares each token's query (Q) against every prior key (K) and blends the values (V) by those scores; a processed token's K/V never change, which is why they are cached (the KV cache) rather than recomputed each step (Ch 2).
- **logits** — the model's raw, unnormalized per-vocabulary scores at a generation step; the sampler turns them into the next token (Ch 2).

Inference and serving

- **TTFT** — time to first token: latency from request to the first output token (prefill-dominated).
- **TPOT** — time per output token: steady-state decode latency per token.
- **ITL** — inter-token latency: the decode phase's per-token lag; the book treats TPOT (steady-state) and ITL (per-token, incl. any measured inter-token gap) as the same canonical per-token metric and writes them "TPOT/ITL." Where a measurement distinguishes them, treat ITL as the per-token value that includes any queueing/scheduling gap between emitted tokens, i.e. a tail-sensitive complement to bounded TPOT.
- **tail latency** — latency at the high percentiles of the distribution (p95/p99), set by the slowest requests rather than the typical one; the SLOs in this book are written against the tail (TTFT/TPOT p95/p99), so a median that meets its budget says nothing about the tail (Ch 20).
- **prefill** — the pass that processes the prompt tokens and builds the KV cache/state. Often the

compute-bound pass in high-arithmetic-intensity regimes, but the compute- vs bandwidth-bound classification is a function of model, sequence length, batch, kernel, and device operating point (Ch 8, §8.2). Long-context and large-batch regimes can shift where it sits on the roofline.

- **decode** — the autoregressive pass that generates the output one token at a time from the built state. Often memory-bandwidth-bound at low batch (small arithmetic intensity per emitted token), but not invariably so; large-batch and bandwidth-friendly regimes can move it. Refer to the operating-point discussion in Ch 8, §8.2 for the conditional, not unconditional, classification.
- **goodput** — useful throughput: throughput that meets the latency/quality bar, discounting failures.
- **P/D disaggregation** — running prefill (P) and decode (D) on separate pools/services.
- **continuous batching** — scheduling new requests into a running decode batch so the GPU is kept busy token-by-token rather than waiting for an entire batch to finish; raises throughput at some latency cost.
- **chunked prefill** — splitting a long prompt's prefill into sub-blocks interleaved with decode work, so a long prompt does not monopolize the GPU and stall latency-sensitive decode.
- **FlashAttention** — an I/O-aware attention kernel that tiles/fuses the Q·K·V computation through fast on-chip storage, reducing HBM traffic while preserving the same attention mathematics.
- **PagedAttention** — a memory-management strategy for the KV cache that allocates key/value blocks in non-contiguous pages, reducing fragmentation and enabling near-full memory utilization.
- **speculative decoding** — a draft model proposes a candidate sequence that the target model verifies in parallel, accepting matching tokens to raise effective throughput at the cost of draft + verification compute.
- **MFU** — model FLOPs utilization: achieved FLOPs as a fraction of hardware peak.
- **RPS / QPS** — requests per second / queries per second: a *rate* of incoming work, the primary input to a capacity model.
- **concurrency** — the number of requests *in flight* (being served) at the same time; distinct from *concurrent users*, which is a population measure, and related to the arrival rate by Little's law (in-flight $\approx \lambda W$) (Ch 17, 20).

Memory and attention

- **KV cache** — the keys/values of past tokens retained so attention need not recompute.
- **KV quantization** — reducing the *bytes* per K/V element (e.g. FP16 $\rightarrow$ FP8), not the number of K/V entries; the canonical raw byte-halving is 2.62 $\rightarrow$ 1.31 MB/token (exactly 50%), a raw-array figure that is *not* a vendor-measured engine footprint, and the vLLM FP8-KV blog's 54% is a decode-ITL *latency slope*, not a memory ratio (Ch 2, 6, 7; S6).
- **KV offloading** — moving some KV state out of GPU HBM (to host DRAM/SSD), trading capacity against transfer latency; it does *not* shrink the state itself (that is quantization), and the

cited 2–22× TTFT range is a particular warm-cache reuse benchmark, not a generic cold-cache improvement (Ch 2, 6; S7).

- **GQA** — grouped-query attention; **MQA** — multi-query attention; **MHA** — multi-head attention; **MLA** — multi-head latent attention: a compressed per-token KV (K/V stored in a low-rank latent space), so KV per token still grows with context but at fewer bytes/token than full MHA (Ch 1, 8; App. A).
- **APC / RadixAttention / prefix cache** — caching of shared prompt prefixes to avoid recomputation.
- **prompt caching** — the broader system/provider term; the book uses it to mean *reusing the KV of a shared prompt prefix across requests*, so it is *not* a separate mechanism from prefix caching above (Ch 2) — the provider-facing name for the same reuse, kept as its own entry because providers document and bill it as a feature.
- **cache hit / miss** — a cache *hit* serves a request (or a shared prefix) from cached state without recomputing it; a *miss* must be computed (or re-prefilled); the hit ratio (hits ÷ requests) is the FACT that the prefix- and semantic-cache arithmetic starts from (Ch 15, 19, 26).
- **TTL** — time-to-live: how long a cached entry stays valid before it must be refreshed or evicted; the semantic response cache uses a 5-min TTL, and its hit ratio is measured at TTL=T (Ch 26).
- **LRU** — least-recently-used: the eviction policy that discards the least recently used cache entry first (Ch 26, Table 26-2).
- **HBM** — high-bandwidth memory: the large, relatively slow-capacity memory attached to a GPU (distinct from fast on-chip SRAM).
- **arithmetic intensity** — FLOPs moved per byte read from memory (FLOP/byte); the quantity that determines whether a kernel is compute-bound or memory-bound.
- **MoE** — mixture of experts: a sparse model that routes each token to a subset of expert layers, cutting compute-per-token without reducing the parameter count or (necessarily) the KV cache.

Parallelism and flows

- **TP** — tensor parallelism; **PP** — pipeline parallelism; **DP** — data parallelism; **EP** — expert parallelism; **FSDP** — fully sharded data parallelism (shards the model weights, gradients and optimizer state across ranks, reducing per-rank memory vs full-replica DP); **CP** — context parallelism (shards the sequence dimension across ranks when a single context is too long for one rank).
- **all-reduce** — the collective that *aggregates* (e.g. sums) a tensor across ranks so every rank ends with the same reduced value; used to share gradients, activations, or states.
- **RQO** — Reasoned Quality Optimization: a structured process that optimizes a quality metric (e.g. answer relevance) by iterating over prompts, retrieval, and model choices, rather than treating quality as a fixed model property (Ch 25 §6).

System and economics

- **SLO** — service-level objective (the latency/availability target committed to); **SLA** — service-level agreement.
- **TCO** — total cost of ownership (capex + opex + staff + energy over a horizon).
- **PUE** — power usage effectiveness: total facility power over IT equipment power.
- **ADR** — architecture decision record: a short write-up of a design choice and its rationale.
- **RAG** — retrieval-augmented generation: augment generation with retrieved context.
- **PIES** — prompt-injection exposure surface: the count of distinct prompt-pattern classes an adversary can submit through all user-facing entry points, with "distinct" fixed by an author-chosen normalized-edit-distance threshold stated before any number appears; a local, author-defined operational proxy for one deployment, not a standardized or portable security metric (Ch 24).
- **NED / normalized Levenshtein (normalized edit distance, NLE)** — string distance scaled to [0,1] by the longer string's length; it is the deduplication criterion behind PIES (two probe patterns count as the same class within NLE $\leq$ 0.25) (Ch 24).
- **MTTR** — mean time to recover from a bad release: mean time to detect + roll back; the factory loop's core reliability number (Ch 21).
- **FAISS** — a vector-similarity index library for nearest-neighbor embedding retrieval; the RAG corpus-policy example moves the retrieval index from a pure FAISS index to a provenance-aware store (Ch 24).

Notation used in the arithmetic

- **PFLOP** — peta-FLOPs; **FLOP/param** — floating-point operations per parameter per forward pass (≈2 for a matmul).
- **roofline** — a capacity model that plots achievable performance (FLOP/s) against arithmetic intensity; a kernel sits on a bandwidth-bound line below the ridge point and a compute-bound plateau above it. The *ridge point* is the arithmetic intensity at which a machine transitions from memory-bound to compute-bound (peak FLOP/s ÷ peak bandwidth).
- **GB vs GiB** — decimal vs binary units: 1 GB = 10^9, 1 GiB = 2^{30}. The book uses decimal GB unless stated.
- **CDF** — cumulative distribution function: $F(x)$ is the probability a draw is at most x; the capstone's two-point latency model gives $F(50) = 0.35$ and $F(250) = 1.0$, which separates the 180 ms mean from the 250 ms p99 (Ch 26).
- **tokens/s** — throughput in tokens per second; **token/request** — average tokens per request (a workload property).
- **κ (kappa)** — per-token KV cache footprint in bytes/token (e.g. ≈2.62 MB/token FP16 for the canonical full-MHA 70B; $\kappa = 2 \times n_{\text{layers}} \times d_{\text{hidden}} \times$ bytes). Used in the KV-residency and concurrency arithmetic (Ch 7, 17).
- **ρ (rho)** — the effective throughput fraction after load-balancer and scheduling effects (the

fraction of theoretical peak a host actually sustains under the chosen LB/fleet configuration); used with the capacity formula (Ch 17).

Where an acronym is ambiguous or its definition is load-bearing, the body defines it at first use and the relevant chapter develops the consequence.

References

The body text cites sources as [S1]–[S7]. Each entry below gives the work, its venue, and a stable link (an arXiv identifier or a first-party page). These are the *primary* sources for the system-level mechanisms the book describes; hardware figures and prices are additionally flagged in-text for verification against current vendor documentation.

1. **Continuous batching (Orca).** G.-I. Yu, J. S. Jeong, G.-W. Kim, S. Kim, and B.-G. Chun, "Orca: A Distributed Serving System for Transformer-Based Generative Models," in *Proc. 16th USENIX Symposium on Operating Systems Design and Implementation (OSDI '22)*, USENIX Association, 2022, pp. 521–538. `https://www.usenix.org/system/files/osdi22-yu.pdf`
2. **PagedAttention / vLLM.** W. Kwon, Z. Li, S. Zhuang, Y. Sheng, L. Zheng, C. H. Yu, J. E. Gonzalez, H. Zhang, and I. Stoica, "Efficient Memory Management for Large Language Model Serving with PagedAttention," in *Proc. 29th ACM Symposium on Operating Systems Principles (SOSP '23)*, 2023. arXiv:2309.06180. `https://arxiv.org/abs/2309.06180`
3. **Prefix caching (SGLang / RadixAttention).** L. Zheng, L. Yin, Z. Xie, C. Sun, J. Huang, C. H. Yu, S. Cao, C. Kozyrakis, I. Stoica, J. E. Gonzalez, C. Barrett, and Y. Sheng, "SGLang: Efficient Execution of Structured Language Model Programs," 2023. arXiv:2312.07104. `https://arxiv.org/abs/2312.07104`
4. **P/D disaggregation (Mooncake; see also Splitwise).** Y. Qin et al., "Mooncake: A KVCache-centric Disaggregated Architecture for LLM Serving," 2024. arXiv:2407.00079. `https://arxiv.org/abs/2407.00079`; and P. Patel, E. Choukse, C. Zhang, A. Shah, Í. Goiri, S. Maleki, and R. Bianchini, "Splitwise: Efficient Generative LLM Inference Using Phase Splitting," in *Proc. ISCA*, 2024. arXiv:2311.18677.
5. **Speculative decoding (DFlash).** J. Chen, Y. Liang, and Z. Liu, "DFlash: Block Diffusion for Flash Speculative Decoding," 2026. arXiv:2602.06036. `https://arxiv.org/abs/2602.06036`
6. **FP8 KV quantization (vLLM).** vLLM project, "The State of FP8 KV-Cache and Attention Quantization in vLLM," vLLM blog, 2026-04-22. `https://vllm.ai/blog/2026-04-22-fp8-kvcache`. (Reports FP8-vs-BF16 *inter-token-latency (ITL) slope ratios*, a decode-*latency* metric; Table 3, "FP8 slope (% of BF16)," gives Llama-3.1-8B at 54%. It also describes FP8 as halving KV

storage in the usual tensor-level sense.) *This blog does NOT supply a measured per-token KV* memory *footprint for the 80-layer hidden-8192 full-MHA geometry, and its 54% is a latency slope, not a storage ratio.* The book therefore does NOT claim a vLLM-measured "1.42 MB/token" memory figure; it uses the *raw tensor* FP8 value (1 byte/element ⇒ 2 x 80 x 8192 = 1,310,720 B ≈ 1.31 MB/token, exactly 50% of BF16). Any block-allocation / scale-offset / fragmentation overhead is *not* vendor-measured here and must be established by a deployment benchmark before it is used as a capacity coefficient.

7. **KV cache offloading (vLLM).** vLLM project, "Inside vLLM's New KV Offloading Connector," vLLM blog, 2026-01-08. `https://vllm.ai/blog/2026-01-08-kv-offloading-connector`. (This is a *distinct* blog from the FP8-quantization one. Its reported TTFT reduction of 2–22× comes from a particular warm CPU-KV-cache-hit / cache-reuse benchmark for that connector and published model/prompt configuration; it is *not* a generic offloading speedup that applies to a cold cache or to every workload, and memory block layout here depends on the model, attention backend, and block size.) This source is cited as [S7] for the TTFT-offloading claim, separately from the FP8-KV blog [S6].

Primary sources for the major mechanisms in Chapters 1–26. Beyond the seven system-level [Sn] tags cited in the body, the following carry the mechanisms the handbook describes (transformer architecture, the roofline, attention kernels, parallelism, quantization, mixture-of-experts, and benchmarking). They are the provenance layer for the corresponding mechanism discussion.

- **The transformer.** A. Vaswani et al., "Attention Is All You Need," in *Advances in Neural Information Processing Systems (NeurIPS) 30*, 2017. arXiv:1706.03762. `https://arxiv.org/abs/1706.03762`
- **The roofline model.** S. Williams, A. Waterman, and D. Patterson, "Roofline: An Insightful Visual Perspective on Peak, Memory Bandwidth, and Arithmetic Intensity," *Communications of the ACM* 52(4):65–76, 2009. `https://doi.org/10.1145/1498765.1498785`
- **FlashAttention.** T. Dao, D. Y. Fu, S. Ermon, A. Rudra, and C. Ré, "FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness," in *NeurIPS 35*, 2022. arXiv:2205.14135; and T. Dao, "FlashAttention-2: Faster Attention with Better Parallelism and Work Partitioning," 2023. arXiv:2307.08691.
- **Grouped-query attention (GQA).** J. Ainslie, J. Lee-Thorp, M. de Jong, Y. Zemlyanskiy, F. Lebron, and S. Sanghai, "GQA: Training Generalized Multi-Query Transformer Models from Multi-Head Checkpoints," in *EMNLP*, 2023. arXiv:2305.13245.
- **Mixture-of-experts (sparse).** N. Shazeer et al., "Outrageously Large Neural Networks: The Sparsely-Gated Mixture-of-Experts Layer," in *ICLR*, 2017. arXiv:1701.06538; W. Fedus, B. Zoph, and N. Shazeer, "Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity," *JMLR* 23, 2022. arXiv:2101.03961; and A. Q. Jiang et al., "Mixtral of Experts," 2024. arXiv:2401.04088.

- **Tensor and pipeline parallelism.** M. Shoeybi et al., "Megatron-LM: Training Multi-Billion Parameter Language Models Using Model Parallelism," 2019. arXiv:1909.08053; and Y. Huang et al., "GPipe: Efficient Training of Giant Neural Networks using Pipeline Parallelism," in *NeurIPS 32*, 2019. arXiv:1811.06965.
- **Quantization.** B. Jacob et al., "Quantization and Training of Neural Networks for Efficient Integer-Arithmetic-Only Inference," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018, pp. 2704–2713, arXiv:1712.05877. (Leading author is Benoit Jacob, not the author of the binary-network paper of the same period; `https://openaccess.thecvf.com/content_cvpr_2018/html/Jacob_Quantization_and_Training_CVPR_2018_paper.html`.) Also E. Frantar et al., "GPTQ: Accurate Post-Training Quantization for Generative Pre-trained Transformers," in *ICLR*, 2023. arXiv:2210.17323; and T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient Finetuning of Quantized LLMs," in *NeurIPS 36*, 2023. arXiv:2305.14314.
- **Speculative decoding (canonical).** Y. Leviathan, M. Kalman, and Y. Matias, "Fast Inference from Transformers via Speculative Decoding," in *ICML*, 2023. arXiv:2211.17192; and C. Chen et al., "Accelerating Large Language Model Decoding with Speculative Sampling," 2023. arXiv:2302.01318.
- **Benchmarking a model, not a leaderboard.** P. Liang et al., "Holistic Evaluation of Language Models (HELM)," *TMLR*, 2023. arXiv:2211.09110; and L. Zheng et al., "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena," in *NeurIPS 36*, 2023. arXiv:2306.05685.

Appendix A first-party model cards and reports. The frontier-model figures in Appendix A are drawn from the vendors' own technical reports and model cards (all [1P]): DeepSeek-V4 (report and card), Kimi K3 (report and card), Qwen3.8-Flash-Next (report and card), and GLM-5.3-Flash (report and card). The links are listed at the end of Appendix A and must be re-opened against the current versions, as the appendix's content is a dated snapshot.

Other provenance. Home-lab measurements (where the book marks that it measured, rather than sourced) are reproducible from the build scripts in the accompanying repository. General knowledge of inference, memory, and attention behavior not tied to a specific system claim does not carry an [Sn] tag.

Sources, Method, and Reproducibility

This handbook marks every number with an evidence label so a reader never has to guess the provenance, the epistemic status, or the measurement status of a figure. The book publishes exactly *one* authoritative taxonomy, and it has **three orthogonal axes**: Axis 1 source provenance (where the number comes from), Axis 2 epistemic status (what the number claims to be), and Axis 3 measurement status (how far the number has climbed the measurement-status hierarchy). Labels of the form [PROVENANCE][EPISTEMIC-STATUS] combine one item from each of Axes 1 and 2; the Axis-3 measurement status rides with that pair (e.g. [LAB][MEASURED]) or stands alone (e.g. a bare [ANALYTICAL]). The axes are orthogonal — each answers a different question, so an item from one axis never substitutes for an item from another, and the measurement-status hierarchy below is Axis 3 of this taxonomy, not a second, competing scheme.

Axis 1 — Source provenance: where the number comes from.

- **[1P] First-party / primary source.** A vendor technical report, model card, or official documentation. These are the model's own stated parameters, benchmarks, and limits.
- **[CANONICAL SCENARIO]** The book's own internally-defined canonical workload and model (Ch 4, Table 4-2). This is an *internal* source the book sets up so its arithmetic is anchored and reproducible; it is author-defined, *not* external first-party evidence. Used to distinguish "where this number comes from inside the book" from "[1P]" (a real vendor source).
- **[2°] Secondary source.** A third-party measurement, survey, or synthesis (e.g. an independent benchmark or a community write-up). Requires independent verification.
- **[LAB]** Measured on the author's own hardware. These are home-lab measurements, not production hardware, and are used to illustrate mechanisms and orders of magnitude.
- **[ILLUSTRATIVE]** A worked-example or scenario input chosen to demonstrate a calculation, not a reported measurement. It is a number we assumed so the arithmetic would be concrete.

Axis 2 — Epistemic status: what the number claims to be.

- **[FACT]** Stated by the source as a fact (e.g. a parameter count or a vendor benchmark).

- **[DERIVED]** Computed by arithmetic from stated inputs. The derivation is our work; the inputs come from a source item.
- **[ASSUMPTION]** A deliberately chosen scenario input (a number we picked so a worked example would be concrete), distinct from a hypothesis because it is not a claim about the real workload at all. It pairs with a provenance of [ILLUSTRATIVE]: [ILLUSTRATIVE][ASSUMPTION].
- **[HYPOTHESIS]** A reasoned expectation that has not yet been validated. Deliberately kept, because it distinguishes what we know from what we only expect.
- **[UNRESOLVED]** An open item that could not be pinned to a first-party source at the time of writing. Such items are flagged in the text and *must be re-checked against current vendor documentation before any procurement or deployment decision*; they are precisely the numbers most likely to have drifted. In evidence-label lines and copy-ready templates, the parenthetical "(to be verified)" is the plain-language form of [UNRESOLVED] and means exactly the same thing.

Axis 3 — Measurement status (the measurement-status hierarchy). Where Axis 1 says *where* a number came from and Axis 2 says *what* it claims to be, Axis 3 says *how far* it has climbed the measurement-status hierarchy — a third, orthogonal axis, folded into this one authoritative taxonomy rather than published as a separate scheme. A number in this book can fall into one of four stages, and they are not interchangeable. Reading "ceiling" as "achieved" is the single most consequential mistake an architect can make with these figures. The same convention is applied in the fleet and TCO synthesis tables (Chs. 12, 17, 20, 22).

Stage	What it is / what it is not
ANALYTICAL	an arithmetic or physical upper bound from stated inputs (e.g. KV occupancy ceiling C, or the per-host prefill rate). Valid for *planning*; *not* an achieved rate.
ILLUSTRATIVE	a worked-example value on stated assumptions, chosen to make the method concrete; not a measurement or a vendor claim.
MODELED (offered-load)	the result of a simulation or queueing model on a synthetic or recorded load curve; reflects the model, not a measured system.
MEASURED (SLO-goodput)	the only stage that demonstrates a deployed system meets a rate and a tail-latency SLO on real hardware. Requires a load test with a recorded trace.

In the text and figures, an [ANALYTICAL], [ILLUSTRATIVE], [MODELED], or [MEASURED] tag states the stage; where the stage is not yet determined, the value is marked [UNMEASURED] and cannot be treated as achieved throughput. A capacity ceiling becomes a deployment claim only after the [MEASURED] stage is reached. Author-run probes (a one-off API call to probe a capability) are

labeled [LAB] and are evidence of *one* functional path, not a model benchmark or an [1P] vendor claim; they never double as a vendor validation.

Why [ILLUSTRATIVE] appears on two axes. It is the same worked-example number viewed from two axes that answer different questions: on Axis 1 it is the *provenance* (an input we chose so the arithmetic would be concrete), on Axis 3 it is the *stage* (a worked-example value, not a measurement or a vendor claim). The two uses never conflict — a worked-example input is by definition at the ILLUSTRATIVE stage — so [ILLUSTRATIVE] is one token shared by two orthogonal axes, not an ambiguity.

Scope of the labeling. The label is mandatory for every *load-bearing* quantitative claim — a number that a later calculation, sizing decision, or comparison depends on; the Axis-3 stage rides with every load-bearing claim whose stage is known. Such a claim carries the labels directly (inline) or via an identified table or section that states them for every row. Purely illustrative or rhetorical numbers that no later calculation depends on (e.g. a round figure used only to make a sentence concrete) may carry the labels in the surrounding prose rather than inline. This is the unambiguous exception the preface refers to: the test is whether a downstream number depends on it.

Reading a label. [1P][FACT] means a vendor-stated fact; [1P][DERIVED] means arithmetic we computed from a first-party input; [LAB][FACT] means a home-lab measurement; [ILLUSTRATIVE][ASSUMPTION] means a number we chose so the worked example would be concrete — it is not evidence of anything about the real workload. The Axis-3 measurement status reads alongside them: a bare [ANALYTICAL] means an arithmetic upper bound from stated inputs (valid for planning, not an achieved rate); [MODELED] means the result of a simulation or queueing model (it reflects the model, not a measured system); [MEASURED] means a load test with a recorded trace that demonstrates an achieved rate and tail-latency SLO on real hardware; [UNMEASURED] means the stage is not yet determined, so the value cannot be treated as achieved throughput; and the combined [LAB][MEASURED] pairs the Axis-1 provenance (our own hardware) with that Axis-3 stage. When only one axis is shown, the other is implied by the surrounding sentence (e.g. a bare [DERIVED] carries the status, with the provenance stated in prose).

The [S#] keys are a bibliography index, not a provenance. A label such as [S6][1P] combines a source *reference key* ([S6], pointing to an entry in the References chapter) with a provenance on that source ([1P]). The [S#] key is not a fifth provenance item; it merely says *which* reference the first-party or secondary evidence comes from. A composite label always carries at least one provenance item in addition to any [S#] key.

Prices, models, and benchmarks are a moving target. The model names, parameter counts, context limits, prices, and throughput figures in this book are a dated snapshot. They vary with the provider, region, commit/on-demand/spot status, hardware SKU, precision and sparsity mode, quantization, batch and concurrency, software stack, GPU count and topology, kernel version, warmup procedure, and percentile method used. **Re-verify before acting.**

Reproducibility. The book's quantitative examples are worked from the stated inputs in the surrounding text; the home-lab measurements were made on the author's own hardware under the configuration described in the chapter. Where a number is flagged as unresolved, the workspace did not have a first-party source at hand, and we say so rather than present an estimate as fact.

Home-lab scope. The author's lab is a CPU-only workstation (Intel i5-3210M, four cores, 15 GB RAM). Measurements reflect that environment and the reduced-precision / small-model regime; they are used to *illustrate* mechanisms and orders of magnitude, not to characterize production hardware. Kernel-performance and throughput figures from public sources are to be treated as vendor-reported until re-measured on the target cluster. **No H100/H200 production-performance claim in this book should be interpreted as a home-lab measurement unless explicitly labeled as such.**

Code and data availability. The build scripts that produce this book (text → LaTeX → PDF, plus the figure generators) are in the accompanying repository. The figures are generated where possible (matplotlib and a hand-drawn diagram pipeline), so the arithmetic and layouts are inspectable rather than opaque artifacts.

Claim-to-source ledger. Every load-bearing number traces to a source by a fixed path, so a reader can re-derive it without guessing: (1) a [S#] key resolves to the matching entry in the References chapter, which gives the work, venue, and a stable identifier (arXiv id or first-party URL); all such sources were accessed as of the build date (v20260913). (2) a number derived from the canonical scenario traces to Ch 4, Table 4-2 (the single set of inputs every chapter cites). (3) the calculation itself is either the in-text arithmetic (stated with its operands) or the figure's generator script in the repository (`render/fig_*.py`), which is reproducible from the stated inputs. A [1P] first-party claim is cited to its source but is a vendor statement, not an independent re-measurement; per the "moving target" note above, re-verify it against the current source before acting. This ledger is the mechanism; it does not substitute for the independent re-derivation and print proof that the release gates require.

Canonical parameter-and-unit ledger. Every derivative fleet/TCO/memory table cites this single ledger for its geometry, precision, and byte conventions, so a number is never silently re-based between the raw tensor overhead, the cache-block allocation, and the serving-engine observed footprint. The canonical scenario (Ch 4, Table 4-2) is full multi-head attention (MHA), 80 layers, hidden width 8192, BF16/FP16 KV, on an 8 × H100 host. The ledger is split into two blocks: the *geometry and byte arithmetic* and the *planning and engine observations*.

Geometry and byte arithmetic	**Value**	**Convention**
Host nominal HBM (canonical)	∼640 GB (8 × H100)	*nominal/advertised* aggregate capacity (8 × 80 GB), *before* any runtime reserve, allocator overhead, or per-rank fragmentation; the practical *allocator* budget is lower and per-rank, so 640 GB is an upper bound, not usable memory
Model weight bytes (70B, FP16)	∼140 GB	2 B/param, dense
KV, raw per token (full-MHA, 8-bit/FP8)	$2 \times 80 \times 8192 \times 1 = 1{,}310{,}720$ B $= 1.25$ MiB $= 1.31$ MB	raw array, 1 B/element; exactly 50% of BF16 by byte-halving. No block/metadata overhead.
KV, raw per token (full-MHA, BF16/FP16)	$2 \times 80 \times 8192 \times 2 = 2{,}621{,}440$ B $= 2.5$ MiB $= 2.62$ MB	raw array; no block or overhead
KV, allocated per request (FP16, canonical 9.5K)	∼24.9 GB	per-request allocated residency within the SLO
KV, allocated per request (FP8, canonical 9.5K)	∼12.5 GB	per-request allocated residency at the raw 1.31 MB/token, byte-halving basis; *not* a vendor-measured engine footprint. "Allocated" metadata/block overhead is *not* yet measured (see status note). *Do not treat the raw byte-halving as a measured resident footprint.*
KV, observed ITL slope ratio (vLLM, [S6])	FP8 ≈ 54% of BF16	*decode inter-token-latency slope* ratio, a *latency* metric from the vLLM FP8-KV blog [S6] (Llama-3.1-8B, Table 3). This is *not* a memory/CV-size ratio and is *not* used as a capacity coefficient in this book. See [S6].

Planning and engine observations	**Value**	**Convention**
Concurrent requests/host (KV ceiling)	$C \approx 17.5$ (integer floor 17)	arithmetic allocation bound from usable HBM ÷ per-request KV
Service time per request	∼8.6 s (∼1.08 s prefill + ∼7.5 s decode)	uncontended request-level estimate, not measured under concurrency
Per-host request rate (planning)	$C/W \approx 2.0$ req/s	upper-order planning estimate, not observed goodput
GQA KV reduction	∼8× (one config)	geometry-dependent sensitivity, not a universal fact

Reference-geometry convention. Any isolated per-token KV or memory figure in this book (e.g. *'2.62 MB/token'*, the raw FP8 *'1.31 MB/token'*, or a GB figure) refers to the *canonical reference geometry* — full multi-head attention (MHA), 80 layers, hidden width 8192, BF16/FP16 — unless the surrounding text or caption names a different geometry. This is the deliberately pessimistic upper bound from Ch. 1/7. It is *not* a typical 70B-model KV footprint: a real 70B model may use GQA, MLA, or hybrid attention, which reduce KV per token, so an architecture-specific figure must be derived for that model's own attention shape rather than inheriting the MHA number. A decimal GB/binary GiB distinction is stated wherever a precise mount depends on it; where only an order of magnitude matters, the base is given explicitly.

Two conventions apply throughout. (1) "KV raw per token" always means the un-allocated array product, stated in base-2 (MiB) and base-10 (MB) as appropriate; "KV allocated" or "measured footprint" includes the metadata and cache-block overhead. Do not conflate them. (2) A precision adjective is always attached to its subject ("FP16 *weights*" vs "FP8 *KV*"), never implied. (3) An architecture-specific advantage (GQA ∼8×, MLA, hybrid) is a sensitivity for that configuration only and is not inherited by a different model.

Edition history. This is the release-information panel for the PDF produced from build `v20260913`. A later content change requires a new build identifier and a new row here — except a dated post-cutoff addendum carried under its own revision identifier and listed in the Appendix addenda row; a re-render of the same source changes only the generation timestamp, not the identifiers. Any subsequent revision increments the build identifier and appends its change log here.

Field	Value / note
Edition	First edition, 2026 (title page)
Build identifier	`v20260913` (content edition, 2026-09-13)
Evidence cutoff	2026-08-30 (single cutoff; see Preface)
Appendix addenda	one boxed 2026-09-27 post-snapshot observation (App. A, A.6), outside the cutoff envelope; its own revision identifier is "v20260913+addendum-20260927"
Provenance record	The release manifest pins: (1) the *source commit* (the "Source revision" row, full SHA), (2) the *figure/code-generator* revision as the same committed SHA plus each figure generator's path hash (`sha256` of `render/fig_*.py` at that commit), (3) the *build command* and *environment* (`bash render/build.sh`, Python/matplotlib versions), and (4) the *final-file SHA-256*, which is recorded in the *external signed release manifest* that accompanies the published PDF – *not* in the PDF's own metadata, because a file's digest cannot be stored inside that same file. All figures are built from committed inputs, and the post-cutoff addendum is separately labeled and is *not* folded into the 2026-08-30 evidence-only snapshot. See the repository release manifest for the hashes.
Generation date	recorded in PDF metadata (the date this source was rendered to PDF)
Source revision	repository commit `da0befd42bc006d6bb328d5bfb0126888acab904` (full SHA; see the Preface release log)

Caption style convention. A figure caption follows a three-part order — (1) a one-sentence takeaway of what the figure shows, (2) a succinct 'Scope/source:' line naming the geometry, assumptions, and evidence basis, and (3) any measurement warning — intended to make the figure scannable without deleting a qualification. A detailed derivation or cross-chapter reconciliation lives in the section body or a nearby note, not in the caption. Where a caption is observed to repeat a body paragraph at length, it is shortened to this convention rather than stripped of its provenance/scope condition.

Presentation of evidence tags. Inline provenance and status tags are carried on a number because a later calculation or decision depends on it (load-bearing). When the *same* tag applies to a contiguous run of related values or an entire section, the book does not repeat it on every line: it states the tag once in a boxed per-section *Assumptions & evidence* note (or in a table footnote that names the whole group), and the reader applies it to every value the note governs. A tag is always shown inline on a number that carries a *different* status from its neighbours, so the reader can spot a status change without re-reading the surrounding prose. Never strip a source/status control; group it, so it stays legible rather than fragmenting the sentence.

The Architecture Worksheet

How to use this

Every chapter of this book turns a vague ask into a defensible number. This worksheet is the reverse: a single reusable worksheet that applies the whole loop to the architect's own workload. Fill it in row by row; each row is a decision in Chapters 1–26. When a row is empty, that is precisely the gap to investigate next. The canonical workload box (Chapter 4) shows what a fully-filled row looks like; the two derived rates most often needed are given under its table.

All quantities are the architect's own — traceable, verifiable, and stated in the evidence taxonomy (provenance: [1P] first-party, [canonical scenario] the book's own workload, [2°] reputable secondary, [LAB] home-lab, [ILLUSTRATIVE] worked-example; epistemic status: FACT / DERIVED / ASSUMPTION / HYPOTHESIS / UNRESOLVED; measurement status — the third, orthogonal axis — ANALYTICAL / ILLUSTRATIVE / MODELED / MEASURED / UNMEASURED). See the Sources, Method, and Reproducibility chapter for the full three-axis definition.

Row 1 — Requirement

Business objective: _____

Constraints (privacy, region, ops, budget): _____

Row 2 — Workload

Quantity	Measured / target	Evidence
Registered users (or seats)		
Concurrency (% active)		
Average request rate (rps)		
Peak request rate (rps)		
Input tokens / request		
Output tokens / request		
TTFT budget / SLO		
TPOT budget / SLO		

Row 3 — Model

Quantity	Value	Evidence
Model class (dense / MoE, total params)		
Active params / token		
Weight precision; bytes/param		
Weight residency		
KV precision; KV per token		
KV residency (weights + KV)		

Row 4 — Compute & memory

Quantity	Derived	Evidence
FLOPs / token (prefill, decode)		
Arithmetic intensity (FLOP/byte)		
Ridge point of the hardware		
Compute- or memory-bound?		
MFU (measured)		

Row 5 — Architecture implication

So the architecture does X, and not Y, because: _____

Parallelization strategy: _____

Batching / serving choices: _____

Row 6 — Decision record

Decision: _____

Alternatives rejected (and why): _____

Consequences / monitoring to add: _____

Row 7 — Validation & operations

Field	Recorded value
Quality acceptance metric (eval set; pass/fail threshold)	
Benchmark result (which suite / harness)	
p95 / p99 latency at target load	
Cost per 1M tokens (or per request)	
Failure mode observed	
Monitoring trigger (when to page)	
Revalidation date	

Row 8 — Economics, reliability & recovery

Field	Recorded value
Burst policy (what peak demand is shaped / queued vs served)	
Failure scenario assumed and capacity reserved (N−1 headroom, spare)	
Pricing basis: $/GPU-hr, depreciation, ops, power	
Fully-loaded monthly fleet cost (peak and average)	
Availability / SLO error budget (target 9s/"nines")	
Test-load trace ID (recorded load generator config, if any)	
Rollback trigger (when to revert the decision)	
ADR reference (which decision record / date)	

Following up

Keep one sheet per significant architecture decision, and re-check it when the workload's numbers change. A machine-readable (Markdown) companion to this worksheet ships in the repository (`render/architecture_worksheet.md`), so a practitioner can copy, fill, and version it alongside the corresponding ADR rather than transcribing the printed page. The worksheet's sequence — requirement, workload, model, compute/memory, architecture, decision, validation & operations — is the same loop Chapter 22 makes explicit, and the same reason the Patterns Library in Chapter 26 exists: a decision recorded with its evidence can be reused, while a decision recorded without it must be re-derived every time. Rows 7–8 close the loop by pinning what was measured, at what load, the economics and failure policy assumed, and when it must be re-verified.