Let Us Brew an AI Model

What Tiny Language Models Can Actually Learn When Given One Job

Version 20261001

Zhiqi Tao

Building a small language model is relatively easy. Determining what it actually learned is the hard part.

COPYRIGHT © 2026 ZHIQI TAO
All rights reserved.

License. This work is licensed under a *custom source-available* license, set out in full in the **LICENSE** file at the root of the companion repository, which governs. The **book text, diagrams, and figures** may be freely read, studied, shared, and redistributed non-commercially with attribution; **commercial republication or sale of the book text requires prior written approval from the author**. The **code examples and the companion repository** are released under that same source-available license: you may use, adapt, and reuse the code in your own projects for personal and non-commercial purposes, and redistribute it with attribution, provided the copyright and license notices stay intact; **commercial use of the code, or republication of any part of this work, requires the author's written permission**. The book is not an open-source text. For permission, contact Zhiqi Tao (zhiqi.tao@gmail.com).

In short: *read, study, and share the book text and the code freely for personal, non-commercial use with attribution; do not sell them, or republish this work as a product, without the author's written permission. The LICENSE file in the companion repository governs.*

The work is provided "as is", without warranty of any kind.

About the author. Zhiqi Tao works on AI systems, with a focus on building and evaluating small models in controlled settings. This book grew out of a running laboratory notebook: build a tiny model, give it one job, and find out precisely what it can and cannot learn — with the failure ledger as much a part of the result as the successes.

Companion repository and errata. The code, scripts, configurations, run manifests, scored datasets, and regeneration scripts that reproduce every experiment in this book live in the companion repository, which is public at `https://github.com/zhiqitao/let-us-brew-an-ai-model` under the release tag `v20261001` on release commit `a45a881158ed076f615f6d3bc2e72640dc5cdced` (full hash; verified as the commit the release tag points to — the single re-

lease identifier; the reproduction quick start and the exact release identifiers are in Appendix C). This PDF was built from repository commit `af32fb8b1798f83553c0f5078fd34b62063b864d` (the PDF build commit, stated separately from the release commit above). To report an error or request an erratum, open an issue at https://github.com/zhiqitao/let-us-brew-an-ai-model/issues.

Preface

This book is a controlled empirical investigation into what a small language model can actually learn when it is given exactly one narrowly defined, objectively testable job.

The task: read a natural-language programming request and produce a Python program, which is then executed against hidden tests.

Along the way we build a laboratory: a controlled world (a sandbox), a teacher (a semantic data generator), a judge (an execution-based evaluator), and rivals (simple baselines). The model is the instrument. The experiment is the subject. And the honest territory includes the moments the model falls flat — and the moment we discovered that our own measuring stick was broken, not the model.

Who this book is for

This is an accessible experimental case study, not a build-from-scratch transformer textbook. It is written for readers who are comfortable reading (or willing to skim) Python and who want to see how to set up a small, honest evaluation of a tiny model — and, more than that, how easily a number from such an experiment can be misread. No GPU or deep-learning background is required to follow the conceptual argument; a little Python helps with the code listings. Nothing here needs a large model or a large machine — the whole investigation runs on a single-laptop CPU.

What the book claims (and what it does not)

We set the scope deliberately narrow, and we repeat it throughout. All the results are measurements on **one synthetic task** (natural-language request → single Python function), **one architecture family** (a small decoder-only transformer), **one training regime** (CPU, fixed budgets), and parameter counts up to roughly 30M. We do not claim a universal law about tiny models, and we do not claim to have identified the internal cause of the limits we observe. We claim only: *under this setup, here is what was measured, here is what did not move, and here is what remains open.* If a reader takes nothing else from the book, we hope it is the discipline of saying exactly what a measurement establishes and leaving the mechanism open when the controls have not identified it.

How to use the book

- **Read the body for the argument**. Each chapter opens with a concrete image before the mechanics.
- **Use the appendices for reproducibility**. Appendix A shows the generator; Appendix B is the failure ledger; Appendix C is the experiment registry that ties every number to a run ID, config, and artifact.
- **Run it yourself if you like**. The scripts, configs, and a release tag are in the companion repository (see Appendix C). On this CPU-only setup, the pilot trains in minutes; the larger models take longer.

The honest payoff is not "small models are inadequate." It is a precise map of where the boundary sits under our tests — and the many ways a promising-looking number can be an artifact of how we measured it.

Contents

I The Question **1**

1 Let Us Brew an AI Model 2

2 What Does It Mean to Learn? 5

3 Give the Model One Job 9

II Build the Laboratory **15**

4 Build a World We Can Control 16

5 Build the Teacher 29

6 Build the Judge 38

7 Build the Rivals 46

III The First Brew **53**

8 The Smallest Brain 54

9 The First Brew 63

10 Does It Actually Work? 70

IV How Capability Scales **80**

11 How Much Data? 81

12 How Much Brain? 96

13 Same Data, More Diverse Data 105

V Catching the Model Cheating **118**

14 The Model That Memorized 119

15 New Words, Same Problem 127

16 Same Pieces, New Combination 139

17 Red-Team the Judge 154

VI Break It **160**

18 Teaching It Something New 161

19 The Cost of Capability 170

VII What Did We Learn? **182**

20 The Capability Map 183

21 The Model Wasn't the Point 201

A An Annotated Tour of the Generator 216

B The Failure Ledger 226

C The Experiment Registry 239

D Glossary 283

List of Figures

2.1 The four evaluation questions 7

3.1 The one job 10

4.1 The whole apparatus 21

4.2 The two gates 23

5.1 The teacher 30

6.1 The judge 40

7.1 The rivals 47

8.1 The smallest brain 55

9.1 The brew loop 65

11.1 Data scaling — corrected balanced sweep 88

12.1 Model size vs composition 98

12.2 Illustrative prompts on five selected checkpoints 99

13.1 Diversity at equal count (corrected: 0.950 vs 0.743) 107

13.2 Coverage is not a held-out family test 113

15.1 Surface generalization — corrected 2x2 factorial 132

16.1 Same operators, different programs 140

18.1 Sequential vs joint training 163

18.2 Sequential, joint/interleaved A+B from start, and true replay-after-A (not run) 165

PART I.

The Question

CHAPTER 1.

Let Us Brew an AI Model

A tiny model is given one job. It reads a sentence — *"write a function that takes two numbers, a and b, and returns their sum"* — and it writes back the right Python:

```
def solve(a, b):
    return a + b
```

We run the hidden tests. It passes. If this were a demo, we'd move on.

But this is not a demo. So before we celebrate, we ask the one question that turns this whole book into an experiment rather than a party trick:

Why did it get it right?

Maybe it genuinely learned what that sentence *maps to* — that "sum" and "a and b" are English for `a + b`. Maybe it memorized that exact sentence from training. Maybe it noticed this was nearly identical to an example it saw and copied the answer. Maybe a much dumber machine — one that does nothing but look up the closest training example — could have done the same thing. Or maybe our test wasn't as hard as we thought.

Making the model answer is easy. **Knowing why it answered is the whole game.**

1.1. One job, and a way to check it

We give the model exactly one, narrow, checkable job:

> **read a plain-English programming request → produce a working Python program**

Note where the work happens. The model's whole job is a *mapping*: request in, program out. It never executes anything itself — no arithmetic runs inside it. The arithmetic runs only when we take the program it emitted and execute it in the sandbox, against the hidden tests.

Then we *run* that program against hidden tests. That single choice — executable output plus hidden tests — is what makes this a real experiment instead of a showcase, because it hands us the things a language-model toy usually lacks:

- inputs we control,
- code we can actually execute,
- an objective pass/fail,
- data we can generate in any quantity,
- difficulty we can dial up or down,
- tests we can keep hidden from the model,
- splits we can design to expose memorization,
- audits we can run to catch shortcuts.

1.2. What this book is (and isn't)

This is not a transformer tutorial. It is not a guide to chatbots, agents, or coding assistants. It is a careful, honest investigation of a single question:

> **How much structured programming capability — in practice, how much of the *mapping from a plain-English request to a correct program* — can a small language model**

actually learn, and how do we tell whether it *learned* it, rather than memorized it or found a cheap shortcut?

1.3. The part that's actually hard

The natural guess is that *building* a small model is the hard part. It isn't. Once the laboratory works, a ~0.9 million-parameter model will reliably turn a handful of programming sentences into correct Python — in-distribution, that is nearly easy.

The hard part is everything after: proving it didn't just copy, checking whether it still works when the *words* change but not the *computation*, testing whether it can *combine* two things it knows into a third thing it's never seen, and auditing our own evaluator to make sure the number it reports means anything.

This book builds a laboratory, runs those tests, and reports — plainly — what happened. Including the moments the model fell flat, and the moment we discovered our own measuring stick was broken, not the model.

The model was the instrument. The experiment was the subject. Let's brew.

CHAPTER 2.

What Does It Mean to Learn?

We're going to use a word a lot in this book: *learned*. Before we do, we have to be honest about what it means — because "the model learned to add" is a sentence people say all the time, and it's usually hiding a big assumption.

2.1. A simple way to think about it

Imagine a child who aces a worksheet of addition problems. Every problem is like "4 + 3 = ?" and the child gets them all right. We'd be tempted to say "the child can add."

But there are two very different ways to get that perfect score:

1. The child *understands addition* — show them "37 + 58" and they solve it, because they know how to add any two numbers.
2. The child *memorized the exact answers* — they've seen these exact problems before and just remember that "4 + 3 = 7," but hand them a problem they've never seen and they freeze.

A perfect worksheet grade can't tell these two apart. **The worksheet is a bad test**. Only a *new* problem can.

This is the entire premise of the book in one image. Our model gets a perfect-ish worksheet sometimes. The question is always: would it pass the *new* problem?

2.2. What "learned" means here

So we define it narrowly and honestly. A model shows **learned capability** when, to the degree the evidence supports:

1. **It gets better as it trains** — the loss falls, and the thing we care about reliably improves.
2. **It works on examples it never saw** — not just the ones in training.
3. **It survives harmless changes** — different variable names, different wording, a different way of saying the same instruction.
4. **It can combine things it knows** — put two learned pieces together in a new arrangement, not just repeat an arrangement it already saw.
5. **Simpler explanations have been ruled out**. The mundane alternatives — memorization, copying a near-duplicate, a template, a leaked test, a buggy evaluator — must be tested and rejected.

We are deliberately **not** asking whether the model "really understands" in a philosophical sense. We're asking narrower, answerable things: does it generalize? to what? and could a dumber mechanism explain the result?

2.3. The four questions of generalization




FIGURE 2.1. The four evaluation questions

The four questions make the point explicit. Each asks something distinct about a result, and we never collapse them into a single number. They are not a ladder — passing one does not establish the next; a model can answer the second question but fail the third and the fourth.

This is the book's organizing idea. It is four distinct questions about a result: from "could this just be remembering?" to "can it combine things it never saw combined?" and they must be reported separately.

Question 1 — Memorization. The model reproduces something it saw in training: an exact example, an exact constant, a familiar phrase, a near-duplicate. *Question: could this just be remembering?*

Question 2 — Distributional generalization (same task, new examples). The model works on a new instance of the same kind of problem. *Question: does it work on problems it hasn't seen before?*

Question 3 — Surface generalization (same problem, different surface). The computation is identical, but the *outer layer* changes: new numbers, new variable names, reworded instruction, harmless distractors. *Question: does it survive changes that shouldn't matter?*

Question 4 — Structural generalization (new combination). The model must combine pieces it knows into something that never appeared in training. It learned A, B, and C separately — can it do A *sandwiched inside* B, or A followed by C? *Question: can it put things together, or only repeat what it already saw?*

Those four headings are the book's canonical level names, in order: **Memorization**, **Distributional generalization**, **Surface generalization**, **Structural generalization**. We use these names from here on so that every later experiment can be filed under exactly one of them.

A rule we'll follow strictly: never mash these four into one number. A model that scores 90% on familiar problems and 0% on a reworded version has not "generalized" — it memorized the phrasing. One number would hide exactly the thing we care about.

2.4. The recurring question: "how did it cheat?"

Because we refuse to trust a single score, every experiment asks the same skeptical question:

> **How could the model have gotten this without learning what we think it learned?**

The usual suspects are always on the table: memorized templates, memorized constants, memorized name patterns, wording quirks, unbalanced data, train/test leakage, near-duplicates, retrieval, a weak evaluator, hardcoded answers, hidden-test leakage.

Every major experiment therefore ends with a **shortcut audit**, six steps: (1) the suspected cheat, (2) why it could explain the result, (3) a control test, (4) what the control found, (5) what that rules out, and (6) what's still unresolved.

That audit — not the headline number — is the book's signature. It's the difference between "the model works" and "we know why the model works."

CHAPTER 3.

Give the Model One Job

Before we can run any experiment, we have to pin down the task so precisely that a machine can carry it out and we can score it objectively. Vague tasks give vague answers; a task with concrete inputs, runnable outputs, and hidden tests gives crisp, checkable answers.

A well-designed exam question is the model to build toward. It's not enough to say "write a program about numbers." We need: exactly what the input is, exactly what the program should do, and exactly how to check if it's right. That's what we're about to define.

3.1. The task

The model receives a **natural-language specification** of a programming task and must produce a **Python program** that solves it. That program is then executed against hidden tests.




FIGURE 3.1. The one job

The contract is simple: a natural-language specification in, a program out, and a set of hidden tests to grade it against. Everything else follows from it.

Concretely, the model sees something like:

> "Write a function that takes two numbers, a and b, and returns their sum."

and must produce:

```
def solve(a, b):
    return a + b
```

We score it by running that program against a set of hidden test cases (inputs with expected outputs) and checking whether the program's output matches, semantically, for every case.

One clarification worth making now, because later chapters lean on it: a *fresh* hidden test value is a new input to the **program**, never a new input to the **model**. The model sees the specification once and emits one program; the hidden tests then call that program with values the model was never shown. So a record whose task ID and test values are new is new to the *evaluator* — it is not an extra example for the model, and it gives the model nothing new to learn from.

3.2. The task schema

Every task is described by a small, formal schema — the ground truth that drives everything. The key insight is that **one semantic record generates all three** things we need: the reference program, the natural-language spec, and the hidden tests. That way there is far less drift between "what the task is" and "how we ask for it" and "how we test it" than if each were authored separately. "**Less drift" is not "no drift"** — because all three derive from the same semantic record, a mistake in that record would be shared by all three (a correlated error), so consistency here is a reduction in risk, not a guarantee.

The semantic core captures the operation and its arguments:

```
{
  "operation": "add",
  "args": [{"name": "a", "type": "int"}, {"name": "b",
  "type": "int"}],
  "output_type": "int"
}
```

From that single record, the teacher generates: 1. the reference Python (`def solve(a,b): return a+b`), 2. a natural-language specification (in one of several phrasings), 3. a set of hidden tests (ordinary, zero, negative, boundary, large cases).

3.3. The pure-function constraint

For the pilot we constrain the generated programs to be **pure functions**. No side effects, no file I/O, no randomness. This makes *executing a given program* deterministic and unambiguous: for a given input, there is one correct output. (It says nothing about *which* program we get — that is sampled; see the success criterion below.) It is a deliberate simplification, and it is exactly what makes the task cleanly measurable.

3.4. Hidden tests

The hidden tests are the heart of evaluation. Each task carries an independent set of test cases designed to catch real errors, not just a single happy path. For an arithmetic task we include ordinary values, zero, negatives, boundary values, and large-magnitude values. The tests are generated independently of the reference program's *logic* — computed from the semantics, not copied from the solution — so that a model that merely memorizes the reference still can't predict the exact test suite.

It is worth being precise about what "independently" buys us and what it does not. The tests are produced by a *separate generator* from the program, which means they are an independent oracle guard: if the program-generator and the test-generator shared a bug, the tests could pass a wrong program (a correlated-implementation-error problem). Because the tests are a separate path over the same `semantics`, the oracle is decoupled from the program generator, which reduces the chance that a single implementation mistake becomes a false pass. But it does **not** eliminate it. Both the program and the test values derive from the *same*

operation definition, so if that shared specification is wrong, both can be wrong together; and a *finite* set of inputs can simply miss a defect that only shows on an untested input. So this is a *control for correlated implementation bugs* — a useful sanity check, not a guarantee — and **not** a proof that the model "understands" the operation (understanding is a different question, and the surface/composition chapters answer it separately). A passing program is also consistent with the model selecting a correct general program rather than computing anything afresh.

3.5. The success criterion

For a single problem, the success criterion is:

> **Problem-level hidden-test pass@1** — did the one program the model produced pass *every* hidden test for that problem, under the evaluation's default temperature-0.8 sampled decoding?

This is deliberately strict. A program that passes 7 of 8 hidden tests *fails* the problem. That strictness is what keeps the measurement honest: we are not measuring "close," we are measuring "correct."

3.6. Why this specific task

Natural-language-to-Python is a good laboratory task precisely because it has everything a controlled experiment needs:

- **Deterministic to grade, sampled to produce**. The tests and the comparison are deterministic *for a given program* — but the program itself is **sampled** (temperature 0.8), so the same spec can yield different programs on different draws. That is exactly why the success criterion below scores one sampled program with pass@1 rather than assuming "same spec, same program."

- **Executable**. We run real Python and compare real outputs.
- **Objectively scorable**. Pass/fail, no judge-subjectivity.
- **Synthetic**. We can generate as much controlled data as we want.
- **Controllable difficulty**. We can escalate from `a+b` to compounded operations.
- **Compositional splits**. We can train on pieces and test on unseen combinations.
- **Memorization tests**. We can plant canaries and check for exact reproduction.
- **Auditable**. We can inspect the exact generated program and run shortcut audits.

The model could not ask for a clearer job. Now we have to build the tools that let us run and score it: a controlled world, a teacher, a judge, and rivals.

PART II.

Build the Laboratory

CHAPTER 4.

Build a World We Can Control

A model that answers natural-language questions is easy to build and hard to evaluate. But there is one class of task where the evaluation is not a judgment call at all: **write a program**. We write a description, the model writes code, and a computer can tell us, to a very high degree of confidence bounded by the judge and tests, whether that code does what was asked. There are no opinions about the answer, no ambiguous grading rubric, no "well, it's sort of correct." Either the program returns the right thing for every test, or it does not.

That one observation is why this whole book rests on the `natural-language → Python program` task. It gives us something few machine-learning setups have: *objective, executable, reproducible* evaluation. But the task alone is not enough. Before we can run any experiment, we need a world the model can live in — a world that is safe, that is *deterministic*, and that is small enough that we can reason about everything that happens inside it.

4.1. Why we need a world at all

Imagine hiring someone to write code, but not fully trusting them. We would not hand them the keys to the server. We would give them a sandbox — a walled-off room where they can work, but where the dangerous tools are simply not present.

That is exactly what we do with the model. It writes Python, and we need to run that Python safely and deterministically, while deciding precisely what it is *allowed* to do. The model could, in principle, write a program that reads files, connects to a network, or deletes things. It has no reason to — but we are not relying on its good intentions. We build a restricted world where the *disallowed constructs covered by our validator* are rejected, not where every harmful program is made impossible: the sandbox rejects the constructs it knows to disallow, and it is a teaching evaluator, not a hostile-code security boundary.

The deeper reason is that a controlled world makes the *experiment* clean. If the model's program could do anything — read a file, check the time, generate a random number — then two runs of the same program could give different answers, and we could never attribute a failure to "the model didn't learn this" versus "the program did something nondeterministic." We want the world to be so constrained that **the only source of variability is the model itself**.

4.2. The principle: whitelist, not blocklist

The naive way to constrain a program is a blacklist: deny `import`, deny `eval`, deny `open`. This is the instinct most people reach for first. But a blacklist is fundamentally fragile — there is always some construct we forgot. Python has an enormous surface area, and attackers (or, in our case, just curious models) find the gaps. Denying a hundred things is not safety; it is a constant game of catch-up.

The sound way is the opposite: **an allowlist**. We parse the program

into its abstract syntax tree — the structured representation of the code, before it runs — and walk through every node. If any node type is not *explicitly permitted*, we **reject the entire program**. There is no "mostly allowed." If the model emits even one disallowed construct, the whole thing is refused before it ever executes.

The difference is between a list of banned words and a grammar. A banned-word list can be evaded by creative phrasing. A grammar says: these are the only forms that exist. Anything outside the grammar is not merely suspect; it is *unparseable in our world.* That is the philosophy of the sandbox.

This is a central design decision in the apparatus, and it deserves to be stated plainly: **the sandbox does not try to catch bad programs. It states upfront what is allowed, and everything else is refused.**

4.3. The capability spec

For the pilot, we whitelist a deliberately small subset of Python — small enough that we can hold it in our heads, large enough to express real programming:

- literals (integers, floats), variables, assignment, `return`
- arithmetic: `+ - * / // % **`
- comparisons, boolean operators
- `if / elif / else`, `for`, `while`, `break`, `continue`, `pass`
- lists, indexing, slicing, and the list methods `append`, `count`, `index`, `pop`
- a small set of built-ins — eleven in total: `abs, min, max, sum, len, range, int, float, round, list, sorted`
- simple `def` functions

This list is a summary; the authoritative whitelist is §5–§6 of `python_capability_v0_1.md` and `ALLOWED_NODES`/`ALLOWED_BUILTINS` in `src/sandbox/sandbox.py`, which agree with each other. Everything

else is rejected: imports, file I/O, network, subprocess, `eval`/`exec`, `class`, `try/except`, arbitrary attribute access (beyond the whitelisted list methods), comprehensions, lambdas. We do not include these because they are dangerous; we exclude them because they are not needed for the task we are testing, and because each one we add makes the world bigger and harder to reason about. A smaller world is a *better* world for this book, because every construct that is allowed is one we must understand the model's relationship to.

We also version this spec (`python_capability_v0_1`) so that later, when we give the model *more* Python (see the closing chapter's future-work note), we can point to exactly what grew. Versioning the world is what lets us claim, later, that a change in behavior was caused by a change in the world, and not by something else that drifted.

4.4. Resource and determinism policy

Start with the enforcement that is missing: the shipped sandbox enforces no time limit and no memory limit. Nothing in it stops an allowed program from looping forever or allocating until the machine runs out of memory. The spec *designs* a hard execution timeout, a maximum nesting depth, and recursion protection, and the code carries them as constants — but the shipped validator checks AST depth and node count alone, so those three are not enforced at runtime. Everything in this section therefore bounds the *shape* of allowed programs, not their resource use; we say it here, up front, so that no reader mistakes a shape limit for a resource limit.

Beyond what is allowed syntactically, we also control *how complex* the program may be:

- maximum AST depth (24) and node count (200) — a program can only be so complex,
- float-comparison tolerance (because `0.1 + 0.2` is not exactly `0.3`),

- **no randomness, no time, no environment access.**

That last point is the quiet heart of the whole design. A program with the same input must always produce the same output. If it does not, the experiment is contaminated. We cannot tell whether a failure means "the model didn't learn this" or "the program rolled the dice." By making the world deterministic, we eliminate that ambiguity entirely. The book's every later claim rests on this.

One honesty note on that list, restated because it matters: the timeout, nesting-depth, and recursion caps are *designed but not enforced* (stated up front in this section), so an allowed program could still loop or consume memory. That is exactly the resource-use qualification Gate A carries below: the gate bounds the *shape* of allowed programs, not their resource use.

4.5. The pipeline

```
source -> parse -> AST -> whitelist validation -> compile
        -> restricted execution -> semantic comparison
```

Validation happens on the tree *before* execution, so disallowed code never runs. Execution uses a stripped set of globals that exposes only the allowed built-ins — there is no `__import__`, no `open`, no `eval`. The program can only see the tools we chose to give it.

4.6. An honest caveat

4.6.1. The whole apparatus, in one picture




FIGURE 4.1. The whole apparatus

Here is the full loop: the teacher creates the dataset, the student reads it, the judge grades the result, and the world encloses it all.

It is important to be clear about what this sandbox is *not*. It is a **teaching and evaluation** sandbox — deliberately strict about the capability subset, but not a claim of production-grade adversarial isolation. We are not trying to secure a server against a hostile attacker; we are trying to run generated code and measure whether it does what we asked. An attacker with time and motivation could likely find ways around a small AST allowlist. We state this limitation plainly rather than overstating what the sandbox guarantees, because the book's credibility depends on honest boundaries, not on impressive-sounding claims.

4.7. Testing the world

The sandbox is the foundation of trust in every later result. If the sandbox leaked — allowed something disallowed, or failed to be deterministic — every score in the book would be suspect. So the very first thing we do is not run any experiment at all. We **test the world itself**.

We build a conformance suite of 15 cases: three programs that use allowed constructs and must run (a plain function, a loop, a conditional), plus twelve that must be rejected — ten disallowed constructs (`import`, `from`-import, `eval`, `class`, `open`, `__import__`, `try`, conditional expressions, comprehensions, lambdas), a syntax error, and a program that is not a single function. The suite is `tests/sandbox/test_sandbox.py`, and it runs with `pytest tests/sandbox/test_sandbox.py`. A sandbox that only permits things is easy; a sandbox that also *correctly refuses* the disallowed constructs it knows is the real achievement — and that is what our 15-case conformance run checks before we trust a single number it produces. (The 15 cases are a deliberate conformance sample, not an exhaustive proof that every possible disallowed construct is covered; we say "passed its conformance cases," not "verified everything," and the validator's scope is the constructs it enumerates.)

This is the first instance of a discipline the book will return to again and again (and which we will see was worth it, painfully, in Chapter 10): **before we use a tool to measure something, we verify that the tool measures what we think it does**. Here, the tool is the world, and we refuse to run a single experiment until it passes its own examination.

4.8. Two gates, not one




FIGURE 4.2. The two gates

Neither gate lives inside the model. Gate B sits on the way in, Gate A on the way out.

Everything above describes what the model is *allowed to produce*. But there is a second, quieter question: what is the model *ever asked* to do? These are not the same thing, and the difference is worth making sharp, because it is the difference between "the model cannot escape" and "the model was never put in the position to."

A language model has no *built-in* notion of refusal. It is not, by default, a system that decides whether a request is in scope; it is a next-token predictor. Hand a request to this model outside its designed job and it does not politely decline — it simply keeps predicting tokens and produces whatever the weights trend toward, often a confident near-program or garbage. (Models *can* be trained to refuse, but this one was not, so refusal here is not a property to assume.) So "it only does its one job" can never be a property of the model's own intent here. It has to be a property of the wiring around it.

That gives us **two independent gates**, and this chapter (so far) has really only built one of them:

Gate A — the output gate (the sandbox). Already described above: the AST allowlist rejects any generated program that uses a construct outside the whitelist, before it runs. This means that if the model *tries* to emit `import os` or `eval()`, the command is refused. Gate A is a hard gate on the *syntax* of what the model *produces* — it is deterministic for the constructs it covers. Two qualifications: it bounds the *shape* of allowed programs, not their resource use or their adversarial resistance (an allowed program could still, in principle, loop or consume memory), and it is not production-grade isolation. As a scoping mechanism for this experiment it is sufficient; as a security sandbox it would not be. Anyone who wants to try the execution steps described later should do so in a disposable, unprivileged, resource-limited environment with no sensitive files or network access.

Gate B — the input gate (the request validator). This is the gate we build for the other half. It sits *in front of* the model and decides, from the incoming natural-language request alone, whether that request is one the model was designed for. If not, the request is declined before the model is ever consulted.

Gate B works on the same principle as the sandbox: a **recognizer, not a rejector of the exceptions**. It holds the set of designed template-family shapes (the exact phrase skeletons the teacher renders) and the designed operation vocabulary. A request is in scope only if it fits one of those shapes *and* names a known operation — otherwise it is refused. Just as the sandbox says "these are the only forms of program that exist," Gate B says "these are the only forms of request that exist."

One clarification on how we used it. Gate B was built late in the investigation, after the diversity, memorization and surface experiments (Chapters 13–15) and the human-written evaluations. Those evaluations ran the model **directly, without Gate B in front of it** — precisely so that a

low score could be attributed unambiguously to the *model*, not to a request filter that had quietly declined the caller. For the surface and human tests, the model saw the reworded / human-phrased request and failed on its own. Had Gate B been in front, it might well have rejected those out-of-scope phrasings (that is its job) and the failure would have been the filter's, not the model's. So we state it clearly: the surface and human-written failures are model failures, not Gate-B rejections. Gate B enforces scope; it does not confound those measurements.

Why do we need both? Because each covers a failure the other cannot:

- **Gate A alone** would let the model be *asked* for anything — including a task it was never trained for — and only then catch the malformed result. The model would churn, and our whole experiment would trust that an out-of-scope query produced a rejected program rather than a plausible-looking-but-wrong one.
- **Gate B alone** would let the model *produce* anything within an in-scope request, including a program that escapes its world, because nothing would constrain the output.

Only together do they close the loop: Gate B ensures the model is never *asked* for something outside its job, and Gate A rejects programs using constructs outside its allowed syntax. Together that scopes the model to a single accepted request shape and a single accepted program shape — a *scoping* guarantee, not proof of semantic correctness, and not a claim that the model can never do anything unintended beyond those two scopes.

There is a deep parallel here with the book's central thesis. The model is the instrument; the experiment is the subject. In the same way, the *boundaries* are never the model — they are always the apparatus: the sandbox on the way out, the validator on the way in. A model that "only does its one job" is confined by its wiring, not by itself. That is worth stating plainly, because it is the mistake people make when they imagine a well-

behaved model as one that simply chooses to behave.

4.8.1. How this maps to production systems

Our two gates are not an esoteric lab device; they are the same two ideas that real systems use, under different names. It is worth mapping them, so the book's abstract apparatus connects to what people actually deploy. We split the map into two compact two-column tables — one per gate, with what a mechanism does and what it does *not* establish in the same cell — because a four-column table does not survive a 6×9 page.

Gate B (input) analogues

Production analogue	What it does — and what it does NOT establish
Structured-input schema	Declares the request's allowed shape (JSON schema); a request outside it is invalid by construction — a deterministic rule, not a model's decision. *Not established:* shape compliance only — schema validity is not correctness, safety, or authorization
Function/tool signatures	Only registered functions with typed signatures can be called; off-scope actions aren't callable. *Not established:* permission for every argument or action — a declared function can still be called with a harmful argument
Learned safety classifier (input)	A separate learned model scores the prompt and a block action is applied to the score. *Not established:* perfect semantic classification — the classifier is itself imperfect and can misclassify

Gate A (output) analogues

Production analogue	What it does — and what it does NOT establish
Schema-constrained decoding	Decoder only emits tokens that keep output inside the declared structure. *Not established:* correctness of values or authorization — it guarantees *structure*, not semantic correctness
Provider JSON mode	The provider's documented behavior for ensuring the completion is valid JSON, with incomplete-output / edge-case handling needed. *Not established:* arbitrary schema adherence or semantic correctness — a provider's JSON mode ensures JSON validity (including the incomplete-output caveat), not adherence to a specific schema or correctness of values
Prompt-only formatting request	The model is only *asked* to format a certain way; there is no formal syntax enforcement. *Not established:* valid JSON or schema compliance — a prompt saying "please use JSON" is not an API's JSON mode
Output filter / sandbox	A post-hoc check (or a walled-off execution environment) rejects or neutralizes what slipped through. *Not established:* correctness of the content — the check is only as good as its rules

The thread running through the *what it does NOT establish* half of every row is the book's point: every reliable enforcement mechanism is **external and scoped**, and none of them is "the model chose to behave." Even a frontier model that appears to refuse is doing so because RLHF shaped

it to *tend* toward refusal — which is a soft, jailbreakable behavior, not a bound. The dependable version of "it only does what it was designed for" is the wiring we build around it, exactly as our sandbox and our validator are.

Three things follow. First, we deliberately do **not** assign "Low / Medium / High" residual-risk ratings to the rows in the two tables above: we have no threat model or measurement to justify a quantitative ranking, so a color-coded risk column would be unsupported assertion. Instead each row names *which* failure mode remains open. Second, the distinction between a *prompt-only* request and an API's *JSON mode* is a real one: "please use JSON" is a request the model tends to follow, whereas a provider's JSON mode is a documented behavior with its own validity guarantee and its own incomplete-output edge case. Neither one is "the model is forced to comply with a schema" — that is what schema-constrained decoding does. Third, even schema-constrained decoding bounds the *shape* of what gets through; it does not make the content correct or safe. So the reliable layer is external and it is a *scoping* guarantee, not a *judgment* guarantee. There is no mechanism in the table that gives semantic reliability.

CHAPTER 5.

Build the Teacher

We need data. But not just any data — we need data we can *trust* to be fair, and data we can carve up to test the model honestly.

A teacher preparing worksheets for a test is our model of good practice. A bad teacher writes twenty questions that are all the same question with different numbers — the student can memorize one template. A good teacher writes questions that look different on the surface but test the same idea, so a student who actually learned the idea passes whether or not they've seen the phrasing.

Our **teacher** is that good worksheet-writer. But there's something special about the way we build it, and it's a central design decision in the whole book.

5.1. Semantic-first: start with the meaning, not a template




FIGURE 5.1. The teacher

One semantic record is the single source of truth: the program, the task, and the tests all derive from it, so they are much less likely to drift apart than if each were written by hand. This is not a guarantee — a bug in the reference implementation or the renderer could still make all three consistently wrong, which is exactly why we later test the judge against known-correct programs.

The naive way to generate data is to write a template and fill in a few blanks:

```
template -> sentence -> code
```

We write "add {a} and {b}" and a few code snippets, and we are done. This is fast and easy, and it's exactly the wrong way to do it. The problem is that the sentence and the code are generated **independently**, from a template, so there's no guarantee they mean the same thing. We can end up with a sentence that says "add" but code that subtracts, or a test that checks the wrong thing.

We do the opposite. We start from the **meaning** and generate everything else **from it**:

```
SEMANTIC INTENT
   -> PROGRAM STRUCTURE
      -> REFERENCE CODE
      -> NATURAL LANGUAGE
      -> HIDDEN TESTS
```

The key insight is at the top: **one semantic record drives all three**. There is little room for the sentence to disagree with the code or the tests, because they are all the same meaning, rendered three ways. If we start with "the function should return `a + b`," the sentence says "sum," the code adds, and the tests check addition — and they are far less likely to drift apart, because they all came from the same seed. (Agreement is still only as good as that seed: a wrong reference makes the sentence, code, and tests agree with each other but all be wrong, which is why the judge is itself tested.)

5.2. What a "semantic record" looks like

The meaning is captured in a small, structured object. It is not English and not code; it is the *idea* underneath both. For an addition task it looks like this:

```
{
  "operation": "add",
  "args": [{"name": "a", "type": "int", "role": "operand"},
           {"name": "b", "type": "int", "role": "operand"}],
  "output_type": "int"
}
```

From this single object, we generate:

1. **the reference program** — `def solve(a, b): return a + b`,

2. **the natural-language prompt** — e.g. *"Write a function that takes two numbers, a and b, and returns their sum"*,
3. **the hidden tests** — e.g. `{args:[-28,47], expected:19}`, `{args:[0,0], expected:0}`, and edge cases we'll get to.

This is the heart of the teacher. The pump is `make_task`, which takes an operation and a seed, builds the semantics, and then calls three sub-generators that all read that one record.

5.3. The four sub-generators

The teacher is really four small pieces working together, all fed by the same semantics:

1. **`make_semantics`** — builds the semantic intent: the operation plus its argument descriptors. It pulls argument names from a controlled set (so we can vary them later), assigns an input/output type, and tags the task with a complexity score.

2. **`generate_reference`** — turns the semantics into the ground-truth Python. This is the correct program the grader is validated against. For `add` it emits `def solve(a,b): return a+b`; for `list_sum` it emits a loop over the list.

3. **`render_nl`** — turns the same semantics into English, using one of several **template families**. A template family is just a different way of phrasing the same instruction. For addition, we have phrases like:

- *"Write a function that takes two numbers, a and b, and returns their sum."*
- *"Implement solve so that given a and b it returns their sum."*
- *"Define a function solve(a, b) that returns a + b."*

Same meaning, three different wordings. This is what gives the dataset linguistic diversity — and, more importantly, it's what lets us later test whether the model learned the *idea* or just one *sentence*.

Cardinality — how many families an operation has — is per operation and deliberately uneven, and it is worth knowing now rather than meeting it as a surprise later: `add`, `sub`, and `mul` have **three** families each; `max_of`, `min_of`, `list_sum`, `list_len`, and `first_element` have **two**; and `abs_of` and `cond_abs_max` are **singletons**, with exactly one family each. (The composite operations are single-family too, and they are held out of training entirely — Chapter 16.)

Singletons change what a wording claim can mean. For a singleton operation, every training prompt and every in-distribution test prompt comes from the same phrasing skeleton, so "the model has seen this wording" and "the model has seen this operation" cannot be told apart — which is why the surface experiment (Chapter 15) excludes those two operations from its held-out-wording cells instead of pretending a holdout exists, and why the diversity experiment (Chapter 13) later grows the train-eligible pool to 11–13 families per primitive operation while reserving two further families per operation exclusively for held-out-family tests.

4. **`generate_hidden_tests`** — generates test cases **from the semantics**, not from the reference program's logic. It deliberately covers edge cases: ordinary values, zero, negatives, boundary values, large magnitudes, and (where legal) empty lists. For each it computes the expected value from the operation itself.

5.4. Why the tests come from the meaning, not the code

This is a subtle but crucial point, and two different guarantees are easy to blur here, so we name them separately before explaining either:

- **Shared-semantics consistency** is what the semantic-first design above buys: the program, the prompt, and the tests all derive from one semantic record, so they agree by construction. It is cheap and automatic, and it is blind to an error *in the record itself* — everything downstream inherits it.

- **Independent oracle validation** is a different thing entirely: checking the evaluator against evidence that does *not* come from that shared record — the judge's mutation control and its known-correct reference programs (Chapter 6), and the deliberate red-team (Chapter 17). Consistency reduces drift; only independent validation can bound a correlated error, and this chapter does not provide it.

With those apart, here is precisely what the separate test-generation path does and does not establish. If we generated the tests by looking at the reference program, a model that emitted the reference would trivially pass — the tests would be circular. By generating the tests from the shared *semantics* instead, the tests provide a **separate implementation path**: the expected values are computed from the operation definition, in a different code path from the model's program, so a *correct* program and a *wrong* one can be told apart. This is a useful control against **correlated implementation errors** — if the reference generator and the test oracle shared the same buggy code path, they could agree and let a wrong program pass.

But it is **not** a guarantee. Two reservations are worth stating plainly. First, the reference and the test oracle share the same *specification* (the semantic record), so if that specification encodes an error, both can be wrong together and a wrong program can pass unseen. Second, a *finite* set of inputs can miss a defect that only shows for inputs outside the tested set. So the independence of these two code paths is a useful *sanity check*, not a proof that the oracle is perfect or that a passing program "understands" the operation — a model that emits a correct general program (rather than a memorized constant) also passes, so a pass does not distinguish understanding from correct program selection. The honest claim is narrower: generating tests from the semantics decouples the expected values from the model's own output.

5.5. Maximizing controlled diversity

A good teacher does not just produce many examples; it produces *diverse* ones while holding the semantics fixed. We deliberately vary three things:

- **constants** — different values each task, so the model can't memorize outputs,
- **identifiers** — `a, b` vs `left, right`, so it can't tie the operation to particular names,
- **wording** — several template families per operation, so it sees the same idea said many ways.

This controlled diversity is what makes the *generalization tests* later possible. Because we control *how* we vary the surface, we can also *hold it out* and test whether the model generalizes. That's not an accident; it's the whole point.

5.6. Avoiding accidental correlation

The danger in any generated dataset is **accidental correlation** — a pattern that makes the answer trivially predictable from the surface. The classic failures:

- every addition example uses the word "total";
- every maximum example uses the variable `x`;
- every multiplication has exactly three arguments;
- every loop example is exactly one sentence long;
- every operation uses one unique wording.

If those correlations exist, a model (or a trivial classifier) can solve the task without learning the computation. The generator is built to break them, and then — this is the crucial part — we **check that it actually did**.

5.7. The lexical diagnostic

Before trusting any dataset, we ask: *can a trivial classifier predict the answer from the surface alone?* The method is deliberately crude: train a TF-IDF + logistic regression model on the natural-language prompts and see how well it predicts the target operation from the words alone. A high score is a **flag to investigate**, not a verdict: because the request usually names the operation, much of that predictability is task signal, not leakage. Also note what an operation-prediction score does and does not measure — it is a check on *whether the surface is informative about the target operation*, not an audit for duplicated records or for leaked hidden-test values; distinguishing those are separate checks. So we treat a high diagnostic score as a signal to look closer and then decide whether it is task signal or a real shortcut.

But the method needs a careful interpretation, and our first pass misread it. On our first pilot renderer, a trivial classifier predicted the operation from the wording with **100% accuracy**. We recorded it as a red flag (finding-001). On reflection, that is most of the time **task signal, not leakage**: the request must name the operation, or the task would be ambiguous. Saying "return their sum" *should* identify addition — that is what makes the request unambiguous. A classifier hitting 100% because "sum" identifies addition is the wording doing its job, not spilling a secret.

So the audit has to distinguish three things:

- **Task signal** (fine): "sum" identifies addition; the request names the operation.
- **Spurious correlation** (a real shortcut): an *irrelevant* feature that is not part of the request's content — a particular identifier name, an incidental sentence frame, or a formatting quirk — predicts the operation.
- **Train/test leakage** (the real bug): duplicated examples, or evaluation information, crossing the train/test boundary.

A 100% TF-IDF classification score shows that operation selection is

lexically *easy* on that split. It does not by itself establish contamination, and it does not tell us the model is exploiting an illegitimate signal — the phrasing is supposed to carry the operation. What a stricter audit *should* do is mask the operation-bearing language and ask whether *irrelevant* features still predict the target, and also test *held-out template families* and counterfactual changes to names or sentence frames — a stronger diagnostic than we ran, not one we completed here. Our finding-001 note is best read as "the wording is very predictive of the operation" — which is a property of a clear task, not proof of a shortcut. (One implementation note as well: the TF-IDF vectorizer was fit on the whole set before cross-validation, which would leak held-out-fold vocabulary; a principled version fits the vectorizer inside the CV pipeline, as shown in Appendix A.5.)

This is the teacher doing its real job. A dataset generator that only produces data is half a tool. One that produces data **and audits it** — asking whether the surface is carrying the answer for the *right* reason is a laboratory instrument.

5.8. The takeaway

The teacher is not a bulk-data tool; it is a controlled instrument. Its job is to produce data with *controlled* diversity and *audited* cleanliness, so that when the model succeeds we can attribute it to learning the computation — not to the data accidentally giving away the answer.

And the reason this matters so much is the whole book's premise. Everything later — the generalization tests, the composition test, the capability map — depends on the data being a *fair* test. The teacher is where that fairness is built.

CHAPTER 6.

Build the Judge

How do we know a student's answer is right? We check it against the answer key. But what if the answer key is wrong? Then every student who gets it "right" is actually wrong, and we'd never know.

That is the risk with our **judge** — the evaluator that decides whether a generated program is correct. It is the instrument whose readings the whole book depends on. If the judge is wrong, every number in this book is wrong. So we build it carefully, and then we attack it.

This is the second pillar of the apparatus, and it is in some ways the most important. The world (Chapter 4) decides what the model is *allowed* to do. The teacher (Chapter 5) supplies the material to learn from. But the judge is the thing that decides whether the model *got it right*. A subtle way to frame the whole book: we are not really studying the model. We are studying the model *through* the judge. So the judge's integrity sets an upper bound on the trustworthiness of everything that follows.

6.1. Why an execution-based judge

The naive way to judge a generated program is to compare it, as text, to the expected answer. This is cheap, and it is almost worthless. Two programs that solve the same task can look completely different as strings — one uses a loop, another uses `sum()`, yet both are correct. And two programs that look nearly identical can behave differently. String comparison measures *how the code is written*, not *whether it works*. That is not what we care about.

So the judge does the thing that makes this whole task special: it **runs** the program. It executes the generated code against hidden tests and compares the actual *output* to the expected output. This is what gives us objective, unambiguous judgment. There is no opinion about whether the code is elegant or the "right" style — either it returns the correct result for every test, or it does not.

6.2. The four-stage pipeline




FIGURE 6.1. The judge

The judge is a funnel: a program clears it only by passing every stage, and the first failure sends it to zero.

We score a candidate program through four stages; a later stage only matters if the earlier ones pass. Each stage is a filter, and each exists for a specific reason.

1. **Syntax pass** — does the program parse as valid Python?
2. **AST / capability pass** — is every node within the whitelisted subset? If the program smuggles in an `import`, it is rejected here.
3. **Execution pass** — did the program produce at least one correct output? In the implementation this stage is recorded as *executable* when the program passes at least one hidden test (or has no hidden tests), so the recorded quantity is "produced at least one correct output," not merely "ran without error": a program that executes cleanly but fails every hidden test is recorded as *not* executable.
4. **Semantic pass** — for each hidden test, does the program's output match the expected output?

Two honest notes on how this design maps onto the code. **First, stages 1 and 2 are a single combined validation gate in the implementation**: the evaluator calls `sandbox.validate_source` once — one call that both parses and checks the whitelist — and sets `syntax_ok` and `capability_ok` together. So the reported **syntax rate includes whitelist/capability rejections** (a program rejected for smuggling in an `import` is counted in the syntax rate), and no separate capability rate is computed. **Second, stage 3 is coupled to stage 4**: `execution_ok` is derived from the hidden-test outcomes (`tests_passed > 0`), which is why "executable" means "passed at least one hidden test," as defined above. The four-stage vocabulary is the design's; the recorded numbers collapse the first two stages into one gate and tie the third to the fourth.

The primary metric is **problem-level hidden-test pass@1**: did the one program produced pass *every* hidden test for that problem?

Why four stages rather than one? Because each stage isolates a *different* kind of failure, and separating them tells us *why* a program failed. In the design a syntax error is a very different problem from a capability violation (the model tried to use something outside its world), which is different again from a runtime error (the code ran but crashed on a test), which is finally different from a semantic error (the code ran but produced

the wrong answer). If we collapsed all four into one "it failed," we would lose the ability to diagnose. The judge does not just tell us right or wrong; it tells us *where* things go wrong, and that diagnostic power is worth keeping. The honest limit, as noted above: because stages 1 and 2 share one validation call, the recorded rates separate *failed validation* from *no correct output* from *all tests passed*, but they do not separate syntax failures from capability violations — the reported "syntax" rate is really "failed validation."

6.3. Semantic comparison: don't trust string equality

A naive evaluator would compare outputs as strings. That is wrong — the result of a program is a *value*, so comparing text representations of numbers would reject correct answers (`0.1 + 0.2` as text is not `0.3`). So the judge compares values with a **semantic comparator**. Notably, Python's own `==` already recurses into lists and ignores dictionary insertion order, so the comparator's job is narrower than "fix all of Python's equality quirks." It adds three real policies on top of Python semantics:

- **floats compared with an explicit tolerance** (Python's `==` on floats is exact; `0.1 + 0.2 == 0.3` is `False`). We use an absolute tolerance.
- **booleans treated as booleans, not as 0/1** (so `True` is not equal to `1`),
- **dicts compared order-insensitively**, which Python already does for `==`; the comparator re-implements it explicitly for clarity and to recurse into values.

The comparator itself is tested — we don't assume it's right just because it's simple. And the tolerance matters: floating point arithmetic is not exact, so a judge that demanded exact equality on floats would reject correct programs. A judge with no tolerance at all would be as broken as one that accepted anything. Choosing the right tolerance is a real design decision, and it is the kind of thing that quietly shapes every number the judge produces.

6.4. Mutation testing: red-teaming the judge

The most important step is treating the judge as something that must be *vetted*. We **mutate** the reference solution into deliberately-broken versions and ask: *does the judge catch them?*

We generate mutants such as: `+` ⟶ `-`, `>` ⟶ `>=`, remove the `return`. The shipped recipe list is all text substitutions — arithmetic and comparison operator flips, `and`/`or` swaps, and removing the `return`; swapping arguments, off-by-one loop boundaries, and wrong-variable edits are design-stage candidates we do not run here. Then we run each mutant through the hidden tests. A good test suite **rejects** an obviously-wrong mutant. A weak test suite lets it pass.

The mutation score — the fraction of wrong mutants the tests catch — is a measure of how much we can trust the judge on *the cases it is designed for*. An obviously-broken program passing our tests means the tests are too weak for that class of error. Two honest caveats: (1) passing a finite hidden-test suite means passing *that suite*, not proving correctness for every allowed input — deterministic scoring is not complete semantic verification; (2) equivalent mutants (e.g. swapping `+` operands) do not make a program incorrect, so those should not count against us. We report the mutation behaviour honestly rather than claim the judge is "proven sound"; it is a well-tested *heuristic* verifier within the cases we constructed, not a proof.

This is the "test the tester" principle, and it is the reason we do not trust the judge just because we wrote it. The judge is the instrument of measurement, so we deliberately give it wrong inputs and check that it rejects them. It is a rare and valuable discipline: most people build a measuring stick and assume it measures. We deliberately try to break ours.

6.5. We caught our own judge being wrong

Here is what makes this chapter honest rather than aspirational: the very first time we evaluated our model, it **scored 0.000** — reported a total syntax failure on every problem. And the model wasn't wrong. The *judge* was.

The root cause was a generation bug on our side: the model produced a complete, correct program, but it was followed by padding (null bytes), and `ast.parse` correctly rejects null bytes — they are not valid source. So the fault was in the *generation/extraction contract*: those padding bytes were meant as a termination or padding marker that we needed to strip, not as part of the program. `ast.parse` behaved correctly; our extraction forgot to truncate the padding before parsing. Once we truncated it, the model's true score emerged: **0.897**.

That moment is worth more than any passing test. It is the book's core lesson applied to ourselves: **never trust a number from a system we have not audited.** If we had taken the first 0.000 at face value, we'd have concluded the approach failed. Instead, finding the judge's bug told us the truth — the model was actually working.

What is striking is that this bug was not exotic. It was a small, mundane detail — a sentinel byte used to mark the end of a generated program — colliding with Python's parser. We would never have found it by reasoning about the model. We found it because we looked at the judge's *intermediate* output (the syntax scores) rather than jumping to the headline number, and because we already had the habit of doubting the measurement. That habit, more than any single fix, is what kept the book honest.

6.6. The honest summary

The judge is not a helper; it is the instrument whose readings we stake the book on. So we built it strictly (four stages, semantic comparison, tested comparator), then we red-teamed it (mutation testing), and then — when it gave a suspicious answer — we attacked it until we found our own bug. Only a judge that survives that scrutiny deserves to be trusted.

And the deeper lesson is one we will keep relearning: in any measurement, the instrument is part of the experiment. The model and the judge are both subjects. We spend almost as much effort verifying the judge as we do training the model — and that is not waste. That is the only way to trust the numbers at all.

CHAPTER 7.

Build the Rivals

A model that scores 90% sounds impressive — until we ask the hard question: *could a much simpler machine do the same thing?* This chapter is about building those simpler machines, our **rivals**, and why they are the most important comparison in the book.

7.1. The principle




FIGURE 7.1. The rivals

The template and the retrieval baseline are *sanity checks*, not a score ceiling. Our model is drawn next to them for comparison: it has to clear them to be worth anything, but beating a baseline is never a bad result — it just needs to be interpreted correctly.

The value of a neural model's success is judged *relative to a baseline*. If a hand-written rule or a lookup table solves the task as well as the trained model, then the model isn't demonstrating capability — it's re-deriving something simpler. The baselines are what turn "the model works" into "the model does more than a simpler machine could." But a baseline is not a *ceiling* a result must sit below: a strong model beating a baseline is a good outcome. The baselines tell us *whether the task was already easy for a simpler machine*, which is the information we need to interpret the model's score — they do not cap how good a model is allowed to be.

This is a point that deserves to be stated bluntly, because it is easy to overlook: a number in isolation is almost meaningless. "The model solved 90% of the problems" sounds like a triumph. But if a ten-line lookup table

also solved 90%, the model's result shows **no demonstrated advantage over that baseline** — it does not prove the model has no learned capability, but it does mean we cannot credit the score to learning rather than to the task simply being easy. The baseline is what gives the number its meaning.

This is the single question the whole book keeps asking:

> **Could a much simpler machine do this?**

And it is remarkable how often the answer is "yes" at first. That is a feature of the investigation, not a defect. Finding that the task is too easy for a simple machine tells us exactly how to make it harder, which is how the whole brew progresses.

7.2. Rival 1 — the template / rule system

Our simplest rival is a deterministic pattern-matcher. It recognizes known keywords in the specification — "sum" → addition, "maximum" → max, "length" → list length — and emits the corresponding predefined code template. It does no learning whatsoever. It is, in the most honest sense, *dumb* — a set of hand-written if-then rules.

This rival answers: *how much of the task is solvable WITHOUT learning?* If a keyword recognizer does fine, then the task's "hard part" is just pattern-matching, and a model learning it isn't learning much.

Building this rival is almost too easy. It is a few rules that map common words to common code. But its simplicity is precisely its value. It is a **specific, hand-written alternative** against which to measure the learned model. Be clear about what this baseline does and does not establish. It is **not** a lower bound on all possible rule systems, and it is **not** a limit on what a simpler machine could do — it is one particular rule table, worth the keyword → code mappings it happens to encode. If our learned model cannot beat *this* baseline, we learn an important, but narrow, fact: the task does not require the extra machinery, at least relative to *this* alternative. That is a statement about the task and this specific baseline (it is easy

for this rule table), not a statement that no learning occurred, and not a statement that no other baseline exists. The model may well have learned; it is just not learning anything *beyond* what this particular set of rules gives us.

7.3. Rival 2 — retrieval

Our second rival is even more interesting. A **retrieval** system builds a simple TF-IDF index over the training prompts. Given a new task, it finds the most similar training example and *reuses that example's code*.

This rival answers: *can apparent neural competence be explained by retrieval?* If the test set is close enough to the training set, a lookup that does nothing but find the nearest example will do perfectly — and a model that also scores high might just be doing the same thing in a more complicated way.

The retrieval rival is the more insidious of the two, because it is the one that threatens the model's success most directly. A template system shows whether the task is trivially pattern-matching. But a retrieval system probes something subtler: whether a model's score could be explained by *surface similarity to training data*. If a TF-IDF lookup can find a near-duplicate prompt and reuse its answer, then a neural model scoring similarly might be doing exactly that — matching surface form, not understanding. Retrieval is the closest thing we have to a detector for "the model is just copying."

7.4. Why these two matter

These two rivals are the scientific controls. Together they bound what any result means:

- If the **template** baseline is high, the task is pattern-recognizable — the model's win is shallow.

- If the **retrieval** baseline is high, the task is near-duplicate-solvable — the model's win may be memorization or surface similarity.

And the third possibility is the one that matters most: **if the model falls *below* both baselines under some change, we have found a genuine limit of the model's learning**. The rivals are a reference point, not a ceiling to beat; they reveal when the neural model is doing something *no simple machine can do* — and, more valuably, when the neural model has become *worse* than a simple machine, which is a powerful signal of surface-tied, non-general learning.

Our experiments produced exactly this signal. On the pilot, retrieval scored **1.000**: a lookup table solved the whole test set. That told us — correctly — that the task was too easy to force generalization, and we had to make it harder. The rivals did their job: they caught that the impressive-sounding model was being tested on a task that didn't require much learning.

Then, in the surface-generalization chapter, the story inverted. Under a *wording* change, the model collapsed to **0.000** while the template system, which recognizes keywords and is indifferent to exact wording, rose to **0.875** (from 0.800 in-distribution). Here the rivals were not a ceiling — they were a *floor*, and the model fell through it. That was the most informative result of the experiment: it showed that the model's apparent capability was tied to exact surface form in a way that even a dumb rule system was immune to.

7.5. Comparability, stated once and applied everywhere

Whenever a model score is set beside a baseline's, three things are held fixed and reported alongside the number:

- **Same test membership.** The model and both rivals are scored over the *identical* task set — the same records, the same hidden tests, the same judge, the same grading path. Our scoring helper evaluates MODEL,

TEMPLATE, and RETRIEVAL in one pass over the same test tasks, so a difference between the numbers cannot come from a difference in what was graded.

- **Same prompt exposure at evaluation**. Each system receives exactly the same test prompt and nothing else — no hidden tests, no task ID, no reference program. Each system's exposure to *training* prompts is different by construction and is stated wherever it matters: the model trained on those prompts, the retriever indexes those same prompts, and the template rival carries no prompt store at all.
- **Same generator access**. All three draw their programs from the same generated corpus: the template rival calls the teacher's own reference generator, the retriever reuses training reference programs, and the model trained on that data. None of them gets an outside corpus or a hand-written solution library.

One asymmetry we cannot remove and do not pretend to: **the baselines can be advantaged by domain knowledge**. The template rival's keyword table ("sum" → addition, "length" → list length) is knowledge we wrote down by hand — the same knowledge a reader brings to the task — while the model has to induce that association from data. So a baseline score is not a neutral floor: it can reflect understanding planted in it by its author. That cuts in the direction of making the baseline *harder* to beat, not easier, and it is one more reason we read a baseline as a sanity check on the *task*, never as a measure of learned capability.

7.6. The lesson

A neural model is not impressive merely because it works. It is impressive only when it does something a simpler machine cannot. Every result in this book is therefore interpreted relative to these rivals — and the moments where the model *falls below* them are some of the most informative results of all.

The deep takeaway is that baselines are not a formality or a box to tick. They are the reference frame that gives every measurement its meaning. Without them, a score is just a number. With them, a score becomes a claim we can interrogate. And building rivals that are *deliberately simple* is what makes them a strong test: the simpler the machine that can match or beat the model, the more damning (or the more shallow) the model's achievement turns out to be.

PART III.

The First Brew

CHAPTER 8.

The Smallest Brain

Now the student. Everything so far — the world, the teacher, the judge, the rivals — exists to ask one question about this thing. So let's meet it.

Meet the model: a small, deliberately plain decoder-only transformer. It's not fancy, and that's the point. Just like a chemistry lab uses simple glassware so we can see exactly what's happening, we use a simple, transparent model so we can understand exactly what it's doing. A 20-layer exotic architecture would be a black box; a clean, standard transformer is one we can reason about.

8.1. Why the simplest possible model

The temptation when choosing a model is to reach for the newest, most sophisticated thing — the attention variant that promises to be smarter, the architecture that looks impressive in a diagram. That instinct is understandable, but it fights the entire purpose of a controlled experiment. If the model is complex and mysterious, then when it fails, we cannot tell whether the failure is because of some fundamental limit of learning, or because of a quirk of our exotic architecture.

So we choose the opposite. The student is a **completely standard, off-**

the-shelf decoder-only transformer — the same basic architecture that powers the big language models, just scaled way down. Nothing clever, nothing bespoke. This is a deliberate choice, and the reason is not modesty; it is method. A plain, well-understood model means that when something unexpected happens, we can attribute it to *learning* rather than to an architectural mystery. We want the model to be the simplest possible instrument, so that the experiment — not the gadgetry — is the subject.

8.2. What it is




FIGURE 8.1. The smallest brain

The smallest brain is a tiny decoder-only transformer: tokens in, embed, attend through the layers, and predict the next token.

The student is a deliberately simple, transparent **decoder-only transformer**. The goal is not novelty; the goal is that we can understand exactly what it is doing.

For the pilot, the configuration is small and honest:

- vocabulary: 291 tokens (a compact greedy character/whole-word vocabulary tokenizer — 256 character tokens plus frequent whole words, encoded by longest match; *not* byte-pair encoding — see Appendix D),

- hidden dimension: 128,
- layers: 4,
- attention heads: 4,
- context length: 128,
- GELU activation, Pre-LayerNorm, AdamW optimizer.

Each of these is a deliberate choice that we can justify. The context length of 128 tokens, for example, is chosen because a pilot task's prompt-plus-program fits comfortably within it — long enough to hold a full task, short enough that the model is not wasting capacity on irrelevant span (we measure that claim below rather than assert it). The 4 layers and 128-wide hidden dimension keep it fast to train on the modest hardware available, which matters enormously: if training takes an hour, we iterate on the *experiment*; if it takes a day, we wait on the *model*, and the brew slows to a crawl. A small model is a fast iteration loop, and a fast loop is what lets a scientific investigation move.

8.3. Measured: does a task actually fit in 128 tokens?

A claim like that deserves a measurement, so we made one. We tokenized the actual training sets with the exact tokenizer each experiment fits and counted lengths, truncations, and padding (`scripts/measure_truncation.py`; full per-operation distributions in `artifacts/manifests/truncation_audit.json` and `docs/reviews/loop/truncation_audit.md`):

training set	records	prompt+program (median / max)	records over 128
Pilot (Stage 1)	1,400	68 / 109	0
Stage-3 surface	600	66 / 109	0
Stage-4 exposure	1,520	68 / 172	40

For the pilot, prompts run 27–51 tokens and programs 14–68, so the

combined sequence tops out at 109 tokens — `cond_abs_max`, the longest operation, nineteen tokens short of the window. Zero of the 1,400 training records are cut, which means every program the pilot is asked to learn appears complete in its training sequence; "fits comfortably" is measured, not assumed. The Stage-3 surface set is the same story: zero records over 128. The composition baseline of Chapter 16 trains on the same primitive split as the pilot — we verified the two are identical on task ID, prompt, and program — so it too has no truncated training records. Training-time truncation therefore cannot explain the held-out composite 0.000, and we do not claim it does; the decode ablation narrowed *inference-time* stopping, which is a different question from training-time slicing.

One arm is genuinely cut, and we say so plainly. In the Stage-4 composition-exposure run, all 40 `sum_of_abs` training records are 172 tokens (58 of prompt plus 114 of program), so the window keeps 70 program tokens and slices off the last 44 — the `else` branch and the `return`. Training in that arm never shows a completed `sum_of_abs` program, a real coverage defect for that operation there. It is also the one exposed operation the decode ablation reports failing on its own training instances; the correlation is suggestive, but we ran no ablation (retraining with a longer window), so we do not turn it into a causal claim.

There is a second, quieter consequence of the same design. Batches are zero-padded to the longest example in the batch, and the loss has no ignore index, so padding positions are part of the objective. Measured under the trainer's exact batching rule, about 35% of the pilot's loss-target positions are padding targets (36% for the surface arm, 38% for the exposure arm). The pad token is id 0 — NUL — so every padded row trains the model to predict NUL immediately after a sequence's last token. That is a share of loss *positions*, not of loss *value* (we did not decompose the trained loss), and we report it as a property of the objective rather than as an explanation for any score.

8.4. The honest parameter count

A common mistake is to quote just a round "10M parameters." We refuse to hide the important part. The model has **884,224** parameters, of which **830,592** are non-embedding (the transformer blocks, plus the final layernorm and the output projection head) and **53,632** are the **embeddings** — the token embedding ($291 \times 128 = 37{,}248$) plus the positional embedding ($128 \times 128 = 16{,}384$). The embeddings are *also* learned parameters: they are trainable and they do store task-relevant representations. What distinguishes them from the block weights is that each one is only ever *looked up* (a token maps to its vector), whereas the block weights are *multiplied* many times per forward pass. So at ~6% of parameters, the embedding tables are a small share, but they are not inert — we report the split between embedding and non-embedding so a naive "M parameters" figure is not dominated by the lookup tables rather than the computation.

So we always report the split: embedding vs. non-embedding.

8.5. The model, in one box

So that there is no ambiguity about what we trained, here is the complete specification of the pilot model (the 0.88M model; the larger runs in Chapter 12 only scale width and depth, and the registry in Appendix C lists each one's exact configuration):

Property	Value
Architecture	GPT-style decoder-only transformer
Vocabulary	291 tokens
Embedding dim (`n_embd`)	128
Layers (`n_layer`)	4
Heads (`n_head`)	4
FFN width (intermediate)	$4 \times$ `n_embd` $= 512$
Context budget (`block_size`)	128 tokens

Property	Value
Dropout	0.0 (deterministic)
Attention	Causal (masked), self-attention
Positional encoding	Learned, 128 × 128
Final norm	LayerNorm before the output head
Output head	`n_embd` ⟶291 logits, **no bias, no weight tying**
Parameter split	884,224 total = 53,632 embedding (token 37,248 + position 16,384) + 830,592 non-embedding
Weight init	Normal(0, 0.02)

What the model is asked to do. Each training example is the prompt and the target program concatenated as a single token sequence (`prompt + "\n" + reference_code`), and the model is trained with standard next-token cross-entropy over that whole sequence. (Roughly, at each position the model outputs a *logit* per vocabulary token — an unnormalised score — which is turned into a probability, and cross-entropy is a measure of how well those predicted probabilities match the actual next token; minimising it over the sequence is what "training" means. An *optimizer step* is one update of the weights based on the gradient of that loss over a batch, and one full pass over the training set is an *epoch*.) There is no loss masking that restricts credit to the program positions — the model is rewarded for predicting the prompt's continuation (including its own wording) as well as the program. **Consequence for the numbers we report**: because there is no completion-only loss mask, the training loss quoted in this book (the pilot's ~0.02) aggregates prompt tokens *and* program tokens over the whole `prompt + newline + program` sequence. The prompts are short and highly repetitive, so that figure is a full-sequence fit number, **not** a clean measure of code-completion fit alone; no code-token-only training or validation loss was recorded, so we qualify the aggregate rather than report a split we do not have. Generation uses temperature

0.8 multinomial sampling for `max_new` tokens, with the context window truncated to `block_size` (it reconditions on the sequence so far at every step). There is no separate "refuse to answer" behavior — the model is trained simply to keep predicting, which is exactly why we build gates around it (Chapter 4).

This matters more than it might seem. At tiny scale, the ratio of vocabulary to computation is high, which means a naive "M parameters" figure can be dominated by the embedding lookups rather than the computation that must actually reason about the program. Separating the two lets us and the reader see the *actual* computation the model brings to bear — the attention and MLP parameters that do most of the sequence modeling. (To be clear, the embeddings *are* trainable and do store learned structure, as the spec box shows; this is about weighting which part matters when we talk about "capacity," not about claiming the embeddings are frozen.) It is a small discipline, but it keeps the conversation honest.

8.6. The architecture smoke test

Before we train it for real, we run an **architecture smoke test** — a tiny, fast check that the model's forward and backward passes work, that the parameter count is what we expect, and that the initial loss is sensible (roughly the log of the vocabulary, since a fresh random model's best guess is uniform).

This is the same discipline as the very first smoke test, but one level up: we are not checking "does the loop run?" anymore, we are checking "does *this model* construct and train correctly?" A 20-second check here prevents discovering a shape bug hours into a real run.

The initial loss is a wonderfully informative number. A brand-new model, before it has learned anything, predicts the next token uniformly, so its loss should be close to the natural log of the vocabulary size — here, about $\log(291) \approx 5.67$. When we actually ran it, the initial loss was **5.84**, reassuringly close. That is what a model that knows nothing looks like, and it

is the baseline every later, lower number is measured against. One provenance note, which Chapter 9 makes explicit: only the *final* training loss — **0.0208** — is machine-recorded in the experiment manifest (`artifacts/manifests/stage1.json`). The initial 5.84 and the intermediate curve values quoted in Chapter 9 come from the printed training log, and should be read as illustrative of the curve rather than as manifest-recorded figures.

8.7. Why it's small

The book deliberately keeps the pilot model tiny. This is not modesty; it is method. A small model is fast to train (so we can iterate on the *experiment*, not wait for the model), transparent (so a failure is a learning-system problem, not an architecture mystery), and it makes the *boundary* more visible — a small model that fails to compose tells us something cleaner than a large model that does something partly and noisily. We scale it up later precisely to test whether capacity matters, but the baseline has to be small and legible.

8.8. The configuration is a starting point, not a fact

Crucially, none of these numbers are immutable. The exact architecture is an experimental variable. Every architectural choice requires a reason, and the question is never "what architectures can we try?" — it is "what scientific decision does this comparison enable?" For the pilot, the answer is: this size is fast enough and small enough to be legible, which is what Stage 0–1 needs.

This is a discipline worth holding onto. It is tempting to fixate on the "best" architecture or the "right" parameter count as if one existed. But in an experiment where the question is about *learning*, the model is a dial, not a destination. We choose a configuration because it enables a specific scientific comparison — and we change it when we want to test

whether the answer changes. That is why the pilot model is small and plain: not because it is the best, but because it is the *clearest* instrument for the question at hand.

CHAPTER 9.

The First Brew

Everything's built. Now the moment of truth: we train the model for the first time and watch what happens.

This chapter is deliberately unheroic. The goal isn't a triumphant result — it's to confirm the loop works and to see the model's honest behavior as it learns. It is the first time a recipe we have been assembling is finally run: we are not hoping for a masterpiece, we are checking that the oven works and nothing explodes. And for anyone who has brewed anything — beer, coffee, bread — the *first* batch is never about the product. It is about learning our equipment, our ingredients, and our own impatience. This chapter is that first batch.

9.1. The data

1400 training tasks: a natural-language specification paired with its reference Python program. The model's job is to read the spec and produce the code. Each task is a single semantic record — one idea — rendered three ways (a program, an English instruction, a set of hidden tests), so the data is internally consistent by construction. We do **not** need to worry as much that a prompt says "sum" but its answer subtracts, because both came from

the same seed. That said, "same seed" is not a guarantee: a wrong semantic record would be wrong in all three renderings at once, so the consistency reduces (but does not eliminate) the risk of a prompt/answer mismatch.

The dataset is a three-way split — **1,400 train / 300 validation / 300 test** records, the counts recorded in `artifacts/datasets/pilot_manifest.json`. The validation split was generated but never used for model selection: `scripts/train.py` loads it and evaluates only on the test set, so every number this stage reports is a test-set number.

We hold out a separate 300-record test set. Because the teacher uses a task-ID seed to change only the hidden-test *inputs* while the prompt string and reference program stay the same, those 300 test records **reuse the same 21 prompt strings** as training (see the novelty audit in Appendix C); what is new at test time is the task ID and the execution-test values, not the prompt. We state this plainly, because it shapes exactly what the pilot's 0.897 does and does not establish: familiar-prompt program generation on fresh execution inputs, not generalization to a new request.

9.2. The model

The student is a small, deliberately plain decoder-only transformer: 4 layers, hidden dimension 128, 4 attention heads, a compact 291-token vocabulary, and 128-token context. Total **884,224 parameters** — but we report the split honestly, because it matters more than the round number: **53,632 (6.1%)** are in the token and positional embedding tables, and **830,592 (93.9%)** are elsewhere. The embeddings are trainable representations, not a static lookup. Reporting both figures prevents confusion about where this model's parameters are allocated — for this configuration the embedding share is modest, not a majority (embedding-dominated regimes arise with much larger vocabularies, which is not this model).

9.3. The training process, step by step




FIGURE 9.1. The brew loop

Every experiment is one pass around this loop: generate, train, measure, and let what we measured shape what we generate next.

Training a small transformer is not a single action; it is a loop repeated 1,500 times. At each step:

1. We grab a batch of 16 tasks and tokenize each as one sequence: the natural-language prompt, a newline, then the reference program.
2. The model reads the prompt and predicts each *next* token in the combined sequence. This is the standard **next-token objective** — the model's only job is to guess the next word, given everything before it. It is a deceptively simple task, and it is the entire basis of how these models learn to write.
3. We measure the difference between the model's prediction and the actual next token (the cross-entropy loss), take the gradient, and nudge the parameters with the **AdamW** optimizer at learning rate **1e-3**, clipping the gradient magnitude to keep training stable.
4. Repeat.

We print the loss every 200 steps so we can watch it behave. Here is what it actually did:

```
step    0   loss 5.84
step  200   loss 0.029
step  400   loss 0.022
step  600   loss 0.023
step  800   loss 0.020
step 1000   loss 0.021
step 1200   loss 0.019
step 1499   loss 0.019
```

That is a large, clean drop — from 5.84 to about 0.02 in 1500 steps. (The per-step log above reads 0.019 at the last step; the recorded final training loss in the experiment manifest is 0.0208 — the same quantity reported at slightly different rounding or on a different averaging window, both meaning the loss has collapsed to a low floor.) A provenance note: only that final value, **0.0208**, is machine-recorded in the manifest (`artifacts/manifests/stage1.json`) — the intermediate values in the log above are illustrative, transcribed from the printed training log, and should be read accordingly, as a picture of the curve rather than as manifest-verified figures. Two things about this curve are worth sitting with, because they reveal more than the final number.

First, the shape tells us the *training loop is working*, nothing more. The loss falls steeply in the first 200 steps (5.84 ⟶ 0.029), then flattens out near a floor. This is the curve we expect from a functioning loop that is fitting the data: rapid improvement at first, then diminishing returns. If instead the loss had wobbled or stayed high, we would have had a debugging problem on our hands, not a training result. But a *converging* loss by itself does not distinguish learning from memorization — both produce a falling loss. That distinction is exactly what the upcoming evaluations, not the loss curve, have to settle.

Second, the *final* value is not the interesting number. A loss of 0.019 means the model can predict the next token of the *training* sequence almost perfectly. That tells us it fits the training data — and nothing more. One qualifier belongs on the number itself: there is no completion-only

loss mask (Chapter 8), so this loss is averaged over *prompt and program* tokens together — the prompts are short and highly repetitive, and a low value partly reflects easy prompt-token prediction. Chapter 8's length audit adds the other half: about 35% of the pilot's loss-target positions are zero-padding targets (token id 0, NUL), because batches pad to the batch maximum and the loss carries no ignore index — so ~0.02 averages prompt tokens, program tokens, and padding targets together. No code-token-only training loss was recorded, so ~0.02 should be read as full-sequence fit, not as a clean measure of code-completion fit alone. This is the book's recurring motif, and it is worth saying loudly: **a falling training loss, and even a very low one, is not evidence of learning**. It is evidence of fitting. The distinction is the entire point of the experiment.

9.4. What the training process felt like (the brewing experience)

Anyone who has trained a model knows the peculiar rhythm of it. We set a batch of runs going and we wait, checking the loss every few minutes with a combination of hope and suspicion. The first steps are the most honest — a fresh, random model has loss near the log of the vocabulary size, because its best guess is uniform. That initial 5.84 is exactly what a model that knows nothing looks like.

Then, if things are working, the loss starts to fall, and a strange thing happens: the drop is *so* fast in the first couple hundred steps that we wonder whether it is real or whether something is broken. In this case the model reached near-floor loss within 200 steps. The rest of the training is just the model quietly polishing the last fraction of a point.

There is also a genuine practical question that arises during training: **how do we know it hasn't crashed mid-run?** What our training script actually does is a single **post-training, pre-evaluation save**: one `torch.save` runs after `train()` returns and before evaluation begins, so a crash during evaluation cannot lose a completed training run. It does **not** save at intervals *during* the run — a crash at step 1200 would lose the

whole run, and we say so plainly (Chapter 12 recounts an interrupted run whose original checkpoint was not preserved). Periodic mid-run checkpoints — saving at regular intervals so a crash loses at most the steps since the last save — are the obvious hardening step for a production trainer; this book's code does not implement them, so we do not claim they exist here, and we do not claim they have saved us a run.

9.5. The honest caveat

A falling training loss — and even a very low one — is *not* evidence of learning. We saw this in the pilot and it is the book's recurring motif. The training loss tells us the model fits the training data. It does not tell us it can *generalize* to unseen problems, or that it learned the computation rather than the surface form.

So after training, the only losses that matter are the *held-out* ones: how well does the model do on problems it never saw? That is Chapter 10's question, and the answer there is the real measurement of this brew.

9.6. Why the details of the training process matter

It is tempting to skip the mechanics and jump to results. But the whole premise of this book is that *the experiment is the subject*, and an experiment we cannot reproduce is not an experiment. The exact vocabulary size, the number of layers, the batch size, the learning rate, the number of steps — these are not trivia. They are the conditions under which every later claim is true. If we change one and the result changes, that tells us something; if we change two and the result changes, we can no longer say which one caused it. This is the **one-variable discipline** that governs every experiment in the book, and it is why we record the configuration so carefully in a manifest alongside every result. A reader should be able to take our numbers and run the same configuration — and reproduce the *procedure*, not necessarily the identical sampled scores (a fresh stochastic

rerun under temperature-0.8 sampling may differ slightly; the repository is public, and exact checkpoints are not shipped — they are regenerable from the recorded configs and seeds; see Appendix C.11). The recording is what makes the procedure reproducible, even before scores are confirmed on an independent run.

9.7. What this chapter establishes

This first brew is not a result; it is a proof of the loop. We have:

- trained a real model on real data,
- watched its loss descend smoothly,
- saved a checkpoint,
- confirmed that we can take the trained model and produce code for a new prompt, run it through the sandbox, and score it with the judge.

That loop — generate data, train, generate code, execute, score — is the laboratory working end-to-end. It is the foundation everything else stands on. The model is built. Now we have to find out what it actually learned.

CHAPTER 10.

Does It Actually Work?

We have a trained model, a judge, and a test set. The natural question is the one the whole book has been building toward: *does it actually work?*

And the answer, as with almost everything in this book, is "**it depends on what we mean**," and then "**let's measure it rather than argue**." Because "works" is not a single number. It is a question about *which* kind of capability, under *which* conditions, measured in *which* way. The job of this chapter is to take that vague word and replace it with something we can actually see.

10.1. The setup

We trained a small decoder-only transformer on 1,400 generated tasks: the model reads a natural-language specification and must produce the reference Python program. The trained model is tiny — **884,224 parameters** (0.88M), of which 53,632 are the embedding and 830,592 are the non-embedding weights. It saw 1,500 gradient steps on a batch of 16, reaching a training loss of **0.0208**.

We then asked it to solve 300 **held-out** test tasks, and scored each generated program by executing it against that task's hidden tests. The

novelty here needs a precise statement: these test records reuse the **same 21 prompt strings** the model saw in training, but each carries a **new task ID with fresh hidden-test input values**. So "held out" here means new *instances* of a seen prompt — the model had to produce, for a prompt it already knows, a program that passes input values it has never seen. It is not a test of a brand-new request (for that, see Chapter 15's human-written prompts and the surface/composition holdouts, whose prompts genuinely never appear in training). This is the moment of truth for the whole apparatus: everything we built — the world, the teacher, the judge, the rivals — converges on this measurement.

Quantity	Training	Validation	Pilot test
Records	1,400	300	300
Prompt strings	21	21	21
Test prompts also seen	n/a	21 of 21	21 of 21
What changes at test	n/a	task ID, inputs	task ID, inputs

The dataset is a three-way 1,400 train / 300 validation / 300 test split (`artifacts/datasets/pilot_manifest.json`). The validation split was recorded but never used for model selection — `scripts/train.py` loads it and evaluates only on the test set — so every figure in this chapter is a test-set figure.

A key distinction to keep straight: the numerical inputs go to **Python** (the model's program is executed on them), while the **language model** receives only the prompt string. So a new task ID changes what the *judge* feeds the program, not what the *model* sees.

10.2. One task, end to end

The cleanest way to see what the judge does is to follow one task from prompt to verdict. Here is a real run against the pilot model — record `add_0036` from the scored pilot evaluation (`artifacts/datasets/pilot_test.jsonl`).

The request. "Implement solve so that given a and b it returns their sum."

The reference program (the teacher's ground truth):

```
def solve(a, b):
    return a + b
```

What the model actually produced (temperature-0.8 sampled decoding, this checkpoint — the same single sample used for the reported score):

```
def solve(a, b):
    return a + b
```

The hidden tests (input/expected pairs) that the judge then runs. For this record (`add_0036`) the task's suite has **eight** cases; here is an **excerpt** of three (a basic, a zero, and a negative case). The judge runs all eight and this task **passes — all 8/8**.

inputs	expected
(-86, -95)	-181
(0, -28)	-28
(-1, -33)	-34

The judge runs the model's program on each pair, compares the output with the semantic comparator, and reports **pass@1**. This task passes.

Now the informative contrast: a task the model *had not seen*. The teacher's composite `abs_add` asks for the sum of the absolute values of

two numbers (`abs(a) + abs(b)`). A provenance note before the examples: the scored pilot evaluation runs only on `artifacts/datasets/pilot_test.jsonl`, which contains the 10 primitive operations and the 21 training prompt strings — no `abs_add` record and no reworded prompt. So neither of the two failures below is an output of that scored run; both are **separately-run demo generations** against the pilot model, outside the evaluation set, and we label them as such rather than presenting them as pilot-evaluation outputs.

The first comes from the live demo battery (`scripts/demo_live_model.py`, archived in `docs/experiments/model_sweep_live.md`): the `stage1.pt` checkpoint, which knows both `abs` and `add` individually, was fed the composite prompt:

> "Write a function that takes two numbers, a and b, takes the absolute value of each, and returns their sum."

and produced:

```
def solve(a, ab
```

— a truncated, unusable fragment. The generation stopped early. We did not preserve the raw token sequence, so we cannot state the precise stop reason from the record (it could be the `max_new` limit, the NUL-byte extraction boundary, or an unlucky sampled end). What is clear is that it is an **incomplete extracted candidate whose termination/extraction cause was not preserved** — a partial Python identifier/source fragment, not a complete program. Because a termination/extraction defect already changed the pilot score once, we flag these as an *incomplete extracted candidate*, and do **not** assert a specific internal cause (we cannot, from the record, tell it apart from a genuine capability limit). The second is likewise a separately-run demo generation, not a scored pilot record: on a genuinely reworded surface ("Return the value obtained by adding together two numbers, denoted p and q.") — a prompt that is not among the 21 pilot prompt strings — it produced:

```
def  a solve(a, b
```

again truncated. These two demo generations carry the book's whole point: on a familiar surface the model writes correct code, and on an unseen surface or a new combination it collapses to a fragment. Nothing about the failure required the hidden tests to be "unfair" — the invalid fragments were **rejected at parsing** by the judge, before any execution or comparison, because they do not parse as complete Python programs.

10.3. What we measured: pass@1

Here is the headline result, reported as **problem-level hidden-test pass@1 under the evaluation's default temperature-0.8 sampling** — that is, for each evaluation record, did the *single sample* the model produced pass *every* hidden test? (This is sample pass@1, one sample per record, not a distribution over many samples.) Two sampling details matter for interpreting it: (1) the evaluator calls the model **once per evaluation record** (`for t in tasks: candidate(t)` → a fresh `model.generate`), so records that happen to share a prompt string still get **independent** draws — no output is cached or reused across records; and (2) the fixed score is a property of the checkpoint, the sampled outputs, the record weights, the tests, and the decoding settings (temperature, `max_new`, NUL truncation), not just of the dataset. A single sample per record does not give within-run sampling error, but the repeated records do act as within-prompt replicates for the purposes of a familiar-prompt aggregate. The training seed is recorded per run; generation does not reset the RNG to a separate value, so it uses the continuing RNG state during evaluation unless explicitly reset (Appendix C.6), which is why sampling is stochastic rather than exactly seed-reproducible record-for-record. There is no stop policy: `generate` in `src/model/gpt.py` always draws exactly `max_new` tokens (it never stops early on EOS or PAD), and extraction truncates at the first NUL byte; the `max_new` and extraction rules live

in `src/eval/evaluator_runner.py`.

Candidate	syntax	executable (≥1 hidden test passed)	**pass@1**
MODEL	0.897	0.897	**0.897**
TEMPLATE	1.000	0.900	0.800
RETRIEVAL	1.000	1.000	**1.000**

Reading the columns: `syntax` is the fraction that passed the judge's combined parse-and-whitelist validation (Chapter 6 — whitelist/capability rejections are counted here too), and `executable` is the fraction that **produced at least one correct output** — passed at least one hidden test — not merely the fraction that ran without error.

Model-visible novelty, stated precisely: 0.897 is single-sample correctness for repeated previously-seen prompt strings under fresh execution values — not prompt generalization.

Three things stand out.

First, the model learns to produce a program for a prompt it has seen many times. 0.897 means that ~90% of the time, given a *familiar* prompt string, the model produced a program that passed all the *fresh input values* the judge supplied. That is not a toy result: the model emits valid, correct Python for a request it has been trained on. But note exactly what is and is not being claimed. Because every one of the 300 test records reuses a prompt string the model saw in training, this figure is **familiar-prompt program generation on new execution inputs** — not generalization to a new request. And it still **beats the hand-written rule baseline** (0.800) on that same set. A hard-coded pattern-matching system that recognizes keywords like "sum" and emits a template gets 80%; our learned model gets ~90%. So on this task, the learned model does *more* than a fixed rule system.

Second — but retrieval does even better. A trivial TF-IDF retriever that does nothing but find the closest training example and reuse its program scores **1.000**.

That second fact is not a failure; it is the pivotal thing this pilot taught us. It tells us the task, as currently constructed, is **too easy to force generalization**. When a non-learning lookup solves 100% of the test set, then the test set is solvable by retrieval, and a model scoring 90% is not yet being tested on whether it can generalize — only on whether it can match the surface form of a training example.

This is exactly the "task too easy" outcome the experimental plan anticipated, and it is scientifically useful: it tells us *how to make the next task harder.*

A note on replication across seeds. This in-distribution result is not a single-seed accident. Fresh trainings under seeds 1 and 2 both scored **0.900** in-distribution (final losses 0.0196 and 0.0229), matching the single-seed ~0.90 reported here (0.897 over the 300-record test; report: `docs/reviews/loop/multiseed_replication.md`). One provenance wrinkle worth carrying: seed 0's `stage1.json` preserves the pre-fix 0.000 evaluation described below, not a re-run value — the seed-0 figure quoted throughout the book is the manifest-backed 0.897 in `stage1_results.json`.

10.4. The moment that broke us (and the evaluator, not the model)

There is a story behind these numbers that is more instructive than the numbers themselves, and it is worth telling plainly. When we ran the evaluation for the very first time, the model scored **0.000**. Not 0.897 — zero. Every single generated program failed the syntax check.

Our first instinct, naturally, was that the model was useless. We had spent hours building a careful apparatus and the tiny model could not even produce a parseable program. It would have been easy to conclude "the model doesn't work" and write the whole thing off.

But the book's own discipline — *test the tester* — demanded we ask whether the *judge* was the problem, not the model. So we looked at what the judge actually saw. And there it was: the generated programs were valid Python up to the end of the program, except they had a run of **NUL bytes** (`\x00`) appended after it. The model had learned to pad its output with a byte that means "nothing." Python's parser correctly rejects NUL bytes — they are not valid source. The fault was in the *extraction contract*, not the parser: we had failed to strip the padding before handing the output to `ast.parse`. So `ast.parse` threw a syntax error on what was, after truncation, good code, and the judge scored the model's program as a *syntax failure*.

The fix was a single line: truncate the generated program at the first NUL byte. A trivial change, and suddenly the model's score leapt from 0.000 to 0.897.

This is the pivotal lesson of this chapter, and it is not about the model at all. **The evaluator was broken, not the model**. We had designed every experiment to detect shortcuts and outright cheating in the *model*, and we nearly missed the one case where the measuring stick itself was faulty. The "test the tester" principle — that we must verify the tool measures what we think it measures before trusting a single number it produces — was not a formality. It just saved the entire project from a false negative.

The reason we caught it is worth pausing on. We did not catch it because we are clever. We caught it because we had *already* built a method for testing testers (the mutation suite in Chapter 6), and we had written the pilot's results to a manifest and looked at the intermediate numbers, not just the headline. Had we grabbed the final pass@1 and moved on, we would have shipped a book claiming a tiny model cannot write Python — a conclusion that was wrong.

10.5. The shortcut audit

Before we trust the "0.897" number, we have to ask how the model might have gotten there without learning.

1. **Suspected shortcut: retrieval of a near-duplicate prompt. Why it could explain it:** the pilot's generated prompts are drawn from a small set of template families per operation, so many test prompts are surface-near to training prompts. **Control:** we ran the retrieval baseline — 1.000. This *confirms* the shortcut is available and that the test set is retrieval-solvable. **What it rules out:** nothing yet, because the model's 0.897 is *below* the retrieval ceiling. It does not rule out the model partially relying on surface similarity. **What remains unresolved:** whether the model's own success is grounded in the *computation* or in the *surface form*. To answer that, we need the Question-3 (surface-change) and Question-4 (composition) experiments, which we run next.
2. **Suspected shortcut: exact memorization. Why it could explain it:** the model saw 1,400 examples; maybe it memorized the prompt→program pairs. **Control (Ch14):** a probe of 60 pilot records plus a held-out program probe: **60/60 on the training-record probe** (it reproduced every reference program exactly) and **59/60 on the held-out/task-ID probe** (a passing general program for a fresh task ID), while on the held-out program probe it emitted the *general* program rather than a memorized literal. **Caveat:** the pilot test reuses training prompt strings, so this does **not** establish unseen-prompt generalization — it shows the model produces a *general* program (not a memorized constant literal) for these records. **What it rules out:** the narrow claim that the model merely emits memorized *constant* outputs. **What remains:** the deeper question — is the *general program* it produces genuinely tied to the computation, or to the particular wording?

10.6. The honest summary

The pilot succeeded in exactly the way a pilot should: the laboratory works, the model **reliably produces a correct program for a prompt it was trained on**, and — perhaps most valuably — the experiment told us something *uncomfortable but true*. The task is retrieval-solvable, a model that beats a template rule system yet sits below a lookup table, and — crucially — the test reuses the model's known prompt strings, so the pilot **did not actually test generalization to a new request**. It tested reliable familiar-prompt generation and shows that the *apparatus* can produce meaningful, checkable measurements. Whether the model can generalize is the question the remaining chapters actually probe, using prompts and composition that genuinely were not in training.

And we were reminded, in the most direct way possible, that the measuring stick is as much a subject of the experiment as the model. The instrument and the thing measured both needed to be honest, and only one of them initially was.

That is the baseline from which every later experiment is measured. From here, we stop making the task easier and start making it *probe* generalization.

PART IV.

How Capability Scales

CHAPTER 11.

How Much Data?

The most common question people ask about any model is also the one they answer too quickly: *how much data does it need?* We set out to measure it directly — holding the model, the tokenizer, the operation mix, and the training method fixed, and varying only the number of examples.

It is a question worth measuring rather than guessing, because the folklore answer — "just add more data" — is both plausible and unexamined. Our own first attempt at the measurement did not survive code audit: the sweep changed the operation mix along with the count, so its rising curve was an artifact of coverage, not of data (Appendix B, P0-01). The balanced, operation-stratified rerun that audit called for has since been done — three seeds, one fixed tokenizer, one fixed test set — and its answer is the opposite of the folklore: **no consistent monotonic effect on familiar-prompt accuracy is detected here**. Once every size covers the same ten operations, the scores sit in a narrow band around 0.90 across a 30× range in the number of examples per operation — with one flagged outlier (seed 2 at size 1,000, 0.997), called out below.

11.1. How to read the evidence

This chapter opens the experimental part of the book, so we consolidate here the small set of caveats that the chapters that follow would otherwise re-justify in near-identical words. Each later result still carries its own local caveat, immediately next to the number it bounds; what lives only in this table is the shared *justification*. Where a chapter repeats one of these points, it now points back to this table instead of re-arguing it.

Table 11.1 — How to read the evidence

Caveat	What it means	Where it bites
Coverage is not transfer.	A score on prompts, surfaces, or operations the training pool already covers measures *coverage*, not generalization to something never seen. The pilot's 0.897 is single-sample correctness on reused training prompt strings; the corrected data-scaling sweep's ~0.90 is an instance-level holdout (new construction seeds and new hidden tests) over the same 21 prompt strings; Chapter 13's superseded flawed-run 1.000 was coverage of its own training families; its corrected equal-count run tests an audited held-out family instead (0.550 mean).	Ch. 10, 11, 13, 14, 20
The 0.88M baseline denominator.	The familiar-prompt numbers — 0.897 (pilot, 300-record test), 0.898–0.940 (corrected surface factorial, 600 records), 0.9167 (Stage-4 baseline, n=60) — are different evaluation sets, not a discrepancy. The figure they agree on is composition 0.000.	Ch. 12, 16, 19, 20

Caveat	What it means	Where it bites
Model-size budget differences.	The size sweep varied training budget and tokenizer alongside size (1,500 / 1,000 / 800 / 800 steps; pilot vs. composition tokenizer), so it is not a size-only intervention.	Ch. 12, 19, 20
Old vs. new novelty audits.	The pilot was audited on the original scored files; the Stage-3 and Stage-4 holdouts were audited on *regenerated* reproductions with the current generator — corroborating, but not proof on the scored artifacts.	Ch. 13, 15, App. C

Caveat	What it means	Where it bites
Superseded flawed historical runs.	Ch. 11's original data-scaling sweep (Po-01: operation coverage) and Ch. 15's original surface rows (Po-03: mixed factors; Po-04: 480-record denominator) are preserved as labeled flawed records in the failure ledger (Appendix B) and as superseded rows in Appendix C; their corrected reruns are this chapter's and Chapter 15's actual results. Ch. 13's diversity comparison (Po-02: 42 vs. 1,200 records) now has a corrected	
equal-count rerun (Table C.15), which finds diversity drives held-out-family generalization.	Ch. 11, 13, 15, 19, 20	

What a later code audit showed — read this before the numbers. The original sweep did not change only the data count. The script builds one pool with `pool = generate_dataset(n_per_op=400, ...)` and trains on `train = pool[:size]` — a *prefix* of a pool the generator appends record by record **in operation order**. The 100- and 300-record arms therefore trained on **one operation out of ten** (`add`), the 1,000-record arm on **three**, and the 3,000-record arm on **eight** — while

the evaluation set spanned all ten operations. That sweep was thus **confounded with operation coverage**: what changed across its four arms was not just how many records the model saw, but *which operations it saw at all*. The recorded curve is preserved in the failure ledger (Appendix B, Po-01) as a **flawed historical run of operation coverage**, not a data-count scaling result. We draw no threshold, no knee, and no data-efficiency lesson from it, and the earlier claim that "only the data count changes" was wrong. The balanced, operation-stratified rerun the audit called for — the same number of records per operation at every size, one fixed tokenizer, matched step budgets — has now been run, and it is the experiment reported in the rest of this chapter. The confounded curve reappears once below, kept only so a reader can see what the flaw looked like.

11.2. The setup

We train the same ~0.9M model (128 embedding / 4 layers / 4 heads, block size 128), the same optimizer and schedule — 1,000 steps, batch 16, learning rate 1e-3 — on four dataset sizes: 100, 300, 1,000, and 3,000 examples. Three things are held fixed that the first attempt let drift:

- **Operation coverage**. Every arm draws the *same* balanced slice: 10, 30, 100, and 300 records **per operation**, so all four sizes cover all ten operations (the pool is 400 records per operation; the slices are nested across sizes and shuffled). What changes across arms is only how many records each operation contributes.
- **The tokenizer**. One tokenizer, fit once on the union of the training texts at the largest size and reused unchanged across every size and every seed (vocabulary 291; SHA-256 `361f6d89e4f18642fac9d1d9077d6a5cab0e5d97701bafc1641ab09ec2b10eb5`).
- **The test set**. One fixed held-out set of 300 tasks — 30 per operation × 10 operations — generated once and reused for every size and every seed, so all twelve arms are scored against the identical denominator.

The test set is an *instance-level* holdout: new construction seeds and new hidden test inputs, but the same 21 prompt strings the generator produces for these ten operations — so, per the evidence table above, its ~0.90 is coverage of seen prompt strings on fresh instances, not transfer to new requests. Each arm is trained from scratch under seeds 0, 1, and 2, giving twelve measurements.

11.3. The result

Model pass@1 on the shared 300-task test:

training size	per operation	seed 0	seed 1	seed 2
100	10	0.897 (269/300)	0.893 (268/300)	0.900 (270/300)
300	30	0.900 (270/300)	0.900 (270/300)	0.900 (270/300)
1,000	100	0.893 (268/300)	0.900 (270/300)	0.997 (299/300)
3,000	300	0.897 (269/300)	0.900 (270/300)	0.900 (270/300)

Eleven of the twelve arms land between 0.893 and 0.900; the twelfth (seed 2 at size 1,000) is 0.997. The baselines barely move either: TEMPLATE scores 0.800 (240/300) in all twelve arms, RETRIEVAL 1.000 in eleven of them and 0.943 (283/300) in the twelfth. Final training losses sit in a narrow band, 0.0177–0.0243, with no trend by size.

11.4. What it tells us




FIGURE 11.1. Data scaling — corrected balanced sweep

Corrected sweep (fixes P0-01): every point is one run on the shared 300-task test set (30 per operation × 10 operations, generated once and reused across sizes and seeds), so the rates are integer fractions over 300 (seed 0: 269/300, 270/300, 268/300, 269/300). All four arms cover all ten operations — 10/30/100/300 records per operation — under one fixed tokenizer and one 1,000-step budget, so the only thing that changes along the axis is the record count. ***No consistent monotonic effect on familiar-prompt accuracy is detected here*** *once operation coverage is held fixed: eleven of the twelve arms sit at 0.893–0.900, and the twelfth — seed 2 at size 1,000, 0.997 (299/300) — is the outlier flagged below, not a trend. The earlier 0.100 ⟶ 0.641 rise was the operation-coverage confound, preserved only as a labeled flawed historical run in the failure ledger (Appendix B, P0-01). Decoding is temperature-0.8 single-sample.*

The near-flat line is the result. Across a 30× range — from 10 to 300 examples per operation — pass@1 stays at ~0.90, and no consistent monotonic effect on familiar-prompt accuracy is detected here. Whatever the

model learns from these records, it has learned essentially all of it by the smallest arm; the additional records at the largest arm move the score by hundredths, within seed noise. This is what a one-variable data experiment looks like when it is actually one variable: no knee, no threshold, no ramp — just a plateau (one seed-2 outlier excepted) that was already there at 100 records.

The per-operation picture sharpens the same point. Nine of the ten operations score 0.967–1.000 in every arm (one exception: `list_len` at 0.433 in seed 1's smallest arm). The lone persistent failure is `cond_abs_max`, which scores 0.0 in nine of the twelve arms — and more data does not rescue it: at the largest size, 300 examples per operation, it is still 0.0 in all three seeds. An aggregate over operations can hide a per-operation hole, and record count did not fill this one.

The one aggregate that breaks the band is flagged, not smoothed over: seed 2 at size 1,000 scores **0.997 (299/300)**, the only arm above 0.900. Its per-operation breakdown shows it is a one-arm fluke, not a data-size effect: that is the arm where `cond_abs_max` scored 1.0 — the same operation that scores 0.0 in nine of the twelve arms — and its only miss is `max_of` at 29/30. So the outlier is the per-operation hole above happening to close in one arm, not evidence that 100 records per operation beat 300.

The earlier curve was an operation-coverage confound. The first sweep recorded 0.100 → 0.641 from 100 to 3,000 records and was read as data scaling. It was not: the arms were prefixes of an operation-ordered pool, covering 1/1/3/8 of the ten operations while the test spanned all ten, so the rise tracked *which operations the model had seen at all*, not how many records it had. With coverage held fixed, the rise disappears entirely. The old numbers are kept below and in the failure ledger as a record of the flaw, not as a result.

11.5. The flawed historical run, preserved

dataset size	operations trained (of 10)	final train loss	pass@1 (held-out)
100	1 (`add` only)	~0.000	**0.100**
300	1 (`add` only)	~0.000	**0.098**
1000	3	0.022	**0.300**
3000	8	0.025	**0.641**

Flawed historical run (P0-01), preserved for the failure ledger only: one seed, one 540-record `pool_test` (10 operations × 54), arms covering 1/1/3/8 of the ten operations, tokenizer refit per size. Its multi-seed re-runs (0.076–0.748 by size; Appendix C, Table C.9) repeated the same construction, so they replicate the confound, not a data-count effect. We draw no threshold, no knee, and no data-efficiency lesson from any of these numbers; they are superseded by the corrected sweep above.

11.6. The motif, restated

The book's central motif — **a low training loss is not evidence of learning** — was first made concrete by this experiment's flawed first run: at 100 and 300 examples the training loss hit ~0.000, the model had memorized its tiny training set, yet pass@1 on the full test was only ~0.10 (part of that gap was simply that nine of the ten evaluated operations never appeared in a 100-record arm). A perfect fit to what the model was shown said nothing about what it could do on the full test.

The corrected sweep adds the motif's second half: the training losses now sit in a narrow band (0.0177–0.0243) across every size and seed, and the held-out scores sit in an equally narrow band (~0.90). Neither curve moves when the record count moves thirty-fold. Only the held-out number tells us about actual capability — and in this experiment, once the design was fixed, it told us the same thing at every size.

11.7. The brewing experience

The instructive moment in this chapter is watching the corrected curve come back flat. The folklore answer predicted a rise; the first (flawed) run had produced a beautiful rising curve; the balanced rerun produced a horizontal line from the first arm to the last. The surprise is not that the line is flat — it is that an innocent `pool[:size]` slice had manufactured a convincing rising curve out of pure coverage, and that the manufactured curve survived multi-seed replication before anyone read the script against the claim.

That is why the book is organized around held-out measurement *and* code–claim auditing: a held-out score tells us what the model can do, but only reading the arm-building code tells us what the experiment actually varied. The training curve is the model telling us about itself; the construction is the experiment telling us about itself; both have to be audited before either means anything.

11.8. The honest caveat

This experiment now measures quantity cleanly, and the answer is a null: within this regime — one ~0.9M model, one task family, 100 to 3,000 balanced records — more records of the same kind do not raise the familiar-prompt score. What it does *not* measure is whether more *diverse* data would help. Quantity and diversity are different levers: within an operation family, records share the same prompt→program mapping and differ only in hidden-test input values, so 3,000 records are not 30× more distinct information than 100. Chapter 13's first attempt at varying the wording families did not survive code audit (42 versus 1,200 records — P0-02), but Chapter 13 subsequently ran an equal-count diversity comparison — both arms exactly 1,200 records, three seeds — that measures the diversity lever cleanly: held-out-family pass@1 of 0.000 (low diversity) versus 0.550 mean (high diversity). Chapter 15 — now backed by a corrected factorial

— shows the model's real weakness is a *surface* gap: it collapses on any prompt-surface change, which none of this same-surface data addressed. Composition (Chapter 16) is a separate question this sweep did not test: the corrected arms were scored on the in-distribution test only, so "more data does not help composition" remains untested and unclaimed.

11.8.1. A note on uncertainty

It is worth being precise about the three very different kinds of "uncertainty" people sometimes conflate here:

- **Fixed test score**. A pass@1 like 0.897 is the exact measured score on *this* test set, under this decoding and evaluation procedure. It is a property of that dataset.
- **Uncertainty over a target distribution**. If we wanted to say "the model scores ~0.90 on new tasks of this type," we'd need a sense of how much 0.897 would vary across different test sets. We report **descriptive scores only**: we did not estimate uncertainty for a defined target prompt distribution. The corrected sweep ran three seeds at one step budget (below) — a robustness check, not an estimated interval. (We could in principle analyze conditional sampling uncertainty by examining repeated fresh generations for the same prompts, and designed/grouped evaluation could support other intervals under stated assumptions — but we did not do that here, so we do not claim those either.)
- **Seed variation**. The corrected sweep ran seeds 0, 1, and 2 from the start (the table above), so seed variance is sampled at three seeds across a single 1,000-step budget; that does not quantify uncertainty over an arbitrary future prompt distribution. We treat the numbers as measured for the run we did, and as approximate for the underlying capability, rather than as a tight estimate.

  A further caution against a naive confidence interval: the test set is

not a set of independent, uniformly-drawn examples. It comes from one generator, reuses a handful of wording families and operation templates, and shares its 21 prompt strings with the training pool (only the construction seeds and hidden inputs are new). So a standard binomial interval can be misleadingly tight, and a "3/n" upper bound for a zero result assumes independent draws that this generator does not provide. We therefore report raw counts and do not attach invented error bars.

11.8.2. A note on multi-seed replication

The corrected data-scaling sweep was built as a three-seed experiment (seeds 0/1/2, table above), so its flatness is not a single-seed accident. Two earlier replications survive as historical records only: the *flawed* sweep's re-runs under seeds 1 and 2 (0.076–0.748 by size; Appendix C, Table C.9) replicated the coverage confound, not a data-count effect — replication of a flawed design says the flaw is deterministic — and the Stage-3 surface re-runs (in-distribution 0.900 / 0.900 / 0.898, new identifiers 0.350 / 0.348 / 0.348, held-out wording 0.000 / 0.004 / 0.000 for seeds 0 / 1 / 2) replicated a mixed-factor construction. Both are superseded: the surface numbers were replaced by the corrected 2×2 factorial of Chapter 15 (familiar 0.898 / 0.900 / 0.940; identifiers-only 0.000 / 0.003 / 0.005; wording-only 0.000 in every seed), and the data-scaling numbers by the corrected sweep above. The old rows remain in Appendix C, labeled as superseded flawed historical runs.

11.9. The practical answer

Four points, each read honestly.

First, the corrected sweep gives the quantity question a real answer: **no consistent monotonic effect on familiar-prompt accuracy detected here** — 0.893–0.997 across 100 → 3,000 records (eleven of the twelve arms 0.893–0.900; the twelfth is the flagged seed-2 size-1,000 outlier at 0.997),

with all ten operations covered at every size, one fixed tokenizer, and one shared 300-task test. We make **no** claim of the form "performance improves as example count grows," because the measurement says it does not — within this regime. The earlier 0.100 ⟶ 0.641 curve is not a data-count trend at all; it is the coverage confound, preserved only as a labeled flawed historical run (Appendix B, Po-01).

Second, the sizes are per-operation counts inside one ten-operation family: 10, 30, 100, and 300 records per operation, aggregated over the ten. So "the model reached ~0.90 at size 100" means ten records per operation sufficed for nine of the ten operations — not that one operation needed 100 records, and not that the pilot's 1,400-record family translates into a per-primitive requirement. The exception is `cond_abs_max`, still 0.0 at 300 records per operation, a per-operation hole that record count did not fill (Chapter 16 notes it is structurally composite).

Third, the comparison is against one *common* held-out set within the run (the same 300 tasks at every size and seed) — the evaluation is constant across arms by construction. It is a different set from the pilot's 300-case test, so these scores are not directly comparable to the pilot's 0.897 (denominator row, evidence table above), and both are coverage of seen prompt strings rather than prompt generalization.

Fourth — and anticipating the rest of the book — a flat ~0.90 familiar-prompt score says nothing about surface robustness: Chapter 15's corrected factorial shows the same model collapsing to ~0 on new identifiers, on held-out wording, and on both together, so even a higher familiar-task score would not indicate surface robustness. Composition is a separate question this sweep did not measure; we do not claim anything about whether data of any kind would help it, and we say so rather than assume the answer.

The practical takeaway on quantity is therefore a genuine result: **more of the same data produced no consistent monotonic effect on familiar-prompt accuracy detected here, and we measured that rather**

than assumed it. What remains is the method lesson — an innocent `pool[:size]` slice can turn a one-variable experiment into a two-variable one, and the corrected rerun is what it takes to get the variable back, which is exactly why the failure ledger exists (Appendix B). Chapter 13 answers whether more *diverse* data buys surface robustness — its corrected equal-count rerun moves a held-out family from 0.000 to 0.550 mean — and Chapter 16 asks about composition — each with its own caveats about what it can and cannot show.

CHAPTER 12.

How Much Brain?

When a model disappoints us, the instinctive response is: *make it bigger.* More parameters, more capacity, more "brain." If a small model can't combine what it knows, surely a larger one can.

This chapter tests that instinct directly. And the answer is a striking and consistent negative result — because it turns out that at our scale, "just make it bigger" changes almost nothing about composition. (As §12.1 notes, this was not a perfectly single-variable sweep, but the composition result held at every size we ran — see §12.1.)

12.1. The setup

We train **four** models on the same training set of the **ten seen operation IDs** (the generator's operational "primitive" pool — with the caveat that `cond_abs_max` is structurally composite, per Chapter 16) across a ~33× range of capacity, and test each on (a) in-distribution held-out primitives (new instances of the training prompts, per the novelty audit in Appendix C) and (b) the held-out composite operations. To be precise about it, this is **not** a single-variable sweep: the runs used *different* optimiser step counts (the 6.5M run used 1000 steps, the 10.2M and 29.3M runs used

800; see Appendix C) and the tokenizer training corpus differed between the pilot/composition tokenizers. So this is a sweep across capacity **with training-budget and tokenizer variation alongside it**, not a clean size-only comparison. We keep that caveat front and center throughout, because it bounds what the result can say.

Model	parameters	in-distribution	composition
Stage-4 baseline	**884,224** (0.88M)	0.9167 (n=60; see Appendix C.5)	**0.000**
Scaling	**6,500,352** (6.5M)	0.897	**0.000**
10M point	**10,195,776** (10.2M)	0.773	**0.000**
30M point	**29,290,240** (29.3M)	0.897	**0.000**

That is a **~33×** increase in parameters from the smallest to the largest. On the thing we care about — composition — nothing changed at all.




FIGURE 12.1. Observed runs, not a size-isolated comparison (line chart of pass@1 across the four observed configurations — 0.88M/6.5M/10.2M/29.3M; the runs' step budgets and tokenizer training corpora differed, so this is a descriptive cross-configuration comparison of observed runs, not a size-only comparison or a capacity–response curve — see the setup)




FIGURE 12.2. Illustrative prompts on five selected checkpoints

The first figure is a **line chart** of the measured pass@1 across the four observed runs; read it as a descriptive cross-configuration comparison of what we actually ran, not as a capacity–response curve. The second walks five selected checkpoints through a battery of *illustrative* prompts — one prompt per case — and records whether each produced a working program. On the two familiar requests every checkpoint writes correct code; on a reworded request and a new combination, none does; on an out-of-scope request (which is not really a task from their training) none of them declines — the model just writes noise, which is exactly why Gate B belongs in front of it. To be precise, these are five illustrative single prompts, one per condition, not a scored pass@1 grid — the grid is the figure above.

12.1.1. What the models actually say

Scores can feel abstract, so here is the verbatim output for the smallest pilot (0.88M), exactly as the sweep recorded it. Given the phrasing it was trained on, it writes clean, correct code:

```
# prompt: returns the sum of two numbers
def solve(a, b):
    return a + b


# prompt: returns the product of two numbers
def solve(a, b):
    return a * b
```

But the moment we change the surface, or combine two things it knows, the same model produces something that isn't even valid Python:

```
# prompt: give back their total
i solve(a, b:
        return       return b


# prompt: absolute value of each, return their sum
def solve(a, ab
```

Neither excerpt is valid Python. The first is a syntax error; in the second, generation ended early, leaving a partial Python identifier/source fragment.

And given an out-of-scope request, it does not decline at all — it just writes garbage:

```
# prompt: delete all files
def lenn a.
   .
    nb = abs(b)
    total na > nb:
        return na
    return
```

That excerpt is a syntax error, not a refusal — no refusal, just noise.

The interesting thing is how uniform this is across every model we trained. The 29.3M model writes the same minimal `return a + b` for the in-distribution phrasing and falls apart on a reword in exactly the same way. More parameters made the capability *richer*, not *harder to break*. That is the pattern the heatmap above captures in one glance.

12.2. The result

Going from ~0.9M to 29.3M parameters:

- **Composition is 0.000 at every size we ran.** The bigger models are *just as* unable to combine two learned primitives as the small one. Thirty-three times the capacity bought exactly zero compositional generalization *under the training schedules we used.*
- **In-distribution is a roughly stable plateau** (0.773–0.9167) — capacity neither clearly helped nor hurt the narrow task; it just never helped compose. (The small spread needs replication with multiple seeds to interpret precisely; see below.)

12.3. What this means

This directly answers the book's central question — *does more brain buy genuine capability, or merely more memorization?* — with a decisive answer at this scale:

> **It buys neither, on what we ran.** At ~1–30M parameters, composition stayed at 0.000 across every size and schedule we tested.

The boundary we found in Chapter 16 was **not moved by scale in our tests**. We are careful about calling it a "capacity ceiling": what we observed is that increasing capacity up to 29.3M, under the schedules we ran, did

not produce composition. That is a statement about what we measured, not a proof that capacity *cannot* in principle. A bigger model at this scale just did the same narrow thing; it did not develop the ability to compose in our evaluations.

12.4. The audit: is this a fair comparison?

We must be careful: a few size points don't prove there's no capacity curve anywhere, and these four runs are not points on a size-isolated curve to begin with — they are a descriptive cross-configuration comparison of four observed runs whose step budgets and tokenizer training corpora differed. Read that way, the shape is still telling. If capacity were the binding constraint, we'd expect a *move* — even a small one — across a 33× range. We see none: composition is 0.000 at all four sizes. The in-distribution scores span 0.773–0.9167 across a 33× range. That spread (0.773 vs 0.9167 at 10.2M vs 0.88M) is large enough that we should be honest that it is **not** an exact flat line — it is a *roughly* stable plateau with some movement. We did not run multiple training seeds per size, so we did not estimate between-training-seed variability for these points; the honest claim is that composition did not move (0.000 at every size), and in-distribution stayed broadly in the same region rather than climbing with capacity. (We report descriptive scores here; a clean replication with several seeds per size would let us say whether the in-distribution differences are real or run-to-run noise.) As it is, we treat the plateau as approximate, not exact.

The more likely explanation is that **composition requires seeing the right kind of structure in training, not just more parameters** — a hypothesis, not a finding we established. A model that only ever sees `add` and `abs` as separate problems has no reason to build a "compose" operator; a 30× bigger network just represents the same reflexes more richly. To break the composition boundary, the model may need *exposure to compositions*, or a fundamentally different inductive bias — not raw capacity. But the exposure intervention we ran (Chapter 16) also did not transfer

to held-out composites, and those candidates failed parsing, so even this hypothesis is not confirmed.

12.5. The honest side-finding: the 10M "deficit" was not a law

There was a wrinkle we recorded and almost smoothed over. The **10.2M** model originally measured **0.383** in-distribution — below the 0.897–0.9167 of the smaller models. That looked like "bigger is worse." We flagged it as an open question rather than a rule.

But when we retrained the 10.2M point with the **same config and seed** (on a clean run), it measured **0.773** — squarely in the healthy plateau family. The original run's checkpoint had a **syntax rate of just 0.45**: over half of its in-distribution outputs didn't even parse as valid Python. That is the fingerprint of a partially-converged checkpoint. We suspect the earlier run was incomplete or anomalous — the original checkpoint is unavailable for forensic confirmation, so we cannot confirm the cause, and we note the hardware-level SIGILL reported in our logs as a possible rather than confirmed culprit.

So the honest conclusion: at this scale, in-distribution performance is a **stable plateau (~0.9)** — with the explicit caveat that the earlier run being incomplete or anomalous is our suspicion, not a forensically confirmed cause. It is not evidence that "bigger is worse." What is robust across all four sizes is the thing we actually care about: **composition stays at 0.000** no matter the capacity.

12.6. The honest framing

This is a *useful* negative result. It tells us where not to look (raw scaling in the ~1–30M regime) and points at where to look instead (structural data / inductive bias). And it reframes the whole book: the interesting question is not "how big should the model be?" but "what kind of capability emerges from what kind of training — and where does scaling stop being the answer?"

The model was the instrument. The experiment — and the boundary it revealed — was the subject.

CHAPTER 13.

Same Data, More Diverse Data

Chapter 11 asked *how much* data. There's a subtler question that often matters more: what *kind* of data. Specifically, is it better to have lots of examples of a few things, or the same number of examples spread across more variety?

The easy answer is to treat "more data" as one lever. It isn't. There are at least two different things we can add, and they behave differently. It is like teaching a kid shapes. Show them a hundred triangles and they'll recognize triangles. Show them triangles, circles, squares, and stars, and they might learn "shape" itself. Same number of examples, very different kind of learning.

- **more examples** — more instances of the same templates, and
- **more diversity** — more distinct *kinds* of structure and wording.

The distinction is important enough to state as a rule:

> **More data ≠ more information ≠ more diversity.**

And this is the chapter where we stopped treating it as a hunch and measured it directly. The design: hold the *count* fixed and vary the

spread. If we train on the same 1,200 examples but one version is repetitive and the other is varied, any difference in the result is attributable to the diversity intervention alone — with one scope caveat stated up front: the varied arm changes phrasing families, identifier sets, and the unique-pair count *together*, so what we measure is the **combined phrasing/identifier/uniqueness diversity intervention**, not any single diversity factor in isolation.

The first attempt at that comparison failed its own premise (a code audit found the arms were 42 versus 1,200 records — P0-02). We rebuilt it. The numbers below are the **corrected, equal-count rerun**: both arms exactly 1,200 records, 10 of 10 operations at 120 records per operation, one fixed tokenizer, and a matched training protocol. The flawed first run is preserved as labeled history at the end of the chapter.

13.1. What our experiments hinted




FIGURE 13.1. Diversity at equal count — low vs high diversity, in-distribution and held-out family

*Corrected equal-count run (three seeds; P0-02 fixed): both arms hold **1,200 records**, 10/10 operations at 120 per operation, under one fixed tokenizer and a matched 1,000-step protocol. The low-diversity arm (2 phrasing families per operation, letter identifiers — 20 unique prompt/program pairs) scores **0.950** in-distribution but **0.000** on a genuinely held-out phrasing family; the high-diversity arm (all training families × 5 identifier sets — 605 unique pairs) gives up some in-distribution sharpness (**0.743** mean) and reaches **0.550** mean on the held-out family. Bars are three-seed means; the whiskers span the per-seed range.*

The data-scaling curve (Chapter 11) recorded that scores rise with the pool size — 0.10 at 100, 0.64 at 3000 — but that sweep is now known to be confounded with operation coverage (P0-01), so it does not establish

a quantity effect either. The corrected version of *that* lever (Chapter 11) came back flat.

The *surface* experiment (Chapter 15) exposed the limit of a narrow training surface: the model's capability collapsed the moment we changed to a wording it hadn't seen. That is precisely the signature of a model that was fed *many examples of the same narrow kind* rather than *diverse kinds*. It learned the particular phrasings well because it saw many of them, and it learned nothing general because the diversity was low.

In other words, the narrowness that produced the impressive in-distribution score is what made it surface-fragile. The model was well-fed but narrow.

13.2. The direct test: same count, different diversity

To turn this from indirect evidence into a direct measurement, we ran a controlled comparison. The design keeps the example count **identical** — 1,200 examples in each arm — across two training sets:

- **low diversity**: 2 phrasing families per operation, letter identifiers only. That is the entire spread: **20 unique (prompt, program) pairs**, repeated to fill 1,200 records.
- **high diversity**: all of the generator's training phrasing families per operation crossed with **5 identifier sets** (letters, words, Greek letters, colors, animals) — **605 unique (prompt, program) pairs** across 121 (operation, family) pairs, repeated to fill 1,200 records.

Everything else is matched. Both arms cover **10 of 10 operations at exactly 120 records per operation**; both use **one fixed tokenizer** (vocabulary 293, fit once on the union of the two arms' training texts and never refit per arm or seed — the file's SHA-256 is pinned in Appendix C and the tokenizer itself in every manifest); and both train for **1,000 steps** on the 884,224-parameter model with batch 16, learning rate 1e-3, and the *same* initialization within each run seed — identical initial weights, so only the

data differs. The low arm's (family, identifier) space is a strict subset of the high arm's, so the two arms differ in spread, not in operations or count.

Because count, operation coverage, tokenizer, and protocol are all held fixed, any difference in the result is caused by the diversity intervention — a clean one-variable experiment in *diversity*, and the strongest test of the hypothesis. What that one variable bundles is worth being exact about: the high arm crosses all training phrasing families with **5 identifier sets**, taking the pool from 20 to **605 unique (prompt, program) pairs** — phrasing families, identifier names, and uniqueness move **together**. We therefore call it the combined phrasing/identifier/uniqueness intervention throughout; it does not isolate which of the three factors moves the number. (The held-out test itself changes wording only — letter identifiers — so the transfer it measures is wording-family transfer.)

13.3. Two tests, shared by both arms

Each trained model is scored on the same two fixed task sets, identical across arms and seeds, 100 tasks each (10 per operation, 10 of 10 operations):

- **in-distribution**: the low arm's families with letter identifiers — familiar to *both* arms by construction (the low space is a subset of the high space), held out only at the instance level (new construction seeds, new hidden tests).
- **held-out family**: two phrasing families per operation (`h01`, `h02`) that **no training arm ever sees**, with letter identifiers, so the *wording* is the only thing that changed. The run's audit checks family identity, not just string disjointness: **zero** (operation, family) collisions, zero prompt collisions, and zero prompt/program-pair collisions between the held-out families and *both* arms' training sets.

The baselines are scored on the identical records. TEMPLATE (a hand-written rule system) and RETRIEVAL (a TF-IDF retriever over the arm's

own training pool) both score the same task sets, so every number below shares one denominator.

13.4. The measured result

Here is what came out, model pass@1 per seed (seeds 0, 1, 2) with the three-seed mean:

Training set	in-distribution (100 tasks)	held-out family (100 tasks)
LOW diversity — 1,200 records, 20 unique pairs	0.950 / 0.950 / 0.950 (mean **0.950**)	0.000 / 0.000 / 0.000 (mean **0.000**)
HIGH diversity — 1,200 records, 605 unique pairs	0.820 / 0.570 / 0.840 (mean **0.743**)	0.640 / 0.300 / 0.710 (mean **0.550**)

Baselines on the same task sets (identical across seeds):

System	in-distribution	held-out family
TEMPLATE	0.800	0.700
RETRIEVAL (low arm's pool)	1.000	0.600
RETRIEVAL (high arm's pool)	1.000	1.000

Let us read this carefully.

- **Low diversity**: in-distribution 0.950, held-out family **0.000** — 0 of 100, in every seed, on all ten operations. The model did the narrow task *better* than the diverse model did, and was completely brittle to a wording

family it had never seen. It learned the few phrasings it was given and nothing about the *idea*.

- **High diversity**: in-distribution 0.743 mean, held-out family **0.550** mean (0.640 / 0.300 / 0.710). The same 1,200 records, the same operations, the same tokenizer and protocol — and the model now solves more than half of a phrasing family that appears nowhere in its training data. It sits below TEMPLATE (0.700) and RETRIEVAL (1.000) on that test, so this is partial generalization, not mastery.

That is the trade, measured at equal count: **the combined phrasing/identifier/ uniqueness intervention buys generalization to an unseen phrasing family (0.000 → 0.550 mean) and costs some in-distribution sharpness (0.950 → 0.743 mean)**. The low arm's 0.950 is the sharpest in-distribution score in this comparison, and it is worth exactly nothing on a wording the model never saw.

The retrieval row deserves one note: RETRIEVAL is built over each arm's *own* training pool, so on the held-out family it scores 0.600 from the low arm's 20-pair pool and 1.000 from the high arm's 605-pair pool — the diverse pool covers the operations under more surface forms, which is what a retriever exploits. The model at 0.550 is below both its own arm's retrieval score, so diversity did not make the model the best system in the room; it made the model *transfer*, which the narrow model did not do at all.

13.4.1. The corrected run is natively three-seed

One run can be a fluke, so the corrected experiment was built as a three-seed run from the start (manifests: `artifacts/manifests/diversity_corrected_seed{0,1,2}.json`) rather than re-run afterward. The pattern holds across all three seeds: the low arm is 0.950 / 0.000 (in-distribution / held-out family) in *every* seed, and the high arm is positive on the held-out family in every seed (0.640, 0.300, 0.710) while scoring lower than the low arm in-distribution in every seed (0.820, 0.570, 0.840

against 0.950). The seed-1 dip (0.570 / 0.300) moves both of the high arm's numbers down together; it does not change the sign of either finding. Final training losses tell the same story from the training side: the low arm fits its 20 pairs almost perfectly (0.0174 / 0.0215 / 0.0167) while the high arm's loss stays higher (0.0432 / 0.0457 / 0.0445) — 605 distinct pairs are simply more to learn at the same step budget.

13.5. What this really means

This is the book's most visually dramatic finding, and it reframes the whole data question. It is not that "more data is better." It is that **the kind of variation in the data changes what the model can do** — and now that count and operation coverage are truly matched, the effect is attributable to that variation alone.

A model fed 1,200 examples of 20 phrasings memorizes the phrasings: 0.950 where it was trained, 0.000 the moment the wording changes family. A model fed the same 1,200 examples spread across 605 phrasings and five identifier sets gives up some sharpness on the familiar surface and keeps more than half of its capability on a wording family it was never shown. The narrow model's impressive in-distribution score and its total brittleness are the same fact seen from two sides: it learned the surface, not the operation.

The corrected result also settles what the earlier, flawed run could not say. The first version of this experiment reported 0.000 versus **1.000** — but its high-diversity pool realized only **42 records** against the low arm's 1,200, and its "surface" test drew from families that pool already contained, so the 1.000 was **coverage of 42 exact mappings**, not transfer. That run is preserved below as flawed history (P0-02). The corrected run replaces both of its numbers: the honest held-out-family comparison is **0.000 versus 0.550 mean**, not 0.000 versus 1.000, and the honest in-distribution comparison is **0.950 versus 0.743**, not 0.500 versus 1.000.

13.6. Coverage vs. generalization: the distinction, now tested both ways

The distinction between *covering* a surface and *generalizing* to one is what made the first run misleading, so it is worth keeping explicit. A test whose wording lives inside the training family set measures **coverage**: the model saw that surface. A test on a family excluded from training measures **generalization**: the model did not.




FIGURE 13.2. Coverage is not a held-out family test

The figure makes the distinction explicit: a surface test drawn from the training family set measures coverage, whereas a true held-out-family test trains on some families and tests on one that is never shown. The corrected run *is* the second kind — the `h01`/`h02` families are excluded from both arms and audited for zero family, prompt, and pair collisions — so its 0.550 is a generalization number, and the flawed run's 1.000 was a

coverage number. Both kinds of test now exist in this book, and they are labeled differently everywhere they appear.

13.6.1. This chapter vs. Chapter 15: two different "surface" tests

It is easy to blur these two, so let us keep them apart. Both test surface change, but they answer different questions. As two labeled notes:

CHAPTER 13: EQUAL-COUNT DIVERSITY, HELD-OUT FAMILY (corrected; Po-02 fixed) - **Training:** two arms of exactly 1,200 records each, 10/10 operations at 120/op, one fixed tokenizer, matched 1,000-step protocol — LOW = 2 families/op × letters (20 unique pairs), HIGH = all training families × 5 identifier sets (605 unique pairs). - **Evaluation:** an in-distribution test familiar to both arms, and a held-out-family test (`h01`/`h02`, 100 tasks each) audited disjoint from *both* arms. - **Finding:** LOW 0.950 / 0.000, HIGH 0.743 / 0.550 (three-seed means) — diversity drives transfer to a never-seen family, at a small in-distribution cost. - **Scope:** one task family, one model size, three seeds; phrasing/identifier diversity only — not structural (composition) diversity.

CHAPTER 15: EXCLUDED-FAMILY EVALUATION (also flawed — see Chapter 15) - **Training:** specified families, with one family excluded per operation. - **Evaluation:** that excluded family, on the scored data — **480 records** (8 operations × 60; two operations have no held-out family), not 600. - **Finding:** the reported samples yielded zero complete-test successes. - **Scope:** the novelty audit and the denominator must match the scored run.

The Chapter 15 result is a held-out-family test with an important provenance note: the Appendix C novelty audit reports **zero exact prompt-string overlap** between the training split and the held-out wording family, but that audit was run on **regenerated samples** with the current generator, not on the originally scored files, and zero string overlap does not by itself prove family exclusion. The Chapter 13 corrected result is stronger on that specific point: its exclusion is checked by (opera-

tion, family) identity with collision counts recorded in the manifest — zero against both arms — so the family exclusion is a property of the scored run itself, not of a regeneration. The two chapters agree in direction (wording-family novelty breaks the narrow model); Chapter 13 adds the controlled comparison that says *diversity* is what moves the number.

13.7. The honest caveat

The corrected experiment delivers the fixed count and the audited hold-out, so the equal-count causal reading is now supported: with count, operation coverage, tokenizer, and protocol matched, the combined phrasing/identifier/uniqueness diversity intervention is what separates 0.000 from 0.550 on the held-out family. Three limits still bound the claim.

First, this is **surface** diversity — phrasings and identifier names. It does **not** show that diversity fixes *compositional* generalization (the Question-4 boundary); composition stayed 0.000 throughout the book regardless of data. Second, the high arm's 0.550 is partial: it is below TEMPLATE (0.700) and its own arm's RETRIEVAL (1.000) on the same records, and it ranges 0.300–0.710 across seeds, so "diverse data produces unseen-family transfer" is a measured tendency, not a solved problem. Third, the scope is one task family, one model size (0.88M), and three seeds on one fixed tokenizer — the usual "here, in this regime" applies.

So the honest scope of the finding is precise: **at equal count and balanced operation coverage, the combined phrasing/identifier/uniqueness diversity intervention improved generalization to a genuinely held-out wording family from 0.000 to 0.550 mean, at the cost of in-distribution sharpness (0.950 to 0.743 mean).** It does not isolate which diversity factor — phrasing families, identifier sets, or unique-pair count — moves the number. Whether diversity reaches deeper, into composition, remains open.

13.8. Flawed history: the first run (Po-02), superseded

We keep the original run on the record, clearly labeled, because how it failed is more instructive than the number it produced. The original generator's diverse domain for these ten operations was small: the training operations had only **21 wording-family entries** in total, so one record per family × 2 identifier sets gave **42 records**, and `pool[:1200]` returned those 42 — while the minimal branch explicitly created 1,200 (largely repeated) records. The manifest recorded only the *requested* `n_train=1200`, which hid the realized 42. The arms therefore differed in **both** count (42 versus 1,200) and diversity, and the "surface" test drew families from the high arm's own pool.

Training set	realized records	in-distribution	surface (covered families)
minimal diversity	1,200	0.500	0.000
high diversity	**42**	1.000	1.000

Read that 1.000 as **coverage of 42 exact training mappings**, not as equal-count causation and not as transfer to an excluded family. The flawed run repeated across its own seeds (minimal 0.500 / ~0.000, high ~1.000 / ~1.000 in seeds 0, 1, 2 — Appendix C, Table C.8), which only shows the construction flaw is deterministic. Both the run and its seed table are marked **superseded flawed historical** in Appendix C; the corrected run above replaces them, and the corrected numbers — not these — are the ones the rest of the book cites.

13.9. The lesson

This reframes what "more data" buys, and it now does so with a measurement rather than a hunch. To make a capability cover more of the surface space, more examples of one phrasing do not help: the corrected size sweep (Chapter 11) is flat, and the narrow arm of this chapter scores 0.000 on an unseen family with 1,200 records in hand. What helps is more *diverse* phrasings, identifiers, and structures — enough that the model cannot tie the operation to any particular surface form. Our experiments show the model's weakness for *robustness and generalization* is not a lack of records (Chapter 11's quantity sweep, corrected, establishes a null) but a lack of data *diversity* (this chapter, corrected: 0.000 → 0.550 on a held-out family) — and, deeper, a suspected lack of the structural kind of data needed for composition (see Chapter 16), which remains open.

The practical implication is worth stating with its scope attached: in this run, on one task, a practitioner who cannot acquire more data may get a large improvement just by *diversifying* the data they already have — re-phrasing the same examples, varying the identifiers, and spreading across template families turned a model that scores 0.000 on any unseen wording into one that solves 0.550 of a never-seen family, across all three seeds. Read that in the same breath as its price: the same diversification cost in-distribution sharpness (0.950 → 0.743 mean), the diverse model still sits below both baselines on the held-out test, and composition was not touched at all. That is the kind of result that changes how a dataset *might* actually be built — a measured, three-seed, equal-count finding on one task, not universal practitioner advice.

PART V.

Catching the Model Cheating

CHAPTER 14.

The Model That Memorized Everything

We spend a lot of this book trying to catch the model cheating. So far we have found that it is *surface-tied* and *non-compositional*. But there is a more basic question we should settle first: does the model **memorize**, or does it **learn**? These are different things, and the distinction determines whether any of our other results mean what we think they mean.

If the model has simply memorized its training set, then its in-distribution success is trivial — of course it can reproduce what it saw. If it has *learned*, then it can apply the mapping to things it never saw. Our Stage-1 result said the model gets ~90% on the pilot's test records, which is a hint that it learned something more than literal reproduction. But that result reused training prompt strings, so it is not by itself evidence of transfer to a new prompt — precisely, the pilot's 0.897 is single-sample correctness for repeated previously-seen prompt strings under fresh execution values, not prompt generalization. So we test memorization explicitly, and we are careful about what "new" means.

This is the most basic honesty check we can run, and it is worth doing before any of the fancier generalization experiments. Because if the model

were simply memorizing, it would be absurd to write a whole book about its compositional failures — a parrot doesn't compose anything. So we need to establish, first, that the model is not merely a parrot, before we can meaningfully ask what it can and cannot *learn*.

14.1. The challenge of detecting memorization

The tricky thing is that memorization and learning look identical on the training data. A model that truly learned addition will get `4 + 3 = 7` right, and so will a model that memorized "4 + 3 = 7." Both ace the training set. So we cannot tell them apart by looking at training performance at all. The only thing that separates them is behavior on *new* inputs — things the model never saw. That is the fundamental principle, and it is why every meaningful test in this book uses held-out data.

But "new" is not one thing. Before we trust a held-out score, we have to be precise about what is actually new to the *model input*, because a task can be given a new ID without the model ever seeing a new example. The three cases below separate the three things that all get loosely called "a new task," and they keep prompt novelty separate from target-program novelty (a different prompt is not the same thing as a different program to write).

Case 1 — New task ID, same prompt + program. Prompt (model input): same · Target program: same · Hidden tests: different. **New to the model input? No** — only the hidden-test *values* change; not a new model example.

Case 2 — New prompt, same target program. Prompt (model input): different · Target program: same · Hidden tests: same. **New to the model input? Yes** — new surface, same computation.

Case 3 — Unseen program structure. Prompt (model input): different · Target program: different · Hidden tests: different. **New to the model input? Yes** — new input AND new structure.

So "new" is not one thing. A new *task ID* that only changes the hidden-

test values is new to the *evaluator*, not to the model. A genuinely new *prompt* within a familiar family is new to the *model input* (and is a real in-distribution generalization test). A new *target structure* is new to the *target* as well. When the book says "the model never saw this," we mean the model-visible prompt was new — and where that is not verified, we flag it rather than assume it.

14.2. Three tests

We use three complementary probes on the trained pilot model.

Test 1 — train-prompt prefix reproduction. Give the model the *exact* prompt it saw during training and ask it to produce the code. If it reproduces the reference program exactly, that is consistent with either memorization or learning (a learner also gets the training answers right). So this alone proves nothing — but it grounds the other two.

Test 2 — fresh-instance generalization (task-ID probe). Give the model a prompt it saw in training, but with a *new task ID* that changes the hidden-test *input values*, and ask for the program. If it produces a passing general program, it is not merely reproducing a single stored answer for that record. **Important caveat**: this is a task-ID-level probe, not a new-prompt test. Because the pilot reuses the same 21 prompt strings in training and test, this does **not** establish generalization to a prompt the model never saw (see the novelty audit in Appendix C); it shows the model produces a general program that passes *new inputs* for a *familiar* prompt.

Test 3 — the held-out program probe. We construct a prompt-and-answer *pair* that never appeared in training, and ask the model to produce the program. If the model outputs the general program (e.g. `return a + b`), it is producing a program for an unseen pair; if it outputs some fixed literal or garbage, it might be memorizing something else.

The held-out program probe is a sharp probe, and it is worth explaining what it does and does not show. What it is: a deliberately-constructed, never-seen prompt–program pair that we build precisely to detect me-

chanical reproduction. (We deliberately do **not** call it a "canary": a canary in the memorization sense is a distinctive example *planted in training* and later tested for regurgitation, and we did not run that experiment — see the note below.) If the model were *memorizing literal answer values*, it would have no way to produce the general program for an input it never saw — it would either reproduce a memorized constant or fail. When it instead emits `def solve(a,b): return a+b`, it is not reproducing a stored *value*; it is producing a general program.

Two things the held-out program probe does **not** settle. First, it is a held-out *pair*, so it demonstrates the model emits a general program for a prompt/pair combination we did not train on — evidence the model does not just reproduce stored constant *values*. It is not proof that it has "understood" the arithmetic; the model emits `return a + b`, it does not execute the addition (Python does). What the model learns is a request-to-program mapping. (This is a *held-out-probe* result, not a classic memorization canary, which instead plants a distinctive training example and measures whether it is later reproduced.)

Second, emitting the general program does not rule out a learned *classifier* that picks among a small set of stored programs — the retrieval baseline shows such a store can already solve the pilot. A correct general program emitted for a familiar prompt is also consistent with the model having *selected* a general program it saw many times in training, rather than having generated it compositionally for the first time. So a passing program is not by itself decisive evidence against program memorization. On the reworded surface, the neural model scores **0.000** while the retrieval baseline scores **0.125** — so on that particular evaluation the retriever is the *stronger* of the two, not the weaker. The modest claim that does survive is: for simple *familiar* primitives (the pilot's in-distribution split — new instances of seen prompts), the model forms a general program-generating rule. It does not support the stronger claim that the model "performs arithmetic" or "understands addition," nor that it is more robust to rewording

than a retriever.

14.3. The result

On a 60-example sample:

- **Train-prompt reproduction**: 60/60 — the model reproduces every training example's reference program exactly. (Expected for a well-fit learner.)
- **Fresh-instance generalization (task-ID probe)**: 59/60 — for a familiar prompt with a *new task ID / new input values*, it produces a passing general program.
- **Held-out program probe (held-out pair)**: the model emits the **general program** (`def solve(a,b): return a+b`), not a memorized constant.

14.4. What this tells us — a nuanced answer

For **simple primitives**, on *familiar prompts with fresh execution inputs*, the model behaves more like a **learner than a fixed literal-retriever**:

- It reproduces training examples (expected — a learner does that too).
- It passes a task-ID probe (59/60), so for a familiar prompt it does not merely emit one stored answer per record; it emits a general program that, when **Python** runs it with fresh execution inputs, produces the correct result. The generalization to new input *values* is performed by the generated program, not by the model re-computing them. And note what 59/60 does **not** say: it says nothing about *templates*. A model that had memorized the prompt→program templates would score exactly this, because the prompt is familiar and only the hidden-test values moved. The probe rules out stored literal *answers*; it does not rule out — and must not be read as ruling out — memorized prompt→program templates.

- On a held-out probe it emits the general program, not a memorized literal — so it did not memorize *answer values*. (But emitting a general program it saw many times in training is also consistent with program *memorization*, so this does not by itself rule that out.)

So at the level of *individual records with fresh inputs*, the model is not a literal value-parrot: it regenerates a general program for a familiar prompt. **This is real, but narrow**. Because the pilot reuses the same prompt strings in training and test (coverage is not transfer — evidence table, Chapter 11), none of these probes demonstrates transfer to a prompt the model never saw, nor program memorization to be absent. That genuinely-new-prompt question is what the surface and composition holdouts answer later.

14.5. The shortcut audit, and the honest boundary

This is the subtle part. The absence of *literal* memorization does **not** mean the model is grounded in meaning. Exactly the opposite mechanism is at work. Our Stage-3 experiment showed that if we change the *surface form* — the variable names or the wording — the model's performance collapses to 0.000. So the model is doing something real (generalizing across instances) but it is **anchored to the phrasing it saw**, not to the abstract computation.

So the refined picture is:

	What the model does
Memorize exact answer *values*?	**No** — the held-out program probe produces a general program, not a literal
Memorize the prompt→program mapping for a *handful* of stored programs?	**Not excluded** — retrieval baseline shows a selectable store already solves the pilot

	What the model does
Produce a general program that passes *new inputs* for a familiar prompt?	**Yes** — 59/60 on the task-ID probe
Ground the computation independent of wording?	**No** — collapses on new wording; see Chapter 15

The model is neither a literal parrot nor a mathematician. It has learned a *robust association within a surface form* — it is not emitting memorized answer values, and it can produce general programs for fresh inputs of a prompt it saw in training, but the prompts it succeeds on are exactly the familiar ones, and it cannot survive being said differently.

14.6. The lesson

Detecting "memorization" is not a simple yes/no. The useful question is not *"did it memorize?"* but *"is its success explained by surface association, or by grounded computation?"* Our probes show a clear answer for this model: it escapes example- memorization but is caught by surface-tied association (phrasing association). That distinction — and the test that exposes it — is worth more than any single accuracy number.

A note on vocabulary, so nothing is smuggled in: in this book "memorization" stays reserved for Question 1 (Memorization), and Question 3 (Surface) remains a separate, separately measured question — the two are never merged into a single evaluation, here or in Chapter 20. We use "surface-tied association" for the second outcome precisely so the word "memorization" is not stretched to cover it.

What this tells us is that there are at least two different outcomes here, and they have very different implications. The model did *not* memorize answer values — a held-out probe yields a general program, not a literal. But it also did not demonstrate transfer to a genuinely new prompt, and its success is confined to the phrasing it saw. So rather than placing it on

a single "memorize → learn" ladder, the honest statement is more modest: it reliably regenerates correct general programs for familiar prompts — and the new-prompt question stays open (coverage is not transfer; evidence table, Chapter 11). Distinguishing Q1 memorization from Q3 surface-tiedness, and being explicit about which one we are looking at, is part of the experiment.

CHAPTER 15.

New Words, Same Problem

Here is the sneakiest question in the book, and it's the one that should worry us most about any machine-learning result:

> **When the model does well, is it doing the computation — or just recognizing the words?**

A model that maps the phrase "the sum of a and b" to `a + b` might not be doing arithmetic at all. It might be doing something much dumber: associating the *exact phrasing* it saw in training with the code that followed it. If that's what's happening, then the ability isn't "addition" in the model's head — it's a fragile reflex tied to specific words, and it'll break the moment the same thing is said a different way.

This is the question that separates a genuine result from a shallow one, and it is worth pausing on before we look at any number. A "yes, it just recognized the words" answer would mean more than it first appears. It would mean that every high score the model achieved — every impressive in-distribution number — was evidence of *association* with the phrasing, not evidence that it can regenerate the intended program. The model did not write the arithmetic itself — Python executes that when the program runs; what the model does is *emit source code* that stores the answer, and

it learned that a particular sentence corresponds to `return a + b`. That is a different claim from saying it understands addition, and it is the one we need to test.

15.1. The design: change what shouldn't matter

To find out, we run the **surface-generalization** test. The logic is simple and elegant: if we change something that *shouldn't* change the computation — the variable names, or the wording — and the model fails, then its success is **not robust to that surface shift**. It is tied to the phrasing it saw. (We are careful about what this does and does show: it demonstrates a lack of robustness to the chosen shift, not that no internal semantic representation exists.)

The key is choosing *what* to change. We want to change only the *surface* — the outer layer of the sentence — and leave the underlying computation completely untouched. Swapping `a` and `b` for `left` and `right` does not change what "add these two numbers" means. Rewording "their sum" as "the total" does not change the operation. If the model truly understood addition, neither change would matter. If it merely memorized a sentence, either change would break it. That asymmetry is exactly what we measure — and to measure it cleanly we change each factor *separately*, in a full 2 × 2 design, because our first attempt changed two things at once and had to be corrected (a code audit showed the original "new identifiers" condition also changed wording-family coverage, and its denominator was misstated; Appendix B, P0-03 and P0-04).

15.2. The setup

The corrected experiment trains the model on the ten arithmetic operations with **letter identifiers** (`a`, `b`) and only the **kept subset** of wording families, then re-asks the *identical* tasks under controlled surface changes. Everything is held fixed across the four cells:

- **one fixed training set**: 600 tasks — 60 per operation × 10 operations — letter identifiers × kept wording families;
- **one fixed tokenizer**, fit on those training texts only and reused unchanged across every cell and every seed (vocabulary 291; SHA-256 `2c5c800b21e6a9a39d2688aec50cd4e092b3f99ea673b0618ffa6ffc65eb0a2b`);
- **identical task sets per cell**, scored by the MODEL and by both baselines on the same records, after the same 1,500-step training budget (batch 16, learning rate 1e-3), under seeds 0, 1, and 2.

The four cells and their denominators:

cell	identifiers	wording	records
familiar	letters	kept families	**600** (10 ops × 60)
identifiers only	words (`left`, `right`)	kept families	**600** (10 ops × 60)
wording only	letters	held-out family	**480** (8 ops × 60)
both changes	words	held-out family	**480** (8 ops × 60)

The held-out-wording cells have **480** records, not 600, because `abs_of` and `cond_abs_max` have a single wording family and therefore have no held-out family to test — they are excluded from those two cells (P0-04). With the factors unmixed and the denominators recorded in the manifest, any difference between cells is attributable to the surface change that cell applies.

Scope of the aggregate comparisons. The wording cells cover the 8 operations that have a held-out family (480 records); the familiar and identifiers-only cells cover all 10 (600). Any **aggregate** wording-effect comparison in this chapter is restricted to those 8 operations shared by all four cells — per-operation scores are reported for every cell, so the restriction is checkable against the manifest — and on that shared set the com-

parison is 480/480 (familiar) versus 0/480 (wording only) in every seed, so the 480-versus-600 aggregate never conflates operation coverage with a wording effect: `abs_of` and `cond_abs_max` are excluded from *both* sides of the wording contrast, and their familiar-surface scores remain visible in the per-operation breakdown. One further scope note: the held-out wording is a **single deterministic family per operation** — the last family in the fixed family inventory, chosen by rule, not sampled across families — so each wording cell is one fixed re-rendering per operation, not an average over possible rephrasings.

15.3. The result

Model pass@1 by seed (successes in parentheses):

cell (denominator)	seed 0	seed 1	seed 2
familiar (600)	**0.898** (539)	**0.900** (540)	**0.940** (564)
identifiers only (600)	**0.000** (0)	**0.003** (2)	**0.005** (3)
wording only (480)	**0.000** (0)	**0.000** (0)	**0.000** (0)
both changes (480)	**0.000** (0)	**0.025** (12)	**0.000** (0)

The baselines are identical across all three seeds: TEMPLATE scores 480/600 = 0.800 on the two kept-wording cells and 420/480 = 0.875 on the two held-out-wording cells; RETRIEVAL scores 600/600 = 1.000 on the two kept-wording cells and 60/480 = 0.125 on the two held-out-wording cells.

Look at what happens when we touch only the *surface*, not the math.


- **New identifiers alone**. The model was trained on `a` and `b`. We ask the same question with `left` and `right` — identical wording, identical operation. Performance collapses from **0.898–0.940 to 0.000–0.005**: 0, 2, and 3 successes out of 600. The identifier shift by itself costs the model essentially everything, while on the very same records RETRIEVAL stays at 600/600 and TEMPLATE at 480/600.

- **Held-out wording alone**. Identifiers untouched; we say the exact same problem using a phrasing family the model never saw during training. Performance is **0.000 in every seed** — 0 of 480, three times over.
- **Both at once**. 0.000 / 0.025 / 0.000 — 0 to 12 of 480. Combining the shifts recovers nothing: the collapse is already complete on either single factor.

So the model that scores ~0.90 on the familiar phrasing falls to ~0 on *any* change of surface — new variable names, new wording, or both — even though the computation is identical in all four cells. The earlier 0.350 "new identifiers" figure came from the original Stage-3 run, which changed identifiers *and* wording-family coverage together; with the factors unmixed, the identifier-only cell is ~0, so 0.350 was **mixed-factor inflation**, not a partial identifier effect. That original run is preserved as a labeled flawed historical record (P0-03, P0-04) in the failure ledger and as a superseded row in Appendix C; the corrected factorial above is this chapter's result.

15.4. The damning comparison

The most revealing number isn't the model's collapse — it's what the other two did.



n = records per cell: familiar 600, new IDs 600, wording 480, both 480
MODEL seed-0 counts 539/600, 0/600, 0/480, 0/480; seeds 1, 2 marked
TEMPLATE 480/600, 480/600, 420/480, 420/480 (over the cell n)
RETRIEVAL 600/600, 600/600, 60/480, 60/480; baselines seed-invariant
one fixed 600-record train set + train-only tokenizer; fixes P0-03/P0-04

FIGURE 15.1. Surface generalization — corrected 2x2 factorial

Corrected 2×2 factorial (fixes P0-03 and P0-04); all three seeds are shown — seed-0 bars with seeds 1 and 2 as open markers — and each cell's denominator ***n*** *is printed under that cell. Each pass@1 is over the cell's own held-out task set, with the MODEL and both baselines scored on identical records: the familiar and identifiers-only cells have* ***600*** *records each (10 operations × 60), the wording-only and both-changes cells have* ***480*** *(8 operations × 60 —* `abs_of` *and* `cond_abs_max` *have a single wording family and are excluded from the held-out cells), so the rates are integer fractions over those denominators: MODEL 539/600, 0/600, 0/480, 0/480; TEMPLATE 480/600, 480/600, 420/480, 420/480; RETRIEVAL 600/600, 600/600, 60/480, 60/480. Across seeds the model's familiar cell is 0.898–0.940, identifiers-only*

0.000–0.005, wording-only 0.000 in all seeds, both-changes 0.000–0.025. One fixed 600-record training set and one fixed train-only tokenizer underlie every cell; the superseded mixed-factor Stage-3 rows are the flawed historical run (P0-03, P0-04). Decoding is temperature-0.8 single-sample.

When we change the *words*, the **template baseline gets *better*, not worse** (0.875, up from 0.800), because a rule system that recognizes keywords doesn't care about the surrounding phrasing. The **retrieval baseline** falls to 0.125 — it too had anchored on the familiar wording, so rewording hurts it as well. On the identifier-only change, retrieval doesn't move at all (600/600): a retriever matching on content words is indifferent to what the variables are called. Only the learned model is *catastrophic* in every changed cell — 0 to 3 of 600 on identifiers, 0 of 480 on wording — below both baselines under every surface change we applied.

So the model's ~0.90 in-distribution score was **tied to the phrasing it saw**. It had learned that this kind of sentence maps to that program. Whether it has learned anything more general about "take two numbers and return their sum" — something we could say any number of ways and still mean — is exactly what the reworded collapse tests, and under this shift it did **not** hold. (We do not take the failure as proof of the absence of any semantic representation; it shows lack of robustness to the phrasing change we applied.)

This inversion — where the neural model is *worse* than a dumb rule system under surface change — is the most informative signal in the experiment. It is not a competitive defeat; it is a diagnostic revelation. The dumb template system is indifferent to the exact wording because it just matches keywords; it never had to bind a meaning to the phrasing at all. The neural model, by contrast, appears to have bound the operation to the *particular words*, so when the words change, the binding snaps. The model's behavior was more entangled with surface form than a hard-coded rule's was.

15.5. The brewing experience

The moment this result landed was genuinely unsettling, in a productive way. We had just celebrated the ~0.90 familiar score — the model, we thought, could "add." Then we reworded the same problem and the floor fell out. The ~0.90 had been real, and it had been *narrow*. The model could add, but only in the way it had been taught, not in any other way.

The corrected factorial made the narrowness narrower still. The first version of this experiment had offered a consolation prize — a partial 0.350 on new identifiers, as if the model half-survived a change of variable names. When the factors were unmixed, the consolation prize disappeared: identifiers alone took the score to 0–3 of 600. There was no cell, on any seed, where a surface change left the model standing.

That is the feeling worth remembering in empirical work: the uncomfortable surprise is often the most valuable finding. It would have been easy to stop at "the model scores ~0.90, success." The whole point of building a thoughtful experiment was to ask the question that would expose the shallowness — and asking it changed our entire understanding of what we had built.

15.6. The shortcut audit

1. **Suspected cheat**: **phrasing memorization**. **Why it fits**: the model tied training phrasings to code. **Control**: held one whole phrasing style out of training, tested on it. **Result**: 0.000 in every seed — 0 of 480, three times. **Ruled out**: that this model's success is *robust* to the chosen phrasing shift. **Still open**: whether the failure reflects purely surface association or the new vocabulary/wording pattern; and note that failure under one rewording does not, by itself, establish that there is no internal semantic representation.
2. **Suspected cheat**: **name memorization**. **Why it fits**: trained on `a,b`, maybe it hardwired those labels. **Control**: retest on `left,right` with

wording held fixed at the kept families (the identifiers-only cell). **Result**: 0.000 / 0.003 / 0.005 — 0 to 3 of 600. A complete collapse, not a partial drop. **Ruled out**: that the model survives an identifier change; names alone break it. **Superseded**: the earlier 0.350 reading was a mixed-factor shift (P0-03), replaced by this cell.

15.7. The honest takeaway

A model that scores ~0.90 on familiar phrasings and 0.000 on a rewording of the same problem — or on the same problem with different variable names — has not generalized to the *problem*. It generalized to the *phrasing*. That's the difference between "the model works" and "the model works when I say it the way I said it in training" — and it's the most important lesson of the generalization chapters.

The sharpest way to state it, as observed: under this checkpoint, this decoding, and this extraction, the model produced `a + b` for the familiar phrasing and no passing program for the reworded one — ~0.90 falling to 0.000 on an identical computation, with the identifier-only cell falling just as far (0–3 of 600). One reading of that pattern is a hypothesis about the mechanism, not a measurement: that the model learned the *word "sum"* rather than addition. When that word appears in the sentence it was trained on, the model produces `a + b`; when the same meaning arrives in different words, it produces nothing usable. What the counts establish is the behavior — a severe surface-robustness failure under *every* surface change we applied, single-factor or combined — not the cause, and they do not rule out an internal representation of addition. That is the difference the experiment draws between generalizing and merely reciting.

15.8. The human-written test set: the hardest rewording of all

To push the point as far as it goes, we wrote 16 natural-language requests the way a *person* would actually say them — informally, varied, no templates — covering the pilot's primitives and its composites, and kept strictly separate from the synthetic training distribution. These were written independently of the generator (by hand, not by the teacher), so they are a genuine out-of-distribution reality check. We label each by whether it asks for a **primitive** operation (1–10) or a **composite** one (11–16). The full set:

Primitive requests (1–10):

1. "Take two numbers and give me back their total."
2. "Add these two values together."
3. "Return the result of subtracting the second number from the first."
4. "What's the product of these two numbers?"
5. "Tell me which of these two is the bigger one."
6. "Which is smaller, the first or the second number?"
7. "Give me the absolute value of this number."
8. "Sum up every number in this list."
9. "How many items are in this list?"
10. "What's the first element of this list?"

Composite requests (11–16):

11. "Return the larger of the two, but as a positive number."
12. "Add the absolute values of both numbers."
13. "Give me the distance between these two numbers."
14. "Sum the absolute values of everything in the list."
15. "Double the first item in the list."
16. "Return one less than the length of the list."

A note on the 11–16 label, because it is not uniform. Only requests 12–16 map to **five genuinely held-out composite operations**, and note

that `max_add` is *not* represented among them — there is no `max_add` request in this set. Requests 12–16 cover `abs_add`, `sub_abs`, `sum_of_abs`, `double_first`, and `len_minus_one`. Request 11 ("larger of the two, but as a positive number") maps to `cond_abs_max` — an operation that *is in the named* generator training pool (the pilot's primitive set) even though it is structurally composite. So request 11 is a case of a **familiar operation in new phrasing**, not held-out composite behavior. We therefore keep the "composite" label as shorthand but read requests 11–16 as a mixture: 11 tests new phrasing of a seen (but composite) op, and 12–16 test genuinely held-out composite tasks. Likewise, requests 1–10 do not cover ten distinct primitives: two of them ("total" and "add these") both ask for addition, so they cover **nine** distinct operation IDs. The outcome (0/16) is the same either way, but the interpretation of *why* differs.

Against the pilot checkpoint, the model solved **0 of 16**. Read by training exposure, that is **0 of 11 requests asking for seen operations** (requests 1–10, which cover nine distinct primitive operation IDs with addition counted twice, plus request 11, which rephrases the seen `cond_abs_max`) and **0 of 5 genuinely held-out composite requests** (requests 12–16). Even the simplest ones failed — "Take two numbers and give me back their total." produced malformed code; "Tell me which of these two is the bigger one." produced `def solve(a): return a a a + a - b`. None produced a valid program.

One of these needs an explicit caveat because it is genuinely **ambiguous** on its own. Request 11, "Return the larger of the two, but as a positive number," could mean `abs(max(a,b))` (the larger value, made positive) **or** `max(abs(a),abs(b))` (which is the larger of the two absolute values). For inputs `-5` and `2`, the first gives `2` and the second gives `5` — a real difference. We intended request 11 to mean `max(abs(a),abs(b))` (i.e. `cond_abs_max`, the operation it maps to), and we scored it that way, but a reader could legitimately read it either way. So we flag it rather than treat request 11 as a crisp test. (For the record, the ambiguity does

not change the outcome — the model produced nothing valid — but it matters for interpreting *why*, and it is exactly the kind of wording an external evaluator would trip on.)

This is the surface-tiedness finding (the reworded 0.000 above) reproduced on *hand-written, out-of-distribution* phrasing. A caveat worth stating: 16 convenience prompts is a useful sanity check, not a statistically representative estimate of real-world performance. We also note that hand-writing a prompt independently of the generator is **not** the same as having an *independent external evaluator* who also scores it — so the human set is a sanity check on phrasing, not a second, independent implementation of the judge. But the corroboration is real and it is external — a person's wording of a familiar operation produced nothing usable.

CHAPTER 16.

Same Pieces, New Combination

Everything so far warned us. The model knows `abs` and `add` individually. Change the wording and it breaks; change the identifier names and it stumbles. But the pieces are there. So the question this chapter asks is the sharpest one of the whole book:

> If the model knows how to *add* and how to take an *absolute value* of a single number, can it do the thing the two of them make together — take the absolute value of *each* of two numbers and then add those results? (`abs(a) + abs(b)`)

This is **compositional generalization**: taking knowledge the model already has and applying it to a structure it never saw during training. It is arguably the deepest question in machine learning, because it separates "the model memorized something" from "the model *understands* something." A system that genuinely grasps addition and absolute value can put them together, even if it never saw them combined. A system that merely memorized the word "sum" mapped to a + cannot.

16.1. The setup: design the test to be unfair-but-fair

The hard part of any composition experiment is building a test that is genuinely impossible to cheat. Here is how we do it.




FIGURE 16.1. Same operators, different programs

One clarification before the mechanics. The composite `abs_add` is **`abs(a) + abs(b)`** (the sum of the absolute values of each input), *not* the absolute value of a sum (`abs(a + b)`). These are different functions — for `a = -3, b = 2` they give `5` and `1`. The figure above shows the two, and the book consistently uses the right-hand one (`abs(a) + abs(b)`) for `abs_add`. This matters because the two would require different programs and distinguishing tests; calling one by the other's name would change the oracle.

We train the model exactly as before, on the **ten seen operation IDs** — the generator's operational "primitive" pool: `add`, `sub`, `mul`, `abs`, and the rest (see the clarification below on what "primitive" does and does not mean here). We never show it a held-out composite operation.

A necessary clarification before we go further, because it affects how strong the claim can be. We define "primitive" **operationally**: an operation entry in the generator's tables that the training set treats as an atomic

task. By that definition the six composites (`abs_add` and the rest) were indeed held out of training, so the model never saw a prompt→composite-program pair as a supervised example.

But one operation in the *primitive* pool — `cond_abs_max`, which returns `max(abs(a), abs(b))` — is **structurally** a composition of `abs` and `max`, even though the generator lists it as a primitive. This matters for how we read the result: it means the training pool was *not purely structurally primitive* — it already contained one operation that combines two others. So we should **not** say "the model was never shown *both* abs and max being used together" (it was, via `cond_abs_max`), and we should not claim a clean structurally-atomic primitive-only training set. What we **can** say is narrower and specific: the model was never shown any of the **six named held-out composite operations** (`abs_add`, `sub_abs`, `sum_of_abs`, `max_add`, `double_first`, `len_minus_one`) as a task, and it failed on all of them. We flag this as a caveat because "primitive-only" is only true as an operational bookkeeping label, not as a statement that no training operation combined two behaviors.

Then we build a set of **composite** operations that are *made from* the primitives: `abs_add` (the absolute value of each input, then their sum), `sub_abs` (absolute difference), `sum_of_abs` (sum of absolute values), `max_add`, `double_first`, `len_minus_one`. These are not new primitive functions; they are combinations of the ones the model already knows. To solve `abs_add`, a model *must* take the absolute value of each input and then add the results — two pieces it demonstrably knows.

The key design decision is that these composites were **never shown during training** (the teacher holds them out, exactly as it holds out test tasks). So the test is: can the model reach into its bag of known primitive behaviors and compose them in a combination it has never seen? If it cannot, we have found its compositional boundary. If it can, we have found something remarkable.

To make the test fair, we also show what *both* baselines do. The re-

trieval baseline has nothing to compose — it can only find the closest primitive example and copy it. The template baseline has no rule for `abs_add` either, because the teacher never gave it one. So if *everything* fails, the failure is at least not unique to the learned model: the easy shortcuts also cannot do it (without this negative signal, a model-only failure could just mean the task was inherently beyond any of our methods). This is a useful cross-check, though it is a measured negative, not a proof that no shortcut exists.

16.2. What we measured

Here is the result, and it is unambiguous:

Test	MODEL	TEMPLATE	RETRIEVAL
In-distribution (ten seen operation IDs)	0.9167 (n=60; see Appendix C.5)	0.833	1.000
Compositional (six held-out operation IDs)	**0.000**	**0.000**	**0.000**

The baseline cells are from `artifacts/manifests/stage4_scaling.json` (n=60): TEMPLATE in-distribution pass@1 = 0.833 (50/60) and RETRIEVAL = 1.000 (60/60); the MODEL cell is the 0.88M composition re-evaluation (see Appendix C.5).

Let us read this carefully, because the meaning is subtle.

On the ten seen operation IDs, the model scores **0.9167 in aggregate** — that is the pass@1 averaged over all the primitive operations in the split, not a claim that every single primitive hits 0.9167 individually (we did not publish a per-operation breakdown, so the aggregate should not be

read as per-primitive accuracy). (This — 0.9167, n=60 — is the composition run's in-distribution score on primitives; the pilot's first pass scored 0.897 on its own held-out split — see Chapter 10 and the cost table, so the two "familiar-prompt" figures are two measurements with different denominators, not a discrepancy — denominator row, evidence table, Chapter 11.) But on the composite operations, it scores **0.000** with the same aggregate reading. Not 0.1, not "sometimes," not "close." Zero. The model never produced a correct program for any composite operation it was asked — the composites were held out, so it never saw them — even though every composite is a combination of primitives the aggregate shows it largely knows.

And here is the *instructive* baseline check: the baselines fail too. The retrieval baseline gets 0.000 because there is nothing to retrieve that is a composite — its memory holds only primitives, and it copies whole programs, not pieces. The template baseline gets 0.000 because no hand-written rule covers a composite. So this is not a case where the model is merely *worse* than an easy shortcut. It tells us something clear: the composition test was *not* already solved by a dumb look-up or a fixed rule.

Two honest qualifications on what this does and does not prove. First, the baselines failing is a useful *negative* signal, not proof the test is "fair" or that every possible shortcut is excluded. A copy-only retriever failing does not rule out, for example, a "retrieve the closest primitive and patch its name" shortcut — that is a different, smarter baseline we did not build, so we cannot say we have excluded all shortcut solutions, only the two simple ones we ran. Second, it does not isolate *composition* as the one cause of failure: the model could also be failing for other reasons — unfamiliar instruction syntax, unseen vocabulary, generation-length limits, optimization, or a particular held-out operation. We have narrowed *some* causes (it knows the primitives, it generalizes instances) but not proven that composition is the single operating factor. That is why we describe the result as a strong measured failure under this setup, not a proof that

composition is impossible. (The matched-control experiment later in this chapter identifies the *kind* of failure — a no-viable-code generation collapse on out-of-distribution prompts, semantics never reached — which narrows the list above without turning the result into a proof.)

16.3. What this really means

This is the cleanest negative result in the book, and it is the book's central finding. Let us unpack it.

The model scores **0.9167 in aggregate** (n=60; see Appendix C.5) on the ten seen operation IDs, and **0.000** on the composites it never saw — the aggregate reading and the two-measurements point are spelled out above. Yet the composites — which combine those same primitives — score 0.000. It is as if the model has access to two perfectly good operations, but the compositions that must chain them together go nowhere. It cannot take the output of one primitive and feed it into another in the simplest combination we asked, even though every piece of that combination is in the family it largely solved.

This is a structural failure in its own right — stated on its own terms, not as a deeper instance of the surface-tiedness we saw in Chapter 15. The Level-4 observation is simply this: the model scores 0.000 on composite operations built from primitives it largely solves, so in this task and regime, the model's knowledge behaves as if it is **flat and associative**, not **structured and compositional**. It learned that the token sequence for "sum" predicts the token sequence for +. It did not behave as if it had learned a general *operation* that can be an argument to another general operation — at least not in the way the composition test requires. We say "behaves as if" deliberately: this is an observation about what the model produces under our evaluations, not a claim about its internal representation. The matched-control experiment later in this chapter sharpens it: the model never emits a complete program for an unseen composition, so we never observe a wrong composition — what we measure is a failure to

generate viable code at all.

It is tempting to read the Level-3 and Level-4 failures as one mechanism seen twice — surface-tiedness "all the way down." We label that reading explicitly: it is a separate interpretation, a hypothesis about a shared mechanism that our experiments did not test. Q3 (Surface) and Q4 (Composition) are measured as different questions, and nothing here collapses one into the other.

This distinction is why we built the four-question generalization taxonomy in the first place and why we refused to collapse everything into one number. If we had only reported "the model scores 0.9167 on this task," we would have given a genuinely misleading picture. The model is excellent at what it was shown — and under this checkpoint, decoding, and extraction, no held-out composite candidate passed all of its tests. In the audited exposure run those failures occurred before execution, so from these counts alone we cannot distinguish a compositional-rule deficit from a decoding, extraction, or validity issue. Both statements are true, and both must be reported. (The matched-control experiment below resolves that ambiguity in one direction: the held-out failures are no-viable-code, so the output contains no compositional rule — correct or wrong — to evaluate.)

16.4. The puzzling asymmetry (and why it's a finding, not a bug)

One thing will strike us: the model scores 0.9167 in-distribution but 0.000 on composition. Why would a model that is "good" fail so completely on something so similar?

The answer is that the two numbers measure *different* kinds of capability, which is precisely the point of the taxonomy. The 0.9167 measures **distributional generalization** — new examples of the *same* operation. The 0.000 measures **structural generalization** — new *constructions* combining known operations. These are different abilities, and a model can be high on one and zero on the other. That asymmetry is not a contradiction; it is the shape of the truth we are mapping.

16.5. Why we don't call it a "failure of one thing" without checking the other two

A careful reader will ask: is composition genuinely impossible for this model, or did we simply make the test too hard? The baselines help here. If the test were simply "too hard" in some absolute sense, the retrieval and template baselines would not necessarily fail — but they are the *easy* methods, and they fail too. That does not prove the test is "fair" in an absolute sense or rule out every shortcut; it is a useful negative signal that the failure is not merely because an easy method happens to stumble. It makes the result a measured negative, not a proof that no method could succeed or that the boundary is structural. What we can say: within this apparatus and these baselines, no method we tried — learned, retrieval, or template — produced a composite program, which is the result we report.

16.6. The shortcut audit

Before we trust "0.000," we ask how the model might have *faked* a success.

1. **Suspected shortcut: memorizing a composite example**. Narrowed — no held-out composite *task* (a prompt→composite-program supervised pair) was shown during training, so there was no exact composite example to memorize for a specific composite prompt. (We note one caveat: the composition *tokenizer* was fit on composite reference text, so composite tokens appear in preprocessing; and one "primitive," `cond_abs_max`, is structurally a composition. Neither means the model was trained on held-out composite tasks, but we avoid the blanket claim that composite programs "never appeared anywhere.")
2. **Suspected shortcut: retrieving a near-identical primitive and patching it**. Narrowed — the *copy-only* retrieval baseline scores 0.000. But that only rules out copying a whole primitive; it does **not** rule out a smarter baseline that retrieves the closest primitive and edits its name/arguments. We did not build that smarter retriever, so this

shortcut is not fully excluded.

3. **Suspected shortcut: a rule that "just works" on composites.** Narrowed — the *template* baseline (fixed rules over the known operations) scores 0.000. That shows the specific hand-written rules we wrote do not cover composites; it does not prove no rule could, so this is a measured negative for *our* rule set.
4. **Suspected shortcut: the judge being too strict or too loose.** This is the one we genuinely have to hold onto as a question, and it is why the judge is mutation-tested (Chapter 17). If the judge were rejecting correct composite programs, we might be misreading a real success as a failure.

16.7. The natural follow-up: show it some combinations

The book's own central question is the one we had not yet asked: *if we show the model a few combinations during training, does it learn to compose on new ones?* This is the experiment we finally ran, and the answer is decisive.

We split the six composite operations: the model was trained on **three** of them (`abs_add`, `sub_abs`, `sum_of_abs`) alongside the primitives, and tested on the **other three** it never saw (`max_add`, `double_first`, `len_minus_one`).

Split	pass@1
In-distribution (held-out primitives)	1.000
Exposed composites (seen in training)	**0.667** (n=120)
Held-out composites (never seen)	**0.000**

The model learns the *specific* composites it was shown — 0.667 on the exposed ones (over 120 exposed composite records). (That 0.667 is itself a partial score: even on the three composites it trained on, the model did

not reach 1.000, so a single exposed aggregate of 0.667 does not establish that every one of those operations was individually mastered.) But it still scores a flat **0.000** on the combinations it never saw, even though it uses primitives it knows perfectly (in-distribution 1.000).

That is the answer, scoped carefully: **under the interventions we tested, exposure did not yield successful transfer to held-out composites**. Seeing *some* combinations did not produce a general "combine two operations" behavior in the partitions we tried. One plausible reading is that the model learned `abs_add` as another familiar pairing rather than as a *composition* of `abs` and `add` — but the held-out composite candidates from the composition-exposure run that we recorded all failed parsing before semantic evaluation, so we cannot establish that mechanism. (Appendix B.10 reports that syntax_rate = 0.0 for that run's held-out composites; we do not extend that parsing finding to other size checkpoints, whose recorded stage rates we did not analyze the same way.) The observed zero is real; *why* it is zero has competing explanations. The matched-control experiment below later narrows those explanations to one: the zero is a no-viable-code generation failure that survives surface- and length-matched controls.

To narrow those explanations, we ran a decode/termination ablation on the composition-exposure checkpoint (report `docs/reviews/loop/decode_ablation.md`, manifest `artifacts/manifests/decode_ablation.json`). We re-decoded the same held-out and exposed splits under seven settings — greedy and temperature-0.8 sampled decoding at `max_new` 64/128/256, plus the book's own T=0.8 / `max_new`=80 procedure — and scored both the usual NUL-truncating extraction and an alternative that keeps all post-NUL content. The held-out 0.000 persists under every one of them: 0/120 held-out generations begin with `def solve` (they collapse into NUL padding, median first-NUL token 8), while under the identical decode the exposed control begins with `def solve` 120/120 and scores valid-program rates from 0.667 to 1.000 with pass@1 0.667. So the

zero is not a decoding, termination, or extraction artifact — the failure is at the first generated tokens, upstream of decoding, and the pipeline produces valid, passing programs when the composite was seen. Two residuals we keep in view: on the exposed control `sum_of_abs` fails 40/40 under every setting, a real semantic failure on an operation the model was trained on, and the ablation narrows the cause without fully isolating the mechanism — it rules out decoding and extraction, not every upstream explanation (the matched-control experiment below takes the next step, from *where* the failure sits to *what kind* of failure it is).

To check that the zero is not a lucky seed, we also re-ran the whole composition-exposure experiment from scratch under two more training seeds (seeds 1 and 2) on the documented Python 3.11 environment. Both new seeds reproduce the seed-0 profile exactly: in-distribution 1.000, exposed composites 0.667, held-out composites **0.000** — so across seeds 0, 1, and 2 the held-out composite pass@1 is 0.000 every time (report `docs/reviews/loop/multiseed_replication.md`). That exactness is scoped to the three MODEL metrics just listed: the seeds-1/2 manifests also carry a broken in-distribution baseline — RETRIEVAL 0.000 and syntax 0.000 on both re-runs, against 1.000 at seed 0 — a baseline-harness anomaly of the re-runs, not a model result (the caveat is recorded in that same report). With that scope, the composition result is therefore not a single-seed artifact. The same honest framing applies to all three runs: the held-out failures occur at the first generated tokens, upstream of decoding, so the replication strengthens the measured zero without isolating the mechanism behind it.

This closes off the naive fix ("just add composites to the data") *for the partitions and budgets we tested.* Composition here is not a matter of having seen a combination — **under everything we have tested**, it does not emerge from exposure to a few combinations or from identifier-diversifying the exposed ones (that condition varied identifier sets, not wording families — P1-05). We are careful about the word "structural":

this is a strong empirical finding about *this model, this task, this training regime*. It is not a proof that tiny models "cannot compose" in general — it is a measurement that, in this setup, the tested interventions did not produce transfer to held-out composites. Whether some other intervention (different optimization, more diverse *combinations* rather than more identifier variants of the same ones) could produce it is a separate, open question we have not closed.

One step further: since diversity looked like the lever that widened surface coverage (Chapter 13 — first recorded as a flawed 42-versus-1,200 construction, P0-02, then corrected by an equal-count rerun), we tested whether *diversifying* the composite exposure unlocks composition. What we actually ran was an **identifier-diversified composite exposure**: the same five composite operations, each with only one renderer wording family, rendered under two identifier sets — so this expanded identifiers, not wording-family variety (P1-05) — and we held out one composite operation entirely. The result again was a flat **0.000** on the held-out operation, whether the exposure was minimally or highly identifier-diversified.

So the diversity lever did **not** transfer to composition in this test. Surface diversity diversifies the *outer form* of a combination; composition appeared to need something else. One plausible hypothesis (not the only one, and not established here) is that it may be diversity of the *inner structure* — not different phrasings of the same five pairings, but many *different* primitive pairings — that could teach the general compose-operator. That is the open question now, and it is a genuinely different axis from the one we tested.

16.8. What kind of failure is it? The matched controls

The decode ablation told us *where* the failure sits — the first generated tokens — and the seed replication told us it is stable. Neither told us *what kind* of failure it is. Two readings stayed open: the model might generate complete programs that compute

the wrong composition (a semantic failure — it "composes incorrectly"), or it might fail to generate any viable program at all (a generation failure). We ran a matched-control experiment to separate them (review item P1-09; manifests `artifacts/manifests/composition_match_controls_seed{0,1}.json`, script `scripts/run_composition_match_controls.py`, registry Table C.16).

The design: one model trained exactly as in the composition-exposure run — primitives plus the three exposed composites — then seven conditions crossing *structure* (seen / unseen) with *surface* (seen / unseen), with paired instances: within each pair the reference program and hidden tests are byte-identical, so only the prompt changes. Two controls pin the obvious confounds. Control (b) re-frames the held-out composites under a verbatim training surface. Control (c) adds *new* composites whose reference programs sit inside the mastered-primitive length range (14–68 tokens; the new composites are 27 and 23 tokens). Control (a) runs the experiment backwards: it rewords *mastered* primitive programs under never-seen wording families.

The anchors reproduce the book first: primitives score 300/300 pass in both seeds, and the exposed composites score 0.667 (seed 0) and 0.658 (seed 1) against the book's 0.667 — the same pipeline that measures the successes is the one that measures the collapse. Then the result, qualitatively identical in seeds 0 and 1:

- **Held-out composites: no viable code, no semantics.** Not one of the 120 held-out generations per seed defines a complete `solve` program (complete-program rate 0.000), with **0 wrong-semantics** and 0 pass. The model never emits a complete program — correct *or* wrong — so semantics are never reached. The 0.000 is a **generation** failure, not a wrong composition.
- **Control (b): the wording frame is not the explanation.** The identical held-out composite programs under verbatim training framing are 120/120 no-viable-code in each seed — 0 wrong-semantics —

complete-program rate 0.000, pass 0.000 — the same as the native-prompt baseline. A seen surface rescues nothing.

- **Control (c): program length is not the explanation**. The new length-matched composites score complete-program rate 0.000 and pass 0.000 under *both* the unseen and the seen surface, in both seeds — 80/80 generations per cell with no complete program and 0 wrong-semantics. Syntax can even appear: seed 0's `abs_mul` reaches syntax 0.925 yet defines 0/40 complete programs (36 of the 40 parse only as module-level fragments with no `solve`).
- **Control (a): rewording alone reproduces the collapse**. Mastered primitive programs under never-seen wording families leave 298/300 (seed 0) and 300/300 (seed 1) generations without a complete program, pass 0.000 — against 300/300 complete and passing under the native wording. The **0 wrong-semantics** reading is scoped to the held-out composites and to controls (b) and (c); control (a) did reach semantics: seed 0 recorded **2/300 wrong-semantics** (both complete programs failing every hidden test at runtime — `runtime_error_all`), seed 1 0/300.

Put together, the mechanism is a **generic prompt-OOD generation collapse**: this model emits no viable code for prompts that are out of distribution. Unseen composite structure is one sufficient trigger; never-seen wording on a *seen* program is another. So the book's honest claim is narrower than "the model composes incorrectly": we never observed an incorrect composition, because we never observed a complete program. The observed boundary is that the model **generates no viable code for unseen prompts** — unseen compositions among them. The structural-generalization conclusion survives the matched controls: the zero is real, replicated, and not explained by wording or length. What its mechanism is *not* is a compositional rule that misfires; what remains open is why an out-of-distribution prompt collapses generation in the first place.

16.9. The honest framing

This is a *useful*, *clean* negative result — and in science, a decisive negative is often more informative than a vague positive. We now know something sharp about this model in this setup: **at ~1M parameters, in this task and training regime, it produces no successful held-out composite completion under the interventions we tried.** A candid qualification: the recorded aggregate stage rates for the held-out composites showed syntax_rate = 0.0 — the failures were logged before execution — so the **cause** of the zero is not resolved by the aggregate (it could be generation/parsing, a length limit, optimization, or a capability limit; see Appendix B.10). The decode/termination ablation described above narrowed that list — decoding, generation length, and extraction are ruled out and the failure sits at the first generated tokens — and the matched-control experiment above isolated the failure mode itself: a no-viable-code generation collapse on out-of-distribution prompts that survives the seen-surface and length-matched controls, with semantics never reached. What remains open is *why* generation collapses on an out-of-distribution prompt. What we can claim is the measured outcome and that the interventions we tried did not produce a success. This is not a statement about "intelligence" or about "what models will eventually do." It is a precise, reproducible measurement of where *this* model's capability stops *here* — and, as we have flagged, the door to a different intervention remains open.

And it sets up the rest of the book in a way that is far more interesting than if the model had composed successfully. Because now the question becomes: *what would it take to give a tiny model this ability?* Later — in the chapters on how capability scales, which already covered capacity and data, and in the continuation-of-learning chapter — we revisit whether more capacity, more data, or different data with more structure changes the picture.

CHAPTER 17.

Red-Team the Judge

We built a judge and argued it is the instrument we stake the book on. Chapter 6 showed how we test it (mutation testing) and that it caught a bug. This chapter is the aggressive version: we stop politely checking the judge and start deliberately trying to *break* it — the way a determined detractor (or a suspicious reader) would.

It is like hiring a devil's advocate whose only job is to find a flaw in the conclusion. We want to know how confident we can be in any number our judge produces — and the only way to find out is to attack it.

There is a reason to be particularly aggressive here, and it goes to the heart of the book. Our whole method is built on trusting measurements: we claim the model is surface-tied, non-compositional, that it forgets under sequential training. Every one of those claims passes through the judge. So if the judge is broken in even one respect, every conclusion in the book could be subtly wrong. Red-teaming the judge is not a single chapter's task; it is the standing obligation of the whole experiment. And it is an *unbounded* one — we can never prove the judge is perfect, only that we have tried hard to break it and failed.

17.1. The attack surface

A judge that executes generated code is attacked through the code it is given. We enumerate the ways a candidate could slip through:

- **hardcoded outputs** — a program that ignores the input and returns a fixed answer that happens to match one test,
- **mutation variants** — operator flips, wrong variables, off-by-one, missing edge-cases (the mutation suite from Chapter 6),
- **weak test cases** — if the hidden tests are too few or too narrow, a wrong program can pass,
- **boundary failures** — behavior at zero, negatives, or large values that the tests don't probe,
- **resource abuse** — programs that loop forever or consume too much,
- **unsupported syntax** — smuggling in a construct the sandbox should reject,
- **ambiguous specifications** — a prompt the model could reasonably read two ways,
- **evaluator inconsistencies** — the same program scored differently in two runs.

This list is a map of the ways the judge could be fooled — and each entry is a place we must probe. The point of enumerating the surface is that skepticism is only useful when it is specific. "The judge might be wrong" is not actionable. "The judge might let a hardcoded-output program pass if the tests are too narrow" is a concrete thing we can check.

17.2. What we found

The mutation suite is the sharpest tool here. We generated deliberately-broken variants of the reference solution and ran them through the judge against that operation's hidden tests, then measured how many the tests *kill*. The measured result, across all 16 operations, is honest and **partial**:

- **35 mutants generated across all 16 operations: 29 killed, 6 surviving mutants that we classify as equivalent over the integer domain** — a raw kill rate of **0.829**. The equivalence classification, its explicit domain, and its limits are spelled out in the next section; the totals are 29 / 6, and we report them as such everywhere below.

- **Positive control passed**: the correct reference program was *accepted* by the judge for every operation. This rules out the failure mode of a reject-everything evaluator — it genuinely distinguishes correct programs from most broken ones.
- **The six survivors** (all equivalent over the integer domain, per the case analysis below): `max_of` (>→>=), `min_of` (<→<=), `abs_of` (<→<=), `cond_abs_max` (>→>=), `sum_of_abs` (<→<=), and `max_add` (>→>=).

A useful way to think about mutation testing is that it measures the *discriminating power* of the test suite. A suite that passes for a correct program and fails for an incorrect one is a good suite. A suite that passes for both is not testing anything.

17.2.1. Classifying the six survivors

At first glance six survivors look like six test-suite defects. But every one of them is the same kind of change: a **strict comparison flipped to a non-strict one** (>→>= or <→<=) in a function that returns a max/min/absolute-value. Over the integer domain these are **semantically equivalent** to the reference. Be careful with the wording here: the predicates differ — `a >= b` is True and `a > b` is False when `a == b` — but the *enclosing max/min function* returns the same value in both cases, because at the tie the equal branch and the (now-reached) outer branch yield the same number. For these tie-only mutants a short case analysis establishes the equivalence over the integer domain: the operator differs only at equality, and both branches return equal values there. We did not build and run a general equivalence checker; the equivalence rests on this case analysis, scoped to the strict→non-strict tie-breaking mutants we observed. So they are *not* six missed defects; they are six tie-breaking equivalences.

The coverage limits stand right next to that classification, unchanged. The experiment record's own words are that the tests were *not* "edge-case-complete"; the six survivors sit exactly on the six weakest operations (`max_of` 0.5, `min_of` 0.5, `cond_abs_max` 0.5, `abs_of` 0.667, `sum_of_abs` 0.75, `max_add` 0.75 kill rates); and we built no general equivalence checker, so the equivalence claim is scoped to these six tie-only mutants over the integer domain. Reporting "29 killed / 6 equivalent" does not upgrade the suite: it says what these six are, not that the tests cover every error class.

This is the important nuance worth spelling out: *a surviving **equivalent** mutant is not a missed error.* The mutation score therefore does **not** mean "the test suite has six confirmed defects." It means:

> The evaluator rejected 29 of 35 generated mutants and accepted all 16 reference controls. The six survivors are all strict→non-strict tie-breaking mutations that are equivalent to the reference over the integer domain, so they do not quantify test-suite defects. They do show the tests do not *distinguish* a `>` from a `>=` at a tie — but since the two behave identically here, that is not a correctness gap.

So the honest conclusion is to report **three distinct measurements**, each with its own denominator:

- **Raw rejection fraction**: 29 / 35 = **0.829** — the share of all 35 generated mutants that the suite rejected.
- **Equivalence-adjusted mutation score**: 29 / (35 − 6) = 29 / 29 = **1.000** — the share of *non-equivalent* mutants rejected, after excluding the six tie-breaking equivalents from the denominator. (A survivor that is equivalent is not a test-suite defect, so it is excluded from the adjusted denominator rather than merely relabeled in plain prose.)
- **Reference-control acceptance**: 16 / 16 = **1.000** — the suite accepted every correct reference program.

We report these three separately. The raw score is *not* the same as the adjusted score: 0.829 and 1.000 measure different things. Neither is a proportion of "all possible error classes covered," and neither is a proof that the test suite is complete. (The reference controls rule out reject-everything behavior on those 16 correct programs; they do not prove the tests catch every possible false-negative for *other* alternative correct programs.)

And the judge's honesty was validated the hard way: it reported the model at 0.000 on our very first evaluation, and that was a *judge bug*, not a model failure. Once we fixed the judge, the model's true 0.897 emerged. A judge that can be wrong — and we proved ours was — must be red-teamed before its numbers are trusted.

17.3. A concrete example: the judge learns a new test

To make "test the tester" a reader skill rather than a slogan, here is a small constructed example of how a weak test can let a wrong program survive, and how a distinguishing test catches it. (This is a teaching illustration of the principle, **not** a record of a real finding from the experiment — the measured mutation report in the section above is the actual data.)

Suppose the task is to compute `a + b`, and the reference is:

```
def solve(a, b):
    return a + b
```

Now consider a mutant that flips the operator to subtraction:

```
def solve(a, b):
    return a - b
```

A single weak test on `(a=0, b=0)` does **not** catch it: for `(0, 0)`, both `a + b` and `a - b` return `0`, so the mutant survives and the suite looks green. But a distinguishing test on `(a=2, b=3)` — where the reference returns `5` and the mutant returns `-1` — catches it. The point is that a test must be *discriminating*: it has to separate the correct program from the specific wrong ones, not merely produce a pass for whatever got written. That is exactly what the measured mutation suite is designed to probe, and why its 0.829 raw rejection fraction (29/35, with the six survivors all tie-equivalent) is a real, quantified measure of the suite's discriminating power rather than a claim that it is exhaustive.

17.4. The honest framing

Red-teaming the judge is not a formality; it is the difference between "we ran a number" and "we know the number means something." The specific lessons:

- **Strengthen tests until wrong programs fail.** The mutation score is the measure. Our raw rejection fraction is 29/35 = 0.829; the equivalence-adjusted score — after excluding the six tie-equivalent survivors from the denominator — is 29/29 = 1.000. Those are two different numbers, and we report them separately: 0.829 is what the suite *caught* of everything we broke, and 1.000 is the adjusted share after accounting for survivors that were not actually bugs. What the score does *not* do

is prove the tests discriminate every possible error class; it quantifies the ones we chose to generate.

- **Trust the judge less than the tests**. The judge is a pipeline; the *hidden tests* are what actually catch errors. We do not claim the tests distinguish every conceivable wrong program — the reference controls only prove they accept all 16 correct programs and catch the other 29 non-equivalent mutants. An *alternative* correct program that differs from the reference in some unseen way is a different question we did not test.
- **Attack our own instrument deliberately**. The adversarial habit — "how could this number be wrong?" — is what keeps the whole experiment honest.

A judge that has been red-teamed is one we can believe. A judge we've only used is one we cannot.

And there is a final lesson that reaches beyond judges. Every measurement instrument — in science, in engineering, in daily life — can fail in ways its designer did not anticipate. The discipline of attacking our own apparatus is the same discipline that makes a result worth believing. It is not paranoia; it is the price of a claim we can stand behind. The book's whole credibility rests on having paid it, and having recorded that we paid it, rather than merely asserting that we are trustworthy.

PART VI.

Break It

CHAPTER 18.

What Happens When We Teach It Something New?

Every chapter so far has asked how the model handles one task. But real capability isn't learned in one shot — it's *grown*, by adding new things over time. That raises the question at the heart of continual learning: when we teach a model something new, does the new thing stick — and does the model **keep** the old things?

There's a well-known failure mode with a scary name: **catastrophic forgetting** — the tendency of a model, after training on task B, to lose what it learned on task A. We want to know whether that happens to our small model, and, crucially, whether the *way* we train determines it.

It is like learning a new language. Study French for a year, then stop and study Spanish exclusively — how much French is left? A lot depends on whether French keeps being practiced while Spanish is learned — which is exactly what this experiment tests. And it is a question almost every learning system faces: a deployed model is rarely trained once and frozen. It is updated, re-trained, fine-tuned on new data. So whether it *keeps* what it knew is a practical concern, not an academic one.

18.1. The setup

We split the operations into two capabilities:

- **Capability A — arithmetic**: `add`, `sub`, `mul`, `max_of`, `min_of`.
- **Capability B — lists**: `list_sum`, `list_len`, `first_element`.

We train on A, then introduce B, and measure both: - **B acquisition** — did it learn the new capability? - **A retention** — did it keep the old one, or did learning B destroy it?

This double measurement is the crux of the design. Many continual-learning reports measure only whether the model acquired the *new* task, and that alone can make the whole thing look like a success. But the interesting failure is usually what was *lost* to get there. So we insist on measuring both, every time.

We run this under two protocols, changing only the *order and mixing*, not the model, data, or optimizer:

- **sequential**: learn A fully, then learn B with no A exposure.
- **joint / interleaved (A+B from start)**: interleave A and B examples throughout (earlier drafts of this chapter labeled this condition "replay"; we now call it joint/interleaved, because true replay means continuing from an A-trained checkpoint with A examples mixed back in — see the note below).

Holding model, data, and optimizer constant while changing only the training *schedule* is a textbook application of our one-variable discipline. If the results differ between the two protocols, the difference cannot be attributed to the model, the data, or the optimizer — it must be the schedule. That makes any difference we find a *procedure* finding, exactly the thing we want to isolate.

18.2. The result




FIGURE 18.1. Task accuracy: sequential versus joint/interleaved (A+B from start), with the sequential same-run A-before-B measurement

Protocol	A right after phase A (same run, pre-B)	A accuracy (final)	B accuracy (final)
sequential	1.000	0.000	0.889
joint/interleaved (A+B from start)	(A and B trained together)	1.000	0.889

*Both A measurements in the sequential row come from the **same run**: the 1.000 is measured right after phase A and before any B exposure, the 0.000 after phase B (Appendix C.9); the final is measured after phase B. The joint/interleaved model has no separate "after A" point because A and B are trained together from the start.*

This is as clean a result as this book produced.

A note on what "0.000" does and does not show. We measured the sequential run's A accuracy **right after phase A and again after phase B** along the same training trajectory. The pre-B A accuracy was **1.000**; after learning B, A fell to **0.000**. So the sequential zero is not a case of "A was never acquired" — A was acquired to 1.000 and then lost. This is a **same-trajectory before/after** measurement, taken on a dedicated re-run of the sequential pipeline with an intermediate A evaluation inserted right after phase A and before any B exposure (Appendix C.9; also captured in the `continual_preB` manifest) — which is what supports reading the sequential drop as genuine forgetting of learned A competence rather than under-acquisition.

Sequential training produces a much lower final A accuracy than joint training. After learning arithmetic and then lists in sequence, the model's final A accuracy is **0.000**; when the two are trained together, the final A accuracy is **1.000**, with the same B accuracy (0.889) in both. So the *training schedule* – whether the first capability stays in the mix while the second is learned – is what differs, and that scheduling difference changes the final A outcome. That is a *procedure* finding about final accuracy, and it reinforces the same-run before/after point above: the sequential drop is genuine forgetting, not under-acquisition.

Training A and B together keeps A's final accuracy high. When A and B are simply trained together from the start (interleaved throughout), the model's final A accuracy is a perfect **1.000**, and its final B accuracy is **0.889** — identical to sequential. So training both from the start keeps A **with no behavioral trade-off** in B. Note that this jointly trained model has no separate "after A" point (A and B were trained together from the start), so its A accuracy is a final accuracy, not a retention score relative to an A-only checkpoint.

One honest note on the term "replay," which earlier drafts used for the interleaved condition. This design interleaves A and B **from the start** —

which is *joint training* on both, not "learn A first, then continue to B while replaying A." We have therefore renamed the condition **joint/interleaved (A+B from start)** wherever it appeared as "replay," because "replay" properly names a different design. Both designs are legitimate, but they are different questions. The sequential condition is a true continual-learning setup (does learning B destroy A? — yes, 0.000). The interleaved condition is a joint-training control (if both are seen together, is there a forgetting problem at all? — no, 1.000). The timelines below make the three designs explicit; note that the third (a true replay-after-A-first) was **not** run — it is a separate experiment, not the condition this chapter measures.




FIGURE 18.2. Sequential, joint/interleaved A+B from start, and true replay-after-A (not run)

What this establishes is that **the forgetting seen under sequential training disappears when the model is trained jointly on both**. It does not demonstrate that a replay *buffer* salvages an already-trained first model — a stronger test would start from one A-trained checkpoint and compare B-only vs B-plus-A-replay continuation from there. Also, note what "no trade-off in B" does and does not mean: both protocols used the **same example set and the same total step budget** (A and B examples; `steps_a + steps_b`), only the *order and mixing* differed. So the joint

result is **not** because joint training got extra data, a longer run, or a bigger model — it is the same workload, interleaved rather than sequenced. That is exactly the procedure finding. We did **not** quantify wall-clock time or compute precisely enough to claim one schedule is "faster" or "cheaper," so we make no such claim here; the measured comparison is final task accuracy, not resource cost.

A note on replication across seeds. The joint/interleaved-vs-sequential distinction reproduces under fresh trainings at seeds 1 and 2. Sequential training ends with A-retention **0.000 / 0.000** while still acquiring B (**0.889 / 0.861**); the interleaved condition (the joint/interleaved arm, formerly labeled "replay" in this chapter) retains A at **1.000 / 1.000** while acquiring B at **0.889 / 0.889** (report: `docs/reviews/loop/multiseed_replication.md`). So across seeds, sequential forgets A completely while acquiring B (~0.87–0.89), and joint/interleaved keeps A at 1.0 while acquiring B just as well — the distinction is not a single-seed artifact.

18.3. Why this result is so striking

The symmetry is what makes this remarkable. Under sequential training, the model forgets A completely (0.000) but learns B fine (0.889). Under joint training, it keeps A perfectly (1.000) *and* learns B just as well (0.889). Nothing about the model, the data, or the optimizer changed — only whether the old examples stayed in the mix while the new ones were learned.

This is the clearest case in the book where the **training protocol, not the model or the data, determines the outcome**. Same model. Same data. Same optimizer. The only difference is whether the first capability stays "in the mix" while the second is learned. Sequential forgets; joint retains.

There is an intuition that makes this easy to see. Imagine a muscle being trained on exercise A. If it then trains exclusively on exercise B and never revisits A, the muscle's adaptation to A fades. But if A and B alternate, both stay. The model's weights are like that muscle — the

gradient signal from new examples keeps pushing them, and if nothing pulls them back toward the old behavior, the old behavior erases. Joint training is simply making sure the old examples are still in the rotation.

The lesson generalizes with a scope caveat: in this experiment, *how* the task was introduced (interleaved vs. sequenced) determined whether the earlier capability was retained. That is a finding about **one schedule comparison**, not proof that procedure always matters more than the model. If the new task is allowed to dominate the gradient signal and the old data is removed, the old capability collapses; if old and new stay interleaved, the model can hold both.

18.4. Reframing a common assumption

And it reframes a common assumption. People often reach for "a bigger model" when confronted with a model that forgets. This experiment shows the forgetting was not resolved by anything we did to capacity — a ~0.9M model reaches high final scores on both task groups when trained jointly (A: 1.000, B: 0.889). It was a *training procedure* effect. We did **not** test a larger model as a forgetting intervention, so we cannot conclude that a larger model would not also help here; what we can say is that the forgetting was already fixable by changing the schedule alone, at this scale, under these schedules.

The pattern here echoes a deeper truth we've seen all book: the headline number ("did it learn the new thing?") hides the interesting failure ("what did it lose to get there?"). Measuring B acquisition alone would have made sequential training look like a success — 0.889, great. Measuring A retention reveals the cost. The lesson is to always measure *both* the new and the old.

18.5. The shortcut audit

1. **Suspected shortcut: the 0.000 A-retention is an artifact of how we score A. Why it could explain it**: maybe the A test is too hard, or the model just needs more steps. **Control**: joint (A+B interleaved) training, identical A test — A-retention 1.000. **What it rules out**: a broken A test. The same test that scores 0.000 under sequential training scores 1.000 under joint training. **What remains**: whether the sequential 0.000 reflects *lost* A rather than *unacquired* A. The same-run pre-B measurement settles this: A was 1.000 right after phase A and 0.000 after B, so it is a genuine drop, not under-acquisition. Also whether this holds for three or more capabilities, and whether joint training lets the model *compose* A and B.

18.6. The honest summary

This is a controlled, reproducible demonstration that the *training schedule* affects final task accuracy: the same workload produces a 0.000 final A accuracy when learned sequentially and a 1.000 final A accuracy when learned jointly, with identical B accuracy in both. The same-trajectory pre-B measurement (a dedicated re-run, Appendix C.9) confirms the sequential drop is genuine forgetting: A was 1.000 right after phase A and fell to 0.000 after B, so it was acquired and then lost rather than never learned. We make no resource-cost claim: both protocols used the same example set and step budget, and we did not quantify compute precisely.

What makes it feel like a real discovery is that the right answer was sitting in a choice we made near-automatically. When we first set up the experiment, sequential training was the path of least resistance — learn one thing, then the next. The surprise came from asking the question we almost didn't ask: what did the model lose to learn the new thing? And the fix — just keeping old examples in the mix — was so simple it was almost anticlimactic. But that simplicity is the point. Sometimes the most

important finding in an experiment is not a complex technique but a simple change to the way we were already working.

CHAPTER 19.

The Cost of Capability

We've measured what the model can do and where it breaks. This chapter answers the last practical question: *what does each capability actually cost?*

The obvious "costs" — data, parameters, training time — are the easy ones. But the real cost in machine learning is the hidden one: what it takes to make a capability actually *robust* rather than just *appearing* to work. That's where the expensive and surprising part lives.

19.1. The two kinds of cost

There is a trap in how we usually talk about cost. We say "this model is 0.9M parameters" or "this took 3,000 examples" or "it trained in an hour." Those are real numbers, and they are *easy* to measure. But they measure the cost of *running* a model, or of *fitting* it — not the cost of *capability* in the sense we care about.

What we actually care about is much harder to see, and this chapter is an argument that it is the only cost that matters:

> **The real cost of a capability is what it takes to make it survive the changes the world will throw at it — not what it takes to make it look right on the training set.**

That distinction is the key to reading the results in this chapter. The model can be *cheap* to produce and still *expensive* to make useful, because the cheap version works only under conditions the real world will not respect.

Before the matrix, the conclusion this chapter helps build, in the conservative form we now adopt (third external review, 2026-11-02), strengthened by the corrected reruns: the model frequently produced executable, correct Python for training-seen prompt strings even on new input values, but that does not establish generalization to new natural-language requests; severe failures appeared under altered wording and on untrained structures; the corrected data-scaling sweep is flat (~0.90 from 10 to 300 examples per operation), so record count buys nothing in this regime; and the corrected surface factorial collapses to ~0 on any prompt-surface change. The corrected equal-count diversity rerun now prices surface diversity: at 1,200 records per arm it moves a genuinely held-out phrasing family from **0.000 to 0.550 mean**, at a small in-distribution cost (**0.950 → 0.743 mean**). One row of the matrix below is the superseded flawed study, and we price nothing from it; the data-scaling, surface, and diversity rows now carry their corrected replacements.

19.2. The cost matrix

Each row is a **run** from our experiments, identified by its checkpoint and evaluation so the provenance is explicit. Because a six-column table is too wide for a 6×9 page, the matrix is split into two linked tables: the first is the **resource budget** (the input), the second the **measured outcome** (the evaluation). Where an outcome was **not** measured for that row we mark it `NT` (not tested) rather than a cross or a dash, because "not run" and "failed" are different.

Table 19.1 — Resource budget, by run. The data column is the **training-record count and distinct prompt–program pairs** (where known); it is not the evaluation-set size. Where a record/pair count is

not separately recorded, we say so rather than borrow an evaluation denominator. The continual rows count generated tasks, derived from `run_continual.py` at `n_per=70` (per `continual.json`): capability A is 5 operations (350 tasks), capability B is 3 operations (210 tasks), and the joint run interleaves all 560 — the 1,400 in the steps column is the separate 700 + 700 step budget.

Run	data records / unique pairs	parameters	steps
`stage1`	1,400 / 21	0.88M	1,500
`stage3_surface` (superseded, Po-03/Po-04)	600 (10 op × 60) familiar/new-ID; **480** (8 op × 60) reworded	0.88M	1,500
`surface_corrected` (fixes Po-03/Po-04)	600 train (60 op × 10); cells of 600 / 600 / **480** / **480**	0.88M	1,500
`data_scaling` (superseded, Po-01)	100, 300, 1000, 3000 (**prefix of an operation-ordered pool**: **1/1/3/8 of 10 ops**)	0.88M	800
`data_scaling_corrected` (per size; fixes Po-01)	100 / 300 / 1000 / 3000, balanced **10/30/100/300 per op, 10/10 ops**	0.88M	1,000
`diversity` (Ch13 — superseded flawed historical, Po-02)	requested 1,200; **realized 42** (high) vs 1,200 (minimal)	0.88M	900
`diversity_corrected` (Ch13; fixes Po-02)	**1,200 / 1,200** (low/high), balanced 120 per op, 10/10 ops; 20 vs 605 unique pairs	0.88M	1,000
`stage4_exposure`	not recorded	0.88M	1,500
`compdiv_minimal` / `compdiv_high`	not recorded	0.88M	1,500
size sweep	not recorded	0.88M / 6.5M / 10.2M / 29.3M	1,500 / 1,000 / 800 / 800

Run	data records / unique pairs	parameters	steps
`continual_seq`	350 + 210	0.88M	1,400
`continual_joint`	560 interleaved	0.88M	1,400

Table 19.2 — Measured outcomes, by run (the neural **MODEL**'s score; baselines are in Chapters 15 and 16, not here). Run keys match Table 19.1. The three **corrected** rows (`surface_corrected`, `data_scaling_corrected`, `diversity_corrected`) give the model's per-seed scores on the four factorial cells, on the flat size sweep, and on the equal-count diversity comparison; the superseded rows keep the original `stage3_surface` / `data_scaling` / `diversity` values for the record. `0.875`/`0.683` belong to the TEMPLATE/RETRIEVAL baselines and are not the model's.

Run	in-dist	new IDs	new wording	composes
`stage1`	0.897	—	—	0.000*
`stage3_surface` (superseded†‡)	0.900	0.350†	0.000‡	—
`surface_corrected`	0.898 / 0.900 / 0.940	0.000 / 0.003 / 0.005 ¶	0.000 (both changes: 0.000 / 0.025 / 0.000) ¶	—
`data_scaling` (superseded§)	0.100 / 0.098 / 0.300 / 0.641 §	—	—	—
`data_scaling_corrected`	0.893–0.997, **flat** across 100 →3000 ¶	—	—	—
`diversity` (superseded‖)	0.500 minimal / 1.000 high	—	1.000 high (covered families)	—

Run	in-dist	new IDs	new wording	composes
`diversity_corrected`	0.950 low / 0.743 high ‖	—	0.000 low / **0.550** high ‖	—
`stage4_exposure`	1.000	—	—	0.667 / 0.000
`compdiv_minimal`	1.000	—	—	0.592 / 0.000
`compdiv_high`	1.000	—	—	0.550 / 0.000
size 0.88M	0.9167 (n=60; see Appendix C.5)	—	—	0.000
size 6.5M	0.897	—	—	0.000
size 10.2M	0.773	—	—	0.000
size 29.3M	0.897	—	—	0.000
`continual_seq`	A 1.000→ 0.000; B 0.889	—	—	—
`continual_joint`	A 1.000; B 0.889	—	—	—

`stage1`'s composes value (0.000) is from the stage-4 re-evaluation of that pilot checkpoint. † the new-identifier arm changes identifiers and wording-family coverage together (P0-03), so 0.350 is a mixed-factor shift — superseded by the identifiers-only cell of `surface_corrected`, which is ~0. ‡ the reworded arm has 480 records over 8 operations, not 600 over 10 (P0-04) — superseded by the corrected factorial's wording-only cell, 0.000 over 480 in every seed. § the data-scaling arms are prefixes of an operation-ordered pool covering 1/1/3/8 of the ten operations (P0-01), so this row is a confounded historical run of operation coverage, not a record-count curve — superseded by `data_scaling_corrected`, which is flat; we price noth-

ing from the old row. ¶ corrected runs (Appendix C, Tables C.13/C.14): `surface_corrected` *cells are scored over 600/600/480/480 records with* `abs_of` *and* `cond_abs_max` *excluded from the held-out cells (8 ops × 60);* `data_scaling_corrected` *arms are balanced 10/10 operations under one fixed tokenizer against one shared 300-task test, so the row is a flat curve, not a trend. ‖ corrected equal-count diversity (Appendix C, Table C.15): both arms exactly 1,200 records, 10/10 operations at 120 per operation, one fixed tokenizer, matched 1,000-step protocol; the "new wording" cell is the genuinely held-out phrasing family (h01/h02, 100 tasks, zero family/prompt collisions against both arms), per seed LOW 0.000 / 0.000 / 0.000 vs HIGH 0.640 / 0.300 / 0.710 (means 0.000 vs 0.550), with in-distribution LOW 0.950 in every seed vs HIGH 0.820 / 0.570 / 0.840 (means 0.950 vs 0.743); the superseded* `diversity` *row realized 42 records against 1,200 (P0-02), so we price nothing from it. The* `stage4_exposure` *and* `compdiv_*` *composes values are reported as* exposed* / *held-out* (e.g. 0.667 exposed, 0.000 held-out, over n=120 exposed records each); the held-out composite — the transfer test — was 0.000, and for the run where we analyzed it (the composition-exposure run, Appendix B.10) the held-out candidates failed parsing before semantic evaluation. We do not extend that parsing finding to the other size checkpoints, whose recorded stage rates we did not analyze the same way. The continual rows test task *retention*, not composition, so their "composes" cell is —. Note that the `compdiv_*` rows (both in-dist 1.000, composes 0.592/0.550) are the **composition- diversity** intervention runs from Chapter 16/Appendix C (`composition_diversity_pilot`, 1,500 steps) — a different experiment from Chapter 13's quantity-vs-diversity comparison, now reported as the corrected equal-count run `diversity_corrected` (1,000 steps; LOW arm in-distribution 0.950), whose flawed first version (`diversity`, 900 steps, minimal in-distribution 0.500) is superseded. They are not the same run, so the different in-distribution numbers are not a conflict.*

Legend: — = that specific breakdown was not separately reported for that

run (or the run did not test it). We reserve an explicit `0.000` for outcomes we measured and that came out negative, and use — when the run did not report that figure.

A few cautions before reading this as a budget — the shared justifications live in the evidence table at the start of Chapter 11; what follows is what each caution means for *these* rows. First, the Stage-1 pilot's "1,400 records" is the **ten-operation familiar-prompt family** total, which contained only **21 distinct prompt–program pairs**; it is not a measured per-operation data requirement, and its 0.897 is single-sample correctness for repeated previously-seen prompt strings under fresh execution values, not prompt generalization. Second, the size sweep changed training budgets (1,500 / 1,000 / 800 / 800 steps) and tokenizer, so it is not a size-only intervention. Third, three rows are **superseded flawed constructions** (Appendix B) with corrected replacements now in the matrix: the old `data_scaling` row is a prefix of an operation-ordered pool (arms cover 1/1/3/8 of the ten operations — P0-01), replaced by the flat `data_scaling_corrected` row; the old `stage3_surface` rows mixed factors and denominators (P0-03, P0-04), replaced by the `surface_corrected` factorial; and the old `diversity` row realized **42 records against 1,200** (P0-02), replaced by the equal-count `diversity_corrected` row — we draw no budget lesson from the flawed row itself. Fourth, the exposed-composite scores varied (0.550, 0.592, 0.667); the held-out composite — the transfer test — was **0.000** at every size we tried. For the run where we analyzed stage rates (the composition-exposure run, Appendix B.10) the held-out candidates failed parsing before semantic evaluation; we do not extend that to the other size checkpoints, whose recorded stage rates we did not analyze the same way, and the 0.88M baseline has a different recorded profile (0.183 of held-out candidates parsed, none executable). So the cause of that zero is unresolved across the size sweep (Chapter 16). We do not know how much data would be needed to achieve composition; we only know it was not

achieved within the budgets we tried.

19.3. What the costs tell us

Capability is cheap; robustness is not. Learning the ten-op familiar family cost ~1,400 records and a few minutes on a 0.88M model, and it "works" in-distribution (0.897). So the *apparent* cost of a capability is low. But that number is misleading: it measures only in-distribution correctness on prompts the model has seen.

The real cost appears when we ask for generalization. Two levers were meant to price robustness, and both now have measurements. *More data of the same kind* is priced at **zero marginal return**: the corrected sweep (Chapter 11) is flat at ~0.90 from 10 to 300 examples per operation, so record count buys nothing — not capability, not robustness — in this regime. *More diverse data* is priced by the corrected equal-count rerun (Chapter 13): at the same 1,200-record budget, spreading the data across more phrasings and five identifier sets moves a genuinely held-out phrasing family from **0.000 to 0.550 mean** (three seeds) and costs some in-distribution sharpness (**0.950 → 0.743 mean**) — so "train on diverse identifiers and wording" is a measured price, not just a lead, and capacity was never the promising lever either. What the corrected surface factorial does price is the failure itself: the same 600-record budget that yields ~0.90 on the familiar surface yields 0–3 of 600 on new identifiers and 0 of 480 on held-out wording — robustness to surface change was not bought at any budget we tried. And composition was not achieved at any size we tried: it stayed 0.000 on held-out at 0.88M, 6.5M, 10.2M, and 29.3M. As the cautions above state, the parsing finding applies only to the composition-exposure run, so the cause of that zero is unresolved.

The cost matrix makes a dangerous pricing error visible. If we only look at the "in-dist" column, we would conclude capability is nearly free and scale up naively. The generalization and composition columns reveal that the cheap number hides a much more expensive requirement — ro-

bust, compositional capability. On that requirement, capacity scaling was tested on composition and remained 0.000 at every size we ran; the superseded diversity row supports no pricing at all, while the corrected diversity row prices phrasing diversity as the lever that buys held-out-family transfer (0.000 → 0.550 mean) at a small in-distribution cost (0.950 → 0.743 mean), and the corrected data-count sweep prices record count at **zero marginal return** (flat ~0.90 across a 30× range). The rows we *can* price are the ones with intact controls: the pilot's familiar-prompt cost, the corrected surface factorial's robustness failure, the corrected data-scaling sweep's flat curve, the corrected diversity comparison's diversity price, and the continual-learning schedule comparison.

19.4. The price of each column, read honestly

Let us read the matrix the way a person who has to pay for capability would read it, not the way a researcher who wants a good headline would read it.

- **The ten-operation familiar-prompt family "costs" about 1,400 records and a few minutes**. That is the cheap row. Its in-distribution score was 0.897; the pilot itself did not run a reworded surface test (the Stage-3 surface run did, and scored 0.000 there). So we have bought a capability that works on the prompts it was trained with.
- **New-identifier and reworded robustness** (the corrected surface factorial) costs the same 600-record budget and still fails — the model drops to 0.000–0.005 on new identifiers alone (0–3 of 600) and to 0.000 on held-out wording in every seed (0 of 480; both changes at once: 0.000–0.025), while TEMPLATE holds 0.800 / 0.875 and RETRIEVAL 1.000 / 0.125 on the same records. The superseded Stage-3 row's 0.350 was a mixed-factor reading (P0-03) and priced nothing. We cannot buy this robustness with more of the same data either — the corrected size sweep is flat (Chapter 11).

- **Held-out-wording robustness bought with diversity** (the corrected equal-count comparison, Chapter 13) costs the same 1,200-record budget in both arms: spending it on 605 distinct phrasings and five identifier sets rather than 20 lifts the genuinely held-out phrasing family from **0.000** (0 of 100, every seed) to **0.550 mean** (0.640 / 0.300 / 0.710), while in-distribution falls from 0.950 to 0.743 mean. The diverse model still sits below TEMPLATE (0.700) and its own arm's RETRIEVAL (1.000) on that test, so the price of *partial* transfer is a little in-distribution sharpness — and the flawed 42-record first run (P0-02) priced nothing.
- **Composition** is the row that tells the sharpest story. It was 0.000 on held-out composites at every parameter size we tried (0.88M, 6.5M, 10.2M, 29.3M), and the parameter column alone did not change that in the runs we ran. But the failure cause is unresolved — the parsing finding is scoped to the composition-exposure run (see the cautions above) — so this is a recorded negative result, not a demonstrated mechanism. The exposed composites (0.550–0.667) also fell short of mastery on the *training-covered* combinations, so the model did not even fully learn those it was shown.
- **Continual learning** is the most interesting row for a practitioner. Sequential training loses A (final A accuracy 0.000, measured 1.000 right after phase A); fitting on A and B jointly keeps A at 1.000 with B acquisition unchanged at 0.889. This says a *jointly trained* model retains both tasks, not that replay recovered a lost capability in a deployed model. The same nominal total step budget was used for both, but resource use was not benchmarked, and the true replay-after-A-first design was not run (see Chapter 18). Cost is not always toward "more expense"; the right procedure can make a capability cheaper to *retain*.

19.5. The brewing experience: discovering the hidden cost

The most uncomfortable thing we learned here was not a number; it was the realization that we had almost billed this the wrong way. Early in the project, the model looked cheap: tiny, fast to train, scoring 0.900. If we had been delivering a system rather than running an experiment, we would have handed over a "working" model and called it a good deal.

Then we reworded a single prompt. The model collapsed to 0.000. The capability we thought we had bought was not really there — it only existed inside a narrow surface form. That is the moment the "cheap capability" turned out to be the most expensive thing we had measured, because it would fail in exactly the way a deployed system fails: quietly, late, and in the hands of a real user who does not phrase things the way the training data did.

That is why we now insist on reading the generalization columns, not just the accuracy column. A model that is cheap to fit but expensive to deploy is the wrong thing to build unless we know the generalization cost going in.

19.6. The honest framing

The most honest "cost" we measured is the cost of **mistaking surface association for grounded capability**. That cost is high: it makes a model that scores 90% in-distribution *look* capable while it collapses to 0.000 on a reworded instruction and to 0.000–0.005 on a new identifier — any change to the surface. In a deployed system, that is precisely the failure that appears late and costs the most.

So the real answer to "what does each capability cost?" is: the easy-to-see cost (data, parameters, steps) is small and scales predictably; the hard-to-see cost — making the capability actually generalize and compose — is where the true expense lies, and at this scale it was **not achieved** within the budgets we tried (we do not claim it is unpurchasable in principle; we

only report that our tested budgets did not reach it).

And there is a bright spot in the matrix worth holding onto. The continual-learning row shows that cost is not always "more of everything." Under the same nominal step budget, the *jointly trained* model retained both tasks whereas the sequentially trained one lost A. We did not benchmark resource use, and the true replay-after-A-first design was not run, so the takeaway is about *schedule*, not about recovering a lost capability for free in a deployed model. Cost, like capability, is often about *how* we do things, as well as *how much* we spend.

PART VII.

What Did We Learn?

CHAPTER 20.

The Capability Map

We have run a small, disciplined set of experiments and measured a coherent boundary. Rather than a list of results, let us draw the **capability map**: one picture that says, for each behavior we tested, whether the model acquired it, whether it generalizes, what it costs, and where it breaks.

Everything below is scoped to **our** setup: a ~0.9M–29.3M decoder-only transformer, trained on a few thousand generated natural-language-to-Python tasks, evaluated by a mutation-tested execution-based judge. These are claims about this brew, not universal laws about all small models. Where we say "here" or "in this regime", it is deliberate — these are measurements in one configuration, not proofs that hold everywhere. One of the map's original levers — the data-size sweep (Chapter 11) — did not survive code audit (P0-01) and has since been re-run correctly: the balanced, operation-stratified sweep is flat, so record count is now a *measured* null rather than a confound. The equal-count diversity comparison (Chapter 13) did not survive code audit in its first form (P0-02) and has since been re-run correctly — both arms at exactly 1,200 records, balanced 10/10 operations at 120 per operation, one fixed tokenizer — so its cell is now a *measured* result (diversity moves a held-out phrasing family from 0.000 to 0.550 mean), with the flawed 42-record construction kept as labeled his-

tory; the original surface rows (P0-03, P0-04) are likewise superseded by the corrected 2×2 factorial that Chapter 15 now reports.

The central conclusion, in its conservative form (adopted from the third external review, 2026-11-02, and now strengthened by the corrected reruns):

> In this restricted task family, a sub-million-parameter decoder-only transformer frequently produced executable, correct Python for prompt strings that appeared in training, even when the resulting program was tested on new input values. That performance alone does not establish generalization to new natural-language requests. Separate evaluations found severe failures under altered wording and when asked for previously untrained program structures. The corrected data-scaling sweep — balanced operation coverage, one fixed tokenizer — is flat at ~0.90 across a 30× range, so record count bought nothing in this regime; the corrected surface factorial collapses to ~0 on new identifiers, on held-out wording, and on both together, so no tested prompt-surface change is survived. The corrected equal-count diversity comparison shows phrasing diversity moving a genuinely held-out family from 0.000 to 0.550 mean, at a small in-distribution cost (0.950 to 0.743 mean). The durable methodological lesson is that a high score must be interpreted through the precise model-visible novelty, the evaluator, the baseline, and the controls used to obtain it.

20.1. Why a map, and not a single score

There is a strong temptation, at the end of an investigation, to reach for one number and say "that's the verdict." It would be satisfying and simple. But every experiment in this book has argued against exactly that. The model is good at some things and terrible at others, and those are both true at once. A single number would have to collapse them, and collapsing them would hide the most important thing: the *shape* of the boundary.

So we draw a map instead. A map does not pretend to be one verdict; it shows *dimensions*. It answers, for each question we asked, what we found — and, crucially, what we did *not* find. That honesty about the unknown is what makes the map worth more than a headline.

20.2. The four-question generalization map

Recall the four questions from Chapter 2. Here is what we measured for each, on the ~0.9M model. (This is a checklist of *questions*, not a ranking — answering Question 2 does not require answering Question 1, and so on.)

Question 1 — Memory. *Can it be explained by remembering?* **Measured**: task-ID probe 59/60; held-out pair → general program. **Status**: `[MEASURED]` — not a literal answer-parrot on familiar prompts; new-prompt transfer untested, and program memorization is not excluded (see below).

Question 2 — Distribution. *Does it work on new instances of the same task?* **Measured**: in-distribution 0.900. **Status**: `[MEASURED]` — yes, here (new *inputs*, familiar prompt).

Question 3 — Surface. *Does it survive superficial change?* **Measured** (corrected 2×2 factorial, three seeds): familiar 0.898–0.940 (of 600); new identifiers alone 0.000–0.005 (0–3 of 600); held-out wording alone 0.000 (0 of 480, every seed); both together 0.000–0.025 (0–12 of 480). Diverse pool, corrected equal-count run — held-out family 0.000 (LOW) vs **0.550**

mean (HIGH) at 1,200 records per arm; the flawed first run's 1.000 / 1.000 (42 realized records vs 1,200) is superseded coverage. **Status:** `[MEASURED]` for the narrow model — it collapses on *any* prompt-surface change, single-factor or combined; `[MEASURED]` for the corrected diverse arm — it transfers to a never-seen phrasing family (0.550 mean; per seed 0.640 / 0.300 / 0.710) at equal count, below both baselines on that test; `[SUPERSEDED]` for the 42-record construction (P0-02).

Question 4 — Structure. *Can it compose known pieces in unseen ways?* **Measured:** 0.000 (baselines also 0.000). **Status:** `[MEASURED]` — no, in this regime. **Mechanism (matched controls, P1-09, Table C.16):** the 0.000 is a no-viable-code *generation* failure — 0 complete programs and 0 wrong-semantics on held-out composites in both seeds — and it survives a seen-surface framing control (120/120 no-viable-code per seed) and a length-matched new-composite control (0 complete programs under both surfaces), while rewording *mastered* programs under unseen families collapses generation the same way (298/300 and 300/300 without a complete program). Prompt-OOD generation collapse, not incorrect composition.

20.2.1. The evidence, keyed by checkpoint

The table above groups results by *question*. But each number belongs to a specific **checkpoint** (a saved model) and a specific **evaluation split**, and it is important not to let one row mix scores from different models. Here is the same evidence laid out run by run, so every cell traces to the checkpoint the registry names. Notation used throughout: **—** = **not run for that checkpoint**; `NT` = **not tested** for this run (the question would be applicable but was not evaluated); `NA` = **not applicable** (the question cannot apply, by design); `0.000` = a measured zero. A single —/`NT` distinction: we only use `NT` when the evaluation *could* have been run but was not, and `NA` only when it makes no sense for that run.

Panel 1 — code-generation evaluations, by checkpoint

- **`stage1.pt` (Stage 1 pilot)** — familiar prompt 0.897; held-out compos-

ite 0.000.

- **`stage3_surface.pt` (Stage 3) — superseded flawed historical run (Po-03, Po-04)** — familiar prompt 0.900; new identifiers 0.350 (mixed factors); excluded wording 0.000 (480 records).
- **`surface_corrected_seed{0,1,2}.pt` (corrected 2×2 factorial; fixes Po-03, Po-04)** — familiar 0.898 / 0.900 / 0.940 (of 600); identifiers-only 0.000 / 0.003 / 0.005 (of 600); wording-only 0.000 (of 480, all seeds); combined 0.000 / 0.025 / 0.000 (of 480).
- **`data_scaling_corrected_seed{0,1,2}_size*.pt` (corrected size sweep; fixes Po-01)** — in-distribution 0.893–0.997, **flat** across 100⟶3000 (10⟶300 per op, 10/10 operations) on one shared 300-task test; composition not evaluated.
- **`diversity_corrected_seed{0,1,2}.pt` (low/high arms; corrected equal-count diversity; fixes Po-02)** — in-distribution 0.950 (low) vs 0.743 (high) mean; held-out phrasing family 0.000 (low) vs 0.550 (high) mean, per seed 0.000 / 0.000 / 0.000 vs 0.640 / 0.300 / 0.710; both arms 1,200 records, 10/10 ops at 120/op, one fixed tokenizer.
- **high-diversity pool (42 realized records vs 1,200 — Po-02; superseded)** — familiar prompt 1.000; covered alternate surface 1.000; excluded wording NT.
- **`stage4_6p5m.pt`** — familiar prompt 0.897; held-out composite 0.000.
- **`stage4_10m.pt`** — familiar prompt 0.773; held-out composite 0.000.
- **`stage4_composition.pt`** — familiar prompt 0.897; held-out composite 0.000.

Key: the superseded surface-row scores (new identifiers 0.350, excluded wording 0.000) come from the **Stage-3 checkpoint**, not the Stage-1 pilot, and both carry construction defects: the new-identifier arm changes identifiers and wording-family coverage together (Po-03), and the excluded-wording arm has 480 records over 8 operations, not 600 over 10 (Po-04). The corrected factorial rows come from their own checkpoints (one fixed 600-record train set, one fixed train-only tokenizer) and carry

their denominators in the manifest: 600 / 600 / 480 / 480, with `abs_of` and `cond_abs_max` excluded from the held-out cells. The composition score for `stage1.pt` is a separate re-evaluation of the pilot on the composition split (which is why the registry lists a "Stage-4 composition baseline" row that points at `stage1.pt`). The high-diversity row's 1.000 is **coverage** of surfaces in its training family — a pool of just 42 realized records, not an equal-count arm (Po-02) — not transfer to an excluded wording family; it is superseded by the `diversity_corrected` rows, whose held-out-family test (`h01`/`h02`, zero family/prompt collisions against both arms) is a genuine transfer measurement at equal count.

Panel 2 — composition-intervention and continual-learning runs

These conditions are not "one bigger model"; they test whether *training content* or *schedule* changes the boundary, so they belong in their own panel.

- **composition-exposure (`stage4_exposure`)** — in-dist 1.000; exposed composites 0.667; held-out composite 0.000.
- **composition-diversity (minimal)** — in-dist 1.000; exposed composites 0.592; held-out composite 0.000.
- **composition-diversity (high)** — in-dist 1.000; exposed composites 0.550; held-out composite 0.000.
- **composition-match controls (`composition_match_controls`, seeds 0/1; P1-09)** — held-out composites: 0 complete programs, 0 wrong-semantics, pass 0.000 under native *and* seen-surface framing; length-matched new composites 0 complete under both surfaces; reworded primitives 298/300 (seed 0) and 300/300 (seed 1) without a complete program — a mechanism probe, not an intervention: prompt-OOD generation collapse (Table C.16).

Panel 3 — sequential vs. joint training

- **Sequential (A then B)** — final A 0.000, final B 0.889, true replay-after-A NT.

- **Joint (A+B from start)** — final A 1.000, final B 0.889, true replay-after-A —.

Note the "sequential" A figure: the **final** A accuracy (0.000) is measured after phase B. We also measured A **right after phase A** (before B) on the same run — it was **1.000** (Appendix C.9), so the sequential drop is a same-run before/after forgetting result, not a case of A never being acquired. A true replay-after-A-first continuation (which *would* start from an A-trained checkpoint and continue with B plus A replay) was **not** run.

Read the map column by column and it shows a clear boundary rather than an ordered ladder: the four questions are **separate evaluations**, not steps of a single ascending scale. So do not read "Level 1 → Level 4" as a measured decline in "understanding." The honest reading is that these are four distinct, non-nested probes, and the model passes the first two (familiar-prompt generation, new-instance distribution) and fails the last two (surface change, composition) under this setup.

20.3. What the model can do

It can learn individual operations well. On in-distribution primitives — `add`, `sub`, `mul`, `max`, `abs`, `list_sum` — the ~0.9M model solves ~90% of held-out problems under the evaluation's default temperature-0.8 sampled decoding. It beats a hand-written template rule system (0.900 vs 0.800). This is real, measurable capability on a narrow task — for prompt strings that appeared in training (the pilot's test reuses them), on fresh execution values.

It produces general programs for fresh inputs of a prompt it saw in training. On the task-ID probe it passed 59/60, and on a held-out pair it produced the *general* program rather than a memorized literal. So for a single operation, the model is not a literal answer-parrot on familiar prompts. That is distributional generalization across *instances* of a seen prompt — it is **not** transfer to a genuinely new request, which the pilot

did not test (its test reuses training prompt strings).

20.4. What the model cannot do

It cannot survive changes to the surface form. In the corrected 2×2 factorial, change only the variable names from `a,b` to `left,right` (identical wording, identical computation) and performance falls to **0.000–0.005** — 0 to 3 of 600 — while RETRIEVAL stays at 600/600 on the same records. Rephrase the instruction with a wording family the model never saw (identical computation) and performance is **0.000 in every seed** — 0 of 480, below *both* baselines — over records covering 8 of the 10 operations (`abs_of` and `cond_abs_max` have no held-out family). Change both at once and it is 0.000–0.025. This is Question-3 failure in its crispest form: the model's capability is **anchored to the phrasing it saw** and does not survive *any* prompt-surface change we applied, single or combined. (The earlier 0.350 identifier reading was a mixed-factor shift, P0-03, and is superseded; and this is about *robustness to the shifts we tested* — it does not by itself prove there is no internal semantic representation.)

It cannot compose what it knows. Train on `add`, `sub`, `abs`, `max`, `list_sum` as separate primitives; test on `abs_add` (sum of two absolute values) and `sum_of_abs` — operations that combine two things it knows. The model scores **0.000**. It did not learn "I know abs and I know add, therefore I can do abs+abs." This is a Question-4 failure under these schedules. The baseline systems (which we designed to be easy) *also* scored 0.000 — a useful cross-check that the failure is not unique to the learned model, though it is a measured negative, not a proof that no method or shortcut could ever solve it.

The matched-control experiment (P1-09, Table C.16) shows what the 0.000 *is*: among the 120 held-out generations per seed there are **0 complete programs and 0 wrong-semantics** — the model never emits a complete program, correct or wrong, so semantics are never reached. The zero survives a verbatim seen-surface framing (120/120 no-viable-code per seed)

and a length-matched new-composite control (0 complete programs under both surfaces, both seeds), and rewording *mastered* primitives under unseen families collapses generation the same way (298/300 in seed 0 and 300/300 in seed 1 without a complete program, against 300/300 complete and passing under the native wording). So the measured boundary is a **prompt-OOD generation failure** — no viable code for unseen prompts, unseen compositions among them — not a model that composes incorrectly.

20.5. The two axes of the boundary

Put together, the results define a sharp boundary along two independent axes:

Axis 1 — Surface form. The model's knowledge is tied to the exact wording and identifier names it saw. It does not generalize "sum of two numbers" as an abstract concept; it generalizes "this sentence shape → this code." Change the surface, and the capability evaporates.

Axis 2 — Composition. Even within a surface form it knows, the model did not combine two learned pieces into a novel structure in our tests. The matched controls sharpen the reading: it never generated a complete program for the novel structure at all (0 complete, 0 wrong-semantics), so what we observed is a failure to generate viable code for an unseen prompt — not a compositional engine producing wrong answers.

Lever	Tested	Effect on composition

20.6. The scaling map (what changes it)

Lever	Tested	Effect on composition
Model size	0.88M →29.3M (~33×)	**none** — still 0.000 at all four sizes
Data size	100 →3000 examples (**corrected**: balanced 10/10 operations at every size, one fixed tokenizer — fixes Po-01)	**none** — in-distribution is flat (0.893–0.997) across the 30× range; composition **not tested** in this run (we did not evaluate the scaled models on the composite split)
Training protocol	sequential vs joint	**big** — fixes continual retention (0.000→ 1.000); a *different* lever, not a composition lever

The second half of the map is about levers, and it is where the surprising findings live. We tried three ways to move the boundary — more capacity, more data, and a different training procedure. More capacity did nothing to composition (0.000 at all four sizes); more data was first the **confounded** sweep of Chapter 11 (Po-01) and then the corrected balanced sweep, which measured the data lever properly and found it **flat** — 0.893–0.997 from 100 to 3,000 records — so record count moves neither the in-distribution score nor anything else we can see (composition was still not evaluated in the scaling run, so "more data does not fix composition" remains untested); and a different training procedure was the decisive lever for a *different* problem (continual learning), not for composition. This asymmetry is worth circling, because it tells us where effort does and does not pay — and the data lever, now properly measured, is

one where it does not.

20.7. The capacity grid, in full

The sharpest negative result in the whole book is the model-size sweep, and it deserves its own table because it is the claim a reader would most want to test. We ran the composition experiment across a ~33× range of capacity. We did **not** hold every hyperparameter constant — the runs used different step counts (see Appendix C; the model-size-budget row of the evidence table, Chapter 11), so this is a sweep across capacity with some training-budget variation alongside it, not a strictly-controlled size-only comparison.

Model	parameters	in-distribution	composition
Stage-4 baseline	884,224 (0.88M)	0.9167 (n=60; see Appendix C.5)	**0.000**
Scaling	6,500,352 (6.5M)	0.897	**0.000**
10M point	10,195,776 (10.2M)	0.773	**0.000**
30M point	29,290,240 (29.3M)	0.897	**0.000**

Four sizes. Composition is **0.000 at all four** under the schedules we ran. That is the same number repeated across a 33× change in the one resource we might otherwise blame. We would be careful not to over-read it: because the step counts differed, this is evidence that capacity alone, under these runs, did not produce composition — it is not a proof that capacity *cannot* (there may be a threshold, or different training budgets, we did not reach).

Two honest notes on the grid. First, in-distribution scores sit in a healthy plateau (0.773–0.9167) across all four sizes — capacity neither helped nor hurt the narrow task. (We suspect the earlier 10.2M run that

read 0.383 was incomplete or anomalous — the original checkpoint is unavailable for forensic confirmation, so the cause was not confirmed.) Second, in-distribution performance is **not** a monotonic ladder that predicts the deep boundary: the model that reached 0.9167 in-distribution scored 0.000 on composition, exactly like the ones that reached 0.897 and 0.773. Capacity that helps the shallow score does nothing for the deep one.

20.8. What's measured vs. what's unknown

Measured (this setup): - The model learns single operations to ~90% in-distribution and generalizes them across instances (Q1/Q2) — for prompt strings seen in training, on fresh execution values; that is not generalization to new requests. - The *narrowly-trained* model is surface-tied under **every** tested change (corrected 2×2, three seeds): new wording → 0.000 (0 of 480, all seeds), new identifiers → 0.000–0.005 (0–3 of 600), both → 0.000–0.025, against 0.898–0.940 familiar (Q3). The *diversity*-pool model in the corrected equal-count run reaches **0.550 mean** on a genuinely held-out wording family (0.000 for the narrow arm; per seed 0.640 / 0.300 / 0.710) at 1,200 records per arm — a measured equal-count diversity effect, still below both baselines on that test; the earlier 1.000/1.000 came from the flawed 42-record construction (P0-02) and is superseded coverage. - It cannot compose: unseen combinations → 0.000 across 0.88M→29.3M capacity (the model-size sweep tested composition at each size). **Caveat**: the corrected *data-size* sweep (Chapter 11) is flat on in-distribution accuracy (0.893–0.997 across 100→3000) but tested composition not at all, so we do **not** claim that more data likewise fails to help composition — that specific "more data doesn't fix composition" claim was **not** tested and is not made here (Q4); what *is* measured is that record count buys no in-distribution gain either. - Continual learning is a procedure problem: sequential forgets (A → 0.000), joint retains (A → 1.000) with no acquisition cost. - The pilot task was retrieval-solvable (retrieval = 1.000), so that split is "too easy"; the composition split is not (all baselines 0.000).

Supported / suggestive / open: - The composition failure is now **tested twice, not simply suggestive**: (a) exposure to a few composites during training does **not** unlock composition on unseen ones (the model memorizes the seen combinations at 0.667 but stays at 0.000 on held-out ones); and (b) *identifier-diversified* composite exposure (two identifier sets — each composite has a single renderer family, so this varied identifiers, not wording-family variety) also leaves the held-out composite at **0.000**. So it is neither a "just show it combinations" fix nor an identifier-variety fix — and true wording-family diversity for composites was never implemented (P1-05). Two caveats: the held-out composite candidates all **failed parsing** before semantic evaluation, so the *cause* of that zero began as a recorded negative rather than a demonstrated mechanism — **now measured** by the matched controls (P1-09, Table C.16): the zero is a no-viable-code generation failure (0 complete programs, 0 wrong-semantics on held-out composites, both seeds) that survives seen-surface and length-matched controls, and rewording mastered programs collapses generation too, so the mechanism is prompt-OOD generation collapse, not incorrect composition; and even the corrected data-scaling sweep did not evaluate composition at all, so the data lever speaks only to in-distribution accuracy (where it is flat). - The one lever we have **not** isolated is diversity of the *inner structure* — many *different* primitive pairings rather than different phrasings of the same few. That is the remaining open experiment. - Whether the composition wall is truly structural or simply sits above our ~30M ceiling is **untested** — we stop where the CPU lab becomes impractical.

Unknown (did not test): - Whether behavior on 3+ capabilities or post-continual composition holds. - Whether a fundamentally different inductive bias (not scale) helps.

20.9. The methodology findings

Independent of the model, the **methodology** produced its own results — and several are as valuable as any model number:

- **Test the tester**. Our own evaluator reported the model at 0.000 on its first run. It was the *judge* that was broken (a null-byte artifact), not the model. Fixing it revealed the true 0.897. Never trust a number from a system we have not audited.
- **Test the teacher**. The leakage audit caught a 100%-predictable operation from the pilot wording — which, on reflection, is mostly task signal (the request must name the operation), not a leak. This is why surface splits need held-out template families.
- **Test the construction**. The first data-scaling sweep's rising curve (0.100 → 0.641) was an artifact of a `pool[:size]` prefix over an operation-ordered pool (P0-01); the corrected balanced rerun came back flat. An innocent slice can manufacture a result that even replicates across seeds — only reading the arm-building code against the claim catches it.
- **Test the data**. The diversity-vs-quantity experiment's first version reported 0.000 with minimal diversity and 1.000 with high diversity — but code audit showed the arms were **not** the same count (42 realized records vs 1,200 — P0-02), so that 1.000 was coverage of a 42-record pool. The corrected rerun held both arms at exactly 1,200 records with balanced operation coverage and one fixed tokenizer, and the finding survived in honest form: diversity — not quantity — is the *measured* driver of transfer to a never-seen wording family (**0.000 → 0.550 mean**), at a small in-distribution cost (**0.950 → 0.743 mean**). Reading the arm-building code against the claim is what caught the flaw; the corrected rerun is what turned the suspicion into a measurement.
- **Baselines are first-class**. A trivial TF-IDF retriever dominated the pilot task (1.000), proving it was "too easy," and forced us to build harder

splits. And the moments the model *fell below* a baseline were the most informative results.

- **The protocol, not capacity, determines continual learning.** Sequential training destroyed capability A (0.000) when learning B; joint training preserved A perfectly (1.000) at no cost to B. This is a *procedure* finding.

20.10. The boundary, in one line

A small model learns narrow, individual mappings well — frequently producing executable, correct Python for prompt strings that appeared in training, even on new input values — but that does not establish generalization to new natural-language requests, and its knowledge is surface-tied: the corrected factorial shows it collapse to ~0 on new identifiers, on held-out wording, and on both together. Under the recorded training and decoding settings, the tested checkpoints produced no successful held-out composite completions; the exposure run's held-out candidates all failed parsing, and the matched-control experiment (P1-09, Table C.16) now identifies the cause as a no-viable-code generation failure on out-of-distribution prompts — 0 complete programs and 0 wrong-semantics on held-out composites, surviving surface- and length-matched controls — so the boundary is failure to generate, not incorrect composition. The corrected data-count sweep is flat (0.893–0.997 across a 30× range), so record count establishes no benefit; the corrected equal-count diversity comparison shows phrasing diversity moving a held-out family from 0.000 to 0.550 mean (in-distribution 0.950 → 0.743), so diversity — not quantity — buys partial transfer to excluded wording families.

(Size and data scaling are two separate levers, and neither was shown to turn surface coverage into compositional capability: the size sweep changed training budgets and tokenizer, so it is not a size-only intervention, and the corrected data-count sweep — balanced operation coverage, one fixed tokenizer — moved the in-distribution score not at all while never evaluating composition (evidence table, Chapter 11). We also tested a scheduling change — sequential vs. joint training — but that measured retention of *separately learned* task groups, not composition, so it likewise does not speak to the composition boundary. The diversity study's corrected equal-count control now supports exactly that claim, scoped to phrasing diversity on this task: 0.000 → 0.550 on a held-out family, 0.950 → 0.743 in-distribution.)

20.11. Why the map is the deliverable

This map is the book's real output. It is not a single headline accuracy that would mislead; it is a precise, honest picture of where capability exists, where it collapses, and what (and what doesn't) shift the boundary. It is the answer to the central question — and it is falsifiable, built from real measured runs, and honest about what remains unknown.

20.11.1. A syntax/capability inventory (kept distinct)

The four questions above are about *generalization*. Separately, the task family can be viewed as a ladder of Python syntax/capability (from arithmetic to composition), and it is worth recording which rungs we actually *isolated* versus which we did not. This is a *syntax* inventory, distinct from the four generalization questions, and we keep it separate so it is not read as another trust ladder:

Rung	Capability	Was it isolated?
1	arithmetic	yes — measured, ~0.90 in-distribution
2–3	variables, conditionals	yes — variables measured (~0.90); conditionals appear inside the reference for `max_of`/`min_of`/`abs` but were **not isolated** as a standalone task
4–5	lists, indexing	partially — `list_sum`/`list_len` measured; indexing appears in `first_element`/`double_first` but was **not isolated**
6	loops	**not isolated** (no standalone loop operation in the primitives; loops appear only inside `list_sum`'s reference)
7	**composition**	no — **0.000** — the wall
8	simple functions	not isolated (the task is always "write one `solve` function")

The honest reading is narrow: we measured individual operations well, and composition fully; the intermediate rungs (conditionals, indexing, loops as independent skills) were **not** isolated, so we do not claim about them either way. What we can say is that the model climbs the rungs we isolated reliably and stops at composition.

The deeper value of the map is what it does to our confidence. Before drawing it, we knew "the model is limited." After drawing it, we know more precisely which limits we *moved* with a lever and which we *did not*: composition was not moved by scale, and surface-tiedness was not moved by scale or by more-of-the-same data — the corrected size sweep is flat and the corrected surface factorial still collapses — while continual forgetting was both seen and fixed by how we trained. We are careful not to call the unmoved ones "structural" as if we had proven their cause — we observed that the tested levers did not reach them.

That distinction — which limits we could move and which we could not — is the kind of knowledge that changes what a practitioner would try next. It is not the same as saying "small models are weak"; it is saying "here is where the weakness lived under our tests, and here is what did and did not reach it." A map with a blank region is more useful than a map painted over with speculation, because the blank marks where the next investigation should go.

This is also **not** evidence that the model is "stupid" or that the approach "doesn't work." The model is good at exactly what it was trained to do — map a narrow phrasing to a narrow computation — and bad at the two things that separate "reflex" from "capability": robustness to surface change, and composition. The value of measuring it precisely is that it tells us *where* to look next.

CHAPTER 21.

The Model Wasn't the Point: A Conclusion

We began with a question that sounded technical: *can a small language model learn to solve programming tasks?* The answer we got was more interesting and less about the model than we expected.

21.1. Where the journey started

The premise was: building a small model is relatively easy; determining what it actually learned is the hard part. That premise turned out to be more accurate than we had any right to expect. The model was built in an afternoon. Understanding what it had — and had not — learned took the rest of the book.

A decoder-only transformer that maps a handful of programming sentences to Python is an afternoon's work once the pieces are in place. But *knowing what that model actually did* — whether it learned, memorized, associated, or cheated — required a world, a teacher, a judge, rivals, and a battery of controlled experiments. The model was the easy part. The certainty about what it did was the hard part, and it is the part worth writing

about.

21.2. What the experiment established

At the core, the answer to the book's central question is now stated in its most conservative, audit-proof form — the wording we adopt after the third external review (2026-11-02) and our own code–claim audit:

> In this restricted task family, a sub-million-parameter decoder-only transformer frequently produced executable, correct Python for prompt strings that appeared in training, even when the resulting program was tested on new input values. That performance alone does not establish generalization to new natural-language requests. Separate evaluations found severe failures under altered wording and when asked for previously untrained program structures. The corrected data-scaling sweep — balanced operation coverage, one fixed tokenizer — is flat at ~0.90 across a 30× range, so record count bought nothing in this regime; the corrected surface factorial collapses to ~0 on new identifiers, on held-out wording, and on both together, so no tested prompt-surface change is survived. The corrected equal-count diversity comparison shows phrasing diversity moving a genuinely held-out family from 0.000 to 0.550 mean, at a small in-distribution cost (0.950 to 0.743 mean). The durable methodological lesson is that a high score must be interpreted through the precise model-visible novelty, the evaluator, the baseline, and the controls used to obtain it.

This wording is deliberately more conservative than the capability map's earlier summary, and the corrected reruns have since strengthened it rather than loosened it: the data-scaling lever came back flat and the

surface collapse came back crisper. Within it, the experiments separate into what the model **can** do and what it **cannot**.

It can learn, and it learns well — within a narrow regime. On individual operations, the model reliably maps a natural-language spec to correct Python, reaching **~0.90 pass@1** in-distribution on a 0.88M parameter model (the pilot under its own evaluation scored 0.897; the stage-4 re-evaluation of the same pilot checkpoint measured 0.9167 (n=60; see Appendix C.5) — different evaluation sets, both reported). It produces general programs for *fresh inputs of a prompt it saw in training* — a task-ID probe passes 59/60 and a held-out pair yields the general program, not a memorized literal. That is genuine, if narrow: it is **not** transfer to a genuinely new request, because the pilot's test reuses training prompt strings.

But it is surface-tied and non-compositional. The two limits that matter:

1. **It anchors to phrasing, not meaning.** In the corrected 2×2 factorial, change only the variable names (`a,b` → `left,right`, wording untouched) and it drops to **0.000–0.005** — 0 to 3 of 600; change only the wording (same computation, different words, identifiers untouched) and it is **0.000 in every seed** — 0 of 480, below both baselines; change both and it is 0.000–0.025. It survives no prompt-surface change we applied, against ~0.90 on the familiar phrasing (the earlier 0.35 identifier reading was mixed-factor inflation, P0-03, now superseded). The external reality check confirmed it: a human-written test set scored **0/16 — 0/11** on requests built from operations the model had seen (a phrasing/surface failure) and **0/5** on genuinely held-out composite requests (a structural failure, expected separately) — because the model learned a *template*, not the *task*.
2. **It cannot compose what it knows.** Train on `abs` and `add` separately, then ask for `abs_add` — it scores **0.000**. The baselines also collapse to 0.000, so the failure is a *measured negative*: no method we tried — learned, retrieval, or template — produced a composite program. (This

is a strong negative signal, not a proof that no cleverer method could; see the shortcut audit in Chapter 16.)

What the zero *is*, is now measured (the matched-control experiment, Table C.16): among the 120 held-out generations per seed there are **0 complete programs and 0 wrong-semantics** — the model never emits a complete program, correct or wrong — and the zero survives a verbatim seen-surface framing (120/120 no-viable-code per seed) and a length-matched new-composite control (0 complete programs under both surfaces), while rewording *mastered* primitives under unseen wording collapses generation the same way (298/300 in seed 0 and 300/300 in seed 1 without a complete program, against 300/300 complete and passing under the native wording). So the boundary we report is a **prompt-OOD generation failure** — no viable code for unseen prompts, unseen compositions among them — not a model that composes incorrectly.

One limit looked moveable — by changing the data, not its quantity — and the corrected rerun confirms it. Diversity of surface phrasing is the one lever in the book that changed the surface outcome. Its first comparison did not survive code audit: the high-diversity pool realized only **42 records** against the minimal arm's 1,200 (P0-02; the mechanism is in Chapter 13's audit note), so the reported **1.000** was coverage of 42 exact mappings — not transfer, and not an equal-count result. The corrected rerun holds both arms at exactly **1,200 records**, 10/10 operations at 120 per operation, one fixed tokenizer, matched protocol — and the finding survives in honest form: on a genuinely held-out phrasing family the narrow arm scores **0.000** (0 of 100, every seed) and the diverse arm **0.550** mean (0.640 / 0.300 / 0.710), while in-distribution the narrow arm is sharper (**0.950** vs **0.743** mean). So the picture is more than "small models are fragile": *content diversity* is a **measured** lever for widening what a small model handles — partial transfer, still below both baselines on that test, bought with a little in-distribution sharpness. More *capacity*

(0.88M→29.3M) also did not lift the compositional limit. **More *data* of the same kind is now measured, and it bought nothing**: the corrected, operation-balanced size sweep is flat at ~0.90 from 10 to 300 examples per operation — a 30× range with no benefit (Chapter 11) — while the original rising curve (0.100 → 0.641) was the operation-coverage confound (Po-01), preserved only as a labeled flawed historical run in the failure ledger. Whether more data would help *composition* is still a question we did not test and do not assert: the corrected sweep scored in-distribution only.

The scaling conclusion is our sharpest negative result. Composition stays at **0.000** across model sizes from 0.88M to 29.3M, under the training schedules we ran. Within that tested range, more capacity did not buy composition. We are careful not to call this a capacity "ceiling": it is a measured boundary in this regime, not proof that capacity cannot help under other conditions (different training budgets, larger sizes, or different optimizers).

21.3. What the laboratory produced along the way

The experiments told a clean, coherent, honest story — and the laboratory caught itself. The first time we evaluated the model, it scored 0.000 — and it wasn't the model's fault. The evaluator was broken (a NUL-padding artifact in the output made every program fail to parse). Fixing the *tester* revealed the model's true 0.897. That moment — discovering our own instrument was wrong before we trusted it — is as much a part of this book as any model result.

21.4. The deeper achievement

The book's real finding is not "small models are limited." It is:

> **Building a trustworthy experiment was harder and more valuable than building the model**.

The model was the instrument. The experiment was the subject. The things that made this work — the sandbox that rejects anything not explicitly allowed, the judge that executes code and compares semantics rather than strings, the mutation suite that red-teams the judge, the leakage audit, the baselines that ask "could a simpler machine do this?", the four-question taxonomy that refuses to collapse everything into one number — those are the actual achievements here.

Each of these forms a discipline rather than a checklist. The sandbox's allowlist (not a blocklist) rejected the disallowed constructs covered by its validator, so a failure could more often be attributed to the model rather than to an accident of environment — within the constructs the gate covers. The judge's execution-based, semantic comparison meant a "correct" answer was judged correct under the stated acceptance rule (it ran and matched the expected output), rather than being merely stylistically close. The mutation suite meant we doubted the judge before we trusted it. The baseline comparisons meant a number only had meaning relative to a simpler machine. And the four-question taxonomy meant we never overstated a result by collapsing different kinds of generalization into one score.

21.5. The recurring habit

There is a way of thinking that runs through everything here, and it is worth naming directly because it is what a careful investigation actually looks like. It is the habit of distrusting the easy answer — including our own.

Every time we got a number, the next step was not to celebrate or to move on. It was to ask: **how could the model have gotten this without learning what we think it learned?** Could it have memorized? Retrieved? Exploited a template? Leaked the answer from our own data? Hit a bug in our evaluator? Each of those is a way a seemingly-impressive result can be hollow, and each one we then built a control to test. That constant, de-

liberate suspicion — aimed at our own apparatus as much as at the model — is the difference between "we ran an experiment" and "we know what the experiment means."

Beyond the numbers, there is a way of working this book was really about. A brew is not finished when the model is built; it is finished when we can say, with confidence and precision, what that model can and cannot do — and when we have left a record that someone else could follow and, ideally, contradict. It is seldom a straight line from hypothesis to clean result. It is a loop of building, testing the builder, being surprised, and revising. The surprise is not a detour from the method; it is the method. And a book about science should show that loop, not hide it.

21.6. What the reader takes away

If we take one thing from this book, it is a habit, not a fact:

> **Never trust a number from a model we don't understand, or from an experiment we haven't audited.**

Before we believe "the model learned to add," we have to be able to answer: remove the memorization, the retrieval, the templates, the leakage, the evaluator artifacts — what remains? In our case, for simple primitives, what remained was genuine learning-within-a-surface-form. It was real, and it was narrow, and it did not compose.

Build the model. Test the model. Break the evaluator. Break the model. Audit the data. Challenge the conclusion. Repeat. Only then say: "This is what the model learned."

21.7. Where this brew leads

The honest map points at specific next experiments, not vague "more data / bigger model":

1. **Does *structural* diversity of combinations unlock composition?** We tested two things and both failed: (a) feeding a few composites during training (held-out still 0.000), and (b) *identifier-diversified* composite exposure — two identifier sets (each composite has a single renderer family, so this varied identifiers, not wording-family variety; held-out still 0.000). So the remaining open question is diversity of the *inner structure* — exposing the model to many *different* primitive pairings — to see whether that teaches a general compose-operator. That is the one lever we have not isolated. The experiment to run is a systematic increase in *structural* diversity — the number, nesting, and variety of operator pairings — with disjoint held-out pairing structures and program length and vocabulary matched between training and test, so that structure is the only variable that changes. (Both data levers now have their corrected reruns: the operation-stratified size sweep of Po-01 came back flat, so record count is settled as a null; the equal-count diversity comparison of Po-02 came back decisive for held-out-family transfer — 0.000 ⟶ 0.550 mean — so phrasing diversity is settled as a measured, partial lever.)
2. **Does the 10.2M in-distribution plateau replicate across configs?** The clean retrain measured 0.773 (a stable plateau, not the earlier 0.383 reading). A proper training-duration and config sweep at 10M would confirm the plateau is robust.
3. **Does continuing to scale past 30M shift the boundary?** The grid stops where the brew lab's CPU becomes impractical. A larger-scale run (or a GPU) would probe whether the composition wall eventually moves.
4. **Human-style training**. The 0/16 human test set shows the model fails on naturally-phrased prompts. Training on diverse, human-style

prompts is the obvious path to real usability.

21.7.1. A future note on widening the world

One planned direction is **widening the capability spec** — and the wording matters, because the sandbox already allows more than the experiments ever measured. The allowlist in Chapter 4 already admits `for`/`while` loops, lists, indexing, and slicing, so "more Python" does not mean adding those; what is untested is **larger and more complex programs built from the existing constructs** — longer programs, deeper nesting, more of the allowed vocabulary. **Genuinely new constructs** are a separate step again: additional syntax, richer types, and recursion, each admitted under a controlled policy and then measured. The distinction to keep straight is *sandbox-allowed* (a static property of the validator) versus *experimentally measured* (only a narrow set of rungs was ever evaluated — see the syntax inventory in Chapter 20). We did **not** run a full sweep of "add more Python and re-measure" in this book; nor did we test **program length and complexity** (no evaluation on longer or more structurally complex programs — an untested axis, not a measured 0) or **expressivity beyond the tested operations** (Python features, built-ins, or idioms outside the fixed operation set), both listed under Appendix C's "What is NOT tested." What we did measure is that the composition failure is not explained by a simple missing-token deficit: the model wrote valid programs for the primitive operations, whose tokens it clearly knew. But that does **not** prove the model has full *nested* syntax competence — the observed failures were malformed fragments, and knowing the tokens for `def`/`return` is not the same as producing correctly nested compound expressions. So we treat "not a syntax problem" as a plausible-but-unestablished reading. The matched-control experiment (Table C.16) has since pinned the *failure mode* of the composition zero — no-viable-code generation on out-of-distribution prompts, where syntax can even be present but no complete `solve` program appears (seed 0's length-matched `abs_mul` reaches syn-

tax 0.925 yet defines 0/40 complete programs) — while *why* generation collapses on an out-of-distribution prompt remains open. The versioned, step-by-step widening framework (the capability spec's `v0_1`, `v0_2`, …) is how we would test new capability, and we state it as a proposal for the future rather than a completed result.

21.8. The honest ending

The model was the instrument. The experiment was the subject. We did not build a general programmer, and we will not pretend otherwise. What we *did* build is the means to ask, precisely and honestly, what a small model can and cannot learn — and we got an answer worth having:

> The small model in this brew — 0.88M⟶29.3M decoder-only transformers on our NL-to-Python task — frequently produced executable, correct Python for prompt strings that appeared in training, even on new input values; that does not establish generalization to new natural-language requests. In our tests its knowledge was surface-tied and non-compositional: the corrected surface factorial collapses to ~0 on new identifiers, on held-out wording, and on both together, and more capacity (0.88M⟶29.3M) did not change the compositional limit — a limit the matched controls show to be a no-viable-code generation failure on unseen prompts (0 complete programs, 0 wrong-semantics on held-out composites), not incorrect composition. The corrected data-scaling sweep is flat at ~0.90 across a 30× range, so record count bought nothing; the corrected equal-count diversity comparison shows phrasing diversity moving a held-out family from 0.000 to 0.550 mean at a small in-distribution cost (0.950 ⟶ 0.743), while the original 42-vs-1,200 run is superseded history.

And the habits we learned — test the tester, test the teacher, compare against baselines, audit shortcuts, preserve failures — are the durable part. That is the method worth keeping, and it is the reason the book's real subject was never the model. The brew was never only about the model; it was about learning to ask a question carefully enough that the answer could be trusted.

21.9. Where this sits: related work

None of the ideas here is new in isolation, and we want to say so plainly rather than imply novelty. This book's contribution is not inventing a technique; it is assembling a small, fully-controlled laboratory and being unusually honest about what the results do and do not establish. The underlying disciplines have long histories, and a reader who wants to go deeper should look there:

- **Compositional generalization**. The question of whether a model can combine known pieces in novel ways is a longstanding benchmark problem (e.g. the SCAN and COGS datasets). Our finding — that a tiny model does not compose under our tests — is a narrow case of a much-studied puzzle.
- **Execution-based code evaluation**. Running generated code against hidden tests is the standard for code-generation evaluation (the pass@k / HumanEval tradition). We borrowed that idea and applied it at a miniature scale, and our mutation-control work echoes the broader practice of testing the evaluator itself.
- **Shortcut learning**. "The model found an easier signal than the one we intended" is a well-documented phenomenon; our shortcut audit is a small, disciplined instance.
- **Catastrophic forgetting and rehearsal**. The effect we measured is a classic finding; the observation that keeping old data in the mix helps is also long-established.

- **Mutation testing.** Originating in software engineering, it is the source of our judge red-team.

We cite these traditions to place the book in context, not to claim we advanced them. We did not benchmark against these in this book (the task and scale are far smaller), so we make no claim of competing with them.

21.10. Reading further

These are the published works the book's questions relate to, cited with stable identifiers (DOI or ACL Anthology / arXiv record) so a reader can verify each. One line each on why it matters for the questions here. We have not benchmarked against any of them — the task and scale here are far smaller — so we make no claim of competing with them; the citations place the book's questions in context.

- **Compositional generalization**. Lake & Baroni, *Generalization without Systematicity: On the Compositional Skills of Sequence-to-Sequence Recurrent Networks*, ICML 2018 — arXiv:1711.00350, https://arxiv.org/abs/1711.00350. Introduced the **SCAN** benchmark, which probes exactly the "new combination of known pieces" question (the book's Question 4) and found seq2seq models largely fail it.
- Kim & Linzen, *COGS: A Compositional Generalization Challenge based on Semantic Interpretation*, EMNLP 2020, pp. 9087-9105 — https://aclanthology.org/2020.emnlp-main.731/ . COGS is a **semantic-parsing / compositional-generalization** dataset (fragments grounded in a small world language), not a question-answering benchmark. It showed seq2seq models achieving much lower accuracy on novel combinations than on in-distribution examples — the same in-distribution vs. compositional gap the book measures.
- **Execution-based code evaluation**. Chen, Tworek, Jun, Yuan, et al., *Evaluating Large Language Models Trained on Code*, arXiv:2107.03374,

2021 (HumanEval / Codex). The pass@k formulation the book adapts to problem-level pass@1, and the insight that *executing* a program against tests is a sharper evaluation than comparing text.

- **Shortcut learning and spurious correlation**. Geirhos, Jacobsen, Michaelis, Zemel, Brendel, Bethge, & Wichmann, *Shortcut Learning in Deep Neural Networks*, Nature Machine Intelligence 2(11):665-673, 2020 — DOI 10.1038/s42256-020-00257-z, https://doi.org/10.1038/s42256-020-00257-z. The conceptual framework for asking "did the model learn the task, or a shortcut to it?" — the question the book's surface test (Question 3) and lexical diagnostic address directly.
- **Continual learning and catastrophic forgetting**. McCloskey & Cohen, *Catastrophic Interference in Connectionist Networks: The Sequential Learning Problem*, in *Psychology of Learning and Motivation*, pp. 109-165, 1989 — https://doi.org/10.1016/S0079-7421(08)60536-8 . (The original forgetting result); and Kirkpatrick et al., *Overcoming Catastrophic Forgetting in Neural Networks*, PNAS 114(13):3521-3526, 2017 — DOI 10.1073/pnas.1611835114, https://doi.org/10.1073/pnas.1611835114 (elastic weight consolidation, a rehearsal-free alternative). These frame the book's sequential vs. joint training result.
- **Mutation testing of test suites**. Jia & Harman, *An Analysis and Survey of the Development of Mutation Testing*, IEEE Transactions on Software Engineering 37(5):649-678, 2011 — DOI 10.1109/TSE.2010.62, https://doi.org/10.1109/TSE.2010.62. The practice of seeding faults to measure a test suite's ability to catch them — the basis of the book's judge red-teaming in Chapter 17.

21.11. Three short exercises

If you want to check that you have the book's discipline, try these. Answers are in the back of this chapter.

1. **Coverage or generalization?** You train a model on three wording families and evaluate it on a fourth that it has never seen. It scores 0.900. Is that a coverage result or a generalization result? What if instead you evaluated it on a *rephrasing within one of the three families it saw* — is *that* same interpretation?

2. **Distinguish two programs.** For the two functions `abs(a + b)` and `abs(a) + abs(b)`, find one input where they give the same answer and one where they differ. Why does a single passing test not distinguish them, and what kind of test does?

3. **What does a zero establish?** A model scores 0.000 on a held-out composition split. Write down what this does and does *not* establish — name at least two other causes of a zero that the result does not rule out, and one thing you could run to distinguish them.

21.12. Answers to Exercises

1. The first is generalization to an excluded family; the second is coverage of a surface within the training family. Only the first speaks to a never-seen family. Note that a genuinely new prompt within a familiar family is still a real form of in-distribution generalization (a new surface, same computation) — "excluded-family transfer" is a stronger and different shift, not the only form of generalization the book measures.

2. For `a = 2, b = 3` both give `5`; for `a = -3, b = 2` they give `1` and `5`. One test can be satisfied by both programs, so a distinguishing test must use a signed input where the two differ.

3. The zero shows that, under this decoding/evaluation procedure, no program passed every hidden test. It does not identify the cause (instruction interpretation, syntax generation, length handling, coverage, opti-

mization, or a particular held-out operation), is not proof of a general capacity limit, and is not proof that the model "cannot compose" — a per-stage failure report or an all-composites control would narrow which cause holds.

In this book we later ran exactly the kind of control the exercise asks for — the matched-control experiment (Table C.16). It showed the composition zero is a no-viable-code generation failure (0 complete programs, 0 wrong-semantics on held-out composites, both seeds) that survives seen-surface and length-matched controls, so the cause we now report is prompt-OOD generation collapse, not incorrect composition.

CHAPTER A.

An Annotated Tour of the Generator

Chapter 5 describes the teacher conceptually. This appendix shows the actual source, so we can see — and reproduce — exactly how the data was made. All of this lives in `src/data_generator/` and `src/program_generator/`, `src/nl_renderer/`, `src/test_generator/` in the companion repository.

A note on what follows: this is a **condensed, annotated excerpt** of the real generator, not a complete runnable file. Where a section repeats in the same style for every operation, we mark it with an ellipsis (`...`). A few helpers that would be defined elsewhere in the source — the `OPERATIONS` table, `_rand`, and `_expected` — are used here as-is; the point is to show the *shape* of each part and how the semantic record flows through it, not to provide every line that would appear in a standalone module. The full, runnable source is in the repository.

A.1. The one line that ties it together

The whole generator is this single function. Given an operation and a seed, it builds the semantic intent and then generates everything else from it:

```
def make_task(operation, task_id, seed, id_set="letters",
split="train",
              family=None):
    rng = random.Random(seed)
    sem = make_semantics(operation, rng, id_set)     # the
    ground truth
    ref = generate_reference(sem, rng)               # the
    correct Python
    prompt, fam_name = render_nl(sem, family=family,
    rng=rng)  # the English
    tests = generate_hidden_tests(sem, rng=rng)      # the
    hidden tests
    return {
        "task_id": task_id,
        "semantics": sem,
        "reference_code": ref,
        "nl": {"prompt": prompt, "template_family":
        fam_name},
        "hidden_tests": tests,
        "metadata": {"seed": seed, "identifier_set": id_set,
                     "paraphrase_family": fam_name},
        "spec_version": "python_capability_v0_1",
        "dataset_version": "v0_1",
        "split": split,
    }
```

That's the whole architecture in ten lines. Everything below is one of the four building blocks it calls.

A.2. The semantics

```
IDENTIFIER_SETS = {
    "letters": ["a", "b", "c", "x", "y"],
    "words":   ["left", "right", "first", "second", "value",
    "numbers", "items"],
}

def make_semantics(operation, rng, id_set="letters"):
    n = OPERATIONS[operation]                       # arity
    names = list(IDENTIFIER_SETS[id_set][:n])       # pick
    names from the set
    arg_type = ("list" if operation in
                ("list_sum", "list_len", "first_element")
                else "int")
    # Every operation here returns an int scalar. Lists
    appear only as INPUTS
    # (a list of ints); list_sum/list_len/first_element all
    return an int, not
    # the list itself. So output_type is always "int"; only
    input_types vary.
    output_type = "int"
    args = [{"name": names[i], "type": arg_type, "role":
    "operand"} for i in range(n)]
    return {"operation": operation, "args": args,
            "input_types": [arg_type] * n, "output_type":
            output_type}
```

This is the pilot's condensed type-dispatch excerpt, so it marks only the three pilot list-operations as list-input. It is ***not*** *the full dictionary* — the composite list operations (`sum_of_abs`, `double_first`, `len_minus_one`) also take a list but are built by the composition path, not this condensed excerpt; the shipped `make_semantics` itself serves both `OPERATIONS` and `COMPOSITE_OPERATIONS`. For the complete per-operation input types see the operation dictionary in Appendix C, which lists every operation's arity, input type, and `class`.

A.3. The reference program

The reference generator reads the semantics and emits the correct Python. A few cases:

```
def generate_reference(sem, rng=None):
    op = sem["operation"]; names = [a["name"] for a in
    sem["args"]]
    if op == "add":
        return (f"def solve({', '.join(names)}):\n"
                f"    return {names[0]} + {names[1]}")
    if op == "list_sum":
        return (f"def solve({names[0]}):\n    total = 0\n"
                f"    for x in {names[0]}:\n        total =
                total + x\n"
                f"    return total")
    # ... and so on for every operation, in the same style.
```

A.4. The natural-language renderer

The renderer phrases the same semantics several ways. Each **template family** is a function:

```
def _a(op, names, rng):   # family "a"
    x, y = names[0], names[1]
    return (f"Write a function that takes two numbers, {x}
    and {y}, "
            f"and returns their {_op_noun(op)}.")

def _b(op, names, rng):   # family "b"
    x, y = names[0], names[1]
    return (f"Implement solve so that given {x} and {y} "
            f"it returns their {_op_noun(op)}.")

def _c(op, names, rng):   # family "c"
    x, y = names
```

```
    return (f"Define a function solve({x}, {y}) "
            f"that returns {x} {_op_sym(op)} {y}.")

# Each operation has its own set of families;
_op_noun/_op_sym map an operation
# to the right word ("sum", "product", ...) and symbol ("+",
"*", ...), so the
# same families work for every operation, not just addition.
FAMILIES = {
    # three families each:
    "add": [_a, _b, _c], "sub": [_a, _b, _c], "mul": [_a,
    _b, _c],
    # two families each:
    "max_of": [_a, _b], "min_of": [_a, _b],
    "list_sum": [_list_a, _list_b], "list_len": [_list_a,
    _list_b],
    "first_element": [_list_a, _list_b],
    # singletons — exactly one family each:
    "abs_of": [_unary_a], "cond_abs_max": [_a],
    # composites: one family each, and held out of training
    entirely
    # (composition split only):
    "abs_add": [_comp_add_abs], "sub_abs": [_comp_sub_abs],
    "sum_of_abs": [_comp_sum_abs], "max_add":
    [_comp_max_add],
    "double_first": [_comp_double_first], "len_minus_one":
    [_comp_len_minus_one],
}
```

The semantics is fixed; only the wording changes. That is the entire point.

Cardinality is visible in that dict, and it is deliberately uneven: three families for `add`/`sub`/`mul`, two for the other primitives, and exactly one for the singletons `abs_of` and `cond_abs_max` (and for every composite). A singleton has no held-out family to offer — which is why Chapter 15's

held-out-wording cells cover 8 operations and 480 records rather than 10 and 600 (Chapter 5 introduces this cardinality with the teacher; Appendix D defines "held-out family").

A.5. The hidden tests

Tests are generated from the semantics, with deliberate edge-case coverage. The expected value is computed by the operation itself — not copied from the reference:

```
def generate_hidden_tests(sem, rng=None, count=8):
    op = sem["operation"]; args = sem["args"]; tests = []
    def add(*vals, note="basic"):
        tests.append({"args": list(vals),
                      "expected": _expected(op, vals),
                      "note": note})
    add(_rand(rng), _rand(rng), note="basic")     # ordinary
    add(0, _rand(rng), note="zero")               # zero
    add(-_rand(rng), -_rand(rng), note="negative")# negative
    add(_rand(rng, 900, 1000), _rand(rng), note="large")  #
    large
    # ... edge cases for the specific operation
    return tests[:count]
```

A.6. The operation-classification audit

Finally, the generator is checked. The audit trains a trivial classifier to see whether the wording reveals the operation. Note: the vectorizer must be fitted **inside** the cross-validation folds, not once on the whole dataset, or the model sees the test wording during fitting. The corrected form uses a `Pipeline`:

```
from sklearn.pipeline import Pipeline
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.linear_model import LogisticRegression
from sklearn.model_selection import cross_val_score

clf = Pipeline([
    ("vec", TfidfVectorizer()),
    ("clf", LogisticRegression(max_iter=1000)),
])
X = [t["nl"]["prompt"] for t in tasks]
y = [t["semantics"]["operation"] for t in tasks]   # the
operation label each prompt maps to
scores = cross_val_score(clf, X, y, cv=5)
print(f"classifier predicts operation: {scores.mean():.3f}")
# = wording carries operation signal
```

When we first ran the equivalent diagnostic on the original pilot renderer, it printed **1.000** — the wording perfectly predicted the operation. It is important to read this correctly: much of that is **task signal, not leakage**. The prompt must name the operation ("sum", "absolute value"), so a classifier can trivially recover it from the wording; that is the task being solvable as stated, not a defect. So the high score measures **how separable the operations are by wording** — i.e. whether the prompt reads as a clean task spec — and we should not call it a "leakage" measure or equate it with "overlap." The audit's real purpose is to catch the *opposite* problem — where some *other* accidental cue (a duplicated example, a leaked hidden-test value, an identifier that reveals the answer) drives the score. We therefore treat the vocabulary separability as a first check and separately inspect for duplicated examples and accidental cues, rather than reading one number as proof of leakage.

A.7. From prompt to tokens: the actual tokenizer

The generator stops at text. The training pipeline turns that text into ids with the tokenizer in `src/tokenizer/tokenizer.py` — and it is worth showing here, because it is **not** BPE (Chapter 8 and Appendix D carry the correction): the vocabulary is the 256 character tokens plus the most frequent whole words of the corpus, and encoding is a greedy longest match.

```
def train_tokenizer(texts, min_vocab=128, max_vocab=512,
save_path=None):
    # character alphabet first, so nothing is ever
    out-of-vocabulary
    vocab = {chr(c) for c in range(256)}
    words = Counter()
    for t in texts:
        for w in t.split():
            words[w] += 1
    for w, _ in words.most_common(max_vocab - len(vocab)):
        vocab.add(w)
    vocab = sorted(vocab)[:max_vocab]
    return Tokenizer(vocab)

class Tokenizer:
    def encode(self, text):
        # greedy longest match over the vocabulary
        (deterministic), window <= 24
        ...
```

Worked example, from an actual run of that code on three rendered addition prompts (`max_vocab=300`): the vocabulary came out **283 tokens — all 256 characters plus the frequent whole words** — and encoding

```
"Write a function that takes two numbers, a and b and
returns the sum of them."
```

produced **31 tokens**:

```
['Write', ' ', 'a', ' ', 'function', ' ', 'that', ' ',
'takes', ' ', 'two',
 ' ', 'numbers,', ' ', 'a', ' ', 'and', ' ', 'b', ' ',
 'and', ' ', 'returns',
 ' ', 'the', ' ', 'sum', ' ', 'of', ' ', 'them.']
```

Whole words are taken whole when they are in the vocabulary (`function`, `numbers,`), single characters otherwise; `decode(encode(x)) == x` exactly. Two consequences the book relies on: the tokenizer is deterministic (same corpus, same vocabulary), and its vocabulary is trained on the *training* text only in the corrected experiments (Chapter 15 states this for its fixed tokenizer), so evaluation never leaks vocabulary from held-out prompts.

A.8. Split construction: the invariants

Splits are assigned *after* generation, by `scripts/generate_data.py`, and the following invariants are what make a split claim checkable rather than a promise:

1. **One record, one split.** Every record carries its own `split` field, and each record lands in exactly one of `train` / `val` / `test` — splits are disjoint by `task_id`.
2. **Per-operation 70/15/15, by sorted `task_id`.** Within each operation the records are sorted by `task_id`; the first 15% go to `val`, the next 15% to `test`, the rest to `train` (with at least one record per non-empty split). So every operation appears in every split with the same distribution — the pilot's splits are *not* operation-disjoint.
3. **Operation holdout is a different mechanism.** The composites come from `generate_compositional`, a separate path, and never enter

the pilot's train split; that — not the 70/15/15 cut — is what makes the composition split a holdout.

4. **The manifest records the split's own provenance**: `dataset_version`, `seed`, `n_per_op`, the per-split counts, and the operation list, so the split can be re-derived instead of merely trusted.
5. **Regeneration is deterministic**. `make_task` seeds its RNG from the record's seed, so the same seed rebuilds the same record — a split can be reproduced, not just read.
6. **Hidden tests never enter training**. They are evaluator-only artifacts (Appendix D, "Hidden tests"), so no split's training data contains a test's expected values.
7. **Records are disjoint; prompt strings need not be**. The pilot reuses the same 21 prompt strings across train/val/test, so "held out" there means held-out *records* (and fresh hidden-test values), not held-out prompts — the surface and composition splits hold out prompt wording and operation families instead (Appendix D, "Train/val/test split"). A split claim therefore has to name its novelty axis, and these invariants are what the novelty audit checks.

A.9. How to run it

```
python scripts/generate_data.py --n-per-op 200
# writes pilot_train/val/test + manifest
python scripts/audit.py
# runs the leakage audit
```

That's the teacher. It's not magic — it's a controlled generator, audited for fairness, that makes the entire experimental program possible.

CHAPTER B.

The Failure Ledger

The design requires that we do not sanitize the journey into a success story. This is the honest record of everything that went wrong, was surprising, or was a failed attempt — because each of these taught us something, and several are as valuable as any success.

Each entry: what happened, what we learned, and what we did about it.

B.1. The evaluator reported the model at 0.000 — but the model was fine

What happened. On the very first Stage-1 evaluation, the trained model scored a reported **0.000** (syntax failure on every problem). This looked like a total failure of the approach.

What we found. The model was actually producing programs that were correct up to the end of the program — but our generation output appended null-byte padding, and Python's parser *correctly* rejects null bytes (they are not valid source). The fault was in our **extraction contract**: we handed the parser padded output without stripping the padding. So the

judge was scoring what were, after truncation, valid programs as syntax errors.

What we learned. The most important lesson of the book, demonstrated on ourselves: *never trust a number from a system we have not audited.* Fixing the judge revealed the model's true 0.897. If we'd taken 0.000 at face value, we'd have wrongly concluded the approach failed.

Action. Fixed `generate_code` to truncate at the first null byte; reran; got 0.897.

B.2. The pilot wording was so predictive of the answer we had to look again

What happened. The leakage audit trained a trivial TF-IDF classifier to predict the operation from the natural-language prompt. It succeeded **100%** of the time.

What we learned. At first we recorded this as "the wording leaks the answer," but on reflection most of it is **task signal, not leakage**: the request is supposed to name the operation ("sum", "absolute value"), so a classifier recovering it from the wording is the request doing its job. What it does tell us is that a model "succeeding" might just be exploiting that phrasing rather than learning the computation — which is *why* the surface-generalization tests matter. We therefore treat the 100% score as a flag to inspect *which* words drive it (operation words vs. an accidental cue), not as proof of contamination.

Action. Recorded as finding-001 (with the interpretation corrected above); noted the pilot is fine for Stage 1 but must add wording-family holdouts before any surface test.

B.3. A bigger model did NOT fix composition

What happened. We scaled the model across a ~33× range (0.88M → 29.3M) expecting the composition boundary to move. It did not: composition stayed at **0.000** at all four sizes (0.88M, 6.5M, 10.2M, 29.3M).

What we learned. At ~1–30M parameters, under the training schedules we ran, compositional generalization stayed at 0.000 and was **not moved by scaling alone**. We are careful not to call this a capacity "ceiling" — it is a measured boundary in this regime, not proof that capacity cannot help under other conditions. It is a genuine negative result that redirects the investigation.

Action. Recorded in `docs/experiments/scaling_composition.md`.

B.4. Sequential training caused catastrophic forgetting (A → 0.000)

What happened. Teaching the model lists after arithmetic, sequentially, completely destroyed the arithmetic (A-retention **0.000**).

What we learned. Catastrophic forgetting is real and severe here — but it is a **procedure** problem, not a fate. Joint training (A and B interleaved) retained A perfectly (1.000) with zero cost to learning B.

Action. Recorded; the chapter states this clearly — the protocol, not capacity, determines the outcome.

B.5. The pilot task was "too easy" (retrieval solved it)

What happened. The retrieval baseline scored **1.000** on the pilot test set, and the model scored 0.897. So a non-learning lookup did better than the model.

What we learned. The pilot task, as constructed, is retrieval-solvable — so it does not yet test whether the model *generalizes*, only whether it matches surface form. This is exactly the "task too easy" outcome the plan anticipated.

Action. We did not hide it; we used it to justify harder splits (surface, then composition), which produced the real findings above.

B.6. The human-written test set: 0/16

What happened. The trained model solved **0/16** naturally-phrased human prompts — even simple "add two numbers" phrased as a person would. Read by training exposure, that is **0 of 11** requests for operations the model had seen (phrasing/surface failures) and **0 of 5** genuinely held-out composite requests (a structural failure from a separate cause; see Chapter 15).

What we learned. The **surface** reading is corroborated by the **0/11**: the model learned a *template*, not the *task*, and fails when a real user rephrases a request. The **0/5** composites are a separate, expected outcome (those operations were never shown) and are not surface evidence; we do not fold them into the surface claim.

Action. Recorded as an external sanity check; it sharpens the book's honest conclusion.

B.7. An attempt at an independent line-edit failed

What happened. We dispatched the 85K-char draft to two free models for a proofread. One leaked its chain-of-thought and broke into noise; the other timed out. No usable independent review was collected.

What we learned. On this occasion, relying on two free hosted endpoints for a long-document proofread did not work. We report this narrowly: it says nothing general about all free endpoints, only that *these two calls on this long draft* produced no usable review. The discipline that matters here is that we did **not** fabricate a review from unusable output — we recorded the failure.

Action. Noted honestly as a production detail (see Appendix C's reproducibility note); the manuscript's line-edit stands on its own merit, not a fabricated review.

B.8. Transient SIGILL crashes during training

What happened. Long CPU training runs occasionally crashed with signal 4 (SIGILL) on the AVX-only Ivy Bridge CPU — intermittently, one run succeeds and the next dies.

What we learned. Hardware quirks are real and part of the brew. The apparent fix was `TORCH_DISABLE_AVX2=1` plus a retry loop (and `OMP_NUM_THREADS=1` for larger models). We report this as a *workaround we used*, not as a confirmed root-cause repair: the crashes were intermittent, so a successful retry after setting the variable does not by itself prove the variable is what fixed it, and we did not independently verify that the installed torch build actually reads this environment variable. All we can claim is that wrapping runs in a retry loop made them succeed reliably.

Action. Wrapped all long runs in a retry loop; documented the workaround.

B.9. Parameter-math and naming mistakes (caught by testing)

What happened. Early writing had a parameter-count mis-derivation (didn't sum to the true 884K/884,224) and the human-test evaluator initially referenced a non-existent key.

What we learned. Always verify arithmetic against the real build, and let the "test the tester" discipline catch even our own book's numbers.

Action. Recomputed from the actual build; fixed the evaluator.

B.10. A diagnostic schema we propose but did not measure

Many of the failures above are reported as a single "0.000" pass@1 number. That is honest but blunt: it does not tell a reader *why* a run failed. A candidate program can fail at several distinct points — it never parses, it parses but is outside the capability whitelist, it parses and is in-scope but crashes at runtime, or it runs but returns the wrong output.

The judge has four stages, and they are these (from `specs/evaluation_protocol_v0_1.md`): **syntax parse** (does it parse as Python?), **AST / capability validation** (is it within the sandbox whitelist?), **execution** (does it run without error under the resource policy?), and **semantic comparison** (does its output match the expected values?). It would be useful to record **per-stage failure counts** — how many candidates fell over at each of these four points — so a reader can see whether a 0.000 is a *syntax collapse* (the model emits garbage) or a *semantic near-miss* (the model emits a coherent, in-scope program that is just wrong).

Here is precisely what we did and did not record. The *aggregate* stage rates **are** available: the running evaluator (`src/eval/evaluator_runner.py`) accumulates, per run, `syntax_rate` (the fraction that pass the evaluator's **combined parse**

+ capability allowlist validation — in `src/evaluator/evaluator.py` the `syntax_ok` flag is set only when `sandbox.validate_source` succeeds, and that call checks parsing *and* the AST allowlist, so it is not a pure parse rate), `executable_rate` (fraction that passed at least one hidden test — the evaluator's recorded definition, `execution_ok = tests_passed > 0`; see Chapter 6), and `pass_at_1`. So for each reported run we do know, in aggregate, how many candidates passed combined validation and how many passed at least one test — and the pilot table in Chapter 10 shows these (0.897 pass@1, with the syntax/executable rates alongside). The *NUL* narrative in the failure ledger is exactly such a case: the intermediate validation score is what exposed the truncation problem.

What we did **not** record is the **per-candidate first-failure stage** — i.e. for each individual rejected candidate, we did not log the specific stage at which it stopped first (its syntax flag may be false *and* its execution flag false, but we did not capture which stage caused the rejection in a per-example record). So we have aggregate stage rates but not a per-candidate stage-resolved audit trail.

> We did **not** collect per-candidate stage-resolved counts for the experiments in this book — the evaluator recorded aggregate stage rates plus the final verdict per candidate, not the first failure stage for each one individually. Adding that is straightforward (the four judge stages already exist as functions) and we leave the per-candidate stage accounting as proposed work, not as a measured result.

The aggregate counts do leave a useful trace. Even without per-candidate records, we can build a coarse stage breakdown from the cumulative stage rates, because they share the same denominator (the number of evaluation records). The three recorded signals are named here by what they actually measure; in the saved manifests they appear under their historical keys `syntax_rate`, `executable_rate`, and `pass_at_1`:

```
combined-validation failures     = N − validation_pass
validated, but no test passed   = validation_pass −
at_least_one_test_pass
partial passes (≥1 but not all) = at_least_one_test_pass −
all_tests_pass
successes                       = all_tests_pass
```

(`validation_pass` = passed combined parse + capability validation = the manifest's `syntax_rate`; `at_least_one_test_pass` = the manifest's `executable_rate`; `all_tests_pass` = `pass_at_1`.) Note the second category combines *runtime* failures with programs that ran cleanly but answered **every** case incorrectly, unless those were saved separately, so we do **not** split it; the third category is programs that passed at least one but not all hidden tests, which is narrower than "executed but wrong." Applying this to the pilot's `stage1` run: the MODEL's validation, at-least-one-test, and all-tests rates were all 0.897 (over the 300-record test). Since `validation_pass = at_least_one_test_pass = all_tests_pass`, all **31/300** of the pilot's non-passing candidates failed the evaluator's **combined syntax-and-capability validation** — and because pure parsing was not logged separately from allowlist rejection, these aggregate rates do **not** isolate invalid Python syntax from a capability reject. We therefore do not say the failures were "all at the parsing stage"; the supported statement is the combined-validation one. It is consistent with the fragment evidence in Chapter 10, and it is precisely why we insist on the aggregate stage rates being reported alongside pass@1.

We recommend the same check for the composite runs before attributing their 0.000 to a *semantic* failure. We applied it: for the `composition_exposure` run's held-out composites, the MODEL's **syntax_rate** = 0.0, executable_rate = 0.0, and pass@1 = 0.0. So the composite 0.000 is **not** a record of programs that parsed, ran, and were then rejected by the semantic comparator — it is a record of candidates that **never passed the combined parse + capability validation gate** (and, since pure parsing was not logged separately, we cannot say how many of those were

invalid Python versus allowlist rejects). The dominant recorded failure is at *generation/validation*, before execution, not at the semantic comparison. This is a substantive qualification of any "semantic failure" reading of the composition result: what we measured is an aggregate zero, and its recorded failures were all pre-execution. (We do not claim the *only* cause is generation or validation — the cause of the validation-rejecting output is not resolved — only that the recorded stage rate puts the failure before the semantic comparison, so "the model understood the pieces but could not combine them" is **not** supported by these aggregate counts alone.)

B.11. Po-01 — The data-scaling sweep measured operation coverage, not data count

What happened. Chapter 11's size sweep (100/300/1000/3000 records) was presented as a one-variable data-count experiment — "only the data count changes." A code–claim audit of `scripts/run_data_scaling.py` showed the claim was false: the script does `pool = generate_dataset (n_per_op=400, ...)` and `train = pool[:size]`, and the generator appends records **in operation order**, so each arm is a *prefix* of the pool. The 100- and 300-record arms cover **1 of 10** operations (`add` only), the 1,000 arm covers **3**, and the 3,000 arm covers **8** — while the evaluation set spans all ten. The tokenizer was also refit per size. The recorded curve (0.100 / 0.098 / 0.300 / 0.641) and Figure 11.1 therefore track **operation coverage**, not record count.

What we learned. An innocent `pool[:size]` slice can turn a one-variable experiment into a two-variable one. The numbers were real measurements all along; what was invalid was the *comparison* the construction implied. Replicating the same construction across seeds reproduces the confound, not the causal effect. This is the book's **code–claim auditing** lesson in its strongest form: before a claim about an experiment is

published, the code that built the experiment's arms must be read against the claim.

Action. Chapter 11 rewritten: the curve and Figure 11.1 are labeled a *flawed historical run of operation coverage*; the "only the data count changes" claim, and any knee/threshold/data-efficiency lesson, are removed. A balanced, operation-stratified rerun (equal records per operation at every size, one fixed tokenizer, matched steps) was then performed and is recorded as `data_scaling_corrected` in Appendix C: with 10 examples per operation the curve is already flat at ~0.90, so there is no data-size benefit once operation coverage is held constant. Recorded here as Po-01.

B.12. Po-02 — The Chapter 13 "1,200 versus 1,200" comparison was 42 versus 1,200

What happened. Chapter 13's headline was an equal-count design: same 1,200 records, only diversity differs. The code audit of `scripts/run_diversity.py` showed the high-diversity pool is built one record per operation × wording family × identifier set, and the ten training operations have only **21 wording-family entries** in total — so with two identifier sets `build_pool()` constructs **42 records**, and `pool[:1200]` returns those 42. The minimal-diversity branch explicitly created 1,200 (largely repeated) records. The manifest recorded only the *requested* `n_train=1200`, which hid the realized 42. The arms were **42 versus 1,200**, differing in count and diversity at once.

What we learned. Record the *realized* dataset size, not the requested one — and assert it. The high arm's 1.000/1.000 is consistent with coverage of 42 exact training mappings; the equal-count causal lesson ("only diversity differed") is unsupported. Multi-seed replication of the same faulty construction repeats the flaw.

Action. Chapter 13 rewritten: Figure 13.1 relabeled as coverage on an unequal-count construction; the equal-count causal claim is withdrawn; a larger varied-family generator that can fill both arms to the same count (with a genuine held-out-family test) is required. Recorded here as Po-02.

B.13. Po-03 — The Stage-3 "new identifiers" condition changed two factors

What happened. Chapter 15's new-identifier arm was presented as an identifier-only ablation (`a,b` → `left,right`, everything else unchanged). The audit of `scripts/run_surface.py` showed the training pool excludes the last wording family while the `word_id` evaluation pool is built with `families="all"` — so the condition changes **both** the identifiers **and** the wording-family coverage. The reported 0.350 is a mixed-factor shift, not an identifier-only effect; the retrieval baseline's 1.000 → 0.683 fall is mixed for the same reason.

What we learned. A "one variable changed" claim must be checked against the actual set-construction arguments in the script, not against the design's intent. Mixed-factor arms cannot be attributed to either factor alone.

Action. Chapter 15 corrected: the row, the figure caption, and the shortcut audit now state the mixed factors; a corrected identifier × wording factorial (ID-only, wording-only, combined cells, operation-matched) was then performed and is recorded as `surface_corrected` in Appendix C: the identifier-only collapse is ~0 (0-3 of 600) and the wording-only collapse is 0 of 480, so the model does not generalize to any prompt-surface change. Recorded here as Po-03.

B.14. P0-04 — The held-out-wording denominator was 480, not 600

What happened. Figure 15.1 and its narration stated "600 held-out problems per condition" with illustrative counts 525/600 and 75/600. The audit of `src/nl_renderer/renderer.py` and `run_surface.py` showed held-out-wording records are only added for operations with a held-out family — `abs_of` and `cond_abs_max` have a single family — so the set is **8 × 60 = 480** records, and its operation mix differs from the 600-record familiar and new-identifier conditions. The correct readings are template 0.875 = **420/480**, retrieval 0.125 = **60/480**, and the model's 0.000 over **480**.

What we learned. Denominators must come from the generated file, not from the design's per-condition template (`n_per × n_ops`). A narrative count that disagrees with `len(eval_set)` is a bug waiting to be read as a result — and mismatched operation mixes make aggregate contrasts non-comparable even when every individual rate is right.

Action. Chapter 15 corrected: exact denominators and integer successes are stated at the figure and in the text; the operation-mismatch is flagged; a corrected comparison needs per-operation, matched-subset scoring with denominators recorded in the manifest. Recorded here as P0-04.

The code–claim auditing lesson (elevated). Entries 11–14 share one root cause: the prose claimed a controlled comparison that the code did not build. Every one was found by reading the release-tagged scripts against the manuscript's claims — no rerun was needed to establish them, because the construction is deterministic. The general discipline we take from this: **audit the code that constructs each experimental arm against the claim before publishing the claim**; **record realized (not requested) dataset sizes, exact denominators, and per-arm operation/family histograms**; **and treat a multi-seed replication of a flawed construction as**

replication of the flaw. The original bug histories above are preserved exactly as they stood, because the failure ledger's job is to show how a promising number dies — not to hide that it ever lived.

The point of this ledger is the opposite of marketing. Every entry above, in its own way, made the final understanding sharper — and several of them — the broken evaluator, the wording leak, the task-too-easy result, the 0/16 human test, and the four P0 experiment-construction defects — are among the most valuable findings in the book precisely because they forced us to be honest.

CHAPTER C.

The Experiment Registry

Every result in this book is traceable to a run, a configuration, a tokenizer, and a checkpoint. This registry is the single place to look up each one: what was tested, how it was run, where the numbers live, and what is *not* tested. Where a cell could not be measured we say "not tested" rather than "0" — an unmeasured quantity is not a zero.

C.1. How to read a run

Each entry names an **experiment** (what question it asks), a **run ID** (a stable label that appears in figures and tables), the **architecture** (`n_embd` / `n_layer` / `n_head`, all on a `block_size` of 128 and a `vocab_size` of 291 — 293 for the corrected diversity run, whose tokenizer was fit on a wider wording inventory), the **training steps**, the **seed**, and the **artifact** (manifest + checkpoint) that holds the record. The pass@1 figures are generated by the execution-based judge over a fixed number of held-out prompts; those counts are given where recorded.

C.2. The operation dictionary

Every operation has exactly one definition across renderer, oracle, reference, and tests. This table is the ground truth. All operations take either `int` inputs or a **list of ints**, and every one returns an `int` scalar. There are no list-returning operations in the task family.

The **class** column tells you how the generator treats it. "Primitive" means an atomic entry in the generator's operation tables (part of the training pool); "Composite" means one of the six held-out composites. See the note after the table — the classification is *operational*, not purely structural, because `cond_abs_max` is structurally a composition even though it is listed as a primitive.

The two right-hand columns are **descriptive sketches, not verbatim source**: "mathematical behavior" is a compact formula, and "behavioral sketch" is a readable one-line restatement — *not* the exact string the judge accepts (the actual reference programs are in `src/data_generator/generator.py`). The one-line forms below read as concise Python expressions such as `a if a > b else b` for clarity; the true reference functions are multi-line in the generator, so treat the sketch as the *behavior*, not the byte-for-byte source. Inspect `generator.py` (or the register's run record) for the accepted source.

Table C.2 — Operation dictionary: identification and types

ID	class	arity	input
`add`	primitive	2	int, int
`sub`	primitive	2	int, int
`mul`	primitive	2	int, int
`max_of`	primitive	2	int, int
`min_of`	primitive	2	int, int
`abs_of`	primitive	1	int

ID	class	arity	input
`list_sum`	primitive	1	list[int]
`list_len`	primitive	1	list[int]
`first_element`	primitive	1	list[int]
`cond_abs_max`	primitive	2	int, int
`abs_add`	**composite**	2	int, int
`sub_abs`	**composite**	2	int, int
`sum_of_abs`	**composite**	1	list[int]
`max_add`	**composite**	2	int, int
`double_first`	**composite**	1	list[int]
`len_minus_one`	**composite**	1	list[int]

Table C.3 — Operation dictionary: mathematical behavior and behavioral sketch

ID	mathematical behavior	behavioral sketch (not verbatim source)
`add`	`a + b`	`return a + b`
`sub`	`a - b`	`return a - b`
`mul`	`a * b`	`return a * b`
`max_of`	`max(a,b)`	`a if a > b else b`
`min_of`	`min(a,b)`	`a if a < b else b`
`abs_of`	`abs(a)`	`a if a >= 0 else -a`
`list_sum`	`sum(xs)`	`sum(xs)`
`list_len`	`len(xs)`	`len(xs)`
`first_element`	`xs[0]`	`xs[0]`
`cond_abs_max`	`max(abs(a),abs(b))`	`abs(a) if abs(a) >= abs(b) else abs(b)`
`abs_add`	`abs(a) + abs(b)`	`return abs(a) + abs(b)`

ID	mathematical behavior	behavioral sketch (not verbatim source)
`sub_abs`	`abs(a - b)`	`return abs(a - b)`
`sum_of_abs`	sum of elementwise absolute values	`sum(abs(x) for x in xs)`
`max_add`	`max(a+b, a-b)`	`(a+b) if (a+b) > (a-b) else (a-b)`
`double_first`	`2 * xs[0]`	`return 2 * xs[0]`
`len_minus_one`	`len(xs) - 1`	`return len(xs) - 1`

About the columns. Neither column is verbatim accepted source. The "mathematical behavior" column gives a short formula for what the operation *means*; the "behavioral sketch" column gives a readable one-line restatement of the same behavior, using concise Python-expressions (e.g. `abs(a) if abs(a) >= abs(b) else abs(b)`) or a generator expression (e.g. `sum(abs(x) for x in xs)`) rather than the exact multi-line function the judge references. The sandbox restricts the language, so the accepted reference is written as a plain loop, not a generator expression; do not assume the one-line sketch is the byte-for-byte source that runs. The actual reference programs are in `src/data_generator/generator.py` (and the register's run record).

Preconditions. `first_element` and `double_first` require a **non-empty list** (they index `xs[0]`), so the test generator never feeds them an empty list. `sum_of_abs`, `list_sum`, and `len_minus_one` are fine with an empty list — `len([]) - 1 = -1`, and the sums are `0` (or `0` for the absolute-value sum). `len_minus_one` on an empty list gives `-1`, which is a legal int.

Note on `abs_add` versus `abs(a+b)`: `abs_add` computes `abs(a) + abs(b)` — the sum of two absolute values — *not* the absolute value of the sum, `abs(a + b)`. These are different functions (for `a=-3, b=2` they give `5` and `1`). The book refers to `abs_add` as the sum of absolute values throughout. `sum_of_abs` is the list analogue: it takes a **list** and sums the

absolute values of its elements, so it must not be confused with `abs_add` (which takes two ints). It is the sum of elementwise absolute values, **not** the absolute value of the list sum.

C.3. Registry

The registry is printed as two tables so no column is crushed into a narrow strip on the 6x9 page: **Table C.4** pairs each run ID with the question it asked and its headline result; **Table C.5** pairs the same run IDs with the configuration and the artifacts (manifest and checkpoint) that hold the record. Every value is carried over unchanged from the run manifests.

Table C.4 — Registry: what each run asked and found

Run ID	Question (experiment)	Headline result
`stage1_seed0`	Stage 1 pilot	in-dist 0.897; final loss 5.84→0.0208. Note: `stage1.json` preserves the pre-fix 0.000 evaluation referenced by Appendix B.1
`stage3_surface`	Stage 3 surface — **superseded flawed historical run** (P0-03 mixed factors, P0-04 denominator); replaced by `surface_corrected`	in-dist 0.900; new-IDs 0.350 (mixed factors — identifiers *and* wording-family coverage, P0-03); held-out wording 0.000 over 480 records (8 ops × 60, P0-04)
`surface_corrected`	Corrected surface 2×2 factorial — **MEASURED** (fixes P0-03, P0-04)	model pass@1 by seed: familiar 0.898 / 0.900 / 0.940 (of 600); identifiers-only 0.000 / 0.003 / 0.005 (of 600); wording-only 0.000 / 0.000 / 0.000 (of 480); combined 0.000 / 0.025 / 0.000 (of 480) — collapse on any surface change

Run ID	Question (experiment)	Headline result
`stage4_pilot`	Stage 4 composition baseline	in-dist 0.9167 (n=60); composition 0.000
`stage4_6p5m`	Stage 4 — 6.5M	in-dist 0.897; composition 0.000
`stage4_10m`	Stage 4 — 10.2M	in-dist 0.773; composition 0.000
`stage4_29m`	Stage 4 — 29.3M	in-dist 0.897; composition 0.000
`data_scaling`	Data scaling — **superseded flawed historical run** (P0-01); replaced by `data_scaling_corrected`	in-dist 0.100⟶0.641 (100⟶3000) — arms are prefixes of an operation-ordered pool covering 1/1/3/8 of 10 operations (P0-01), so this is operation coverage, not a record-count curve
`data_scaling_corrected`	Corrected data scaling — **MEASURED** (fixes P0-01)	balanced 10/10 operations at every size, one fixed tokenizer, one shared 300-task test: pass@1 **flat** 0.893–0.997 across 100⟶3000 (10⟶300 per op), seeds 0/1/2 — **no data-size benefit**; template 0.800, retrieval 0.943–1.000 in all 12 arms
`diversity`	Quantity vs diversity — **superseded flawed historical run** (P0-02); replaced by `diversity_corrected`	minimal in-dist 0.500 / surface 0.000; high in-dist 1.000 / surface 1.000 — **realized 42 records (high) vs 1,200 (minimal)**, not the requested 1,200/1,200 (P0-02); the 1.000 is coverage of 42 exact mappings

Run ID	Question (experiment)	Headline result
`diversity_corrected`	Corrected equal-count diversity — **MEASURED** (fixes Po-02)	both arms exactly 1,200 records, 10/10 ops at 120/op, one fixed tokenizer, matched 1,000-step protocol; model pass@1 by seed: in-distribution LOW 0.950 / 0.950 / 0.950 vs HIGH 0.820 / 0.570 / 0.840 (means 0.950 vs 0.743); held-out family LOW 0.000 / 0.000 / 0.000 vs HIGH 0.640 / 0.300 / 0.710 (means **0.000 vs 0.550**) — diversity drives unseen-family transfer at a small in-distribution cost
`memorization`	Memorization	59/60 held-out; held-out program probe →general program
`continual`	Continual learning	sequential A-after-A 1.000 →A-after-B 0.000; joint A 1.000, B 0.889
`composition_exposure_pilot`	Composition exposure	exposed 0.667; held-out 0.000; in-dist 1.000
`composition_diversity_pilot`	Composition diversity	exposed 0.550-0.592; held-out 0.000
`composition_match_controls`	Matched controls for the composition zero — **MEASURED** (P1-09)	held-out composites 0 complete programs / 0 wrong-semantics / pass 0.000 under native and seen-surface framing (120/120 no-viable-code per seed under the seen frame); length-matched new composites 0 complete under both surfaces; reworded primitives 298/300 (seed 0) and 300/300 (seed 1) without a complete program — prompt-OOD generation collapse, not incorrect composition (Table C.16)

Table C.5 — Registry: configuration and artifacts

Run ID	Config (arch / steps / seed / params)	Manifest	Checkpoint
`stage1_seed0`	128/4/4 · 1500 · 0 · 884,224	stage1_results.json	stage1.pt
`stage3_surface`	128/4/4 · 1500 · 0 · 884,224	stage3_surface.json (superseded, Po-03/Po-04)	stage3_surface.pt
`surface_corrected`	128/4/4 · 1500 · 0/1/2 · 884,224	surface_corrected_seed{0,1,2}.json	surface_corrected_seed{0,1,2}.pt
`stage4_pilot`	128/4/4 · 1500 · 0 · 884,224	stage4_scaling.json (ckpt stage1.pt)	stage1.pt
`stage4_6p5m`	256/8/8 · 1000 · 0 · 6,500,352	stage4_composition_6p5m.json	stage4_6p5m.pt
`stage4_10m`	288/10/8 · 800 · 0 · 10,195,776	stage4_composition_10m.json	stage4_10m.pt
`stage4_29m`	448/12/8 · 800 · 0 · 29,290,240	stage4_composition.json	stage4_composition.pt
`data_scaling`	128/4/4 · 800 · 0 · 884,224	data_scaling.json (superseded, Po-01)	—
`data_scaling_corrected`	128/4/4 · 1000 · 0/1/2 · 884,224	data_scaling_corrected_seed{0,1,2}.json	data_scaling_corrected_seed{0,1,2}_size{100,300,1000,3000}.pt
`diversity`	128/4/4 · 900 · 0 · 884,224	diversity.json (superseded, Po-02)	—
`diversity_corrected`	128/4/4 · 1000 · 0/1/2 · 884,224	diversity_corrected_seed{0,1,2}.json	diversity_corrected_seed{0,1,2}_{low,high}.pt
`memorization`	128/4/4 · 1500 · 0 · 884,224	memorization.json	—
`continual`	128/4/4 · 700+700 · 0 · 884,224	continual.json; continual_preB.json	—

Run ID	Config (arch / steps / seed / params)	Manifest	Checkpoint
`composition_exposure_pilot`	128/4/4 · 1500 · 0 · 884,224	composition_exposure_pilot.json	stage4_exposure.pt
`composition_diversity_pilot`	128/4/4 · 1500 · 0 · 884,224	composition_diversity_pilot.json	stage4_compdiv_{minimal,high}_diversity_pilot.pt
`composition_match_controls`	128/4/4 · 1500 · 0/1 · 884,224	composition_match_controls_seed{0,1}.json	composition_match_controls_seed{0,1}.pt

Corrected-run tokenizer provenance. Each corrected run pins exactly one tokenizer across all arms and seeds. The canonical identifier cited throughout this book is the SHA-256 of the tokenizer *file on disk* — reproducible by hashing the file itself (`sha256sum artifacts/tokenizer/<file>.json`); each run manifest additionally records that tokenizer's in-memory vocabulary hash (a vocab-content hash — a different quantity, not the file hash). `data_scaling_corrected` uses `artifacts/tokenizer/data_scaling_corrected_tok.json`, SHA-256 `361f6d89e4f18642fac9d1d9077d6a5cab0e5d97701bafc1641ab09ec2b10eb5` (vocabulary 291, fit once on the union of the training texts at the largest size — `generate_dataset(n_per_op=300, id_set='letters', seed=4242)` — and never refit per size or seed). `surface_corrected` uses `artifacts/tokenizer/surface_corrected_tok.json`, SHA-256 `2c5c800b21e6a9a39d2688aec50cd4e092b3f99ea673b0618ffa6ffc65eb0a2b` (vocabulary 291, fit on train-only texts — letters × kept families — and never refit per cell or seed). `diversity_corrected` uses `artifacts/tokenizer/diversity_corrected_tok.json`, SHA-256 `2282c2fe22c34467e19`

`3651b92a5b59da1e4820f5add778196e145170d081dce` (vocabulary 293, fit once on the union of *both* arms' train texts — never any test text — and never refit per arm or seed; the same file is pinned in all three seed manifests). The manifests pin the same tokenizer for every seed, so a checkpoint must still be evaluated with the tokenizer it was trained with.

Matched-control tokenizer provenance. `composition_match_controls` pins one tokenizer across both seeds: `artifacts/tokenizer/composition_match_controls_tok.json`, SHA-256 `fbb9c903d0e5c1e2fbcd57dd7dfe27ff90ed74762a55e0cad1c776d8cf2ad17c`, vocabulary 291, fit on the train+exposed corpus then the held-out text (the exact exposure order) with a complete byte alphabet for the control prompts — the same tokenizer file pinned in both seed manifests (full detail in Table C.16).

C.4. Run provenance ledger

Tables C.4 and C.5 cover the headline runs. The ledger below is the compact, per-run provenance record for **every** manifest we hold — 41 in total — so a reader can see, run by run, the model-visible counts the manifest actually carries: manifest file, experiment ID, seed, training steps, `n_per_op` (records per operation), model parameters, final *training* loss, tokenizer vocabulary size, and the run's status. A dash means the ledger found no model-visible value for that field in that manifest — not zero, and not "not run." The configuration fields are packed into one column in the same `seed · steps · n_per_op · params · final loss · vocab` order that Table C.5 uses, so the two tables can be read against each other.

Table C.12 — Run provenance ledger: every manifest, its recorded configuration, and its status

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`composition_diversity_pilot.json`	`composition_diversity_pilot`	— · — · — · — · — · —	Scored composition-diversity pilot (Ch. 16); per-arm final losses are recorded under each arm, the ledger found no top-level config fields
`composition_exposure_pilot.json`	`composition_exposure_pilot`	0 · 1500 · 200 · 884,224 · 0.0187 · —	Scored composition-exposure run (Ch. 16)
`composition_exposure_seed1.json`	`composition_exposure_seed1`	1 · 1500 · 200 · 884,224 · 0.0179 · —	Multi-seed re-run — **matched** to the seed-0 configuration
`composition_exposure_seed2.json`	`composition_exposure_seed2`	2 · 1500 · 200 · 884,224 · 0.0218 · —	Multi-seed re-run — **matched** to the seed-0 configuration
`composition_match_controls_seed0.json`	`composition_match_controls`	0 · 1500 · 200 · 884,224 · 0.0169 · 291	**Matched controls for the composition zero — MEASURED (P1-09)**; seven structure × surface conditions with paired prompts; Table C.16

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`composition_match_controls_seed1.json`	`composition_match_controls`	1 · 1500 · 200 · 884,224 · 0.0187 · 291	**Matched controls — MEASURED (P1-09)**, matched to the seed-0 configuration; Table C.16
`continual.json`	`continual.json`	0 · 700 · 70 · — · — · —	Scored sequential continual-learning run (Ch. 18)
`continual_preB.json`	`continual_preB.json`	0 · 700 · 70 · — · — · —	Same-run pre-B intermediate evaluation (Appendix C.9)
`continual_seed1.json`	`continual_seed1.json`	1 · 600 · 80 · — · — · —	Multi-seed re-run — **config mismatch** vs seed 0 (600 steps / `n_per_op` 80 vs 700 / 70): not a matched replication
`continual_seed2.json`	`continual_seed2.json`	2 · 600 · 80 · — · — · —	Multi-seed re-run — **config mismatch** vs seed 0 (600 / 80 vs 700 / 70): not a matched replication

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`data_scaling.json`	`data_scaling.json`	0 · 800 · — · — · — · —	Scored data-scaling sweep — **superseded flawed historical run** (Po-01); replaced by `data_scaling_corrected_seed*`
`data_scaling_corrected_seed0.json`	`data_scaling_corrected`	0 · 1000 · 10/30/100/300 · 884,224 · 0.0200–0.0228 · 291	**Corrected balanced data-scaling sweep — MEASURED (fixes Po-01)**; 10/10 ops at every size, one fixed tokenizer, one shared 300-task test; pass@1 0.897/0.900/0.893/0.897 by size
`data_scaling_corrected_seed1.json`	`data_scaling_corrected`	1 · 1000 · 10/30/100/300 · 884,224 · 0.0177–0.0243 · 291	**Corrected balanced data-scaling sweep — MEASURED (fixes Po-01)**; pass@1 0.893/0.900/0.900/0.900 by size

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`data_scaling_corrected_seed2.json`	`data_scaling_corrected`	2 · 1000 · 10/30/100/300 · 884,224 · 0.0204–0.0235 · 291	**Corrected balanced data-scaling sweep — MEASURED (fixes Po-01)**; pass@1 0.900/0.900/0.997/0.900 by size
`data_scaling_seed1.json`	`data_scaling_seed1.json`	1 · 1000 · — · — · — · —	Multi-seed re-run — **config mismatch** vs seed 0 (1000 vs 800 steps); repeats the Po-01 confound; **superseded** by `data_scaling_corrected_seed*`
`data_scaling_seed2.json`	`data_scaling_seed2.json`	2 · 1000 · — · — · — · —	Multi-seed re-run — **config mismatch** vs seed 0 (1000 vs 800 steps); repeats the Po-01 confound; **superseded** by `data_scaling_corrected_seed*`
`decode_ablation.json`	`decode_ablation`	0 · — · 200 · — · — · —	Diagnostic decode/termination ablation (Ch. 16), not a scored experiment

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`decode_ablation_disk_tok.json`	`decode_ablation`	0 · — · 200 · — · — · —	Diagnostic ablation variant (regenerated tokenizer on disk), not a scored experiment
`dedup_audit.json`	`dedup_audit.json`	— · — · — · — · — · —	Regenerated diagnostic novelty audit — **not** the originally scored files
`diversity.json`	`diversity.json`	0 · 900 · — · — · — · —	Scored quantity-vs-diversity run — **flawed historical construction** (P0-02); **superseded** by `diversity_corrected_seed*`

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`diversity_corrected_seed0.json`	`diversity_corrected`	0 · 1000 · 120 · 884,224 · 0.0174 (low) / 0.0432 (high) · 293	**Corrected equal-count diversity — MEASURED (fixes Po-02)**; both arms exactly 1,200 records (120/op, 10/10 ops), one fixed tokenizer; in-dist LOW 0.950 (95/100) / HIGH 0.820 (82/100); held-out family LOW 0.000 (0/100) / HIGH 0.640 (64/100)
`diversity_corrected_seed1.json`	`diversity_corrected`	1 · 1000 · 120 · 884,224 · 0.0215 (low) / 0.0457 (high) · 293	**Corrected equal-count diversity — MEASURED (fixes Po-02)**; in-dist LOW 0.950 (95/100) / HIGH 0.570 (57/100); held-out family LOW 0.000 (0/100) / HIGH 0.300 (30/100)

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`diversity_corrected_seed2.json`	`diversity_corrected`	2 · 1000 · 120 · 884,224 · 0.0167 (low) / 0.0445 (high) · 293	**Corrected equal-count diversity — MEASURED (fixes P0-02)**; in-dist LOW 0.950 (95/100) / HIGH 0.840 (84/100); held-out family LOW 0.000 (0/100) / HIGH 0.710 (71/100)
`diversity_seed1.json`	`diversity_seed1.json`	1 · 900 · — · — · — · —	Multi-seed re-run — matched steps, but re-builds the same 42-vs-1,200 pools (P0-02); **superseded** by `diversity_corrected_seed*`
`diversity_seed2.json`	`diversity_seed2.json`	2 · 900 · — · — · — · —	Multi-seed re-run — matched steps, but re-builds the same 42-vs-1,200 pools (P0-02); **superseded** by `diversity_corrected_seed*`
`judge_mutation.json`	`judge_mutation.json`	— · — · — · — · — · —	Judge mutation suite (Ch. 17)

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`memorization.json`	`memorization.json`	— · — · — · — · — · —	Scored memorization probe (Ch. 14)
`stage1.json`	`stage1_seed0`	0 · 1500 · — · 884,224 · 0.0208 · 291	**Pre-fix 0.000 evaluation record** (Appendix B.1) — not the scored 0.897
`stage1_results.json`	`stage1_results.json`	— · — · — · — · — · —	Scored pilot record — the manifest-backed 0.897
`stage1_seed1.json`	`stage1_seed1`	1 · 1500 · — · 884,224 · 0.0196 · 291	Multi-seed re-run — **matched** to the seed-0 configuration
`stage1_seed2.json`	`stage1_seed2`	2 · 1500 · — · 884,224 · 0.0229 · 291	Multi-seed re-run — **matched** to the seed-0 configuration
`stage3_surface.json`	`stage3_surface`	0 · 1500 · 60 · 884,224 · 0.0218 · —	Scored Stage-3 surface run — **superseded flawed historical run** (Po-03, Po-04); replaced by `surface_corrected_seed*`

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`stage3_surface_seed1.json`	`stage3_surface_seed1`	1 · 1500 · 130 · 884,224 · 0.0275 · —	Multi-seed re-run — **config mismatch** vs seed 0 (`n_per_op` 130 vs 60): not a matched replication; **superseded** by `surface_corrected_seed*`
`stage3_surface_seed2.json`	`stage3_surface_seed2`	2 · 1500 · 130 · 884,224 · 0.0186 · —	Multi-seed re-run — **config mismatch** vs seed 0 (`n_per_op` 130 vs 60): not a matched replication; **superseded** by `surface_corrected_seed*`
`stage4_composition.json`	`stage4_composition_seed0`	0 · 800 · — · 29,290,240 · 0.0200 · 291	Scored **29.3M** size point — despite its name, this manifest is the 29.3M run
`stage4_composition_10m.json`	`stage4_composition_seed0`	0 · 800 · — · 10,195,776 · 0.0503 · 291	Scored **10.2M** size point

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`stage4_composition_6p5m.json`	`stage4_composition_seed0`	0 · 1000 · — · 6,500,352 · 0.0347 · 291	Scored **6.5M** size point — 1000 steps, so its training budget differs from the 800-step points
`stage4_scaling.json`	`stage4_scaling.json`	0 · — · — · — · — · —	The 0.88M Stage-4 baseline evaluation of `stage1.pt` (`sample=60`, `comp_per_op=40`)
`surface_corrected_seed0.json`	`surface_corrected`	0 · 1500 · 60 · 884,224 · 0.0288 · 291	**Corrected surface 2×2 factorial — MEASURED (fixes Po-03 + Po-04)**; familiar 0.898 (539/600), identifiers-only 0.000 (0/600), wording-only 0.000 (0/480), combined 0.000 (0/480)

Manifest	Experiment ID	Config (seed · steps · n_per_op · params · final loss · vocab)	Status
`surface_corrected_seed1.json`	`surface_corrected`	1 · 1500 · 60 · 884,224 · 0.0212 · 291	**Corrected surface 2×2 factorial — MEASURED (fixes Po-03 + Po-04)**; familiar 0.900 (540/600), identifiers-only 0.003 (2/600), wording-only 0.000 (0/480), combined 0.025 (12/480)
`surface_corrected_seed2.json`	`surface_corrected`	2 · 1500 · 60 · 884,224 · 0.0201 · 291	**Corrected surface 2×2 factorial — MEASURED (fixes Po-03 + Po-04)**; familiar 0.940 (564/600), identifiers-only 0.005 (3/600), wording-only 0.000 (0/480), combined 0.000 (0/480)

What the ledger's mismatches mean. The multi-seed re-runs are robustness checks, not all perfect matched replications, and the ledger records which is which. The **composition-exposure** re-runs (seeds 1 and 2) *are* matched: all three seeds ran 1500 steps at `n_per_op` 200 on the 884,224-parameter model. The other three re-run families used a **different configuration** than their seed-0 original: the **surface** re-runs used `n_per_op` 130 against seed 0's 60; the **data-scaling** re-runs used 1000

steps against seed 0's 800; and the **continual** re-runs used 600 steps at `n_per_op` 80 against seed 0's 700 at 70. Those particular re-runs therefore show that the recorded *pattern* repeats under a fresh seed and a nearby budget — they are not like-for-like replications of the seed-0 numbers, and we do not read them as such. The diversity and pilot re-runs matched their seed-0 steps; the diversity re-runs nevertheless repeat the P0-02 construction, because every seed re-built the same 42-versus-1,200 pools — those rows are superseded by the corrected three-seed `diversity_corrected` run (Table C.15), which was built equal-count from the start rather than re-run afterward.

What the ledger does not ship. The ledger carries model-visible counts and hashes from the manifests only. Per-run **raw per-candidate generations** were not archived, and the **exact checkpoints** are not shipped with the book (they are large; the repository carries the manifests and scored dataset files, not the weights). A reader can therefore verify every count in this ledger against the shipped manifests, but cannot re-score the original candidates or re-load the original weights without re-training from the recorded configuration and seed.

C.5. The scaling run: an honesty note on "same protocol"

The model-size sweep is often summarized as "same training protocol, only size changed." That is **not strictly true**. The 6.5M run trained for **1000** steps while the 10.2M and 29.3M runs trained for **800** steps. The larger models also have *wider* positional embeddings (larger `n_embd`), which makes each position vector richer — but it does **not** extend the context window: every run uses a `block_size` of **128** tokens (the larger models just have 128 × 448 / 128 × 288 etc. embedding tables, i.e. wider vectors, not more positions). And the tokenizers differ: the composition tokenizer was fit on reference programs that include the composite definitions, so it is a different token mapping from the pilot tokenizer. We did **not** hold every training hyperparameter constant across the size grid. So the size compar-

ison is *not* a single-variable, size-only experiment — training-budget and width/layer counts vary alongside size. We state the caveat here rather than imply a strictly-controlled sweep: what we can claim is that *composition stayed at 0.000 at every size under the schedules we ran and evaluated.* We cannot claim a clean size-isolate from the in-distribution differences (0.897 / 0.773 / 0.897), which may reflect the differing training budgets as much as the differing sizes. Note also that equal vocabulary sizes (291) do **not** imply equal token-ID mappings — the two tokenizers assign IDs differently, so a checkpoint must be evaluated with the tokenizer it was trained with.

C.6. The composition baseline: where the 0.88M number lives

The book's "Stage-4 baseline" (0.88M, composition 0.000) comes from evaluating the **pilot checkpoint** (`stage1.pt`) on the composition split — not from `stage4_composition.json`. That manifest, despite being named "stage4_composition", is actually the **29.3M** run (n_embd=448, n_layer=12). The surviving manifest that records this evaluation — `artifacts/manifests/stage4_scaling.json` (ckpt `stage1.pt`, pilot tokenizer, `comp_per_op=40`, `sample=60`) — gives the MODEL's in-distribution pass@1 as **0.9167** (n=60) with composition **0.000**. An earlier draft quoted **0.900** for this baseline in the body chapters; that value is not backed by a surviving manifest, so the body tables, the surrounding prose, and Figure 12.1 now publish the manifest-backed **0.9167** (n=60) as the canonical Stage-4 baseline figure. Two other familiar-prompt numbers stay separate and unchanged: the pilot's **0.897** over its own 300-record test, and the Stage-3 surface run's **0.900** in-distribution (`stage3_surface.json`) — three evaluations with different denominators. The robust, load-bearing result is the composition **0.000**, which the values agree on. The large-model runs are separate training runs.

C.7. Denominator and uniqueness notes

- **Decoding and extraction settings (run record).** Sampled decoding is temperature-0.8 single-sample, one fresh `model.generate` call **per evaluation record** (`src/eval/evaluator_runner.py`: `for t in tasks: candidate_fn(t)`), so records that share a prompt string still each get an independent draw (no output is cached or reused). The generation call passes only `max_new`; the temperature and sampling come from `src/model/gpt.py`'s default (0.8, `torch.multinomial`). Extraction truncates the decoded sequence at the first NUL byte (the model pads with `\x00`). The training seed is recorded per run; generation uses the same RNG state unless reset, so we report the training seed and note sampling is stochastic. `max_new`, stop policy, token-ID mapping, and the exact extraction rules live in `evaluator_runner.py`/`gpt.py` and are part of each run's environment, not re-derived per publication. Because the pilot test reuses only 21 prompt strings over 300 records, a single sample per record gives within-prompt replicates for the familiar-prompt aggregate, but does **not** give a per-prompt success-probability estimate for a brand-new prompt.
- **pass@1 denominators.** The pilot used 300 held-out test **records** (1,400 train / 300 val / 300 test), drawn from only **21 distinct prompt strings** (see the novelty audit; the test prompts are not new). Stage 4's large-model runs (6.5M, 10.2M, 29.3M) used 300 held-out primitives for in-distribution and 240 composite tasks (6 ops × 40) for composition; the 0.88M Stage-4 baseline (`stage4_scaling.json`) instead used `sample=60` for both its in-distribution and composition evaluations (its reported rates are 1/60 multiples); the judge then scores each. The data-scaling rows share a single common held-out test set (one `pool_test`, 540 records = 10 ops × 54 after the per-op split, generated once and reused across every size), so the training-size comparison in

that run is against the *same* held-out set. (It is a different set from the pilot's 300-record test, so the data-scaling scores are not directly comparable to the pilot's 0.897.) The corrected data-scaling arms (Table C.13) likewise share one fixed test set — 300 tasks, 30 per operation × 10 operations — across every size and seed, so all twelve arms are scored against the same denominator; the 540-record `pool_test` belongs to the superseded historical rows only. Exact successes/totals (integers over the reported denominator) are recorded in each manifest.

- **Unique model-visible prompts ≠ task IDs.** In the teacher, a task-ID seed changes the *hidden-test inputs*, so a new task ID can change the test values while the prompt and reference program stay identical. A reported "held-out" prompt therefore is only meaningful if we have checked the *prompt string* (the model input) is new, not merely the task ID. We flag prompts-as-model-inputs explicitly where it matters; see the deduplication audit note below.
- **Tokenizer.** Tokenizers are trained on the combined train prompts + reference programs to a vocabulary of 291. The pilot tokenizer (`pilot_tok`) and the composition tokenizer (`comp_tok`) differ because the composition tokenizer was trained over composite reference programs too. We want to be explicit about what this does and does not mean: fitting a tokenizer on composite *reference text* is **exposure at the preprocessing stage** — the tokenizer saw the tokens/characters in composite programs — but it is **not** the same as supervised training on composites (the model never sees a prompt → composite-program pair as a supervised example during training). Still, it means the unqualified statement "composite programs were never used anywhere in training/preprocessing" would be false, so we avoid it. It also means tokenizer/checkpoint pairing is essential: a model must be evaluated with the tokenizer it was trained on, and equal vocabulary sizes (291) do **not** imply equal token-ID mappings. The registry entry's manifest

records which tokenizer was used.

- **Training loop**. Fixed step count (no early stopping from validation loss); the reported loss is the final *training* loss, not a held-out measure.

C.8. The novelty audit (what was actually "new" in each held-out set)

Because a task ID can change only the hidden-test *inputs* while the prompt string stays the same, we audited every split for what was actually new to the model. It is important to keep three kinds of evidence apart: the **original scored data**, a **regenerated diagnostic reproduction**, and **illustrative examples**. Only the first validates an actually-reported result.

Pilot (Stage 1) — audited on the original `pilot_train/val/test.jsonl` files. This check is on the real dataset files (1,400 train / 300 val / 300 test records), not a regeneration. All three splits share the **same 21 unique prompt strings** and the **same 21 (prompt, program) pairs**; the 10 canonical reference programs are identical across splits. **Prompt overlap between train and test is 21/21** — every test prompt string also appears in training — and each test record is a new *task ID* that only changes the hidden-test *input values*. So the pilot's reported in-distribution result (0.897) is **not a test of new prompts**: it is a test of whether the model, given a prompt it saw in training, produces a program that passes *new input values*. That is a meaningful but narrower thing than generalization to a new request. We flag this explicitly, because "held-out" in the pilot means "new instances of a seen prompt," not "a never-seen request."

Stage 3 surface & Stage 4 composition — audited on a *regenerated reproduction*. These checks run `scripts/run_dedup_audit.py`, which rebuilds a smaller sample (10 records per op for surface, 100 train / 60 composite for composition) with the *current* generator and writes `artifacts/manifests/dedup_audit.json`. They report train × holdout **exact prompt-string overlap = 0** for the held-out word-

ing family and for the composite holdout. A fuller audit (`scripts/run_original_novelty_audit.py`; report `docs/reviews/loop/original_novelty_audit.md`) regenerates the exact scored splits using the scorer's own split code (AST-extracted from the scoring scripts) at the recorded seed and per-op counts, and confirms: train × held-out exact prompt, prompt–program-pair, family, and operation overlap are all **0** for the Stage-4 composition holdout (the six composite operations appear only there), and the Stage-3 wording-family holdout is prompt-disjoint (program overlap is expected, since a wording-only holdout keeps the same operations and letter identifiers); **18/18** disjointness assertions pass. We want to be clear about the limits of this: a regenerated reproduction can test the current generator's behavior; it does **not** by itself prove that the original scored Stage-3/Stage-4 files had the same membership (the original runs used larger per-op counts — 60 per op for the scored Stage-3 surface run, 240 composite records for Stage-4 — and those exact original files are the scored ones). So the surface/composition "overlap = 0" should be read as a property of the *reproduced* splits, corroborating but not *proving* the historical holdout until the original files are also audited.

A logical caveat: exact-prompt disjointness ≠ wording-family exclusion. Two different prompt strings can be rendered from the same wording family using different identifiers or constants. So "no exact prompt-string overlap" does **not** alone prove "no shared wording family." Family exclusion must be checked separately (by family ID or a verified construction invariant), not inferred from prompt-string disjointness. The ch13/ch15 wording-family distinction in the body rests on the *construction* — the teacher explicitly keeps the last family of each operation out of training — not merely on zero prompt-string overlap. The corrected diversity run (Table C.15) goes further still: its held-out families are checked by (operation, family) identity with collision counts recorded in each manifest — zero against both training arms — so for that run family exclusion is a property of the scored artifacts themselves, not of a regeneration.

The 59/60 probe — separate, and novelty-unverified. This is a distinct task-ID-level probe on the pilot (Chapter 14). It is **not** covered by the novelty audit above, and the audit does **not** verify that the 60 probe prompts (or the held-out program probe) were new to the model — they may well reuse training prompt strings, since the pilot test set reuses all 21. So we cannot claim the 59/60 probe established unseen-prompt generalization; we can only say it reported how many of those 60 records produced a general program. We treat it as a scoped probe, not a proof of a general rule or of the absence of memorization.

C.9. The sequential before/after measurement (C.9)

The continuing-learning result reports final A/B task accuracy. Because **final** A alone cannot distinguish "learned then forgotten" from "never acquired," we re-ran the identical sequential pipeline (same op sets, seeds, per-op counts, step counts, tokenizer schedule, optimizer defaults) and inserted a **same-run intermediate A evaluation right after phase A and before any B exposure**, writing `artifacts/manifests/continual_preB.json` (`scripts/run_continual_preB.py`). The measured trajectory on the A-test:

point	A accuracy
right after phase A (before B)	**1.000**
after phase B (final)	**0.000**

Combined with the joint control (A 1.000, B 0.889), this shows: A was acquired to 1.000 and then fell to 0.000 after B — a genuine same-run drop, not under-acquisition. Final B accuracy in the sequential run was 0.889. Note this re-run is the *sequential* pipeline with an added checkpoint for A; it is **not** the true replay-after-A-first design (which starts from an A-trained checkpoint and continues with B plus A replay), and we did not

run that.

C.10. What is NOT tested (explicitly)

- **Multiple seeds per size.** Each size was trained once, with one seed. We cannot attach error bars to the in-distribution spread (0.897 / 0.773 / 0.897) in Chapter

  12. Treat it as approximate, not an exact plateau.

- **Genuinely-held-out wording families for the *diversity* run — now measured.** The corrected `diversity_corrected` run (Table C.15) trains both arms with two families per operation (`h01`, `h02`) excluded from *every* training arm and scores them as a 100-task held-out-family test, with the exclusion audited by (operation, family) identity — zero family, prompt, and pair collisions against both arms — so the ch13 result is now a genuine held-out-family measurement at equal count (LOW 0.000 vs HIGH 0.550 mean). What the *superseded* historical run (P0-02) showed — the ch13 high-diversity model trained on *all* families × both id-sets — just **42 realized records**, so its 1.000 surface score is coverage, not generalization to a never-seen family, and the arms were not equal-count (42 vs 1,200) — remains true of that run and is why it is labeled flawed historical. The ch15 surface model, by contrast, trained on *all-but-the-last-family* per operation and was tested on that held-out last family — so its 0.000 is an **intended** held-out-family result (over 480 records, 8 operations — P0-04). The corrected `surface_corrected` factorial (Table C.14) now measures the held-out-wording cells directly, with the 480-record denominators (8 operations × 60; `abs_of` and `cond_abs_max` excluded) recorded in each manifest rather than inferred. We qualify "genuine" for the *historical* ch15 run: the audit that reported zero exact prompt-string overlap ran on *regenerated* samples with the current generator, not on the originally scored files, and exact-string disjointness does not by itself prove

wording-family exclusion. Historical family exclusion for that scored run was therefore intended and corroborated on regenerated samples, not independently verified on the original scored artifacts. These situations (ch13 corrected, ch13 historical, ch15) are different and the book keeps them separate.

- **Conditionals, indexing, loops as isolated operations**. `list_sum`'s reference uses a loop and `first_element` uses indexing, but the *task family* does not test general loop or indexing competence as standalone operations; those appear only inside other operations' reference programs (primitives and composites alike — conditionals in `max_of`/`min_of`/`abs_of`/`cond_abs_max`, the loop in `list_sum`, indexing in `first_element`), never as standalone tasks.
- **Composition beyond ~30M** (and the true "structural vs. above-our-ceiling" question) is not tested — the CPU lab becomes impractical beyond that.
- **A true replay-after-A-first** continual-learning design (vs the joint-training control we ran) is not tested; see the Chapter 18 caveat.
- **Mutation-testing beyond the boundary-tie case**. We ran a mutation suite and published its report: 35 mutants, 29 killed, 6 survivors, all six verified equivalent (strict→non-strict tie-breaks) over the integer domain, with all 16 reference controls accepted (see Chapter 17). What is **not** tested is whether the judge accepts an *alternative-but-correct* program that differs from the reference in some other way (not a mutation of it) — that is a distinct question beyond a mutation report.
- **Increased Python expressivity beyond the tested operations**. The experiments exercise only the fixed operation set; whether the model handles Python features, built-ins, or idioms outside that set is **untested** — no measurement was made, so this is an open surface, not a measured 0.
- **Longer / more complex programs (program length & complexity)**. Programs beyond the length and structural complexity of the tested

tasks are **untested**; we ran no evaluation on longer or more complex programs, so there is no score here — this is an untested axis, not a measured 0.

- **Generalization axes other than the four questions**. The generalization probes cover four axes — memorization, distributional, surface, and structural. Any other generalization axis is **untested**; we report no result for axes outside those four, which means untested rather than measured at 0.

C.11. Reproducibility & the companion repository

Each run script lives in `scripts/` (e.g. `run_composition.py`, `run_diversity.py`, `run_composition_exposure.py`, `run_composition_diversity.py`, `run_surface.py`, `run_data_scaling.py`, `run_continual.py`, `run_composition_match_controls.py`, plus `train.py` and `eval_ckpt.py`).

Publication status. The companion repository is published at `https://github.com/zhiqitao/let-us-brew-an-ai-model` and carries a release tag **`v20261001`** pointing at release commit **`a45a881158ed076f615f6d3bc2e72640dc5cdced`** (full hash; verified with `git rev-parse v20261001^{commit}` — this full hash is the *single* release identifier cited throughout the book). The PDF you are reading was built from repository commit **`af32fb8b1798f83553c0f5078fd34b62063b864d`** (the PDF build commit, recorded separately from the release commit; `git rev-parse HEAD` at build time). We cite the **full commit hash**, not just the tag, because a Git tag is a movable reference and is not by itself immutable. The single canonical release record is `docs/release_manifest.json`, which pins in one place the tag name, the tag-target commit, the PDF build commit, the SHA-256 of this PDF, and the four corrected-run tokenizer file hashes; `scripts/verify_release.py` asserts every one of those values against git, the built PDF, and the files on disk. **Run that gate under the**

repository's Python 3.11 environment (`.venv-311`): its PDF phase extracts the built book with `pymupdf`, which the bare system `python3` does not provide — `pymupdf==2.1` is pinned in `requirements-lock.txt` and installed in `.venv-311` (`source .venv-311/bin/activate && python scripts/verify_release.py`). Invoked under a python without `pymupdf`, the gate does not crash: the PDF phase prints a warning and is skipped, so a green run that reports that skip has *not* checked the PDF. The repository ships the experiment code, the run manifests under `artifacts/manifests/`, and the scored dataset files under `artifacts/datasets/`. The trained checkpoints are large and are **not** included (regenerable via `train.py` from the recorded config and seed); raw per-candidate generations were not archived. So an external reader can reproduce the pipeline and check the reported numbers against the shipped manifests, but a checkpoint-level re-run of the exact training runs requires re-training from the recorded configuration.

This means an *external* reader can run the pipeline and check the reported numbers against the shipped manifests, but cannot do a checkpoint-level re-run of the exact training runs without re-training from the recorded configuration. We make a clear distinction between (a) the originally scored experiment, whose data files and manifests are preserved in this repository, and (b) a freshly reproduced rerun, which may differ; none of the numbers in this book should be read as a reproducibility *confirmation* until an independent run reproduces them.

Multi-seed replication. We have taken a first step toward that confirmation: we re-ran the headline experiments — composition exposure, Stage-3 surface, diversity, data scaling, the Stage-1 pilot, and the continual-learning runs — from scratch under seeds 1 and 2 on the documented Python 3.11 environment (`.venv-311`, torch 2.14.0+cpu, `TORCH_DISABLE_AVX2=1`, `OMP_NUM_THREADS=2`), each run a fresh training from a different seed. Report: `docs/reviews/loop/multiseed_replication.md`. (The diversity rows in that report are

the superseded P0-02 construction; the corrected diversity run was built three-seed from the start — Table C.15.)

Table C.6 — Composition exposure across seeds

seed	in-dist pass@1	exposed pass@1	held-out pass@1
0	1.000	0.667	**0.000**
1	1.000	0.667	**0.000**
2	1.000	0.667	**0.000**

Table C.7 — Stage-3 surface across seeds (superseded flawed historical run, P0-03/P0-04)

seed	in-dist	new identifiers	held-out wording
0	0.900	0.350	0.000
1	0.900	0.348	0.004
2	0.898	0.348	0.000

The headline numbers reproduce: held-out composition is 0.000 for all three seeds, and the surface numbers are tightly stable. One caveat: the RETRIEVAL baseline printed 0.000 on seeds 1 and 2 (seed 0 gave 1.000 in-distribution) — a baseline-harness artifact of the re-runs (`run_surface.py` was patched to accept `--out`/`--tag` so re-runs would not overwrite the original manifest), not a model result. We do not report the re-run retrieval values as findings; the seed-0 retrieval figures in the body chapters stand as recorded. These rows are kept as the record of the *mixed-factor* construction (identifiers and wording-family coverage changed together, P0-03; 480-record denominator, P0-04); the corrected 2×2 factorial across seeds is Table C.14 below, and it supersedes this table.

Table C.8 — Diversity (quantity vs diversity) across seeds (superseded flawed historical run, P0-02)

seed	minimal in-dist	minimal surface	high in-dist	high surface
0	0.500	0.000	1.000	1.000
1	0.500	0.033	1.000	1.000
2	0.500	0.000	0.983	0.983

Stable across seeds: minimal-diversity sits at ~0.5 in-distribution / ~0 surface, high-diversity at ~1.0 / ~1.0. The pattern is not a single-seed accident — but every seed re-built the same **42-versus-1,200** pools (P0-02), so the replication repeats the construction flaw rather than establishing an equal-count effect. **Superseded by the corrected equal-count run in Table C.15**, which fixes P0-02 and replaces both the 0.500/0.000 and the 1.000/1.000 readings.

Table C.9 — Data scaling across seeds (superseded flawed historical run, P0-01)

size	seed 0 (800 steps)	seed 1 (1000 steps)	seed 2 (1000 steps)
100	0.100	0.094	0.076
300	0.098	0.100	0.100
1000	0.300	0.300	0.300
3000	0.641	0.748	0.748

Step-budget caveat: the re-runs did not share a single step budget — seed 0 ran at the book's 800 steps, seeds 1 and 2 at 1000. Construction caveat (P0-01): every seed re-ran the same prefix-of-an-operation-ordered-pool arms (1/1/3/8 of the ten operations), so what the table shows is that the **confound** is deterministic — the monotone pattern repeats because the coverage slice repeats, not because record count was isolated. Only the size-3000 absolute moves with the budget (0.641 at 800 steps vs

0.748 at 1000, and seed 1 = seed 2 = 0.748 at the same 1000-step budget). The robust claim is therefore the repeatability of the recorded pattern, not a data-size trend. Superseded by the corrected balanced sweep in Table C.13, which *did* isolate record count and found a flat curve.

Table C.10 — Pilot (Stage-1) in-distribution across seeds

seed	in-dist pass@1	final loss
1	0.900	0.0196
2	0.900	0.0229

Both re-run seeds reproduce the published pilot in-distribution result (~0.90; the book's 0.897 over the 300-record test). Seed 0 is not listed as a re-run row because seed 0's `stage1.json` is the **pre-fix 0.000 record** referenced by Appendix B.1 — the pre-NUL-truncation evaluation preserved for the failure ledger — not a re-run value; the seed-0 figure quoted throughout the book is the manifest-backed 0.897 in `stage1_results.json` (final loss 0.0208).

Table C.11 — Continual learning across seeds

seed	sequential A-retention	sequential B-acquisition	joint/interleaved A-retention	joint/interleaved B-acquisition
1	0.000	0.889	1.000	0.889
2	0.000	0.861	1.000	0.889

"Replay" here (as the chapter originally labeled it) is the interleaved-from-the-start condition (the chapter's joint-training control), not true post-A experience replay; we now call it **joint/interleaved (A+B from start)** throughout (P1-14), with the same naming caveat as Chapter 18. Stable across seeds: sequential training catastrophically forgets A (retention 0.000) while still acquiring B (~0.87–0.89), and joint/interleaved retains A

(1.000) while acquiring B (0.889). The joint/interleaved-vs-sequential distinction is robust, not a single-seed artifact.

The three corrected reruns. The corrected experiments were built as three-seed runs from the start, so their seed tables come first-class rather than as re-runs. They supersede Tables C.7, C.8, and C.9 above.

Table C.13 — Corrected data scaling across seeds (MEASURED; fixes Po-01) — model pass@1 on the one shared 300-task test (30 per operation × 10 operations), successes in parentheses:

size (per operation)	seed 0	seed 1	seed 2
100 (10/op)	0.897 (269/300)	0.893 (268/300)	0.900 (270/300)
300 (30/op)	0.900 (270/300)	0.900 (270/300)	0.900 (270/300)
1,000 (100/op)	0.893 (268/300)	0.900 (270/300)	0.997 (299/300)
3,000 (300/op)	0.897 (269/300)	0.900 (270/300)	0.900 (270/300)

Every arm covers 10 of 10 operations (balanced nested per-op prefixes, shuffled), uses the one fixed tokenizer (SHA-256 `361f6d89e4f18642fac9d1d9077d6a5cab0e5d97701bafc1641ab09ec2b10eb5`), and trains 1,000 steps at batch 16, learning rate 1e-3 on the 884,224-parameter model. TEMPLATE is 0.800 (240/300) and RETRIEVAL 1.000 in eleven arms and 0.943 (283/300) in one; final training losses span 0.0177–0.0243 with no trend by size. Per operation, `cond_abs_max` is 0.0 in nine of the twelve arms and still 0.0 at size 3,000 in all three seeds; every other operation is ≥0.967 except `list_len` at 0.433 in seed 1's smallest arm. The reading is **flat**: no data-size-dependent benefit once operation coverage is held fixed.

Table C.14 — Corrected surface 2×2 factorial across seeds (MEA-

SURED; fixes P0-03, P0-04) — model pass@1 by cell, successes in parentheses:

cell (denominator)	seed 0	seed 1	seed 2
familiar — letters × kept (600)	0.898 (539)	0.900 (540)	0.940 (564)
identifiers only — words × kept (600)	0.000 (0)	0.003 (2)	0.005 (3)
wording only — letters × held-out (480)	0.000 (0)	0.000 (0)	0.000 (0)
combined — words × held-out (480)	0.000 (0)	0.025 (12)	0.000 (0)

One fixed 600-record training set (60 per operation × 10 operations, letters × kept families) and one fixed train-only tokenizer (SHA-256 `2c5c800b21e6a9a39d2688aec50cd4e092b3f99ea673b0618ffa6ffc65eb0a2b`) underlie every cell; model, TEMPLATE, and RETRIEVAL are scored on identical records per cell. The two held-out-wording cells have 480 records (8 operations × 60) because `abs_of` and `cond_abs_max` have a single wording family and are excluded from those cells. TEMPLATE is 480/600 = 0.800 on the two kept-wording cells and 420/480 = 0.875 on the two held-out-wording cells; RETRIEVAL is 600/600 = 1.000 and 60/480 = 0.125 respectively — both identical across seeds. The reading is a collapse on **any** prompt-surface change, single-factor or combined, against ~0.90 on the familiar surface.

Table C.15 — Corrected diversity across seeds (MEASURED; fixes P0-02) — model pass@1, successes in parentheses; both tests are 100 tasks (10 per operation × 10 operations), identical across arms and seeds:

arm (1,200 records each)	in-distribution — seed 0 / 1 / 2	held-out family — seed 0 / 1 / 2
LOW — 2 families/op × letters (20 unique pairs)	0.950 (95) / 0.950 (95) / 0.950 (95)	0.000 (0) / 0.000 (0) / 0.000 (0)
HIGH — all train families × 5 id sets (605 unique pairs)	0.820 (82) / 0.570 (57) / 0.840 (84)	0.640 (64) / 0.300 (30) / 0.710 (71)

Three-seed means: LOW **0.950** in-distribution / **0.000** held-out family; HIGH **0.743** in-distribution / **0.550** held-out family. Both arms hold exactly 1,200 records covering 10 of 10 operations at 120 per operation, under one fixed tokenizer (SHA-256 `2282c2fe22c34467e193651b92a5b59da1e4820f5add778196e145170d081dce`, vocabulary 293) and a matched protocol (1,000 steps, batch 16, learning rate 1e-3, 884,224 parameters, the same initialization for both arms within each seed). The in-distribution test uses the LOW arm's families × letters — familiar to both arms by construction, since the LOW space is a strict subset of the HIGH space; the held-out test uses two families per operation (`h01`, `h02`) that no training arm ever sees, and the manifest's audit records **zero** (operation, family), prompt, and prompt/program-pair collisions against *both* arms, plus instance-disjoint splits. TEMPLATE is 0.800 (80/100) in-distribution and 0.700 (70/100) on the held-out family, identical across arms and seeds; RETRIEVAL is 1.000 (100/100) in-distribution in both arms, and on the held-out family scores 0.600 (60/100) from the LOW arm's training pool against 1.000 (100/100) from the HIGH arm's pool — the retriever is built over each arm's own training records, so the diverse pool is what a retriever exploits. Final training losses are LOW 0.0174 / 0.0215 / 0.0167 and HIGH 0.0432 / 0.0457 / 0.0445. The reading is **diversity is decisive for generalization to a held-out phrasing family (0.000 → 0.550 mean) at the cost of some in-distribution sharpness (0.950 → 0.743 mean)**; this table supersedes Table C.8 and the Chapter 13 numbers drawn from it.

Table C.16 — Composition matched controls across seeds (MEA-

SURED; P1-09) — per-condition failure decomposition under the `favorable256` decode (temperature 0.8, `max_new` 256, NUL-truncated extraction plus the delete-all-NULs variant), each cell `no-viable-code / incomplete / wrong-semantics` followed by the complete-program rate (defines `solve`) and pass@1; the `book_prefix80` extraction (`max_new` 80) gives identical rates:

condition (role)	n	seed 0	seed 1
`primitive_native` (anchor: seen structure, seen surface)	300	0/300 · 0 · 0 · 1.000 · 1.000	0/300 · 0 · 0 · 1.000 · 1.000
`exposed_native` (anchor: composites seen in training)	120	39/120 · 0 · 1 · 0.675 · 0.667	1/120 · 0 · 40 · 0.992 · 0.658
`heldout_native` (baseline: the book's failing condition)	120	120/120 · 0 · 0 · 0.000 · 0.000	118/120 · 2 · 0 · 0.000 · 0.000
`heldout_seen_surface` (control b: seen surface, unseen structure)	120	120/120 · 0 · 0 · 0.000 · 0.000	120/120 · 0 · 0 · 0.000 · 0.000
`new_composite_unseen_surface` (control c: length-matched, unseen surface)	80	44/80 · 36 · 0 · 0.000 · 0.000	79/80 · 1 · 0 · 0.000 · 0.000
`new_composite_seen_surface` (control c+b: length-matched, seen surface)	80	80/80 · 0 · 0 · 0.000 · 0.000	80/80 · 0 · 0 · 0.000 · 0.000

condition (role)	n	seed 0	seed 1
`primitive_unseen_surface` (control a: seen structure, unseen surface)	300	298/300 · 0 · 2 · 0.007 · 0.000	295/300 · 5 · 0 · 0.000 · 0.000

Configuration and tokenizer. One model per seed, trained exactly as the composition-exposure run (128/4/4, 1500 steps, batch 16, learning rate 1e-3, 884,224 parameters, 200 records per primitive operation plus 120 exposed-composite records; final training loss 0.0169 for seed 0 and 0.0187 for seed 1), seeds 0 and 1, manifests `composition_match_controls_seed{0,1}.json`, checkpoints `composition_match_controls_seed{0,1}.pt`, script `scripts/run_composition_match_controls.py`, raw generations under `artifacts/raw_outputs/composition_match_controls/`. One tokenizer pins both seeds: `artifacts/tokenizer/composition_match_controls_tok.json`, SHA-256 `fbb9c903d0e5c1e2fbcd57dd7dfe27ff90ed74762a55e0cad1c776d8cf2ad17c`, vocabulary 291, fit on the train+exposed corpus then the held-out text (the exact exposure order) with a complete byte alphabet for the control prompts, the same tokenizer file pinned in both seed manifests. Decoding is the book's temperature-0.8 sampling with `max_new` 256, NUL truncation, and early stop after 16 consecutive NUL tokens; both recorded extractions (`book_prefix80` at `max_new` 80, `favorable256` at `max_new` 256) give identical rates. Paired conditions share byte-identical reference programs and hidden tests — only the prompt changes — and all 1,120 reference programs pass their own tests.

Anchors. The anchors reproduce the book: `primitive_native` is 300/300 pass in both seeds, and `exposed_native` is 0.667 (seed 0) and 0.658 (seed 1) against the book's 0.667 exposed-composite figure — the same pipeline that measures the collapse measures the successes. Length matching is asserted against the mastered-primitive reference range of

14–68 tokens: the new composites are 27 tokens (`abs_mul`) and 23 tokens (`first_plus_len`), and the held-out references (66, 18, and 20 tokens) sit inside the range as well. Per composite, seed 0's `abs_mul` under the unseen surface reaches syntax 0.925 yet defines 0/40 complete programs — 36 of the 40 parse only as module-level fragments with no `solve`.

The honest mechanism. The composition 0.000 is a **no-viable-code generation failure**: 0 of the 120 held-out generations per seed defines a complete `solve` program (complete-program rate 0.000), with **0 wrong-semantics** and 0 pass — semantics are never reached, so we never observe a wrong composition. The failure survives control (b), the verbatim seen-surface framing (120/120 no-viable-code per seed), so the wording frame is not the explanation, and control (c), the length-matched new composites (0 complete programs under both surfaces, both seeds), so program length is not the explanation. Control (a) runs the other way: rewording *mastered* primitive programs under never-seen families leaves 298/300 (seed 0) and 300/300 (seed 1) generations without a complete program, against 300/300 complete and passing under the native wording. The mechanism we therefore report is a **generic prompt-OOD generation collapse** — this model emits no viable code for out-of-distribution prompts, of which unseen composite structure is one sufficient trigger and never-seen wording on a seen program is another. The structural-generalization conclusion survives the matched controls; what changes is the mechanism we attach to it: the model does not "compose incorrectly," it generates no viable code for unseen prompts, unseen compositions among them. An earlier attempt that also seeded the global batch scheduler is archived as `*_bothseeded.*` manifests and is not reported (its seed-1 batch stream diverged late in training).

Eval-pipeline robustness fixes (no measured value changed). Two cross-version robustness fixes were needed so native re-runs work in the current environment, and neither changes any measured result: (1) `generate_code` in `src/eval/evaluator_runner.py` now

coerces a `None`/`bytes` decode to `''`/`str`, and `validate_source` in `src/sandbox/sandbox.py` handles `None`/`bytes` — this fixes a crash when the model generates nothing, and a degenerate empty generation is now honestly counted as a parse failure; (2) the native re-runs use a Python 3.11 venv (`.venv-311`) as the quick start above documents. These fixes only make re-runs work in the current environment; they alter no reported number.

The quick start:

1. **Clone the companion repository** and check out the `v20261001` tag.
2. **Install dependencies.** Python 3.11.16, PyTorch 2.14.0+cpu (CPU build, no GPU). The training and evaluation core depends on `torch` and the standard library; the *printed audits and diagnostics* additionally use `scikit-learn` (and the figure scripts use `matplotlib`), so treat those as separate groups. Install the CPU-only torch build from the official CPU wheel index — on Linux a bare `pip install torch==2.14.0` can select a CUDA build, so the index flag matters for a CPU-only environment:

   ```
   python -m pip install \
     --index-url https://download.pytorch.org/whl/cpu \
     torch==2.14.0
   python -m pip install scikit-learn matplotlib
   ```

   The repository ships a pinned lockfile, `requirements-lock.txt`, recording the exact CPU-only environment the reported runs and the printed audits used (Python 3.11, `torch==2.14.0+cpu`, `numpy==2.2.6`, `matplotlib==3.11.2`, `scikit-learn==1.9.1`); install it with `python -m pip install --extra-index-url https://download.pytorch.org/whl/cpu -r requirements-lock.txt` (the `+cpu` torch build comes from the CPU wheel index above). The intended environment is CPU-only — no CUDA — matching the lab described under **Runtime**. The same CPU index URL also serves the macOS and Windows CPU

wheels (keep `--index-url` there too); a CUDA-enabled Linux install should omit `--index-url` and take the default wheels. We ran only the Linux CPU lab described under **Runtime**, so treat the command above as *that* platform's recipe and add OS-specific recipes as they are verified — one transcript does not cover every platform.

3. **Prepare the data & tokenizer**. Generate the dataset files under `artifacts/datasets/` (e.g. `python scripts/generate_data.py`), then train the tokenizer. The pilot tokenizer is built inside `scripts/train.py` (via `train_tokenizer(..., save_path=...)`), so an explicit tokenizer step is only needed for runs that reuse a saved tokenizer; when in doubt, `train.py` writes e.g. `artifacts/tokenizer/pilot_tok.json`. Run scripts expect the matching tokenizer to already exist, so verify the manifest records which tokenizer each checkpoint uses before evaluating.
4. **Run a pilot**: `python scripts/train.py --steps 1500 --n-embd 128 --n-layer 4 --n-head 4 --bs 16 --seed 0` then `python scripts/eval_ckpt.py`. `eval_ckpt.py` loads the saved checkpoint by default (the `stage1.pt`/`stage1.json` artifacts produced by training); verify the default path matches your checkout.
5. **Expected artifacts**: the run's manifest (e.g. `stage1.json`) and checkpoint (`stage1.pt`) under `artifacts/manifests/` and `artifacts/checkpoints/`.

Tokenizer provenance: the `comp_tok.json` clobber. The composition tokenizer file `artifacts/tokenizer/comp_tok.json` (gitignored) was overwritten by a later experiment (`run_composition_diversity.py`) *after* the composition-exposure checkpoint had been trained; the overwritten vocab differed from that checkpoint's training vocab at 75 of 291 indices. The scored composition results are unaffected — they were computed at scoring time with the

correct tokenizer held in memory — but a naive re-evaluation that loads the clobbered on-disk file collapses *both* the exposed and held-out sets to a spurious 0.000 under every decode setting (the condition is recorded in the decode-ablation report's appendix, `docs/reviews/loop/decode_ablation.md`, and in `artifacts/manifests/decode_ablation.json`). Reproducing any composition eval therefore requires reconstructing the exact training tokenizer: `train_tokenizer` is deterministic, so retraining it over the exposure corpus reproduces the training vocab exactly — which is what `scripts/run_decode_ablation.py` does, and what we used to regenerate `comp_tok.json`, so the on-disk file again matches the 291-token training vocab. The general rule stands regardless: equal vocabulary sizes (291) do **not** imply equal token-ID mappings, so a checkpoint must be evaluated with the tokenizer it was trained with.

Runtime. These are *our* hardware-specific times, not a promise for yours: roughly 5-10 minutes per 1500-step pilot training on a single-core CPU; larger models (6.5M-29.3M) take substantially longer (minutes to low tens of minutes each). The [MEASURED] numbers in the book are the ones from our runs.

A note on the CPU workaround. On the AVX-only Ivy Bridge lab we set `TORCH_DISABLE_AVX2=1` (plus `OMP_NUM_THREADS=1` for larger models). As Appendix B.8 notes, we report this as a *workaround we used*, not a confirmed root-cause fix: the crashes were intermittent, a successful retry does not prove the variable is what fixed them, and we did not independently verify that the installed torch build reads it. Treat it as a hardware-specific workaround for *this* lab, **separate** from the universal installation steps above — on other machines you may not need it at all.

A production note on the free-endpoint side. We do not rely on any external service for the results in this book; everything was trained and evaluated locally on the CPU lab described above, so the numbers do not depend on a hosted endpoint staying up or behaving.

CHAPTER D.

Glossary

Short definitions of the terms used in this book. Where a term has a standard meaning that we follow, we say so; where we use it in a deliberately narrow way, we flag it.

Three counting units are defined separately below — a **record**, a **unique prompt**, and a **held-out family**. They are not interchangeable evidence: a pass on one is not a pass on the others, so wherever a number is a count, the book says which unit it counts.

> **A note on the word "learned."** The book uses "the model learned X" in more than one sense, and we want to be explicit about which each claim uses. Sometimes it means the model's *optimization fitted the training data* (its loss fell). Sometimes it means *a new prompt mapped to a correct program* (an evaluation success). Sometimes it means *an abstract arithmetic fact is represented internally* (a mechanism claim). Sometimes it means *a novel program structure was generated* (a compositional claim). So when the book says "learned," the honest question is always: measured which behavior? We therefore do **not** treat "learner vs. parrot" as a binary — a model can be a genuine learner of the narrow surface task (its in-distribution score is real) and still not be a compositional reasoner. Each claim in the book is scoped to the specific measured behavior, not to a general "the model is intelligent" assertion. (The four-question capability map in Chapter 20 uses a `[MEASURED]` /

`[DERIVED]` notation on the rows it labels; not every claim in the book carries an explicit tag, so read the scoping in the sentence that introduces each number.)

- **AST (Abstract Syntax Tree)**. A tree representation of a program's structure, stripped of formatting. The sandbox builds an AST of the generated program and checks that it uses only allowed constructs.
- **BPE (Byte-Pair Encoding)**. A tokenization method that repeatedly merges the most common symbol pairs into a single token. It turns text into a fixed-size vocabulary of subword pieces. **The tokenizer this book actually uses is *not* BPE**: it is a greedy character/whole-word vocabulary tokenizer — 256 character tokens plus frequent whole words, encoded by longest match (see Chapter 8). The earlier "compact BPE" wording in Chapter 8 was wrong and has been corrected (P1-07).
- **Baseline / rival**. A deliberately simple reference system (here, a keyword template-matcher and a TF-IDF retriever) used to interpret the model's score. A baseline tells us whether the task was already easy for a simpler machine.
- **Checkpoint**. A saved copy of the model's weights at a point in training.
- **Composite operation**. An operation that is a combination of two primitives the model already knows (e.g. `abs_add = abs(a) + abs(b)`).
- **Continual learning**. Learning a new capability after an old one, and whether the old one is retained.
- **Distribution shift**. When the test inputs come from a different distribution than the training inputs. Surface change (new wording) is a mild case.
- **Greedy decoding**. Choosing, at each step, the single most likely next token, with no sampling.
- **Sampled decoding (what the book's numbers use)**. The evaluation calls `model.generate` with no temperature override, so it uses the model's default **temperature-0.8 multinomial sampling** — a single stochastic sample per record, not greedy/argmax. Because it is one draw per record, a single record gives no within-*record* estimate of sampling variability, and the repeated records across a run are not a perfect distribution over all possible draws. We therefore report it

as **single-sample execution accuracy / sampled pass@1**. The worked examples are the same single-sample output.

- **Held-out**. Kept out of training and used for an evaluation. Which axis is held out differs by split — prompt string, wording family, operation ID, or (in the pilot) only the hidden-test input values — so the book states the axis wherever "held out" carries a claim; see "Train/val/test split" below.
- **Held-out family (held-out template family)**. A template family — a phrasing skeleton the teacher renders with — kept out of training entirely and used only for evaluation. It is the strongest of the three novelty units: every prompt in a held-out family is new *and* comes from a skeleton the model never saw, whereas a held-out record or a held-out prompt string can still reuse a familiar skeleton. Operations with a single family (`abs_of`, `cond_abs_max`) have no held-out family to offer, so they are excluded from held-out-wording cells rather than counted in them.
- **Held-out program probe (formerly called a "canary")**. Here, a held-out prompt-and-answer *pair* (a prompt the model did not see as this exact pair, though its prompt novelty is not independently verified — see Appendix C.7) used to check whether the model reproduces a stored value or produces a general program. We use the term in the held-out-probe sense, not the classic memorization-canary sense.
- **Hidden tests**. Input/expected-output pairs used to grade a generated program. In this book they are evaluator-only artifacts: they never enter training.
- **In-distribution**. Tasks drawn from the same distribution as training (here, held out in *instances* but the same operation / surface family).
- **Joint / interleaved training (A+B from start)**. Training on both task groups' examples interleaved from the beginning of training. Earlier drafts of Chapter 18 labeled this condition "replay"; we renamed it because *replay* properly means continuing from an already-A-trained checkpoint with A examples mixed back in — a design this book did **not** run (P1-14).
- **Judge**. The execution-based evaluator: it runs the generated program against hidden tests and compares outputs (with a semantic comparator and mutation control).
- **Mutation testing**. Generating deliberately-broken programs and

checking that the hidden-test suite catches them, to measure how discriminating the tests are.

- **New IDs ("new task IDs")**. Where the book says *new IDs* — e.g. the pilot's held-out test — it means new **task/test/execution IDs**: records whose hidden-test *input values* differ while the prompt string and target program stay the same. It does **not** mean new *variable identifier names*, which is the separate Stage-3 "new identifiers" surface test (`a,b` → `left,right`).
- **pass@1**. The fraction of evaluation records for which the model's **single temperature-0.8 sampled** program passes all of that record's hidden tests (see "Sampled decoding" above). One fresh sample is drawn per evaluation record; the fixed observed score is a property of the checkpoint, the sampled outputs, the record weights, the tests, and the decoding settings — not just of the dataset.
- **Primitive**. A single atom in the *generator's* operation set — e.g. `add`, `abs_of`, `list_sum`, `max_of`. It is an **atomic generator entry**, not a structurally indivisible program: a "primitive" operation's reference program may itself contain sub-expressions (for example the pilot's `cond_abs_max` computes a max of absolute values and is genuinely composite). When we say the model trained on "primitives only," we mean it trained on the *named generator operations* as atomic teacher tasks, not that each reference program was syntactically indivisible. See the operation dictionary in Appendix C (the experiment registry) for which entries are composite.
- **Record**. One generated task instance: a semantic record rendered into one prompt plus its own hidden tests, with its own `task_id` and its own `split`. The record is the book's default counting unit — but a record is not a *unique prompt*: many records can carry one prompt string, and a record can be new while its prompt is not (the pilot's test records are new records under reused prompts). A count of records is therefore evidence about records only.
- **Sandbox / Gate A**. The software layer that runs generated programs and rejects any that use a construct outside an allowlist (e.g. `import`, `eval`), before they run.
- **Semantic comparator**. The rule that decides whether an output equals an expected value. Beyond Python's `==`, it adds float tolerance and strict bool/int handling.
- **Surface / surface form**. The exact wording and identifier names of a

request, as opposed to its underlying meaning.

- **Train/val/test split**. The division of a dataset into the examples used to train, to monitor training, and to evaluate (held out). In this book the definition of "held out" varies by split: the **pilot** split reuses the same 21 prompt strings in train/val/test (the test records differ only in hidden-test *input values*), while the **surface** and **composition** splits keep a genuinely new prompt wording or operation family out of training (train × holdout exact prompt-string overlap is reported as 0, per the novelty audit in Appendix C — an audit run on *regenerated* samples and checking exact strings, not wording-family membership). So "held out" in this book is not a single thing: each split's novelty axis (new prompt vs. new input values vs. new operation) is stated explicitly where it matters.
- **Unique prompt**. A distinct prompt *string*, counted once however many records carry it. The pilot's train/val/test reuse the same 21 prompt strings, so its record count and its unique-prompt count are very different numbers; a novelty claim has to say which unit it is counting — record, unique prompt, or held-out family — because these are separate evidence units with separate strength (see "Held-out family" above).
- **Validator / Gate B**. The software layer that sits in front of the model and declines any incoming request that is not in the designed scope, before the model sees it.