

PV ON-GRID STRING INVERTER

SINGLE PHASE INVERTER



RT-G 2~3KW



RT-G 5~6KW

THREE PHASE INVERTER



RT-G 10~40KW



RT-G 50~80KW



RT-G 120KW

RT-G Series three phase -- 3~12KW

Model	RT-G3KW-3P	RT-G4KW-3P	RT-G5KW-3P	RT-G6KW-3P	RT-G8KW-3P	RT-G10KW-3P	RT-G12KW-3P
Input(DC)							
Max.DC Voltage	1100V						
Nominal Voltage	620V						
Start Voltage	250V						
MPPT Voltage Range	140V-1,000V						
Number of MPPT	2						
Strings Per MPPT	1						
Max.Inout Current Per MPPT	15A						
Max.Short-circuit current Per MPPT	20A						
Output(AC)							
Nominal AC Output Power	3000W	4000W	5000W	6000W	8000W	10000W	12000W
Maximum AC Output Power	3300VA	4400VA	5500VA	6600VA	8800VA	11000VA	13200VA
Nominal AC Voltage	400V 3L+N						
AC Grid Frequency Range	50/60Hz(±5Hz)						
Maximum Output Current	4.8A	6.4A	8.0A	9.6A	12.8A	16.0A	19.2A
Power Factor(Φ)	0.8leadng-0.8lagging						
THDi	3%						
Efficiency							
Max.Efficiency	98.4%	98.4%	98.4%	98.4%	98.6%	98.6%	98.6%
Euro Efficiency	97.5%	97.5%	97.5%	97.5%	98.0%	98.1%	98.1%
Protection devices							
DC Switch	Yes						
Output Over Current Protection	Yes						
Anli-Islanding Protection	Yes						
DC Reverse Polanity Protection	Yes						
String Fault Detection	Yes						
DC/AC Surge Protection	DC: Type II /AC:Type III /Type II Optional						
Insulation Detection	Yes						
AC Short Circuit Protection	Yes						
General Specifications							
Dimensions WxHxD	380x483x161mm						
Weight	<17kg						
Operating Temperature Range	-25°C~+60°C						
Cooling Type	Natural cooling						
Max.Operating Altitude	4000m						
Max.Operating Humidity	0-100%(No condensation)						
AC Output Terminal Type	Connector						
IP Class	IP66						
Topology	Transformer-less						
Communication	RS485/Wif/4G						
Display	LCD						
Certification&Standard	EN/IEC62109-1/2;IEC/EN61000-6-2;EC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727;EN50549-1;AS 4777.2;DE-AR-N-4105;VDE0126-1-1;CE10-21;G98;G99;C10/C11;NB/T32004-2018;GB/T19964-2012						

*Specifications subject to change without prior notice.
1. Minimum voltage for inverter to start power output.

RT-G Series three phase -- 15~25KW

Model	RT-G15KW-3P		RT-G17KW-3P		RT-G20KW-3P		RT-G25KW-3P	
Input(DC)								
Max.DC Voltage	1100V							
Nominal Voltage	620V							
Start Voltage	250V							
MPPT Voltage Range	140V-1,000V							
Number of MPPT	2		2		2		2	
Strings Per MPPT	2/1		2		2		2	
Max.Inout Current Per MPPT	30A/15A		30A		30A		30A	
Max.Short-circuit current Per MPPT	40A/20A		40A		40A		40A	
Output(AC)								
Nominal AC Output Power	15000W		17000W		20000W		25000W	
Maximum AC Output Power	16500VA		18700VA		22000VA		27500VA	
Nominal AC Voltage	400V 3L+N							
AC Grid Frequency Range	50/60Hz(±5Hz)							
Maximum Output Current	23.9A		27.1A		31.9A		39.9A	
Power Factor(Φ)	0.8leadng-0.8lagging							
THDi	3%							
Efficiency								
Max.Efficiency	98.6%		98.6%		98.6%		98.6%	
Euro Efficiency	98.2%		98.3%		98.3%		98.3%	
Protection devices								
DC Switch	Yes							
Output Over Current Protection	Yes							
Anli-Islanding Protection	Yes							
DC Reverse Polanity Protection	Yes							
String Fault Detection	Yes							
DC/AC Surge Protection	DC: Type II /AC:Type III /Type II Optional							
Insulation Detection	Yes							
AC Short Circuit Protection	Yes							
General Specifications								
Dimensions WxHxD	380x483x193mm							
Weight	20.7kg							
Operating Temperature Range	-25°C~-+60°C							
Cooling Type	Fan cooling							
Max.Operating Altitude	4000m							
Max.Operating Humidity	0-100%(No condensation)							
AC Output Terminal Type	Connector							
IP Class	IP66							
Topology	Transformer-less							
Communication	RS485/Wif/4G							
Display	LCD							
Certification&Standard	EN/IEC62109-1/2;IEC/EN61000-6-2;EC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727;EN50549-1;AS 4777.2;DE-AR-N-4105;VDE0126-1-1;CE10-21;G98;G99;C10/C11;NB/T32004-2018;GB/T19964-2012							

*Specifications subject to change without prior notice.
1. Minimum voltage for inverter to start power output.



RT-G Series three phase -- 30~40KW

Model	RT-G30KW-3P		RT-G40KW-3P	
Input(DC)				
Max.DC Voltage	1100V			
Nominal Voltage	620V			
Start Voltage	250V			
MPPT Voltage Range	200V-1,000V			
Number of MPPT	3	3		
Strings Per MPPT	2	2		
Max.Inout Current Per MPPT	30A	30A		
Max.Short-circuit current Per MPPT	40A	40A		
Output(AC)				
Nominal AC Output Power	30000W	40000W		
Maximum AC Output Power	33000VA	44000VA		
Nominal AC Voltage	400V 3L+N			
AC Grid Frequency Range	50/60Hz(±5Hz)			
Maximum Output Current	47.8A	63.8A		
Power Factor(Φ)	0.8leadng-0.8lagging			
THDi	3%			
Efficiency				
Max.Efficiency	98.7%	98.7%		
Euro Efficiency	98.4%	98.4%		
Protection devices				
DC Switch	Yes			
Output Over Current Protection	Yes			
Anli-Islanding Protection	Yes			
DC Reverse Polanity Protection	Yes			
String Fault Detection	Yes			
DC/AC Surge Protection	DC: Type II /AC:Type III /Type II Optional			
Insulation Detection	Yes			
AC Short Circuit Protection	Yes			
General Specifications				
Dimensions WxHxD	380*483*223mm	380*483*227mm		
Weight	25.5kg	32.5kg		
Operating Temperature Range	-25°C~+60°C			
Cooling Type	Fan cooling			
Max.Operating Altitude	4000m			
Max.Operating Humidity	0-100%(No condensation)			
AC Output Terminal Type	Connector			
IP Class	IP66			
Topology	Transformer-less			
Communication	RS485/Wif/4G			
Display	LCD			
Certification&Standard	EN/IEC62109-1/2;IEC/EN61000-6-2;EC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727;EN50549-1;AS 4777.2;DE-AR-N-4105;VDE0126-1-1;CE10-21;G98;G99;C10/C11;NB/T32004-2018;GB/T19964-2012			

*Specifications subject to change without prior notice.
1. Minimum voltage for inverter to start power output.



RT-G Series three phase -- 50~80KW



Model	RT-G50KW-3P		RT-G60KW-3P		RT-G70KW-3P		RT-G80KW-3P	
Input(DC)								
Max.DC Voltage	1100V							
Nominal Voltage	620V							
Start Voltage	180V							
MPPT Voltage Range	200V-1,000V							
Number of MPPT	4		4		4		4	
Strings Per MPPT	2		2		3		3	
Max.Inout Current Per MPPT	32A		32A		45A		45A	
Max.Short-circuit current Per MPPT	48A		48A		60A		60A	
Output(AC)								
Nominal AC Output Power	50000W		60000W		70000W		80000W	
Maximum AC Output Power	55000VA		66000VA		77000VA		88000VA	
Nominal AC Voltage	400V 3L+N+PE							
AC Grid Frequency Range	50/60Hz(±5Hz)							
Maximum Output Current	79.7A		95.6A		111.6A		127.5A	
Power Factor(Φ)	0.8leadng-0.8lagging							
THDi	3%							
Efficiency								
Max.Efficiency	98.5%		98.5%		98.6%		98.6%	
Euro Efficiency	98.2%		98.2%		98.3%		98.3%	
Protection devices								
DC Switch	Yes							
Output Over Current Protection	Yes							
Anli-Islanding Protection	Yes							
DC Reverse Polarity Protection	Yes							
String Fault Detection	Yes							
DC/AC Surge Protection	Type II							
Insulation Detection	Yes							
AC Short Circuit Protection	Yes							
General Specifications								
Dimensions WxHxD	515x585x287mm							
Weight	51/55kg							
Operating Temperature Range	-25°C~-+60°C							
Cooling Type	Fan cooling							
Max.Operating Altitude	4000m							
Max.Operating Humidity	0-100%(No condensation)							
AC Output Terminal Type	OT Terminal							
IP Class	IP66							
Topology	Transformer-less							
Communication	RS485/Wif/4G							
Display	LCD							
Certification&Standard	EN/IEC62109-1/2;IEC/EN61000-6-2;EC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727;EN50549-1;AS 4777.2;DE-AR-N-4105;VDE0126-1-1;CE10-21;G98;G99;C10/C11;NB/T32004-2018;GB/T19964-2012							

*Specifications subject to change without prior notice.
1. Minimum voltage for inverter to start power output.

RT-G Series three phase -- 120KW



Model	RT-120CL-MO
Input(DC)	
Max.DC Voltage	1100V
Nominal Voltage	620V
Start Voltage	250V
MPPT Voltage Range	200V-1,000V
Number of MPPT	10
Strings Per MPPT	2
Max.Inout Current Per MPPT	30A
Max.Short-circuit current Per MPPT	50A
Output(AC)	
Nominal AC Output Power	120kW@30°C/110kW@40°C/100kW@50°C
Maximum AC Output Power	121kVA
Nominal AC Voltage	400V 3W+N-PE
AC Grid Frequency Range	50/60Hz(±5Hz)
Maximum Output Current	174.6A
Power Factor(Φ)	0.8leadng-0.8lagging
THDi	3%
Efficiency	
Max.Efficiency	98.7%
Euro Efficiency	98.3%
Protection devices	
DC Switch	Yes
Output Over Current Protection	Yes
Anli-Islanding Protection	Yes
DC Reverse Polarity Protection	Yes
String Fault Detection	Yes
DC/AC Surge Protection	Type II
Insulation Detection	Yes
AC Short Circuit Protection	Yes
General Specifications	
Dimensions WxHxD	1055*700*336mm
Weight	93kg
Operating Temperature Range	-25°C~+60°C
Cooling Type	Fan cooling
Max.Operating Altitude	4000m
Max.Operating Humidity	0-100%(No condensation)
AC Output Terminal Type	Connector
IP Class	IP66
Topology	Transformer-less
Communication	RS485/Wif/4G
Display	LCD
Certification&Standard	EN/IEC62109-1/2;IEC/EN61000-6-2;EC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727;EN50549-1;AS 4777.2;DE-AR-N-4105;VDE0126-1-1;CE10-21;G98;G99;C10/C11;NB/T32004-2018;GB/T19964-2012

*Specifications subject to change without prior notice.
1. Minimum voltage for inverter to start power output.