



>>> Features

- Pure sine wave solar inverter(on/off Grid)Output power factor 1.0
- WIFI&GPRS available for IOS and Android
- Inverter running without battery
- One-key restoration to factory Settings
- Built-in Lithium battery automatic activation
- Built-in 120A(for 3.6KW/6.2KW)
- MPPT:Max 6200W(for 3.6KW),Max 4200W(for 4.2KW),Max 6500W(for 6.2KW)solar charge
- High PV input voltage range(60~450VDC)
- Built-in anti-dusk kit for harsh environment
- Smart battery charge design to optimize battery life
- Dual output

»» Product Data Sheet

MODEL	RT-HY 3.6KW		RT-HY 4.2KW		RT-HY 6.2KW	
Maximum PV Input Power	6200W		6200W		6500W	
Rated Output Power	3600W		4200W		6200W	
Maximum Solar Charging Current	120A		120A		120A	
GRID-TIE OPERATION						
PV Input(DC)						
Nominal DC Voltage/Maximum DC Voltage	360VDC/500VDC					
Start-up Voltage/Initial Feeding Voltage	90VDC/120VDC					
Maximum DC Voltage	60~450VDC					
Number of MPPT Trackers/Maximum Input Current	1/27A					
GRID OUTPUT(AC)						
Nominal Output Voltage	220/230/240VAC					
Output Voltage Range	195.5~253VAC					
Nominal Output Current	15.7A		18.2A		27.0A	
Power Factor	>0.99					
Feed-in Grid Frequency Range	49~51±1Hz					
EFFICIENCY						
Maximum Conversion Efficiency(Solar to AC)	98 %					
TWO LOAD OUTPUT POWER(V2.0)						
Full Load	3600W		4200W		6200W	
Maximum Main Load	3600W		4200W		6200W	
Maximum Second Load(battery mode)	1200W		1400W		2067W	
Main Load Cut Off Voltage	22VDC		22VDC		44VDC	
Main Load Return Voltage	27VDC		24VDC		54VDC	
OFF-GRID OPERATION						
AC INPUT						
AC Start-up Voltage/Auto Restart Voltage	120-140VAC/180VAC					
Acceptable Input Voltage Range	90-280VAC or 170-280VAC					
Maximum AC Input Current	30A		30A		40A	
Nominal operating frequency	50/60Hz					
Surge power	7200W		8400W		12400 W	
BATTERY MODE OUTPUT(AC)						
Nominal Output Voltage	220/230/240VAC					
Output Waveform	Pure sine wave					
Efficiency(DC to AC)	94%					
BATTERY & CHARGER						
Nominal DC Voltage	24VDC		24VDC		48VDC	
Maximum Charging Current (Solar to AC)	120A					
Maximum AC Charging Current	100A					
GENERAL						
PHYSICAL						
Dimension,D x W x H(mm)	440*355*115					
Cartoon Dimension,D X W XH(mm)	505*420*190					
Dimensions of mounting holes(mm)	185-Ø 5x2					
Net Weight(kgs)	7.2		7.8		8.6	
Gross Weight(kgs)	8.3		8.9		9.7	
INTERFACE						
Communication Port	RS232/ WIFI/GPRS					
ENVIRONMENT						
Operating Temperature	-10 ~50℃					

