

Solar Home Refrigerator

BC-50

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	5 L
Temperature range	1~10 for fridge, <=-18 for freezer
Product size(mm)	480*445*500
Carton size(mm)	500*465*530
Loading qty in 40HQ	573
G.W(KG)/N.W(KG)	12/10
Refrigerant	R134A/R600A

BC-70

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	6 L
Temperature range	1~10 for fridge, <=-18 for freezer
Product size(mm)	450*405*845
Carton size(mm)	465*425*870
Loading qty in 40HQ	414
G.W(KG)/N.W(KG)	17/15
Refrigerant	R134A/R600A

BC-90

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	8 L
Temperature range	1~10 for fridge, <=-18 for freezer
Product size(mm)	480*445*845
Carton size(mm)	500*465*870
Loading qty in 40HQ	352
G.W(KG)/N.W(KG)	22/20
Refrigerant	R134A/R600A

BCD-108

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	41 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	450*460*1250
Carton size(mm)	465*480*1305
Loading qty in 40HQ	240
G.W(N.W)(KG)	32/29
Refrigerant	R134A/R600A

BCD-118

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	39 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	480*490*1105
Carton size(mm)	500*540*1160
Loading qty in 40HQ	184
G.W(KG)/N.W(KG)	31/28
Refrigerant	R134A/R600A

BCD-142

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	39 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	480*490*1265
Carton size(mm)	500*540*1320
Loading qty in 40HQ	184
G.W(KG)/N.W(KG)	35/32
Refrigerant	R134A/R600A

BCD-178

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	39 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	500*565*1290
Carton size(mm)	535*620*1340
Loading qty in 40HQ	160
G.W(KG)/N.W(KG)	41/37
Refrigerant	R134A/R600A

BCD-198

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	80 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	520*550*1515
Carton size(mm)	560*600*1550
Loading qty in 40HQ	136
G.W(KG)/N.W(KG)	47/42
Refrigerant	R134A/R600A

Solar Home Refrigerator

BCD-218

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	45 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	550*575*1390
Carton size(mm)	570*605*1450
Loading qty in 40HQ	142
G.W(KG)/N.W(KG)	45/40
Refrigerant	R134A/R600a

BCD-268

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	55 L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	550*570*1619
Carton size(mm)	570*600*1680
Loading qty in 40HQ	106
G.W(KG)/N.W(KG)	50/45
Refrigerant	R134A/R600A

BCD-168

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	57L
Temperature range	0-10 for fridge, <=-18 for freezer
Product size(mm)	500*560*1300
Carton size(mm)	535*620*1340
Loading qty in 40HQ	160
G.W(KG)/N.W(KG)	45/42
Refrigerant	R134A/600A

BCD-270

Input voltage(V)	12V/24V/220V
Capacity (freezer room)	124L
Temperature range	0-10 for fridge, <=-18 for freezer
Production sizs(mm)	580*590*1660
Carton Size (mm)	630*635*1720
Loading qty in 40HQ	77
G.W(KG)/N.W(KG)	56/61
Refrigerant	R134A /600A

BCD-288

Input voltage(V)	12V/24V/220V
Capacity (freezer room)	75L
Temperature range	0-10 for fridge, <=-18 for freezer
Production sizs(mm)	606*680*1520
Carton Size (mm)	625*735*1575
Loading qty in 40HQ	79
G.W(KG)/N.W(KG)	60/54
Refrigerant	600A

BCD-298

Input voltage(V)	12V/24V/220V
Capacity (freezer room)	68L
Temperature range	0-10 for fridge, <=-18 for freezer
Production sizs(mm)	595*695*1525
Carton Size (mm)	625*705*1575
Loading qty in 40HQ	92
G.W(KG)/N.W(KG)	64/60
Refrigerant	600A

BCD-338

Input voltage(V)	12V/24V/220V
Capacity (freezer room)	96L
Temperature range	0-10 for fridge, <=-18 for freezer
Production sizs(mm)	595*695*1855
Carton Size (mm)	650*735*1950
Loading qty in 40HQ	72
G.W(KG)/N.W(KG)	75/65
Refrigerant	600A

85 mm ThicknessFoaming Body Solar Chest Freezer with Curved Glass Door for Ice Cream

SD/SC-168Y

Capacity (litre)	168
Temp Control	mechanical
Voltage (v)	12V/24V220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R134a
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	730*700*826MM
Packing Dimension(W*D*H)MM	785*755*882MM
G.W(KG)/N.W(KG)	38/35
Temperature	≤-18℃
Qty/40HQ	132

SD/SC-308Y

Capacity (litre)	308
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R290
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1250*700*840MM
Packing Dimension(W*D*H)MM	1305*755*882MM
G.W(KG)/N.W(KG)	70/65
Temperature	≤-18℃
Qty/40HQ	81

SD/SC-368Y

Capacity (litre)	368
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R290
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1410*700*840MM
Packing Dimension(W*D*H)MM	1460*780*900MM
G.W(KG)/N.W(KG)	73/68
Temperature	≤-18℃
Qty/40HQ	72

SD/SC-468Y

Capacity (litre)	468
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R134a
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1630*700*840MM
Packing Dimension(W*D*H)MM	1685*755*882MM
G.W(KG)/N.W(KG)	81/75
Temperature	≤-18℃
Qty/40HQ	63

SD/SC-618Y

Capacity (litre)	618
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R290
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1780*700*900MM
Packing Dimension(W*D*H)MM	1835*755*945MM
G.W(KG)/N.W(KG)	95/89
Temperature	≤-18℃
Qty/40HQ	50

SD/SC-268Y

Capacity (litre)	268
Temp Control	mechanical
Voltage (v)	12V/24V220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R290
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1041*700*840MM
Packing Dimension(W*D*H)MM	1096*755*882MM
G.W(KG)/N.W(KG)	61/57
Temperature	≤-18℃
Qty/40HQ	94



SD/SC-408Y

Capacity (litre)	408
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R134a
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1520*700*840MM
Packing Dimension(W*D*H)MM	1575*755*882MM
G.W(KG)/N.W(KG)	78/72
Temperature	≤-18℃
Qty/40HQ	66

SD/SC-508Y

Capacity (litre)	508
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R134a
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	1780*700*840MM
Packing Dimension(W*D*H)MM	1835*755*882MM
G.W(KG)/N.W(KG)	86/80
Temperature	≤-18℃
Qty/40HQ	57

SD/SC-718Y

Capacity (litre)	718
Temp Control	mechanical
Voltage (v)	24V/220V50Hz
Basket	one
Isolation Thickness	85mm
Refrigerant	R290
Wheel	4
Color of Door Frame	white
Key and Lock	Yes
Glass	4mm
Outside Condenser	Yes
Paper sticker	Optional
Fan cooling Compressor	Yes
Unit Dimension(W*D*H)MM	2000*700*900MM
Packing Dimension(W*D*H)MM	2055*755*945
G.W(KG)/N.W(KG)	105/99
Temperature	≤-18℃
Qty/40HQ	45

110 mm ThicknessFoaming Body Solar Chest Freezer- Super Energy Save

BD/BC-68H

Power consumption	37W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	68 Litre	Thermostat	mechanical
Product size(mm)	670*661*640	Colour	white
Carton size(mm)	710*681*682	Defrost	manual
G.W(KG)/N.W(KG)	35/30	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	153



BD/BC-88H

Power consumption	39W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	88 Litre	Thermostat	mechanical
Product size(mm)	840*661*640	Colour	white
Carton size(mm)	880*681*682	Defrost	manual
G.W(KG)/N.W(KG)	34/38	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	132

BD/BC-108H

Power consumption	47W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	108 Litre	Thermostat	mechanical
Product size(mm)	670*661*840	Colour	white
Carton size(mm)	710*681*882	Defrost	manual
G.W(KG)/N.W(KG)	41/36	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	153

BD/BC-158H

Power consumption	49W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	158 Litre	Thermostat	mechanical
Product size(mm)	840*661*840	Colour	white
Carton size(mm)	880*681*882	Defrost	manual
G.W(KG)/N.W(KG)	45/41	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	132

BD/BC-208H

Power consumption	68W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	208 Litre	Thermostat	mechanical
Product size(mm)	996*661*840	Colour	white
Carton size(mm)	1036*681*882	Defrost	manual
G.W(KG)/N.W(KG)	52/47	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	123

BD/BC-258H

Power consumption	78W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	258 Litre	Thermostat	mechanical
Product size(mm)	1038*745*840	Colour	white
Carton size(mm)	1078*765*882	Defrost	manual
G.W(KG)/N.W(KG)	55/50	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	99

BD/BC-308H

Power consumption	95W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	308 Litre	Thermostat	mechanical
Product size(mm)	1196*745*840	Colour	white
Carton size(mm)	1236*765*882	Defrost	manual
G.W(KG)/N.W(KG)	61/56	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	90

BD/BC-358H

Power consumption	105W	Inner' light	optional
Input voltage(w)	DC12V/24V	Basket/pcs	1
capacity	358 Litre	Thermostat	mechanical
Product size(mm)	1380*745*840	Colour	white
Carton size(mm)	1420*765*882	Defrost	manual
G.W(KG)/N.W(KG)	84/78	Compressor/quantities	1
Temperature range	<=-18 degree	Doors/quantities	1
Inner' glass door key& lock	yes	Loading quantity/40HQ	66

BD/BC-408H

Power consumption	110W
Input voltage(w)	DC12V/24V
capacity	408 Litr
Product size(mm)	1566*806*840
Carton size(mm)	1606*815*882
G.W(KG)/N.W(KG)	88/83
Temperature range	<= -18 degree
Inner glass door	yes
key& lock	yes
Inner light	yes
Basket/pcs	1
Thermostat	mechanical
Colour	white
Defrost	manual
Compressor/quantities	1
Doors/quantities	1
Loading quantity/40HQ	52

65mm ThicknessFoaming
Body Solar Chest Freezer

BD/BC-68

Input voltage(w)	DC12V/24V
capacity	68 Litre
Temperature range	<= -18 degree
Product size(mm)	585*555*640
Carton size(mm)	620*580*690
Loading quantity/40HQ	289
G.W(KG)/N.W(KG)	25/23
Refrigerant	R134A/R600A

BD/BC-88

Input voltage(w)	DC12V/24V
capacity	88 Litre
Temperature range	<= -18 degree
Product size(mm)	750*555*640
Carton size(mm)	785*580*690
Loading quantity/40HQ	229
G.W(KG)/N.W(KG)	31/28
Refrigerant	R134A/R600A

BD/BC-108

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	108 Litre
Temperature range	<= -18 degree
Product size(mm)	580*555*840
Carton size(mm)	620*580*885
Loading qty in 40HQ	228
G.W/N.W(KG)	30/27
Refrigerant	R134A/R600A

BD/BC-158

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	158 Litre
Temperature range	<= -18 degree
Product size(mm)	750*555*840
Carton size(mm)	790*580*885
Loading qty in 40HQ	180
G.W/N.W(KG)	35/32
Refrigerant	R134A/R600A

BD/BC-208

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	208 Litre
Temperature range	<= -18 degree
Product size(mm)	906*555*840
Carton size(mm)	946*580*885
Loading qty in 40HQ	148
G.W/N.W(KG)	39/36
Refrigerant	R134A/R600A

BD/BC-258

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	258 Litre
Temperature range	<= -18 degree
Product size(mm)	952*668*840
Carton size(mm)	990*680*855
Loading qty in 40HQ	125
G.W(KG)/N.W(KG)	44/40
Refrigerant	R134A/R600A

BD/BC-308

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	308 Litre
Temperature range	<= -18 degree
Product size(mm)	1110*668*840
Carton size(mm)	1148*670*885
Loading qty in 40HQ	104
G.W(KG)/N.W(KG)	50/47
Refrigerant	R134A/R600A

BD/BC-408

Input voltage(V)	DC12V/24V/220V
Capacity	408Litre
Temperature range	<= -18 degree
Product size(mm)	1410*745*840
Carton size(mm)	1465*755*885
Loading quantity/40HQ	72
G.W(KG)/N.W(KG)	63/60
Refrigerant	R134a/600A

BD/BC-268

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	268 Litre
Temperature range	<= -18 degree
Product size(mm)	1090*585*842
Carton size(mm)	1120*610*880
Loading qty in 40HQ	118
G.W(KG)/N.W(KG)	46/42
Refrigerant	R134A/R600A

BD/BC-358

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	358 Litre
Temperature range	<= -18 degree
Product size(mm)	1294*645*840
Carton size(mm)	1335*665*882
Loading qty in 40HQ	81
G.W(KG)/N.W(KG)	56/52
Refrigerant	R134 A/R600A

BD/BC-508

Input voltage(V)	DC12V/24V
Capacity	508Litre
Temperature range	<= -18 degree
Product size(mm)	1525*675*870
Carton size(mm)	1575*755*885
Loading quantity/40HQ	65
G.W(KG)/N.W(KG)	67/61
Refrigerant	R134A/600A

Double Cabinets Freezer

BCD-258D

Power consumption	80W
Input voltage(w)	12V/24V 220V50Hz
capacity	258 Litre(149Litre FREEZER+ 109Litre FRIDGE)
Product size(mm)	1075*585*840
Carton size(mm)	1120*610*880
G.W(KG)/N.W(KG)	45.8/42
Temperature range	0-10 /<= -18 degree
Inner glass door	yes
key& lock	yes
Inner light	Optional
Basket/pcs	1
Thermostat	Digital
Doors/quantities	2
Loading quantity/40HQ	118

BCD-338D

Power consumption	100W
Input voltage(w)	12V/24V 220V50Hz
capacity	338 Litre(195LitreFREEZER+ 143LitreFRIDGE)
Product size(mm)	1294*645*840
Carton size(mm)	1335*665*882
G.W(KG)/N.W(KG)	71/68
Temperature range	0-10 /<= -18 degree
Inner glass door	yes
key& lock	yes
Inner light	Optional
Basket/pcs	1
Thermostat	Digital
Doors/quantities	2
Loading quantity/40HQ	81

BD/BC-608

Input voltage(V)	DC12V/24V
Capacity	608Litre
Temperature range	<= -18 degree
Product size(mm)	1785*745*834
Carton size(mm)	1835*755*885
Loading quantity/40HQ	56
G.W(KG)/N.W(KG)	76/72
Refrigerant	R134A/600A

BD/BC-708

Input voltage(V)	DC24V
Capacity	708Litre
Temperature range	<= -18 degree
Product size(mm)	1785*795*890
Carton size(mm)	1835*895*965
Loading quantity/40HQ	26
G.W(KG)/N.W(KG)	91/86
Refrigerant	R134a/600A

BD/BC-1088

Input voltage(V)	DC24V
Capacity	1088Litre
Temperature range	<= -18 degree
Product size(mm)	2035*1020*930
Carton size(mm)	2095*1035*1010
Loading quantity/40HQ	22
G.W(KG)/N.W(KG)	130/125
Refrigerant	R134A/600A

BD/BC-1688

Input voltage(V)	DC24V
Capacity	1688Litre
Temperature range	<= -18 degree
Product size(mm)	3175*1025*950
Carton size(mm)	3235*1035*1020
Loading quantity/40HQ	12
N.W./G.W(KG)	176/182
Refrigerant	R134A/600A

BD/BC-658

Input voltage(V)	DC24V
Capacity	658Litre
Temperature range	<= -18 degree
Product size(mm)	1598*885*935
Carton size(mm)	1660*895*1010
Loading quantity/40HQ	28
G.W(KG)/N.W(KG)	87/82
Refrigerant	R134a/600A

BD/BC-798

Input voltage(V)	DC24V
Capacity	798Litre
Temperature range	<= -18 degree
Product size(mm)	1950*885*935
Carton size(mm)	2010*895*1010
Loading quantity/40HQ	24
G.W(KG)/N.W(KG)	112/106
Refrigerant	R134A/600A

BD/BC-1388

Input voltage(V)	DC24V
Capacity	1388Litre
Temperature range	<= -18 degree
Product size(mm)	2335*1025*930
Carton size(mm)	2395*1020*1010
Loading quantity/40HQ	16
G.W(KG)/N.W(KG)	157/152
Refrigerant	R134A/600A

Solar Upright Cooler

LC-138

Input voltage(V)	12V/24V/220V
Capacity	138 Liter
Temperature range	0-10degree
Product size(mm)	500*535*1300
Carton size(mm)	550*585*1340
Loading qty in 40HQ	166
G.W(KG)/N.W(KG)	45/42
Refrigerant	R134A/R600A

LC-188

Input voltage(V)	12V/24V/220V
Capacity	188 Liter
Temperature range	0-10 degree
Product size(mm)	500*535*1655
Carton size(mm)	550*585*1715
Loading qty in 40HQ	111
G.W(KG)/N.W(KG)	53/49
Refrigerant	R134A/R600A

LC-218

Input voltage(V)	12V/24V/220V
Capacity	218 Liter
Temperature range	0-10 degree
Product size(mm)	556*573*1720
Carton size(mm)	625*635*1795
Loading qty in 40HQ	76
G.W(KG)/N.W(KG)	68/55
Refrigerant	R134A/R600A

LC-268

Input voltage(V)	12V/24V/220V
Capacity	268 Liter
Temperature range	0-10 degree
Product size(mm)	556*573*1895
Carton size(mm)	625*645*1970
Loading qty in 40HQ	75
G.W(KG)/N.W(KG)	71/58
Refrigerant	R134A/R600A

LC-328

Input voltage(V)	12V/24V/220V
Capacity	300 Liter
Temperature range	0-10 degree
Product size(mm)	620*573*1895
Carton size(mm)	680*645*1970
Loading qty in 40HQ	72
G.W(KG)/N.W(KG)	75/62
Refrigerant	R134A/R600A

LC-428

Input voltage	24V 220V50hz
Capacity litres	428
Temperature range	0-10 degree
Product Dimension(W*D*H) mm	880*590*2000
Packing Dimension(W*D*H) mm	945*640*2090
G.W(KG)/N.W(KG)	98/89
Refrigerant	R290
Loading qty in 40HQ	43

LC-658

Input voltage	24V 220V50hz
Capacity litres	658
Temperature range	0-10 degree
Product Dimension(W*D*H) mm	1070*590*2000
Packing Dimension(W*D*H) mm	1135*640*2090
G.W(KG)/N.W(KG)	123/110
Refrigerant	R290
Loading qty in 40HQ	36

LC-998

Input voltage	24V 220V50hz
Capacity litres	998
Temperature range	0-10 degree
Product Dimension(W*D*H) mm	1605*590*2000
Packing Dimension(W*D*H) mm	1665*640*2090
G.W(KG)/N.W(KG)	153/140
Refrigerant	R290
Loading qty in 40HQ	25

Solar Ice Maker

BD-198-11



BD-198-7



BD-198-10
ROLL-BOND



BD-198

Input voltage(V)	12V/24V/220V
Capacity(freeze room)	198 L
Temperature range	<= -18 for freezer
Product size(mm)	550*635*1410
Carton size(mm)	570*650*1465
Loading qty in 40HQ	123
G.W(KG)/N.W(KG)	52/49
Refrigerant	R134A/R600A

KF-26GWS

Cooling Capacity	2600W / 0.75ton / 9000BTU
Input Power(W) -Cooling	650~720
Input voltage(V)	DC24V
Rated Current(A)-Cooling	13.5~15
Noise-Indoor-dB(A)	≤39
Noise-Outdoor-dB(A)	≤49
Air Circulation(M3/H)	470
Suitable Area(M2)	11~18
EER-W/W	3.84
EER-Blu/h/w	13.53
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	11/14
Outdoor Unit-Net/Gross(KGS)	33/38
Indoor Unit-Net(mm)	745*255*195
Indoor Unit-Shipping(mm)	780*240*305
Outdoor Unit-Net(mm)	645*245*495
Outdoor Unit-Shipping(mm)	725*320*540

KF-35GWS

Cooling Capacity	3500W / 1ton / 12000BTU
Input Power(W) -Cooling	800~950
Input voltage(V)	DC48V
Rated Current(A)-Cooling	16.7~19.1
Noise-Indoor-dB(A)	≤43
Noise-Outdoor-dB(A)	≤52
Air Circulation(M3/H)	570
Suitable Area(M2)	16~28
EER-W/W	4.23
EER-Blu/h/w	14.08
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	12/15
Outdoor Unit-Net/Gross(KGS)	35/40
Indoor Unit-Net(mm)	775*260*210
Indoor Unit-Shipping(mm)	840*325*265
Outdoor Unit-Net(mm)	790*260*540
Outdoor Unit-Shipping(mm)	910*370*610

KF-50GWS

Cooling Capacity	5000W / 1.5ton / 18000BTU
Input Power(W) -Cooling	890~1000
Input voltage(V)	DC48V
Rated Current(A)-Cooling	18.36~22.1
Noise-Indoor-dB(A)	≤43
Noise-Outdoor-dB(A)	≤52
Air Circulation(M3/H)	1000
Suitable Area(M2)	25~35
EER-W/W	5.38
EER-Blu/h/w	14.13
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	16.3/19.2
Outdoor Unit-Net/Gross(KGS)	63/67
Indoor Unit-Net(mm)	1070*385*265
Indoor Unit-Shipping(mm)	1100*400*285
Outdoor Unit-Net(mm)	850X290X580
Outdoor Unit-Shipping(mm)	995*390*650

KF-70GWS

Cooling Capacity	7000W / 2ton / 24000BTU
Input Power(W) -Cooling	1258~1325
Input voltage(V)	DC48V
Rated Current(A)-Cooling	24.92~26.89
Noise-Indoor-dB(A)	≤43
Noise-Outdoor-dB(A)	≤52
Air Circulation(M3/H)	1200
Suitable Area(M2)	35~45
EER-W/W	5.66
EER-Blu/h/w	14.37
Connecting line specifications	5*1.5mm**3.6m
Power line specifications	3*4mm²
Indoor Unit-Net/Gross(KGS)	20/22
Outdoor Unit-Net/Gross(KGS)	71/77
Indoor Unit-Net(mm)	1070*385*265
Indoor Unit-Shipping(mm)	1100*400*285
Outdoor Unit-Net(mm)	850X290X580
Outdoor Unit-Shipping(mm)	995*390*650