

[illegible]

The diagram shows the RT9013-33GB-MS voltage regulator (U4) in a package. The input pin (VIN) is connected to a 5V source through a 1uF capacitor (C13). The output pin (VOUT) is connected to a 3V3 output through a 100nF capacitor (C12). The ground (GND) and no connection (NC) pins are also shown.

A circuit diagram for LED1. It shows a 3V3 voltage source connected in series with a red LED (LED1) and a resistor R6. The resistor R6 is labeled with a value of 4.7K. The circuit is connected to ground.

3V3 2.54*4

The image displays two pinout diagrams for the Raspberry Pi 4 Model B. The left diagram shows the 3V3 power pins (1-20) and the right diagram shows the 5V power pins (1-20). Both diagrams include pin numbers, pin names, and ground symbols.

3V3 Pinout:

Pin	Pin Name
1	3V3
2	3V3
3	PB14
4	PB15
5	PB12
6	PB13
7	PB10
8	PB11
9	PB1
10	PB0
11	PA7
12	NRST
13	PA6
14	PA5
15	PA4
16	PA3
17	PA2
18	PA1
19	PA0
20	PA0

5V Pinout:

Pin	Pin Name
1	5V
2	5V
3	PA8
4	PA9
5	PA10
6	PA11
7	PA12
8	PA13
9	PA14
10	PA15
11	PB4
12	PB5
13	PB6
14	PB7
15	BOOT0
16	PB8
17	PB9
18	PB10
19	PC13
20	VBA

原理图	Schematic1_1			更新日期	2024-08-02
				创建日期	2024-07-06
图页	P1			物料编码	
绘制	鹿小班	STM32C8T6-MINI			
审阅					
		版本	尺寸	页	1 共 1
		V1.0	A4	鹿小班	