

# 论坛使用接口文档 1.0

[ Base URL: localhost:8080/background\_war\_exploded ]  
[http://localhost:8080/background\\_war\\_exploded/v2/api-docs](http://localhost:8080/background_war_exploded/v2/api-docs)

论坛业务实现接口整合

add-admin-reply-controller

Add Admin Reply Controller



POST

/addNewMessageByAdmin/{adminId}/{messageId}/{messageUserId}

管理员添加信息

Parameters

Try it out

Name	Description
<div><div>adminId * required</div><div>ref</div><div>(path)</div></div>	管理员id
<div><div>messageId * required</div><div>ref</div><div>(path)</div></div>	文章id
<div><div>messageUserId * required</div><div>ref</div><div>(path)</div></div>	文章作者id
<div><div>newMessage * required</div><div></div><div>(body)</div></div>	回复

Example Value

Model

"string"

Parameter content type

application/json

Responses

Response content type

\*/\*

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	0
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

add-collection-controller

Add Collection Controller

▼

POST

/addCollection/{userId}/{messageId}

addCollection

Parameters

Try it out

Name	Description
<b>messageId</b> * required integer(\$int32) (path)	messageId
<b>userId</b> * required integer(\$int32) (path)	userId

Responses

Response content type

\*/\*

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <div><pre>{   "code": 0 }</pre></div>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

POST

/addCollection/checkIsCollection/{userId}/{messageId}

checkIsCollection

Parameters

Try it out

Name	Description
<div><div><b>messageId</b> * required</div><div>integer(\$int32)</div><div>(path)</div></div>	messageId
<div><div><b>userId</b> * required</div><div>integer(\$int32)</div><div>(path)</div></div>	userId

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	0
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

POST

/deleteCollection/{userId}/{messageId}

deleteCollection

Parameters

Try it out

Name	Description
<b>messageId</b> * required integer(\$int32) (path)	messageId
<b>userId</b> * required integer(\$int32) (path)	userId

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	0
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

POST

/getMessage/getAllCollectionMessageByUserId/{userId}/{pageNumber}    getAllCollectionMessageByUserId

Parameters

Try it out

Name	Description
<b>pageNumber</b> * required integer(\$int32) (path)	pageNumber
<b>userId</b> * required integer(\$int32) (path)	userId

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>[   {     "categoryId": 0,     "comments": [       {         "commentCreatTime": "2020-12-22T04:43:40.318Z",         "commentDetail": "string",         "commentId": 0,         "commentReplies": [           {             "commentId": 0,             "commentReplyId": 0,             "commentUserId": 0,             "receiveUserId": 0,             "receiveUserName": "string",             "replayUserId": 0,             "replayUserName": "string",             "replyDetail": "string",             "replyTime": "2020-12-22T04:43:40.318Z"           }         ],         "mangoUser": {           "userAllow": 0,           "userAvatar": "string",           "userCreatTime": "2020-12-22T04:43:40.318Z",           "userGender": 0,</pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

add-comment-controller

Add Comment Controller

▼

POST /addComment/{userId}/{messageId}/{messageUserId} 添加评论	
Parameters	Try it out
Name	Description

Name	Description
<b>messageId</b> * required ref (path)	评论id
<b>messageUserId</b> * required ref (path)	文章作者id
<b>userComment</b> * required (body)	评论内容
<div>Example ValueModel</div> <div>"string"</div>	
<div>Parameter content type</div> <div>application/json</div>	
<b>userId</b> * required ref (path)	用户id
<b>Responses</b>	<div>Response content type</div> <div>*/*</div>

Code	Description
200	<div>OK</div> <div>Example ValueModel</div> <div>{   "code": 0 }</div>
201	<div>Created</div>
401	<div>Unauthorized</div>
403	<div>Forbidden</div>

Code	Description
404	<i>Not Found</i>

add-comment-reply-controller

Add Comment Reply Controller

▼

POST

/addCommentReply/{messageId} 对指定评论进行回复

Parameters

Try it out

Name	Description
mangoCommentReply <i>(body)</i>	回复整合内容  <div><div>Example Value</div><div>Model</div><div>"string"</div></div>
messageId * required string <i>(path)</i>	文章id  <div><div>Parameter content type</div><div>application/json</div></div>

Responses

Response content type

\*/\*

Code	Description
200	<i>OK</i>  <div><div>Example Value</div><div>Model</div><div>{   "code": 0 }</div></div>



Code	Description
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

add-message-detail-controller

Add Message Detail Controller

▼

POST

/addMessage/{userId}

发布文章

Parameters

Try it out

Name	Description
<div><div>mangoMessage</div><div>* required</div><div>(body)</div></div>	<div>文章</div> <div><div>Example Value</div><div>Model</div><div>"string"</div></div> <div><div>Parameter content type</div><div>application/json</div></div>
<div><div>userId</div><div>* required</div><div>string</div><div>(path)</div></div>	<div>用户id</div>

Responses

Response content type

\*/\*

Code	Description

Code	Description
200	<i>OK</i>
201	<b>Example Value</b>
	Model
	<pre>{   "code": 0 }</pre>
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

add-share-count-controller

add Share Count Controller

▼

POST /share/addShareCount/{messageId} 分享文章	
Parameters <div>Try it out</div>	
Name	Description
messageId * required string (path)	文章id
Responses <div>Response content type */*</div>	
Code	Description

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	0
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

delete-by-user-id-controller

Delete By User Id Controller

▼

POST    /deleteMessageById/{userId}/{messageId}    删除指定用户的指定文章文章									
Parameters	Try it out								
<table><tr><th>Name</th><th>Description</th></tr><tr><td><b>messageId</b> * required</td><td rowspan="2">文章id</td></tr><tr><td>string (path)</td></tr><tr><td><b>userId</b> * required</td><td rowspan="2">用户id</td></tr><tr><td>string (path)</td></tr></table>		Name	Description	<b>messageId</b> * required	文章id	string (path)	<b>userId</b> * required	用户id	string (path)
Name	Description								
<b>messageId</b> * required	文章id								
string (path)									
<b>userId</b> * required	用户id								
string (path)									
Responses	Response content type    */*								
<table><tr><th>Code</th><th>Description</th></tr></table>		Code	Description						
Code	Description								

Code	Description
200	<i>OK</i>
201	<b>Example Value</b>
	Model
	<pre>{   "code": 0 }</pre>
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

delete-comment-by-id-controller

Delete Comment By Id Controller

▼

POST /deleteCommentByCommentId/{userId}/{messageId} 删除指定用户的指定文章															
Parameters	Try it out														
<table><tr><th>Name</th><th>Description</th></tr><tr><td><b>messageId</b> * required</td><td></td></tr><tr><td>string</td><td>文章id</td></tr><tr><td>(path)</td><td></td></tr><tr><td><b>userId</b> * required</td><td></td></tr><tr><td>string</td><td>用户id</td></tr><tr><td>(path)</td><td></td></tr></table>		Name	Description	<b>messageId</b> * required		string	文章id	(path)		<b>userId</b> * required		string	用户id	(path)	
Name	Description														
<b>messageId</b> * required															
string	文章id														
(path)															
<b>userId</b> * required															
string	用户id														
(path)															
Responses	Response content type */*														
<table><tr><th>Code</th><th>Description</th></tr></table>		Code	Description												
Code	Description														

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	0
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

POST

/deleteCommentReplyByCommentId/{userId}/{commentReplyId}    删除指定评论的评论回复

Parameters

Try it out

Name	Description
<b>commentReplyId</b> * required string (path)	指定评论的回复评论的id
<b>userId</b> * required string (path)	用户id

Responses

Response content type

\*/\*

Code	Description

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	0
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

get-attend-message-controller

Get Attend Message Controller

▼

POST

/getMessage/getAttendMessageByUserId/{userId}/{pageNumber}    分页获取用户发布文章(非匿名发布)

Parameters

Try it out

Name	Description
<div><b>pageNumber</b> * required</div> <div>string</div> <div>(path)</div>	页号
<div><b>userId</b> * required</div> <div>string</div> <div>(path)</div>	用户id

Responses

Response content type

\*/\*

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>[   {     "categoryId": 0,     "comments": [       {         "commentCreatTime": "2020-12-22T04:43:40.330Z",         "commentDetail": "string",         "commentId": 0,         "commentReplies": [           {             "commentId": 0,             "commentReplyId": 0,             "commentUserId": 0,             "receiveUserId": 0,             "receiveUserName": "string",             "replayUserId": 0,             "replayUserName": "string",             "replyDetail": "string",             "replyTime": "2020-12-22T04:43:40.330Z"           }         ],         "mangoUser": {           "userAllow": 0,           "userAvatar": "string",           "userCreatTime": "2020-12-22T04:43:40.330Z",           "userGender": 0, </pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

get-category-message-controller

Get Category Message Controller

▼

POST

/getMessage/getAllCategoryMessage 获取分类信息

Parameters

Try it out

No parameters

Responses

Response content type

\*/\*

Code	Description
200	<i>OK</i>
	<b>Example Value</b> <b>Model</b>
	<pre>[   {     "categoryId": 0,     "categoryImage": "string",     "categoryName": "string"   } ]</pre>
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

get-lost-message-controller

Get Lost Message Controller

▼

POST

/getMessage/getLostMessage

获取失物招领文章

Parameters

Try it out

No parameters

Responses

Response content type

\*/\*

Code	Description
------	-------------



Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>{  "categoryId": 0,  "comments": [    {      "commentCreateTime": "2020-12-22T04:43:40.332Z",      "commentDetail": "string",      "commentId": 0,      "commentReplies": [        {          "commentId": 0,          "commentReplyId": 0,          "commentUserId": 0,          "receiveUserId": 0,          "receiveUserName": "string",          "replyUserId": 0,          "replyUserName": "string",          "replyDetail": "string",          "replyTime": "2020-12-22T04:43:40.332Z"        }      ]    },    "mangoUser": {      "userAllow": 0,      "userAvatar": "string",      "userCreateTime": "2020-12-22T04:43:40.332Z",      "userGender": 0,      "userId": 0,</pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>
<div><div>get-message-detail-controller</div><div>Get Message Detail Controller</div><div>▼</div></div>	

POST	/getMessage/getAllMessageDetail/{categoryId}/{pageNumber}	获取该分类某页内的所有文章
------	---	---------------

Parameters	Try it out
------------	------------

Name	Description
<b>categoryId</b> * required	
string	分类id
(path)	

Name		Description
<b>pageNumber</b> * required		页号
string (path)		
Responses		Response content type */*
Code	Description	
200	OK	
	Example Value	Model
	<pre>[   {     "categoryId": 0,     "comments": [       {         "commentCreatTime": "2020-12-22T04:43:40.336Z",         "commentDetail": "string",         "commentId": 0,         "commentReplies": [           {             "commentId": 0,             "commentReplyId": 0,             "commentUserId": 0,             "receiveUserId": 0,             "receiveUserName": "string",             "replayUserId": 0,             "replayUserName": "string",             "replyDetail": "string",             "replyTime": "2020-12-22T04:43:40.336Z"           }         ],         "mangoUser": {           "userAllow": 0,           "userAvatar": "string",           "userCreatTime": "2020-12-22T04:43:40.336Z",           "userGender": 0,</pre>	
201	Created	
401	Unauthorized	
403	Forbidden	
404	Not Found	

POST	/getMessage/getAllMessageDetail/{pageNumber}	获取指定页内文章内容
------	--	------------

Name	Description
------	-------------

<b>pageNumber</b> * required	页号
string	
(path)	

Responses	Response content type
-----------	-----------------------

\*/\*

Code	Description
------	-------------

200	OK
-----	----

Example Value    Model

```
[
  {
    "categoryId": 0,
    "comments": [
      {
        "commentCreatTime": "2020-12-22T04:43:40.338Z",
        "commentDetail": "string",
        "commentId": 0,
        "commentReplies": [
          {
            "commentId": 0,
            "commentReplyId": 0,
            "commentUserId": 0,
            "receiveUserId": 0,
            "receiveUserName": "string",
            "replayUserId": 0,
            "replayUserName": "string",
            "replyDetail": "string",
            "replyTime": "2020-12-22T04:43:40.338Z"
          }
        ],
        "mangoUser": {
          "userAllow": 0,
          "userAvatar": "string",
          "userCreatTime": "2020-12-22T04:43:40.338Z",
          "userGender": 0,
```

201	Created
-----	---------

401	Unauthorized
-----	--------------

403	Forbidden
-----	-----------

Code	Description
404	<i>Not Found</i>

POST

/getMessage/getMessageDetailByUserId/{userId}/{pageNumber} 获取用户的该页内的所有文章

## Parameters

## Try it out

Name	Description
<b>pageNumber</b> * required string (path)	页号
<b>userId</b> * required string (path)	用户id

## Responses

### Response content type

***\*/***

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>[   {     "categoryId": 0,     "comments": [       {         "commentCreatTime": "2020-12-22T04:43:40.341Z",         "commentDetail": "string",         "commentId": 0,         "commentReplies": [           {             "commentId": 0,             "commentReplyId": 0,             "commentUserId": 0,             "receiveUserId": 0,             "receiveUserName": "string",             "replayUserId": 0,             "replayUserName": "string",             "replyDetail": "string",             "replyTime": "2020-12-22T04:43:40.341Z"           }         ],         "mangoUser": {           "userAllow": 0,           "userAvatar": "string",           "userCreatTime": "2020-12-22T04:43:40.341Z",           "userGender": 0,</pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

POST

/getMessageDetailById/{id} 通过文章id获取文章

Parameters

Try it out

Name	Description
<b>id</b> * required	
string	文章id
(path)	

Responses		Response content type
		*/*
Code	Description	
200	<i>OK</i>	
	<b>Example Value</b>	<b>Model</b>
	<pre>{   "categoryId": 0,   "comments": [     {       "commentCreateTime": "2020-12-22T04:43:40.343Z",       "commentDetail": "string",       "commentId": 0,       "commentReplies": [         {           "commentId": 0,           "commentReplyId": 0,           "commentUserId": 0,           "receiveUserId": 0,           "receiveUserName": "string",           "replayUserId": 0,           "replayUserName": "string",           "replyDetail": "string",           "replyTime": "2020-12-22T04:43:40.343Z"         }       ],       "mangoUser": {         "userAllow": 0,         "userAvatar": "string",         "userCreateTime": "2020-12-22T04:43:40.343Z",         "userGender": 0,         "userId": 0, </pre>	
201	<i>Created</i>	
401	<i>Unauthorized</i>	
403	<i>Forbidden</i>	
<b>get-new-message-controller</b>		Get New Message Controller
404		

<b>POST</b>	/getMessage/getAllNewMessage/{userId}/{pageNumber}	获取新发布的文章
<b>Parameters</b>		<b>Try it out</b>
Name	Description	
<b>pageNumber</b> * required	pageNumber	
integer(\$int32)		
(path)		

Name		Description
<b>userId</b> * required integer(\$int32) (path)		userId
Responses		Response content type */*
Code	Description	
200	OK	
	Example Value	Model
	<pre>[   {     "messageId": 0,     "newMessageDetail": "string",     "newMessageId": 0,     "newMessageTime": "2020-12-22T04:43:40.344Z",     "newMessageType": 0,     "userId": 0   } ]</pre>	
201	Created	
401	Unauthorized	
403	Forbidden	
404	Not Found	

POST /getMessage/getLastNewMessage/{userId} getLastNewMessage

Parameters

Try it out

Name	Description
<b>userId</b> * required integer(\$int32) (path)	userId

Responses		Response content type
		*/*
Code	Description	
200	<i>OK</i>	
	<b>Example Value</b>	Model
	<pre>{   "messageId": 0,   "newMessageDetail": "string",   "newMessageId": 0,   "newMessageTime": "2020-12-22T04:43:40.345Z",   "newMessageType": 0,   "userId": 0 }</pre>	
201	<i>Created</i>	
401	<i>Unauthorized</i>	
403	<i>Forbidden</i>	
404	<i>Not Found</i>	

get-notice-controller

Get Notice Controller

▼

POST

/getMessage/getAllNoticeMessage 获取全部提示信息

Parameters

Try it out

No parameters

Responses

Response content type

\*/\*

Code

Description



Code	Description
200	<i>OK</i>
	<div><div>Example Value</div><div>Model</div><div>[   {     "noticeDetail": "string",     "noticeId": 0   } ]</div></div>
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

get-shop-message-controllerGet Shop Message Controller

✓

# get-shop-message-controller

## Get Shop Message Controller



## POST

/getMessage/getAllShop 获取所有商店信息

## Parameters

## Try it out

## No parameters

## Responses

### Response content type

**\*/\***

Code	Description
------	-------------

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>[   {     "shopAvatar": "string",     "shopBusinesses": [       {         "businessId": 0,         "shopGoodsImage": "string",         "shopGoodsPrice": 0,         "shopGoodsTitle": "string",         "shopId": 0       }     ],     "shopCreateTime": "2020-12-22T04:43:40.347Z",     "shopId": 0,     "shopImages": [       {         "shopDetailId": 0,         "shopId": 0,         "shopImages": "string"       }     ],     "shopIntro": "string",     "shopLatitude": "string",     "shopLongitude": "string",     "shopName": "string",     "shopPhone": "string"   } ]</pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

<div><div>POST</div><div>/getMessage/getShopMessage/{id} 获取指定商店的信息</div></div>	
Parameters	<div>Try it out</div>
Name	Description
<b>id</b> * required	
string (path)	商店id

Responses		Response content type
		*/*
Code	Description	
200	<i>OK</i>	
	Example Value	Model
	<pre>{   "shopAvatar": "string",   "shopBusinesses": [     {       "businessId": 0,       "shopGoodsImage": "string",       "shopGoodsPrice": 0,       "shopGoodsTitle": "string",       "shopId": 0     }   ],   "shopCreateTime": "2020-12-22T04:43:40.348Z",   "shopId": 0,   "shopImages": [     {       "shopDetailId": 0,       "shopId": 0,       "shopImages": "string"     }   ],   "shopIntro": "string",   "shopLatitude": "string",   "shopLongitude": "string",   "shopName": "string",   "shopPhone": "string" }</pre>	
201	<i>Created</i>	
401	<i>Unauthorized</i>	

get-swiper-message-controller

Get Swiper Message Controller

▼

403		
POST	/getMessage/getAllSwiperMessage	获取滚动图片的信息
Parameters		Try it out
No parameters		
Responses		Response content type
		*/*
Code	Description	

Code	Description
200	<i>OK</i>
	<b>Example Value</b> Model
	<pre>[   {     "swiperId": 0,     "swiperImageUrl": "string"   } ]</pre>
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

login-controller

Login Controller

▼

POST	/checkAdmin	验证是否为管理员
------	-------------	----------

Parameters Try it out

## Try it out

Name	Description
id	
string	用户id
(query)	

Responses Response content type \*/\*

## Response content type

**\*/\***

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>[   {     "userAllow": 0,     "userAvatar": "string",     "userCreatTime": "2020-12-22T04:43:40.350Z",     "userGender": 0,     "userId": 0,     "userIsAdmin": 0,     "userNickname": "string",     "userOpenid": "string"   } ]</pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

POST

/Login

获取用户提供的code进行微信验证

Parameters

Try it out

Name	Description
<b>code</b> * required string (query)	code
<b>mangoUser</b> * required (body)	当前登录用户
<div><div>Example Value</div><div>Model</div></div> <div>"string"</div>	
<div>Parameter content type</div> <div>application/json</div>	

Responses		Response content type
		*/*
Code	Description	
200	<i>OK</i>	
	Example Value	Model
	<pre>{   "code": 0,   "userId": 0 }</pre>	
201	<i>Created</i>	
401	<i>Unauthorized</i>	
<b>search-message-controller</b>		Search Message Controller
403		

POST

/search/{categoryId}/{keyword}

通过关键字在分类中搜索文章

Parameters		Try it out
Name	Description	
<b>categoryId</b> * required	分类id	
string (path)		
<b>keyword</b> * required	关键字	
string (path)		

Responses		Response content type
		*/*
Code	Description	

Code	Description
200	<i>OK</i>
<div><div>Example Value</div><div>Model</div></div> <pre>[   {     "categoryId": 0,     "comments": [       {         "commentCreatTime": "2020-12-22T04:43:40.352Z",         "commentDetail": "string",         "commentId": 0,         "commentReplies": [           {             "commentId": 0,             "commentReplyId": 0,             "commentUserId": 0,             "receiveUserId": 0,             "receiveUserName": "string",             "replayUserId": 0,             "replayUserName": "string",             "replyDetail": "string",             "replyTime": "2020-12-22T04:43:40.352Z"           }         ],         "mangoUser": {           "userAllow": 0,           "userAvatar": "string",           "userCreatTime": "2020-12-22T04:43:40.352Z",           "userGender": 0,</pre>	
201	<i>Created</i>
401	<i>Unauthorized</i>
403	<i>Forbidden</i>
404	<i>Not Found</i>

<div><div>POST</div><div>/searchByKeyword/{keyword}/{pageNumber}</div><div>获取搜索关键字的指定页号内的文章</div></div>	
Parameters	<div>Try it out</div>
Name	Description
<b>keyword</b> * required	
string	关键字
(path)	

Name		Description
<b>pageNumber</b> * required		页号
string (path)		
Responses		Response content type */*
Code	Description	
200	<i>OK</i>	
	Example Value	Model
	<pre>[   {     "categoryId": 0,     "comments": [       {         "commentCreateTime": "2020-12-22T04:43:40.354Z",         "commentDetail": "string",         "commentId": 0,         "commentReplies": [           {             "commentId": 0,             "commentReplyId": 0,             "commentUserId": 0,             "receiveUserId": 0,             "receiveUserName": "string",             "replayUserId": 0,             "replayUserName": "string",             "replyDetail": "string",             "replyTime": "2020-12-22T04:43:40.354Z"           }         ],         "mangoUser": {           "userAllow": 0,           "userAvatar": "string",           "userCreateTime": "2020-12-22T04:43:40.354Z",           "userGender": 0, </pre>	
201	<i>Created</i>	
401	<i>Unauthorized</i>	
403	<i>Forbidden</i>	
404	<i>Not Found</i>	
<b>update-message-by-user-id-controller</b>		Update Message By User Id Controller
POST	/updateMessageById/{id}/{messageId} 修改文章	



Name	Description
<b>id</b> * required string (path)	用户id
<b>message</b> * required (body)	文章修改内容
	<div>Example ValueModel</div> <div>"string"</div>
	<div>Parameter content type</div> <div>application/json</div>
<b>messageId</b> * required string (path)	文章id

Responses	Response content type	*/*
-----------	-----------------------	-----

Code	Description
200	<div>OK</div> <div>Example ValueModel</div> <div>{   "code": 0 }</div>
201	<div>Created</div>
401	<div>Unauthorized</div>
403	<div>Forbidden</div>
404	<div>Not Found</div>

Models



```
IsCollect {
  code integer($int32)
}
```

```
IsComment {
  code integer($int32)
}
```

```
IsCommentReply {
  code integer($int32)
}
```

```
IsDelete {
  code integer($int32)
}
```

```
IsLogin {
  code integer($int32)
  userId integer($int32)
}
```

```
IsUpdate {
  code integer($int32)
}
```

```
IsUpload {
  code integer($int32)
}
```

```
MangoCategory    {
    categoryId      integer($int32)
    categoryImage   string
    categoryName    string
}
```

```
MangoComment     {
    commentCreatTime string($date-time)
    commentDetail    string
    commentId        integer($int32)
    commentReplies   [...]
    mangoUser        MangoUser    {...}
    messageId        integer($int32)
    userId           integer($int32)
}
```

```
MangoCommentReply {
    commentId        integer($int32)
    commentReplyId   integer($int32)
    commentUserId    integer($int32)
    receiveUserId    integer($int32)
    receiveUserName  string
    replayUserId     integer($int32)
    replayUserName   string
    replyDetail      string
    replyTime        string($date-time)
}
```

```

MangoMessage {
    categoryId      integer($int32)
    comments        [...]
    mangoUser       MangoUser {
        userAllow      integer($int32)
        userAvatar      string
        userCreateTime  string($date-time)
        userGender       integer($int32)
        userId           integer($int32)
        userIsAdmin      integer($int32)
        userNickname     string
        userOpenid       string
    }

    messageComment    integer($int32)
    messageCreateTime  string($date-time)
    messageDetail      string
    messageId          integer($int32)
    messageImages      [MangoMessageImages {
        imageId         integer($int32)
        imageUrl         string
        messageId        integer($int32)
    }]

    messageShare       integer($int32)
    messageWatch       integer($int32)
    resultImage        [string]

    userId             integer($int32)
    userIdAnonymity    integer($int32)
    userLevel          string
    userMajor          string
    userPhone          string
}

```

```

MangoMessageImages {
    imageId      integer($int32)
    imageUrl     string
    messageId    integer($int32)
}

```

```

MangoNewMessage {
    messageId      integer($int32)
    newMessageDetail string
    newMessageId   integer($int32)
    newMessageTime string($date-time)
    newMessageType  integer($int32)
    userId         integer($int32)
}

```

```

MangoNotice {
    noticeDetail  string
    noticeId      integer($int32)
}

```

```

MangoShop {
    shopAvatar      string
    shopBusinesses  [MangoShopBusiness {
        businessId    integer($int32)
        shopGoodsImage string
        shopGoodsPrice number
        shopGoodsTitle string
        shopId         integer($int32)
    }]
    shopCreatTime   string($date-time)
    shopId          integer($int32)
    shopImages      [MangoShopImages {
        shopDetailId   integer($int32)
        shopId          integer($int32)
        shopImages      string
    }]
    shopIntro       string
    shopLatitude     string
    shopLongitude    string
    shopName         string
    shopPhone        string
}

```

```

MangoShopBusiness {
    businessId    integer($int32)
    shopGoodsImage string
    shopGoodsPrice number
    shopGoodsTitle string
    shopId        integer($int32)
}

```

```

MangoShopImages {
    shopDetailId   integer($int32)
    shopId          integer($int32)
    shopImages      string
}

```

```

MangoSwiper {
    swiperId        integer($int32)
    swiperImageUrl   string
}

```

```

MangoUser {
    userAllow        integer($int32)
    userAvatar       string
    userCreatTime    string($date-time)
    userGender       integer($int32)
    userId           integer($int32)
    userIsAdmin      integer($int32)
    userNickname     string
    userOpenid       string
}

```