



deeplearning.ai

# Case Studies

---

Why look at  
case studies?

# Outline

## Classic networks:

- LeNet-5 ←
- AlexNet ←
- VGG ←

ResNet (152)

Inception




deeplearning.ai

# Case Studies

---

## Classic networks

# LeNet - 5



60K parameters.

$n_H, n_W \downarrow$   $n_C \uparrow$


conv pool conv pool fc fc output

Advanced: sigmoid/tanh ReLU

II, III.

↓

# AlexNet




- Similar to LeNet, but much bigger.

- ReLU

- Multiple GPUs.

- Local Response Normalization (LRN)



~60M parameters




deeplearning.ai

# Case Studies


---

## Residual Networks (ResNets)

# Residual block



"short cut" / skip connection



$$\underline{z^{[l+1]}} = W^{[l+1]} \underline{a^{[l]}} + b^{[l+1]}$$


$$\underline{a^{[l+1]}} = g(\underline{z^{[l+1]}})$$

$$\underline{z^{[l+2]}} = W^{[l+2]} \underline{a^{[l+1]}} + b^{[l+2]}$$


~~$$\underline{a^{[l+2]}} = g(\underline{z^{[l+2]}})$$~~

$$a^{[l+2]} = g(z^{[l+2]} + \underline{a^{[l]}})$$


# Residual Network



Plain



ResNet







deeplearning.ai

# Case Studies


---

Network in Network  
and  $1 \times 1$  convolutions

# Why does a $1 \times 1$ convolution do?

1	2	3	6	5	8
3	5	5	1	3	4
2	1	3	4	9	3
4	7	8	5	7	9
1	5	3	7	4	8
5	4	9	8	3	5

$6 \times 6 \times 1$




$6 \times 6 \times 32$

\*

2

=

32  $\rightarrow$  # filters.  
 $n_c^{[l+1]}$




$1 \times 1 \times 32$

=

ReLU


Network in Network

2	4	6	...		



$6 \times 6 \times \# \text{ filters}$

# Using $1 \times 1$ convolutions






deeplearning.ai

# Case Studies


---

## Inception network motivation

# Motivation for inception network



# The problem of computational cost






deeplearning.ai

# Case Studies

---

## Inception network

# Inception module





# Inception network

