CSE307
Principles of Programming Languages

Instructor: Zhoulai Fu

State University of New York, Korea

Many slides taken from Cornell's CS3110. Thanks!
https://www.cs.cornell.edu/courses/cs3110/2014fa/lecture_notes.php

Plan

- A review exercise

- Algebraic datatype

A review exercise on lists

- Write a function `**all_even**`, of type, int list -> bool, which returns `true` if all the integers in `lst` are even numbers.

ALGEBRAIC DATATYPES

Recall: datatype for days

```
type day = Sun | Mon | Tue | Wed
         | Thu | Fri | Sat
```

One-of type
Each “branch” is a *constructor*

Recall: datatype for option

- type 'a option = None | Some of ‘a
- **None** constructor cannot carry data
- **Some** constructor can carry data

Algebraic datatypes

```
type mytype = TwoInts of int * int
            | Str of string
            | Pizza
```

- A constructor behaves like a function that makes values of the new type (or is a value of the new type):
  - **`TwoInts : int * int -> mytype`**
  - **`Str : string -> mytype`**
  - **`Pizza : mytype`**

Algebraic datatypes (2)

```
type mytype = TwoInts of int * int
            | Str of string
            | Pizza
```

- Any value of type **`mytype`** is made from *one of* the constructors
- The value contains:
  - A "tag" for "which constructor" (e.g., **`TwoInts`**)
  - The corresponding data (e.g., **`(7,9)`**)

Accessing datatypes values with Pattern matching

```
let f (x:mytype) : int =
  match x with
    Pizza -> 3
  | TwoInts(i1,i2) -> i1+i2
  | Str s -> String.length s
```

- One branch per variant
- Each branch
  - extracts the carried data and
  - binds data to variables local to that branch

Pattern matching algebraic datatypes — summary

Syntax:

```
match e0 with
   p1 -> e1
 | p2 -> e2
 | ...
 | pn -> en
```

For now, each *pattern* is a constructor name followed by the right number of variables (i.e., `C` or `C x` or `C (x,y)` or …)

- Syntactically patterns might look like expressions
- But patterns are not expressions
  - OCaml does not evaluate patterns
  - OCaml does determine whether result of `e0` *matches* patterns

Exercise

- Define a type “point”, which is a 2 dimensional point of two floats

- Define a type “shape”, which is a point, a circle, or a rectangle. A circle is a point and a float of radius; a rectangle are two points

- Define a function area : shape -> float

- Define a function center: shape -> point

Solution

```
type point = float * float
type shape =
  | Point of point
  | Circle of point * float (* center and radius *)
  | Rect of point * point (* lower-left and upper-right corners *)

let area = function
  | Point _ -> 0.0
  | Circle (_, r) -> Float.pi *. (r ** 2.0)
  | Rect ((x1, y1), (x2, y2)) ->
      let w = x2 -. x1 in
      let h = y2 -. y1 in
      w *. h

let center = function
  | Point p -> p
  | Circle (p, _) -> p
  | Rect ((x1, y1), (x2, y2)) -> ((x2 +. x1) /. 2.0, (y2 +. y1) /. 2.0)
```

```
type point = float * float
type shape = Point of point | Circle of point * float | Rect of point * point
val area : shape -> float = <fun>
val center : shape -> point = <fun>
```

Lab exercises for syntax

1. **Define a type named point.** The type will represent a point in two-dimensional space with two integer coordinates. With this type definition, you can create 2D points like this: **Point2D (3, 4).**

2. **Double a Point's Coordinates.** Given a point represented as Point2D (x, y), write a function to double its x and y coordinates. The result should be a new point with the coordinates (2 * x, 2 * y).

   - Input: Point2D (3, 4)

   - Output: Point2D (6, 8)

3. **Adding Two Points.** Given two points represented as Point2D (x1, y1) and Point2D (x2, y2), write a function to add their x and y coordinates respectively. The result should be a new point with the coordinates (x1 + x2, y1 + y2).

   - Input: Point2D (1, 2) and Point2D (3, 4)

   - Output: Point2D (4, 6)

4. **String Representation of a Point.** Given a point represented as Point2D (x, y), write a function to convert this point into a string representation in the format "<x, y>".

   - Input: Point2D (5, 6)

   - Output: "<5, 6>"

Lab exercises for recursion

1. Write the function **is_sorted: int list -> bool** to determine if the integers in an int lst are in sorted in ascending order.

2. Write the function **insert_sorted: int -> int list -> int list**, which inserts an integer into a sorted list and preserves the sort-order. No need to check if the input is sorted.

3. Write the **insertion_sort: int list->int list** function, using `insert_sorted` as a helper.