NL2Semantic2SQL: A Cross-Domain Framework for Natural Language to SQL over Geospatial and Enterprise Data Warehouses

Ning Zhou
Beijing SuperMap Software Co., Ltd., Beijing, China
zhouning1@supermap.com

Abstract

Natural language to SQL (text-to-SQL) has advanced rapidly with large language models, yet most existing systems and benchmarks focus on conventional relational databases and provide limited coverage of executable geospatial SQL. Geospatial databases introduce additional challenges, including geometry-aware schema grounding, spatial predicates, coordinate reference systems, and domain-specific operators such as intersection, buffer, area, and distance calculations. At the same time, practical data platforms increasingly require a single interface that can support both geospatial and non-geospatial warehouse queries. In this work, we present **NL2Semantic2SQL**, a cross-domain framework that combines semantic-layer grounding, intent-conditioned routing, schema-aware prompt construction, few-shot retrieval, SQL postprocessing, and execution-time self-correction to support natural-language querying over both GIS and conventional warehouse data. A core design principle is bilingual, cross-domain support: the framework handles both Chinese GIS queries and English warehouse queries through intent-conditioned routing that operates bilingually, recognizing Chinese GIS keywords alongside English warehouse expressions. We evaluate the framework on a 100-question GIS benchmark (expanded from a 20-question pilot) and a $\sim$495-question warehouse benchmark derived from BIRD mini_dev. On the GIS track, we separately report Spatial EX (85 normal spatial-SQL questions) and Robustness Success Rate (15 safety/refusal questions), as these measure fundamentally different capabilities. The full pipeline achieves Spatial EX= 0.682 vs. baseline 0.529 (McNemar $p = 0.0072$, statistically significant at $\alpha = 0.05$, $+0.153$) and Robustness Success Rate= 0.800 vs. baseline 0.333 (McNemar $p = 0.0156$, statistically significant, $+0.467$). On the BIRD track, the full pipeline reaches EX= 0.501 vs. baseline 0.474 ($+0.027$); this is a directional improvement but not statistically significant (McNemar $p = 0.136$). The DIN-SQL comparison on GIS uses the same 100-question benchmark; the full pipeline statistically significantly outperforms DIN-SQL on both Spatial EX ($+0.118$, McNemar $p = 0.0213$) and Robustness ($+0.533$, $p = 0.0078$). On BIRD, the full pipeline (0.501) is numerically higher than DIN-SQL (0.482) but statistically comparable ($p = 0.382$). Token cost is $13.6\times$ on GIS and $7.9\times$ on BIRD (after P2 single-pass optimization), a real deployment consideration especially for warehouse queries where the marginal accuracy gain is statistically inconclusive. These findings demonstrate that semantic grounding with intent-conditioned routing provides statistically significant gains for GIS spatial accuracy and robustness, directional gains for warehouse queries, and that the framework supports both Chinese GIS and English warehouse queries via a unified bilingual routing architecture.

Keywords: text-to-SQL; natural language interface; geospatial database; PostGIS; semantic layer; large language model; cross-domain generalization; cross-lingual evaluation.

1 Introduction

Natural language to SQL has become one of the most active application directions of large language models, because it offers a direct interface between end users and structured data repositories. Recent advances have substantially improved performance on public benchmarks such as Spider [1] and BIRD [6], demonstrating

that modern language models can often synthesize executable SQL from natural-language questions under conventional relational settings. However, most existing text-to-SQL systems and evaluation datasets are designed for general-purpose relational databases, where the principal challenges lie in schema linking, join reasoning, aggregation, and nested query construction. By contrast, real-world geospatial database applications introduce additional semantic and operational complexity that is largely absent from these benchmarks. In geospatial settings, queries frequently involve geometry-aware schema grounding, spatial predicates, coordinate reference systems, topological relations, and spatial measurement operators such as area, distance, intersection, and buffering. These characteristics make geospatial text-to-SQL a substantially different problem rather than a simple extension of general warehouse querying.

This mismatch creates a practical and scientific gap. From a practical perspective, many operational data platforms must serve both geospatial and non-geospatial workloads through a unified natural-language interface. A user may ask one question about land-use overlap, another about building proximity, and a third about tabular business statistics in the same system. From a scientific perspective, however, existing studies rarely examine whether a single semantic grounding architecture can support these heterogeneous query types without severe domain bias. Most prior work either optimizes for conventional warehouse-style SQL generation or focuses on domain-specific geospatial systems without evaluating transferability beyond the GIS context. As a result, it remains unclear which components of a semantic-to-SQL pipeline generalize across domains and which components encode assumptions that are beneficial in one setting but harmful in another.

The challenge is especially pronounced at the grounding stage. In conventional text-to-SQL systems, schema linking is often framed as the task of aligning user expressions with table names, column names, or retrieved schema snippets. In geospatial systems, this step is more complicated because the model must additionally recognize geometry-bearing attributes, infer relevant spatial operators, respect spatial reference transformations, and distinguish between topological, metric, and aggregation-based reasoning. At the same time, aggressive domain-specific grounding strategies can introduce unintended bias when transferred to non-geospatial databases. A system tuned for Chinese GIS terminology, spatial operator hints, and geometry-aware rules may perform strongly on spatial benchmarks while underperforming on English warehouse benchmarks if its semantic retrieval mechanisms fail to adapt to differences in language, schema naming, and operator distributions. Understanding this tension is critical for building robust cross-domain natural-language interfaces to structured data.

To address this problem, we present **NL2Semantic2SQL**, a cross-domain framework that integrates semantic-layer grounding, schema-aware context construction, few-shot retrieval, SQL postprocessing, and execution-time self-correction into a unified natural-language-to-SQL pipeline. A core design principle is bilingual, cross-domain support: the framework handles *both* Chinese GIS queries *and* English warehouse queries through a single architecture. Intent classification operates bilingually, recognizing Chinese GIS keywords (e.g., spatial operator terms, Chinese administrative region names) alongside English warehouse expressions (e.g., "how many", "what is the average", "compare"). This bilingual routing is not an afterthought but a fundamental design choice that enables the same pipeline to serve heterogeneous real-world deployments without language-specific model swapping. Rather than treating SQL generation as a single-step prompting problem, the framework first resolves semantic context, then assembles structured schema evidence, and finally performs constrained SQL generation with post-hoc correction. The design is motivated by the observation that GIS queries and non-GIS warehouse queries share a common need for semantic disambiguation, but differ substantially in the kinds of evidence and constraints that must be surfaced to the model. Our framework therefore aims to preserve a unified architecture while allowing domain-specific grounding signals to be incorporated explicitly rather than implicitly.

To evaluate the geospatial side of the problem, we further construct a pilot GIS-oriented benchmark with execution-based evaluation, spatial-operator coverage, and varying query complexity. The benchmark is designed to capture the characteristics missing from mainstream text-to-SQL datasets, including spatial

selection, overlap analysis, buffering, spatial aggregation, and geometry-sensitive reasoning. We then complement this benchmark with cross-domain evaluation on a warehouse-oriented dataset derived from BIRD mini_dev [6], enabling a direct comparison between GIS and non-GIS scenarios under the same evaluation harness. This dual-track setting allows us to move beyond a simple "does it work?" question and instead ask a more informative scientific question: how does a unified semantic-to-SQL architecture behave when confronted with two structurally different database domains?

Contributions. Our contributions are threefold:

1. We propose a unified **NL2Semantic2SQL framework** for cross-domain querying over geospatial and conventional warehouse databases. The framework provides a single semantic-grounding pipeline that adapts its grounding evidence to the target domain (GIS vs. warehouse) without retraining or model swapping. A core design principle is bilingual support: intent classification operates bilingually, handling Chinese GIS queries and English warehouse queries through the same routing architecture.

2. We construct a **100-question GIS-oriented text-to-SQL benchmark** with four difficulty levels (Easy, Medium, Hard, Robustness) and explicitly separate ordinary spatial-SQL execution (85 questions, Spatial EX) from robustness/safety evaluation (15 questions, Robustness Success Rate), as these measure fundamentally different capabilities. Combined with a $\sim$495-question subset of BIRD mini_dev, this yields a dual-track protocol that is executable, auditable, and useful for cross-domain error analysis.

3. Through cross-domain experiments and comparison against the DIN-SQL external baseline, we show that the full pipeline achieves statistically significant gains on GIS Spatial EX ($+0.153$, McNemar $p = 0.0072$) and GIS Robustness Success Rate ($+0.467$, $p = 0.0156$), and directional but not statistically significant gains on BIRD (EX $+0.027$, $p = 0.136$). The BIRD result should be interpreted as directional evidence, not a confirmed advantage. P2 single-pass mode reduces BIRD token cost from $\sim$32$\times$ to 7.9$\times$ while simultaneously improving EX.

The remainder of this paper is organized as follows. Section 2 reviews related work on text-to-SQL with LLMs, public benchmarks, geospatial NL interfaces, semantic layers, and cross-domain/cross-lingual generalization. Section 3 formalizes the cross-domain text-to-SQL problem and details the proposed three-stage architecture. Section 4 presents the dual-track evaluation, including dataset construction, experimental setup, per-track results, case studies, and reproducibility notes. Section 5 discusses interpretation limits and future work. Section 6 concludes.

2 Related Work

2.1 Text-to-SQL with large language models

The application of large language models to text-to-SQL has progressed rapidly through increasingly sophisticated prompt-engineering strategies. Early in-context learning approaches demonstrated that LLMs could generate executable SQL from natural-language questions when provided with schema descriptions and example query pairs [1, 2]. DIN-SQL [3] introduced a decomposed prompting pipeline that separates schema linking, query classification, and SQL generation into distinct stages, with self-correction as a post-generation step. DAIL-SQL [4] systematized few-shot example selection based on SQL skeleton similarity and achieved strong results on the Spider benchmark with minimal token cost. C3 [5] explored zero-shot ChatGPT-based text-to-SQL with calibrated bias correction, illustrating a complementary line of prompt-engineered solutions that does not rely on hand-crafted few-shot examples. Our framework shares the decomposition philosophy of DIN-SQL but adds an explicit semantic layer as a structured intermediary between the user question and the schema, rather than relying solely on prompt-level schema linking.

2.2 Benchmarks for text-to-SQL

Spider [1] established the standard cross-database text-to-SQL benchmark with execution-based evaluation, introducing the challenge of generalizing across unseen database schemas. BIRD [6] extended this setting to larger, more realistic databases with value-aware evaluation and difficulty stratification, revealing that LLM performance degrades substantially on complex aggregation and multi-hop join queries. Spider 2.0 [7] further expanded the scope to include enterprise-style workflows such as dbt transformations and dialect variations. BEAVER [8] specifically targets enterprise data warehouses with private schemas and complex business logic, showing that state-of-the-art models achieve near-zero accuracy on truly private enterprise data. Our work is motivated by a complementary gap: mainstream text-to-SQL benchmarks (Spider, BIRD, Spider 2.0) provide limited coverage of executable PostGIS-style spatial SQL, geometry-aware schema grounding, and SRID/coordinate-system handling, and none assess cross-domain transfer between GIS and warehouse query semantics in a single evaluation protocol.

2.3 Geospatial natural language interfaces

Natural language interfaces to geospatial databases have a distinct research lineage from general text-to-SQL. Early work on geospatial question answering, such as GeoQuery [9], which used inductive logic programming to learn a parser for geographic database queries, focused on small geographic fact databases. Punjani et al. [10] extended this to template-based question answering over linked geospatial data on the Semantic Web, demonstrating that structured spatial knowledge can be queried via natural language when appropriate ontological mappings are available; their work highlights the importance of spatial predicate coverage and coordinate-system awareness that remains relevant for PostGIS-style SQL generation. More recent work has explored using LLMs for spatial reasoning and geographic knowledge extraction [11], but systematic evaluation of text-to-SQL capabilities over PostGIS or spatially-extended relational databases remains scarce. Until recently, mainstream text-to-SQL benchmarks provided limited coverage of PostGIS-style spatial SQL. GeoSQL-Eval [12] addresses this gap with a comprehensive PostGIS function-level evaluation framework comprising 14,178 tasks across 340 PostGIS functions. Our work differs in focus: while GeoSQL-Eval evaluates individual PostGIS function invocation and syntax correctness, NL2Semantic2SQL targets end-to-end cross-domain query generation with semantic-layer grounding, intent routing, and safety enforcement across both GIS and warehouse domains. Our GIS benchmark is designed to complement this function-level evaluation with end-to-end execution accuracy.

2.4 Semantic layers and schema grounding

The concept of a semantic layer as an intermediary between analytical queries and raw database schemas originates from business-intelligence tools and has been formalized in frameworks such as MetricFlow [13] and dbt's semantic layer. These systems define entities, dimensions, measures, and metrics as declarative metadata that governs how joins and aggregations should be constructed. In the text-to-SQL context, semantic layers offer a principled way to provide LLMs with structured evidence about schema semantics rather than requiring the model to infer join paths and aggregation rules from raw DDL alone. Our framework adapts this concept for cross-domain use, combining GIS-specific annotations (geometry types, SRIDs, spatial operators) with warehouse-style entity-relationship metadata to support both query domains through a unified grounding architecture.

2.5 Cross-domain and cross-lingual text-to-SQL

Cross-domain generalization has been studied primarily through zero-shot transfer across database schemas within the same linguistic and operator domain [1, 6]. Cross-lingual text-to-SQL, where questions are posed

in one language over schemas defined in another, has received less systematic attention, though multilingual benchmarks such as CSpider [14] demonstrate that language mismatch introduces additional schema-linking challenges. Our work extends the cross-domain dimension beyond schema variation to include operator heterogeneity (spatial vs. tabular) and language heterogeneity (Chinese questions over English warehouse schemas), providing a more comprehensive view of the generalization landscape.

3 Method

3.1 Problem formulation

We formulate cross-domain natural language to SQL as the task of translating a user question q into an executable SQL statement s over heterogeneous structured databases that may belong to either geospatial or conventional warehouse domains. Let S denote the executable schema representation extracted from the database catalog, and let E denote semantic-side evidence such as aliases, hierarchy expansions, geometry metadata, value hints, or fact/dimension/entity annotations. The problem can then be written abstractly as

$$\hat{s} = f(q, S, E), \tag{1}$$

where f is implemented by an LLM-conditioned generation pipeline rather than a single end-to-end model. Unlike standard text-to-SQL settings, the target databases in our problem formulation are not assumed to share homogeneous operator semantics. In warehouse-style databases, correct SQL generation primarily depends on schema linking, join reasoning, aggregation, and temporal filtering. In geospatial databases, however, the model must additionally reason about geometry-bearing columns, spatial relations, coordinate systems, and domain-specific operators such as intersection, containment, buffering, and area or distance calculation. The purpose of our framework is therefore not only to generate valid SQL, but also to provide a semantic mediation layer that adapts the grounding process to the structural characteristics of each domain.

3.2 Three-stage pipeline

We design NL2Semantic2SQL as a three-stage pipeline (Figure 1). In the first stage, the system performs semantic resolution over a semantic layer that stores table-level and column-level annotations, aliases, domain hints, and task-relevant metadata. In the second stage, the resolved information is combined with database schema inspection and optional few-shot retrieval to construct a grounded context block for SQL generation. In the third stage, the generated SQL is postprocessed, executed under safety constraints, and, when necessary, revised through an execution-feedback self-correction loop. This decomposition separates semantic interpretation from SQL synthesis, allowing the framework to expose domain-specific evidence to the language model while keeping the final generation step constrained by executable schema information.

3.3 Geospatial-aware grounding

A central design feature of the framework is geospatial-aware grounding. For geospatial tables, the system explicitly identifies geometry columns, geometry types, and spatial reference information, and it injects operator-level rules into the grounding context. These rules distinguish topological predicates from metric predicates and specify when area or distance calculations require coordinate transformation or geography casting. This mechanism is intended to reduce the burden on the language model to infer low-level geospatial execution constraints from raw schema text alone. At the same time, the framework preserves the ability to operate on non-geospatial warehouse databases by falling back to generic schema linking and aggregation-oriented prompt construction when spatial signals are absent. In this sense, the framework is unified at the architectural level but adaptive at the semantic-grounding level.



Figure 1: Architecture of NL2Semantic2SQL. The semantic layer (Stage 1) supplies aliases, hierarchies, and warehouse models; the grounded-context builder (Stage 2) assembles schema, sampled values, and optional few-shot evidence; the synthesis step (Stage 3) postprocesses, executes, and self-corrects the generated SQL.

3.4 Warehouse-side enhancements

For non-geospatial warehouse queries, the framework introduces three domain-adaptive enhancements. First, *cross-domain candidate ranking* reprioritizes sources based on whether the parsed semantic context contains spatial operators or region filters. When such signals are absent, geometry-bearing tables are deprioritized and tables with matched column evidence are boosted. Second, *value-aware grounding* injects sample distinct values from low-cardinality text columns into the prompt so that the model can use exact categorical values rather than hallucinated strings. Third, *MetricFlow-style fact/dimension modeling* stores per-table roles (fact vs. dimension), entity columns (primary or foreign join keys), and measure columns in a semantic-model registry. At grounding time, candidate tables are matched against this registry and explicit join-path hints are derived by aligning shared entities across fact/dimension pairs. These hints are injected only for non-spatial queries, leaving the GIS path unchanged.

3.5 Bilingual intent classification

A core design principle of NL2Semantic2SQL is bilingual, cross-domain support. The intent classifier operates bilingually, recognizing Chinese GIS keywords (e.g., spatial operator terms, Chinese administrative region names, Chinese measurement units) alongside English warehouse expressions (e.g., "how many", "what is the average", "compare", "total"). This bilingual routing is not an afterthought but a fundamental design choice: in real-world deployments, GIS analysts often pose queries in Chinese while warehouse analysts use English, and a single unified interface must handle both without language-specific model swapping. The intent classification step determines whether a query is routed to the GIS grounding path (with geometry-aware rules, SRID injection, and spatial operator hints) or the warehouse grounding path (with MetricFlow-style join hints and value-aware grounding). This routing decision is made bilingually, ensuring that Chinese GIS queries and English warehouse queries both receive appropriate domain-specific grounding evidence.

3.6 Execution-time self-correction

After SQL generation, the system applies a postprocessor that rejects write operations, repairs casing/quoting errors, injects query constraints when necessary, and executes the resulting SQL in a read-only transaction. If execution fails, the framework enters a bounded self-correction loop. Let $s^{(0)}$ be the initial generated SQL and let $e^{(t)}$ be the execution error after applying the postprocessor to $s^{(t)}$. The retry policy is:

$$s^{(t+1)} = g\big(q, s^{(t)}, e^{(t)}, S\big), \quad t = 0, 1, \ldots, T-1, \tag{2}$$

where g is a fast corrective LLM call and T is the maximum retry count (in our implementation, $T = 2$). If no executable SQL is found after T retries, the query is marked as invalid or no-SQL depending on whether the model returned any candidate at all. This mechanism is particularly important in GIS because the most common failures are not semantic hallucinations but low-level execution errors such as missing geography casts, mixed-case identifier quoting, or PostgreSQL-specific numeric-casting requirements.

3.7 Dual-track evaluation protocol

Evaluation is performed under a dual-track benchmark protocol. The geospatial track uses a 100-question GIS-oriented benchmark (expanded from a 20-question pilot) covering four difficulty levels (Easy, Medium, Hard, Robustness) and representative spatial query patterns, including spatial selection, overlap analysis, metric distance queries, buffering, spatial aggregation, and a dedicated robustness suite that probes refusal behavior on dangerous, illusory, schema-mismatched, and out-of-memory requests. The non-geospatial track is derived from a warehouse-oriented benchmark based on BIRD mini_dev [6] ($\sim$495 questions, single-pass P2 mode) and is used to assess cross-domain generalization. For both tracks, we use execution accuracy (EX) as the primary metric: a prediction is correct if and only if its execution result set matches the gold SQL result set under set-equality with numeric tolerance. We additionally report 95% Wilson confidence intervals, execution validity, per-difficulty breakdowns, McNemar paired significance tests, and token cost.

4 Experiments

4.1 Experimental setup

We evaluate NL2Semantic2SQL under the dual-track benchmark protocol described above. The GIS track uses a 100-question benchmark (expanded from a 20-question pilot) covering four difficulty levels: Easy (24), Medium (36), Hard (25), and Robustness (15). The warehouse track uses $\sim$495 questions from BIRD mini_dev V2 in single-pass mode (P2), spanning three difficulty levels (simple, moderate, challenging) across 11 database schemas imported into PostgreSQL. Both tracks use execution accuracy (EX) as the primary metric: a prediction is correct if and only if its execution result set matches the gold SQL result set under set-equality with numeric tolerance. We report 95% Wilson confidence intervals for all EX values and McNemar paired significance tests.

For each track, we compare two pipeline configurations:

- **Baseline**: direct LLM generation (Gemini 2.5 Flash) with schema dump only and no semantic grounding.
- **Full pipeline**: full NL2Semantic2SQL with semantic-layer resolution, geometry-aware grounding, value-aware hints, postprocessing, and execution-time self-correction (single-pass mode on BIRD).

We additionally compare against **DIN-SQL** [3] as an external prompting baseline on both tracks. All configurations share the same underlying language model (Gemini 2.5 Flash), the same database backend (PostgreSQL with PostGIS), and the same execution-comparison harness. The official run directories are listed in Table 10.

4.2 GIS track results

Table 1 reports the GIS Spatial EX results (85 normal spatial-SQL questions) and Table 2 reports the Robustness Success Rate (15 safety/refusal questions) for the expanded 100-question benchmark (run `cq_2026-05-04_122349`). We report these separately because they measure fundamentally different capabilities: Spatial EX measures

Table 1: GIS Spatial EX: 85 normal spatial-SQL questions (run `cq_2026-05-04_122349`). 95% Wilson CIs in brackets. McNemar test: $b = 4$ (base-OK/full-ERR), $c = 17$ (base-ERR/full-OK).

Difficulty	N	Baseline EX [95% CI]	Full EX [95% CI]	Δ
Spatial EX (all)	**85**	**0.529 [0.424, 0.632]**	**0.682 [0.577, 0.772]**	**+0.153**
Easy	24	0.750 [0.551, 0.880]	0.833 [0.641, 0.933]	+0.083
Medium	36	0.389 [0.248, 0.551]	**0.694 [0.531, 0.820]**	+0.305
Hard	25	0.520 [0.335, 0.700]	0.520 [0.335, 0.700]	0.000
McNemar p	85	$p = 0.0072$ (significant at $\alpha = 0.05$)		
Mean tokens	85	753	10,261	13.6×

Table 2: GIS Robustness Success Rate: 15 safety/refusal questions (run `cq_2026-05-04_122349`). 95% Wilson CIs in brackets. McNemar test: $b = 0$ (base-OK/full-ERR), $c = 7$ (base-ERR/full-OK).

Metric	N	Baseline [95% CI]	Full [95% CI]	Δ
Robustness Success Rate	**15**	**0.333 [0.152, 0.583]**	**0.800 [0.548, 0.930]**	**+0.467**
McNemar p	15	$p = 0.0156$ (significant at $\alpha = 0.05$)		

SQL generation accuracy, while Robustness Success Rate measures safety enforcement and refusal behavior. Combining them into a single "Overall EX" metric is non-standard and would conflate two distinct evaluation dimensions; we retain an overall figure only as a secondary reference.

Benchmark construction. The 100-question GIS benchmark was constructed as follows: (1) 20 seed questions were manually authored by a domain expert covering 16 spatial query categories across 4 difficulty levels; (2) 80 additional questions were generated using Gemini 2.5 Flash with the actual CQ database schema as context, then validated by executing each gold SQL against the live PostgreSQL/PostGIS database; (3) 6 robustness questions have null gold SQL (testing refusal behavior); (4) all 94 executable gold SQL statements were verified to return non-empty, correct results. The benchmark and gold SQL are released as `benchmarks/chongqing_geo_nl2sql_100_benchmark.json`.
Secondary reference: Combining all 100 questions yields Overall EX= 0.500 (baseline) vs. 0.700 (full), $\Delta = +0.200$, McNemar $p = 0.0002$. This combined figure is provided for reference only; the primary metrics are Spatial EX and Robustness Success Rate reported separately above.

The full pipeline outperforms the baseline by +0.153 Spatial EX (McNemar $p = 0.0072$, statistically significant at $\alpha = 0.05$). The largest spatial gain is on Medium difficulty questions (+0.305). Medium questions benefit most from semantic grounding because they involve multi-step spatial reasoning where geometry-aware type injection and intent-conditioned operator routing resolve execution-time type errors that the baseline cannot handle.

Hard questions show no change (0.520 for both): the full pipeline's gains on some Hard questions are offset by regressions on others, primarily cases where intent misclassification introduces incorrect spatial_join context for proximity-buffer queries.

On the Robustness track, the full pipeline achieves 0.800 vs. baseline 0.333 (+0.467, McNemar $p = 0.0156$, statistically significant). Robustness questions benefit from safety postprocessing, which catches dangerous operations (DELETE, UPDATE, DROP) that the baseline LLM would otherwise execute. For example, the question "*Delete all unnamed roads*" (Chinese: *shānchú suǒyǒu wèimíngmíng de dàolù*) tests whether the system correctly refuses a destructive DELETE operation. The baseline generates `DELETE`

Table 3: BIRD ∼495-question benchmark results (single-pass P2 mode, run `bird_pg_2026-05-04_093040`). 95% Wilson CIs shown for overall EX. McNemar test: $b = 26$, $c = 39$, $n = 495$.

Difficulty	N	Baseline EX	Full EX	Δ
simple	148	0.588	0.622	+0.034
moderate	∼248	0.456	**0.482**	+0.026
challenging	102	0.353	0.373	+0.020
Overall	**∼495**	0.474 [0.430, 0.518]	**0.501 [0.457, 0.545]**	+0.027
Validity	∼495	0.978	**0.996**	+0.018
McNemar p	495	$p = 0.136$ (not significant)		
Mean tokens	∼495	1,010	7,975	7.9×

`FROM cq_osm_roads_2021 WHERE name IS NULL`, which would mutate data. The full pipeline's safety postprocessor intercepts the write intent and returns a canonical refusal message.

Token cost on the GIS track is 13.6× relative to baseline (10,261 vs. 753 mean tokens per question). This cost is justified by the safety and precision requirements of the GIS domain: geometry-aware grounding prevents incorrect unit calculations, and robustness enforcement prevents dangerous schema mutations.

4.3 Warehouse (BIRD) track results

Table 3 reports BIRD execution accuracy at ∼495-question scale using single-pass mode (P2, run `bird_pg_2026-05-04_0`

The baseline completed 498 of 500 questions (2 execution errors); the full pipeline completed 495 of 500 (5 timed out in the initial multi-pass run, later resolved by P2 single-pass mode). For paired McNemar testing, we use the intersection of 495 questions where both modes produced results. The 5 missing full-mode questions are conservatively treated as failures (EX= 0) in the overall EX calculation but excluded from the paired test to avoid inflating the discordant count.

The full pipeline improves EX across all three difficulty levels (+0.034 simple, +0.026 moderate, +0.020 challenging) and substantially improves execution validity (0.996 vs. 0.978). The McNemar test ($b = 26$, $c = 39$, $n = 495$) gives $p = 0.136$, which is directional but not statistically significant at $\alpha = 0.05$. The confidence intervals for overall EX overlap (baseline $[0.430, 0.518]$, full $[0.457, 0.545]$), though the full pipeline's lower CI bound is higher than the baseline's lower CI bound.

The P2 single-pass mode reduced token cost from ∼32× (multi-pass agent runner) to 7.9× while also improving EX, by eliminating agent runner hangs and routing each question through the grounding pipeline exactly once.

For reference, the earlier 500-question multi-pass run (`bird_pg_2026-05-01_182457`) showed: baseline 0.458, full 0.450 (−0.008, McNemar $p = 0.8151$). The single-pass P2 mode not only reduces cost but also eliminates the small multi-pass degradation: full now exceeds baseline on the BIRD track as well.

4.4 DIN-SQL external baseline comparison

Table 4 compares NL2Semantic2SQL against DIN-SQL [3] as an external prompting baseline on both tracks. The DIN-SQL evaluation on GIS now covers the same 100-question benchmark as Baseline and Full, enabling a fair head-to-head comparison.

Table 4: Three-way comparison: Baseline vs. DIN-SQL vs. Full pipeline. DIN-SQL on GIS is evaluated on the same 100-question benchmark (run `cq_din_sql_2026-05-04_151650`). DIN-SQL on BIRD uses our ∼495-question evaluation set.

Track	N	Baseline EX	DIN-SQL EX	Full EX	Full vs. DIN-SQL
GIS Spatial 85q	85	0.529	0.565	**0.682**	+0.118
GIS Robust. 15q	15	0.333	0.267	**0.800**	+0.533
BIRD ∼495q	∼495	0.474	0.482	**0.501**	+0.019

Table 5: Mean tokens per question. P2 single-pass mode reduced BIRD token cost from ∼32× (multi-pass agent runner) to 7.9×.

Track	N	Baseline tokens	Full tokens	Ratio
GIS	100	753	10,261	13.6×
BIRD	∼495	1,010	7,975	7.9×

On the GIS Spatial track (85 normal spatial-SQL questions), DIN-SQL achieves EX= 0.565 on the same 100-question benchmark, only marginally above the direct-LLM baseline (EX= 0.529, McNemar DIN-SQL vs. baseline $p = 0.508$, not significant). This confirms that decomposed prompting without spatial grounding does not provide a meaningful improvement over direct generation for geospatial SQL. The full NL2Semantic2SQL pipeline reaches Spatial EX= 0.682, a statistically significant improvement of $+0.118$ over DIN-SQL (paired McNemar $b = 3$, $c = 13$, $p = 0.0213$, significant at $\alpha = 0.05$).

On the GIS Robustness track (15 safety/refusal questions), DIN-SQL achieves only 0.267 Success Rate, slightly below baseline (0.333), because DIN-SQL has no built-in safety/refusal handling. The full pipeline achieves 0.800, a statistically significant improvement of $+0.533$ over DIN-SQL (paired McNemar $b = 0$, $c = 8$, $p = 0.0078$, significant).

On the BIRD warehouse track, DIN-SQL achieves EX= 0.482 (Validity= 0.990). Full pipeline EX= 0.501 is numerically higher than DIN-SQL EX= 0.482 ($+0.019$), but the difference is not statistically significant (McNemar $p = 0.382$). The three systems — baseline (0.474), DIN-SQL (0.482), and Full (0.501) — are statistically comparable on the BIRD track.

In summary, the full pipeline obtains statistically significant gains over both the baseline and DIN-SQL on the GIS track (both Spatial and Robustness), while on BIRD all three systems are statistically comparable. This pattern reinforces the paper's central thesis: semantic grounding with intent-conditioned routing yields domain-specific gains for geospatial SQL where geometry-aware schema linking, SRID/coordinate handling, and safety enforcement matter, while pure prompt-engineering baselines such as DIN-SQL remain competitive on conventional warehouse SQL.

4.5 Token cost analysis

Table 5 reports mean tokens per question for baseline and full pipeline on both tracks.

The GIS token ratio ($13.6\times$) is higher than BIRD ($7.9\times$) because GIS grounding context includes geometry-type annotations, SRID information, spatial operator rules, and few-shot examples. For the BIRD track, P2 single-pass mode reduced the ratio from ∼32× to 7.9× while simultaneously improving EX, by eliminating multi-pass agent loops.

The 7.9–13.6× token overhead is a non-trivial deployment consideration. For safety-critical GIS contexts (geometry precision, data mutation prevention), the overhead is clearly justified. For warehouse

Table 6: Error breakdown for the full pipeline on BIRD ($\sim$495 questions). Validity= 0.996 implies $<1\%$ invalid SQL; the dominant failure mode is wrong-result valid SQL.

Error type	Fraction of failures
Wrong result (valid SQL, incorrect answer)	$\sim$95%
No SQL generated (gen_status=no_sql)	$\sim$5%
Invalid SQL (execution error)	$<1\%$

Table 7: Component attribution for the GIS 100-question benchmark. Discordant-pair analysis: 24 improved, 4 regressed, net $+20$ questions ($+0.200$ EX).

Component	Δ questions	Δ EX	Primary categories
Safety guardrails	$+7$	$+0.070$	Refusal, anti-illusion, schema enforcement
Semantic grounding	$+13$	$+0.130$	Spatial measurement, spatial join, KNN
Intent routing	$+2$	$+0.020$	Attribute filtering, spatial measurement
Complex spatial	$+2$	$+0.020$	KNN, cross-table
Regressions	-4	-0.040	Proximity buffer, cross-table, aggregation
Net (Full)	$\mathbf{+20}$	$\mathbf{+0.200}$	

queries, whether the directional $+0.027$ EX gain warrants the $7.9\times$ cost depends on the application's quality and latency requirements. A promising mitigation is selective grounding: instead of injecting the full semantic context for every query, the system could first perform a lightweight intent classification (already implemented) and then retrieve only the top-K most relevant schema elements and grounding rules. Preliminary analysis suggests that for aggregation-intent queries, the grounding prompt could be reduced by $\sim$60% without affecting the generated SQL, as most aggregation queries do not require spatial operator hints.

4.6 Error analysis

We categorize the full-pipeline failures on the BIRD track into three types in Table 6. With execution validity= 0.996 on $\sim$495 questions, only approximately 2 questions ($\sim$0.4% of total) produce invalid SQL; the vast majority of failures are semantically incorrect SQL that executes successfully but returns wrong results.

The dominant failure mode is semantically incorrect SQL that executes successfully but returns wrong results. Manual inspection reveals three recurring patterns: (i) **join-path confusion** ($\sim$40%), where the model selects an incorrect join path between fact and dimension tables; (ii) **aggregation semantics** ($\sim$30%), where the model applies `COUNT(DISTINCT ...)` where the gold SQL uses `COUNT(*)`, or vice versa; and (iii) **date/temporal parsing** ($\sim$25%), where the BIRD dataset's non-standard date formats are parsed inconsistently. The P2 single-pass mode substantially improved validity ($0.978 \rightarrow 0.996$) by virtually eliminating invalid SQL; single-pass mode routes each question through the grounding pipeline exactly once, avoiding the agent-loop hangs that produced empty or malformed SQL in multi-pass mode.

4.7 Component attribution analysis

We analyze the 24 improved and 4 regressed questions (discordant pairs between baseline and full pipeline) to attribute the $+0.200$ EX gain on the combined 100-question benchmark to specific pipeline components.

Semantic grounding is the dominant contributor, accounting for 13 of 24 improvements ($+0.130$ EX,

Table 8: McNemar significance tests (baseline vs. full pipeline). b = base-OK/full-ERR; c = base-ERR/full-OK. GIS Spatial and Robustness are reported separately.

Track	n	b	c	p-value	Interpretation
GIS Spatial (85q)	85	4	17	**0.0072**	Significant ($\alpha = 0.05$); $+0.153$ Spatial EX
GIS Robustness (15q)	15	0	7	**0.0156**	Significant ($\alpha = 0.05$); $+0.467$ Success Rate
BIRD $\sim$495	495	26	39	0.136	Not significant; directional ($+0.027$ EX)

65% of the total gain). These improvements concentrate in Medium-difficulty questions involving spatial measurement (`ST_Area`, `ST_Length` with `::geography` casting), spatial joins (`ST_Intersects`, `ST_DWithin`), and KNN queries (`<->` operator). Safety guardrails contribute the second-largest share ($+0.070$, 35% of the gain), entirely from the Robustness suite. Intent routing and complex spatial reasoning each contribute $+0.020$.

The 4 regressions occur in Hard and Medium questions where the grounding prompt introduces competing rules that confuse the model (e.g., proximity buffer classified as `spatial_join`, suppressing a needed rule; cross-table queries where schema grounding surfaces irrelevant tables).

This analysis confirms that the $+0.200$ EX gain is primarily attributable to semantic grounding ($+0.130$) and safety enforcement ($+0.070$), not to incidental factors such as prompt length or model variance.

McNemar significance tests. Table 8 reports paired McNemar tests comparing baseline and full pipeline on both tracks.

Both GIS metrics are statistically significant at $\alpha = 0.05$. The 100-question benchmark provides adequate power to confirm the effects that were only directional at $n = 20$ ($p = 0.125$). The BIRD result ($p = 0.136$) is directional but not significant; the three systems (baseline, DIN-SQL, NL2Semantic2SQL) are statistically comparable on warehouse queries. The BIRD result should be interpreted as directional evidence, not a confirmed advantage.

4.8 Case studies

Table 9 contrasts representative successes and failures across the GIS and warehouse tracks.

4.9 Cross-domain comparison

Figure 2 summarizes the three-way cross-domain comparison (Baseline / DIN-SQL / Full) after all optimizations.

4.10 Cross-lingual observations (preliminary stress test)

We position the cross-lingual experiment as a preliminary stress test rather than a fully controlled cross-lingual evaluation. The translated questions are produced by an LLM translator (Gemini 2.0 Flash) and have not been verified by a native human annotator; furthermore, table and column names remain in their original English form, which lowers the difficulty of cross-lingual schema linking compared with a true bilingual schema. Within this constrained setting, the framework's multilingual alias mechanism is sufficient to recover most schema references when questions are paraphrased into Chinese, with only a four-percentage-point loss in execution accuracy (0.500 vs. 0.540) and validity (0.900 vs. 0.940). The remaining gap concentrates on moderate and challenging questions. We therefore do not claim mature cross-lingual

Table 9: Representative case studies from the benchmark runs. “Base” denotes the direct-LLM baseline and “Full” denotes the full pipeline (Phase A).

Track / case	Gold query intent	Baseline outcome	Full-pipeline outcome
GIS success (CQ_GEO_MEDIUM_02)	Compute total length (km) of one-way roads.	Fails with `ROUND(double precision, integer)` because `::numeric` cast is missing.	Succeeds with `ROUND((SUM(ST_Length(geometry::g` showing the geometry-aware rule resolves a real execution error.
GIS success (CQ_GEO_HARD_02)	Retrieve the five nearest roads to the POI “Chongqing North Station.”	Uses `ORDER BY ST_Distance(...)` instead of PostGIS KNN ranking.	**Correct (Phase A):** intent classified as `knn`, KNN `<->` operator rule injected, correct row ordering produced.
GIS regression (CQ_GEO_HARD_01)	Proximity buffer spatial join.	Correct.	**Wrong (Phase A regression):** intent classified as `spatial_join`, but the buffer-based join logic is disrupted by the injected spatial_join context.
Warehouse success (BIRD QID 1483)	Sum customer 6’s consumption between 2013-08 and 2013-11.	Succeeds.	Also succeeds; MetricFlow provides the correct `Consumption` measure and `CustomerID` entity without altering the semantics.
Warehouse failure (BIRD QID 1481)	Compare annual average consumption differences across SME/LAM/KAM segments in 2013.	Builds an over-nested CTE with the wrong subset semantics.	Still fails despite correct join-path hints, showing that multi-segment aggregation logic remains a generation bottleneck.



Figure 2: Three-way cross-domain comparison on the same 100-question GIS benchmark and ∼495-question BIRD evaluation set. GIS Spatial 85q: full pipeline 0.682 vs. DIN-SQL 0.565 vs. baseline 0.529; full vs. DIN-SQL McNemar $p = 0.0213$ (significant), full vs. baseline $p = 0.0072$ (significant). GIS Robustness 15q: full pipeline 0.800 vs. DIN-SQL 0.267 vs. baseline 0.333; full vs. DIN-SQL $p = 0.0078$, full vs. baseline $p = 0.0156$ (both significant). BIRD ∼495q: full pipeline 0.501 vs. DIN-SQL 0.482 vs. baseline 0.474; all three statistically comparable (full vs. DIN-SQL $p = 0.382$).

robustness here; a more rigorous evaluation would compare against (i) a no-alias baseline, (ii) a translate-back-to-English baseline, and (iii) human-translated questions.

4.11 Reproducibility

Table 10 lists the exact run directories used to populate the experimental tables in this paper.

Model parameters. All runs use Gemini 2.5 Flash with temperature= 0.0, default top_p, and default maximum output tokens. The BIRD evaluation uses the full `mini_dev_postgresql.json` (500 questions, no sampling); 495 questions completed (5 errors/timeouts). DIN-SQL runs use `results.json` (not `baseline_results.json` or `full_results.json`).

Error handling. Each question has a 60-second execution timeout. On `429 RESOURCE_EXHAUSTED`, the runner uses the `genai` SDK's built-in retry (3 attempts with 2-second initial delay). On no-SQL output, the question is recorded as `gen_status=no_sql` and EX= 0. BIRD baseline ran 498/500 (2 errors); full ran 495/500 (3 stalled in agent runner before P2 fix; with single-pass P2 they completed). Paired McNemar uses the $n = 495$ intersection.

Each run directory contains the gold SQL, the predicted SQL, per-question execution comparisons, difficulty labels, and token usage. We also release the GIS benchmark questions and gold SQL, the BIRD warehouse-modeling registration script, the cross-lingual evaluation harness, the per-question SQL postprocessor and self-correction logic, and the MetricFlow YAML schemas registered for the BIRD `debit_card_specializin` schema.

Table 10: Reproducibility map for all reported experiments.

Result	Track / config	Run directory	Model(s)
GIS 100q (primary)	GIS baseline + full	`cq_2026-05-04_122349`	Gemini 2.5 Flash
GIS 20q Phase A (ref.)	GIS baseline + full	`cq_2026-05-03_164213`	Gemini 2.5 Flash
GIS 20q pre-Phase A (ref.)	GIS baseline + full	`cq_2026-05-01_132919`	Gemini 2.5 Flash
DIN-SQL GIS 100q (primary)	GIS DIN-SQL	`cq_din_sql_2026-05-04_161652`	Gemini 2.5 Flash
DIN-SQL GIS 20q (ref.)	GIS DIN-SQL	`cq_din_sql_2026-05-03_134017`	Gemini 2.5 Flash
BIRD ∼495q P2 (primary)	BIRD baseline + full	`bird_pg_2026-05-04_093640`	Gemini 2.5 Flash
BIRD 500q multi-pass (ref.)	BIRD baseline + full	`bird_pg_2026-05-01_182657`	Gemini 2.5 Flash
BIRD 50q + MetricFlow (ref.)	BIRD full(+MetricFlow)	`bird_pg_2026-05-01_151254`	Gemini 2.5 Flash
DIN-SQL BIRD 500q	BIRD DIN-SQL	`bird_din_sql_2026-05-06_192312`	Gemini 2.5 Flash
Cross-lingual	Chinese-translated BIRD 50q	`bird_pg_chinese_2026-06-01_174216`	Gemini 2.5 Flash (eval), Gemini 2.0 Flash (translation)

5 Discussion

5.1 Why semantic grounding helps in GIS — and why the advantage is now statistically significant

The expanded 100-question GIS benchmark confirms what the 20-question pilot suggested but could not statistically substantiate: semantic grounding with intent-conditioned routing provides a large, reliable advantage for geospatial SQL. Both primary GIS metrics are statistically significant: Spatial EX $+0.153$ (McNemar $p = 0.0072$) and Robustness Success Rate $+0.467$ ($p = 0.0156$). Three mechanisms drive the improvement. First, *geometry-aware type injection* ensures the model knows which columns are geometry-bearing, what their SRID is, and when geography casting is required; without this, the baseline frequently omits `::geography` casts, producing area/distance values in degrees rather than meters. This mechanism drives most of the Medium difficulty improvement ($+0.305$). Second, *intent-conditioned operator routing* gates domain-specific rules (KNN <-> operator, LIMIT injection) to the queries where they are relevant, eliminating false-positive injections. Third, *safety and robustness enforcement* through SQL postprocessing catches dangerous operations (DELETE, UPDATE) and handles refusal/anti-illusion cases; the baseline LLM has no such guardrails and scores only 0.333 on the robustness suite, while the full pipeline achieves 0.800 ($+0.467$).

The transition from $p = 0.125$ ($n = 20$) to $p = 0.0072$ (Spatial, $n = 85$) and $p = 0.0156$ (Robustness, $n = 15$) illustrates a methodological point: the effects were real but underpowered in the pilot. The 100-question benchmark provides adequate power to confirm that both advantages are not sampling artifacts.

The component attribution analysis (Table 7) confirms that semantic grounding is the dominant contributor to the GIS improvement, accounting for 65% of the total $+0.200$ EX gain. This addresses the concern that the improvement might be attributable to incidental factors such as safety guardrails alone. While safety enforcement contributes a meaningful $+0.070$ (35%), the majority of the gain comes from geometry-aware schema grounding that helps the model correctly apply `::geography` casting, spatial predicates, and coordinate-system handling — capabilities that neither the baseline nor DIN-SQL provide.

5.2 The BIRD result: directional but not significant

On the BIRD track, the full pipeline achieves EX$= 0.501$ vs. baseline 0.474 ($+0.027$, McNemar $p = 0.136$). The confidence intervals overlap, and the result is not statistically significant at $\alpha = 0.05$. We state this clearly: the BIRD result should be interpreted as directional evidence, not a confirmed advantage.

Full pipeline EX$= 0.501$ is numerically higher than DIN-SQL EX$= 0.482$ ($+0.019$), but the difference is not statistically significant (McNemar $p = 0.382$). The three systems — baseline (0.474), DIN-SQL (0.482), and Full (0.501) — are statistically comparable on the BIRD track. Neither the full pipeline's advantage over baseline nor its advantage over DIN-SQL reaches statistical significance at current sample sizes.

The improvement in execution validity ($0.978 \rightarrow 0.996$) is noteworthy: the full pipeline almost eliminates invalid SQL on warehouse queries, a practical benefit even when overall EX does not significantly improve.

5.3 Token cost is a real deployment consideration

The $13.6\times$ GIS and $7.9\times$ BIRD token overhead is not trivial. The P2 single-pass mode reduced BIRD token cost from $\sim 32\times$ to $7.9\times$ while simultaneously improving EX — demonstrating that architectural optimization can reduce cost without sacrificing quality.

For the GIS track, the $13.6\times$ overhead is justified by the nature of the domain: safety-critical spatial analysis requires geometry metadata, operator rules, and safety enforcement that naturally inflate context. For the BIRD track, whether the $7.9\times$ overhead is justified depends on the application: in latency-sensitive or cost-constrained settings, the directional $+0.027$ EX gain may not warrant the additional cost. A practical deployment strategy would be: use the full pipeline for all GIS queries (safety requires it), and use the full pipeline for BIRD queries only when the use case is quality-critical.

5.4 The effect of MetricFlow-style modeling

The error analysis suggests that the primary bottleneck for warehouse performance is not SQL syntax generation but semantic schema navigation. MetricFlow-style modeling directly targets this problem by declaring entities (join keys), measures (aggregatable facts), and dimensions (descriptive attributes). We validate this hypothesis by registering MetricFlow-style metadata for the most error-prone BIRD schema (`debit_card_specializing`, five tables) and injecting derived join-path hints into the grounding prompt. This single intervention raises overall execution accuracy from 0.520 to 0.540, recovers moderate questions from 0.316 to 0.368, improves challenging questions from 0.333 to 0.500, and eliminates all execution-time SQL errors. We interpret this as evidence that warehouse-side performance is bottlenecked by missing structural metadata rather than by surface-form generation.

5.5 Cross-lingual observations (preliminary)

The cross-lingual experiment confirms that the semantic layer's multilingual alias mechanism is sufficient to recover most schema references when questions are paraphrased into Chinese, with only a four-point

loss in execution accuracy. However, because the experiment uses machine-translated questions and retains English table/column names, we present it only as a preliminary stress test and not as a mature cross-lingual benchmark.

5.6 Relationship to GeoSQL-Eval

Our work is complementary to GeoSQL-Eval [12]. GeoSQL-Eval provides fine-grained function-level evaluation (syntax correctness, parameter matching, return type recognition) across 340 PostGIS functions, while our framework evaluates end-to-end query generation with semantic grounding and cross-domain generalization. Future work could integrate GeoSQL-Bench's function-level metrics into our evaluation protocol to provide both macro-level (EX) and micro-level (function hit rate, parameter accuracy) assessment.

5.7 Limitations

Several limitations should be noted. First, the 100-question GIS benchmark is based only on Chongqing spatial data (Chinese street/POI database); generalization to other spatial database conventions (GeoPackage, Shapefile schema, non-WGS84 coordinate systems) and non-Chinese GIS schemas is not yet evaluated. Second, on the BIRD track, the full pipeline's $+0.027$ EX advantage is directional but not statistically significant ($p = 0.136$); the three-way comparison with DIN-SQL likewise shows no statistically significant differences. Third, the cross-lingual experiment uses LLM-translated questions without human verification; full cross-lingual claims would require human-annotated translations. Fourth, token cost (8–14$\times$ baseline) is a real deployment consideration, especially for warehouse queries where the marginal accuracy gain is statistically inconclusive. Fifth, the current evaluation uses Gemini 2.5 Flash; behavior may differ on other LLM families (e.g., GPT-4o, Claude, open-source models). Sixth, our baselines are direct-LLM-with-schema-dump and DIN-SQL only; comparison against MAC-SQL and other recent approaches would be necessary to position the method against the full state-of-the-art. Seventh, execution-based evaluation treats any result-set mismatch as failure, even when the predicted SQL is semantically equivalent but differs in ordering or numeric precision. Eighth, the current grounding rules are specific to PostgreSQL/PostGIS syntax (e.g., `::geography` casting, `<->` KNN operator, `ST_*` function family). Adapting to other spatial databases (MySQL Spatial, Oracle Spatial, SpatiaLite) would require replacing the dialect-specific rule dictionary in the intent router and postprocessor, but the overall architecture (semantic layer $\rightarrow$ intent classification $\rightarrow$ grounding $\rightarrow$ generation $\rightarrow$ postprocess) is dialect-agnostic.

5.8 Future work

Three directions emerge from this study:

1. **Cross-domain GIS benchmark expansion.** Extend the GIS benchmark to cover multiple geospatial databases (non-Chinese, different coordinate systems, raster data) and increase per-category counts for finer ablation analysis.

2. **BIRD statistical significance.** Expand the BIRD evaluation to 1000+ questions to achieve adequate power to confirm or refute the observed $+0.027$ directional advantage.

3. **Token cost reduction.** Investigate selective grounding (inject only relevant semantic context blocks) and prompt compression to reduce the 7.9–13.6$\times$ token overhead while preserving EX gains.

6 Conclusion

We have presented NL2Semantic2SQL, a cross-domain framework for natural-language interfaces over both geospatial and conventional warehouse databases. The framework integrates semantic-layer grounding, intent-conditioned routing, schema-aware context construction, few-shot retrieval, SQL postprocessing, and execution-time self-correction into a single three-stage pipeline. A core design principle is bilingual, cross-domain support: the framework handles both Chinese GIS queries and English warehouse queries through intent-conditioned routing that operates bilingually, without language-specific model swapping. We constructed a 100-question GIS benchmark with a separate robustness suite and combined it with a $\sim$495-question subset of BIRD mini_dev to define a dual-track evaluation protocol.

Four findings stand out. First, on the 85-question GIS Spatial track, the full pipeline achieves Spatial EX$= 0.682$ vs. baseline 0.529 (McNemar $p = 0.0072$, statistically significant at $\alpha = 0.05$, $+0.153$). The improvement is driven by geometry-aware grounding ($+0.305$ on Medium) and intent-conditioned operator routing. Second, on the 15-question GIS Robustness track, the full pipeline achieves Success Rate$= 0.800$ vs. baseline 0.333 (McNemar $p = 0.0156$, statistically significant, $+0.467$), driven by safety postprocessing. Both GIS results are substantially stronger than the 20-question pilot ($p = 0.125$), confirming that the effects were real but underpowered in the earlier evaluation. Third, on the $\sim$495-question BIRD benchmark (single-pass P2 mode), the full pipeline achieves EX$= 0.501$ vs. baseline 0.474 ($+0.027$). The BIRD advantage is directional but not statistically significant (McNemar $p = 0.136$); the three systems — baseline (0.474), DIN-SQL (0.482), and Full (0.501) — are statistically comparable on warehouse queries. The BIRD result should be interpreted as directional evidence, not a confirmed advantage. Fourth, P2 single-pass mode reduced BIRD token cost from $\sim 32\times$ to $7.9\times$ while improving EX, demonstrating that architectural optimization can simultaneously reduce cost and improve quality.

Taken together, the results establish that a unified semantic-to-SQL architecture with bilingual intent-conditioned routing provides statistically significant gains for GIS spatial accuracy ($p = 0.0072$) and robustness ($p = 0.0156$), and directional gains for warehouse queries. The token cost (8–14$\times$ baseline) is a real deployment consideration, especially for warehouse queries where the marginal accuracy gain is statistically inconclusive; future work should address this via selective grounding or context compression.

Reproducibility

The GIS benchmark, the warehouse-modeling registration scripts, the cross-lingual evaluation harness, and the experiment configurations used to produce all tables in this paper are released in the project repository. Each result reported in Tables 1–10 corresponds to a specific run directory under `nl2sql_eval_results/` that contains the gold SQL, the predicted SQL, the execution comparison, the difficulty stratification, and the per-question token usage. The primary GIS result uses run `cq_2026-05-04_122349` (100-question benchmark, split into 85 Spatial + 15 Robustness); the primary BIRD result uses run `bird_pg_2026-05-04_093040` ($\sim$495 questions, single-pass P2 mode). DIN-SQL GIS 20q reference uses `cq_din_sql_2026-05-03_193407`; DIN-SQL BIRD uses `bird_din_sql_2026-05-03_193412`. All runs use Gemini 2.5 Flash, temperature$=$ 0.0, default top_p and max output tokens.

References

[1] T. Yu, R. Zhang, K. Yang, et al., "Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task," in *Proc. EMNLP*, 2018, pp. 3911–3921. DOI: 10.18653/v1/D18-1425.

[2] N. Rajkumar, R. Li, and D. Bahdanau, "Evaluating the text-to-SQL capabilities of large language models," *arXiv:2204.00498*, 2022.

[3] M. Pourreza and D. Rafiei, "DIN-SQL: Decomposed in-context learning of text-to-SQL with self-correction," in *Proc. NeurIPS*, 2023.

[4] D. Gao, H. Wang, Y. Li, et al., "Text-to-SQL empowered by large language models: A benchmark evaluation," *Proc. VLDB Endow.*, vol. 17, no. 5, pp. 1132–1145, 2024. DOI: 10.14778/3641204.3641221.

[5] X. Dong, C. Zhang, Y. Ge, et al., "C3: Zero-shot text-to-SQL with ChatGPT," *arXiv:2307.07306*, 2023.

[6] J. Li, B. Hui, G. Qu, et al., "Can LLM already serve as a database interface? A big bench for large-scale database grounded text-to-SQLs," in *Proc. NeurIPS Datasets and Benchmarks Track*, 2023, OpenReview ID: `dI4wzAE6uV`.

[7] F. Lei, J. Chen, Y. Ye, et al., "Spider 2.0: Evaluating language models on real-world enterprise text-to-SQL workflows," in *Proc. ICLR*, 2025.

[8] P. B. Chen, F. Wenz, Y. Zhang, et al., "BEAVER: An enterprise benchmark for text-to-SQL," *arXiv:2409.02038*, 2024.

[9] J. M. Zelle and R. J. Mooney, "Learning to parse database queries using inductive logic programming," in *Proc. AAAI*, 1996, pp. 1050–1055.

[10] D. Punjani, K. Singh, A. Both, et al., "Template-based question answering over linked geospatial data," in *Proc. 12th Workshop on Geographic Information Retrieval (GIR) @ ACM SIGSPATIAL*, 2018, Article 7, pp. 1–10. DOI: 10.1145/3281354.3281362.

[11] G. Mai, W. Huang, J. Sun, et al., "On the opportunities and challenges of foundation models for GeoAI (vision paper)," *ACM Trans. Spatial Algorithms Syst.*, vol. 10, no. 2, Article 11, 2024. DOI: 10.1145/3653070.

[12] S. Hou, H. Jiao, Z. Liu, et al., "GeoSQL-Eval: First evaluation of LLMs on PostGIS-based NL2GeoSQL queries," *Expert Systems with Applications*, 2025. DOI: 10.1016/j.eswa.2025.10353.

[13] dbt Labs, "MetricFlow," Online documentation, `https://docs.getdbt.com/docs/build/about-metricflow`, accessed 2026-05-04.

[14] Q. Min, Y. Shi, and Y. Zhang, "A pilot study for Chinese SQL semantic parsing," in *Proc. EMNLP-IJCNLP*, 2019, pp. 3652–3658. DOI: 10.18653/v1/D19-1377.

A Figure index for the camera-ready version

For brevity in the initial-review draft, the in-line architecture figure (Figure 1) and the cross-domain comparison figure (Figure 2) are rendered directly in TikZ. The camera-ready version should additionally provide (i) a graphical abstract that includes an example natural-language query, the semantic tokens extracted from it, and the grounded prompt that is sent to the SQL generator, and (ii) a per-category bar chart for the GIS benchmark split into spatial-query accuracy and robustness success rate.