ContractKV: Certified Prompt Compilation for Transactional Prefix Reuse in Multi-Tenant LLM Services

Bin Zhou and Xi Cao, *Member, IEEE*

***Abstract*—Repeated context reduces LLM serving cost only when a serving engine can reuse its physical KV state. Dynamic questions and observations often interrupt that prefix, while reordering can change generation and expose unsupported state to later tenants. We present ContractKV, a service control plane that governs prompt layout, behavioral evidence, and shared-state publication together. Its compiler constructs dependency-valid stable-prefix layouts; scoped certification checks model-generated token paths and termination; Prefix-Selective Transactional Promotion publishes only the exact, block-aligned certified prefix; and Service-Template Certificates bind authorization, version and lifecycle so admission costs can be shared across tenants. On six source-disjoint HotpotQA and RepoBench templates, Qwen3-8B, Mistral-7B and Llama-3.1-8B achieve 1.619×, 1.109× and 1.070× full-cost throughput in three paired fresh-process repetitions under greedy decoding. These zero-slack measurements charge successful and failed qualification and waiting. All 1,296 admitted compiled future pairs retain their raw output token IDs. Separately, deployment-qualified controls reduce verifier calls from 125 to five and unhidden verification cost from 25.05 to 3.24 ms/request. At a fixed 80%-load point with 25 tenants per template, an open-arrival study raises 500-ms SLO goodput from 0.173 to 0.831 requests/s. These distinct protocols connect behavioral admission to actual service gains: a reusable prefix becomes a governed object whose qualification, visibility and amortization can be managed explicitly.**

***Index Terms*—Large language model serving, KV cache, prefix caching, behavioral certification, transactional publication, multi-tenant services.**

I. Introduction

Consider a retrieval service that sends the current question before a long set of source documents. Two authorized users ask different questions about the same documents. Almost all of the document text repeats, yet native prefix caching stops at the first changed question token. This order occurs in a fixed revision of Azure's public RAG demonstration, whose conversation history and question precede the retrieved sources [1]. The opportunity is concrete: move reusable context ahead of changing fields, and subsequent requests can reuse a longer physical KV prefix.

The difficulty is deciding when that transformed state is suitable for a shared service. A dependency-valid reorder can still change an autoregressive model's answer. A development NarrativeQA case retained its compiled witness when metadata changed the raw answer (Section VI-C). A speculative candidate can also enter the shared cache before its qualification finishes. These are linked service decisions: admissible layout, applicable behavioral evidence, and authorized publication. Addressing only the layout leaves later tenants dependent on an unchecked execution artifact.

Existing systems establish several ways to exploit repeated context. PagedAttention and RadixAttention manage exact-prefix sharing [2], [3]; Prompt Cache exposes reusable modules [4]; CacheBlend and EPIC reuse context across positions through different execution mechanisms [5], [6]. Application-aware systems such as Parrot expose dependencies to the serving layer [7]; row/field reordering also improves reuse in relational analytics [8]. ContractKV addresses the complementary control-plane question: *what evidence and identity permit a transformed prefix to become shared state?*

We argue that reusable KV should be governed as a service object: its layout, behavioral evidence and transactional visibility must share one validity binding. The same binding that authorizes a compiled layout governs the state visible to later requests. Four mechanisms implement this idea. The *Contract-Aware Layout Compiler* (CALC) exposes stable leading content while preserving registered dependencies. *Scoped Behavioral Certification* associates model-backed token-path evidence with an input and execution scope. *Prefix-Selective Transactional Promotion* (PSTP) keeps candidate state private until a valid pass, then commits only the eligible stable blocks. A *Service-Template Certificate* binds identity, authorization, and lifecycle so that qualified requests can share the object and its admission cost.

The Service-Template Certificate makes the prefix and its qualification cost shareable under versioned authorization. Distinct behavioral scopes may refer to the same physical object. Section IV-C defines the witness and cost units for deployment-qualified registration and stricter query-qualified execution.

The evaluation closes the argument from two directions. First, six source-disjoint HotpotQA/RepoBench templates yield 1.619×, 1.109×, and 1.070× zero-slack full-cost throughput across three models; all 1,296 admitted compiled future pairs preserve raw output IDs. Second, deployment controls hold layout fixed while template scope reduces verifier calls 25-fold and unhidden verification exposure 7.7-fold. A separate open-arrival study adds 0.658 compliant requests/s at its fixed 80%-load point, and density replay over 10–80 authorized identities demonstrates physical consolidation. These results

B. Zhou is with Beijing University of Chemical Technology, Beijing 102218, China (e-mail: 2025200800@buct.edu.cn).

X. Cao is with Beijing University of Chemical Technology, Beijing 102218, China (e-mail: caoxi@buct.edu.cn).

Corresponding author: Xi Cao.




Fig. 1. ContractKV makes a compiled stable prefix an evidence-bound service object. CALC repairs a structural prefix gap; one of two separately evaluated witness protocols supplies scoped token-path evidence; PSTP commits eligible state only after PASS and a valid binding. Authorized tenants of the same template share the prefix and keep changing suffixes private. The deployment certificate and controlled-client query records are distinct (Table II); their prefix associations refer to the same physical object. The commit cut excludes incomplete blocks and private suffixes.

test behavioral admissibility and service economics within their respective protocols.

The paper makes four contributions, each connecting a mechanism to observable service behavior:

- **Contract-aware compilation** of bounded, dependency-valid layout candidates with exact rendered-token identities (Section IV-B).
- **Scoped model-backed admission** that binds token-path and termination evidence to declared inputs and execution conditions, evaluated with real free-running generation (Sections IV-C and VI-C).
- **Transactional KV publication** at an exact-LCP, block-aligned commit boundary, with zero promotion for rejected candidates (Sections IV-D and VI-D).
- **Service-Template Certificates** that bind authorized, versioned prefix reuse to its lifecycle and make qualification shareable across tenants, with measured 25-fold call amortization, SLO service benefit and physical consolidation (Sections IV-E, VI-B, and VI-D1).

II. Background and Motivation

A. The Gap Between Repetition and Prefix Reuse

A causal language model first computes prompt states during prefill, then generates output autoregressively. Native prefix caching reuses a leading sequence whose tokens and cache identity match a resident entry [2], [3]. For fully rendered prompt $\mathbf{t}$, let $\mathcal{P}(\mathcal{R})$ be the token prefixes represented by resident state under the matching cache identity. The block-aligned reuse opportunity is

$$\begin{aligned} k^* &= \max\{k : \mathbf{t}_{1:k} \in \mathcal{P}(\mathcal{R})\}, \\ k_B(\mathbf{t}, \mathcal{R}) &= B\,\lfloor k^*/B \rfloor\,, \end{aligned} \tag{1}$$

where B is the block size. Byte-identical text outside that leading sequence offers a layout opportunity. Its KV state also depends on preceding tokens and positions [2].

The Azure template in Section I establishes a realizable prefix-breaking order [1]. The following controlled traces independently measure the reuse gap; they do not estimate that application's traffic or sharing frequency.

B. Measuring the Structural Opportunity

We reconstruct stability and native reuse from actual API prompt IDs, the frozen renderer's segment spans, and scheduler-recorded prefix hits. Let n_r be the prompt length, S_r the set of token positions fully contained in manifest-declared stable body segments, and h_r the measured native hit length. Three distinct token-weighted quantities are

$$\begin{aligned} \rho_s &= \frac{\sum_r |S_r|}{\sum_r n_r}, \qquad \rho_h = \frac{\sum_r h_r}{\sum_r n_r}, \\ \rho_{s|h} &= \frac{\sum_r |S_r \cap \{1, \ldots, h_r\}|}{\sum_r |S_r|}. \end{aligned} \tag{2}$$

The first describes stable content, the second all native hits, and the third recovery of the stable body itself. The full-prompt denominator includes chat-control tokens and headings; the

TABLE I
MEASURED STRUCTURAL OPPORTUNITY IN THE SIX-TEMPLATE, TASK-PRESERVING COHORT. EACH ROW CONTAINS 1,620 FUTURE RAW REQUESTS ACROSS THREE REPETITIONS. RATIOS ARE TOKEN-WEIGHTED AND USE EQ. (2).

Model	Stable body ρ_s	Native hits ρ_h	$\rho_{s\|h}$
Qwen3-8B	98.520%	0.950%	0.030%
Mistral-7B	98.477%	0.985%	0.034%
Llama-3.1-8B	98.357%	1.114%	0.031%

stable body excludes wrappers and cross-boundary tokens. Source-macro averages are calculated separately.

Table I shows substantial stable content but little native recovery in the controlled traces. Supplementary Tables S-I/S-II give all five families' prepared/serving orders and measured token displacement.

C. From a Layout Opportunity to a Shared Service Object

Continuity leaves two service decisions: which legal layouts have evidence for the intended behavior, and which candidate blocks may become atomically visible to authorized consumers. An overbroad qualification or stale identity can affect tenants beyond the request that created the state.

qualification authorizes reuse, publication exposes an eligible prefix, and residency determines the reuse actually obtained.

III. SERVICE MODEL AND DESIGN OBJECTIVES

A. Structured Requests and Registered Dependencies

A structured request $r = (s_1, \ldots, s_m)$ contains application segments. Each segment carries an identifier, original content, a stability type, and a registered content identity. We retain three types: STABLE, MUTABLE, and QUERY. Stable content belongs to an immutable template version; mutable content includes observations and changing state; query content carries the current task. A query may recur within an authorized directory while remaining outside the promoted stable prefix.

The trusted operator manifest defines segment boundaries, separators, stability, dependencies, and the sharing domain (Section VIII-B). Unregistered tenant content remains private. A segment dependency graph $G_r = (V, E, \lambda)$ associates each edge with a data, causal, or positional ordering constraint. A layout π is legal when it is a topological order of G_r:

$$(s_i, s_j) \in E \quad \Longrightarrow \quad \mathrm{pos}_\pi(s_i) < \mathrm{pos}_\pi(s_j). \tag{3}$$

All cache identities and prefix boundaries are computed from the fully rendered prompt $\mathbf{t}_\pi$, including the model's chat template. Per-segment token counts guide construction, but exact boundaries follow retokenization; concatenation can change tokenization at segment edges. Let $P(\pi)$ denote the token boundary of the leading shareable stable content. CALC provides a bounded candidate set $\Pi_L(G_r)$ containing raw order L0 and registered compiled levels. Behavioral qualification selects among these legal candidates.

B. Templates, Qualifications, and Cache Identity

A service template

$$\Theta = (V, \mathbf{S}, \mathcal{A}, \mathcal{P}, \mathcal{M}, F) \tag{4}$$

binds a version V, stable content $\mathbf{S}$, an authorized tenant set $\mathcal{A}$, a frozen policy $\mathcal{P}$, its manifest $\mathcal{M}$, and declared fan-out F. The input may interleave stable and private segments; stable-first order is a compilation result.

ContractKV uses two related identities. A *behavioral qualification* determines whether a request may use a particular compiled layout. A *stable-prefix identity* identifies the corresponding reusable KV prefix within its authorized template namespace. Several admitted query scopes can map to the same stable-prefix identity.

Execution identity binds the model, tokenizer/chat template, decoding/stopping settings, policy and runtime. Section IV-E defines the complete template and lifecycle binding.

C. Publication and Service Objectives

ContractKV aims to turn admissible structural reuse into lower complete service cost while preserving the following publication properties.

P1: Evidence-gated publication. Candidate compiled state becomes shared only after a completed verifier pass and a valid publication binding.

P2: Stable-prefix confinement. PSTP publishes complete blocks within the stable, certified, exact-match boundary. Mutable and query suffixes are excluded from this promotion.

P3: Atomic failure handling. A failed, incomplete, expired, or conflicting transaction contributes no newly promoted candidate blocks. Raw-order execution remains the service fallback.

P4: Authorization-bound reuse. The deployment control path validates template identity and authorization before admitting reuse, and separates cache namespaces across incompatible sharing domains.

These properties concern admission and publication. We assess behavior with paired free-running outputs and task scores, and efficiency with native hits and complete service wall time.

IV. CONTRACTKV DESIGN

ContractKV compiles a legal prefix, qualifies its behavior, and transactionally publishes it for authorized reuse (Fig. 1). Qualification and physical residency have separate lifetimes.

A. An End-to-End Request Example

A changing observation precedes a stable document. CALC moves eligible document content forward; the first raw business reply supplies a query witness. A successful check commits eligible stable blocks for later authorized requests. A new query needs its own decision but may share the prefix identity. Rejection retains the raw reply and promotes no candidate state.

B. Contract-Aware Layout Compiler

CALC operates on the registered dependency graph. Stable segments may be split into contiguous, character-preserving units to construct a bounded layout ladder. A stable-priority topological traversal moves only eligible units, respects dependency edges, and breaks ties by original order. For the 16-unit ladder, L1, L2, and L3 expose 4, 12, and 16 eligible units, respectively; L0 retains raw order. Full retokenization determines the actual stable-prefix boundary of each rendered candidate.

A source-disjoint development stage establishes the allowed model–family–layout combinations and freezes the policy before evaluation. The deployment studies use the registered ladder and its allowed descent policy. The final query-qualified implementation chooses one development-fixed candidate per scope and performs at most one GPU qualification attempt. Inherited L0 families retain raw execution.

The task-preserving renderer keeps essential fields and source whitespace intact (Section V). For an expanded graph $G' = (V', E')$, priority topological construction costs $O(|E'| + |V'| \log |V'|)$ per fixed candidate; model-backed qualification remains the dominant admission work.

C. Scoped Behavioral Certification

1) Witnesses and token-path checks: A behavioral witness is a completed model-generated output trajectory associated with a rendered input and execution identity. Query-qualified execution obtains it from the actual first raw business response, avoiding a separate raw generation solely to create a reference. Write its nonterminal witness tokens as $\mathbf{y} = (y_1, \ldots, y_L)$ and its natural terminal token as e; the recorded output IDs include both. The verifier evaluates the compiled prompt on the forced history $\mathbf{y}$, including termination.

For token z at output position i, define its next-token margin as

$$m_i(x, z) = \log p_\theta(z \mid x, \mathbf{y}_{<i}) - \max_{v \neq z} \log p_\theta(v \mid x, \mathbf{y}_{<i}). \quad (5)$$

The raw witness supplies its own per-position margins. The candidate must choose each witness token, and the terminal token, as its top choice. In the evaluated query-qualified protocol, the raw floor is 0.0625 and the candidate and terminal floors are 0.125:

$$\begin{aligned} m_i(x_{\mathrm{raw}}, y_i) &\geq \tau_{\mathrm{raw}}, \\ m_i(x_{\mathrm{cand}}, y_i) &\geq \tau_{\mathrm{cand}}, \quad i = 1, \ldots, L, \\ m_{L+1}(x_{\mathrm{cand}}, e) &\geq \tau_{\mathrm{cand}}. \end{aligned} \quad (6)$$

The raw terminal margin is also checked. Complete witness IDs, finite margins, the stop protocol, and the publication boundary are required for acceptance. The task-score threshold used in evaluation is separate from these model-level conditions.

For identical next-token distributions at verification and execution, agreement through the terminal token yields the same greedy sequence by induction. Finite-precision and execution-shape differences make this an execution condition, not a universal runtime theorem. Scope binding separately specifies which subsequent input instances may consume that evidence; free-running experiments measure their actual behavior. Greedy decoding, the output budget, stop settings, and model/runtime identity are part of the evaluated execution protocol.

TABLE II
TWO EVALUATED QUALIFICATION PROTOCOLS SHARE THE IN-ENGINE VERIFIER/PSTP BACKEND, WITH DISTINCT REQUEST-SIDE ADMISSION RECORDS AND CHECKS.

	Deployment-qualified	Query-qualified
Witness	Compiled trajectory on a development-qualified route	First real raw business reply in the selected scope
Admission	Authenticated template binding and lifecycle checks	Controlled-client lookup at $(\mathrm{namespace}, q)$
Identity	Model/runtime, version, layout, policy, authorization, epoch	Exact bound inputs/settings and policy; prefix association at $(\mathrm{namespace}, H_s)$
Cost unit	$O(1)$ attestation per registered template	$O(U)$ decisions for U scopes; at most one GPU attempt per selected scope
Evidence	Registration, amortization, open arrival and density	Free-running task pairs and complete service wall

2) Qualification scope and request binding: Table II distinguishes the two evaluated paths. Deployment registration attests a representative compiled-prompt trajectory on a prospectively qualified model–workflow–layout route; later private inputs are supported by that prior qualification and the separate template-quality audit. Query-qualified execution instead uses an actual raw business reply. Its scope key q hashes the exact query, system message, stable segments, model identity, generation settings/budget, renderer and policy.

The query-qualified experiments permit a declared metadata-only observation schema containing session identity, turn, and status, with no additional answer evidence. History and scratchpad segments are outside that schema. The shared-scope eligibility rule accepts a short, non-abstaining reference of at most 16 normalized words when it is a literal stable-context span, or when its raw minimum margin is strictly above 0.125. References failing this rule are classified as requiring an exact-observation scope; the evaluated trace declares no such repeated observations, so those requests remain raw. A further Python statement check is retained for the declared RepoBench subset. These frozen eligibility conditions define the empirical class; metadata typing and positive margins alone do not prove future invariance.

3) Compact in-engine verification: The verifier runs on the serving model backend. Previously approved, hash-matching resident prefix blocks can be reused during verification; a one-block guard and the answer/stop checks protect the verification boundary. The executor collects the rows needed for the witness and termination rather than exporting full prompt-logprob tensors. It returns a compact decision and publication record.

D. Prefix-Selective Transactional Promotion

PSTP makes a verifier decision a shared-cache event. Candidate KV initially resides outside the shared prefix index. The state machine advances through PRIVATE, VERIFYING, VERIFIED, and COMMITTED; unsuccessful paths end in ABORTED.

Algorithm 1 Single-shot query qualification. All work remains on the service clock.

Require: Registered Θ, request r, frozen policy
Render raw input; derive scope q; look up (Θ, q)
if an issued qualification matches this request **then**
  Check compiled-prefix identity; serve with native lookup
  return the business response
end if
Apply the pre-reference gate; serve r in raw order
if q is new and selected for qualification **then**
  Reserve q; retain the actual raw response as witness
  if witness/scope/output checks and post-reference gate pass **then**
    Verify one frozen candidate on witness tokens and EOS
    if PASS and valid publication binding **then**
      PSTP commits the eligible prefix; record qualification
    else
      Abort with zero candidate promotion; record rejection
    end if
  else
    Record the raw-route decision without GPU qualification
  end if
end if

Let L_s be the candidate's stable boundary, L_{cert} the authorized prompt-prefix boundary, and L_{lcp} the exact token LCP between the candidate request and its certified prompt. The promoted length is

$$L_{\mathrm{commit}} = B \left\lfloor \frac{\min(L_s, L_{\mathrm{cert}}, L_{\mathrm{lcp}})}{B} \right\rfloor. \tag{7}$$

The scheduler-thread insertion of the eligible block hashes is the publication linearization point. The corresponding KV tensors are already allocated; commit changes their visibility in the shared index rather than copying the tensors.

A non-pass, incomplete result, timeout, duplicate transaction, identity conflict, or invalid scope prevents new candidate publication. Cleanup releases private candidate resources. Raw execution can still populate the engine's ordinary cache, so the transactional property is about candidate promotion rather than freezing the entire cache domain.

After a successful commit, the native cache manager governs residency and reference counts. Its reclamation of an unreferenced block removes a physical reuse opportunity without invalidating the behavioral evidence. A later admitted request can recompute a missing prefix under the qualified layout. Section VI-E verifies this separation using actual lookup, publication, and reclamation events.

E. Service-Template Certificates and Amortization

A service-template certificate organizes the identity and lifecycle of reusable compiled state. The deployment representation is

$$C_\Theta = \langle I, V, H_s, L, P, Q, A, E, \Sigma \rangle, \tag{8}$$

I identifies the model/runtime execution, V the template version, H_s its stable content, L its layout, P the verifier policy, Q the qualification manifest, A the authorization domain, E the epoch, and Σ the authentication tag. The authenticated deployment path uses HMAC-SHA256 and checks the complete binding before forwarding a request.

The controlled query client keeps admission decisions at $(\textit{namespace}, q)$ and prefix associations at $(\textit{namespace}, H_s)$; these are records, not a second backend-signed certificate. Several query decisions may authorize the same physical prefix. Changed bindings prevent reuse; changed deployment objects require lifecycle re-registration.

For N sessions sharing a deployment template, registration changes from $O(N)$ session attestations to $O(1)$ template attestation plus per-request checks. With T template identities and U query scopes, the controlled client uses $O(T+U)$ state and the $O(U)$ decisions in Table II. Fan-out amortizes these decisions when the authorized query directory is fixed.

F. Benefit Admission

Qualification consumes service resources before later requests realize savings. ContractKV therefore separates the decision to *invest in evidence* from the decision to *accept the candidate*. A frozen benefit policy estimates remaining authorized uses, marginal prefill savings, information-gathering cost, and GPU verification cost. In the two-stage query-qualified controller, the pre-reference estimate has the form

$$\widehat{G}_{\mathrm{pre}} = \widehat{p}_E \widehat{p}_{P|E} \widehat{R} \widehat{\Delta t} - \widehat{C}_{\mathrm{info}} - \widehat{p}_E \widehat{C}_{\mathrm{GPU}}. \tag{9}$$

After an eligible witness is available, the GPU decision uses the conditional pass estimate and the full predicted GPU cost. Observed prefix publication selects the calibrated cold/warm cost state, and the gate discounts native reuse already available to raw execution. Predictions are frozen before held-out evaluation.

The evaluated default applies a predicted waiting-budget test in cold sessions and uses expected aggregate benefit in template fan-out. We evaluate a separate length-aware waiting-budget variant in Section VI-E. Benefit admission can reduce qualification attempts; it never substitutes for the token-path or publication checks.

V. Implementation and Measurement

A. Integration with the Serving Engine

The prototype targets the vLLM 0.10.2 V1 scheduler and cache manager. It comprises a request-side compiler and qualification controller, an in-engine verification executor, and PSTP hooks at cache-index publication. Model weights and attention kernels remain unchanged. Candidate identities are derived after full prompt rendering and tokenization. Verification and compiled business requests use the policy hash and template namespace in their cache salt.

Table II gives the request-side boundaries: an authenticated deployment proxy checks the HMAC template binding and lifecycle, whereas the controlled query client checks its frozen identities, scope decision and prefix association. Both invoke the in-engine verifier/PSTP path. The separate manifest-validation helper in Section VIII-B is not an integrated endpoint check.

Compiler and publication overheads measured in the deployment implementation are 0.389 ms mean for CALC, 0.249 ms for the residency lookup, 0.109 ms for the template-scope check, and 0.636 ms for PSTP finalization. The query-qualified studies measure their complete controller path afresh rather than importing these component timings as constants.

B. Task-Preserving Input Construction

The adapter retains each source in full when it fits the common 16K window. Otherwise a fixed head/tail rule crops optional paragraph/code-line substrings, protecting the complete question and code prefix, original order/whitespace and an omission ledger. Selection never inspects answers, outputs, scores, margins or qualification. Adjacent pieces of one source segment remain contiguous in both routes.

Both routes receive the same retained content, checked against every declared model/tenant/turn/layout condition including chat template and output reserve. Independent tokenization is compared with actual API prompt IDs. Common offline packing is reported separately; request rendering, planning and verification remain on the service clock.

The input-construction experiment compares fixed-word-cap, whitespace-normalized packing with structure-preserving rendering under the same window, admission rules and scorer. This isolates how task-critical content affects absolute quality and admissible reuse (Section VI-F).

C. Execution Environment and Timing

The primary hardware is two RTX 3090 GPUs with 24 GB each. Single-model cells use one GPU; Qwen3-14B uses tensor parallelism across two GPUs in the deployment evaluation. The query-qualified environment is Python 3.10.20, PyTorch 2.8.0+cu128, vLLM 0.10.2, transformers 4.55.2, Triton 3.4.0, and FP16. Model checkpoints, tokenizers, runtime files, inputs, and policy identities are recorded per cell. The primary task-preserving cells use two concurrent requests; ten registered tenants per source describe sharing fan-out, not ten simultaneous GPU requests.

A fresh server process is used for each cell. The closed-loop client runs one tenant pair through ten rounds, then advances to the next pair. The next round becomes ready when the preceding business wave finishes; synchronous qualification performed between waves contributes to subsequent readiness delay. For request r,

$$T^{\mathrm{ready}}_{\mathrm{TTFT}}(r) = t_{\mathrm{first}}(r) - t_{\mathrm{ready}}(r). \tag{10}$$

Full service wall includes all business responses, first-use raw witnesses, planning, information and verification calls, unsuccessful attempts, waiting, scoring, logging, and final drain. Server startup, common pre-measurement infrastructure checks, configuration loading, and immutable input preparation have separately declared boundaries.

Closed-loop throughput is completed business requests divided by full service wall. The paired multiplier is the raw wall divided by the ContractKV wall for an equal request population. In the separate fixed-arrival deployment studies, SLO goodput counts responses meeting a specified readiness deadline per unit service time. Their arrival traces and workload protocol are reported separately.

Broad deployment measurements use an explicit residual-verification accounting rule,

$$C_{\mathrm{exposed}} = \max(C_{\mathrm{verify}} - \Delta_{\mathrm{slack}}, 0), \tag{11}$$

with 2,000 ms slack for Qwen/Mistral and 6,000 ms for the broad Llama protocol. All new query-qualified results use the directly measured complete service clock with zero slack. Component RPC sums provide a work breakdown alongside the directly measured wall clock.

D. Physical Accounting and Reproducibility

At initial scheduler allocation, actual prompt IDs and native hit count h_r give $n_r - h_r$ newly required prefill tokens, with separate verification counters. These measure work; latency is measured directly.

Source groups, policy settings, and selection rules are frozen before each independent cohort is opened. Repetitions use new processes and recorded device/policy assignments. Statistical summaries preserve source-template clusters and process repetition; tenant and query repetitions remain within their source cluster. The artifact supplies request-level data, model/runtime manifests, source snapshots, scripts, and archive checksums. The supplemental record preserves the extended tables and unsuccessful variants.[1]

VI. Evaluation

We test one service-level claim: governing the layout, evidence and publication of a reusable prefix can produce useful, amortized service state. The evidence proceeds from template economics and full-cost execution to behavior, governance, scale and operating conditions. Each regime retains its own source set, qualification unit and clock.

A. Workloads, Controls, and Units

The primary cohort contains three HotpotQA and three RepoBench sources, chosen by frozen hash order after excluding 567 previously used sources [9], [10]. Reading-comprehension data come from the LongBench collections [11]. Each source defines a ten-tenant, ten-round template with three recurring query wrappers and changing private metadata. This is an explicitly repeated authorized directory, not a measured production query distribution.

We run Qwen3-8B, Mistral-7B-Instruct-v0.3, and Llama-3.1-8B-Instruct [12]–[14]. Both policies have the same 16K window, retained task content, greedy decoding, fixed seed, request order, and two-request wave clock. HotpotQA has a 128-token generation budget and RepoBench 384. *Raw* retains the original order with native APC; *ContractKV* uses the frozen candidate, eligibility, margin/EOS checks, and publication path. Mistral and Llama inherit the development-frozen RepoBench L0 route.

Every model/policy uses three fresh processes. Each run completes 600 business requests, including 540 future requests. Thus the study contains 10,800 business generations and 4,860 future raw/strategy pairs. Six sources are the independent content units; tenants, rounds, and processes are nested observations. Throughput ranges are process min–max; confidence

[1] https://github.com/zhouz4884-coder/contractkv. The experimental evidence is pinned to commit `9bf891af`; full paths and hashes are listed in the supplementary evidence register.

TABLE III
DEPLOYMENT-QUALIFIED BREADTH OVER FIVE WORKFLOW FAMILIES, THREE REPETITIONS/CONFIGURATION. NET TTFT CHARGES RESIDUAL VERIFICATION AFTER THE STATED SLACK; PREFILL USES THE SAME COHORT.

Configuration	Net TTFT reduction	Prefill	Slack (s)
Qwen3-8B	37.81%	59.13%	2
Qwen3-14B TP=2	44.69%	60.57%	2
Mistral-7B	31.72%	39.46%	2
Llama-3.1-8B	29.41%	30.97%	6

intervals resample source-template clusters and repetitions. Separate cohorts and comparisons sharing raw controls are not pooled as independent trials.

We retain prompt/output IDs, task scores, routes, qualifications, timing, and cache counters. QA uses the frozen token-F1 scorer; code uses the existing SequenceMatcher-based edit-similarity adapter. These are declared benchmark adaptations. Material score changes use $|\Delta s| > 0.03$; exact ID agreement is measured separately. The supplement gives all six sources' utility, compiled coverage and paired tails, plus process values and clock definitions.

B. Does Governed Reuse Repay Qualification?

The mechanism predicts two gains: sharing a qualification reduces its cost per use, and a legal resident prefix reduces repeated prefill. We test their economic units separately. With layout and locality held fixed, deployment-template registration reduces verifier calls from 125 to five per trace and unhidden verification exposure from 25.05 to 3.24 ms/request (Fig. 4). The 25-fold call reduction arises from registering an authorized shared object rather than each consuming session.

Table III tests five-family breadth in four deployment configurations, including 14B tensor parallelism: net mean TTFT improves 29.41–44.69% under residual-verification accounting. The independent zero-slack registration-cost supplement has its own inputs and amortization denominator; it is not a matched slack ablation of these rows. Execution-clock SLO statistics are also reported separately.

We expect a net gain when enough admitted requests reuse a stable prefix to repay first-use qualification. Figure 2 tests this on the same source set, with no tool slack and successful and failed attempts included. Throughput improves by 1.619× on Qwen, 1.109× on Mistral, and 1.070× on Llama. The process ranges are 1.615–1.623×, 1.107–1.110×, and 1.068–1.072×. These are complete service gains rather than prefill-only estimates.

Figure 2(b) measures the work saved: including qualification, total new-prefill counts fall by 45.44%, 14.64%, and 10.89%. These scheduler observations are workload counts, not inferred GPU time. Directly measured mean readiness falls by 43.87%, 12.09%, and 3.99%.

The throughput result does not imply lower tails. All p99 point estimates increase (Table IV); Mistral's source-cluster/repetition interval for p99 reduction is wholly negative, [-60.576, -0.137]%. Mean reduction intervals are [5.640, 79.479]%, [-0.350, 34.781]%, and [1.550, 5.724]%. The cohort

TABLE IV
TAIL COST AND ADMITTED COVERAGE IN THE PRIMARY COHORT. READINESS STATISTICS CONCERN FUTURE REQUESTS. FULL PROCESS RANGES AND SOURCE-CLUSTER INTERVALS ARE IN THE SUPPLEMENT.

Model	Compiled / future pairs	p99 raw → CKV (ms)
Qwen	684 / 1,620	8,561.8 → 9,146.6
Mistral	342 / 1,620	9,418.2 → 9,511.3
Llama	270 / 1,620	7,851.3 → 7,905.7

therefore supports a full-cost execution benefit with source-dependent latency effects.

A separate six-source Qwen cohort supplies an independent content check: unchanged ContractKV reaches 1.803× throughput (process range 1.798–1.808×) and 774/1,620 compiled future pairs. It is a second cohort, not an additional model bar or another repetition of Fig. 2.

Finding: object-level admission can repay its measured cost under both declared regimes; the zero-slack task result does not depend on the deployment slack accounting.

C. Does Qualification Preserve Observed Behavior?

Compilation must obtain its gain within the admitted behavioral scope. Figure 3 reports both scope coverage and free-running evidence. All 1,296 compiled future pairs have identical output IDs and unchanged scores. Including initial business rounds gives 1,440 compiled pairs with the same outcome. HotpotQA contributes compiled requests for every model; Qwen additionally admits RepoBench, whereas Mistral/Llama keep the inherited L0 route.

Behavioral preservation and absolute utility remain different outcomes. Qwen's 684 admitted raw references all receive positive score credit; the counts are 258/342 for Mistral and 90/270 for Llama. Llama preserves 180 zero-F1 future references from two HotpotQA sources, and Mistral preserves 84 from one source. Neither exact agreement nor positive partial credit establishes semantic correctness.

Across all business routes, material score increases/decreases are 0/0 for Qwen, 2/1 for Mistral, and 5/3 for Llama. All changes occur on L0; the Mistral decrease is in an initial request and the Llama decreases are future requests. Corresponding output variants appear in scheduled raw-only repeats, demonstrating background variation, but not proving that every L0 event is unrelated to policy-associated execution conditions.

The separate 50-source bounded-input audit retains 2,442 compiled future pairs: 2,178 RULER, 174 NarrativeQA and 90 RepoBench [15]–[17], with zero compiled ID changes and 33 all-route decreases on L0. Each model's RULER coverage is 726/810 (210/270 cold, 516/540 fan-out). Figure 3 separates this fixed-cap, mixed cold/fan-out protocol from the faithful non-RULER matrix.

a) Why the scope matters.: A broad-wrapper development protocol admitted later wrappers and produced 108 material decreases among 3,672 compiled pairs. A Qwen NarrativeQA development case changed its raw answer under an allowed turn-field change while the compiled answer retained the witness, despite a 0.40625 candidate margin. The evaluated eligibility class was frozen before the independent sources were opened.




Fig. 2. Strict query-qualified performance on six source-disjoint HotpotQA/RepoBench templates, three processes/model, faithful 16K inputs, and zero slack. (a) Throughput charges all business responses, qualification, failed attempts, and synchronous waiting. (b) Actual business plus qualification new-prefill counts per run; orange caps mark certification work at its true scale, with exact added counts below. (c) Mean readiness TTFT over future requests uses the frozen two-request wave clock. Three-repeat values and tail statistics are reported separately.

A margin alone cannot justify extending evidence to unseen dynamic inputs.

b) Actual output horizon.: Separate conditions produce and verify naturally terminated outputs of 642 tokens for Qwen, 769 for Mistral, and 578 for Llama, each with six correct future pairs across three processes. They use explicitly declared 128/128/192-item schemas. Llama's 224-item condition omits the final 100 items and remains a task failure. These results establish actual 512+ output conditions, not universal long-output correctness.

Finding: admitted free-running behavior is preserved in the measured scopes, while coverage and absolute reference utility remain explicit.

D. Does Governance Preserve the Service Benefit?

Figure 4 isolates governance from layout opportunity. D1 uses a prequalified layout without online registration; D2 adds verification and transactional registration. At the same 500-ms SLO, native D0, D1 and D2 deliver 0.066, 1.472 and 1.428 requests/s. D2 retains 97.0% of D1 goodput, paying 0.044 requests/s (3.0%) for governance; TTFTs are 194.95/194.72 ms. D0 supplies context and D1 the layout-matched comparison.

Behaviorally harmful, dependency-valid candidates provide the complementary test. In each of two controlled 20-case sets, all ten harmful candidates are rejected with zero newly promoted candidate tokens. A 14B control also checks actual post-decision outputs against raw scores. Live hook, concurrency, cancellation, duplicate, timeout and authenticated-binding controls exercise publication. The separate 325,000-operation stress study tests the in-memory state machine and is not counted as GPU serving evidence.

1) The unit of amortization: The fixed-layout amortization in Section VI-B changes the registration unit rather than the physical layout: prefix hits remain 97.82%/98.19%. Template identity therefore lets the platform share the evidence cost without surrendering the qualification or publication boundary.

Query-qualified execution has a different amortization unit. The second Qwen cohort obtains 774 compiled future pairs from 27 issued scope-repeat decisions and 42 total GPU calls, including failures. Its cost grows with distinct selected scopes, then amortizes across tenants using them. This preserves the template prefix as the physical object without assigning deployment's $O(1)$ behavioral cost to arbitrary dynamic queries.

Figure 5 tests a separately qualified deployment workload at fixed arrival loads and in bounded-concurrency density replay. At 25 tenants per template and 80% calibrated arrival load, 500-ms goodput rises 0.173 to 0.831 requests/s: +0.658, with a hierarchical-bootstrap 95% interval of [0.539, 0.765] requests/s (supplement). The density experiment then tests whether the shared object remains useful as authorized fan-out increases. Across 10–80 registered identities, ContractKV sustains 9.408–11.072 tiered-SLO requests/s, compared with 0.900–1.152 for native APC (Supplementary Table S-III). At 80 identities, used blocks decrease by 71.9%, leaving 381 more free blocks. Density goodput and block values come from the same cells, but do not isolate headroom as the sole cause of improved throughput. These marker-bearing service traces have a separate task-quality audit and are distinct from the task-bearing primary cohort.

Finding: publication governance retains the frozen layout's service benefit, and the template object supports measurable cost sharing and physical consolidation across tenants.

E. What Determines the Operating Region?

The object pays off when authorized reuse is sufficiently dense and its physical state remains available. Figure 6 varies these conditions with a frozen deployment workload. Benefit rises sharply over an observed sharing interval, but round-robin access to a larger working set nearly eliminates it. A qualified




Fig. 3. Qualification coverage and free-running evidence. (a) Each model/task cell has 810 future pairs; hatched cells inherit L0. The separate RULER strip uses bounded inputs and pooled cold/fan-out traces, not the faithful matrix protocol. (b) Output-ID differences and raw-reference positive-score counts within compiled subsets. Positive credit is not complete correctness. (c) One logged Qwen/HotpotQA witness, PASS, committed prefix and later identical output; full records are archived.




Fig. 4. Separate deployment controls. (a) Registration granularity with fixed layout/locality; three processes and 1,125 future requests/trace. (b) Each 8B/14B TP2 probe rejects 10/10 harmful candidates with zero rejected-candidate promotion. (c) Same-engine D0/D1/D2 500-ms SLO goodput; whiskers are five-process min–max, not confidence intervals.

object still needs resident physical blocks. In the primary cohort, 189 compiled business requests have incomplete hits: 135 Llama zero hits, 42 Mistral zero hits, and 12 Qwen partial hits. All 1,440 compiled business requests match the certified prefix IDs and commit boundary; each incomplete-hit request has a later full-hit peer in its two-request wave.

Three known-source probes replay archived IDs with read-only lookup/publication/reclamation hooks. Among 138 business requests and four qualifications, all 13 incomplete hits follow deletion of the last matching native mapping at reference count zero; salt/hash chains still match. All 12 immediate post-commit controls hit fully. This diagnoses native reclamation [18] in those sources, not every historical miss or serving performance. Figure 2 charges actual recomputation.

The frozen benefit gate selects two of four sealed points (Table V); both selected points are net-positive at 7.04 and 10.84 s/certificate. Rejected points serve raw, while their candidate outcomes remain diagnostics. This validates the declared operating-point rule, not a learned predictor or a claim that diagnostic verifier work was avoided.

A separate length-aware waiting-budget variant illustrates the cost of overly narrow profiling support. On an independent

TABLE V
FOUR SEALED OPERATING POINTS UNDER THE DEVELOPMENT-FROZEN BENEFIT GATE. NET BENEFIT IS PER CERTIFICATE; REJECTED POINTS SERVE RAW. CANDIDATE DIAGNOSTICS WERE ALSO RUN FOR REJECTED POINTS, SO THIS TABLE DOES NOT MEASURE AVOIDED ONLINE VERIFIER CALLS.

Prefix	Uses	Slack (s)	Route	Net benefit (s)
1500	8	3.5	Raw	0.00
3000	12	0.5	CKV	7.04
5000	10	1.5	CKV	10.84
3500	6	6	Raw	0.00

Qwen cohort it lowers p99 from 13,386.9 to 8,801.9 ms but removes useful scopes: compiled coverage falls 774 to 258 pairs and throughput 1.803× to 1.070×. The source/repetition interval for p99 reduction crosses zero. Full development and independent results, including all L0 variations, remain in the supplement; the original query-qualified gate is retained for the main measurements.

Finding: scope determines admissible sharing, and locality, residency and admission cost determine how much of that opportunity becomes service benefit.




Fig. 5. Distinct deployment protocols. (a) Open-arrival 500-ms SLO goodput, with the archived hierarchical-bootstrap interval for the absolute increase at 80% load; 4.81× is that point's ratio. (b) The same 80-identity density cells supply occupancy and goodput under class-specific 750/1,500/3,000-ms SLOs, with a 2,386-block pool. Registered identities are not simultaneous GPU requests.




Fig. 6. Operating region in frozen deployment workloads. (a) The shaded 50–75% sharing interval is an observed transition, not a universal threshold. (b) Access-pattern sensitivity to reuse distance and hot-set skew. Both axes report TTFT reduction; neither is a direct residency fraction.

F. How Does Input Structure Affect Reuse?

Preserving task-critical fields should improve the usefulness of both raw execution and any behavior it can qualify. A same-source four-cell Qwen experiment compares fixed-word-cap, whitespace-normalized packing with structure-preserving rendering on two HotpotQA and two RepoBench sources. Window, two-request concurrency, admission, scoring and service clock stay fixed.

Raw HotpotQA F1 rises from 0 to 0.22222 and code score from 0.12067 to 0.36667. Admitted coverage rises from 30/360 to 112/360 and full-wall throughput from 1.039× to 1.117×, with unchanged compiled IDs. These are input-construction effects, not accuracy gains caused by reordering. The supplement records content retention, code-prefix loss and whitespace effects. The independent primary cohort tests the structure-preserving pipeline without changing its acceptance rules.

Finding: input fidelity changes both absolute task utility and the reuse that can be admitted, so task construction belongs in a cache-system evaluation.

G. What Does Matched-Native Comparison Establish?

In 2,250 matched-native quality pairs/method, CacheBlend records 224 material decreases/331 increases and mean score 0.333210→0.339817; ContractKV records two decreases/no increases and 0.353780→0.353744. Raw means, runtimes, prompts and separators differ, precluding cross-stack speed rankings or causal risk ratios. Supplementary Table S-VIII gives all four methods and both change directions; threshold sensitivity remains archived. Same-engine D1/D2 supplies the performance attribution.

Finding: mean utility and per-request preservation answer different questions; comparisons must retain each system's own execution reference.

VII. Related Work

Physical and cross-position reuse. PagedAttention provides block-based KV memory management and sharing [2]; SGLang's RadixAttention organizes reusable prefixes for structured language-model programs [3]. Prompt Cache exposes reusable modules through explicit schemas [4]. CacheBlend selectively recomputes information when combining cached passages [5], while EPIC uses position-independent composition with LegoLink [6]. CacheSlide and MiniPIC further explore cross-position or position-independent reuse [19], [20]. Liu et al. reorder table rows and fields to increase prefix reuse in analytics [8]. These systems expand the execution

mechanisms and units available for reuse. ContractKV couples a compiled representation to a reusable service contract: behavioral evidence governs admissibility, PSTP governs visibility, and the Service-Template Certificate governs authorization and lifecycle. Supplementary Table S-VI compares these responsibilities without inferring unreported safety capabilities of other systems.

Application and service scheduling. Parrot's Semantic Variables expose application dataflow to the serving system [7]. Llumnix dynamically schedules serving requests across instances [21]; Sarathi-Serve addresses prefill/decode throughput–latency interference [22]; and Preble combines prompt reuse with distributed load balancing [23]. DistServe and Mooncake separate serving stages or distribute KV storage and computation [24], [25]. These mechanisms govern resource placement and execution. ContractKV instead determines when a compiled representation is eligible for publication and authorized reuse within one cache domain. Its waiting and residency measurements identify where model-backed qualification and native scheduling interact.

Cost models, contracts, and cache privacy. Vidur combines experimental profiling with predictive models to estimate serving behavior [26]; our frozen operating-point and cost-profile studies expose the effect of profiling support on useful admission. Classical service contracts such as WSLA associate measurable service obligations with monitoring and enforcement [27]. ContractKV binds a reusable model-execution artifact to evidence, identity, authorization, and a transactional boundary. Work on prompt leakage and audits of prompt-cache sharing demonstrates that cache timing is itself an observable privacy channel [28], [29]. Those results motivate separating authorization-controlled cache state from protection against timing inference.

VIII. Discussion and Limitations

A. What the Service Contract Establishes

Token-path certification is relative behavioral evidence under bound execution conditions, not an answer-correctness oracle. Figure 3 therefore separates output agreement from raw utility. The query-qualified class assumes a repeated authorized directory and metadata-only observations; arbitrary evolving histories and new tool evidence are outside it. Unique-query streams offer little amortization, and production query-repeat frequencies were not measured. Table II states the different evidence and cost units of the two implemented paths.

B. Trust Model and Manifest Registration

The operator is trusted to define template ownership, segment types, dependencies, sharing domains and versions. The controller, model/runtime and cache manager lie within the trusted service boundary; tenant-supplied labels are not registration authority. The CPU registration helper checks issuer/role, segment identities, authentication tags, content hashes, version/domain fields, and consistency of publication with declared stability and visibility. These checks validate a declaration's authority and consistency, not its semantic truth.

Consider tenant A's private `TOOL_OBS`. If the trusted operator wrongly declares its bytes STABLE, marks them domain-shared, and authorizes tenant B in that domain, a correct hash and HMAC do not establish that sharing is appropriate. The mistake can authorize private content as a shared prefix. The hash proves byte identity; the HMAC authenticates the operator's binding. Neither classifies confidentiality. The operator must keep tenant-specific observations outside the shared declaration.

The nine-case CPU registration-helper audit rejects seven malformed or unauthorized declarations, accepts the legitimate case, and also accepts that trusted semantic mislabel (supplement). The helper is separate from the live endpoint. Authenticated deployment admission and in-engine PSTP tests establish their respective identity and publication boundaries; they do not demonstrate detection of operator disclosure mistakes.

Even correctly authorized sharing can reveal cache-hit timing within its domain [28], [29]. ContractKV does not implement a timing-channel defense. P4 is cache-state authorization, not a comprehensive application confidentiality boundary.

C. Workload and Platform Boundaries

The inherited Python-output check excludes some legal next-line fragments. All omitted spans, L0 score changes and unsuccessful variants remain archived; source counts and platform settings are specified in Section VI-A.

The three known-source cache probes diagnose reclamation, not every earlier miss. The partial query-qualified fixed-arrival study (5/54 cells) supplies no capacity claim. The vLLM 0.25.1 audit is not a port; distributed domains require coordinated lifecycle and publication. Practically, qualify where authorized reuse repays its service-clock cost, including residency.

IX. Conclusion

ContractKV governs reusable KV as a service object whose layout, behavioral evidence and transactional visibility share one validity boundary. CALC exposes a dependency-valid physical prefix; scoped certification establishes admissibility; PSTP controls what becomes visible; and the Service-Template Certificate binds authorized reuse to a versioned lifecycle. This coupling gives the service a concrete decision about which transformed execution artifacts later tenants may consume.

The measurements establish complementary parts of that argument. Query-qualified execution achieves 1.070–1.619$\times$ full-cost throughput across three models, with unchanged IDs in all 1,296 admitted compiled future pairs. Deployment-qualified registration reduces calls 25-fold and unhidden verification exposure 7.7-fold; a separate open-arrival point gains 0.658 compliant requests/s, while 80-identity density replay uses 71.9% fewer peak KV blocks. Qualification therefore has a reusable economic unit as well as a publication boundary. Three lessons follow: admission scope determines shareability, atomic commit governs visibility, and locality plus residency determine how much reuse is realized. Aligning these decisions is the service-level contribution of ContractKV.

REFERENCES

[1] Azure Samples, "Azure AI Search + Azure OpenAI demo: Conversation builder and answer template," source revision `558ffd397edd`, *azure-search-openai-demo*. [Online]. Available: https://github.com/Azure-Samples/azure-search-openai-demo. Accessed: Oct. 17, 2026.

[2] W. Kwon *et al.*, "Efficient memory management for large language model serving with PagedAttention," in *Proc. ACM SIGOPS Symp. Oper. Syst. Principles (SOSP)*, 2023, pp. 611–626, doi: 10.1145/3600006.3613165.

[3] L. Zheng *et al.*, "SGLang: Efficient execution of structured language model programs," in *Advances in Neural Information Processing Systems*, vol. 37, 2024.

[4] I. Gim, G. Chen, S.-s. Lee, N. Sarda, A. Khandelwal, and L. Zhong, "Prompt Cache: Modular attention reuse for low-latency inference," in *Proc. Mach. Learn. Syst. (MLSys)*, vol. 6, 2024.

[5] J. Yao *et al.*, "CacheBlend: Fast large language model serving for RAG with cached knowledge fusion," in *Proc. 20th Eur. Conf. Comput. Syst. (EuroSys)*, 2025, doi: 10.1145/3689031.3696098.

[6] J. Hu *et al.*, "EPIC: Efficient position-independent caching for serving large language models," in *Proc. 42nd Int. Conf. Mach. Learn. (ICML)*, PMLR, vol. 267, 2025, pp. 24391–24402.

[7] C. Lin, Z. Han, C. Zhang, Y. Yang, F. Yang, C. Chen, and L. Qiu, "Parrot: Efficient serving of LLM-based applications with semantic variable," in *Proc. 18th USENIX Symp. Oper. Syst. Design Implement. (OSDI)*, 2024, pp. 929–945.

[8] S. Liu *et al.*, "Optimizing LLM queries in relational data analytics workloads," in *Proc. Mach. Learn. Syst. (MLSys)*, vol. 7, 2025. Author version: arXiv:2403.05821.

[9] Z. Yang, P. Qi, S. Zhang, Y. Bengio, W. W. Cohen, R. Salakhutdinov, and C. D. Manning, "HotpotQA: A dataset for diverse, explainable multi-hop question answering," in *Proc. Conf. Empirical Methods in Natural Language Processing (EMNLP)*, 2018, pp. 2369–2380, doi: 10.18653/v1/D18-1259.

[10] T. Liu, C. Xu, and J. McAuley, "RepoBench: Benchmarking repository-level code auto-completion systems," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2024.

[11] Y. Bai *et al.*, "LongBench: A bilingual, multitask benchmark for long context understanding," in *Proc. 62nd Annu. Meeting Assoc. Comput. Linguistics (ACL)*, 2024, pp. 3119–3137, doi: 10.18653/v1/2024.acl-long.172.

[12] A. Yang *et al.*, "Qwen3 technical report," *arXiv preprint arXiv:2505.09388*, 2025.

[13] A. Q. Jiang *et al.*, "Mistral 7B," *arXiv preprint arXiv:2310.06825*, 2023.

[14] A. Dubey *et al.*, "The Llama 3 herd of models," *arXiv preprint arXiv:2407.21783*, 2024.

[15] C.-P. Hsieh *et al.*, "RULER: What's the real context size of your long-context language models?" in *Proc. Conf. Language Modeling (COLM)*, 2024.

[16] T. Kočiský *et al.*, "The NarrativeQA reading comprehension challenge," *Trans. Assoc. Comput. Linguistics*, vol. 6, pp. 317–328, 2018, doi: 10.1162/tacl_a_00023.

[17] P. Dasigi, K. Lo, I. Beltagy, A. Cohan, N. A. Smith, and M. Gardner, "A dataset of information-seeking questions and answers anchored in research papers," in *Proc. Conf. North American Chapter Assoc. Comput. Linguistics: Human Language Technologies (NAACL-HLT)*, 2021, pp. 4599–4610, doi: 10.18653/v1/2021.naacl-main.365.

[18] vLLM Project, "Automatic prefix caching," *vLLM Documentation*, ver. 0.10.2. [Online]. Available: https://docs.vllm.ai/en/v0.10.2/design/prefix_caching.html. Accessed: Oct. 17, 2026.

[19] Y. Liu *et al.*, "CacheSlide: Unlocking cross position-aware KV cache reuse for accelerating LLM serving," in *Proc. 24th USENIX Conf. File Storage Technol. (FAST)*, 2026, pp. 83–99.

[20] N. Ordonez and T. Parnell, "MiniPIC: Flexible position-independent caching in $<$100 LOC," *arXiv preprint arXiv:2606.13126*, 2026.

[21] B. Sun *et al.*, "Llumnix: Dynamic scheduling for large language model serving," in *Proc. 18th USENIX Symp. Oper. Syst. Design Implement. (OSDI)*, 2024, pp. 173–191.

[22] A. Agrawal *et al.*, "Taming throughput-latency tradeoff in LLM inference with Sarathi-Serve," in *Proc. 18th USENIX Symp. Oper. Syst. Design Implement. (OSDI)*, 2024, pp. 117–134.

[23] V. Srivatsa, Z. He, R. Abhyankar, D. Li, and Y. Zhang, "Preble: Efficient distributed prompt scheduling for LLM serving," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2025.

[24] Y. Zhong *et al.*, "DistServe: Disaggregating prefill and decoding for goodput-optimized large language model serving," in *Proc. 18th USENIX Symp. Oper. Syst. Design Implement. (OSDI)*, 2024, pp. 193–210.

[25] R. Qin *et al.*, "Mooncake: Trading more storage for less computation—A KVCache-centric architecture for serving LLM chatbot," in *Proc. 23rd USENIX Conf. File Storage Technol. (FAST)*, 2025, pp. 155–170.

[26] A. Agrawal *et al.*, "Vidur: A large-scale simulation framework for LLM inference," in *Proc. Mach. Learn. Syst. (MLSys)*, vol. 6, 2024.

[27] A. Keller and H. Ludwig, "The WSLA framework: Specifying and monitoring service level agreements for Web services," *J. Network Syst. Manage.*, vol. 11, no. 1, pp. 57–81, 2003, doi: 10.1023/A:1022445108617.

[28] G. Wu, Z. Zhang, Y. Zhang, W. Wang, J. Niu, Y. Wu, and Y. Zhang, "I know what you asked: Prompt leakage via KV-cache sharing in multi-tenant LLM serving," in *Proc. Network Distrib. Syst. Security Symp. (NDSS)*, 2025, doi: 10.14722/ndss.2025.241772.

[29] C. Gu, X. L. Li, R. Kuditipudi, P. Liang, and T. Hashimoto, "Auditing prompt caching in language model APIs," in *Proc. 42nd Int. Conf. Mach. Learn. (ICML)*, 2025. Author version: arXiv:2502.07776.