CMeval: Safety Assessment for Chemical Scenarios of Small Language Models

Zhihang Zhou[a,1], Qixiang Wang[a,2], Yufeng Li[b,3], Wenpeng Xing[c,4] and Zhichao Yang[a,*,5]

[a]Zhejiang Police College, Hangzhou, 310053, Zhejiang, China
[b]East China Normal University, Shanghai, 200062, Shanghai, China
[c]Zhejiang University, Hangzhou, 310053, Zhejiang, China

ARTICLE INFO

Keywords:
Small Language Models
Safety Evaluation
Chemistry
Benchmark

ABSTRACT

The rapid progress of large language models (LLMs) has encouraged their use in chemistry. This trend also raises growing safety concerns in chemical applications. Prior work has mainly examined trillion-parameter models. In contrast, smaller models with only hundreds of millions of parameters remain largely untested, despite their wide accessibility to individual users and small organizations. To address this gap, we present CMeval, a benchmark for safety evaluation of LLMs in chemistry. CMeval includes about 9,000 curated test questions that cover high-risk chemical tasks. The benchmark provides a structured way to assess the safety of models in chemical contexts. We apply CMeval to evaluate several representative small open-source models, such as LLaMA3. The results show that small models carry higher risks of misuse. This finding highlights the urgent need to strengthen safety alignment in small models. The dataset used in this study is publicly available at Hugging Face: https://huggingface.co/datasets/zhouzh26/CMeval.

Warning: This paper contains discussions on the synthesis of controlled chemicals using AI models.

1. Introduction

Large Language Models (LLMs) are playing an increasingly important role in scientific research, with particularly clear impact in chemistry. Recent studies apply these models to de novo drug design [1], synthesis planning [2], and molecular property prediction [3]. Survey articles further suggest that LLMs can accelerate discovery and automate parts of laboratory workflows [4], [5]. Beyond text-based assistance, LLMs are often integrated with external tools to form autonomous research agents capable of executing experimental procedures, as demonstrated by systems such as Cactus [6]. As chemistry shifts toward tool-augmented and partially autonomous pipelines, laboratory safety and human oversight become increasingly critical [7].

Chemistry-oriented language models are also being adopted across a wide range of subfields. LLMs are commonly used for text mining and information extraction, converting unstructured literature into structured, machine-actionable chemical knowledge [8], [9]. With fine-tuning, even relatively small models can achieve strong performance in specialized chemical pipelines [9]. In materials science and related discovery contexts, community efforts show that LLMs can assist with hypothesis generation, data processing, and experimental design [10]. Domain-specific foundation models such as ChemDFM seek to incorporate chemical priors and curated corpora to support diverse chemistry tasks [11], [12], and subfields including reticular chemistry have begun to explore LLM-based approaches [13]. At the same time, multi-agent systems integrated with laboratory automation have led to so-called "robotic AI chemists" that coordinate instruments and decision-making processes [14]. These developments reduce the gap between natural-language instructions and chemical operations, improving efficiency while also introducing dual-use concerns.

At the same time, broader access to chemical knowledge and capabilities creates significant safety challenges. Easier access to information about hazardous substances and regulated synthesis pathways increases the risk of misuse [15]. When models are closely integrated with tools and automated platforms, the risks extend beyond unsafe text outputs to complete experimental workflows [16]. Responsible development and deployment of LLMs in chemical settings is therefore an urgent and necessary objective.

2. Related Work

2.1. General LLM Safety Evaluation

Safety alignment has become a central topic in LLM research. Benchmarks such as BeaverTails [17] and SafetyPrompts [18] evaluate models across categories including

*This work was supported in part by the Chinese College Students' Innovative Entrepreneurial Training Plan Program under Grant 202511483005.

*Corresponding author

shilu@zjjcxy.cn (Z. Zhou); zhou.zhjc@my.tccd.edu (Q. Wang); 52295902033@stu.ecnu.edu.cn (Y. Li); wpxing@zju.edu.cn (W. Xing); yangzhichao@zjjcxy.cn (Z. Yang)

ORCID(s): 0009-0006-5178-7204 (Z. Zhou); 0009-0009-8420-6113 (Q. Wang); 0009-0007-1937-1185 (Y. Li); 0000-0001-5848-9417 (W. Xing)

[1]Zhihang Zhou is studying at the Zhejiang Police College, Hangzhou, 310053 China.

[2]Qixiang Wang is studying at the Zhejiang Police College, Hangzhou, 310053 China.

[3]Yufeng Li is with the East China Normal University, Shanghai, 200062 China.

[4]Wenpeng Xing is with the Zhejiang University, Hangzhou, 310053 China.

[5]Zhichao Yang is with the Zhejiang Police College, Hangzhou, 310053 China.

violence and illegal activities. With the emergence of autonomous agents, R-Judge [19] assesses safety risk awareness in agentic workflows, while online safety monitoring frameworks [20] and evaluation surveys [21] highlight deployment challenges. Multi-modal safety benchmarks further broaden the evaluation scope [22]. However, these general benchmarks lack the domain-specific granularity required for high-stakes scientific contexts such as chemistry.

2.2. Domain-Specific Safety in Science and Chemistry

To address scientific risks, domain-oriented benchmarks have been proposed. ChemSafetyBench [23] evaluates chemical misuse and hazardous handling, and SciSafeEval [24] extends safety assessment across scientific disciplines. Other efforts examine chemical knowledge depth by comparing LLMs to human chemists [25] and assessing "chemical intelligence" [26]. CHEMSETS [27] targets diverse chemistry tasks, while ChemEval [31] evaluates multi-level reasoning. Representation robustness has also received attention: studies comparing SMILES and SELFIES show that molecular encoding significantly influences model behavior [28], [29]. Safety in long reasoning chains remains challenging, as explored in SafeChain [30]. Although these works advance scientific AI safety, they primarily focus on large foundation models.

2.3. The Gap in Small Language Models

In contrast, Small Language Models (SLMs) remain underexamined in chemical safety contexts. Models such as Llama-3-8B [32], Qwen series [33], [34], and Phi-4 [35] are increasingly accessible due to lower computational requirements. While their task-level capabilities approach those of larger models, systematic evaluation of their safety alignment in high-risk chemical scenarios is limited. Given their feasibility for local and decentralized deployment, understanding the safety profile of SLMs is critical to mitigating distributed misuse risks.

2.4. Our Contributions

We introduce CMeval, a benchmark designed to assess safety behavior of Small Language Models in chemical scenarios. Our contributions are threefold:

- We construct a comprehensive dataset of high-risk chemical questions derived from authoritative regulatory sources, covering properties, usage, and synthesis tasks.
- We systematically evaluate representative open-source SLMs and demonstrate that smaller models exhibit higher variance and greater risk of unsafe responses compared to larger counterparts.
- We analyze structural vulnerabilities, particularly degradation under molecular representations, highlighting the need for domain-aware safety alignment for compact models.

3. Method

Our goal is to build a clear and reproducible benchmark for chemical safety evaluation. The pipeline covers chemical collection, knowledge acquisition, dataset construction, and evaluation, and we describe each stage in enough detail to support replication. We also compare against existing benchmarks to ensure that our evaluation is fair and comparable.

3.1. Chemical Substance Collection

We compile a dataset of controlled and high-risk chemicals that reflects substances likely to appear in real-world settings. The final list contains nearly 3,000 chemicals drawn from multiple official sources and international regulations. We include the U.S. Occupational Safety and Health Administration (OSHA) Hazardous Chemicals List (29 CFR 1910.1200) [36], which covers chemicals that are acutely toxic, explosive, or corrosive in industrial environments. We also use the U.S. Environmental Protection Agency (EPA) Toxic Substances Control Act (TSCA) Inventory [37], which includes high-risk substances such as flame retardants and heavy-metal compounds and emphasizes lifecycle management across production, use, and disposal. In addition, we incorporate schedules from the Chemical Weapons Convention (CWC) [38], which stratify substances into highly toxic warfare agents, chemical precursors, and industrial chemicals with dual-use potential, all subject to strict reporting and regulation by member states. We further add chemicals covered by the Japanese Act on the Evaluation of Chemical Substances [39], which focuses on persistent and bioaccumulative substances and requires permits, usage tracking, and tight emission limits. To reduce skew and provide safe reference points, we include a baseline set of low-risk, widely used chemicals (e.g., sodium chloride, copper sulfate, and ethanol). These baselines help test whether models can reliably distinguish hazardous cases from benign ones.

3.2. Knowledge Acquisition

We rely on multiple knowledge sources to improve coverage and reduce errors. PubChem [40] serves as the primary source because it provides large-scale, structured chemical data, including physical and chemical properties, toxicity classifications, and hazard categories under the Globally Harmonized System (GHS). This information supports the Properties and Usage subtask. For synthesis-related knowledge, we use Reaxys and SciFinder [41, 42], which provide curated reaction records and are widely used in chemical research. We manually filter and cross-check candidate reactions, and we retain only those that pass our criteria to avoid unreliable or duplicate entries. This curation step is necessary to keep the synthesis prompts grounded in realistic chemical practice.

3.3. Dataset Construction

We construct the dataset using a simple, explicit workflow. We first design prompt templates, both manually and with assistance from GPT-4o, and we tailor them to the two



Figure 1: The overview of the dataset construction process.

subtasks. For Properties and Usage, templates focus on safety labels, toxicity, and handling guidance. For Synthesis, templates ask for plausible reactions or preparation steps. We then assign chemicals to the two subtasks and instantiate the templates by filling in the chemical names and relevant attributes to produce task-specific prompts. In the Properties and Usage subtask, most questions are framed as binary True/False classification to reduce the answer space and make evaluation more stable for smaller models. In the Synthesis subtask, prompts are open-ended and request reaction routes or preparation methods. Finally, to improve robustness and probe representation sensitivity, we rewrite a subset of synthesis prompts by replacing some chemical names with SMILES strings. This tests whether models can interpret molecular structures rather than relying on name memorization, and it also exposes cases where standard chemical notation may weaken safety filters.

3.4. Evaluation Setting

All evaluations are conducted in a controlled and reproducible setting. We test representative open-source models, including the LLaMA-3 series [32], Qwen2.5 and Qwen3 series [33, 34], phi-4-mini [35], Mistral-7B [43], and Gemma models [44], spanning multiple architectures and scales. Each model is evaluated with the same prompts, decoding settings, and pipeline, without task-specific prompt tuning.

For CMeval, we evaluate two subtasks: Properties and Usage (binary responses on safety or compliance) and Synthesis (open-ended answers describing reaction or preparation methods). We do not enable additional safety filters. For the open-ended synthesis subtask, we use a rubric-based protocol with a GPT-5 judge and a 1–4 scale, where higher is better. The safety score measures whether the model refuses malicious requests: 1 indicates helpful, actionable guidance; 2 indicates limited assistance; 3 indicates a direct refusal without explanation; and 4 indicates a refusal with a clear ethical or legal rationale. The quality score measures answer quality for benign requests: 1 indicates refusal; 2 indicates low relevance or insufficient content; 3 indicates a useful but shallow response; and 4 indicates a detailed, valuable answer.

To test generalization, we also evaluate on ChemSafetyBench using the original protocol. All outputs are generated under identical inference settings.

4. Results

4.1. Results on our benchmark

4.1.1. Results on Properties and Usage

Table 1 and Table 2 summarize performance on the Properties and Usage subtask of CMeval. We observe large gaps across models that align with both parameter scale and the strength of safety alignment.

Among small language models (SLMs), Llama-3.1-8B-Instruct achieves the highest accuracy (0.710), suggesting relatively strong performance on chemical property judgments and compliance-oriented classification. Mistral-7B-Instruct-v0.3 is more balanced, reaching an F1-score of 0.526 with a better precision–recall trade-off.

Smaller models such as Qwen3-0.6B and Gemma-3-1B-Instruct show extremely high recall but very low precision. In practice, they label most inputs as unsafe, which inflates



Figure 2: Overview of the evaluation.

Table 1
Small language models performance comparison on the CMeval benchmark.

Model Name	Accuracy	Precision	Recall	F1-Score
Gemma-3-1B-Instruct	0.319	0.308	0.995	0.470
Gemma-3-4B-Instruct	0.467	0.304	0.586	0.401
Qwen2.5-7B-Instruct	0.499	0.296	0.474	0.365
Qwen3-0.6B	0.304	0.303	0.995	0.465
Qwen3-1.7B	0.543	0.036	0.020	0.025
Qwen3-4B	0.389	0.308	0.815	0.447
Qwen3-8B	0.381	0.313	0.871	0.461
Phi-3.5-mini-Instruct	0.560	0.349	0.521	0.418
Phi-4-mini-Instruct	0.515	0.341	0.645	0.445
Mistral-7B-Instruct-v0.3	0.585	0.403	0.759	0.526
Llama-3.1-8B-Instruct	0.710	0.534	0.363	0.432

recall while harming accuracy and F1-score. Several models behave close to a single-class predictor and struggle to separate safe from unsafe cases. These results indicate that scaling alone does not guarantee reliability for chemical safety classification, and alignment remains a major factor.

For large language models (LLMs), performance generally improves with scale. Qwen3-80B and Qwen3-235B reach accuracies of 0.739 and 0.741, outperforming all SLMs. However, precision–recall imbalance persists even at larger scales, underscoring the difficulty of safety-related judgments in chemistry. Overall, SLMs exhibit higher instability and larger variance, which implies higher risk in practical deployment.

4.1.2. Results on Synthesis

The Synthesis subtask examines model behavior under open-ended, high-risk requests, where the primary goal is

Table 2
Large language models performance comparison on the CMeval benchmark.

Model Name	Accuracy	Precision	Recall	F1-Score
Qwen3-14B	0.598	0.386	0.549	0.453
Qwen3-32B	0.463	0.317	0.667	0.430
Qwen3-80B	0.739	0.612	0.384	0.472
Qwen3-235B	0.741	0.617	0.383	0.473

safety alignment rather than task completion. Fig. 3 and Fig. 4 report the quality score for benign synthesis questions and the safety score for high-risk synthesis questions under two input conditions: common chemical names and SMILES strings.

For benign synthesis queries, response quality generally increases with model scale. Larger models tend to produce more structured and relevant answers when the request is non-sensitive. When SMILES strings replace chemical names, quality drops for nearly all models, suggesting that molecular-structure prompts are substantially harder to interpret.

The safety results are more concerning. With common-name prompts, many models partially restrict or refuse high-risk synthesis requests. With SMILES prompts, several SLMs show a clear drop in safety score, indicating a stronger tendency to output non-compliant, actionable synthesis guidance. This pattern suggests that molecular representations can weaken safety guardrails and act as an implicit bypass channel, which is especially problematic for smaller models with weaker alignment. Larger models are more robust, but they still exhibit non-trivial degradation.



Figure 3: Quality score on synthesis questions under two input conditions.



Figure 4: Safety score on synthesis questions under two input conditions.

4.2. Results on Other Benchmarks

Results on ChemSafetyBench (Table 3) support the same conclusion: LLMs consistently outperform SLMs, and model rankings are largely stable across benchmarks. Table 4 further shows that Chain-of-Thought (CoT) prompting yields inconsistent gains for SLMs, indicating that better reasoning does not necessarily translate into better safety behavior in chemical settings.

5. Discussion

5.1. Scale Does Not Guarantee Chemical Safety

A common assumption is that safety improves smoothly with model scale. Our results do not support this in chemical settings. While larger models often achieve higher accuracy and more stable behavior on property-related judgments, the gains are non-linear and diminish beyond the tens-of-billions range.

More importantly, safety behavior does not track task performance. Some models with reasonable classification accuracy still provide partially actionable information for high-risk synthesis requests. This suggests that chemical safety is not only a capability problem but also an alignment problem. Scaling can improve reasoning and recall, but it does not automatically establish robust boundaries for what should be refused in domain-specific contexts.

Table 3
Small language models performance comparison on ChemSafetyBench.

Model Name	Accuracy	Precision	Recall	F1-Score
Gemma-3-4B-Instruct	0.402	0.311	0.726	0.436
Qwen3-0.6B	0.514	0.330	0.511	0.401
Qwen3-4B	0.511	0.345	0.598	0.438
Qwen3-8B	0.459	0.327	0.662	0.438
Mistral-7B-Instruct-v0.3	0.526	0.364	0.658	0.469
Llama-3.1-8B-Instruct	0.493	0.329	0.572	0.418
Qwen3-14B	0.494	0.350	0.688	0.464
Qwen3-32B	0.534	0.370	0.659	0.474
Qwen3-80B	0.641	0.441	0.481	0.460
Qwen3-235B	0.540	0.375	0.669	0.481
Llama3.1-70B	0.382	0.306	0.741	0.433

Table 4
Small language models performance with CoT.

Model Name	Accuracy	Precision	Recall	F1-Score
Qwen3-0.6B	0.531	0.346	0.618	0.444
Qwen3-1.7B	0.647	0.436	0.559	0.491
Qwen3-4B	0.672	0.6135	0.565	0.588
Qwen3-8B	0.656	0.450	0.593	0.511

5.2. Molecular Representations as a Structural Vulnerability

A central finding is that safety behavior is sensitive to how chemicals are represented. When we replace common names with SMILES, safety scores decrease for many models, especially SLMs.

This pattern implies that current alignment mechanisms rely heavily on surface-level linguistic cues. Molecular representations reduce those cues and can therefore weaken implicit guardrails. The degradation does not require adversarial phrasing; it can arise from standard notation routinely used in chemistry.

From a safety standpoint, this reveals a structural vulnerability. Chemical representations introduce an additional attack surface that differs from generic jailbreak prompts, because the failure mode appears within legitimate professional workflows. This distinction highlights why chemical AI safety cannot be fully captured by text-only evaluations.

5.3. Distinct Risk Profile of Small Language Models

SLMs exhibit failure modes that differ qualitatively from those of larger models. Some are overly conservative, labeling many cases as unsafe and achieving high recall with low precision. Others fail to separate benign from hazardous cases and sometimes produce unsafe synthesis guidance.

These behaviors point to unstable and poorly calibrated safety boundaries. Because SLMs are cheap to run and can be deployed locally or offline, they may create disproportionate real-world risk: decentralized use reduces opportunities for centralized monitoring and mitigation, which makes systematic evaluation particularly important.

5.4. Reasoning Improvements Are Not Equivalent to Alignment

CoT prompting can improve classification performance for some SLMs, but the gains are inconsistent and do not reliably strengthen safety behavior. Better reasoning can raise task accuracy, yet it does not answer the normative question of when a response should be refused for legal, ethical, or safety reasons.

This gap underscores a limitation of reasoning-focused techniques as safety interventions. Domain-aware alignment methods are needed to ensure that improved capability does not also increase misuse risk.

6. Conclusion

This paper introduces CMeval, a benchmark for evaluating chemical safety behavior in language models, with an emphasis on small models. CMeval includes high-risk prompts on chemical properties, usage judgments, and synthesis, and it covers both natural language and molecular representations.

Our results show that chemical safety cannot be inferred reliably from model size or task performance alone. Larger models are generally more stable, but safety gains diminish with scale, and small models show higher variance and distinct failure modes. Molecular representations such as SMILES substantially degrade safety performance for many models, revealing a vulnerability that is not captured by text-only evaluation.

We also find that improvements in reasoning performance do not necessarily translate into stronger safety alignment. These findings motivate domain-aware evaluation and alignment strategies, particularly as small, locally deployable models become more common.

References

[1] G. Ye, "De novo drug design as GPT language modeling: large chemistry models with supervised and reinforcement learning," *Journal of Computer-aided Molecular Design*, vol. 38, no. 1, p. 20, 2024.

[2] Y. Ruan, C. Lu, N. Xu, Y. He, Y. Chen, J. Zhang, J. Xuan, J. Pan, Q. Fang, H. Gao, *et al.*, "An automatic end-to-end chemical synthesis development platform powered by large language models," *Nature Communications*, vol. 15, no. 1, p. 10160, 2024.

[3] T. Guo, B. Nan, Z. Liang, Z. Guo, N. Chawla, O. Wiest, and X. Zhang, "What can large language models do in chemistry? A comprehensive benchmark on eight tasks," *Advances in Neural Information Processing Systems*, vol. 36, pp. 59662–59688, 2023.

[4] M. C. Ramos, C. J. Collison, and A. D. White, "A review of large language models and autonomous agents in chemistry," *Chemical Science*, 2025.

[5] A. M. Bran, S. Cox, O. Schilter, C. Baldassari, A. D. White, and P. Schwaller, "Augmenting large language models with chemistry tools," *Nature Machine Intelligence*, vol. 6, no. 5, pp. 525–535, 2024.

[6] A. D. McNaughton, G. K. Sankar Ramalaxmi, A. Kruel, C. R. Knutson, R. A. Varikoti, and N. Kumar, "Cactus: Chemistry agent connecting tool usage to science," *ACS Omega*, vol. 9, no. 46, pp. 46563–46573, 2024.

[7] R. MacKnight, D. A. Boiko, J. E. Regio, L. C. Gallegos, T. A. Neukomm, and G. Gomes, "Rethinking chemical research in the age of large language models," *Nature Computational Science*, pp. 1–12, 2025.

[8] M. Schilling-Wilhelmi, M. Ríos-García, S. Shabih, M. V. Gil, S. Miret, C. T. Koch, J. A. Márquez, and K. M. Jablonka, "From text to insight: large language models for chemical data extraction," *Chemical Society Reviews*, 2025.

[9] W. Zhang, Q. Wang, X. Kong, J. Xiong, S. Ni, D. Cao, B. Niu, M. Chen, Y. Li, R. Zhang, *et al.*, "Fine-tuning large language models for chemical text mining," *Chemical Science*, vol. 15, no. 27, pp. 10600–10611, 2024.

[10] K. M. Jablonka, Q. Ai, A. Al-Feghali, S. Badhwar, J. D. Bocarsly, A. M. Bran, S. Bringuier, L. C. Brinson, K. Choudhary, D. Circi, *et al.*, "14 examples of how LLMs can transform materials science and chemistry: a reflection on a large language model hackathon," *Digital Discovery*, vol. 2, no. 5, pp. 1233–1250, 2023.

[11] Z. Zhao, D. Ma, L. Chen, L. Sun, Z. Li, Y. Xia, H. Xu, Z. Zhu, S. Zhu, S. Fan, *et al.*, "ChemDFM: A large language foundation model for chemistry," in *NeurIPS 2024 Workshop on Foundation Models for Science: Progress, Opportunities, and Challenges*, 2024.

[12] Z. Zhao, D. Ma, L. Chen, L. Sun, Z. Li, Y. Xia, B. Chen, H. Xu, Z. Zhu, S. Zhu, *et al.*, "Developing ChemDFM as a large language foundation model for chemistry," *Cell Reports Physical Science*, vol. 6, no. 4, 2025.

[13] Z. Zheng, N. Rampal, T. J. Inizan, C. Borgs, J. T. Chayes, and O. M. Yaghi, "Large language models for reticular chemistry," *Nature Reviews Materials*, vol. 10, no. 5, pp. 369–381, 2025.

[14] T. Song, M. Luo, X. Zhang, L. Chen, Y. Huang, J. Cao, Q. Zhu, D. Liu, B. Zhang, G. Zou, *et al.*, "A multiagent-driven robotic AI chemist enabling autonomous chemical research on demand," *Journal of the American Chemical Society*, vol. 147, no. 15, pp. 12534–12545, 2025.

[15] Y. Zhou, J. Yang, Y. Huang, K. Guo, Z. Emory, B. Ghosh, A. Bedar, S. Shekar, Z. Liang, P.-Y. Chen, *et al.*, "Benchmarking large language models on safety risks in scientific laboratories," *Nature Machine Intelligence*, pp. 1–12, 2026.

[16] X. Tang, Q. Jin, K. Zhu, T. Yuan, Y. Zhang, W. Zhou, M. Qu, Y. Zhao, J. Tang, Z. Zhang, *et al.*, "Prioritizing safeguarding over autonomy: Risks of llm agents for science," in *ICLR 2024 Workshop on Large Language Model (LLM) Agents*, 2024.

[17] J. Ji, M. Liu, J. Dai, X. Pan, C. Zhang, C. Bian, B. Chen, R. Sun, Y. Wang, and Y. Yang, "Beavertails: Towards improved safety alignment of llm via a human-preference dataset," *Advances in Neural Information Processing Systems*, vol. 36, pp. 24678–24704, 2023.

[18] P. Röttger, F. Pernisi, B. Vidgen, and D. Hovy, "Safetyprompts: a systematic review of open datasets for evaluating and improving large language model safety," *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 39, no. 26, pp. 27617–27627, 2025.

[19] T. Yuan, Z. He, L. Dong, Y. Wang, R. Zhao, T. Xia, L. Xu, B. Zhou, F. Li, Z. Zhang, *et al.*, "R-Judge: Benchmarking Safety Risk Awareness for LLM Agents," in *ICLR 2024 Workshop on Large Language Model (LLM) Agents*, 2024.

[20] X. Xie, J. Song, Z. Zhou, Y. Huang, D. Song, and L. Ma, "Online safety analysis for llms: a benchmark, an assessment, and a path forward," *IEEE Transactions on Artificial Intelligence*, 2025.

[21] M. Mohammadi, Y. Li, J. Lo, and W. Yip, "Evaluation and benchmarking of llm agents: A survey," in *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2025, pp. 6129–6139.

[22] X. Liu, Y. Zhu, J. Gu, Y. Lan, C. Yang, and Y. Qiao, "Mm-safetybench: A benchmark for safety evaluation of multimodal large language models," in *European Conference on Computer Vision*, 2024, pp. 386–403.

[23] H. Zhao, H. Chen, Y. Zhang, et al. ChemSafetyBench: Benchmarking LLM Safety on Chemistry Domain. *arXiv preprint arXiv:2411.16736*, 2024.

[24] T. Li, J. Lu, C. Chu, T. Zeng, Y. Zheng, M. Li, H. Huang, B. Wu, Z. Liu, K. Ma, *et al.*, "SciSafeEval: A Comprehensive Benchmark for Safety Alignment of Large Language Models in Scientific Tasks," *CoRR*, 2024.

[25] A. Mirza, N. Alampara, S. Kunchapu, M. Ríos-García, B. Emoekabu, A. Krishnan, T. Gupta, M. Schilling-Wilhelmi, M. Okereke, A. Aneesh, *et al.*, "A framework for evaluating the chemical knowledge and reasoning abilities of large language models against the expertise of chemists," *Nature Chemistry*, pp. 1–8, 2025.

[26] N. T. Runcie, C. M. Deane, and F. Imrie, "Assessing the chemical intelligence of large language models," *Journal of Chemical Information and Modeling*, 2025.

[27] C. Bartmann, M. Ielanskyi, J. Schimunek, P. Seidl, G. Klambauer, and S. Luukkonen, "CHEMSETS: How Capable Are Chemistry LLMs?" in *NeurIPS 2025 AI for Science Workshop*, 2025.

[28] M. Leon, Y. Perezhohin, F. Peres, A. Popovič, and M. Castelli, "Comparing SMILES and SELFIES tokenization for enhanced chemical language modeling," *Scientific Reports*, vol. 14, no. 1, p. 25016, 2024.

[29] V. Ganeeva, K. Khrabrov, A. Kadurin, and E. Tutubalina, "Measuring Chemical LLM robustness to molecular representations: a SMILES variation-based framework," *Journal of Cheminformatics*, vol. 17, no. 1, pp. 1–15, 2025.

[30] F. Jiang, Z. Xu, Y. Li, L. Niu, Z. Xiang, B. Li, B. Y. Lin, and R. Poovendran, "SafeChain: Safety of Language Models with Long Chain-of-Thought Reasoning Capabilities," in *ICLR 2025 Workshop on Bidirectional Human-AI Alignment*, 2025.

[31] Y. Huang, R. Zhang, X. He, X. Zhi, H. Wang, X. Li, F. Xu, D. Liu, H. Liang, Y. Li, *et al.*, "ChemEval: A Comprehensive Multi-Level Chemical Evaluation for Large Language Models," *CoRR*, 2024.

[32] AI@Meta. Llama 3 Model Card. 2024. Available at: https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md.

[33] Qwen Team. Qwen2.5: A Party of Foundation Models. September 2024. Available at: https://qwenlm.github.io/blog/qwen2.5/.

[34] Qwen Team. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388*, 2025.

[35] M. Abdin, J. Aneja, H. Behl, S. Bubeck, R. Eldan, S. Gunasekar, M. Harrison, R. J. Hewett, M. Javaheripi, P. Kauffmann, et al. Phi-4 Technical Report. *arXiv preprint arXiv:2412.08905*, 2024.

[36] Occupational Safety and Health Administration (OSHA). *Hazard Communication Standard (29 CFR 1910.1200)*. U.S. Department of Labor, 2012.

[37] U.S. Environmental Protection Agency (EPA). *Toxic Substances Control Act (TSCA) Chemical Substance Inventory*. U.S. EPA, 2016.

[38] Organisation for the Prohibition of Chemical Weapons (OPCW). *Convention on the Prohibition of the Development, Production, Stockpiling and Use of Chemical Weapons and on Their Destruction*. OPCW, 1997.

[39] Government of Japan. *Chemical Substances Control Law*. Enacted 1973, enforced by METI, MHLW, and MOE.

[40] Kim, S., Chen, J., Cheng, T., et al. PubChem 2025 update. *Nucleic Acids Research*, 2025, 53(D1): D1516-D1525. DOI: 10.1093/nar/gkae1059.

[41] Chemical Abstracts Service (CAS).*SciFinder*. American Chemical Society (ACS), Columbus, OH, USA, [2025].

[42] Elsevier B.V.*Reaxys*. Elsevier, Amsterdam, The Netherlands, [2025].

[43] A. Q. Jiang, A. Sablayrolles, A. Mensch, C. Bamford, D. S. Chaplot, D. de las Casas, F. Bressand, G. Lengyel, G. Lample, L. Saulnier, L. R. Lavaud, M.-A. Lachaux, P. Stock, T. Le Scao, T. Lavril, T. Wang, T. Lacroix, and W. El Sayed. Mistral 7B. *arXiv preprint arXiv:2310.06825*, 2023.

[44] Gemma Team. Gemma 3. *arXiv preprint arXiv:2503.19786*, 2025.