

# Approximating the Held-Karp Bound for Metric TSP in Nearly Linear Work and Polylog Depth

**Zhuan Khye (Cedric) Koh**

Omri Weinstein    Sorrachai Yingchareonthawornchai



האוניברסיטה העברית בירושלים  
THE HEBREW UNIVERSITY OF JERUSALEM

**ETH** zürich

# Metric TSP

---

- Given an undirected graph  $G = (V, E)$  with edge costs  $c \in \mathbb{R}_{\geq 0}^m$ ,

**TSP:** Find a minimum-cost **Hamiltonian cycle** in  $G$ .

# Metric TSP

---

- Given an undirected graph  $G = (V, E)$  with edge costs  $c \in \mathbb{R}_{\geq 0}^m$ ,

**TSP:** Find a minimum-cost **Hamiltonian cycle** in  $G$ .

- ▶ Inapproximable

# Metric TSP

---

- Given an undirected graph  $G = (V, E)$  with edge costs  $c \in \mathbb{R}_{\geq 0}^m$ ,

**TSP:** Find a minimum-cost **Hamiltonian cycle** in  $G$ .

- ▶ Inapproximable

**Metric TSP:** Find a minimum-cost **spanning tour** in  $G$ .

# Metric TSP

---

- Given an undirected graph  $G = (V, E)$  with edge costs  $c \in \mathbb{R}_{\geq 0}^m$ ,

**TSP:** Find a minimum-cost **Hamiltonian cycle** in  $G$ .

- ▶ Inapproximable

**Metric TSP:** Find a minimum-cost **spanning tour** in  $G$ .

- ▶ **APX**-hard [Lampis '14]
- ▶  $3/2$  approximation [Christofides '76] [Serdyukov '78]
- ▶  $3/2 - 10^{-36}$  approximation [Karlin, Klein, Oveis Gharan '22]

# Metric TSP

---

- Given an undirected graph  $G = (V, E)$  with edge costs  $c \in \mathbb{R}_{\geq 0}^m$ ,

**TSP:** Find a minimum-cost **Hamiltonian cycle** in  $G$ .

- ▶ Inapproximable

**Metric TSP:** Find a minimum-cost **spanning tour** in  $G$ .

- ▶ **APX-hard** [Lampis '14]
  - ▶  $3/2$  approximation [Christofides '76] [Serdyukov '78]
  - ▶  $3/2 - 10^{-36}$  approximation [Karlin, Klein, Oveis Gharan '22]
- Metric TSP on  $(G, c) \equiv$  TSP on the **metric completion**  $(\hat{G}, \hat{c})$

$\hat{G}$  = Complete graph on  $V$

$\hat{c}_{uv}$  = Shortest path length between  $u$  and  $v$  in  $G$

# Subtour Elimination LP

---

[Dantzig, Fulkerson, Johnson '54]

$$\begin{aligned} \min \quad & \hat{c}^T x \\ \text{s. t.} \quad & \sum_v x_{uv} = 2 \quad \forall u \in V \\ & \sum_{u \in S, v \notin S} x_{uv} \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_{uv} \geq 0 \quad \forall u, v \in V \end{aligned}$$

# Subtour Elimination LP

---

[Dantzig, Fulkerson, Johnson '54]

$$\begin{aligned} \min \quad & \hat{c}^T x \\ \text{s. t.} \quad & \sum_v x_{uv} = 2 \quad \forall u \in V \\ & \sum_{u \in S, v \notin S} x_{uv} \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_{uv} \geq 0 \quad \forall u, v \in V \end{aligned}$$

- Used in many approximation/exact algorithms for TSP.



# Subtour Elimination LP

---

[Dantzig, Fulkerson, Johnson '54]

$$\begin{aligned} \min \quad & \hat{c}^T x \\ \text{s. t.} \quad & \sum_v x_{uv} = 2 \quad \forall u \in V \\ & \sum_{u \in S, v \notin S} x_{uv} \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_{uv} \geq 0 \quad \forall u, v \in V \end{aligned}$$

- Used in many approximation/exact algorithms for TSP.
- The LP optimal value coincides with the **Held–Karp bound**.

# Subtour Elimination LP

---

[Dantzig, Fulkerson, Johnson '54]

$$\begin{aligned} \min \quad & \hat{c}^T x \\ \text{s. t.} \quad & \sum_v x_{uv} = 2 \quad \forall u \in V \\ & \sum_{u \in S, v \notin S} x_{uv} \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_{uv} \geq 0 \quad \forall u, v \in V \end{aligned}$$

- Used in many approximation/exact algorithms for TSP.
- The LP optimal value coincides with the **Held–Karp bound**.

**Conjecture:** The LP integrality gap is at most  $4/3$  [Goemans '95].

## 2-ECSM LP

---

- LP relaxation of the 2-edge-connected spanning multisubgraph problem:

$$\begin{aligned} \min \quad & c^T x \\ \text{s. t.} \quad & \sum_{e \in \delta_G(S)} x_e \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_e \geq 0 \quad \forall e \in E. \end{aligned}$$

## 2-ECSM LP

---

- LP relaxation of the 2-edge-connected spanning multisubgraph problem:

$$\begin{aligned} \min \quad & c^T x \\ \text{s. t.} \quad & \sum_{e \in \delta_G(S)} x_e \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_e \geq 0 \quad \forall e \in E. \end{aligned}$$

**Fact:** Subtour LP optimal value = 2-ECSM LP optimal value.

[Cunningham '90] [Goemans, Bertsimas '93]

## 2-ECSM LP

---

- LP relaxation of the 2-edge-connected spanning multisubgraph problem:

$$\begin{aligned} \min \quad & c^T x \\ \text{s. t.} \quad & \sum_{e \in \delta_G(S)} x_e \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_e \geq 0 \quad \forall e \in E. \end{aligned}$$

**Fact:** Subtour LP optimal value = 2-ECSM LP optimal value.

[Cunningham '90] [Goemans, Bertsimas '93]

- Methods for solving the LP:
  - ▶ **Ellipsoid:** separation oracle is min cut

## 2-ECSM LP

---

- LP relaxation of the 2-edge-connected spanning multisubgraph problem:

$$\begin{aligned} \min \quad & c^T x \\ \text{s. t.} \quad & \sum_{e \in \delta_G(S)} x_e \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_e \geq 0 \quad \forall e \in E. \end{aligned}$$

**Fact:** Subtour LP optimal value = 2-ECSM LP optimal value.

[Cunningham '90] [Goemans, Bertsimas '93]

- Methods for solving the LP:
  - ▶ **Ellipsoid:** separation oracle is min cut
  - ▶ **Held–Karp bound/heuristic:** iterate over 1-trees

## 2-ECSM LP

---

- LP relaxation of the 2-edge-connected spanning multisubgraph problem:

$$\begin{aligned} \min \quad & c^T x \\ \text{s. t.} \quad & \sum_{e \in \delta_G(S)} x_e \geq 2 \quad \forall \emptyset \subsetneq S \subsetneq V \\ & x_e \geq 0 \quad \forall e \in E. \end{aligned}$$

**Fact:** Subtour LP optimal value = 2-ECSM LP optimal value.

[Cunningham '90] [Goemans, Bertsimas '93]

- Methods for solving the LP:
  - ▶ **Ellipsoid:** separation oracle is min cut
  - ▶ **Held–Karp bound/heuristic:** iterate over 1-trees
  - ▶ **Multiplicative weight update (MWU)**

## Solving the LP via MWU

---

- FPTAS which returns a  $(1 + \varepsilon)$ -approximate solution.



# Solving the LP via MWU

---

- FPTAS which returns a  $(1 + \varepsilon)$ -approximate solution.
- Sequential algorithms:
  - ▶  $\tilde{O}(n^4/\varepsilon^2)$  [Plotkin, Shmoys, Tardos '95]
  - ▶  $\tilde{O}(m^2/\varepsilon^2)$  [Garg, Khandekar '02]
  - ▶  $\tilde{O}(m/\varepsilon^2)$  [Chekuri, Quanrud '17]

# Solving the LP via MWU

---

- FPTAS which returns a  $(1 + \varepsilon)$ -approximate solution.
- Sequential algorithms:
  - ▶  $\tilde{O}(n^4/\varepsilon^2)$  [Plotkin, Shmoys, Tardos '95]
  - ▶  $\tilde{O}(m^2/\varepsilon^2)$  [Garg, Khandekar '02]
  - ▶  $\tilde{O}(m/\varepsilon^2)$  [Chekuri, Quanrud '17]

## Main Result [KWY '25]

Parallel algorithm that runs in  $\tilde{O}(m/\varepsilon^4)$  work and  $\tilde{O}(1/\varepsilon^4)$  depth.

# Solving the LP via MWU

---

- FPTAS which returns a  $(1 + \varepsilon)$ -approximate solution.
- Sequential algorithms:
  - ▶  $\tilde{O}(n^4/\varepsilon^2)$  [Plotkin, Shmoys, Tardos '95]
  - ▶  $\tilde{O}(m^2/\varepsilon^2)$  [Garg, Khandekar '02]
  - ▶  $\tilde{O}(m/\varepsilon^2)$  [Chekuri, Quanrud '17]

## Main Result [KWY '25]

Parallel algorithm that runs in  $\tilde{O}(m/\varepsilon^4)$  work and  $\tilde{O}(1/\varepsilon^4)$  depth.

**Framework:** Width-independent epoch-based MWU.

[Garg, Könemann '07] [Fleischer '00] [Luby, Nisan '93] [Young '01]

# Epoch-Based MWU

---

- Initialize edge weights as  $w = 1/c$ .

# Epoch-Based MWU

---

- Initialize edge weights as  $w = 1/c$ .
- Given a fixed lower bound  $\lambda$  on the mincut value, define

$$\mathcal{C}^* := \{C \text{ cut} : w(C) < (1 + \varepsilon)\lambda\}.$$

# Epoch-Based MWU

---

- Initialize edge weights as  $w = 1/c$ .
- Given a fixed lower bound  $\lambda$  on the mincut value, define

$$\mathcal{C}^* := \{C \text{ cut} : w(C) < (1 + \varepsilon)\lambda\}.$$

**While**  $\mathcal{C}^* \neq \emptyset$ :

- ① Select cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w$  along these cuts.

} an epoch

# Epoch-Based MWU

---

- Initialize edge weights as  $w = 1/c$ .
- Given a fixed lower bound  $\lambda$  on the mincut value, define

$$\mathcal{C}^* := \{C \text{ cut} : w(C) < (1 + \varepsilon)\lambda\}.$$

**While**  $\mathcal{C}^* \neq \emptyset$ :

- ① Select cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w$  along these cuts.

} an epoch

- $\lambda \leftarrow \lambda(1 + \varepsilon)$  and a new epoch begins.

# Epoch-Based MWU

---

- Initialize edge weights as  $w = 1/c$ .
- Given a fixed lower bound  $\lambda$  on the mincut value, define

$$\mathcal{C}^* := \{ C \text{ cut} : w(C) < (1 + \varepsilon)\lambda \}.$$

**While**  $\mathcal{C}^* \neq \emptyset$ :

- ① Select cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w$  along these cuts.

} an epoch

- $\lambda \leftarrow \lambda(1 + \varepsilon)$  and a new epoch begins.
- Terminate when  $\|w\|_\infty$  is big.




# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :

- 1 **Select** cut(s) from  $\mathcal{C}^*$ .
- 2 Multiplicatively increase  $w^{(t)}$  along these cuts.




# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :

- ① **Select** cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w^{(t)}$  along these cuts.




**Sequential MWU:** Select **one** cut from  $\mathcal{C}^*$

# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :

- 1 **Select** cut(s) from  $\mathcal{C}^*$ .
- 2 Multiplicatively increase  $w^{(t)}$  along these cuts.




**Sequential MWU:** Select **one** cut from  $\mathcal{C}^*$

# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :


- ① **Select** cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w^{(t)}$  along these cuts.



**Sequential MWU:** Select **one** cut from  $\mathcal{C}^*$

$\implies \tilde{O}(m/\varepsilon^2)$  iterations [Garg, Könemann '07] [Fleischer '00].

- 1 **Select** cut(s) from  $\mathcal{C}^*$ .
- 2 Multiplicatively increase  $w^{(t)}$  along these cuts.




$\Rightarrow \tilde{O}(m/\varepsilon^2)$  iterations [Garg, Könemann '07] [Fleischer '00].

# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :

- ① **Select** cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w^{(t)}$  along these cuts.



**Sequential MWU:** Select **one** cut from  $\mathcal{C}^*$

$\implies \tilde{O}(m/\varepsilon^2)$  iterations [Garg, Könemann '07] [Fleischer '00].


**Parallel MWU:** Select **all** cuts from  $\mathcal{C}^*$

# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :

- ① **Select** cut(s) from  $\mathcal{C}^*$ .
- ② Multiplicatively increase  $w^{(t)}$  along these cuts.



**Sequential MWU:** Select **one** cut from  $\mathcal{C}^*$

$\implies \tilde{O}(m/\varepsilon^2)$  iterations [Garg, Könemann '07] [Fleischer '00].

**Parallel MWU:** Select **all** cuts from  $\mathcal{C}^*$


$\implies \tilde{O}(\log(|\mathcal{C}^*|)/\varepsilon^4)$  iterations [Luby, Nisan '93] [Young '01].

# Epoch-Based MWU

---

**While**  $\mathcal{C}^* \neq \emptyset$ :

- 1 **Select** cut(s) from  $\mathcal{C}^*$ .
- 2 Multiplicatively increase  $w^{(t)}$  along these cuts.



**Sequential MWU:** Select **one** cut from  $\mathcal{C}^*$

$\implies \tilde{O}(m/\varepsilon^2)$  iterations [Garg, Könemann '07] [Fleischer '00].

**Parallel MWU:** Select **all** cuts from  $\mathcal{C}^*$

$\implies \tilde{O}(\log(|\mathcal{C}^*|)/\varepsilon^4)$  iterations [Luby, Nisan '93] [Young '01].


$\implies \tilde{O}(1/\varepsilon^4)$  iterations because  $|\mathcal{C}^*| = O(n^2)$  for cuts.



# Core-Sequence

---


- Parallel MWU can incur  $\Omega(n^2)$  work.




# Core-Sequence

---

- Parallel MWU can incur  $\Omega(n^2)$  work.




**New Selection Rule:**



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:

- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.






# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.
- 3 Repeat Steps 1 and 2 until  $\mathcal{C}^* = \emptyset$ .



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.
- 3 Repeat Steps 1 and 2 until  $\mathcal{C}^* = \emptyset$ .



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.
- 3 Repeat Steps 1 and 2 until  $\mathcal{C}^* = \emptyset$ .



# Core-Sequence


---

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:


- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.
- 3 Repeat Steps 1 and 2 until  $\mathcal{C}^* = \emptyset$ .



# Core-Sequence

---

- Parallel MWU can incur  $\Omega(n^2)$  work.




## New Selection Rule:

- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.
- 3 Repeat Steps 1 and 2 until  $\mathcal{C}^* = \emptyset$ .



# Core-Sequence

- Parallel MWU can incur  $\Omega(n^2)$  work.



## New Selection Rule:

- 1 Fix a **representative set**  $S \subseteq \mathcal{C}^*$ .
- 2 In every iteration, select  $S \cap \mathcal{C}^*$  as long as it is nonempty.
- 3 Repeat Steps 1 and 2 until  $\mathcal{C}^* = \emptyset$ .



## Definition

The sequence  $\mathcal{S} = (S_1, \dots, S_\ell)$  of representative sets is called a **core-sequence** of the epoch.

# Core-Sequence

---

- Special cases:

# Core-Sequence

---

- Special cases:

- ▶  $\mathcal{S} = (S_1, \dots, S_\ell)$  where  $|S_i| = 1$  for all  $i \in [\ell] \implies$  sequential MWU.



# Core-Sequence

---

- Special cases:
  - ▶  $\mathcal{S} = (S_1, \dots, S_\ell)$  where  $|S_i| = 1$  for all  $i \in [\ell] \implies$  sequential MWU.
  - ▶  $\mathcal{S} = (\mathcal{C}^*) \implies$  parallel MWU.

# Core-Sequence

---

- Special cases:

- ▶  $\mathcal{S} = (S_1, \dots, S_\ell)$  where  $|S_i| = 1$  for all  $i \in [\ell] \implies$  sequential MWU.
- ▶  $\mathcal{S} = (\mathcal{C}^*) \implies$  parallel MWU.

## Theorem [KWY '25]

If MWU uses a core-sequence of length  $\leq \ell$  with sets of size  $\leq k$  in every epoch, then the number of iterations is

$$\tilde{O}\left(\frac{\ell \log(k)}{\varepsilon^4}\right).$$

# Core-Sequence

---

- Special cases:
  - ▶  $\mathcal{S} = (S_1, \dots, S_\ell)$  where  $|S_i| = 1$  for all  $i \in [\ell] \implies$  sequential MWU.
  - ▶  $\mathcal{S} = (\mathcal{C}^*) \implies$  parallel MWU.

## Theorem [KWY '25]

If MWU uses a core-sequence of length  $\leq \ell$  with sets of size  $\leq k$  in every epoch, then the number of iterations is

$$\tilde{O}\left(\frac{\ell \log(k)}{\varepsilon^4}\right).$$

- Tradeoff between  $\ell$  and  $k$ .

# Core-Sequence for 2-ECSM LP

---

## Theorem [KWY '25]

For 2-ECSM LP, every epoch has a core-sequence of length  $\tilde{O}(1)$ , in which every set has size  $\tilde{O}(n)$ .

# Core-Sequence for 2-ECSM LP

---

## Theorem [KWY '25]

For 2-ECSM LP, every epoch has a core-sequence of length  $\tilde{O}(1)$ , in which every set has size  $\tilde{O}(n)$ .

- Despite  $|\mathcal{C}^*| = O(n^2)$ , only need to select  $\tilde{O}(n)$  of them!

# Core-Sequence for 2-ECSM LP

---

## Theorem [KWY '25]

For 2-ECSM LP, every epoch has a core-sequence of length  $\tilde{O}(1)$ , in which every set has size  $\tilde{O}(n)$ .

- Despite  $|\mathcal{C}^*| = O(n^2)$ , only need to select  $\tilde{O}(n)$  of them!

## Theorem [KWY '25]

There is a parallel FPTAS for the Held–Karp bound that runs in  $\tilde{O}(m/\varepsilon^4)$  work and  $\tilde{O}(1/\varepsilon^4)$  depth.

# Finding the Core-Sequence

---

**Tree Packing:** Compute  $O(\log n)$  spanning trees  $\mathcal{T}$  such that w.h.p., every cut in  $\mathcal{C}^*$  intersects  $\leq 2$  edges of some  $T \in \mathcal{T}$ . [Karger '00]

# Finding the Core-Sequence

---

**Tree Packing:** Compute  $O(\log n)$  spanning trees  $\mathcal{T}$  such that w.h.p., every cut in  $\mathcal{C}^*$  intersects  $\leq 2$  edges of some  $T \in \mathcal{T}$ . [Karger '00]

- Fix a tree  $T \in \mathcal{T}$ . Assume it is a path for simplicity.




# Finding the Core-Sequence

---

**Tree Packing:** Compute  $O(\log n)$  spanning trees  $\mathcal{T}$  such that w.h.p., every cut in  $\mathcal{C}^*$  intersects  $\leq 2$  edges of some  $T \in \mathcal{T}$ . [Karger '00]

- Fix a tree  $T \in \mathcal{T}$ . Assume it is a path for simplicity.




$T$

# Finding the Core-Sequence

---

**Tree Packing:** Compute  $O(\log n)$  spanning trees  $\mathcal{T}$  such that w.h.p., every cut in  $\mathcal{C}^*$  intersects  $\leq 2$  edges of some  $T \in \mathcal{T}$ . [Karger '00]

- Fix a tree  $T \in \mathcal{T}$ . Assume it is a path for simplicity.




**Idea:** For  $i \geq 0$ , decompose  $T$  into paths  $\mathcal{P}_i$  of length  $2^i$ .

# Finding the Core-Sequence

---

**Tree Packing:** Compute  $O(\log n)$  spanning trees  $\mathcal{T}$  such that w.h.p., every cut in  $\mathcal{C}^*$  intersects  $\leq 2$  edges of some  $T \in \mathcal{T}$ . [Karger '00]

- Fix a tree  $T \in \mathcal{T}$ . Assume it is a path for simplicity.



**Idea:** For  $i \geq 0$ , decompose  $T$  into paths  $\mathcal{P}_i$  of length  $2^i$ . If

$$S_i := \{\text{Cuts in } \mathcal{C}^* \text{ that intersect } \leq 2 \text{ edges of } T \text{ on some } P \in \mathcal{P}_i\},$$

then  $|S_i| = O(n)$  for all  $i$ .

# Conclusion

---

- Introduced **core-sequence** as a new selection rule for MWU.

# Conclusion

---

- Introduced **core-sequence** as a new selection rule for MWU.
- Parallel FPTAS that runs in **nearly linear** work and **polylog** depth for
  - ▶ Held–Karp bound and  $k$ -ECSM LP
  - ▶  $k$ -ECSS LP

# Conclusion

---

- Introduced **core-sequence** as a new selection rule for MWU.
- Parallel FPTAS that runs in **nearly linear** work and **polylog** depth for
  - ▶ Held–Karp bound and  $k$ -ECSM LP
  - ▶  $k$ -ECSS LP
- Future directions:
  - ▶ Apply core-sequence to other implicit packing/covering LPs

# Conclusion

---

- Introduced **core-sequence** as a new selection rule for MWU.
- Parallel FPTAS that runs in **nearly linear** work and **polylog** depth for
  - ▶ Held–Karp bound and  $k$ -ECSM LP
  - ▶  $k$ -ECSS LP
- Future directions:
  - ▶ Apply core-sequence to other implicit packing/covering LPs
  - ▶ Better dependence on  $\varepsilon$

# Conclusion

---

- Introduced **core-sequence** as a new selection rule for MWU.
- Parallel FPTAS that runs in **nearly linear** work and **polylog** depth for
  - ▶ Held–Karp bound and  $k$ -ECSM LP
  - ▶  $k$ -ECSS LP
- Future directions:
  - ▶ Apply core-sequence to other implicit packing/covering LPs
  - ▶ Better dependence on  $\varepsilon$
  - ▶ Extension to streaming/distributed models



# Conclusion

---

- Introduced **core-sequence** as a new selection rule for MWU.
- Parallel FPTAS that runs in **nearly linear** work and **polylog** depth for
  - ▶ Held–Karp bound and  $k$ -ECSM LP
  - ▶  $k$ -ECSS LP
- Future directions:
  - ▶ Apply core-sequence to other implicit packing/covering LPs
  - ▶ Better dependence on  $\varepsilon$
  - ▶ Extension to streaming/distributed models

Thank You!