Supplementary Material

StreamClarify: Proactive Clarification for Grounded Streaming Video Question Answering

A. Notation

Table 7. Notation used by StreamClarify.

Symbol	Meaning
$\mathcal{V} = \{F_1, F_2, \dots\}$	Continuous input stream, with frame F_t at time t
$\mathcal{V}_{\le t_i}$	Frames observed up to query time t_i
$\langle V_i, Q_i, A_i \rangle$	Round-i video context, user query, and model answer
$\langle R_i \rangle$	User-side guidance after clarification in round i
$\mathcal{M}$	Bounded active-context budget
L_{max}	Maximum active-context token budget for the KV cache
L_{comp}	Maximum pyramid/compression level
ℓ	Pyramid level of a token, where $\ell = 0$ is full resolution
2^ℓ	Subsampling stride at pyramid level ℓ
ρ	Compression ratio controlling retained historical tokens
$\mathcal{KV}$	Active KV cache produced by backbone prefilling
$\lvert\mathcal{KV}\rvert$	Active KV cache size, constrained by L_{max}
$\mathcal{T}_{\text{rec}}$	Recency-protection tokens kept at full resolution
$\mathcal{T}_{\text{hist}}$	Historical tokens eligible for compression or eviction
$\mathcal{I}_{\text{vis}}$	Backbone vision encoder for answer generation
$\mathbf{v}_t$	Backbone vision embeddings for frame t
$\mathcal{I}_{\text{ret}}$	Retrieval-key encoder for semantic search, instantiated with SigLIP2
$\mathbf{e}_t$	Image-text retrieval key for frame t
$\mathcal{A}$	CPU-side archive of $(\mathbf{v}_t, \mathbf{e}_t, t)$ entries stored separately from the active KV cache
p	Probability assigned to `[Yes]` in the Stage 1 judgment
H	Binary entropy of the Stage 1 `[Yes]/[No]` judgment
τ	Entropy threshold for triggering clarification
K	Number of top retrieved clips used after clarification
$\mathcal{T}^*$	Historical and recent tokens retained in the updated TP-KV context

B. Memory Management Algorithm

Algorithm 1: Online TP-KV Update and Archive Construction

Inputs : frames $[F_1, F_2, \dots, F_t, \dots]$
Initializations: $\mathcal{KV}=[\cdot]$: active context; $\mathcal{A}=[\cdot]$: retrieval memory; L_{max}: max tokens; ρ: compression ratio; L_{comp}: max compression level

while F_t *arrives* **do**
  $\mathbf{v}_t \leftarrow \mathcal{I}_{\text{vis}}(F_t)$; $\mathcal{KV} \leftarrow \text{Prefill}(\mathcal{KV}, \mathbf{v}_t)$; $\mathbf{e}_t \leftarrow \mathcal{I}_{\text{ret}}(F_t)$; $\mathcal{A}$.append$((\mathbf{v}_t, \mathbf{e}_t, t))$; `// encode & archive`
  if $|\mathcal{KV}| > L_{max}$ **then**
    $\mathcal{T}_{\text{rec}} \leftarrow$ tokens within recent window; $\mathcal{T}_{\text{hist}} \leftarrow$ remaining tokens;
    for *each* $\mathbf{v} \in \mathcal{T}_{\text{hist}}$ *where* level$(\mathbf{v}) < L_{\text{comp}}$ **do**
      compress $\mathbf{v}$ via stride sampling; level$(\mathbf{v})$ += 1 ; `// promote to next pyramid level`
    if $|\mathcal{T}_{\text{hist}}| > (L_{max} - |\mathcal{T}_{\text{rec}}|) \cdot \rho$ **then**
      evict $\mathbf{v}$ where level$(\mathbf{v}) \ge L_{\text{comp}}$, oldest first ; `// ratio unsatisfied: evict max-level tokens`
    $\mathcal{T}^* \leftarrow \mathcal{T}_{\text{hist}} \oplus \mathcal{T}_{\text{rec}}$; order $\mathcal{T}^*$ chronologically;
    $\mathcal{KV} \leftarrow \text{Prefill}(\mathcal{T}^*)$; `// rebuild KV in single forward pass`
  t += 1;

C. Experimental Details

Evaluation Scope. Table 8 distinguishes experiments that report the two benchmarks separately from those that pool their QA pairs. Experiments use the corresponding main configuration unless the evaluated factor is explicitly varied.

Baseline Protocol. GPT-5-mini [25] is evaluated through the OpenAI API in an offline pre-segmented setting, with each video uniformly sampled to 64 frames and submitted as a single batch [19]. It serves as an offline reference and is not treated as an online-memory baseline.

Training-based methods use their officially released weights. For the backbone-matched training-free comparison, StreamChat [35], StreamBridge [28], StreamingVLM [36], and StreamClarify are instantiated on the same three frozen backbones without task-specific fine-tuning. This controls for differences in backbone capability. All streaming methods are evaluated at the same annotated query timestamps using the same QA prompting protocol, answer judge, and evaluation pipeline.

Evaluation Protocol. All OVO-Bench results use the same final 281-QA split, comprising 82 Standard, 48 Ambiguous, and 151 Unanswerable questions. Four legacy baseline runs, GPT-5-mini, Flash-VStream, ReKV, and TimeChat, contained predictions for three additional questions from an earlier 284-QA snapshot. We deterministically filter these outputs to the final 281 exact QA keys and recompute all aggregate metrics using the unchanged frozen evaluator-v20 correctness labels. No inference is rerun.

Micro Accuracy is computed as the overall accuracy across all QA pairs. Macro Accuracy is the unweighted mean of per-scenario accuracies across Standard QA, Referential Ambiguity QA, and Unanswerable QA. System efficiency is quantified by time-to-first-token (TTFT, seconds) and online processing throughput (ProcFPS), measured in frames per second. For trigger diagnostics, incorrect initial answers are treated as positives. For each backbone, Random and Entropy selections are evaluated against the corresponding no-clarification answers on the same 1,837 QA keys. Trigger rate, Precision, and Recall describe selected operating points, while Error AUROC measures threshold-independent ranking using the same labels. We report wrong-to-correct and correct-to-wrong transitions, together with the resulting change in accuracy, to measure the effect of clarification.

Answer correctness is determined by an LLM-based semantic judge (Qwen3-14B) [37] using task-specific prompts conditioned on dense offline captions as scene-level reference context. General knowledge questions are judged for factual correctness, while all other questions are judged for semantic equivalence against the ground-truth

Table 8. Dataset, backbone, and clarification scope of the main experiments and ablations.

Analysis	Evaluation population	Backbone	Clarification setting
Main comparison	StreamBench (1,556 QA) and OVO-Bench (281 QA), reported separately	LLaVA-OV-1.5, InternVL-3.5, Qwen3-VL	Disabled
Oracle-guided analysis	StreamBench and OVO-Bench pooled (1,837 QA)	LLaVA-OV-1.5, InternVL-3.5, Qwen3-VL	Oracle guidance after triggering
Generated-question analysis	Ambiguous QA from StreamBench and OVO-Bench, pooled (302 QA)	Qwen3-VL	No clarification, Generated Clarification (entropy-gated and all-query), Direct Retrieval, and Oracle Guidance
Pre-answer scoring	OVO-Bench (281 QA)	Qwen3-VL	Disabled
TP-KV hyperparameters	OVO-Bench (281 QA)	Qwen3-VL	Disabled
Matched-6K comparison	StreamBench (1,556 QA) and OVO-Bench (281 QA), reported separately	Qwen3-VL	Disabled
Retrieval parameters	OVO-Bench (281 QA)	Qwen3-VL	Oracle guidance
Prompt perturbations	OVO-Bench (281 QA) StreamBench (1,556 QA)	Qwen3-VL Qwen3-VL, InternVL-3.5	Disabled Disabled

answer. Ambiguous questions also require entity-level consistency. Human spot-checks on 50 sampled videos are conducted to verify and improve judgment quality.

Backbone and Retrieval Settings. StreamClarify is instantiated on three instruction-tuned 8B VLM backbones: LLaVA-OV-1.5 [18], InternVL-3.5 [29], and Qwen3-VL [1]. All models are evaluated without task-specific training. The main comparison follows each method's standard configuration. A complementary Qwen3-VL comparison applies a common 6K active-context budget. Unless otherwise specified, TP-KV uses a 10K-token budget, compression ratio 0.25, and a 20 s recency window. For diagnostic clarification experiments, the per-backbone trigger threshold is set from the no-clarification entropy distribution to obtain the reported operating trigger rate, and retrieval uses top-K=16 clips.

All backbones use bfloat16 precision with FlashAttention-2. Input frames are resized to 448×448. Qwen3-VL is sampled at 2 FPS with temporal patch size 2, yielding 196 vision tokens per frame pair. LLaVA-OV-1.5 and InternVL-3.5 are run at 1 FPS with 256 tokens per frame, which keeps the active memory usage comparable across backbones. The retrieval-key encoder $\mathcal{I}_{\text{ret}}$ is instantiated with the same fixed SigLIP2 (so400M, patch size 14, resolution 384) across all backbones. Retrieved top-K clips are prefilled and combined with the current TP-KV context for re-answering after clarification. Each backbone uses its native positional encoding when the retrieved clips are combined with the current TP-KV context. Decoding is greedy with a maximum answer length of 32 tokens. Each open-model inference job uses one NVIDIA A40 GPU.

Matched-6K Comparison. The 6K comparison matches active visual context rather than total storage, and all methods remain within this limit. StreamChat has no persistent visual KV cache, so the limit applies to the retrieved visual context formed at query time. Its searchable CPU archive remains available and occupies 292.0 MB per video on average and 565.6 MB at peak. In this no-clarification comparison, StreamBridge, StreamingVLM, and StreamClarify do not use an external retrieval archive when answering.

Memory Pressure. At the evaluated frame rate, 6K corresponds to about 31 s of dense visual history. Across the full evaluation, StreamBridge, StreamingVLM, and StreamClarify apply compression or eviction in all 355 videos, before 84.8%, 86.7%, and 85.2% of their queries, respectively. The evaluated StreamClarify 10K and strict-6K configurations produce 2.14 and 6.19 compression operations per minute of streamed video.

D. Additional Analyses

D.1. Benchmark Quality Validation

For Referential Ambiguity QA, timestamp-aligned captions identify contexts with multiple plausible referents and guide the query rewrite. Human review covers all 404 candidates and removes insufficiently ambiguous rewrites and cases whose referent remains recoverable from the original annotations, leaving 302 pairs. Timestamp-aligned dense captions are available for all 1,556 StreamBench queries.

For StreamBench Unanswerable QA, the construction run generates 1,563 distractor sets from 995 source pairs, including retries. Caption-based validation rejects 826 sets in which at least one distractor is supported before the query timestamp and accepts 737, each associated with a unique source QA. Balanced split assembly retains 389 of these validated candidates.

Raw-video validation covers all 389 retained StreamBench instances. The 151 OVO-Bench HLD instances are inherited without modification and are not part of this vali-

Table 9. Qwen3-VL memory settings in the main comparison and the matched-6K comparison. Active context denotes the visual context available to the backbone for answering. The 6K limit does not include CPU archive storage.

Method	Main-comparison setting	Matched-6K setting
StreamChat	No persistent visual KV cache. At each query, its native retrieval selects frames from a CPU-side archive to form a fresh visual context.	The archive and retrieval procedure are unchanged, while the retrieved visual context supplied to the backbone is limited to 6K.
StreamBridge	Visual embeddings are accumulated in a memory buffer and progressively compressed. When a question arrives, the current buffer is used to prefill the backbone under its native 16K context limit.	The same query-time prefilling procedure, with the embedding buffer compressed to fit the 6K active-context limit.
StreamingVLM	A sliding window retaining 512 attention-sink tokens and up to 6,192 recent visual tokens, for 6.7K tokens in total.	The same sliding-window design with 512 attention-sink tokens and up to 5,632 recent visual tokens, for 6K tokens in total.
StreamClarify	TP-KV with a 10K-token budget, a 20 s full-granularity recent window, and older history retained at 25% token density.	The same TP-KV policy under a 6K budget, preserving the 20 s recent window and compressing older history to 25% token density.

Table 10. Video-level paired Macro accuracy intervals for the main-table configurations. Differences are StreamClarify minus the selected baseline and follow the one-decimal accuracies reported in Table 2. Differences and interval endpoints are percentage points. Intervals are computed from paired question-level correctness and 100,000 whole-video bootstrap replicates.

Dataset	Backbone	Selected baseline	Difference	Paired 95% CI
StreamBench	LLaVA-OV-1.5	StreamChat	$+0.2$	$[-2.4, +2.7]$
StreamBench	InternVL-3.5	StreamBridge	$+1.1$	$[-1.4, +3.6]$
StreamBench	Qwen3-VL	StreamingVLM	$+3.3$	$[+1.0, +5.7]$
OVO-Bench	LLaVA-OV-1.5	StreamBridge	$+8.2$	$[+2.2, +13.8]$
OVO-Bench	InternVL-3.5	StreamBridge	$+5.7$	$[-1.8, +13.2]$
OVO-Bench	Qwen3-VL	StreamBridge	$+7.8$	$[+2.4, +12.9]$

dation. For each StreamBench instance, we physically clip a separate visual prefix to $[0, t_q]$, sample it at 1 FPS, and remove audio. The resulting input contains no frame after the query timestamp.

Gemini 3.6 Flash performs three successive screening rounds, beginning with all 389 visual prefixes. An instance remains flagged only if the available prefix shows that the object or event assumed by the question is present and directly supports one particular answer option other than the abstention option. Both conditions are required so that a partial visual match is not counted as a label error. Seven instances remain flagged after all three rounds and are inspected by a human reviewer using the original visual prefixes. Human review confirms the original Unanswerable label for every instance. Thus, the validation finds no human-confirmed label error among the 389 screened instances. Gemini is used only to identify candidates, while human review provides the final decision.

D.2. Main-Table Paired Intervals

For each dataset and backbone, we select the strongest training-free baseline using unrounded Macro Accuracy and hold that selection fixed during resampling. We then resample complete videos with replacement and recompute Standard, Ambiguous, and Unanswerable QA accuracy from all sampled questions. Macro is their unweighted mean.

Table 11. Evaluator sensitivity in the generated-question analysis. Accuracies are percentages. Gains and interval endpoints are percentage points. Gain compares the entropy-gated condition with w/o Clarification. Intervals use paired whole-video resampling.

Judge	w/o	Direct	Gen. all	Gen. gated	Oracle	Gated gain (95% CI)
Qwen3-14B	22.5	22.8	34.8	30.8	38.4	$+8.3$ [4.2, 12.5]
GPT-5	20.5	22.2	37.4	31.1	42.4	$+10.6$ [6.5, 14.9]
Gemini 3.6 Flash	29.1	26.5	43.4	37.1	50.7	$+8.0$ [3.3, 12.8]

StreamClarify has higher Macro Accuracy in all six comparisons. The paired interval excludes zero for StreamBench/Qwen3-VL, OVO-Bench/LLaVA-OV-1.5, and OVO-Bench/Qwen3-VL. StreamBench contains 1,556 questions from 260 videos, and OVO-Bench contains 281 questions from 95 videos.

D.3. Evaluator Sensitivity Analysis

Table 4 uses Qwen3-14B as the primary semantic answer judge. We assess sensitivity to this choice by asking blinded GPT-5 and Gemini 3.6 Flash answer judges to score the same answers from w/o Clarification, Direct Retrieval, Generated Clarification, and Oracle Guidance. Each judge receives only the question type, question, reference answer, candidate answer, and query-time caption context. It evaluates the candidate answer without knowing which experimental condition produced it or how Qwen3-14B scored it. For the entropy-gated result, we follow the same selection used in Table 4, taking the Generated Clarification answer for the 162 selected queries and the w/o Clarification answer for the remaining 140.

Pairwise raw agreement ranges from 83.2% to 93.0%, with Cohen's κ ranging from 0.626 to 0.845. All accuracy results retain the complete 302-item denominator. The absolute accuracies vary across judges, but the entropy-gated gain remains positive in all three evaluations.

E. Trigger Score Robustness

Directional score comparison. We compare entropy with $p(\mathrm{No})$ using the `[Yes]/[No]` judgment probabilities on all 1,556 StreamBench queries. For a normalized binary

distribution, $p(\mathrm{No})$, $1 - p(\mathrm{Yes})$, and the signed `No`-versus-`Yes` logit margin produce the same ranking. Table 12 evaluates both rankings against direct-answer correctness. At a common 30.5% selection rate, entropy selects 280 incorrect answers, compared with 154 for $p(\mathrm{No})$.

Table 12. Directional score comparison on StreamBench with Qwen3-VL. Precision and Recall are measured at a common 30.5% selection rate (474/1,556 queries).

Score	Error AUROC	Precision (%)	Recall (%)
Entropy	**0.674**	**59.1**	**44.4**
$p(\mathrm{No})$	0.527	32.5	24.4

The category-conditioned AUROC values for Standard, Ambiguous, and Unanswerable QA are 0.592, 0.571, and 0.795 for entropy and 0.676, 0.632, and 0.138 for $p(\mathrm{No})$, respectively. Thus, the overall entropy advantage is concentrated on Unanswerable QA, while the directional score is slightly stronger on Standard and Ambiguous QA. A possible explanation is that, on Unanswerable QA, a confident `[No]` judgment may accompany correct abstention rather than an error. Entropy does not assign risk to either direction and instead reflects uncertainty between the two judgments.

Prompt perturbations. We denote the original prompt for each evaluated backbone as P0 and vary one component at a time. P1 replaces `Output` with `Respond` and changes one synonym in the final instruction, while retaining the label definitions and demonstrations. P2 only reverses the two demonstrations within each `[Yes]` and `[No]` section. P3 replaces them with two visually grounded and two general-knowledge demonstrations that do not occur verbatim in the benchmark annotations.

Each prompt is evaluated independently from the beginning of every video. All other model, decoding, streaming, memory, and evaluation settings remain fixed. P0 reproduces the original no-clarification outputs and scores.

Table 13. Error AUROC under Stage-1 prompt perturbations.

Dataset / Backbone	P0	P1	P2	P3
OVO-Bench / Qwen3-VL	0.704	0.707	0.709	0.721
StreamBench / Qwen3-VL	0.675	0.667	0.663	0.680
StreamBench / InternVL	0.641	0.638	0.635	0.639

Table 13 evaluates each score ranking against the errors produced by the corresponding prompt's regenerated answers. Across the perturbations, Error AUROC changes by -0.011 to $+0.017$ relative to P0, and Spearman correlation with the P0 ranking is 0.941–0.978. In a separate analysis, we compare every prompt's entropy ranking against the same answer errors from P0. The maximum absolute AUROC change is 0.011, so the ranking result is not explained by changes in the Stage-2 answers.

At the fixed operating threshold selected for each backbone, the prompt changes alter the trigger rate by at most 4.7 points. These results measure ranking and operating-point stability rather than probability calibration.

F. Memory Scalability and Clarification Cost

We conduct a memory scalability analysis to characterize how the offline CPU retrieval archive grows with streaming duration. The experiment is performed on an approximately 30-minute OVO-Bench video using Qwen3-VL-8B-Instruct with the 10K TP-KV configuration used in the main Qwen3-VL experiment. The archive maintains lightweight SigLIP2 retrieval keys and stores Qwen visual representations needed to reconstruct retrieved clips. Raw frames are excluded, and TP-KV is measured separately as the bounded active context rather than as part of the long-term archive.

The archive size grows monotonically and approximately linearly with video time. Over the approximately 30-minute stream, the archive stores about 1.8K Qwen vision clips and indexes about 3.6K frames with SigLIP2 retrieval keys. The Qwen vision-embedding archive occupies about 2.7 GiB, while the SigLIP2 retrieval index adds only about 8.5 MiB. Overall, the offline CPU archive grows at roughly 92 MiB per minute. This growth affects only the searchable CPU-side archive. The online TP-KV remains bounded by its compression policy, while clarification temporarily adds a fixed top-K set of retrieved clips. For longer streams, the searchable history can be limited by a retention policy such as a FIFO window, which bounds archive size without changing the TP-KV budget.

Generated-question analysis latency. When question generation is attempted for all 302 Ambiguous queries, the validity gate accepts 212 questions and the remaining 90 use Direct Retrieval. Mean latency is 0.168 s for the Stage-1 check, 0.665 s for question generation, 1.247 s for search-query generation, 0.031 s for archive search, 1.927 s for retrieved-visual prefilling, and 0.910 s for re-answering. The measured model and retrieval stages total 4.948 s, excluding the evaluation-only GPT-5 gate and any real-user response delay. The gate's 0.935 s wall time is reported separately. Under entropy gating, the Stage-1 check runs for every query, while the remaining clarification steps run only for selected queries.

G. Prompt Templates

We first list the default prompt structure used in StreamClarify's core pipeline. The additional prompt, validity gate, and simulated response used only in the generated-question analysis are listed separately. Stage 1 produces a binary `[Yes]`/`[No]` pre-answer judgment, and Stage 2 generates

the final answer conditioned on the Stage 1 output. The Multiple-Choice Constraint is appended to Stage 2 when answer options are provided. The Search Query Generation prompt is invoked after a clarification is triggered, converting the clarified user-side guidance into visual search phrases for offline retrieval.

G.1. Core Pipeline

Stage 1: Pre-Answer Judgment.

```
Output ONLY [Yes] or [No].
[Yes] = Your answer will be based on what
you SEE in the video (specific objects,
locations, actions).
- "Where did the person put the cup?" ->
[Yes] if you see the location in video.
- "What did the person just do?" -> [Yes]
if you observed the action.
[No] = Your answer will come from general
knowledge (could answer without watching
video).
- "How does a microwave work?" -> [No].
- "What are the benefits of exercise?" ->
[No].
If your answer references ANY specific
detail from the video, use [Yes].
```

Search Query Generation. Invoked on the clarification branch after clarified user guidance is available.

```
You are uncertain about answering this
question based on what you've seen so
far.
Question: "{question}"
Generate up to {max_phrases} visual
search phrase(s) to find missing but
important evidence.
Rules:
- 3 to 8 words per phrase.
- noun-phrase style preferred, with short
descriptive verbs allowed (e.g., "open
door", "person holding cup").
- avoid imperatives/commands (e.g., no
"look for", "find", "show").
- focus on concrete visible
entities/actions/scenes you need to find.
- output JSON list of strings only.
Output:
```

Stage 2: Answer Generation.

```
Answer the question directly without any
prefixes or bracketed tags.
RULES:
- If the question asks about THIS VIDEO
-> answer from video frames.
- If the question asks for GENERAL
KNOWLEDGE -> answer using your knowledge
directly.
Answer with complete sentences. Be
accurate and specific.
Do not add explanations unless asked.
For colors: standard terms only:
red/orange/yellow/green/blue/purple
pink/brown/black/white/gray/beige.
```

Multiple-Choice Constraint. This constraint is appended to Stage 2 when answer options are provided.

```
Multiple-choice response: select one
option from the provided choices.
Do not generate an answer outside the
provided options.
Output format: <number>. <option text>
(copy exactly). Start with the option
number.
```

G.2. Controlled Generated-Question Analysis

Generated-Question Prompt. This prompt is used only in the controlled generated-question analysis. Under entropy gating, it is invoked for the 162 queries selected by Stage 1. In the analysis without entropy selection, it is invoked for all 302 queries.

```
You need one piece of additional
user-side information before answering.

Ask exactly one short clarification
question that requests only the missing
user intent needed to interpret the
latest question.

Rules:
- If a word or phrase has an unclear
reference, ask what it refers to.
- Do not answer the user's question.
- Do not ask the user for information
that should be obtained from the video,
such as a location, color, action, state,
count, or yes/no fact.
- Do not guess, name, or suggest the
missing information yourself.
- Ask exactly one question.
- Use no more than 20 words.
- Output only the question.

Latest user question:
{latest_user_question}

Clarification question:
```

Evaluation-Only Validity Gate. This gate is used only in the controlled generated-question analysis. It receives the latest user query, the generated question, and the annotated referent, then returns a binary validity decision. It does not revise the question or produce a user response. Rejected questions use Direct Retrieval.

```
Determine whether the generated question
is a valid clarification of the latest
user question and can be answered
truthfully using only the provided
intended referent.

Return valid=true only if it asks for the
identity or meaning of the unclear
referent needed to interpret the latest
user question.

Return valid=false if it:
- asks for the original QA answer or a
video-grounded fact;
- asks for information not contained in
the intended referent;
- targets an unrelated expression;
- guesses, names, or suggests a candidate
referent;
- is a leading yes/no confirmation;
- is malformed or is not a clarification
question.

Do not answer either question.
Return only the structured binary
decision.

Gate input:
{
  "latest_user_question":  "...",
  "generated_question":  "...",
  "intended_referent":  "..."
}

Gate output:
{"valid":  true}
```

Simulated Referent-Only Response. For an accepted question, the simulator inserts the annotated referent into the fixed template below. Generated Clarification and Oracle Guidance therefore receive the same reply on accepted items.

```
I mean {referent}.
```