

MEGA 6KW/8KW/10KW/12KW/16KW

HYBRID SOLAR INVERTER / SINGLE PHASE



 High Efficiency
Max. 98%

 Wide MPPT
Range 50-450V

 Maximize PV Input
Power(2 MPPTs)

 Touchscreen

 Parallel Operation
Up to 6 Units

 WiFi

 2 Independent AC Inputs
2 Outputs

 Current
Transformer

MODEL	MEGA-6KW	MEGA-16KW
Phase	1-phase in /1-phase out	
Maximum Pv Input Power	9000W	21800W
Rated Output Power	6000W	16000W
Maximum Charging Power	6000W	14000W(56V)
GRID-TIED OPERATION		
PV INPUT (DC)		
Maximum DC Voltage	520Vdc	
Start-up Voltage /Initial Feeding Voltage	90Vdc/120Vdc	
MPPT Voltage Range	50-450Vdc	
Number of MPPT Trackers /Maximum Input Current	2/18A	3/18A+18A+36A
GRID OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	184-264.5 VAC or 195.5-253 VAC or 184-264.4 VAC(Selectable)	
Nominal Output Current	26.1A	69.6A
Power Factor	>0.99	
EFFICIENCY		
Maximum Conversion Efficiency (DC/AC)	97%	
OFF-GRID OPERATION		
AC INPUT		
AC Start-up Voltage /Auto Restart Voltage	120-140 VAC/180 VAC	
Acceptable Input Voltage Range	90-280 VAC	
Frequency Range	50 Hz/60 Hz(Auto sensing)	
Maximum AC Input Current	40A	100A(Passthrough)
PV INPUT (DC)		
Maximum DC Voltage	520Vdc	
MPPT Voltage Range	50Vdc-450Vdc	
Number of MPPT Trackers/Maximum Input Current	2/18A	3/18A+18A+36A
BATTERY MODE OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Output Waveform	Pure Sine Wave	
Efficiency (DC to AC)	93%	
HYBRID OPERATION		
PV INPUT(DC)		
Maximum DC Voltage	520Vdc	
Start-up Voltage/Initial Feeding Voltage	90Vdc/120Vdc	
MPPT Voltage Range	50Vdc-450Vdc	
Number of MPPT Trackers/Maximum Input Current	2/18A	3/18A+18A+36A
GRID OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	184-264.5 VAC or 195.5-253 VAC or 184-264.4 VAC(Selectable)	
Nominal Output Current	26.1A	69.6A
AC INPUT		
AC Start-up Voltage/Auto Restart Voltage	120-140 VAC/180 VAC	
Acceptable Input Voltage Range	90-280VAC or 170-280 VAC	
Maximum AC Input Current	40A	100A(Passthrough)
BATTERY MODE OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Efficiency (DC to AC)	93%	
BATTERY & CHARGER		
Nominal DC Voltage	48Vdc	
Maximum Solar Charging Current	135A	250A
Maximum AC Charging Current	135A	250A
Maximum Charging Current	135A	250A
GENERAL		
PHYSICAL		
Dimension, D x W x H(mm)	521x470x236	637.5x491x300.5
Net Weight (kg)	15	50
INTERFACE		
Parallel Function	Yes, 6 units	
Communication Port	RS232/RS485/CAN/Wi-Fi/Dry contact	
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
IP degree	IP65	
Operating Temperature	-10℃ ~ 50℃	
Storage Temperature	-15℃ ~ 60℃	