

# Parallelizing Strassen's Algorithm

Project 4.1

Zhu Liang

# Introduction

Strassen's: divide multiplication into [7 sub-multiplications](#).

- It improves efficiency with a potential *recursive* approach.


## **This project:**

- Parallel implementation of Strassen's to leverage efficiency.
- Explores three levels of recursive Strassen's decomposition.

# Table of Content

- Parallel Implementation
- Result & Analysis
- Summary

# Parallelization




Multi Level Master-Slave  
(Leader-Worker) network

Three Steps:


1. Distribute Data
2. Local Multiplication
3. Collect Result

# 1. Distribute Data




- **Leader** assembles  $M_i^A$  and  $M_i^B$  and sends to its workers.
- **Workers** receive its  $M_i^A$  and  $M_i^B$ .
- Repeat until reach the target level.

## 2. Local Multiplication



- **All** processors run its local multiplication

### 3. Collect Result



- **Workers** send results  $M_i$ .
- **Leader** receives and assembles into result  $C$ .
- Repeat until reach the *root*.

# Static Leader-Worker Tree

- Ranks determine [a static Leader-Worker relationship](#).
- Reuse leader as a worker.

## **Special Case:** *root* processor


- a dual role as both sender and receiver, which could lead to deadlock.
- MPI data transfer is not necessary, direct memory copying.



# Results

(in seconds)	Parallel Strassen Algorithm		
	level 1	level 2	level 3
	(cores = 7)	(cores = 49)	(cores = 343)
$N = 2^8$	0.029430	0.010317	0.040137
$N = 2^{10}$	1.757423	0.284435	0.274502
$N = 2^{12}$	63.811983	9.049598	2.902417

# Results



# Analysis

- **Trends**

- Speedup improves when matrices become larger.

- **Key Factors Affecting Trends**

- **Communication Overhead:** Bottleneck at high processor counts, significant for small  $N$ .
  - **Computation to Communication Ratio:** Better for large  $N$ , leading to higher speedup

- **Future Optimization**

- Improve load distribution among processors

# Summary

- Successfully implement the 3 levels via multi-level master-slave network.
- Build a static recursive tree to determine leader-worker relationship.
- It could further apply to higher levels of Strassen's.

Q & A

*Thanks for your attention!*

# Appendix: Strassen's Sub-Matrices

$M_i^A$	$M_i^B$	$M_i$	Assignment
$M_1^A = (A_{11} + A_{22})$	$M_1^B = (B_{11} + B_{22})$	$M_1 = M_1^A \times M_1^B$	$\rightarrow$ Worker 1
$M_2^A = (A_{21} + A_{22})$	$M_2^B = B_{11}$	$M_2 = M_2^A \times M_2^B$	$\rightarrow$ Worker 2
$M_3^A = A_{11}$	$M_3^B = (B_{12} - B_{22})$	$M_3 = M_3^A \times M_3^B$	$\rightarrow$ Worker 3
$M_4^A = A_{22}$	$M_4^B = (B_{21} - B_{11})$	$M_4 = M_4^A \times M_4^B$	$\rightarrow$ Worker 4
$M_5^A = (A_{11} + A_{12})$	$M_5^B = B_{22}$	$M_5 = M_5^A \times M_5^B$	$\rightarrow$ Worker 5
$M_6^A = (A_{21} - A_{11})$	$M_6^B = (B_{11} + B_{12})$	$M_6 = M_6^A \times M_6^B$	$\rightarrow$ Worker 6
$M_7^A = (A_{12} - A_{22})$	$M_7^B = (B_{21} + B_{22})$	$M_7 = M_7^A \times M_7^B$	$\rightarrow$ Worker 7

# Appendix: Static Relationship Tree by Rank

Leader Rank	Worker Ranks
0	[0, 1, 2, 3, 4, 5, 6]
1	[7, 8, 9, 10, 11, 12, 13]
2	[14, 15, 16, 17, 18, 19, 20]
3	[21, 22, 23, 24, 25, 26, 27]
4	[28, 29, 30, 31, 32, 33, 34]
5	[35, 36, 37, 38, 39, 40, 41]
6	[42, 43, 44, 45, 46, 47, 48]
...	...

- Level-1 leader:  $\{0\}$
- Level-2 Leaders:  $\{0, \rightarrow 6\}$
- Level-3 Leaders:  $\{0, \rightarrow 48\}$