

## Problem Set #4

[Help](#)

The **due date** for this quiz is **Mon 4 Aug 2014 2:59 PM CST**.

☐ In accordance with the Coursera Honor Code, I (朱顺) certify that the answers here are my own work.

### Question 1

Consider a directed graph with real-valued edge lengths and no negative-cost cycles. Let  $s$  be a source vertex. Assume that there is a unique shortest path from  $s$  to every other vertex. What can you say about the subgraph of  $G$  that you get by taking the union of these shortest paths? [Pick the strongest statement that is guaranteed to be true.]

- ☐ It is a directed acyclic subgraph in which  $s$  has no incoming arcs.
- ☐ It has no strongly connected component with more than one vertex.
- ☐ It is a path, directed away from  $s$ .
- ☐ It is a tree, with all edges directed away from  $s$ .

### Question 2

Consider the following optimization to the Bellman-Ford algorithm. Given a graph  $G = (V, E)$  with real-valued edge lengths, we label the vertices  $V = \{1, 2, 3, \dots, n\}$ . The source vertex  $s$  should be labeled "1", but the rest of the labeling can be arbitrary. Call an edge  $(u, v) \in E$  *forward* if  $u < v$  and *backward* if  $u > v$ . In every odd iteration of the outer loop (i.e., when  $i = 1, 3, 5, \dots$ ), we visit the vertices in the order from 1 to  $n$ . In every even iteration of the outer loop (when  $i = 2, 4, 6, \dots$ ), we visit the vertices in the order from  $n$  to 1. In every odd iteration, we update the value of  $A[i, v]$  using only the forward edges of the form  $(w, v)$ , using the *most recent* subproblem value for  $w$  (that from the current iteration rather than the previous one). That is, we compute  $A[i, v] = \min\{A[i-1, v], \min_{(w,v)} A[i, w] + c_{wv}\}$ , where the inner minimum ranges only over forward edges sticking into  $v$  (i.e., with  $w < v$ ). Note that all relevant

subproblems from the current round ( $A[i, w]$  for all  $w < v$  with  $(w, v) \in E$ ) are available for constant-time lookup. In even iterations, we compute this same recurrence using only the backward edges (again, all relevant subproblems from the current round are available for constant-time lookup). Which of the following is true about this modified Bellman-Ford algorithm?

- ☐ This algorithm has an asymptotically superior running time to the original Bellman-Ford algorithm.
- ☐ It correctly computes shortest paths if and only if the input graph is a directed acyclic graph.
- ☐ It correctly computes shortest paths if and only if the input graph has no negative edges.
- ☐ It correctly computes shortest paths if and only if the input graph has no negative-cost cycle.

### Question 3

Consider a directed graph in which every edge has length 1. Suppose we run the Floyd-Warshall algorithm with the following modification: instead of using the recurrence  $A[i, j, k] = \min\{A[i, j, k-1], A[i, k, k-1] + A[k, j, k-1]\}$ , we use the recurrence  $A[i, j, k] = A[i, j, k-1] + A[i, k, k-1] * A[k, j, k-1]$ . For the base case, set  $A[i, j, 0] = 1$  if  $(i, j)$  is an edge and 0 otherwise. What does this modified algorithm compute -- specifically, what is  $A[i, j, n]$  at the conclusion of the algorithm?

- ☐ None of the other answers are correct.
- ☐ The number of shortest paths from  $i$  to  $j$ .
- ☐ The length of a longest path from  $i$  to  $j$ .
- ☐ The number of simple (i.e., cycle-free) paths from  $i$  to  $j$ .

### Question 4

Suppose we run the Floyd-Warshall algorithm on a directed graph  $G = (V, E)$  in which every edge's length is either -1, 0, or 1. Suppose further that  $G$  is strongly connected, with at least one  $u-v$  path for every pair  $u, v$  of vertices. The graph  $G$  may or may not have a negative-cost cycle. How large can the final entries  $A[i, j, n]$  be, in absolute value? Choose the smallest number that is guaranteed to be a valid upper bound. (As usual,  $n$  denotes  $|V|$ .) [WARNING: for this question, make sure you refer to the implementation of the Floyd-Warshall algorithm given in lecture,

rather than to some alternative source.]

- ☐  $+\infty$
- ☐  $n^2$
- ☐  $2^n$
- ☐  $n - 1$

## Question 5

Which of the following events cannot possibly occur during the reweighting step of Johnson's algorithm for the all-pairs shortest-paths problem? (Assume that the input graph has no negative-cost cycles.)

- ☐ In a directed acyclic graph, reweighting causes the length of every path to strictly increase.
- ☐ Reweighting strictly increases the length of some  $s$ - $t$  path, while strictly decreasing the length of some  $t$ - $s$  path.
- ☐ The length of some edge strictly decreases after the reweighting.
- ☐ In a directed graph with at least one cycle, reweighting causes the length of every path to strictly increase.

☐ In accordance with the Coursera Honor Code, I (朱顺) certify that the answers here are my own work.

Submit Answers

Save Answers

You cannot submit your work until you agree to the Honor Code. Thanks!