

# Sampling and Monte Carlo Simulations

Lecturer: John Guttag

# Nondeterminism

## **Causal nondeterminism:**

Not every event is caused by previous events

## **Predictive nondeterminism:**

Lack of knowledge about the world makes it impossible make accurate predications about future states

# Stochastic Processes

An ongoing process where the next state might depend on both the previous states **and some random element**.

# Rolling a Die

```
def rollDie():  
    """returns an int between 1 and 6"""
```

```
def rollDie():  
    """returns a random int between 1 and 6"""
```



# Hash Tables

Lecturer: John Guttag



6.00x




Hash Tables

```
def strToInt(s):  
    number = ''  
    for c in s:  
        number = number + str(ord(c))  
    index = int(number)  
    return index
```

```
def hashStr(s, tableSize = 101):  
    number = ''  
    for c in s:  
        number = number + str(ord(c))  
    index = int(number)%tableSize  
    return index
```





6.00x

Hash Tables



6.00x

Hash Tables



6.00x

Hash Tables

# The Law of Large Numbers

Lecturer: John Guttag

# Law of Large Numbers

In repeated **independent tests** with the same **actual probability**  $p$  of a particular outcome in each test, the chance that the **fraction of times** that outcome occurs differs from  $p$  converges to zero as the number of trials goes to infinity.



6.00x

Law of Large Numbers

# Gambler's Fallacy

If deviations from expected behavior occur, these deviations are likely to be evened out by opposite deviations in the future.



6.00x

Law of Large Numbers


```
def flipPlot(minExp, maxExp):  
    """Assumes minExp and maxExp positive  
        integers; minExp < maxExp  
        Plots results of 2**minExp to  
        2**maxExp coin flips"""  
    ratios = []  
    diffs = []  
    xAxis = []  
    for exp in range(minExp, maxExp + 1):  
        xAxis.append(2**exp)  
  
    . . .
```

```
for numFlips in xAxis:
    numHeads = 0
    for n in range(numFlips):
        if random.random() < 0.5:
            numHeads += 1
    numTails = numFlips - numHeads
    ratios.append(numHeads/float(numTails))
    diffs.append(abs(numHeads - numTails))
```

• • •




```
pylab.title('Difference Between Heads and Tails')
pylab.xlabel('Number of Flips')
pylab.ylabel('Abs(#Heads - #Tails)')
pylab.plot(xAxis, diffs)
pylab.figure()
pylab.title('Heads/Tails Ratios')
pylab.xlabel('Number of Flips')
pylab.ylabel('Heads/Tails')
pylab.plot(xAxis, ratios)
```



6.00x

Law of Large Numbers



6.00x

Law of Large Numbers

# How Much Is Enough?

Lecturer: John Guttag



6.00x

How Much Is Enough?

## How Much is Enough?

How many samples do we need to look at in order to have a justified confidence that something that is true about the population of samples is also true about the population from which the samples were drawn?


Depends upon the variance in the underlying distribution

# Variance

We measure the amount of variance in the outcomes of multiple trials.


```
def stdDev(X):  
    mean = sum(X)/float(len(X))  
    tot = 0.0  
    for x in X:  
        tot += (x - mean)**2  
    return (tot/len(X))**0.5
```






6.00x

How Much Is Enough?




6.00x

How Much Is Enough?



6.00x

How Much Is Enough?




6.00x

How Much Is Enough?

# Standard Deviations and Histograms

Lecturer: John Guttag



6.00x

Standard Deviations and Histograms


```
def CV(X):  
    mean = sum(X)/float(len(X))  
    try:  
        return stdDev(X)/mean  
    except ZeroDivisionError:  
        return float('NaN')
```

```
def flip(numFlips):  
  
def flipSim(numFlipsPerTrial, numTrials):  
  
def labelPlot(nf, nt, mean, sd):  
  
def makePlots(nf1, nf2, nt):  
    """nt = number of trials per experiment  
        nf1 = number of flips 1st experiment  
        nf2 = number of flips 2nd experiment"""
```




```
def makePlots(numFlips1, numFlips2, numTrials):  
    val1, mean1, sd1 = flipSim(numFlips1, numTrials)  
    pylab.hist(val1, bins = 20)  
    xmin, xmax = pylab.xlim()  
    ymin, ymax = pylab.ylim()  
    labelPlot(numFlips1, numTrials, mean1, sd1)  
    pylab.figure()  
    val2, mean2, sd2 = flipSim(numFlips2, numTrials)  
    pylab.hist(val2, bins = 20)  
    pylab.xlim(xmin, xmax)  
    ymin, ymax = pylab.ylim()  
    labelPlot(numFlips2, numTrials, mean2, sd2)
```


```
vals = []  
for i in range(100000):  
    num = random.random()  
    vals.append(num)  
pylab.hist(vals, bins = 11)
```



```
vals = []
for i in range(100000):
    num = random.random()
    vals.append(num)
pylab.hist(vals, bins = 11)
xmin, xmax = pylab.xlim()
ymin, ymax = pylab.ylim()
print 'x-range =', xmin, '-', xmax
print 'y-range =', ymin, '-', ymax
pylab.figure
pylab.hist(vals, bins = 11)
#pylab.xlim(-1.0, 2.0)
```



6.00x



Standard Deviations and Histograms