

Simple, highly reliable network communication
system



ISE5005D Unmanaged Industrial Ethernet Switch

· Public Utility

· Smart Manufacturing

· Smart City

· Smart Energy

1. Product Overview

ISE5005D is a product designed specifically for power, transportation, industrial control, and other demanding industrial environments. It integrates features like wide-temperature and wide-voltage design, as well as protected industrial circuits.

Product Features:


- **Reliability & Resilience:** Fanless design, IP30 protection rating, robust metal casing, and wide-temperature operation.
- **Enhanced Security & Control:** QoS supported to process critical data in heavy traffic.
- **Convenient Deployment:** DIN rail mountable, compact dimensions, and fully plug-and-play.
- **Wide Power Input:** Wide-range power input design.
- **Switching Mechanism:** Possessing a quick store-and-forward mechanism.
- **DIP Switch Integration:** Quality of Service (QoS) and Broadcast Storm Protection (BSP) can be conveniently enabled or disabled through accessible hardware dip switches.
- **International Standard:** Complies with FCC, CE, ROHS, and UL standards.

Key Technical Specifications

Parameter	Specification
Type	Unmanaged Industrial Ethernet Switch
Ports	5 x 10/100/1000BaseT (RJ45)
Switching Performance	16 Gbps backplane, Store-and-Forward, 4K MAC
Dimensions / Weight	24 x 100 x 61.8 mm / 0.23 kg
Power	9.6-60 VDC & 18-30 VAC, 5 W
Environment	-40 to +75 °C operating, IP30

Parameter	Specification
EMC	IEC 61000-4-2/3/4/5/6/8/18 Class 3+
Certifications	CE, FCC, UL

2. Product Dimensions



ISE5005D

Note:

1. All dimensions are in millimeters (mm).
2. All dimensions are approximate and **for reference only**.
3. The dimensions shown in the figure **shall not be used for production or processing**.
4. Dimensions must comply with part and manufacturing tolerance requirements.
5. Dimensions are subject to change without notice.

3. Hardware Specifications

Category/Parameter	Specification
Physical Performance	
Enclosure	Fully enclosed seamless metal enclosure
Dimensions (W × D × H)	24 mm × 100 mm × 61.8 mm
Weight	0.23 kg
Mounting Method	DIN-rail mounting
Cooling Method	Fanless cooling
Ingress Protection	IP30
Storage Temperature	-40 °C ~ +85 °C
Operating Temperature	-40 °C ~ +75 °C
Humidity	5 ~ 95% (non-condensing)
Hardware Performance	
Backplane Bandwidth	16 Gbps
Processing Type	Store-and-Forward
MAC Table Size	4K
Packet Buffer Size	1.5 Mbits
Switching Delay	< 10 μs

Category/Parameter	Specification
DIP Switch	Quality of Service (QoS), Broadcast Storm Protection (BSP)
Power Parameters	
Operating Voltage	9.6–60 VDC & 18–30 VAC
Power Consumption	5 W
Overcurrent Protection	Supported
Reverse Polarity Protection	Supported
Electromagnetic Characteristics	
EMS	IEC(EN)61000-4-2, Class 3; IEC(EN)61000-4-3, Class 3 IEC(EN)61000-4-4, Class 3; IEC(EN)61000-4-5, Class 3 IEC(EN)61000-4-6, Class 3; IEC(EN)61000-4-8, Class 5 IEC(EN)61000-4-18, Class 3
Certifications	
Certifications	CE, FCC, UL
Quality Assurance	
Warranty Period	5 years
MTBF	35 years

DIP Switch Settings

Users can use the DIP switch on the device panel to enable/disable Quality of Service (QoS) and Broadcast Storm Protection (BSP) functions. Fast Ethernet ports support 10/100 Mbps auto-negotiation.

Category/Parameter	Specification
Quality of Service (QoS) – On	Enables the QoS function, processes packet priorities in 2 WRR queues. Priority 7,6,5,4 → Queue 1 (WRR Weight 16); Priority 3,2,1,0 → Queue 0 (WRR Weight 1)
Quality of Service (QoS) – Off	Disables the QoS function
Broadcast Storm Protection (BSP) – On	Enables broadcast storm protection for all ports (allows max 200 broadcast packets per second)
Broadcast Storm Protection (BSP) – Off	Disables the broadcast storm protection function

4. Ordering Guide

Model	Description
ISE5005D-P-5GT-24	5-port Layer 2 unmanaged Industrial Switch. 5 * 10/100/1000BaseT Ports. IP30 Protection Class, Operating Temperature from -40°C to +75°C. Single power input: 12/24/48 VDC (9.6~60VDC) or 24 VAC (18~30 VAC) (Only connect to class 2 power supply).

5. Contact Us

- Website: [InHand Networks](#)
- Copyright: ©InHand Networks All rights reserved