

VILAS: A VLA-Integrated Low-cost Architecture with Soft Grasping for Robotic Manipulation

Zijian An¹, Hadi Khezam¹, Bill Cai¹, Ran Yang², Shijie Geng^{3*}, Yiming Feng², Yue (Luna) Zheng¹, and Lifeng Zhou^{1**}

¹ Drexel University, Philadelphia, PA 19104, USA
`{za382,hk542,sc3568,yz894,lz457}@drexel.edu`

² Virginia Seafood Agricultural Research and Extension Center, Virginia Tech, 15
 Rudd Ln, Hampton, VA 23669, USA
`{ryang17,yimingfeng}@vt.edu`

³ Amazon Store Foundation AI (SFAI), 12 W 39th St, New York, NY 10018, USA
`{jeykigung}@gmail.com`

Abstract. We present VILAS, a fully low-cost, modular robotic manipulation platform designed to support end-to-end vision-language-action (VLA) policy learning and deployment on accessible hardware. The system integrates a Fairino FR5 collaborative arm, a Jodell RG52-50 electric gripper, and a dual-camera perception module, unified through a ZMQ-based communication architecture that seamlessly coordinates teleoperation, data collection, and policy deployment within a single framework. To enable safe manipulation of fragile objects without relying on explicit force sensing, we design a kirigami-based soft compliant gripper extension that induces predictable deformation under compressive loading, providing gentle and repeatable contact with delicate targets. We deploy and evaluate three state-of-the-art VLA models on the VILAS platform: π_0 , $\pi_{0.5}$, and GR00T N1.6. All models are fine-tuned from publicly released pretrained checkpoints using an identical demonstration dataset collected via our teleoperation pipeline. Experiments on a grape grasping task validate the effectiveness of the proposed system, confirming that capable manipulation policies can be successfully trained and deployed on low-cost modular hardware. Our results further provide practical insights into the deployment characteristics of current VLA models in real-world settings.

Keywords: Low-Cost Modular Manipulation System, Vision-Language-Action Models, Soft Gripper

1 INTRODUCTION

Robotic manipulation of fragile objects, such as fresh agricultural products, remains a challenging problem in both industrial and research settings [2]. Unlike

* This work is independent of and outside of the author’s work at Amazon.

** Corresponding author

rigid industrial parts, fragile items such as tomatoes or berries possess low tolerance to excessive contact force and are easily damaged during grasping [15, 26]. Reliable manipulation therefore requires careful coordination between perception, control, and mechanical design to ensure stable handling without inducing crushing or surface damage.

In addition to the intrinsic fragility of such objects, safe physical interaction often relies on precise regulation of contact forces. Conventional approaches achieve this through multi-axis force–torque sensors, tactile arrays, impedance control, or specialized end-effectors tailored for delicate handling [16, 19, 22]. While effective, these sensing and control modules increase both hardware cost and system complexity, particularly when integrated into fully functional robotic learning platforms.

Soft and compliant grippers have emerged as a promising alternative, providing passive mechanical compliance that absorbs contact force variations without active sensing [17, 24]. By offloading control complexity to the mechanical design itself, compliant end-effectors can enable gentle and repeatable grasping of delicate objects without relying on closed-loop force regulation [30]. However, existing soft gripper designs are often task-specific or require specialized fabrication processes, limiting their accessibility and integration into general-purpose low-cost manipulation platforms.

Recent advances in Vision-Language-Action (VLA) models have introduced a unified perception-to-action paradigm for robotic control [4, 12]. By directly mapping multimodal observations to executable actions, VLA-based systems reduce reliance on manually engineered modular pipelines and enable flexible task generalization [1, 14, 29]. However, training and deploying such models typically depends on high-cost robotic platforms equipped with integrated hardware ecosystems [6, 9, 23, 31]. As a result, the financial barrier for developing and experimenting with learning-based manipulation systems remains substantial [7, 13, 18].

In this work, we present VILAS, a fully low-cost, modular robotic manipulation platform designed to address fragile object manipulation from a system-level perspective, with the explicit goal of enabling VLA-based learning on affordable hardware. Rather than relying on a unified proprietary robotic ecosystem, we construct a complete manipulation platform from independently selected, cost-efficient components integrated through a custom-developed control and data collection framework tailored for VLA training [8]. To mitigate reliance on expensive force-sensing modules, we introduce a kirigami-based soft compliant extension attached to the end-effector, which passively absorbs contact force variations and provides intrinsic safety during grasping without additional sensing hardware. We further validate the platform by deploying and benchmarking three state-of-the-art VLA models on identical hardware and demonstration data, providing practical insights into their comparative deployment characteristics.

The primary contributions of this paper are as follows:

- We design and implement VILAS, a fully integrated low-cost robotic manipulation platform that supports the complete VLA workflow, covering teleoperation-based data collection, policy fine-tuning, and real-time deployment, using modular and affordable hardware components.
- We design a mechanically compliant kirigami-based soft extension that facilitates safe manipulation of fragile objects without relying on explicit force sensing or complex force-control strategies.
- We deploy and evaluate three state-of-the-art VLA models, namely π_0 [3], $\pi_{0.5}$ [10], and GR00T N1.6 [20,21], on the VILAS platform using an identical demonstration dataset, and demonstrate that capable manipulation policies can be successfully trained and deployed on low-cost modular hardware, while providing empirical insights into the practical trade-offs across models.

2 Related Work

Vision-Language-Action model. Recent advances in robotic learning have increasingly shifted from modular perception–planning–control pipelines toward unified learning-based frameworks [4,12]. VLA models represent a prominent direction within this paradigm, aiming to directly map visual observations and language instructions to executable robot actions through end-to-end policy learning [14]. By jointly leveraging visual context and task-level language guidance, VLA models enable scalable and generalizable robotic control across diverse manipulation tasks. Existing approaches include transformer-based autoregressive action prediction [31] as well as diffusion or flow-matching formulations [5] for modeling continuous control outputs. Among these, π_0 combines a pre-trained vision-language model with a flow matching action expert to enable continuous action generation conditioned on visual observations and language instructions [3], while $\pi_{0.5}$ extends this architecture with a heterogeneous mixture-of-experts design and large-scale internet data pre-training to improve generalization across diverse tasks and environments [10]. NVIDIA Isaac GR00T N1.6 similarly adopts a vision-language model backbone paired with a diffusion transformer head for action generation, and is further trained on thousands of hours of cross-embodiment teleoperation data to support generalization across heterogeneous robot platforms [20]. In this work, we evaluate all three of these models deployed on a fully low-cost robotic manipulation platform, assessing their performance under end-to-end perception-to-action learning on modular hardware.

Low-Cost Robotic Arm. A complete robotics learning system typically comprises several key components. First, the robot arm serves as the primary executor of manipulation tasks, providing the actuation and kinematic degrees of freedom required to interact with the environment [9,31]. Second, a teaching interface or teleoperation device is used for demonstration collection, allowing human operators to guide the robot’s motion and generate high-quality ground-truth data for learning [8,28]. By physically controlling the teaching interface,

the corresponding robot arm movements are recorded, forming the basis for imitation learning or other data-driven training paradigms. Third, one or more cameras form the visual perception module, capturing images or video streams that encode the scene context and object states observed during task execution [5, 25]. These visual inputs are essential for perception-driven control and policy learning.

There exist commercially available systems designed to support learning-based robotic manipulation research. A representative example is the ALOHA system [31]. ALOHA supports end-to-end imitation learning by collecting real-world demonstrations through a teleoperation interface and enables bimanual manipulation tasks on a mobile platform. The system integrates robotic hardware, teleoperation components, and perception modules into a unified setup tailored for data collection and policy training. Complete ALOHA hardware kits are available for purchase at approximately \$33,000 USD, providing a ready-to-deploy platform for real-world robotic learning experiments. However, ALOHA relies on Dynamixel servo motors, which are widely used in academic research platforms but are known to exhibit discrete stepping behavior and limited motion smoothness under continuous control. In contrast, the VILAS platform is built around the Fairino FR5, an industrial-grade collaborative arm driven by brushless DC motors, which produce inherently smoother and more continuous motion profiles. This mechanical characteristic is particularly beneficial for delicate manipulation tasks, where abrupt joint movements can compromise grasping precision or cause unintended contact forces on fragile objects.

Soft Gripper. There has been great development of compliant kirigami-based structures for soft robotic grippers, where strategically placed cuts allow thin sheets to undergo large, controlled shape transformations. In kirigami mechanisms, patterns such as parallel slits, staggered slit arrays, rotating square lattices, auxetic polygonal cuts, elliptical hole patterns, and periodic circular or create flexible ligaments that rotate and buckle under loading. This enables planar sheets to expand into three-dimensional grasping geometries. The mechanical response of these structures depends strongly on the geometry, spacing, and orientation of the cuts. Depending on these geometry cuts, this determines stiffness and deformation modes during stretching or bending [11]. Several soft gripper designs exploit these mechanisms by transforming patterned sheets into curved gripping surfaces under simple actuation. Using a parallel slit kirigami pattern expands laterally to produce curvature that encloses objects, while hole pattern kirigami sheets generate shell like gripping structures through ligament rotation between perforations. A notable implementation is the kirigami shell gripper where a flat sheet with periodic hole arrays forms a three-dimensional shell when pulled by a single actuator, enabling adaptive grasping across objects of varying shapes and sizes [30]. Other studies have explored auxetic kirigami lattices and polygonal cut units to regulate surface curvature and improve contact area during grasping [27]. Kirigami grippers are typically fabricated using laser cutting of thin polymer sheets such as PET or polypropylene to produce precise slit or perforation geometries, recent work has demonstrated 3D print-

ing approaches, including FDM and resin-based printing, to directly fabricate kirigami inspired compliant structures. In most implementations, the kirigami sheet is fixed to the actuation mechanism through mechanical clamping, adhesive bonding, or embedding within elastomer layers, allowing tendon driven tension or pneumatic inflation to stretch the patterned sheet and generate out of plane curvature buckling. These kirigami architectures enable lightweight, highly deformable grippers that conform to objects and distribute contact forces effectively, making kirigami a promising design strategy for adaptive soft robotic manipulation.

3 System Overview

3.1 System Architecture

As illustrated in Figure 1, our VILAS system consists of a physical robotic platform and a two-stage operational pipeline covering data collection and policy deployment. The robotic platform centers on a Fairino FR5 manipulator equipped with a Jodell end-effector and a soft compliant gripper, observed by a base camera (RealSense D455) and a wrist camera (RealSense D405). During data collection, a human operator controls the FR5 via a GELLO leader arm through a ZMQ communication layer; at each timestep t , the system records a 7-dimensional joint state vector, dual-camera RGB observations, and a language prompt, which are stored as structured episode files. During deployment, the observation tuple consisting of joint states, dual-camera images, and a language prompt is passed to the policy model, which outputs an action chunk of shape (50×7) for π_0 and $\pi_{0.5}$, and (16×7) for GR00T N1.6, covering six arm joints and one gripper dimension, executed sequentially on the FR5 and Jodell gripper at 20 Hz.

3.2 Hardware Platform

The primary manipulator is a Fairino FR5, a six-degree-of-freedom industrial-grade collaborative robotic arm designed for real-world deployment in manufacturing and automation environments. With a 922 mm reach, 5 kg payload capacity, and ± 0.02 mm pose repeatability (ISO 9283), the FR5 offers a level of mechanical precision and motion smoothness typically associated with professional-grade industrial systems. These specifications are well-suited for tabletop manipulation tasks such as pick-and-place and grasping, where moderate reach, sub-millimeter precision, and lightweight end-effector compatibility are the primary requirements. The FR5 communicates via standard TCP/IP and supports ROS/ROS2 integration, enabling straightforward interfacing with learning-based control pipelines. Critically, the FR5 achieves this capability at a hardware cost of approximately **\$4,000 USD**, placing it among the most cost-accessible industrial cobots in its payload class.

The end-effector is a Jodell RG52-50 electric parallel gripper, featuring an adjustable stroke of 52 mm, a controllable gripping force ranging from 2 N to 50 N,




Fig. 1: Overview of the VILAS system. (Left) The physical robotic platform. (Center and Right) The data collection and training-and-deployment pipelines.

and a position repeatability of ± 0.02 mm. The gripper is connected to the control workstation via USB, using Modbus RTU as the underlying device protocol, and supports independent control of position, force, and speed, enabling compliant and precise interaction with objects of varying geometry and fragility. Its IP65-rated enclosure and low operating noise (< 40 dB) further make it suitable for close-range manipulation in unstructured environments. At a hardware cost of approximately **\$1,500 USD**, the RG52-50 provides industrial-grade gripping performance at a fraction of the cost of comparable force-controlled end-effectors.

For demonstration collection, we employ a GELLO teleoperation arm [28], a low-cost, open-source leader device constructed from 3D-printed parts and off-the-shelf Dynamixel servo motors, with a total hardware cost of approximately **\$500 USD**. GELLO is designed as a kinematically equivalent replica of the target arm, such that each joint of the leader maps directly and one-to-one to the corresponding joint of the follower, eliminating the need for inverse kinematics and enabling intuitive, joint-space teleoperation. Our GELLO configuration mirrors the seven-degree-of-freedom structure of the FR5 system, comprising six arm joints and one gripper joint, ensuring full kinematic correspondence between the leader and follower during demonstration collection. The GELLO arm is connected to the control workstation via USB, with joint angle readings transmitted using the Dynamixel SDK.

The perception module consists of two Intel RealSense depth cameras selected to provide complementary sensing coverage across the full manipulation workspace. The RealSense D455 is mounted at a fixed overhead position to monitor the global workspace. With an 86° field of view, a depth range of up to 4 m, and a depth error of less than 2% at 4 m, the D455 is well-suited for scene-level object localization and workspace context. A RealSense D405 is mounted in

close proximity to the end-effector to capture fine-grained visual feedback during gripper-object interaction. The D405 is optimized for short-range sensing, operating at an ideal range of 7 cm to 50 cm with sub-millimeter depth accuracy, and features a compact form factor of $42\text{ mm} \times 42\text{ mm} \times 23\text{ mm}$ suitable for wrist-mounted deployment. Both cameras are connected via USB and provide synchronized RGB and depth streams through the Intel RealSense SDK 2.0. With a combined hardware cost of approximately **\$1,000 USD**, this dual-camera configuration was selected as a cost-effective solution that satisfies the complementary requirements of global scene awareness and local contact-level observation, without relying on high-cost industrial vision systems.

3.3 Soft Compliant End-Effector

A low cost kirigami based pattern was developed to be used as a soft extension grabber for a safe and effective method of handling delicate objects as shown in Figure 2. Cut patterns were adapted from previously validated kirigami shell configurations [30], with modifications to enable integration with a commercial parallel electric gripper (RG series). Expanding on previous work, the cuts on this kirigami structure side interfacing with the gripper were shortened to locally increase stiffness and reduce premature folding near the holder interface. The central cut lengths were extended to amplify deformation and promote smooth curvature formation under compressive loading. In addition, a kirigami extension was added

at the distal end of the structure, increasing the overall length. This extension increased the effective contact region and enabled stable grasping of objects with varying diameters and curvatures as needed. The cut geometry was strategically designed to induce predictable deformation pathways, forcing the structure to bend in a prescribed direction under compressive input and improving repeatability across fabrication runs. Fabrication was performed using fused deposition modeling (FDM), printing the holder and kirigami structure as a single integrated PEBA component on a Bambu Lab H2D at $250\text{ }^{\circ}\text{C}$ nozzle and $50\text{ }^{\circ}\text{C}$ bed temperatures. PEBA was selected for its rapid "snap-back" elasticity, and the combined print reduced assembly and alignment errors, with each build taking 45 minutes and 70 g of filament to enable rapid, low-cost iteration.

The RG series gripper employs a two-finger parallel jaw configuration, which constrains the actuation to a single translational degree of freedom. To mechan-




Fig. 2: Kirigami structure design and experimental demonstration. (a) Photograph of the fabricated kirigami structure buckled within a gripper during testing, (b) Top view in Fusion 360, (c) Isometric view in Fusion 360.

ically couple the kirigami structure to this gripper, a custom holder mechanism was integrated directly with the kirigami design, as demonstrated in Figure 2. The holder attaches to the gripper fingers via a friction fit interface, enabling rapid mounting and removal without additional fasteners, adhesives, or permanent modifications. This design choice allows the kirigami gripper to be easily replaced or reconfigured for different experimental conditions. This inclined interface extends the effective closed length of the gripper which increases the achievable buckling curvature and expands the grasping envelope of the soft gripper, allowing it to envelop objects with larger diameters and irregular geometries while maintaining low contact forces. The inclined holder geometry also improves load distribution at the mounting interface, reducing stress concentration and improving durability over repeated actuation cycles. With this design we insured there is adequate buckling over long periods of actuation for a low-cost monolithic soft gripper. The kirigami extension is fabricated from off-the-shelf PEBA filament at a material cost of under **\$100 USD** per unit, further reinforcing the low-cost design philosophy of the overall platform.

The total hardware cost of the VILAS platform, comprising the FR5 arm, Jodell RG52-50 gripper, GELLO teleoperation arm, dual RealSense cameras, and soft compliant extension, amounts to approximately **\$8,000 USD**, which is substantially lower than the \$33,000 USD cost of a comparable ALOHA system⁴.

3.4 Communication and Control Architecture

The FR5 manipulator communicates with the control workstation through an Ethernet-based TCP/IP interface provided by its controller, while a lightweight ZMQ wrapper standardizes access to low-level vendor commands and real-time state feedback by exposing unified arm command and observation endpoints to the teleoperation client. The Jodell gripper is similarly encapsulated within a ZMQ-based service layer, which abstracts the underlying device communication (connected via USB, using Modbus RTU protocol) and provides consistent control and state interfaces aligned with the arm module.

The GELLO teleoperation arm operates within the client process and continuously supplies leader joint states; during teleoperation, these leader commands are transmitted through the ZMQ communication layer to the FR5 and Jodell modules, which execute the corresponding arm and gripper motions while returning synchronized feedback. This architecture establishes a bidirectional communication pipeline that coordinates leader input, follower execution, and state observation within a unified control framework. This architecture establishes a bidirectional communication pipeline that coordinates leader input, follower execution, and state observation within a unified control framework, as illustrated in Figure 3.

⁴ To facilitate reproducibility and accessibility within the research community, we will release the full hardware specifications, software stack, and step-by-step assembly and deployment tutorials upon acceptance of this work.

The teleoperation loop operates at 83.3 Hz, at which rate the GELLO arm reads operator joint angles via USB using the Dynamixel SDK and forwards them to the FR5 and Jodell modules through the ZMQ layer. Camera images are captured at 30 Hz at a native resolution of 640×480 and resized to 224×224 on the client side prior to transmission.




Fig. 3: Communication architecture of the VILAS system during data collection. The Control Workstation runs a unified Client Process comprising three layers: the Dynamixel SDK for GELLO joint reading, the RealSense SDK for camera image acquisition, and a ZMQ Layer that encapsulates communication with the FR5 arm (via Ethernet) and Jodell gripper (via USB). A Data Recorder aggregates all streams into synchronized episode files.

During policy deployment, the control loop runs at 20 Hz. Rather than invoking the model at every control step, we adopt an action chunking strategy in which a single inference call produces a chunk of 50 actions with shape (50×7) , covering 6 arm joints and 1 gripper dimension. A broker module executes one action per control step from the cached chunk; once the chunk is exhausted after 2.5 seconds, a new inference call is triggered. This decouples the high-frequency control loop from the relatively expensive model inference, which effectively runs at approximately 0.4 Hz, and is consistent with the action chunking formulation introduced in π_0 .

Model inference is handled by a dedicated GPU server connected to the robot workstation over a local network. The client is responsible only for observation collection and action execution, keeping the robot-side compute requirements minimal. For π_0 and $\pi_{0.5}$, inference is served via a WebSocket interface, with model selection controlled through a configuration parameter, allowing the two models to share an identical client-side interface. GR00T N1.6 is deployed via an independent ZMQ-based inference server, as its native deployment framework (NVIDIA Isaac GR00T) exposes a ZMQ endpoint by default, in contrast to the WebSocket-based serving interface provided by the π_0 codebase. While this results in heterogeneous communication protocols across models, the client-side observation format remains unified, and model switching requires only a change in the target server address and protocol adapter. In both cases, the observation passed to the server consists of a 7-dimensional joint state vector (6 arm joint angles in radians plus a normalized gripper value) and two RGB image streams corresponding to the global workspace camera and the wrist-mounted camera, with a zero-filled placeholder retained for interface compatibility.

3.5 Data Collection Pipeline

During data collection, a human operator controls the FR5 manipulator in real time via the GELLO teleoperation arm. Joint angle commands from the GELLO leader arm are transmitted through the ZMQ communication layer to the FR5 and Jodell modules, which execute the corresponding motions while returning synchronized state feedback. At each time step, the 7-dimensional joint state vector and dual-camera RGB observations are recorded and stored as structured episode files. Following collection, the dataset is preprocessed and reformatted into the input schema required by each respective model’s training framework.

4 Experiments

4.1 Experimental Setup

For policy learning, we evaluate three VLA models: π_0 , $\pi_{0.5}$, and GR00T N1.6. Rather than training from scratch, all models are initialized from their respective publicly released pretrained checkpoints and fine-tuned on the same demonstration dataset collected from our teleoperation pipeline, consisting of 100 demonstration episodes each comprising 1,200 frames. At each time step, the dataset includes synchronized visual observations from two cameras (a global workspace view and a close-range end-effector view), together with the corresponding robot joint states comprising six arm joints and one gripper joint (7-DoF in total). The recorded state–action pairs are formatted into structured datasets compatible with the respective training frameworks of each model. Fine-tuning for all three models is conducted on an NVIDIA H200 GPU for 50,000 optimization iterations.




Fig. 4: Policy deployment overview and representative execution sequence using GR00T N1.6. (a) Initial system state, with the inset diagram illustrating the deployment communication architecture: dual-camera observations and robot joint states are forwarded to the Policy Server, which outputs an action chunk dispatched via the ZMQ Layer to the FR5 arm and Jodel gripper at 20 Hz. (b)–(g) Sequential grasping execution: (b) approaching the first target grape, (c) grasping the first grape, (d) depositing it into the target box, (e) re-localizing the second target grape, (f) grasping the second grape, and (g) completing the second deposit.

4.2 Task Description

We evaluate all models on a grape grasping task performed on a tabletop workspace of approximately 30×40 cm. At the beginning of each trial, 10 grapes are placed at random positions within the workspace. The robot is tasked with sequentially grasping three grapes and depositing each into a small target box positioned at a fixed location on the table. No homing or reset motion is performed between consecutive grasps; upon completing one grasp-and-place cycle, the robot proceeds directly to the next target. The grape placement follows the same randomization protocol used during demonstration collection, ensuring consistency between training and evaluation conditions. To further assess cross-object generalization, we additionally evaluate all three models on a cherry grasping task in Section 4.5, using the same grape-trained policies without any additional fine-tuning.

4.3 Evaluation Protocol

Each model is evaluated over 50 trials. We report two success metrics: *single grasp success rate*, defined as the proportion of trials in which at least one grape is successfully grasped and deposited, and *multi grasp success rate*, defined as the proportion of trials in which at least two consecutive grasps are completed

Table 1: Comparison of inference latency and grasping success rate across three VLA models. All models are evaluated over 50 trials on the grape grasping task. Per-step cost is computed as mean latency divided by action horizon.

Model	Inference Latency				Action Horizon	Per-step Cost	Success Rate	
	Mean	Median	Std	P95			Single (=1)	Multi (≥ 2)
π_0	73.8 ms	73.8 ms	0.4 ms	74.6 ms	50	1.48 ms	70%	22%
$\pi_{0.5}$	82.8 ms	82.3 ms	2.4 ms	87.3 ms	50	1.66 ms	84%	36%
GR00T N1.6	63.6 ms	63.7 ms	1.2 ms	65.0 ms	16	3.98 ms	82%	58%

successfully. These two metrics jointly capture both basic manipulation competence and the ability to sustain reliable performance across sequential grasping attempts.

4.4 Results

Table 1 summarizes the inference latency and grasping success rates of all three models. In terms of single grasp success, $\pi_{0.5}$ achieves the highest rate at 84%, marginally outperforming GR00T N1.6 at 82%, while π_0 lags behind at 70%. However, the multi grasp metric reveals a more pronounced differentiation: GR00T N1.6 achieves a success rate of 58%, substantially higher than $\pi_{0.5}$ at 36% and π_0 at 22%. This suggests that while $\pi_{0.5}$ and GR00T N1.6 exhibit comparable competence on individual grasps, GR00T N1.6 demonstrates superior consistency across sequential manipulation steps.

Figure 4 presents the deployment communication architecture alongside a representative successful trial using GR00T N1.6. As shown in the inset of Figure 4(a), during deployment the robot receives no teleoperation input; instead, the policy server autonomously generates action chunks from visual observations and joint state feedback, which are executed at 20 Hz via the ZMQ layer. The execution sequence in Figures 4(b)–(g) demonstrates the robot successfully completing two consecutive grasp-and-place cycles without intervention, consistent with GR00T N1.6’s leading multi-grasp success rate of 58%.

Regarding inference latency, GR00T N1.6 achieves the lowest mean latency at 63.6 ms, followed by π_0 at 73.8 ms and $\pi_{0.5}$ at 82.8 ms. All three models exhibit low standard deviations, indicating stable inference behavior suitable for real-time deployment. However, a direct latency comparison is complicated by differences in action horizon: π_0 and $\pi_{0.5}$ generate action chunks of 50 steps per inference call, while GR00T N1.6 produces chunks of 16 steps, a constraint imposed by its pretraining architecture. In our deployment, we adopt the maximum supported action horizon for each model: 50 steps for π_0 and $\pi_{0.5}$, and 16 steps for GR00T N1.6. Using the maximum chunk size minimizes inference frequency, reduces communication overhead between the robot workstation and the remote GPU server, and produces smoother motion trajectories by allowing the model




Fig. 5: Execution sequence of the cherry grasping task using the π_0 model without any modification to the model weights or fine-tuning data. (a) Initial state with cherries randomly placed on the workspace. (b) Approaching the target cherry. (c) Grasping the target cherry. (d) Transporting the cherry toward the target box. (e) Depositing the cherry into the target box. (f) Task completion.

to plan over a longer action horizon before re-querying. When normalized by action horizon, the per-step inference cost of GR00T N1.6 (3.98 ms) is notably higher than that of π_0 (1.48 ms) and $\pi_{0.5}$ (1.66 ms), suggesting that the lower raw latency of GR00T N1.6 is partly attributable to its shorter output sequence rather than a more efficient model architecture.

4.5 Generalization to Other Objects

To assess the generalizability of the learned policies beyond the training object, we evaluate all three models on a cherry grasping task using the same grape-trained policies without any additional fine-tuning. Only the language prompt and the physical object are replaced, with no modification to the model weights. Cherries present a distinct visual appearance from grapes, differing in size, color, and surface texture, making this a meaningful test of cross-object transfer. All three models demonstrate reasonable grasping performance on cherries, suggesting that the fine-tuned VLA policies capture manipulation primitives that generalize across visually distinct objects. Among the three, GR00T N1.6 shows comparatively more consistent performance, and its execution sequence is illustrated in Figure 5 as a representative example.

4.6 Failure Analysis

We identify distinct failure modes for each model family based on qualitative observation across evaluation trials.

For π_0 and $\pi_{0.5}$, two primary failure patterns are observed. First, both models exhibit a tendency to return to the same spatial location after completing the

first grasp, rather than searching for a new target. This suggests that the models fail to adequately update their spatial attention based on the current scene state, likely due to insufficient diversity in the demonstration data with respect to object layout variation. Second, gripper actuation consistency is poor in a subset of trials: the gripper intermittently releases during transport, causing the grasped object to drop, or repeatedly opens and closes at the target location without completing a successful grasp. This behavior indicates instability in the learned action chunks, particularly during the gripper closure phase.

GR00T N1.6 does not exhibit the same spatial repetition issue to the same degree, and gripper actuation is generally more consistent. However, it demonstrates a different failure pattern in multi-grasp trials: when searching for the second and third targets, the model tends to focus its search in the vicinity of the previous grasp location rather than exploring the broader workspace. As a result, multi-grasp success is sensitive to object placement density — trials in which remaining grapes happen to be clustered near the prior grasp site benefit this behavior, while sparser layouts lead to missed targets. This spatial bias likely reflects a prior learned from the pretraining data distribution, where objects in sequential manipulation tasks tend to be spatially proximate.

These observations are consistent with the quantitative results in Table 1: the relatively small gap between single and multi grasp success rates for GR00T N1.6 (82% vs. 58%) compared to π_0 (70% vs. 22%) and $\pi_{0.5}$ (84% vs. 36%) suggests that GR00T N1.6 degrades more gracefully across sequential grasps, even if it is not immune to multi-target localization failures.

5 Conclusion and Future Work

In this work, we presented VILAS, a fully low-cost robotic manipulation platform designed to enable end-to-end VLA-based policy learning and deployment on modular, affordable hardware. The platform integrates a Fairino FR5 collaborative arm, a Jodell RG52-50 electric gripper, a custom kirigami-based soft compliant extension, and a dual-camera perception module, unified through a ZMQ-based communication architecture that supports seamless teleoperation, data collection, and policy deployment within a single framework. We deployed and benchmarked three state-of-the-art VLA models, namely π_0 , $\pi_{0.5}$, and GR00T N1.6, all fine-tuned from publicly released pretrained checkpoints on an identical demonstration dataset. Experiments on a grape grasping task demonstrate that GR00T N1.6 achieves the highest multi-grasp success rate at 58%, outperforming $\pi_{0.5}$ (36%) and π_0 (22%), while $\pi_{0.5}$ leads on single grasp success at 84%. These results validate the effectiveness of VILAS as a reproducible and accessible testbed for VLA evaluation on real hardware.

Several directions remain for future work. On the task side, we plan to extend evaluation to more complex manipulation scenarios requiring longer-horizon reasoning and greater environmental diversity. On the hardware side, future iterations will explore soft gripper designs with improved lateral stiffness to enable reliable grasping in cluttered scenes.

References

1. An, Z., Yang, R., Feng, Y., Zhou, L.: Claw: A vision-language-action framework for weight-aware robotic grasping. arXiv preprint arXiv:2509.14143 (2025)
2. Ao, J., Ji, W., Yu, X., Ruan, C., Xu, B.: End-effectors for fruit and vegetable harvesting robots: A review of key technologies, challenges, and future prospects. *Agronomy* **15**(11), 2650 (2025)
3. Black, K., Brown, N., Driess, D., Esmail, A., Equi, M., Finn, C., Fusai, N., Groom, L., Hausman, K., Ichter, B., et al.: $\pi 0$: A vision-language-action flow model for general robot control. corr, abs/2410.24164, 2024. doi: 10.48550. arXiv preprint ARXIV.2410.24164
4. Brohan, A., Brown, N., Carbajal, J., Chebotar, Y., Chen, X., Choromanski, K., Ding, T., Driess, D., Finn, C., Florence, P., et al.: Rt-2: Vision-language-action models transfer web knowledge to robotic control. In: *Proceedings of The 7th Conference on Robot Learning*. pp. 2165–2183 (2023)
5. Chi, C., Xu, Z., Feng, S., Cousineau, E., Du, Y., Burchfiel, B., Tedrake, R., Song, S.: Diffusion policy: Visuomotor policy learning via action diffusion. *The International Journal of Robotics Research* (2023)
6. Collaboration, O.X.E., O’Neill, A., Rehman, A., Gupta, A., Maddukuri, A., Gupta, A., et al.: Open X-Embodiment: Robotic learning datasets and RT-X models. In: *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)* (2024)
7. Dass, S., Ai, W., Jiang, Y., Singh, S., Hu, J., Zhang, R., Stone, P., Abbatematteo, B., Martín-Martín, R.: Telemoma: A modular and versatile teleoperation system for mobile manipulation. arXiv preprint arXiv:2403.07869 (2024)
8. Fang, H., Fang, H.S., Wang, Y., Ren, J., Chen, J., Zhang, R., Wang, W., Lu, C.: Airexo: Low-cost exoskeletons for learning whole-arm manipulation in the wild. In: *2024 IEEE International Conference on Robotics and Automation (ICRA)*. pp. 15031–15038. IEEE (2024)
9. Fu, Z., Zhao, T.Z., Finn, C.: Mobile aloha: Learning bimanual mobile manipulation with low-cost whole-body teleoperation. In: *Conference on Robot Learning (CoRL)* (2024)
10. Intelligence, P., Black, K., Brown, N., Darpinian, J., Dhabalia, K., Driess, D., Esmail, A., Equi, M., Finn, C., Fusai, N., et al.: $\pi_{0.5}$: a vision-language-action model with open-world generalization. arXiv preprint arXiv:2504.16054 (2025)
11. Isobe, M., Okumura, K.: Initial rigid response and softening transition of highly stretchable kirigami sheet materials. *Scientific Reports* **6** (04 2016). <https://doi.org/10.1038/srep24758>
12. Kawaharazuka, K., Oh, J., Yamada, J., Posner, I., Zhu, Y.: Vision-language-action models for robotics: A review towards real-world applications. *IEEE Access* (2025)
13. Khazatsky, A., Pertsch, K., Nair, S., Balakrishna, A., Dasari, S., Karamcheti, S., Nasiriany, S., Srirama, M.K., Chen, L.Y., Ellis, K., et al.: Droid: A large-scale in-the-wild robot manipulation dataset. arXiv preprint arXiv:2403.12945 (2024)
14. Kim, M.J., Pertsch, K., Karamcheti, S., Xiao, T., Balakrishna, A., Nair, S., Rafailov, R., Foster, E., Lam, G., Sanketi, P., et al.: Openvla: An open-source vision-language-action model. arXiv preprint arXiv:2406.09246 (2024)
15. Kultongkham, A., Kumnon, S., Thintawornkul, T., Chanthasopeephan, T., et al.: The design of a force feedback soft gripper for tomato harvesting. *Journal of Agricultural Engineering* **52**(1) (2021)

16. Li, Z., Yuan, X., Yang, Z.: Design, simulation, and experiment for the end effector of a spherical fruit picking robot. *International Journal of Advanced Robotic Systems* **20**(6), 17298806231213442 (2023)
17. Liu, Y., Hou, J., Li, C., Wang, X.: Intelligent soft robotic grippers for agricultural and food product handling: A brief review with a focus on design and control. *Advanced Intelligent Systems* **5**(12), 2300233 (2023). <https://doi.org/10.1002/aisy.202300233>
18. Mandlekar, A., Zhu, Y., Garg, A., Booher, J., Spero, M., Tung, A., Gao, J., Emons, J., Gupta, A., Orbay, E., et al.: Roboturk: A crowdsourcing platform for robotic skill learning through imitation. In: *Conference on Robot Learning*. pp. 879–893. PMLR (2018)
19. Navas, E., Shamshiri, R.R., Dworak, V., Weltzien, C., Fernández, R.: Soft gripper for small fruits harvesting and pick and place operations. *Frontiers in Robotics and AI* **10**, 1330496 (2024)
20. NVIDIA: GR00T N1.6: An improved foundation model for generalist humanoid robots. https://research.nvidia.com/labs/gear/gr00t-n1_6/ (2025)
21. NVIDIA, Bjorck, J., et al.: GR00T N1: An open foundation model for generalist humanoid robots (2025)
22. Ochoa, E., Mo, C.: Design and field evaluation of an end effector for robotic strawberry harvesting. In: *Actuators*. vol. 14, p. 42. MDPI (2025)
23. Octo Model Team, Ghosh, D., Walke, H., Pertsch, K., Black, K., Mees, O., Dasari, S., Hejna, J., Kreiman, T., Xu, C., Luo, J., Tan, Y.L., Sanketi, P., Vuong, Q., Xiao, T., Sadigh, D., Finn, C., Levine, S.: Octo: An open-source generalist robot policy. In: *Proceedings of Robotics: Science and Systems* (2024)
24. Shintake, J., Cacucciolo, V., Floreano, D., Shea, H.: Soft robotic grippers. *Advanced Materials* **30**(29), 1707035 (2018). <https://doi.org/10.1002/adma.201707035>
25. Wang, S., Nikolić, M.N., Lam, T.L., Gao, Q., Ding, R., Zhang, T.: Robot manipulation based on embodied visual perception: A survey. *CAAI Transactions on Intelligence Technology* **10**, 945–958 (2025). <https://doi.org/10.1049/cit2.70022>
26. Wen, R., Yuan, K., Wang, Q., Heng, S., Li, Z.: Force-guided high-precision grasping control of fragile and deformable objects using semg-based force prediction. *IEEE Robotics and Automation Letters* **5**(2), 2762–2769 (2020)
27. Wu, J., Yang, B., Li, Z., He, S., Bu, Y., Su, B., Wang, Y.: Surface curvature regulation of 3d kirigami soft gripper. *International Journal of Solids and Structures* **317**, 113410 (2025). <https://doi.org/https://doi.org/10.1016/j.ijsolstr.2025.113410>
28. Wu, P., Shentu, Y., Yi, Z., Lin, X., Abbeel, P.: Gello: A general, low-cost, and intuitive teleoperation framework for robot manipulators. In: *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. pp. 12156–12163. IEEE (2024)
29. Yang, R., An, Z., Zhou, L., Feng, Y.: Seqvla: Sequential task execution for long-horizon manipulation with completion-aware vision-language-action model. *arXiv preprint arXiv:2509.14138* (2025)
30. Yang, Y., Vella, K., Holmes, D.P.: Grasping with kirigami shells. *Science Robotics* **6**(54), eabd6426 (2021). <https://doi.org/10.1126/scirobotics.abd6426>
31. Zhao, T.Z., Kumar, V., Levine, S., Finn, C.: Learning fine-grained bimanual manipulation with low-cost hardware. *arXiv preprint arXiv:2304.13705* (2023)