

LaST-R1: Reinforcing Action via Adaptive Physical Latent Reasoning for VLA Models

Hao Chen^{*1, 2} Jiaming Liu^{*,†2} Zhonghao Yan^{*2} Nuowei Han^{*2} Renrui Zhang^{†1}
 Chenyang Gu² Jialin Gao¹ Ziyu Guo¹ Siyuan Qian² Yinxi Wang²
 Peng Jia³ Chi-Wing Fu¹ Shanghang Zhang²  Pheng-Ann Heng¹

¹The Chinese University of Hong Kong ²State Key Laboratory of Multimedia Information Processing, School of Computer Science, Peking University ³Simplexity Robotics

Project page: <https://siriyeep.github.io/last-r1/>

Abstract

Vision-Language-Action (VLA) models have increasingly incorporated reasoning mechanisms for complex robotic manipulation. However, existing approaches share a critical limitation: whether employing explicit linguistic reasoning that suffers from latency and discretization, or utilizing more expressive continuous latent reasoning, they are predominantly confined to static imitation learning that limits adaptability and generalization. While online reinforcement learning (RL) has been introduced to VLAs to enable trial-and-error exploration, current methods exclusively optimize the vanilla action space, bypassing the underlying physical reasoning process. In this paper, we present **LaST-R1**, a unified VLA framework that integrates latent Chain-of-Thought (CoT) reasoning over physical dynamics prior to action execution, along with a tailored RL post-training paradigm. Specifically, we propose **Latent-to-Action Policy Optimization (LAPO)**, a novel RL algorithm that jointly optimizes the latent reasoning process and the action generation. By bridging reasoning and control, LAPO improves the representation of physical world modeling and enhances robustness in interactive environments. Furthermore, an **adaptive latent CoT mechanism** is introduced to allow the policy to dynamically adjust its reasoning horizon based on environment complexity. Extensive experiments show that LaST-R1 achieves a near-perfect 99.8% average success rate on the LIBERO benchmark with only one-shot supervised warm-up, significantly improving convergence speed and performance over prior state-of-the-art methods. In real-world deployments, LAPO post-training yields up to a 44% improvement over the initial warm-up policy across four complex tasks, including both single-arm and dual-arm settings. Finally, LaST-R1 demonstrates strong generalization across simulated and real-world environments.

1 Introduction

Driven by large-scale pre-trained VLMs [1, 2, 3], Vision-Language-Action (VLA) models [4, 5, 6, 7, 8, 9, 10] have emerged as a promising paradigm for general robotic manipulation. Moving beyond direct observation-to-action mapping, recent architectures increasingly draw inspiration from Chain-of-Thought (CoT) reasoning [11]. While explicitly generating linguistic traces [12, 13, 14, 15] or future states [16, 17, 18, 19, 20] provides structured guidance before acting, it incurs non-negligible inference latency and discretization bottlenecks. This inherently restricts the model’s ability to

^{*}Equal contribution, [†]Project lead,  Corresponding author.




Figure 1: **LaST-R1**. (a) Unlike vanilla RL baselines that strictly optimize actions, (b) our approach utilizes LAPO to jointly optimize an adaptive latent CoT alongside physical execution. By bridging cognitive reasoning and control, LaST-R1 achieves (c) faster convergence speed, higher success rate in simulation, and (d) stronger generalization capabilities in real-world scenarios.

capture continuous, high-frequency physical dynamics. Therefore, recent research [21, 22] has pivoted toward reasoning in a compact latent space that accommodates fine-grained, hard-to-verbalize physical knowledge, establishing a highly expressive reasoning foundation for complex manipulation.

Despite the advantages of latent reasoning, existing frameworks remain grounded in imitation learning, requiring massive, high-cost expert demonstrations. Their reliance on static datasets prevents closed-loop environmental interaction, leading to compounding errors and limited generalization. To break this bottleneck, a nascent line of research [23, 24, 25, 26, 27, 28, 29, 30] has introduced online reinforcement learning (RL) for VLA post-training, improving exploration and robustness through trial-and-error interaction with the environment. However, current methods are largely restricted to vanilla architectures that operate directly in the action space, bypassing the underlying physical reasoning process, as shown in Figure 1 (a). This omission restricts the model’s capacity to deeply comprehend and dynamically adapt to complex physical environments. Consequently, a critical question emerges: *Can we formulate an RL framework for VLA dedicated to optimizing a latent reasoning-before-acting paradigm, thereby enabling robust and adaptive robotic manipulation?*

To this end, we introduce a unified **LaST-R1** framework with a tailored RL-based post-training paradigm for optimizing the coupled reasoning-execution process, as shown in Figure 1 (b). We first present the LaST-R1 VLA model, which integrates latent CoT reasoning with action generation. The model autoregressively produces latent reasoning tokens to capture structured physical dynamics, serving as conditions for parallel action decoding. To ensure stable and expressive reasoning, these latent tokens are anchored on global future representations from a vision foundation model [31], providing a strong semantic and spatial prior. Building on this architecture, we propose **Latent-to-Action Policy Optimization (LAPO)**, a novel RL algorithm that jointly optimizes latent reasoning and action generation. Unlike prior RL approaches that operate solely in the action space [24, 23, 25], LAPO treats latent reasoning tokens as implicit decision variables, allowing reward signals to indirectly shape the internal reasoning space. By unifying latent reasoning and action generation within a joint step-level likelihood ratio, LAPO facilitates effective credit assignment from environmental rewards, thereby improving the representation of physical world modeling and enhancing robustness in interactive environments. Finally, an **adaptive latent CoT mechanism** is introduced to augment the framework, enabling dynamic adjustment of the reasoning horizon based on task diversity. This facilitates allocating extensive computational resources to scenarios requiring high-level cognitive planning, while ensuring low-latency execution for reactive behaviors, optimizing the reasoning-inference trade-off.

To empirically validate our framework, LaST-R1 is first initialized with pre-trained Qwen3-VL-4B [2] and undergoes large-scale pre-training across diverse robotic manipulation datasets [32, 33, 34]. For specific downstream tasks, the policy is adapted through a supervised fine-tuning (SFT) warm-up before engaging in online RL post-training. During evaluation, our approach achieves a near-perfect 99.8% average success rate on the LIBERO benchmark with one-shot warmup, outperforming prior state-of-the-art (SOTA) baselines. In real-world deployments, LAPO post-training yields up to a 44% improvement over the initial warm-up policy across four complex tasks, reaching a 90%

average success rate in both single-arm and dual-arm settings. Furthermore, systematic evaluations demonstrate that the proposed framework exhibits strong generalization across both simulated and real-world environments, consistently outperforming vanilla action-only RL policies trained with standard PPO [35]. Notably, LaST-R1 achieves zero-shot generalization to unseen objects, backgrounds, and lighting conditions after RL post-training. Main contributions are as follows:

- 1) We introduce **LaST-R1**, a unified VLA framework that integrates latent CoT reasoning over physical dynamics before action execution, along with a tailored RL post-training paradigm.
- 2) We propose **Latent-to-Action Policy Optimization (LAPO)**, a novel RL algorithm that jointly optimizes latent reasoning and action generation, improving the representation of physical modeling and enhancing robustness.
- 3) We design an **adaptive latent CoT mechanism** that dynamically adjusts the reasoning horizon based on task diversity, balancing reasoning capacity and inference efficiency.

2 Methodology

2.1 Preliminaries

We formulate the Vision-Language-Action (VLA) model as a parameterized policy π_θ that maps multimodal observations (i.e., visual inputs and language instructions) to an action chunk $\mathbf{a}_{t:t+H}$ in $SE(3)$ space. For single-arm robots such as the Franka Research 3, the action is a 7-DoF end-effector control vector $\mathbf{a}_t \in \mathbb{R}^7$, comprising 3-DoF positional offsets, a 3-DoF orientation (represented as Euler angles), and a 1-DoF gripper state. For dual-arm systems, we extend this formulation to 14-DoF via vector concatenation. The policy can be optimized either through supervised fine-tuning (SFT) using expert demonstrations or via reinforcement learning (RL) via environment interaction.

SFT Formulation. We assume access to a dataset of expert demonstrations $\mathcal{D} = \{(s_t, \mathbf{a}_{t:t+H})\}$, where s_t denotes the multimodal observations at timestep t . The policy is trained to imitate expert behavior by maximizing the conditional log-likelihood:

$$\mathcal{J}_{\text{SFT}}(\theta) = \mathbb{E}_{(s_t, \mathbf{a}_{t:t+H}) \sim \mathcal{D}} [\log \pi_\theta(\mathbf{a}_{t:t+H} \mid s_t)]. \quad (1)$$

While this objective enables effective behavioral cloning, the model’s capability and generalization remain inherently bounded by the quality, scale, and diversity of the training data.

RL Formulation. To surpass the limitations of static imitation, we cast the sequential decision-making problem as an interacting process where the policy engages with the environment over trajectories of length $T + 1$. At each timestep t , the agent observes a state s_t and samples an action chunk $\mathbf{a}_{t:t+H} \sim \pi_\theta(\cdot \mid s_t)$. The environment then transitions to the next state s_{t+1} and yields a scalar reward r_t . This interaction induces a trajectory τ , whose distribution is governed by the initial state and the environment dynamics. The objective is to maximize the expected discounted return:

$$\mathcal{J}_{\text{RL}}(\theta) = \mathbb{E}_{\tau \sim \pi_\theta} \left[\sum_{t=0}^T \gamma^t r_t \right], \quad \nabla_\theta \mathcal{J}_{\text{RL}}(\theta) = \mathbb{E}_{\tau \sim \pi_\theta} \left[\sum_{t=0}^T \nabla_\theta \log \pi_\theta(\mathbf{a}_{t:t+H} \mid s_t) \hat{A}_t \right], \quad (2)$$

where $\gamma \in [0, 1)$ is the discount factor, and $\hat{A}_t$ denotes the advantage estimate, capturing the relative utility of the sampled action chunk $\mathbf{a}_{t:t+H}$ compared to the expected value at state s_t .

2.2 LaST-R1 Model Architecture

We propose **LaST-R1**, a unified VLA model that jointly models both processes within a single architecture, as shown in Figure 2 (a). We first introduce the overall pipeline of LaST-R1, followed by a novel method for constructing image latent representations.

Overview. LaST-R1 builds upon the Qwen3-VL-4B [2], consisting of a visual encoder and an LLM backbone. The visual encoder is instantiated with SigLIP2-Large, which employs 2D-RoPE with interpolated absolute positional embeddings to encode spatial information into visual tokens. Given an input image $I \in \mathbb{R}^{H \times W \times 3}$, it is partitioned into patches to produce dense visual features. The visual tokens ($f_v \in \mathbb{R}^{N_v \times 2560}$) are concatenated with tokenized language inputs ($f_l \in \mathbb{R}^{N_l \times 2560}$) and fed into the LLM backbone, where N_v and N_l denote the sequence lengths of the respective tokens.




Figure 2: **Overview.** (a) LaST-R1 is a unified VLA model that takes visual observations and language instructions as input, where a vision foundation model provides physically grounded latent targets to guide latent CoT reasoning before action generation. (b) During LAPO RL post-training, the policy interacts with the environment in a closed loop manner, storing latent tokens, actions, and rewards in a rollout buffer for jointly reshaping the latent and action spaces. It further enables adaptive reasoning by learning to emit the `<latent_end>` token based on predicted probabilities, dynamically adjusting the reasoning horizon across tasks. (c) Through LAPO RL, LaST-R1 achieves adaptive reasoning lengths across diverse tasks, improving generalization and execution stability.

The model first generates latent reasoning tokens, followed by action prediction. To fully leverage the strong reasoning capability of the LLM, latent tokens are generated in an autoregressive manner, with their representation detailed in the next paragraph. To support action generation, we normalize and discretize continuous actions into tokens, extending the LLM vocabulary accordingly [4]. We adopt a parameter-free action tokenizer to map between continuous actions and discrete tokens, while employing parallel decoding to improve inference efficiency [5]. To enable RL-based post-training, we introduce a value head composed of a 4-layer MLP to estimate state values, which shares the same backbone with the VLA actor [28, 23].

Latent Representation. To model temporal environmental dynamics, LaST-R1 autoregressively infers future states over a horizon N_z , yielding N_z latent reasoning tokens. Prior methods extract these latents via average pooling [21] or auxiliary learnable parameters [22], which often sacrifices fine-grained spatial structures or injects undesired inductive biases into the learned latent space. To overcome this, we construct latent tokens using DINOv3 [31], a state-of-the-art vision foundation model. Specifically, we extract its `<CLS>` token ($f_d \in \mathbb{R}^{1 \times 4096}$) as a holistic image embedding and apply top- k ($k = 2560$) selection based on feature magnitude along the channel dimension. These selected latent targets align with the hidden size of the VLA embedding while preserving the most salient visual components. By harnessing DINOv3’s structurally rich and semantically dense feature space, the extracted `<CLS>` token serves as a highly informative cognitive anchor, facilitating accurate modeling of physical dynamics. Crucially, these latent targets are precomputed offline, fully decoupling the foundation model from the policy to ensure zero additional computational overhead during both training and inference. We systematically compare this approach with prior latent representation formats in Section 3.2 to further validate its effectiveness.

2.3 Latent-to-Action Policy Optimization

To effectively train the proposed *latent reasoning-before-acting* policy LaST-R1, we introduce **Latent-to-Action Policy Optimization (LAPO)**, a RL framework that jointly optimizes latent reasoning and action generation, as shown in Figure 2 (b). In our formulation, the policy first generates latent tokens, which condition subsequent action prediction. While prior works [28, 36] have established Proximal Policy Optimization (PPO) [35] as an effective post-training method for VLA models, they operate solely in the action space and overlook intermediate reasoning processes that are integral to decision-making. To address this limitation, we propose LAPO, which treats latent tokens as *implicit*

decision variables and introduces a unified optimization framework that enables reward signals to shape both reasoning and action generation across the entire trajectory.

Rollout Collection. At each environment step t , given the current state s_t comprising visual observations and language instructions, the policy first generates a sequence of latent tokens $\mathbf{Z}_t^{\text{old}} = \{\mathbf{z}_{t,k}^{\text{old}}\}_{k=1}^{N_z}$ autoregressively: $\mathbf{z}_{t,k}^{\text{old}} \sim \pi_\theta(\cdot \mid s_t, \mathbf{z}_{t,<k}^{\text{old}})$. Conditioned on these latents, a sequence of discrete action tokens $\mathbf{C}_t = \{\mathbf{a}_{t,j}\}_{j=1}^{N_a}$ is then produced, where N_a denotes the total number of tokens representing the H -step action chunk. Specifically, we reuse the KV cache from the latent generation phase and decode the action tokens in parallel via a single forward pass with bidirectional attention over N_a placeholder vectors. We further insert a special `<latent_end>` token between the latent and action sequences to signify the completion of reasoning. The final hidden embedding of this token is routed into a value head to output the state value estimation v_t . To formulate a unified action distribution for decision step t , we compute the joint log-probability of the action sequence by summing over the individual tokens: $\log \pi_\theta(\mathbf{C}_t \mid \cdot) = \sum_{j=1}^{N_a} \log \pi_\theta(\mathbf{a}_{t,j} \mid \cdot)$. During rollout, we store the sampled latent sequences $\mathbf{Z}_t^{\text{old}}$, action sequences $\mathbf{C}_t$, their corresponding log-probabilities, and the estimated state values. Ultimately, a scalar reward is assigned based on task success or failure, yielding complete trajectories that are subsequently used to compute the advantage estimates $\hat{A}_t$ via Generalized Advantage Estimation (GAE) for policy optimization.

Policy Optimization. During policy updates, the model processes the identical rollout context to yield updated continuous latent embeddings $\mathbf{Z}_t^\theta = \{\mathbf{z}_{t,k}^\theta\}_{k=1}^{N_z}$ and updated discrete action log-probabilities. Because the advantage $\hat{A}_t$ is computed at the decision-step level, we define a step-level likelihood ratio $r_t(\theta)$ for both the action sequence and the continuous latents. For the discrete action sequence, the likelihood ratio is computed via the joint probabilities: $r_t^a(\theta) = \exp(\log \pi_\theta(\mathbf{C}_t \mid \cdot) - \log \pi_{\theta^{\text{old}}}(\mathbf{C}_t \mid \cdot))$. For the continuous latent tokens, we approximate the distribution of rollout latents $\mathbf{Z}_t^{\text{old}}$ using an isotropic Gaussian centered at the current policy output $\mathbf{Z}_t^\theta$. By summing the squared Euclidean distances over the entire latent sequence length N_z , we define the step-level latent likelihood ratio as:

$$r_t^z(\theta) = \frac{\pi_\theta(\mathbf{Z}_t^{\text{old}} \mid \cdot)}{\pi_{\theta^{\text{old}}}(\mathbf{Z}_t^{\text{old}} \mid \cdot)} = \exp\left(-\frac{1}{2\sigma^2} \sum_{k=1}^{N_z} \|\mathbf{z}_{t,k}^{\text{old}} - \mathbf{z}_{t,k}^\theta\|^2\right), \quad (3)$$

where σ is a fixed hyperparameter regulating the latent variance. By jointly optimizing reasoning latents and action sequences, we compute a joint LAPO clipped surrogate loss. The loss is computed as the masked mean over all valid decision steps t , formally written as an expectation:

$$\mathcal{L}_{\text{policy}}(\theta) = -\mathbb{E}_t \left[\sum_{m \in \{z,a\}} \min\left(r_t^m(\theta) \hat{A}_t, \text{clip}(r_t^m(\theta), 1 - \epsilon_{\min}, 1 + \epsilon_{\max}) \hat{A}_t\right) \right], \quad (4)$$

where $\epsilon_{\min}$ and $\epsilon_{\max}$ are the clipping thresholds. This objective enables the environment reward to shape both the action space and the internal reasoning space simultaneously. Specifically, when $\hat{A}_t > 0$, the optimization explicitly minimizes the latent distance $\sum_k \|\mathbf{z}_{t,k}^{\text{old}} - \mathbf{z}_{t,k}^\theta\|^2$, effectively pulling the current policy’s latent representations toward the "good-reasoning" manifolds that facilitated successful trajectories. In practice, to achieve better optimization flexibility, we decouple the joint policy objective $\mathcal{L}_{\text{policy}}(\theta)$ into two separate components: the action loss $\mathcal{L}_{\text{action}}(\theta)$ (for $m = a$) and the latent loss $\mathcal{L}_{\text{latent}}(\theta)$ (for $m = z$). Finally, the total training loss unifies these policy objectives with state-value estimation, governed by weighting coefficients λ_1 and λ_2 :

$$\mathcal{L}_{\text{total}}(\theta) = \mathcal{L}_{\text{action}}(\theta) + \lambda_1 \mathcal{L}_{\text{latent}}(\theta) + \lambda_2 \mathcal{L}_{\text{value}}(\theta), \quad (5)$$

where $\mathcal{L}_{\text{value}}(\theta) = \mathbb{E}_t [(v_t - \hat{r}_t)^2]$ is the mean squared error (MSE) against the target return $\hat{r}_t$.

2.4 Adaptive Latent CoT Reasoning

While fixed-length reasoning provides a baseline, it imposes a static cognitive horizon that fails to capture the inherent diversity of robotic tasks. Enforcing a fixed latent length N_z incurs unnecessary computational overhead on highly predictable motions and restricts the reasoning capacity required for maneuvers demanding intricate cognitive planning. To address this, we introduce an **adaptive latent CoT mechanism** optimized via our proposed RL framework. By allowing the model to adapt

its reasoning length based on reward signals, we enable an "early-exit" strategy that dynamically tailors the latent reasoning horizon to the specific demands of each task.

Dynamic Latent Generation. To enable adaptive reasoning, we shift the `<latent_end>` token from a deterministic sequence terminator to a dynamically emitted transition signal within the latent generation process. During autoregressive generation, if the policy predicts the `<latent_end>` token with a sufficiently high confidence probability $p \geq 0.99$ (where $p \in [0, 1]$), indicating that the model is highly certain the reasoning phase should conclude at the current decision step, the latent generation terminates and the model transitions to action prediction. To stabilize the training process and prevent erratic fluctuations in latent reasoning length, we restrict the emission of the `<latent_end>` token to a predefined set of $M = 4$ candidate positions (e.g., after 2, 4, 6, and 8 latent tokens), bounded by a maximum reasoning length $N_{\max}$.

Exploration via Length Sampling. During RL rollouts, exploring various reasoning lengths is crucial for discovering the optimal cognitive horizon across diverse environmental states. We treat the reasoning length as a stochastic decision to encourage environmental interaction. Specifically, we extract the pre-softmax logits l_m associated with the `<latent_end>` token across all M predefined candidate positions, and then apply a temperature parameter β to control the exploration entropy, yielding a normalized categorical distribution over the candidate lengths:

$$p_m = \frac{\exp(l_m/\beta)}{\sum_{j=1}^M \exp(l_j/\beta)}, \quad \forall m \in \{1, \dots, M\}. \quad (6)$$

Based on this distribution, we sample the reasoning length index $m \sim \text{Categorical}(p_1, \dots, p_M)$, which explicitly dictates the number of latent tokens generated for the current step. During training, reasoning lengths are sampled for exploration, while inference adopts a confidence-based exit strategy.

Adaptive Length Optimization. To optimize the adaptive length selection, the decision of *when* to stop reasoning must be explicitly supervised. We introduce an additional policy loss term for the `<latent_end>` token. Let $\mathbf{z}_t^{\text{end}}$ denote the transition token emitted at the sampled position m . We record its log-probability $\log \pi_\theta(\mathbf{z}_t^{\text{end}} | \cdot)$ during rollout. During the policy update, we construct a discrete likelihood ratio for the transition token: $r_t^{\text{end}}(\theta) = \frac{\pi_\theta(\mathbf{z}_t^{\text{end}} | \cdot)}{\pi_{\theta_{\text{old}}}(\mathbf{z}_t^{\text{end}} | \cdot)}$. This ratio is incorporated into a transition-specific LAPO surrogate objective, $\mathcal{L}_{\text{end}}(\theta)$. For models equipped with adaptive reasoning, the total training objective is augmented to include this term, weighted by a coefficient λ_3 :

$$\mathcal{L}_{\text{total}}(\theta) = \mathcal{L}_{\text{action}}(\theta) + \lambda_1 \mathcal{L}_{\text{latent}}(\theta) + \lambda_2 \mathcal{L}_{\text{value}}(\theta) + \lambda_3 \mathcal{L}_{\text{end}}(\theta). \quad (7)$$

Guided by the state-action advantage $\hat{A}_t$, this objective naturally penalizes premature actions in scenarios demanding intricate cognitive planning, while rewarding efficient, shorter reasoning paths during highly predictable operational states.

3 Experiments

Following prior works [8, 9], LaST-R1 is first pre-trained on a custom-designed large-scale dataset, detailed in Appendix B.1. We then systematically evaluate our framework: Section 3.1 compares our method against SOTA baselines on the LIBERO benchmark, and Section 3.2 provides ablation studies on our core designs. Furthermore, Section 3.3 validates the performance of LaST-R1 in real-world robotic deployments, while Section 3.4 thoroughly investigates its generalization capabilities.

3.1 Simulation Experiment

Settings. We validate our method on four LIBERO task suites [37]: LIBERO-Spatial, LIBERO-Object, LIBERO-Goal, and LIBERO-Long, each comprising 10 distinct manipulation tasks. All setups feature a simulated Franka Panda with a single front-view observation with 256×256 resolution. Following prior VLA RL work [24], we adopt a two-stage training pipeline. We first perform a SFT warm-up using a single randomly selected expert trajectory per task, enabling a controlled evaluation of the subsequent RL post-training. We then transition to online RL, iteratively collecting rollouts and updating the policy within the simulator. More training details are placed in Appendix C.2 and C.3. Finally, performance is measured by the average Success Rate (SR) across 50 held-out test scenarios for each task.

Table 1: **Comparison on the LIBERO.** For RL, we use single-trajectory warm-up and single-view data. Specifically, $\dagger$ denotes full-trajectory warm-up, and $\ddagger$ indicates two-camera training.

Models	Paradigm	Spatial		Object		Goal		Long		Average	
		SR $\uparrow$	Rank $\downarrow$	SR $\uparrow$	Rank $\downarrow$	SR $\uparrow$	Rank $\downarrow$	SR $\uparrow$	Rank $\downarrow$	SR $\uparrow$	Rank $\downarrow$
OpenVLA [4]	SFT	84.7	11	88.4	11	79.2	11	53.7	11	76.5	11
GR00T-N1 [42]	SFT	94.4	7	97.6	7	93.0	7	90.6	6	93.9	7
π_0 [6]	SFT	96.8	6	98.8	3	95.8	6	85.2	7	94.2	6
$\pi_{0.5}$ [7]	SFT	98.8	3	98.2	6	98.0	4	92.4	4	96.9	4
OpenVLA-OFT [5]	SFT	97.6	5	98.4	5	97.9	5	94.5	2	97.1	3
GRAPE $\dagger$ [38]	RL	88.5	10	92.1	9	83.1	8	57.2	10	80.2	10
TGRPO $\dagger$ [40]	RL	90.4	8	92.2	8	81.0	10	59.2	9	80.7	9
VLA-RL $\dagger$ [25]	RL	90.2	9	91.8	10	82.2	9	59.8	8	81.0	8
SimpleVLA-RL [24]	RL	98.2	4	98.7	4	98.8	3	91.7	5	96.9	4
π_{RL} $\ddagger$ [23]	RL	99.6	2	100.0	1	99.6	2	94.0	3	98.3	2
LaST-R1 (Ours)	RL	99.8	1	100.0	1	100.0	1	99.4	1	99.8	1




Figure 3: **Online RL learning curves on LIBERO.** We compare our proposed LaST-R1 optimized via LAPO (red), against the standard Action-Only baseline optimized via PPO (blue).

Baselines. We conduct a comprehensive comparison against both SFT-only and RL-trained models. All SFT baselines are trained on the full training dataset (50 trajectories per task). Among the RL-trained baselines, GRAPE [38] utilizes DPO [39], VLA-RL [25] and π_{RL} [23] rely on PPO [35], and both TGRPO [40] and SimpleVLA-RL [24] are optimized via GRPO [41]. All RL-trained baselines follow their official warm-up strategies, as detailed in Table 1.

Result Analysis. Table 1 presents the quantitative comparison across the LIBERO benchmark. Our proposed LaST-R1 achieves state-of-the-art performance, recording a near-perfect average success rate of 99.8% and ranking first across all four task suites. Notably, despite using only a single trajectory for warm-up, our method outperforms strong SFT baselines such as $\pi_{0.5}$ (96.9%) and OpenVLA-OFT (97.1%), which heavily rely on complete expert datasets. When compared to the leading RL-based method π_{RL} under the identical one-trajectory setting, LaST-R1 maintains a consistent advantage. This gap becomes particularly pronounced on the highly challenging LIBERO-Long suite (99.4% vs. 94.0%), demonstrating that our framework possesses superior capabilities in handling complex and long-horizon manipulation tasks. The results demonstrate that our RL framework substantially improves the physical world modeling capability of VLA models, leading to near-perfect action performance even with only one-shot training data. Meanwhile, Figure 3 presents the learning curves across all environments. Starting from the same warm-up model, LaST-R1 trained with LAPO achieves significantly faster convergence and higher asymptotic success rates compared to the standard Action-Only baseline optimized via PPO. The baseline policy struggles with optimization efficiency, especially in the LIBERO-Spatial and LIBERO-Long suites, requiring significantly more steps yet still converging to sub-optimal performance. The results validate that introducing latent CoT optimization during post-training acts as an effective cognitive buffer, which smooths the RL optimization landscape and enables sample-efficient online learning. Furthermore, detailed analyses demonstrating how this optimized reasoning mechanism yields both computational efficiency (via adaptive reasoning lengths) and physical execution efficiency (via shortened episode lengths) are provided in the Appendix D.2 and D.3.

3.2 Ablation Studies

To validate our core designs, we conduct ablation studies evaluated on the LIBERO-Spatial suite unless otherwise specified. **(1) Effectiveness of Latent Reasoning in SFT and RL Post-Training.** As shown in Figure 3, after one-shot SFT, incorporating latent reasoning (LaST-R1 Warm-up) improves the average SR from 51.0% to 62.0% compared to the Action-Only baseline. The improvement is particularly pronounced on LIBERO-Long (long-horizon tasks), where incorporating latent CoT




Figure 4: **Ablation studies.** We evaluate (a) latent representation methods, (b) different fixed latent CoT lengths, and (c) adaptive CoT length with varying `<latent_end>` placements.

boosts performance from 26.2% to 48.6%. During RL post-training, our full method (LaST-R1 + LAPO) further amplifies this advantage, achieving 99.8% SR across all task suites and significantly outperforming Action-Only + PPO (94.6%). These results demonstrate that our latent reasoning mechanism enhances physical understanding, leading to more effective action optimization. **(2) Design Choices for Latent Representation.** As shown in Figure 4 (a), we study the impact of different latent representation construction methods by comparing our DINOv3-based approach with three alternatives: averaging SigLIP encoder features [43] via global pooling [21], downsampling them with convolution [22], and extracting latents using a Q-Former [44]. Detailed implementations of these variants are deferred to Appendix C.1. Evaluated after RL post-training, our DINOv3 representation achieves the highest SR of 99.8%, outperforming Convolution (98.4%), Q-Former (97.2%), and Global Pooling (96.8%). This validates that leveraging pre-trained global representations from DINOv3 better preserves intricate spatial and semantic structures, while the top-k selection scheme maximally retains dynamic information. **(3) Impact of Latent Reasoning Length.** We ablate the CoT horizon by varying the fixed latent sequence length $N_z \in \{1, 2, 4, 8\}$, as shown in Figure 4 (b). Compared to the Action-Only baseline (no latent reasoning, 95.0% SR), performance monotonically increases from 96.2% (1 token) to 98.4% (8 tokens). This indicates that a longer cognitive horizon effectively encodes richer condition information for downstream actions. Moreover, we observe that the performance gain from 4 to 8 tokens is marginal. To strike an optimal balance between task accuracy and inference speed, we cap the maximum reasoning sequence at 8 tokens. **(4) Adaptive CoT Length and `<latent_end>` Placement.** Finally, we validate our adaptive latent CoT mechanism in Figure 4(c). Given a maximum reasoning length $N_{\max} = 8$, we ablate the number of valid candidate positions M for emitting `<latent_end>`. Specifically, we evaluate $M \in \{1, 2, 4, 8\}$ by uniformly distributing the candidate positions across the latent sequence. For example, $M = 1$ allows emission only after the 8th latent token, whereas $M = 8$ permits emission after every latent token. We find that $M = 4$ achieves the best performance (99.8%). While adaptive termination generally improves both efficiency and performance over the fixed-length baseline (98.4%), setting M too large ($M = 8$, 99.0%) slightly degrades performance. Therefore, a moderately constrained adaptive strategy ($M = 4$) offers the best trade-off between reasoning flexibility and optimization stability. Additional ablation studies are provided in Appendix D.1.

3.3 Real-World Experiment

Settings. We validate our method on four practical real-world manipulation tasks using Franka Research 3 arms, including one single-arm task and three dual-arm tasks: (1) *Insert hexagon block*, (2) *Open bag zipper*, (3) *Wipe the Vase with a Sponge*, and (4) *Open bottle cap*. For each task, we collect 30 expert demonstrations using a space mouse for SFT warm-up (full fine-tuning). Given the significant domain gap between simulation and real-world deployment, we follow recent real-world VLA RL methods [26, 27] and adopt our proposed *latent reasoning-before-acting* RL framework. To improve RL update efficiency, we incorporate Low-Rank Adaptation (LoRA) [45] into all attention layers of LaST-R1, updating only the LoRA parameters. For observations, we use one third-person camera and two wrist cameras, with input resolutions matching those in simulation. Both the SFT-initialized and RL-optimized policies are evaluated across 20 rollouts under varied tabletop configurations. Additional implementation details are provided in Appendix C.4.

Result Analysis. The “Original” column in Table 2 summarizes the real-world performance of LaST-R1 before and after RL optimization. Overall, the average success rate improves substantially from 52.5% after SFT warm-up to 93.75% after RL, demonstrating that our proposed RL method significantly enhances the action robustness of VLA models in real-world settings. For the *Insert*

Table 2: **Comparison on real-world tasks.** Evaluation includes the original training scenario and three generalization settings: unseen objects, background variations, and lighting conditions. Example cases are shown below, with changed configurations highlighted in **red boxes**.

Stages	Insert hexagon block				Open bag zipper			
	Original	Unseen-Object	-Background	-Lighting	Original	Unseen-Object	-Background	-Lighting
After warm-up	45	35 (-22%)	35 (-22%)	40 (-11%)	55	30 (-45%)	50 (-9%)	45 (-18%)
After RL	90	75 (-16%)	85 (-5%)	80 (-11%)	95	80 (-15%)	95 (-0%)	90 (-5%)

Stages	Wipe the Vase with a Sponge				Open bottle cap			
	Original	Unseen-Object	-Background	-Lighting	Original	Unseen-Object	-Background	-Lighting
After warm-up	65	35 (-46%)	40 (-38%)	20 (-69%)	45	30 (-33%)	30 (-33%)	35 (-22%)
After RL	95	80 (-15%)	90 (-5%)	95 (-0%)	95	95 (-0%)	80 (-15%)	85 (-10%)





Figure 5: **Generalization analysis on LIBERO.** While the OOD performance of the Action-Only PPO baseline (blue) stagnates, our LaST-R1 with LAPO (red) demonstrates continuous improvement.

hexagon block task, a precise single-arm manipulation, our proposed method boosts the success rate from 45% to 90%, highlighting its effectiveness in refining visually guided precision behaviors. For the dual-arm tasks, *Open bag zipper* and *Wipe the Vase with a Sponge*, our RL method improves dual-arm coordination and, through continual interaction with the physical environment, enhances performance on contact-rich manipulation tasks. Finally, for the *Open bottle cap* task, which requires a nuanced understanding of physical relationship (e.g., the interaction between the cap and the bottle), the performance gain indicates that our post-training strengthens the policy’s ability to model temporally evolving physical interactions. Additional visualizations of real-world execution are provided in Appendix E.2.

3.4 Generalization Analysis

Simulation. To evaluate out-of-distribution (OOD) generalization, we test across all four LIBERO task suites. Following the setup of prior work [24], for each suite, we perform online RL on 9 “seen” tasks and hold out 1 task for OOD evaluation, matching our one-trajectory warm-up setting. As shown in Figure 5, the standard Action-Only + PPO baseline suffers from severe overfitting, its OOD performance stagnates and even degrades on the LIBERO-Goal and LIBERO-Long suites. Conversely, our LaST-R1 + LAPO policy demonstrates continuous, significant OOD improvements across all suites. This demonstrates that our latent reasoning, combined with the LAPO RL mechanism, progressively improves the model’s understanding of both the scene and underlying physical dynamics through interaction with the real world, enabling it to extract transferable spatial and semantic concepts rather than overfitting to the training distribution. Additional experiments are presented in Appendix D.4.

Real-World. Table 2 further reports real-world generalization performance under three unseen settings: changes in manipulation objects, background perturbations, and lighting variations. Across these OOD scenarios, the warm-up policy exhibits clear sensitivity to unseen real-world configurations, leading to a significant drop in accuracy. In contrast, the RL-optimized LaST-R1 shows only an average performance decrease of 8% across all tasks and unseen settings. These results

indicate that our RL approach not only improves performance in the original setting but also enhances action robustness. In particular, by interacting with the physical world, the VLA model learns from real feedback, enabling it to better capture environment–robot dynamics and generalize beyond memorized demonstration data.

4 Conclusion

In this work, we present LaST-R1, a unified framework that tightly couples latent reasoning and action generation for VLA models, along with a tailored RL-based post-training paradigm. By introducing latent Chain-of-Thought reasoning grounded in global visual representations, our approach enables structured modeling of physical dynamics prior to action execution. Building on this design, we propose Latent-to-Action Policy Optimization (LAPO), a novel RL paradigm that jointly optimizes reasoning and action spaces, allowing environmental feedback to shape both external behavior and internal decision processes. Furthermore, we introduce an adaptive latent CoT mechanism that dynamically adjusts the reasoning horizon based on task complexity, improving both efficiency and performance. Overall, our results highlight the importance of integrating physical latent reasoning into VLA learning and show that jointly optimizing reasoning and action through RL is a promising direction for improving generalization and physical understanding. We hope this work provides a foundation for future research on scalable latent reasoning-driven policies for robotic manipulation.

References

- [1] Siddharth Karamcheti, Suraj Nair, Ashwin Balakrishna, Percy Liang, Thomas Kollar, and Dorsa Sadigh. Prismatic vlms: Investigating the design space of visually-conditioned language models. *arXiv preprint arXiv:2402.07865*, 2024.
- [2] Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, Wenbin Ge, Zhifang Guo, Qidong Huang, Jie Huang, Fei Huang, Binyuan Hui, Shutong Jiang, Zhaohai Li, Mingsheng Li, Mei Li, Kaixin Li, Zicheng Lin, Junyang Lin, Xuejing Liu, Jiawei Liu, Chenglong Liu, Yang Liu, Dayiheng Liu, Shixuan Liu, Dunjie Lu, Ruilin Luo, Chenxu Lv, Rui Men, Lingchen Meng, Xuancheng Ren, Xingzhang Ren, Sibao Song, Yuchong Sun, Jun Tang, Jianhong Tu, Jianqiang Wan, Peng Wang, Pengfei Wang, Qiuyue Wang, Yuxuan Wang, Tianbao Xie, Yiheng Xu, Haiyang Xu, Jin Xu, Zhibo Yang, Mingkun Yang, Jianxin Yang, An Yang, Bowen Yu, Fei Zhang, Hang Zhang, Xi Zhang, Bo Zheng, Humen Zhong, Jingren Zhou, Fan Zhou, Jing Zhou, Yuanzhi Zhu, and Ke Zhu. Qwen3-vl technical report, 2025.
- [3] Lucas Beyer, Andreas Steiner, André Susano Pinto, Alexander Kolesnikov, Xiao Wang, Daniel Salz, Maxim Neumann, Ibrahim Alabdulmohsin, Michael Tschannen, Emanuele Bugliarello, et al. Paligemma: A versatile 3b vlm for transfer. *arXiv preprint arXiv:2407.07726*, 2024.
- [4] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, et al. Openvla: An open-source vision-language-action model. *arXiv preprint arXiv:2406.09246*, 2024.
- [5] Moo Jin Kim, Chelsea Finn, and Percy Liang. Fine-tuning vision-language-action models: Optimizing speed and success. *arXiv preprint arXiv:2502.19645*, 2025.
- [6] Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, et al. π_0 : A vision-language-action flow model for general robot control. *arXiv preprint arXiv:2410.24164*, 2024.
- [7] Physical Intelligence, Kevin Black, Noah Brown, James Darpinian, Karan Dhabalia, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, et al. $\pi_{0.5}$: a vision-language-action model with open-world generalization. *arXiv preprint arXiv:2504.16054*, 2025.
- [8] Jiaming Liu, Hao Chen, Pengju An, Zhuoyang Liu, Renrui Zhang, Chenyang Gu, Xiaoqi Li, Ziyu Guo, Sixiang Chen, Mengzhen Liu, et al. Hybridvla: Collaborative diffusion and autoregression in a unified vision-language-action model. *arXiv preprint arXiv:2503.10631*, 2025.

- [9] Hao Chen, Jiaming Liu, Chenyang Gu, Zhuoyang Liu, Renrui Zhang, Xiaoqi Li, Xiao He, Yandong Guo, Chi-Wing Fu, Shanghang Zhang, et al. Fast-in-slow: A dual-system foundation model unifying fast manipulation within slow reasoning. *arXiv preprint arXiv:2506.01953*, 2025.
- [10] Qixiu Li, Yaobo Liang, Zeyu Wang, Lin Luo, Xi Chen, Mozheng Liao, Fangyun Wei, Yu Deng, Sicheng Xu, Yizhong Zhang, et al. Cogact: A foundational vision-language-action model for synergizing cognition and action in robotic manipulation. *arXiv preprint arXiv:2411.19650*, 2024.
- [11] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.
- [12] Angen Ye, Zeyu Zhang, Boyuan Wang, Xiaofeng Wang, Dapeng Zhang, and Zheng Zhu. Vla-r1: Enhancing reasoning in vision-language-action models. *arXiv preprint arXiv:2510.01623*, 2025.
- [13] Chi-Pin Huang, Yueh-Hua Wu, Min-Hung Chen, Yu-Chiang Frank Wang, and Fu-En Yang. Thinkact: Vision-language-action reasoning via reinforced visual latent planning. *arXiv preprint arXiv:2507.16815*, 2025.
- [14] Fanqi Lin, Ruiqian Nai, Yingdong Hu, Jiacheng You, Junming Zhao, and Yang Gao. Onet-wovla: A unified vision-language-action model with adaptive reasoning. *arXiv preprint arXiv:2505.11917*, 2025.
- [15] Michał Zawalski, William Chen, Karl Pertsch, Oier Mees, Chelsea Finn, and Sergey Levine. Robotic control via embodied chain-of-thought reasoning. *arXiv preprint arXiv:2407.08693*, 2024.
- [16] Qingqing Zhao, Yao Lu, Moo Jin Kim, Zipeng Fu, Zhuoyang Zhang, Yecheng Wu, Zhaoshuo Li, Qianli Ma, Song Han, Chelsea Finn, et al. Cot-vla: Visual chain-of-thought reasoning for vision-language-action models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 1702–1713, 2025.
- [17] Chenyang Gu, Jiaming Liu, Hao Chen, Runzhong Huang, Qingpo Wu, Zhuoyang Liu, Xiaoqi Li, Ying Li, Renrui Zhang, Peng Jia, et al. Manualvla: A unified vla model for chain-of-thought manual generation and robotic manipulation. *arXiv preprint arXiv:2512.02013*, 2025.
- [18] Zhuoyang Liu, Jiaming Liu, Jiadong Xu, Nuowei Han, Chenyang Gu, Hao Chen, Kaichen Zhou, Renrui Zhang, Kai Chin Hsieh, Kun Wu, et al. Mla: A multisensory language-action model for multimodal understanding and forecasting in robotic manipulation. *arXiv preprint arXiv:2509.26642*, 2025.
- [19] Jun Cen, Chaohui Yu, Hangjie Yuan, Yuming Jiang, Siteng Huang, Jiayan Guo, Xin Li, Yibing Song, Hao Luo, Fan Wang, et al. Worldvla: Towards autoregressive action world model. *arXiv preprint arXiv:2506.21539*, 2025.
- [20] Physical Intelligence, Bo Ai, Ali Amin, Raichelle Aniceto, Ashwin Balakrishna, Greg Balke, Kevin Black, George Bokinsky, Shihao Cao, Thomas Charbonnier, et al. *pi*_{0.7}: a steerable generalist robotic foundation model with emergent capabilities. *arXiv preprint arXiv:2604.15483*, 2026.
- [21] Zhuoyang Liu, Jiaming Liu, Hao Chen, Jiale Yu, Ziyu Guo, Chengkai Hou, Chenyang Gu, Xiangju Mi, Renrui Zhang, Kun Wu, et al. Last_{0}: Latent spatio-temporal chain-of-thought for robotic vision-language-action model. *arXiv preprint arXiv:2601.05248*, 2026.
- [22] Junhao Cai, Zetao Cai, Jiafei Cao, Yilun Chen, Zeyu He, Lei Jiang, Hang Li, Hengjie Li, Yang Li, Yufei Liu, et al. Internvla-a1: Unifying understanding, generation and action for robotic manipulation. *arXiv preprint arXiv:2601.02456*, 2026.
- [23] Kang Chen, Zhihao Liu, Tonghe Zhang, Zhen Guo, Si Xu, Hao Lin, Hongzhi Zang, Quanlu Zhang, Zhaofei Yu, Guoliang Fan, et al. π rl: Online rl fine-tuning for flow-based vision-language-action models. *arXiv preprint arXiv:2510.25889*, 2025.

- [24] Haozhan Li, Yuxin Zuo, Jiale Yu, Yuhao Zhang, Zhaohui Yang, Kaiyan Zhang, Xuekai Zhu, Yuchen Zhang, Tianxing Chen, Ganqu Cui, et al. Simplevla-rl: Scaling vla training via reinforcement learning. *arXiv preprint arXiv:2509.09674*, 2025.
- [25] Guanxing Lu, Wenkai Guo, Chubin Zhang, Yuheng Zhou, Haonan Jiang, Zifeng Gao, Yansong Tang, and Ziwei Wang. Vla-rl: Towards masterful and general robotic manipulation with scalable reinforcement learning. *arXiv preprint arXiv:2505.18719*, 2025.
- [26] Yuhui Chen, Shuai Tian, Shugao Liu, Yingting Zhou, Haoran Li, and Dongbin Zhao. Conrft: A reinforced fine-tuning method for vla models via consistency policy. *arXiv preprint arXiv:2502.05450*, 2025.
- [27] Qinwen Xu, Jiaming Liu, Rui Zhou, Shaojun Shi, Nuowei Han, Zhuoyang Liu, Chenyang Gu, Shuo Gu, Yang Yue, Gao Huang, et al. Twinrl-vla: Digital twin-driven reinforcement learning for real-world robotic manipulation. *arXiv preprint arXiv:2602.09023*, 2026.
- [28] Jijia Liu, Feng Gao, Bingwen Wei, Xinlei Chen, Qingmin Liao, Yi Wu, Chao Yu, and Yu Wang. What can rl bring to vla generalization? an empirical study. *arXiv preprint arXiv:2505.19789*, 2025.
- [29] Yunfei Li, Xiao Ma, Jiafeng Xu, Yu Cui, Zhongren Cui, Zhigang Han, Liqun Huang, Tao Kong, Yuxiao Liu, Hao Niu, et al. Gr-rl: Going dexterous and precise for long-horizon robotic manipulation. *arXiv preprint arXiv:2512.01801*, 2025.
- [30] Physical Intelligence, Ali Amin, Raichelle Aniceto, Ashwin Balakrishna, Kevin Black, Ken Conley, Grace Connors, James Darpinian, Karan Dhabalia, Jared DiCarlo, et al. $\pi_{0.6}^*$: a vla that learns from experience. *arXiv preprint arXiv:2511.14759*, 2025.
- [31] Oriane Siméoni, Huy V Vo, Maximilian Seitzer, Federico Baldassarre, Maxime Oquab, Cijo Jose, Vasil Khalidov, Marc Szafraniec, Seungeun Yi, Michaël Ramamonjisoa, et al. Dinov3. *arXiv preprint arXiv:2508.10104*, 2025.
- [32] Abby O’Neill, Abdul Rehman, Abhiram Maddukuri, Abhishek Gupta, Abhishek Padalkar, Abraham Lee, Acorn Pooley, Agrim Gupta, Ajay Mandlekar, Ajinkya Jain, et al. Open x-embodiment: Robotic learning datasets and rt-x models: Open x-embodiment collaboration 0. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6892–6903. IEEE, 2024.
- [33] Kun Wu, Chengkai Hou, Jiaming Liu, Zhengping Che, Xiaozhu Ju, Zhuqin Yang, Meng Li, Yinuo Zhao, Zhiyuan Xu, Guang Yang, et al. Robomind: Benchmark on multi-embodiment intelligence normative data for robot manipulation. *arXiv preprint arXiv:2412.13877*, 2024.
- [34] Alexander Khazatsky, Karl Pertsch, Suraj Nair, Ashwin Balakrishna, Sudeep Dasari, Siddharth Karamcheti, Soroush Nasiriany, Mohan Kumar Srirama, Lawrence Yunliang Chen, Kirsty Ellis, et al. Droid: A large-scale in-the-wild robot manipulation dataset. *arXiv preprint arXiv:2403.12945*, 2024.
- [35] John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.
- [36] Hongzhi Zang, Mingjie Wei, Si Xu, Yongji Wu, Zhen Guo, Yuanqing Wang, Hao Lin, Liangzhi Shi, Yuqing Xie, Zhexuan Xu, et al. Rlinf-vla: A unified and efficient framework for vla+ rl training. *arXiv preprint arXiv:2510.06710*, 2025.
- [37] Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. Libero: Benchmarking knowledge transfer for lifelong robot learning. *Advances in Neural Information Processing Systems*, 36:44776–44791, 2023.
- [38] Zijian Zhang, Kaiyuan Zheng, Zhaorun Chen, Joel Jang, Yi Li, Siwei Han, Chaoqi Wang, Mingyu Ding, Dieter Fox, and Huaxiu Yao. Grape: Generalizing robot policy via preference alignment. *arXiv preprint arXiv:2411.19309*, 2024.

- [39] Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741, 2023.
- [40] Zengjue Chen, Runliang Niu, He Kong, Qi Wang, Qianli Xing, and Zipei Fan. Tgrpo :fine-tuning vision-language-action model via trajectory-wise group relative policy optimization, 2025.
- [41] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.
- [42] Johan Bjorck, Fernando Castañeda, Nikita Cherniadev, Xingye Da, Runyu Ding, Linxi Fan, Yu Fang, Dieter Fox, Fengyuan Hu, Spencer Huang, et al. Gr00t n1: An open foundation model for generalist humanoid robots. *arXiv preprint arXiv:2503.14734*, 2025.
- [43] Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 11975–11986, 2023.
- [44] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730–19742. PMLR, 2023.
- [45] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3, 2022.
- [46] Songming Liu, Lingxuan Wu, Bangguo Li, Hengkai Tan, Huayu Chen, Zhengyi Wang, Ke Xu, Hang Su, and Jun Zhu. Rdt-1b: a diffusion foundation model for bimanual manipulation. *arXiv preprint arXiv:2410.07864*, 2024.
- [47] Yulin Luo, Hao Chen, Zhuangzhe Wu, Bowen Sui, Jiaming Liu, Chenyang Gu, Zhuoyang Liu, Qiuxuan Feng, Jiale Yu, Shuo Gu, et al. Look before acting: Enhancing vision foundation representations for vision-language-action models. *arXiv preprint arXiv:2603.15618*, 2026.
- [48] Karl Pertsch, Kyle Stachowicz, Brian Ichter, Danny Driess, Suraj Nair, Quan Vuong, Oier Mees, Chelsea Finn, and Sergey Levine. Fast: Efficient action tokenization for vision-language-action models. *arXiv preprint arXiv:2501.09747*, 2025.
- [49] Junjie Wen, Minjie Zhu, Yichen Zhu, Zhibin Tang, Jinming Li, Zhongyi Zhou, Chengmeng Li, Xiaoyu Liu, Yaxin Peng, Chaomin Shen, et al. Diffusion-vla: Generalizable and interpretable robot foundation model via self-generated reasoning. *arXiv preprint arXiv:2412.03293*, 2024.
- [50] Songming Liu, Bangguo Li, Kai Ma, Lingxuan Wu, Hengkai Tan, Xiao Ouyang, Hang Su, and Jun Zhu. Rdt2: Exploring the scaling limit of umi data towards zero-shot cross-embodiment generalization. *arXiv preprint arXiv:2602.03310*, 2026.
- [51] Haoyu Zhen, Xiaowen Qiu, Peihao Chen, Jincheng Yang, Xin Yan, Yilun Du, Yining Hong, and Chuang Gan. 3d-vla: A 3d vision-language-action generative world model. *arXiv preprint arXiv:2403.09631*, 2024.
- [52] Delin Qu, Haoming Song, Qizhi Chen, Yuanqi Yao, Xinyi Ye, Yan Ding, Zhigang Wang, JiaYuan Gu, Bin Zhao, Dong Wang, et al. Spatialvla: Exploring spatial representations for visual-language-action model. *arXiv preprint arXiv:2501.15830*, 2025.
- [53] Xinghao Chen, Anhao Zhao, Heming Xia, Xuan Lu, Hanlin Wang, Yanjun Chen, Wei Zhang, Jian Wang, Wenjie Li, and Xiaoyu Shen. Reasoning beyond language: A comprehensive survey on latent chain-of-thought reasoning. *arXiv preprint arXiv:2505.16782*, 2025.
- [54] Zeyuan Yang, Xueyang Yu, Delin Chen, Maohao Shen, and Chuang Gan. Machine mental imagery: Empower multimodal reasoning with latent visual tokens. *arXiv preprint arXiv:2506.17218*, 2025.

- [55] Shuanghao Bai, Jing Lyu, Wanqi Zhou, Zhe Li, Dakai Wang, Lei Xing, Xiaoguang Zhao, Pengwei Wang, Zhongyuan Wang, Cheng Chi, et al. Latent reasoning vla: Latent thinking and prediction for vision-language-action models. *arXiv preprint arXiv:2602.01166*, 2026.
- [56] Shuhan Tan, Kairan Dou, Yue Zhao, and Philipp Krähenbühl. Interactive post-training for vision-language-action models. *arXiv preprint arXiv:2505.17016*, 2025.
- [57] Hongyin Zhang, Zifeng Zhuang, Han Zhao, Pengxiang Ding, Hongchao Lu, and Donglin Wang. Reinbot: Amplifying robot visual-language manipulation with reinforcement learning. *arXiv preprint arXiv:2505.07395*, 2025.
- [58] Mingjie Pan, Siyuan Feng, Qinglin Zhang, Xinchun Li, Jianheng Song, Chendi Qu, Yi Wang, Chuankang Li, Ziyu Xiong, Zhi Chen, et al. Sop: A scalable online post-training system for vision-language-action models. *arXiv preprint arXiv:2601.03044*, 2026.
- [59] Frederik Ebert, Yanlai Yang, Karl Schmeckpeper, Bernadette Bucher, Georgios Georgakis, Kostas Daniilidis, Chelsea Finn, and Sergey Levine. Bridge data: Boosting generalization of robotic skills with cross-domain datasets. In *RSS*, 2022.
- [60] Homer Walke, Kevin Black, Abraham Lee, Moo Jin Kim, Max Du, Chongyi Zheng, Tony Zhao, Philippe Hansen-Estruch, Quan Vuong, Andre He, Vivek Myers, Kuan Fang, Chelsea Finn, and Sergey Levine. Bridgedata v2: A dataset for robot learning at scale, 2023.
- [61] Zichen Jeff Cui, Yibin Wang, Nur Muhammad Mahi Shafiullah, and Lerrel Pinto. From play to policy: Conditional behavior generation from uncured robot data. *arXiv preprint arXiv:2210.10047*, 2022.
- [62] Dmitry Kalashnikov, Alex Irpan, Peter Pastor, Julian Ibarz, Alexander Herzog, Eric Jang, Deirdre Quillen, Ethan Holly, Mrinal Kalakrishnan, Vincent Vanhoucke, et al. QT-Opt: Scalable deep reinforcement learning for vision-based robotic manipulation. *arXiv preprint arXiv:1806.10293*, 2018.
- [63] Suneel Belkhale, Yuchen Cui, and Dorsa Sadigh. Hydra: Hybrid robot actions for imitation learning. *arxiv*, 2023.
- [64] Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Joseph Dabis, Chelsea Finn, Keerthana Gopalakrishnan, Karol Hausman, Alex Herzog, Jasmine Hsu, Julian Ibarz, et al. Rt-1: Robotics transformer for real-world control at scale. In *arXiv preprint arXiv:2212.06817*, 2022.
- [65] Sudeep Dasari, Frederik Ebert, Stephen Tian, Suraj Nair, Bernadette Bucher, Karl Schmeckpeper, Siddharth Singh, Sergey Levine, and Chelsea Finn. Robonet: Large-scale multi-robot learning. In *Conference on Robot Learning*, pages 885–897. PMLR, 2020.
- [66] Shivin Dass, Jullian Yapeter, Jesse Zhang, Jiahui Zhang, Karl Pertsch, Stefanos Nikolaidis, and Joseph J. Lim. CLVR jaco play dataset, 2023.
- [67] Corey Lynch, Ayzaan Wahid, Jonathan Tompson, Tianli Ding, James Betker, Robert Baruch, Travis Armstrong, and Pete Florence. Interactive language: Talking to robots in real time. *IEEE Robotics and Automation Letters*, 2023.
- [68] Nur Muhammad Mahi Shafiullah, Anant Rai, Haritheja Etukuru, Yiqian Liu, Ishan Misra, Soumith Chintala, and Lerrel Pinto. On bringing robots home, 2023.
- [69] Eric Jang, Alex Irpan, Mohi Khansari, Daniel Kappler, Frederik Ebert, Corey Lynch, Sergey Levine, and Chelsea Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *Conference on Robot Learning*, pages 991–1002. PMLR, 2022.
- [70] Gaoyue Zhou, Victoria Dean, Mohan Kumar Srirama, Aravind Rajeswaran, Jyothish Pari, Kyle Hatch, Aryan Jain, Tianhe Yu, Pieter Abbeel, Lerrel Pinto, Chelsea Finn, and Abhinav Gupta. Train offline, test online: A real robot learning benchmark, 2023.
- [71] Jiayuan Gu, Fanbo Xiang, Xuanlin Li, Zhan Ling, Xiqiang Liu, Tongzhou Mu, Yihe Tang, Stone Tao, Xinyue Wei, Yunchao Yao, Xiaodi Yuan, Pengwei Xie, Zhiao Huang, Rui Chen, and Hao Su. Maniskill2: A unified benchmark for generalizable manipulation skills, 2023.

- [72] Minho Heo, Youngwoon Lee, Doohyun Lee, and Joseph J. Lim. Furniturebench: Reproducible real-world benchmark for long-horizon complex manipulation. In *Robotics: Science and Systems*, 2023.
- [73] Jihoon Oh, Naoaki Kanazawa, and Kento Kawaharazuka. X-embodiment u-tokyo pr2 datasets, 2023.
- [74] Vikash Kumar, Rutav Shah, Gaoyue Zhou, Vincent Moens, Vittorio Caggiano, Abhishek Gupta, and Aravind Rajeswaran. Robohive: A unified framework for robot learning. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023.
- [75] Tatsuya Matsushima, Hiroki Furuta, Yusuke Iwasawa, and Yutaka Matsuo. Weblab xarm dataset, 2023.
- [76] Jianlan Luo, Charles Xu, Fangchen Liu, Liam Tan, Zipeng Lin, Jeffrey Wu, Pieter Abbeel, and Sergey Levine. FMB: A functional manipulation benchmark for generalizable robotic learning. <https://functional-manipulation-benchmark.github.io>, 2023.
- [77] Russell Mendonca, Shikhar Bahl, and Deepak Pathak. Structured world models from human videos. *CoRL*, 2023.
- [78] Erick Rosete-Beas, Oier Mees, Gabriel Kalweit, Joschka Boedecker, and Wolfram Burgard. Latent plans for task agnostic offline reinforcement learning. In *Proceedings of the 6th Conference on Robot Learning (CoRL)*, 2022.
- [79] Oier Mees, Jessica Borja-Diaz, and Wolfram Burgard. Grounding language with visual affordances over unstructured data. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, London, UK, 2023.
- [80] Abhishek Padalkar, Gabriel Quere, Antonin Raffin, João Silvério, and Freek Stulp. A guided reinforcement learning approach using shared control templates for learning manipulation skills in the real world. 2023.
- [81] Ajay Mandlekar, Yuke Zhu, Animesh Garg, Jonathan Booher, Max Spero, Albert Tung, Julian Gao, John Emmons, Anchit Gupta, Emre Orbay, Silvio Savarese, and Li Fei-Fei. RoboTurk: A crowdsourcing platform for robotic skill learning through imitation. *CoRR*, abs/1811.02790, 2018.
- [82] Lawrence Yunliang Chen, Simeon Adebola, and Ken Goldberg. Berkeley UR5 demonstration dataset. <https://sites.google.com/view/berkeley-ur5/home>.
- [83] Sylvain Gugger, Lysandre Debut, Thomas Wolf, Philipp Schmid, Zachary Mueller, Sourab Mangrulkar, Marc Sun, and Benjamin Bossan. Accelerate: Training and inference at scale made simple, efficient and adaptable. <https://github.com/huggingface/accelerate>, 2022.
- [84] Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. Zero: Memory optimizations toward training trillion parameter models. In *SC20: international conference for high performance computing, networking, storage and analysis*, pages 1–16. IEEE, 2020.
- [85] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.
- [86] Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297, 2025.
- [87] Philipp Moritz, Robert Nishihara, Stephanie Wang, Alexey Tumanov, Richard Liaw, Eric Liang, Melih Elibol, Zongheng Yang, William Paul, Michael I Jordan, et al. Ray: A distributed framework for emerging {AI} applications. In *13th USENIX symposium on operating systems design and implementation (OSDI 18)*, pages 561–577, 2018.
- [88] Yanli Zhao, Andrew Gu, Rohan Varma, Liang Luo, Chien-Chin Huang, Min Xu, Less Wright, Hamid Shojanazeri, Myle Ott, Sam Shleifer, et al. Pytorch fsdp: experiences on scaling fully sharded data parallel. *arXiv preprint arXiv:2304.11277*, 2023.

- [89] Jianlan Luo, Zheyuan Hu, Charles Xu, You Liang Tan, Jacob Berg, Archit Sharma, Stefan Schaal, Chelsea Finn, Abhishek Gupta, and Sergey Levine. Serl: A software suite for sample-efficient robotic reinforcement learning. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pages 16961–16969. IEEE, 2024.
- [90] Jianlan Luo, Charles Xu, Jeffrey Wu, and Sergey Levine. Precise and dexterous robotic manipulation via human-in-the-loop reinforcement learning. *Science Robotics*, 10(105):eads5033, 2025.
- [91] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pages 618–626, 2017.

A Related Work

Vision-Language-Action (VLA) models. Based on pretrained vision-language models (VLMs), VLA models [8, 6, 10, 46, 47] have demonstrated promising performance in robotic control with discrete action generation [4, 48] or continuous action representation. Recent frameworks have diversified into regression-based [5], diffusion-based [49, 9, 17, 46], and flow-matching-based architectures [42, 7, 50]. To further enhance precision and spatial awareness, several studies incorporate 3D spatial information or point-cloud reasoning into the VLA backbone [51, 52], significantly boosting performance in complex manipulation tasks. Inspired by Chain-of-Thought (CoT) reasoning in VLMs [11], recent research focuses on endowing VLAs with powerful reasoning capabilities. This includes generating intermediate text [7, 14], visual [22, 16], or multimodal plans [17], notably through methods like Embedded CoT [15] to strengthen spatial reasoning. However, these explicit decoding processes inevitably introduce inference latency. To alleviate this, further research explores introducing latent reasoning [53, 54] into the action generation process [55, 21, 22], balancing performance gains with execution efficiency. While these VLA frameworks have evolved significantly, the field remains predominantly confined to the imitation learning paradigm, where the lack of environmental interaction hinders the models’ ability to generalize beyond static datasets or further refine their internal reasoning for robust control.

Reinforcement Learning (RL) for VLA models. To overcome the limitations of static imitation learning, Reinforcement Learning (RL) has been increasingly adopted to fine-tune VLA models through environmental feedback [56]. Early efforts focus on offline preference alignment [57, 38], such as GRAPE [38], which employs Direct Preference Optimization (DPO) [39] to align robot trajectories with human intent. To further enhance closed-loop robustness, online RL frameworks have emerged [28, 24, 23, 25, 27, 58, 26, 36]. For examples, VLA-RL [25] and RL4VLA [28] utilize Proximal Policy Optimization (PPO) [35] to improve generalization in unseen environments, while SimpleVLA-RL [24] and TGRPO [40] apply Group Relative Policy Optimization (GRPO) [41] to achieve efficient post-training without complex reward modeling. Depending on the action space, these methods optimize either discrete token probabilities [24, 25] or continuous action sequences [23]. However, a critical gap remains: current RL-based VLA methods predominantly support vanilla architectures, focusing exclusively on action-space supervision. They fail to address how to conduct RL post-training for reasoning-based VLAs, leaving the intrinsic link between the internal "thought" process and the final "act" unoptimized. Therefore, we present LaST₀^{*}, a unified model that sequentially performs latent reasoning and action generation. Building on this, we propose Latent-Action Policy Optimization (LAPO) to concurrently optimize both the reasoning trajectory and the execution policy, achieving superior robustness and precision in complex manipulation tasks.

B Dataset Details

B.1 Large Scale Pre-Training Datasets

To ensure LaST-R1 inherits a robust foundation of motor primitives and physical common sense, we curated a diverse corpus of 400K trajectories (28M frames) from the Open-X-Embodiment [32], DROID [34], and RoboMIND [33] repositories. Table 3 details the proportion of each dataset used in our pre-training mixture. Notably, beyond adhering to standard data quality filtering practices established by prior VLA works [21], we additionally ensure that all robot state annotations are accurate and physically consistent. Crucially, to empower the reasoning process without introducing computational bottlenecks during training, we precompute the DINOv3-based latent tokens for all pre-training frames offline. As detailed in Section 2.2, this involves extracting the <CLS> token from DINOv3 and applying top-*k* selection to generate dense, semantically rich image representations. Because these spatial and temporal latent targets are processed entirely offline, they are simply loaded alongside the standard visual and textual inputs during this pretraining stage. This strategy provides the model with highly informative cognitive anchors to learn environmental dynamics and spatial reasoning, while adding virtually zero computational overhead to the pre-training pipeline. Ultimately, this stage establishes a shared representation space across diverse robotic datasets, enabling a seamless integration of reasoning and execution within the unified VLA framework.

Table 3: Datasets used for pre-training. The names of selected datasets for large-scale pretraining and their sampling ratios (%).

Training Dataset Mixture			
Dataset	Ratio (%)	Dataset	Ratio (%)
BridgeV2 [59, 60]	20.82	Nyu Franka Play [61]	0.24
Kuka [62]	20.22	Stanford Hydra [63]	0.20
Fractal [64]	13.67	RoboMIND [33]	0.20
Robo-Net [65]	11.53	Jaco Play [66]	0.19
Language Table [67]	7.72	Dobb-E [68]	0.18
BC-Z [69]	7.54	Toto [70]	0.17
Maniskill [71]	5.26	Furniture Bench [72]	0.09
DROID [34]	4.82	Utokyo Pr2 Tabletop [73]	0.04
Roboset [74]	3.21	Utokyo Xarm Pap [75]	0.04
FMB Dataset [76]	1.50	CMU Stretch [77]	0.02
Taco Play [78, 79]	1.26	DLR Sara Grid Clamp [80]	0.02
RoboTurk [81]	0.70	Utokyo Pr2 Fridge [73]	0.01
Berkeley Autolab Ur5 [82]	0.35	—	—

C Training Details

C.1 Alternative Latent Implementation Details

To systematically evaluate the architectural design of our latent reasoning tokens, we compare our proposed DINOv3-based representation against three alternative compression strategies: **1) Global Pooling**, **2) Convolutional Downsampling**, and **3) a Lightweight Q-Former** [44]. The most straightforward baseline, Global Pooling, trivially collapses the N_v visual tokens from the VLA vision encoder into a single vector via sequence-dimensional average pooling, which operates without additional parameters but severely sacrifices fine-grained spatial details. To explicitly model the spatial hierarchy, the Convolutional baseline reshapes the N_v visual tokens back into a 2D feature map and applies a sequence of 1×1 projections, aggressive strided downsampling (stride of 8), and global spatial convolutions with GELU activations to squeeze the map into a single flattened token. Alternatively, the Q-Former baseline employs an attention-based mechanism where a single learnable query adaptively aggregates task-relevant context from the dense N_v visual tokens through stacked Pre-LayerNorm cross-attention and MLP blocks. While these baselines introduce varying degrees of parametric complexity to compress visual features, our proposed approach simply extracts the `<CLS>` token from a pre-trained DINOv3 model and applies top- k dimension selection entirely offline. By directly harnessing the structurally rich and semantically dense feature space of a powerful vision foundation model, our DINOv3-based method circumvents the information loss inherent to naive pooling, spatial downsampling, or from-scratch query optimization. Consequently, this offline extraction strategy provides an optimal, computationally free cognitive anchor, ultimately achieving the best reasoning performance and highest success rates in our empirical evaluations.

C.2 Warm-up Details

Our policy is initialized with pre-trained Qwen3-VL-4B [2] weights, expanding the tokenizer vocabulary to include discrete action tokens (`<action_i>` for $i \in [0, 255]$) and a special transition token (`<latent_end>`). As illustrated in Figure 6, we adopt a hybrid decoding architecture: latent tokens are generated autoregressively to exploit the VLM’s robust reasoning, while action tokens are decoded in parallel with a chunk size of 8 for physical execution efficiency. During training, we tailor the latent length strategy to the target domain. For the multi-task LIBERO benchmark, we encourage length exploration by uniformly sampling the reasoning length from $\{2, 4, 6, 8\}$ per sample (anchored on a maximum length of 8 with $M = 4$ candidate positions); conversely, for single-task real-world deployments, we strictly enforce a fixed latent length of 8. The network is optimized using a joint objective comprising a cosine similarity loss for the predicted latents against offline ground-truth (GT) latents, a Cross-Entropy (CE) loss for the `<latent_end>` token, and a standard CE loss for the parallel-decoded action tokens. These components are empirically weighted at 1 : 0.1 : 1 to




Figure 6: Hybrid Attention Mask Design. Our model employs a custom attention mask to unify autoregressive reasoning and parallel action execution. The vision and text prompts, alongside the latent reasoning tokens, utilize a causal lower-triangular mask for sequential generation. After the `<Latent_end>` transition token aggregates the full reasoning context, the action tokens employ a bidirectional mask. This allows all action tokens within a chunk to attend to the entire historical context as well as to each other, enabling efficient parallel decoding.

balance token-level gradients. Training is distributed across $8 \times \text{H20}$ GPUs using Accelerate [83] and DeepSpeed [84] in bf16 mixed precision, with a global batch size of 64 and the AdamW [85] optimizer (peak learning rate 1×10^{-5} , cosine decay with a minimum ratio of 0.1). Finally, we customize the training duration per environment: the four LIBERO suites are trained in an extremely low-data regime (1 expert trajectory per task) for 10K iterations each, whereas real-world models are fine-tuned on 20 trajectories per task for 1K iterations.

C.3 RL Training Details on LIBERO.

We implement our Latent-Action Policy Optimization (LAPO) framework using ver1 [86] with Ray [87] and Fully Sharded Data Parallel (FSDP) [88] on a single $8 \times \text{H20}$ GPU node. The VLA policy is initialized from the SFT warm-up checkpoint for continuous online interaction. During rollouts, the policy decodes an action chunk of 8 future action steps in parallel (yielding exactly 56 tokens per chunk) with a sampling temperature of 1.6, while trajectory lengths are capped at 240 steps for LIBERO-Spatial, 320 for LIBERO-Object/LIBERO-Goal, and 576 for LIBERO-Long. A strict verifier mechanism yields a sparse binary reward (0 or 1) for task success, which is scaled by a factor of 5 at the terminal step. Advantages are computed via GAE ($\gamma = 0.99$, $\lambda = 0.95$) with valid-timestep masking applied to accommodate variable-length trajectories. At each RL iteration, a rollout batch of 512 sampled trajectories is evenly partitioned into 4 mini-batches to perform 4 PPO optimization epochs. We train the policy using learning rates of 3×10^{-5} for the VLA actor and 3×10^{-4} for the value head. To ensure stability and efficiency, we apply global gradient clipping at 10, asymmetric PPO clipping bounds ($\epsilon_{\min} = 0.2$, $\epsilon_{\max} = 0.28$), and gradient/optimizer state offloading, alongside evaluating the model’s success rate every 5 update steps.

C.4 RL Training Details on Real-World

To enable efficient real-world online reinforcement learning, we deploy our framework on a Franka Research 3 robot equipped with an Intel RealSense D455 camera (side view) and two D435 cameras (wrist views), powered by a workstation with two NVIDIA RTX 4090 GPUs. Building upon the continuous asynchronous actor-learner pipeline [89, 90], policy rollout and model optimization run concurrently without pausing data collection. The actor continuously executes the policy—which predicts actions conditioned on language prompts and dual-view RGB observations—and streams transition tuples to the learner. To preserve critical corrective signals, human interventions are routed to a dedicated buffer, allowing the learner to sample mixed mini-batches from both demonstration




Figure 7: Ablation studies on loss coefficients. Performance impact of varying (a) latent loss weight λ_1 , (b) state-value weight λ_2 , and (c) transition penalty λ_3 . In each sub-figure, unlisted coefficients are fixed at their optimal values. The combination ($\lambda_1 = 0.1$, $\lambda_2 = 1$, $\lambda_3 = 0.1$) achieves the optimal gradient balance and highest success rate.

and rollout streams. We initialize the LaST-R1 model using the supervised warm-up checkpoint, and to ensure stable and computationally tractable online updates, we freeze the base model and exclusively update newly injected Low-Rank Adaptation (LoRA) [45] parameters with rank $r = 32$. Online optimization commences after collecting an initial replay threshold of 500 transitions. The learner optimizes a joint objective combining behavior cloning ($\lambda_{BC} = 1.0$) and Q-guided policy improvement ($\lambda_Q = 0.5$) using the AdamW [85] optimizer with a learning rate of 1×10^{-5} , zero weight decay, and gradient clipping at a maximum norm of 1.0. We apply a critic-to-actor update ratio of 2:1, where the critic utilizes one-step temporal-difference targets with a discount factor of $\gamma = 0.98$ and target value parameters are softly updated at a rate of $\tau = 0.005$. Gradient accumulation is set to 16 micro-steps with a micro-batch size of 2 per stream, yielding an effective batch size of approximately 32. Finally, to handle sparse real-world feedback, the environment provides a terminal reward of +10 upon operator-confirmed task completion, coupled with a constant step penalty of -0.05 to encourage execution efficiency, while the learner periodically broadcasts updated weights back to the actor for hot-loading.

D Additional Quantitative Analysis

D.1 Additional Ablation Studies on Hyperparameters

To systematically evaluate the impact of the weighting hyperparameters in our joint training objective $\mathcal{L}_{\text{total}}(\theta)$, we conduct an ablation study varying the coefficients λ_1 , λ_2 , and λ_3 on LIBERO-Spatial. As shown in Figure 7, in each experiment, we isolate the effect of one coefficient while fixing the others at their empirically optimal values (i.e., $\lambda_1 = 0.1$, $\lambda_2 = 1$, $\lambda_3 = 0.1$). First, analyzing the latent loss weight λ_1 , we observe that relying entirely on implicit gradient backpropagation from the action loss ($\lambda_1 = 0$) yields a suboptimal success rate of 97.2%. Introducing explicit latent supervision significantly improves performance, peaking at 99.8% with $\lambda_1 = 0.1$. However, excessively high values (e.g., $\lambda_1 = 1$) slightly degrade performance to 99.0%, likely because the latent objective begins to overshadow the primary physical execution task. Second, for the state-value estimation weight λ_2 , a balanced weight of $\lambda_2 = 1$ achieves the best result (99.8%). Lower weights such as 0.1 and 0.5 degrade the success rate to 97.8% and 98.4% respectively, underscoring the necessity of robust value estimation for accurate advantage computation in our LAPO framework. Finally, evaluating the transition weight λ_3 reveals that a modest penalty of $\lambda_3 = 0.1$ is optimal (99.8%). Increasing this weight up to 2 forces a sharp performance drop to 98.6%, indicating that over-penalizing the `<latent_end>` token disrupts the delicate exploration balance required for the policy to learn state-conditional reasoning lengths. Consequently, the configuration of $\lambda_1 = 0.1$, $\lambda_2 = 1$, and $\lambda_3 = 0.1$ establishes the most effective gradient balance across action generation, internal reasoning, and value estimation.

D.2 Analysis of Adaptive Reasoning Length

To investigate the efficacy of our dynamic reasoning mechanism, we analyze the frequency distribution of the chosen latent reasoning lengths (bounded by a maximum of 8 tokens) across the four LIBERO task suites. Figure 8 illustrates the contrast between the policy right after SFT warm-up and the fully RL-optimized policy. During the warm-up phase, where reasoning lengths are sampled randomly, the pre-RL model exhibits a relatively uniform distribution across lengths 2, 4, 6, and 8. This indicates a




Figure 8: Frequency distribution of adaptive latent reasoning lengths. Compared to the SFT warm-up (blue), the RL-optimized policy (red) successfully learns the optimal number of latent reasoning steps, achieving an excellent balance between reasoning precision and inference efficiency.




Figure 9: Comparison of average execution steps across LIBERO task suites. We report the average steps taken by the expert demonstrations, the pre-RL (Before RL) policy, and the RL-optimized (After RL) policy. After RL, the model not only drastically reduces the execution steps compared to the imitation baseline, but even surpasses the temporal efficiency of experts in most scenarios.

lack of cognitive prioritization, treating simple and complex states with equal computational budgets. Following Latent-Action Policy Optimization (LAPO), the length distribution undergoes a dramatic shift. Guided by the environment reward and our transition-specific optimization objective, the model effectively learns an "early-exit" strategy. Across all environments, the RL-optimized policy heavily gravitates toward shorter cognitive horizons, with reasoning lengths of 2 or 4 tokens dominating the decision steps. This empirical behavior strongly validates our design: rather than passively executing fixed-length reasoning, LaST-R1 proactively learns to terminate its internal deliberation once sufficient state representations are formed. By drastically reducing the token count per step without compromising the near-perfect success rates, the model achieves an optimal balance between robust physical control and inference efficiency.

D.3 Episode Length Comparisons

To further demonstrate the efficacy of our framework, we evaluate the average number of execution steps across 500 test trajectories for each LIBERO suite. Notably, these averages are computed unconditionally over all rollouts, regardless of ultimate task success or failure. As illustrated in Figure 9, the policy trained after warm-up SFT (Before RL) requires significantly more steps than the simulator-provided expert demonstrations. This inflation in trajectory length stems from compounding errors and purely reactive behaviors; when the pre-RL model encounters out-of-distribution (OOD) states, it often gets trapped in inefficient loops or prolonged, unsuccessful wandering that approaches the maximum step limit. However, following online interaction, the RL-optimized policy (After RL) exhibits a dramatic reduction in execution steps, notably outperforming even the original expert trajectories in the Spatial, Object, and Goal task suites. We attribute this exceptional temporal efficiency directly to the optimized latent reasoning process. Rather than passively mimicking the scripted expert data, which often relies on conservative motion planning and rigid, waypoint-based trajectories, the RL-driven reasoning strategy empowers the policy with a deeper, more generalized understanding of the task dynamics. By jointly optimizing the reasoning and action spaces, the model learns to synthesize highly efficient internal representations, thereby discovering optimal shortcuts and formulating more direct, precise, and decisive trajectories than the original algorithmic experts.

D.4 Additional Generalization Analysis

To provide a more granular understanding of the out-of-distribution (OOD) learning process, Figure 10 details the step-by-step generalization curves for two representative held-out tasks from each




Figure 10: Generalization analysis on LIBERO. For each task suite, models are warmed up with one trajectory per task, followed by online RL training on 9 tasks, with the remaining 1 task for evaluation. While the out-of-distribution performance of the Action-Only PPO baseline (blue) stagnates, our LaST-R1 with LAPO (red) demonstrates continuous generalization improvements across all task suites.

LIBERO suite. The learning dynamics reveal a stark contrast between the two paradigms throughout the online interaction phase. The Action-Only PPO baseline (blue) exhibits a classic overfitting pathology. Across almost all tasks, its OOD success rate flatlines early in training and frequently oscillates or even collapses (e.g., Spatial-Task8 and Long-Task7). This empirical evidence confirms that optimizing purely in the action space forces the model to memorize the specific kinematic trajectories of the 9 training tasks, leaving it entirely brittle and incapable of adapting when faced with the unseen spatial configurations or objects of the held-out task. In sharp contrast, our LaST-R1 optimized with LAPO (red) displays a remarkably stable and continuous upward trajectory across the entire training process. The curves demonstrate no signs of catastrophic forgetting or OOD performance degradation. Notably, our policy not only rapidly converges to a perfect 100% OOD success rate on several tasks (Spatial-Task0, Object-Task0, and Goal-Task5), but also shows robust, monotonic growth on the most challenging multi-stage tasks. For instance, in Long-Task4, while the action-only baseline completely fails to surpass a 20% success rate due to compounding errors, our method steadily climbs to 54%. This extended analysis clearly illustrates that jointly optimizing the latent reasoning space empowers the policy to abstract high-level semantic and physical principles, allowing it to dynamically compose learned skills for novel scenarios rather than rigidly overfitting to the training distribution.

E Additional Qualitative Analysis

E.1 Action-to-Vision Attention

To gain deeper insights into the internal decision-making mechanisms of our policy, we utilize Grad-CAM [91] to visualize the cross-attention weights from the action tokens to the visual tokens. As illustrated in Figure 13, we compare spatial attention maps across four representative trajectories from the LIBERO task suites to evaluate the impact of explicit latent reasoning and our LAPO framework. Examining the SFT-trained models, the Action-Only policy frequently exhibits diffused and scattered attention, struggling to consistently localize task-relevant entities and often lagging behind the robot’s end-effector. In stark contrast, by generating latent reasoning tokens prior to action decoding, our proposed LaST-R1 establishes a strong semantic anchor, resulting in highly concentrated and precise visual grounding on critical objects of interaction. These advantages become even more pronounced after reinforcement learning post-training. While applying standard PPO to the Action-Only model tends to over-focus on the gripper’s immediate vicinity and lacks long-horizon awareness, LaST-R1 + LAPO achieves the most robust, goal-directed attention. Because LAPO jointly optimizes the latent reasoning space and the action space using the environment reward, the policy learns to dynamically shift its intense visual focus from the manipulated object to the target receptacle as the trajectory progresses, confirming that our framework successfully aligns internal visual cognition with precise physical execution.




Figure 11: Real-world execution trajectories of the proposed policy. The sequences illustrate the continuous execution progress across diverse robotic manipulation tasks.




Figure 12: Policy robustness in visually diverse and cluttered environments. The model consistently maintains task success when subjected to severe visual variations, effectively ignoring out-of-distribution distractors, unseen object instances, and dynamic lighting conditions (indicated by red bounding boxes).

E.2 Real-World Visualization

To evaluate the practical deployment capabilities of LaST-R1, we visualize its execution trajectories across diverse real-world manipulation tasks, as shown in Figure 11. As demonstrated, the policy exhibits stable closed-loop control during standard execution (e.g., precise insertion, bimanual coordination). Crucially, the model demonstrates remarkable robustness in visually cluttered environments, as shown in Figure 12. Despite severe out-of-distribution perturbations—such as dynamic lighting, novel distractor objects, and background variations—LaST-R1 consistently maintains execution stability, highlighting its strong generalization capabilities in complex, unconstrained scenarios.

F Broader Impact

Our work proposes LaST-R1, a foundation model for robotic manipulation that seamlessly integrates adaptive-length latent reasoning and parallel action execution within a unified Vision-Language-Action (VLA) framework. While our method significantly enhances spatial awareness and dynamically allocates cognitive compute through Latent-Action Policy Optimization (LAPO), deploying high-capacity VLA models in physical environments inherently introduces potential risks. These risks primarily involve unpredictable physical behaviors when the policy encounters out-of-distribution visual scenarios, unfamiliar physical dynamics, or ambiguous human instructions. To mitigate these challenges, future real-world deployments must incorporate rigorous safety guardrails, robust anomaly

detection mechanisms, and strict hardware-level operational boundaries. Broadly, by empowering robots to fluidly balance deliberate cognitive planning with rapid physical reflexes, our framework advances the development of reliable, general-purpose robotic assistants for complex, unstructured domains such as smart manufacturing, elder care, and domestic automation.




Figure 13: Visualizations of Action-to-Vision Cross-Attention. We compare the attention maps across four representative trajectories from four task suites in LIBERO.